IEEE Standards

**IEEE Std 260.1™-2004**
(Revision of
IEEE Std 260.1-1993)

# 260.1™

# IEEE Standard Letter Symbols for Units of Measurement (SI Units, Customary Inch-Pound Units, and Certain Other Units)

## IEEE Standards Coordinating Committee 14

Sponsored by the
Standards Coordinating Committee on Quantities, Units, and Letter Symbols (SCC14)

IEEE

3 Park Avenue, New York, NY 10016-5997, USA

24 September 2004

Print: SH95220
PDF: SS95220

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS

Not for Resale

and Electronics Engineers, Inc.
IEEE
nitted without license from IHS
Not for Resale

*Recognized as an*
*American National Standard (ANSI)*

**IEEE Std 260.1™-2004**
(Revision of
IEEE Std 260.1-1993)

# IEEE Standard Letter Symbols for Units of Measurement (SI Units, Customary Inch-Pound Units, and Certain Other Units)

Sponsor

**Standards Coordinating Committee on Quantities, Units, and Letter Symbols (SCC14)**

Approved 22 July 2004

**American National Standard Institute**

Approved 25 March 2004

**IEEE-SA Standards Board**

**Abstract:** Letter symbols for units of measurement are covered in this standard. It does not include abbreviations for technical terms, nor does it cover symbols for physical quantities.
**Keywords:** letter symbols, limited typography, metric, quantities, SI, units of measurement

---

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2004 by the Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 24 September 2004. Printed in the United States of America.

IEEE is a registered trademark in the U.S. Patent & Trademark Office, owned by the Institute of Electrical and Electronics Engineers, Incorporated.

Print: ISBN 0-7381-3997-1 SH95220
PDF: ISBN 0-7381-3998-X SS95220

*No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.*

--`,,,,`,,`-`-`,,`,,`,`,,`---

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS

Not for Resale

**IEEE Standards** documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

Use of an IEEE Standard is wholly voluntary. The IEEE disclaims liability for any personal injury, property or other damage, of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, or reliance upon this, or any other IEEE Standard document.

The IEEE does not warrant or represent the accuracy or content of the material contained herein, and expressly disclaims any express or implied warranty, including any implied warranty of merchantability or fitness for a specific purpose, or that the use of the material contained herein is free from patent infringement. IEEE Standards documents are supplied "**AS IS**."

The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE Standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard. Every IEEE Standard is subjected to review at least every five years for revision or reaffirmation. When a document is more than five years old and has not been reaffirmed, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE Standard.

In publishing and making this document available, the IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity. Nor is the IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing this, and any other IEEE Standards document, should rely upon the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

Interpretations: Occasionally questions may arise regarding the meaning of portions of standards as they relate to specific applications. When the need for interpretations is brought to the attention of IEEE, the Institute will initiate action to prepare appropriate responses. Since IEEE Standards represent a consensus of concerned interests, it is important to ensure that any interpretation has also received the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to interpretation requests except in those cases where the matter has previously received formal consideration. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position, explanation, or interpretation of the IEEE.

Comments for revision of IEEE Standards are welcome from any interested party, regardless of membership affiliation with IEEE. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Comments on standards and requests for interpretations should be addressed to:

Secretary, IEEE-SA Standards Board

445 Hoes Lane

P.O. Box 1331

Piscataway, NJ 08855-1331USA

NOTE—Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. The IEEE shall not be responsible for identifying patents for which a license may be required by an IEEE standard or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

Authorization to photocopy portions of any individual standard for internal or personal use is granted by the Institute of Electrical and Electronics Engineers, Inc., provided that the appropriate fee is paid to Copyright Clearance Center. To arrange for payment of licensing fee, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

# Introduction

**This introduction is not part of IEEE Std 260.1-2004, IEEE Standard Letter Symbols for Units of Measurement (SI Units, Customary Inch-Pound Units, and Certain Other Units.)**

This standard supersedes ANSI/IEEE Std 260.1-1993 in accordance with IEEE's policy of periodic standards review and update. Since the 1993 standard was approved, significant changes have occurred in the International System of Units (SI). Corresponding updates have been issued for some of the documents referred to by this standard. Significant, newly revised references are IEEE/ASTM SI 10-2002 (superseding ANSI/IEEE Std 268-1992 and ASTM E 380) and the seventh edition of Le Système international d'unités (The International System of Units, 1998, BIPM).

Since IEEE Std 260.1-1993 was issued, the IEEE has adopted Policy 9.19, Metric Policy, which calls upon all IEEE organizational units to support the use of the SI. The IEEE-SA Standards Board Implementation Plan for this policy, approved in 1995, states in part:

> Stage III—After January 1, 2000: Proposed new standards and revised standards submitted for approval shall use metric units exclusively in the normative portions of the standard. Inch-pound data may be included, if necessary, in footnotes or annexes that are informative only.

Standards Coordinating Committee 14 (SCC14) shall work with the committees responsible for generating IEEE standards to help them carry out this implementation plan. Policy 9.19 recognizes the need for some exceptions and contains the following statement: "Necessary exceptions to this policy, such as where a conflicting world industry practice exists, must be evaluated on an individual basis and approved by the responsible major board of the Institute for a specific period of time." SCC14, as part of the coordination process, shall review requests for individual exceptions and shall report its recommendations to the IEEE-SA Standards Board.

## Notice to users

### Errata

Errata, if any, for this and all other standards can be accessed at the following URL: http://standards.ieee.org/reading/ieee/updates/errata/index.html. Users are encouraged to check this URL for errata periodically.

### Interpretations

Current interpretations can be accessed at the following URL: http://standards.ieee.org/reading/ieee/interp/index.html.

### Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. The IEEE shall not be responsible for identifying patents or patent applications for which a license may be required to implement an IEEE standard or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

Copyright © 2004 IEEE. All rights reserved.


Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

## Participants

At the time this standard was completed, the working group had the following membership:

**James R. Frysinger,** *Chair*

Gordon J. Aubrecht
Bruce B. Barrow
Stanley L. Ehrlich
Stan I. Jakuba
Joseph G. Langenstein
John T. Scott
Ralph M. Showers
Barry N. Taylor
Lorelle Young
Allan J. Zuckerwar

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

O. C. Amrhyn
Gordon J. Aubrecht
Bruce B. Barrow
David Barton
John Benedict
Anne Bosma
William Brenner
Dennis Brownridge
Stephen P. Conrad
Gary Donner
Stanley L. Ehrlich
Jim Elwell
Howard Frazier
James R. Frysinger
Dudley Galloway
Randall Groves
Robert Grow
Bal Gupta
Donald W. Hillger
John Horch
Stan I. Jakuba
Tony Jeffree
Geza Joos
Thomas M. Kurihara
Dee S. Long
Jack Loudon
Roger Marks
Frank Mayle
Arthur O. McCoubrey
Nigel McQuin
Gary Michel
James W. Moore
John Nichols
T. W. Olsen
Lorraine Padden
Ronald Petersen
Percy Pool
Bill Potts
John Rossetti
Mohindar S. Sachdev
Anne-Marie Sahazizian
Robert Schaaf
John T. Scott
John Sheppard
Ralph M. Showers
John St. Clair
Thomas Starai
James Stoner
Eva Tarasiewicz
Barry N. Taylor
James Wilson
Lorelle Young
Allen J. Zuckerwar
Theodore Wildi

When the IEEE-SA Standards Board approved this standard on 25 March 2004, it had the following membership:

**Don Wright,** *Chair*
**Steve M. Mills,** *Vice Chair*
**Judith Gorman,** *Secretary*

Chuck Adams
H. Stephen Berger
Mark D. Bowman
Joseph A. Bruder
Bob Davis
Roberto de Boisson
Julian Forster*
Arnold M. Greenspan
Mark S. Halpin
Raymond Hapeman
Richard J. Holleman
Richard H. Hulett
Lowell G. Johnson
Joseph L. Koepfinger*
Hermann Koch
Thomas J. McGean
Daleep C. Mohla
Paul Nikolich
T. W. Olsen
Ronald C. Petersen
Gary S. Robinson
Frank Stone
Malcolm V. Thaden
Doug Topping
Joe D. Watson

*Member Emeritus

Also included are the following nonvoting IEEE-SA Standards Board liaisons:

Satish K. Aggarwal, *NRC Representative*
Richard DeBlasio, *DOE Representative*
Alan Cookson, *NIST Representative*

Don Messina
*IEEE Standards Project Editor*


Copyright © 2004 IEEE. All rights reserved.

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

# Contents

1. Overview ..... 1

1.1 Organization ..... 1
1.2 Scope ..... 1

2. References ..... 2

3. Abbreviations ..... 2

4. General principles of letter symbol standardization ..... 2

4.1 Letter symbols ..... 2
4.2 Alphabets and typography ..... 3
4.3 Remarks concerning quantity symbols ..... 4
4.4 Remarks concerning unit symbols ..... 4
4.5 The International System of Units (SI) ..... 5
4.6 Usage ..... 7

5. Unit symbols ..... 7

6. Unit symbols to be used with limited character sets ..... 17

6.1 Limitations arising from the use of ASCII 0000-0127 ..... 18
6.2 Limitations arising from the use of HTML-coded web pages and electronic mail ..... 19
6.3 Examples of symbols for limited character sets ..... 20
6.4 Limitations arising from importing and exporting documents between computer programs ..... 21

Annex A (normative) Notation for expressing the reference of a level ..... 22

Annex B (informative) Bibliography ..... 23

Copyright © 2004 IEEE. All rights reserved.


Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

# IEEE Standard Letter Symbols for Units of Measurement (SI Units, Customary Inch-Pound Units, and Certain Other Units)

## 1. Overview

### 1.1 Organization

This standard is divided into six clauses. Clause 1 provides the organization and scope of this standard. Clause 2 gives the reference to the IEEE/ASTM standard on metric practice. Clause 3 provides a list of abbreviations used throughout this standard. Clause 4 establishes the general principles of letter symbol standardization and includes a list of SI prefixes and their symbols. Clause 5 provides a list of units and their symbols. Clause 6 makes provisions for adaptation of this standard in cases where only a character set limited in capability is available.

This standard also contains two annexes. Annex A provides information about the identification of reference levels when using logarithmic scaling units. Annex B provides a bibliography.

### 1.2 Scope

This standard covers letter symbols[1] for units of measurement. It does not include abbreviations for technical terms, nor does it cover symbols for physical quantities.[2]

The symbols given in this standard are intended for all applications, including use in text and equations; in graphs and diagrams; and on panels, labels, and nameplates. Provision is made for modifications to be used when only character sets of limited capability are available.

---

[1]"Letter symbol" as a technical term does not have the same meaning as either "name" or "abbreviation." An abbreviation is a letter or a combination of letters that by convention represents a word or a name in a particular language. For example, the symbol for electromotive force is *E*, whereas the abbreviation is emf in English, fem in French, and EMK in German. The unit names ampere and second have sometimes been abbreviated amp and sec, respectively, but this usage is now deprecated. The standard unit symbols for ampere and second are A and s, respectively.

[2]As used in this standard, the term *physical quantity* means a measurable attribute of phenomena or matter. Examples are length, mass, and time.

Copyright © 2004 IEEE. All rights reserved.


--`,,,,`,,-`-`,,`,,`,`,,`---

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

## 2. References

This standard shall be used in conjunction with the latest version of the following publication:

IEEE/ASTM SI 10-2002, American National Standard for Use of the International System of Units (SI): The Modern Metric System.[3]

## 3. Abbreviations

ANSI American National Standards Institute

CGPM Conférence Générale des Poids et Mesures (General Conference on Weights and Measures)

cgs centimeter-gram-second

CIPM Comité International des Poids et Mesures (International Committee for Weights and Measures)

IEC International Electrotechnical Commission

IEEE Institute of Electrical and Electronics Engineers

ISO International Organization for Standardization

SI Système International d'Unités (International System of Units)

## 4. General principles of letter symbol standardization

### 4.1 Letter symbols

Letter symbols include symbols for physical quantities (quantity symbols) and symbols for the units in which these quantities are measured (unit symbols).

A quantity symbol is, in general, a single letter[4] (for example, *I* for electric current) specified as to general form of type and modified when appropriate by one or more subscripts or superscripts. In a given work, the same letter symbol should appear throughout for the same physical quantity, regardless of the units employed or of special values assigned.

A unit symbol[5] is a letter or group of letters (for example, mm for millimeter), or in a few cases a special sign, that may be used in place of the name of a unit. It may include numbers to indicate exponents (for example, $m^2$ for square meter) and multiplication or division operators (for example, m/s for meter per second).

[3]IEEE publications are available from the Institute of Electrical and Electronics Engineers, 445 Hoes Lane, P.O. Box 1331, Piscataway, NJ 08855-1331, USA (http://standards.ieee.org/).

[4] Symbols composed of two letters are sometimes used for numerical transport parameters, such as *Re* for Reynolds number.

[5] Unit symbols have sometimes been treated in the same manner as general abbreviations, but the recommendations of the International Committee for Weights and Measures (CIPM), and of many other international and national bodies concerned with standardization, emphasize the symbolic character of these designations and rigidly prescribe the manner in which they shall be treated. This concept of the unit symbol is therefore adopted in this standard.


Copyright © 2004 IEEE. All rights reserved.

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS Not for Resale

## 4.2 Alphabets and typography

Letter symbols are mainly restricted to the English and Greek alphabets. Those Greek letters that are easily confused with English letters shall be avoided. The type families that are used for text in modern book and journal publishing all include sloping (italic) type faces and related upright (roman) type faces. The former are used for quantity symbols; the latter, for unit symbols. The distinctions are discussed more fully in the following paragraphs. (In the context of this standard, upright is used simply in contrast with sloping and carries no connotation regarding serifs, line widths, or the like.) In situations where upright and sloping are not both available, care shall be taken to avoid confusion between quantities and units.

Unconventional typefaces should generally not be used for letter symbols. Script and Old English faces, for example, are not appropriate for unit symbols. Such special faces have seen limited use for quantity symbols, but good modern practice avoids them.

Symbols for physical quantities, mathematical variables, indexes, and general functions[6] are printed in sloping type. For example:

— $A$ area
— $e$ elementary electric charge
— $x, y, z$ Cartesian coordinates
— $i, j, k, n$ indexes
— $f(x)$ function of $x$

Symbols for units of measurement, mathematical constants, specific mathematical functions, operators, and numerals are printed in upright type. For example:

— cm centimeter
— e base of natural logarithms
— $\sin x$ sine of $x$
— $\mathrm{J}_2(z), \mathrm{J}_n(z)$ Bessel functions
— $\mathrm{d}x$ differential of $x$
— $E = \frac{1}{2}mv^2$ formula for kinetic energy

Subscripts and superscripts are governed by the above principles. Those that are letter symbols for quantities or for indexes are printed in sloping type, while all others are printed in upright type. For example:

— $C_p$ heat capacity at constant pressure $p$
— $a_{ij}, a_{45}$ matrix elements
— $I_i, I_o$ input current, output current
— $x_{\mathrm{av}}$ average value of $x$

For indicating the vector character of a quantity, boldface sloping type is used. For example:

— $\boldsymbol{F}$ force
— $\boldsymbol{H}$ magnetic field strength

Ordinary sloping type is used to represent the magnitude of a vector quantity. It is also commonly used for a vector quantity when there is no need to draw attention to the vector character of the quantity.

When tensor quantities of second or higher order are to be represented by a single letter, sans serif type should be used (for example, ***A, B***).

[6] The term *general functions* is here used to contrast with specific mathematical functions, for which upright type is to be used.

Copyright © 2004 IEEE. All rights reserved.


Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

## 4.3 Remarks concerning quantity symbols

Quantity symbols may be used in mathematical expressions in any way consistent with good mathematical usage. The product of two quantities, *a* and *b,* is indicated by writing *ab*. The quotient may be indicated by writing

$$\frac{a}{b} \quad a/b \quad \text{or} \quad ab^{-1}$$

If more than one slash (/) is used in any algebraic term, parentheses shall be inserted to remove any ambiguity. Thus, one may write $(a/b)/c$, or $a/(b/c)$, but not $a/b/c$.

Subscripts and superscripts are widely used with quantity symbols. Several subscripts or superscripts, sometimes separated by commas, may be attached to a single letter. But, so far as logical clarity permits, subscripts and superscripts should not be attached to other subscripts and superscripts. A symbol that has been modified by a superscript should be enclosed in parentheses before an exponent is attached.

Conflicts that occur because different quantities are assigned identical symbols in the same or different standard symbol lists should be resolved in one of the following ways:

a) By use of a reserve symbol (alternative symbol) if one is listed.

b) By use of a subscript or superscript selected by the author for one or more of the conflicting requirements.

c) By use of uppercase letters as variants for lowercase letters and vice versa, but only if no ambiguity results.

## 4.4 Remarks concerning unit symbols

An upright (roman) type font shall be used for unit symbols, even when the surrounding text is in a sloping font. In general, unit symbols are lowercase letters, except for a very few that use special signs (such as ° for degree). If, however, the symbol is for a unit whose name is derived from a proper name (e.g., James Watt), uppercase upright type is used for the first letter (W, for the example given).[7] As a further exception to the general rule, the symbol L is used for liter to avoid confusion between the lowercase letter l and the numeral 1. Some additional exceptions arise in the special cases where symbols are joined, as in eV, the symbol for electronvolt, and in mmHg, the symbol for conventional millimeter of mercury, a unit of pressure. The distinction between uppercase and lowercase letters shall be followed, even if the symbol appears in applications where the other lettering is uppercased. The form of unit symbols is the same for both singular and plural, and they are not followed by a period except at the end of a sentence.

In the complete expression for a quantity, a space should be left between the numerical value and the unit symbol. For example, write 35 mm, not 35mm, and 2.371 m, not 2.371m. When the quantity is used in an adjectival sense, a hyphen is often used in lieu of a space between the number and the unit name or between the number and the symbol.

— *Example:* A 3-meter pole. The length is 3 meters.

— *Example:* A 35-mm film. The width is 35 mm.

**EXCEPTION:** No space is left between the numerical value and the symbols for degree, minute, and second of plane angle.

[7] Prefixes are considered separately (see 4.5).


Copyright © 2004 IEEE. All rights reserved.

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

When a compound unit is formed by multiplication of two or more other units, its symbol consists of the symbols for the separate units joined by a raised dot (preferred) or separated by a thin, non-breaking space (for example, N·m or N m for newton meter). The dot may be omitted in the case of familiar compounds such as watthour (symbol Wh) if confusion is unlikely. Hyphens should not be used in symbols for compound units. Positive and negative exponents may be used with the symbols for units.

When a compound unit is formed by division of one unit by another, its symbol is constructed in one of the following forms:

$$\mathrm{m/s} \quad \text{or} \quad \mathrm{m \cdot s^{-1}} \quad \text{or} \quad \frac{\mathrm{m}}{\mathrm{s}}$$

NOTE—$\mathrm{m \cdot s^{-1}}$ or $\mathrm{m\ s^{-1}}$ may be used for meter per second but $\mathrm{ms^{-1}}$ symbolizes 1/ms or $10^3\ \mathrm{s^{-1}}$ as described in 4.5. The raised dot or space is therefore extremely important.[8]

In simple cases use of the slash is preferred, but in no case should more than one slash, or a slash followed by a product, be used in the same expression unless parentheses are inserted to avoid ambiguity. For example, write:

— $\mathrm{J/(mol \cdot K)}$ or $\mathrm{J \cdot mol^{-1} \cdot K^{-1}}$ or $\mathrm{(J/mol)/K}$

— but not $\mathrm{J/mol/K}$ or $\mathrm{J/mol \cdot K}$

In complicated cases, negative powers should be used.[9]

Letter symbols and mathematical notation should not be mixed with unit names in the same expression. For example, write joules per kilogram or J/kg. Do not write joules/kilogram or joules/kg, or J/kilogram.

## 4.5 The International System of Units (SI)

In this standard, some units are identified as SI units. These units belong to the International System of Units (Le Système International d'Unités), which is the name given in 1960 by the General Conference on Weights and Measures (Conférence Générale des Poids et Mesures) to the coherent system of units built upon the base units in Table 1.

**Table 1—SI base units**

| Unit | Physical quantity |
|---|---|
| meter | length |
| kilogram | mass |
| second | time |
| ampere | electric current |
| kelvin | thermodynamic temperature |
| mole | amount of substance |
| candela | luminous intensity |

[8]Notes in text, tables, and figures are given for information only, and do not contain requirements needed to implement the standard.

[9] The notation for products and quotients of unit symbols is intentionally made more explicit than that given in 4.3 for quantity symbols because some unit symbols are composed of more than one letter.

Copyright © 2004 IEEE. All rights reserved.


Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

The spellings *meter* and *liter* are recommended.[10] The variant spellings *metre* and *litre* are also used.[11]

The prefixes in Table 2 are used to indicate decimal multiples or submultiples of SI units.

**Table 2—SI prefixes**

| Multiple | SI prefix | Symbol |
|---|---|---|
| $10^{24}$ | yotta | Y |
| $10^{21}$ | zetta | Z |
| $10^{18}$ | exa | E |
| $10^{15}$ | peta | P |
| $10^{12}$ | tera | T |
| $10^{9}$ | giga | G |
| $10^{6}$ | mega | M |
| $10^{3}$ | kilo | k |
| $10^{2}$ | hecto | h |
| 10 | deka | da |
| $10^{-1}$ | deci | d |
| $10^{-2}$ | centi | c |
| $10^{-3}$ | milli | m |
| $10^{-6}$ | micro | μ |
| $10^{-9}$ | nano | n |
| $10^{-12}$ | pico | p |
| $10^{-15}$ | femto | f |
| $10^{-18}$ | atto | a |
| $10^{-21}$ | zepto | z |
| $10^{-24}$ | yocto | y |

Compound prefixes, formed by the juxtaposition of two or more SI prefixes, shall not be used. For example, use

— nm, not mμm

— pF, not μμF

For historical reasons, although the SI unit of mass is the kilogram (kg), the SI prefixes are attached to the gram (g). Thus, use milligram (mg), not microkilogram (μkg).

[10]These spellings are in accordance with guidance given by the U.S. Department of Commerce, which, under the Metric Conversion Act of 1975, is given the responsibility of interpreting SI for the United States.

[11] The spelling of some unit names varies from language to language. One of the principal advantages of unit symbols is that they are language invariant.


Copyright © 2004 IEEE. All rights reserved.

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

If values are required outside the range covered by the prefixes, they should be expressed using powers of ten applied to the unit in question. Thus, $10^{-34}$ J.

An exponent attached to a symbol containing a prefix indicates that the multiple or submultiple of the unit (the unit with its prefix) is raised to the power expressed by the exponent. For example, where := indicates "is defined as,":

— $cm^3$ $:= (10^{-2}\ m)^3$ $= 10^{-6}\ m^3$
— $ns^{-1}$ $:= (10^{-9}\ s)^{-1}$ $= 10^{9}\ s^{-1}$
— $mm^2/s$ $:= (10^{-3}\ m)^2/s$ $= 10^{-6}\ m^2/s$

For further information concerning metric practice and SI, refer to IEEE/ASTM SI 10-2002.

### 4.6 Usage

The use of unit symbols in place of full names of the units is frequently desirable where space is restricted. Their use presupposes that the reader will find them intelligible. When an unfamiliar unit symbol is first used in text, it should be followed by its name in parentheses or the name should be given with the symbol in parentheses; the symbol may be used alone thereafter. Explanatory notes or keys should be included where appropriate on drawings and in tabular matter.

Attachment of letters to a unit symbol as a means of giving information about the quantity under consideration is incorrect. Thus MWe for "megawatts electrical (power)," Vac for "volts ac," and kJt for "kilojoules thermal (energy)" shall not be used. For this reason, no attempt should be made to construct SI equivalents of the abbreviations "psia" and "psig," so often used to distinguish between absolute and gage pressure. If the context leaves any doubt as to which is meant, the word pressure shall be qualified appropriately. For example:

— "...at a gage pressure of 13 kPa" or
— "...at an absolute pressure of 13 kPa"

When space limitations make it necessary to juxtapose information about the quantity being measured with the unit name or unit symbol, such information shall be separated from the unit symbol by a space, by a comma followed with a space, or by the equivalent. Thus, the following examples are appropriate for use on nameplates, gage scale plates, table headings, graph labels, etc.:

— rating—115 V ac
— kPa, gage
— kPa (abs.)

On the other hand, letters may be attached to a unit symbol where needed to properly identify the unit involved. In such symbols as inHg, mmHg, and $ftH_2O$, the suffixes are needed to identify the units, which are units of pressure, not of length. Similarly, it is proper to write $Btu_{IT}$, $cal_{th}$, $gal_{US}$, etc. to distinguish from the related but different units $Btu_{60}$, $cal_{15}$, $gal_{Imp}$, etc. However, such subscripts are neither needed nor permitted with SI units.

## 5. Unit symbols

Symbols for units are listed in Table 3 alphabetically by the name of the unit. The list is intended to be reasonably complete but could not possibly include all units in current use.

Obsolescent units, such as apothecaries' weights, and units used almost exclusively in narrow fields of commerce, such as the bushel and hundredweight, have been omitted. Many compound symbols and many

Copyright © 2004 IEEE. All rights reserved.


Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

illustrations of the use of the SI prefixes are included. Other combined forms may easily be constructed using multiplication, division, and exponentiation according to the principles set forth in 4.4.

The distinction between uppercase and lowercase letters shown in the list is part of the standardization of the symbol, following international rules. Changing the letter case changes the symbol and violates this standard. There are situations in which the standard symbols cannot be used, for example, when the printing equipment has no provision for Greek letters or for lowercase letters. These situations are discussed in Clause 6.

**Table 3—Units of the SI and units used with the SI**

| Unit | Symbol | Notes[a] |
|---|---|---|
| ampere | A | SI unit of electric current. Also, SI unit of magnetomotive force. |
| ampere-hour | Ah | Also A·h. |
| ampere per meter | A/m | SI unit of magnetic field strength. |
| ångström | Å | Å := $10^{-10}$ m<br>Deprecated (see IEEE/ASTM SI 10-2002). |
| astronomical unit | ua | ua = 1.495 979 × $10^{11}$ m |
| atmosphere, standard | atm | atm := 101 325 Pa<br>Deprecated (see IEEE/ASTM SI 10-2002). |
| atmosphere, technical | at | at := $kgf/cm^2$<br>Deprecated (see IEEE/ASTM SI 10-2002). |
| atomic mass unit (unified) | u | See unified atomic mass unit. |
| atto | a | SI prefix for $10^{-18}$. |
| attoampere | aA | |
| bar | bar | bar := 100 kPa<br>Deprecated (see IEEE/ASTM SI 10-2002). |
| barn | b | b := $10^{-28}$ $m^2$<br>Deprecated (see IEEE/ASTM SI 10-2002). |
| barrel | bbl | bbl := 42 gal US = 158.99 L<br>This is the standard barrel used for petroleum and petroleum products. Different standard barrels are used for other commodities. |
| baud | Bd | In telecommunications, a unit of signaling speed equal to one element per second. |
| becquerel | Bq | SI unit of activity of a radionuclide. |
| bel | B | See Annex A for guidance concerning notation. |
| billion electronvolts | GeV | The name gigaelectronvolt is preferred for this unit. |
| bit | b | In information theory, the bit is a unit of information content equal to the information content of a message, the *a priori* probability of which is one-half. In computer science, the name bit is used as a short form of *binary digit*. |
| bit per second | b/s | |


Copyright © 2004 IEEE. All rights reserved.

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

**Table 3—Units of the SI and units used with the SI *(continued)***

| Unit | Symbol | Notes[a] |
|---|---|---|
| British thermal unit (International Table) | $Btu_{IT}$ | $Btu_{IT}$ = 1055.056 J |
| British thermal unit (thermochemical) | $Btu_{th}$ | $Btu_{th}$ = 1054.350 J |
| byte | B | A byte is a string of bits, usually eight bits long, operated on as a unit. A byte is capable of holding one character in the local character set. |
| calorie (International Table) | $cal_{IT}$ | $cal_{IT}$ := 4.1868 J<br>Deprecated (see IEEE/ASTM SI 10-2002). |
| calorie (nutrition) | kcal | kcal := 4184 J |
| calorie (thermochemical) | $cal_{th}$ | $cal_{th}$ := 4.184 J<br>Deprecated (see IEEE/ASTM SI 10-2002). |
| candela | cd | SI unit of luminous intensity. |
| candela per square inch | $cd/in^2$ | Use of the SI unit, $cd/m^2$, is preferred. |
| candela per square meter | $cd/m^2$ | SI unit of luminance. |
| candle | cd | The unit of luminous intensity has been given the name candela; use of the name candle for this unit is deprecated. |
| centi | c | SI prefix for $10^{-2}$. |
| centimeter | cm | |
| centipoise | cP | cP := mPa·s<br>The name centipoise is deprecated (see IEEE/ASTM SI 10-2002). |
| centistokes | cSt | cSt := $mm^2/s$<br>The name centistokes is deprecated (see IEEE/ASTM SI 10-2002). |
| circular mil | cmil | cmil := $(\pi/4)\cdot 10^{-6}$ $in^2$ |
| coulomb | C | SI unit of electric charge. |
| cubic centimeter | $cm^3$ | |
| cubic foot | $ft^3$ | |
| cubic foot per minute | $ft^3/min$ | |
| cubic foot per second | $ft^3/s$ | |
| cubic inch | $in^3$ | |
| cubic meter | $m^3$ | |
| cubic meter per second | $m^3/s$ | |
| cubic yard | $yd^3$ | |
| curie | Ci | Ci := $3.7 \times 10^{10}$ Bq<br>A unit of activity of a radionuclide. Use of the SI unit, the becquerel, is preferred. |
| cycle per second | Hz | See hertz. |
| day | d | d := 24 h = 86 400 s |

Copyright © 2004 IEEE. All rights reserved.


--`,,,,`,-`-`,,`,,`,`,,`---
Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

**Table 3—Units of the SI and units used with the SI *(continued)***

| Unit | Symbol | Notes[a] |
|---|---|---|
| deci | d | SI prefix for $10^{-1}$. |
| decibel | dB | See Annex A for guidance concerning notation. |
| degree (plane angle) | ° | |
| degree Celsius | °C | SI unit of Celsius temperature. The degree Celsius is a special name for the kelvin, used in expressing Celsius temperatures or temperature intervals. |
| degree Fahrenheit | °F | Note that the symbols for °C, °F, and °R are composed of two elements, written with no space between the ° and the letter that follows. The two elements that make the complete symbol are not to be separated. |
| degree Kelvin | | Now called the kelvin. |
| degree Rankine | °R | |
| deka | da | SI prefix for 10. |
| dyne | dyn | dyn := $10^{-5}$ N<br>Deprecated (see IEEE/ASTM SI 10-2002). |
| electronvolt | eV | eV = 1.602 176 × $10^{-19}$ J, approximately<br>Experimentally determined unit of energy accepted for use with SI. |
| erg | erg | erg := $10^{-7}$ J<br>Deprecated (see IEEE/ASTM SI 10-2002). |
| exa | E | SI prefix for $10^{18}$. |
| exbi | Ei | Prefix for $2^{60}$. |
| farad | F | SI unit of capacitance. |
| femto | f | SI prefix for $10^{-15}$. |
| femtometer | fm | |
| foot | ft | ft := 0.3048 m |
| foot of water | ft$H_2O$ | ft$H_2O$ = 2989.1 Pa (ISO)[b] |
| foot per minute | ft/min | |
| foot per second | ft/s | |
| foot per second squared | $ft/s^2$ | |
| foot pound-force | ft·lbf | |
| footcandle | fc | fc := $lm/ft^2$<br>The name lumen per square foot is also used for this unit. Use of the SI unit of illuminance, the lux (lumen per square meter), is preferred. |
| footlambert | fL | fL := $(1/\pi)$ $cd/ft^2$<br>A unit of luminance. One lumen per square foot leaves a surface whose luminance is one footlambert in all directions within a hemisphere. Use of the SI unit, the candela per square meter, is preferred. |
| gal | Gal | Gal := $cm/s^2$<br>Deprecated (see IEEE/ASTM SI 10-2002). |


Copyright © 2004 IEEE. All rights reserved.

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

**Table 3—Units of the SI and units used with the SI *(continued)***

| Unit | Symbol | Notes[a] |
|---|---|---|
| gallon | gal | gal (Imp) = 4.5461 L |
| | | gal (US) := 231 $in^3$ = 3.7854 L |
| gauss | G | The gauss is the electromagnetic cgs unit of magnetic flux density. Deprecated (see IEEE/ASTM SI 10-2002). |
| gibi | Gi | Prefix for $2^{30}$ = 1 073 741 824. |
| gibibyte | GiB | GiB := $2^{30}$ B = 1 073 741 824 B |
| giga | G | SI prefix for $10^9$. |
| gigabit | Gb | Gb := $10^9$ b |
| gigabyte | GB | GB := $10^9$ B |
| gigaelectronvolt | GeV | |
| gigahertz | GHz | |
| gilbert | Gb, Gi | The gilbert is the electromagnetic cgs unit of magnetomotive force.<br>Deprecated (see IEEE/ASTM SI 10-2002). |
| grain | gr | gr := lb/7000 |
| gram | g | |
| gram per cubic centimeter | $g/cm^3$ | |
| gray | Gy | SI unit of absorbed dose in the field of radiation dosimetry. |
| hectare | ha | ha := $hm^2$ |
| hecto | h | SI prefix for $10^2$ |
| henry | H | SI unit of inductance. |
| hertz | Hz | SI unit of frequency. |
| horsepower | hp | Use of the SI unit of power, the watt, is preferred. |
| hour | h | h := 60 min = 3600 s |
| inch | in | in := 2.54 cm |
| inch of mercury | inHg | inHg = 3386.4 Pa (ISO)[b] |
| inch of water | $inH_2O$ | $inH_2O$ = 249.09 Pa (ISO)[b] |
| inch per second | in/s | |
| joule | J | J := N·m = W·s<br>SI unit of energy, work, and quantity of heat. |
| joule per kelvin | J/K | SI unit of heat capacity and of entropy. |
| katal | kat | kat := mol/s<br>SI unit of catalytic activity. |
| kelvin | K | SI unit of thermodynamic temperature. In 1967, the CGPM gave the name kelvin to the SI unit of temperature, which had formerly been called degree Kelvin, and assigned it the symbol K (without the symbol °). |

Copyright © 2004 IEEE. All rights reserved.


Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

**Table 3—Units of the SI and units used with the SI *(continued)***

| Unit | Symbol | Notes[a] |
|---|---|---|
| kibi | Ki | Prefix for $2^{10} = 1024$. |
| kibibyte | KiB | KiB := $2^{10}$ B = 1024 B |
| kilo | k | SI prefix for $10^3$. The symbol K shall not be used for kilo. The prefix kilo shall not be used to mean $2^{10}$ (that is, 1024). |
| kilobit per second | kb/s | |
| kilobyte | kB | kB := 1000 bytes |
| kilogauss | kG | Deprecated (see IEEE/ASTM SI 10-2002). |
| kilogram | kg | SI unit of mass. |
| kilogram-force | kgf | 1kgf := 9.806 65 N<br>Deprecated (see IEEE/ASTM SI 10-2002). |
| kilohertz | kHz | |
| kilohm | kΩ | |
| kilometer | km | |
| kilometer per hour | km/h | |
| kilopound-force | klbf | |
| kilovar | kvar | |
| kilovolt | kV | |
| kilovoltampere | kVA | |
| kilowatt | kW | |
| kilowatthour | kWh | kWh := 3.6 MJ |
| knot | kn | kn := nmi/h |
| lambert | L | L := $(1/\pi)$ cd/cm$^2$<br>A cgs unit of luminance. Deprecated (see IEEE/ASTM SI 10-2002). |
| liter | L | L := $10^{-3}$ m$^3$<br>In 1979, the CGPM approved L and l as alternative symbols for the liter. Because of frequent confusion with the numeral 1, the letter symbol l is not recommended for US use (see Federal Register notice of July 28, 1998, vol. 63, no. 144, p. 40334). The script $\ell$ shall not be used as a symbol for liter. |
| liter per second | L/s | |
| lumen | lm | SI unit of luminous flux. |
| lumen per square foot | lm/ft$^2$ | A unit of illuminance and also a unit of luminous exitance. Use of the SI unit, lumen per square meter, is preferred. |
| lumen per square meter | lm/m$^2$ | SI unit of luminous exitance. |
| lumen per watt | lm/W | SI unit of luminous efficacy. |


Copyright © 2004 IEEE. All rights reserved.

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

**Table 3—Units of the SI and units used with the SI *(continued)***

| Unit | Symbol | Notes[a] |
|---|---|---|
| lumen second | lm·s | SI unit of quantity of light. |
| lux | lx | lx := $lm/m^2$<br>SI unit of illuminance. |
| maxwell | Mx | The maxwell is the electromagnetic cgs unit of magnetic flux. Deprecated (see IEEE/ASTM SI 10-2002). |
| mebi | Mi | Prefix for $2^{20}$ = 1 048 576. |
| mebibyte | MiB | MiB = $2^{20}$ B = 1 048 576 B |
| mega | M | SI prefix for $10^6$. The prefix mega shall not be used to mean $2^{20}$ (that is, 1 048 576). |
| megabit | Mb | Mb = $10^6$ b = 1 000 000 b |
| megabit per second | Mb/s | |
| megabyte | MB | MB := 1 000 000 bytes |
| megaelectronvolt | MeV | |
| megahertz | MHz | |
| megohm | MΩ | |
| meter | m | SI unit of length. |
| meter cubed | $m^3$ | SI unit of volume. |
| meter per second | m/s | SI unit of speed. |
| meter per second squared | $m/s^2$ | SI unit of acceleration. |
| meter squared | $m^2$ | SI unit of area. |
| metric ton | t | t := 1000 kg |
| mho | mho | The name mho was formerly given to the reciprocal ohm. Deprecated; see siemens (S). |
| micro | μ | SI prefix for $10^{-6}$. |
| microampere | μA | |
| microfarad | μF | |
| microgram | μg | |
| microhenry | μH | |
| microinch | μin | |
| microliter | μL | See note for liter. |
| micrometer | μm | |
| micron | μm | The name micron is deprecated. Use micrometer. |
| micropascal | μPa | The normal threshold of hearing at 1 kHz is approximately 20 μPa. |
| microsecond | μs | |
| microwatt | μW | |
| mil | mil | mil := 0.001 in |

Copyright © 2004 IEEE. All rights reserved.


Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

**Table 3—Units of the SI and units used with the SI *(continued)***

| Unit | Symbol | Notes[a] |
|---|---|---|
| mile (statute) | mi | mi := 5280 ft = 1609 m |
| mile per hour | mi/h | Although use of mph as an abbreviation is common, it should not be used as a symbol. |
| milli | m | SI prefix for $10^{-3}$. |
| milliampere | mA | |
| millibar | mbar | mbar := hPa |
| milligram | mg | |
| millihenry | mH | |
| milliliter | mL | See note for liter. |
| millimeter | mm | |
| millimeter of mercury | mmHg | mmHg = 133.322 Pa<br>Deprecated (see IEEE/ASTM SI 10-2002). |
| millimicron | nm | Use of the name millimicron for the nanometer is deprecated. |
| millipascal second | mPa·s | Replaces the centipoise. |
| millisecond | ms | |
| millivolt | mV | |
| milliwatt | mW | |
| minute (plane angle) | ' | |
| minute (time) | min | 1 min := 60 s<br>Time may also be designated by means of superscripts as in the following example: $9^{h}\ 46^{m}\ 30^{s}$. |
| mole | mol | SI unit of amount of substance. |
| month | mo | Not uniquely defined. |
| nano | n | SI prefix for $10^{-9}$. |
| nanoampere | nA | |
| nanofarad | nF | |
| nanometer | nm | |
| nanosecond | ns | |
| nautical mile | nmi | nmi := 1852 m |
| neper | Np | See Annex A for guidance concerning notation. |
| newton | N | SI unit of force. |
| newton meter | N·m | SI unit of torque (moment of force) or of work or energy. When referring to energy, the joule is normally used: J := N·m. |
| newton per square meter | $N/m^2$ | SI unit of pressure or stress; see pascal. |
| octet | o | An octet is a string of eight bits, operated on as a unit. |


Copyright © 2004 IEEE. All rights reserved.

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

**Table 3—Units of the SI and units used with the SI *(continued)***

| Unit | Symbol | Notes[a] |
|---|---|---|
| oersted | Oe | The oersted is the electromagnetic cgs unit of magnetic field strength. Deprecated (see IEEE/ASTM SI 10-2002). |
| ohm | Ω | SI unit of electric resistance. |
| ounce (avoirdupois) | oz | oz := 1/16 lb = 28.350 g |
| pascal | Pa | Pa := $N/m^2$<br>SI unit of pressure or stress. |
| pascal second | Pa·s | SI unit of dynamic viscosity. |
| pebi | Pi | Prefix for $2^{50}$ = 1 125 899 906 842 624. |
| peta | P | SI prefix for $10^{15}$. |
| phot | ph | ph := $lm/cm^2$<br>The cgs unit of illuminance. Deprecated (see IEEE/ASTM SI 10-2002). |
| pico | p | SI prefix for $10^{-12}$. |
| picofarad | pF | |
| picowatt | pW | |
| pint | pt | pt (Imp) = 0.568 26 L |
| | | pt (US dry) = 0.550 61 L |
| | | pt (US liquid) = 0.473 18 L |
| poise | P | Deprecated (see IEEE/ASTM SI 10-2002). |
| pound (avoirdupois) | lb | lb := 0.453 592 37 kg |
| pound per cubic foot | $lb/ft^3$ | |
| pound-force | lbf | lbf = 4.4482 N |
| pound-force foot | lbf·ft | |
| pound-force per square foot | $lbf/ft^2$ | |
| pound-force per square inch | $lbf/in^2$ | Although use of the abbreviation psi is common, it should not be used as a symbol. |
| poundal | pdl | pdl := $lb·ft/s^2$ = 0.1383 N |
| quart | qt | qt (Imp) = 1.1365 L |
| | | qt (US dry) = 1.1012 L |
| | | qt (US liquid) = 0.946 35 L |
| rad | rad | rad := 0.01 Gy<br>A unit of absorbed dose in the field of radiation dosimetry. Use of the SI unit, the gray, is preferred. |
| radian | rad | SI unit of plane angle. |
| rem | rem | rem := 0.01 Sv<br>A unit of dose equivalent in the field of radiation dosimetry. Use of the SI unit, the sievert, is preferred. |
| revolution per minute | r/min | Although use of rpm as an abbreviation is common, it should not be used as a symbol. |

Copyright © 2004 IEEE. All rights reserved.


Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

**Table 3—Units of the SI and units used with the SI *(continued)***

| Unit | Symbol | Notes[a] |
|---|---|---|
| revolution per second | r/s | |
| roentgen | R | A unit of exposure in the field of radiation dosimetry. |
| second (plane angle) | " | |
| second (time) | s | SI unit of time. |
| siemens | S | $S := \Omega^{-1}$<br>SI unit of conductance. |
| sievert | Sv | SI unit of dose equivalent in the field of radiation dosimetry. |
| slug | slug | slug := lbf·$s^2$/ft = 14.594 kg. |
| square foot | $ft^2$ | |
| square inch | $in^2$ | |
| square meter | $m^2$ | |
| square meter per second | $m^2/s$ | SI unit of kinematic viscosity. |
| square millimeter per second | $mm^2/s$ | Replaces the centistokes. |
| square yard | $yd^2$ | |
| steradian | sr | SI unit of solid angle. |
| stilb | sb | sb := $cd/cm^2$<br>A cgs unit of luminance. Deprecated (see IEEE/ASTM SI 10-2002). |
| stokes | St | Deprecated (see IEEE/ASTM SI 10-2002). |
| tebi | Ti | Prefix for $2^{40}$ = 1 099 511 627 776. |
| tera | T | SI prefix for $10^{12}$. |
| terabyte | TB | TB := $10^{12}$ B |
| tesla | T | T := $Wb/m^2$<br>SI unit of magnetic flux density (magnetic induction). |
| therm | thm | thm = $1.000 \times 10^5$ Btu |
| ton (short) | ton | ton := 2000 lb |
| ton, metric | t | t := 1000 kg<br>Use of the name tonne for this unit is deprecated in the US (see IEEE/ASTM SI 10-2002). |
| unified atomic mass unit | u | u = $1.660\ 539 \times 10^{-27}$ kg<br>The (unified) atomic mass unit is defined as one-twelfth of the mass of an atom of the carbon-12 nuclide. Use of the old atomic mass unit (amu), defined by reference to oxygen, is deprecated (see IEEE/ASTM SI 10-2002). |
| var | var | IEC name and symbol for the SI unit of reactive power. |
| volt | V | SI unit of voltage. |
| volt per meter | V/m | SI unit of electric field strength. |


Copyright © 2004 IEEE. All rights reserved.

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

**Table 3—Units of the SI and units used with the SI *(continued)***

| Unit | Symbol | Notes[a] |
|---|---|---|
| voltampere | VA | IEC name and symbol for the SI unit of apparent power. |
| watt | W | SI unit of power. |
| watt per meter kelvin | W/(m·K) | SI unit of thermal conductivity. |
| watt per steradian | W/sr | SI unit of radiant intensity. |
| watt per steradian square meter | $W/(sr \cdot m^2)$ | SI unit of radiance. |
| watthour | Wh | Wh := 3.6 kJ |
| weber | Wb | Wb := V·s<br>SI unit of magnetic flux. |
| yard | yd | yd := 0.914 4 m |
| year | a | Not uniquely defined. |
| yocto | y | SI prefix for $10^{-24}$. |
| yotta | Y | SI prefix for $10^{24}$. |
| zepto | z | SI prefix for $10^{-21}$. |
| zetta | Z | SI prefix for $10^{21}$. |

[a]The notes give exact definitions (indicated by the symbol :=) for many of the units and give conversion factors in other cases. The conversion factors indicated with the equals sign are accurate to the number of figures shown. For more accurate conversion factors and other general information about units, see IEEE/ASTM SI 10-2002.
[b]The term (ISO) means that the definition is from ISO 31 [B4] (see Annex B).

## 6. Unit symbols to be used with limited character sets

Historically the originator of written information had full control of its appearance when distributed to the readers. Now that information is often transmitted electronically, this control of the final appearance of information is in jeopardy. This loss of control is commonly seen in the use of three common forms of communication formats: electronic mail, HTML-formatted web pages, and the transmission of computer files.

The problem in electronic transmission of information is that there are no universally accepted standards in use. The problem is exacerbated by the use of multiple types of platforms (at the transmission end, the receiving end, and in the transmission path), encoding protocols, type families, operating systems, and computer programs. The originator must now take care to ensure that when information is transmitted, received, and decoded it is faithfully reproduced, at least as far as technical details are concerned.

Various technical details relating to the transmission of quantities and units are discussed below. These should be followed whenever the originator suspects that the communication path is limited by the following constraints.

Copyright © 2004 IEEE. All rights reserved.


Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

## 6.1 Limitations arising from the use of ASCII 0000-0127

Perhaps the most common digitally encoded character set used around the world in electronic communications is the American Standard Code for Information Interchange (ASCII). Since the uppercase and lowercase Latin letters are all represented, the only SI symbols not available are the uppercase omega (Ω), used for the ohm, and the lowercase mu (μ), used for the prefix micro. The normal arithmetic and algebraic symbols +, –, ), (, =, <, >, /, period (.), and comma (,) are available; note that the hyphen is used as the minus sign as is commonly done in typewriting. The use of superscripts and subscripts is not possible. The following substitutions are to be used when communications are limited to basic ASCII codes (character values of 0000 through 0127):

a) For μ, substitute u.

—*Example:* μA for microampere becomes uA.

b) For Ω , substitute Ohm.

—*Example:* The symbol Ω for ohm becomes Ohm.

c) For °C, substitute C.

—*Example:* A temperature of 12 degrees Celsius becomes 12 C.

d) For units of plane angle, substitute as follows:

| | | | | |
|---|---|---|---|---|
| — | degree | ° | use | deg |
| — | minute | ' | use | min |
| — | second | " | use | sec |

NOTE—Depending on the recipient's type face (often called "font"), the straight minute and second symbols may be replaced by the curly apostrophe (or single quote) and double quote but this should not result in any ambiguity.

e) For superscripted numerals in units, use numerals on the line. Use either a caret or omit any space between the principal unit symbol and its exponent, whether positive or negative. The use of the caret is more explicit and less likely to be misunderstood than merely placing the exponent on the line without an intervening space. The latter, however, is the form specified by ISO 2955 [B15].[12]

—*Example:* The symbol for square millimeter becomes either mm^2 or mm2. The symbol for watt per square meter becomes W/m^2, W/m2, W m^-2, or W m-2.

f) For superscripted numerals used to indicate the exponent of a numerical quantity or variable, use the carat before the numeral.

—*Example:* A square that is 8 cm by 8 cm has an area of (8 cm)^2 or 64 cm^2.

g) For subscripts, use an underscore ( _ ) or a parenthetical expression starting with the word "sub" followed by a space.

—*Example:* $V_{ab}$ may be written as V_ab or V(sub ab). Note that sloping type is not available.

h) For a raised dot within products of units, use a space or a full stop (a period; i.e., a dot on the line). The former is preferred, but the latter is the form specified by ISO 2955 [B15].

— *Example:* The joule (1 J = 1 W·s) is equivalent to 1 W s or 1 W.s.

i) For a raised dot (·) or multiplicative cross (×) between numerical quantities, use a lowercase x. Spaces surrounding the x improve clarity.

— *Example:* The product 4·5 may be represented by 4 x 5.

[12]The numbers in brackets correspond to those of the bibliography in Annex B.


--`,,,,`,-`-`,,`,,`,`,,`---
Copyright © 2004 IEEE. All rights reserved.
Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

j) For the symbol π use pi.

— *Example:* There are 2pi radians in a complete circle.

NOTE—Since pi is not a unit symbol there is no space between it and the numeral.

k) For ± (plus or minus) use +/– and for its inverse use –/+.

l) For ≈ (approximately) use ~ (tilde).

## 6.2 Limitations arising from the use of HTML-coded web pages and electronic mail

Hypertext Markup Language (HTML)-coded pages are normally read with "browsers," which vary in their capabilities and style. Even with an imposed limitation to the use of one specified browser in a given communications link, individual operators might set various preferences that can significantly alter the display of information. Similarly, programs that read electronic mail ("e-mail") vary and can cause similar problems. These preferences include the type font, type face, type size (all are sometimes collectively called "font" in colloquial parlance), spacing (proportional or fixed pitch), and encoding protocols (e.g., ASCII, Unicode, ISO-8859-1, etc.). The result can be confusion of symbols and the spacing between numeral and unit or within units.

Authors who use HTML have a wider array of tags and codes at their disposal but this usually leads to cross-platform problems. The ASCII code for the non-breaking space (0160) is not implemented identically on all platforms, for example. On some, the space may be extraordinarily wide. Some browsers differ in their ability to decode HTML tags. Scaling problems often occur when trying to represent individual symbols with in-line embedded graphic images. These may appear smaller or larger than the surrounding HTML encoded text.

It would be prudent to standardize explicitly the platforms, operating systems, programs, preferences, etc. in a given communications link but transmission beyond a select group of receivers becomes virtually impossible to control. To maintain absolute control of the formatting of information would require distribution of hard copies. The next best technique, and one that will allow electronic transmission is the use of graphic representations of the pages. The sender of graphic images is cautioned that some programs may distort aspect ratios, which would create problems for scale drawings but should satisfactorily convey typography. Proprietary programs that combine graphic and embedded font information are available and maintain aspect ratios, even across platform or operating system boundaries.

In light of the above considerations the following guidance is specified:

a) The transmitter of information should either ensure that the path and receiving end will enable accurate rendering of the transmitted information or should explicitly state the necessary information for the receiver to do so—e.g., type font, program to be used for reading the information, including version, operating system and platform on which it is run.

b) When the above is not readily possible the transmitter should revert to the limitations of basic ASCII as discussed in 6.1. This basic character set is usually included in most encoding protocols as a baseline and the fewest differences exist with this set of characters across platform, operating system, and program lines.

c) When the possibility exists that a line break may be imposed on transmitted information by the path or the receiver, the space between the numeral and the unit in a quantity should still be used but spaces between symbols in a compound unit should be avoided. If necessary, spell out the unit name rather than using a compounded unit symbol.

— *Example:* For 12 N·m use 12 N m only if spacing between the N and the m are assured; otherwise use 12 newton meters.

Copyright © 2004 IEEE. All rights reserved.


Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

## 6.3 Examples of symbols for limited character sets

Table 4 shows many examples of how the foregoing principles may be applied.

The column labeled Form I applies to data systems that have the capability to use both uppercase and lowercase letters; digits; and at least the graphic characters apostrophe (’) quotation mark (”), hyphen (-), period (.), and slash (/). However, they do not have the capability to use the Greek letters mu (μ) and omega (Ω).

The column labeled Form II applies to data systems that are further limited in that they have only one case (either uppercase or lowercase), and they lack the apostrophe and quotation mark.

**Table 4 Examples of symbols for limited character sets**

| | Form I | Form II | |
|---|---|---|---|
| | (Both cases) | (Lowercase only) | (Uppercase only) |
| ampere | A | a | A |
| ampere per meter | A/m | a/m | A/M |
| ångström | A | a | A |
| barrel | bbl | bbl | BBL |
| becquerel | Bq | bq | BQ |
| British thermal unit | Btu | btu | BTU |
| candela per square meter | cd/m2 | cd/m2 | CD/M2 |
| centimeter | cm | cm | CM |
| coulomb | C | c | C |
| cubic meter per second | m3/s | m3/s | M3/S |
| decibel | dB | db | DB |
| degree (angle) | deg | deg | DEG |
| degree Celsius | c | c | C |
| degree Fahrenheit | F | f | F |
| farad | F | f | F |
| foot per second | ft/s | ft/s | FT/S |
| henry | H | h | H |
| hertz | Hz | hz | HZ |
| hour | h | h | H |
| joule per kelvin | J/K | j/k | J/K |
| kilogram | kg | kg | KG |
| kilometer | km | km | KM |
| kilowatthour | kWh | kwh | KWH |
| liter | L | l | L |
| lumen per watt | lm/W | lm/w | LM/W |
| megahertz | MHz | mhz | MHZ |
| megohm | MOhm | mohm | MOHM |
| meter | m | m | M |
| metric ton | t | t | T |


Copyright © 2004 IEEE. All rights reserved.

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

**Table 4 Examples of symbols for limited character sets *(continued)***

| | Form I | Form II | |
|---|---|---|---|
| | (Both cases) | (Lowercase only) | (Uppercase only) |
| microfarad | uF | uf | UF |
| microsecond | us | us | US |
| mile per hour | mi/h | mi/h | MI/H |
| milliliter | mL | ml | ML |
| millipascal second | mPa s | mpa s | MPA S |
| newton meter | Nm | nm | NM |
| picowatt | pW | pw | PW |
| pound-force foot | lbf ft | lbf ft | LBF FT |
| tesla | T | t | T |
| volt per meter | V/m | v/m | V/M |
| watt per steradian square meter | W(sr m2) | w(sr m2) | W(SR M2) |
| weber | Wb | wb | WB |
| yard | yd | yd | YD |

## 6.4 Limitations arising from importing and exporting documents between computer programs

Despite the claim by many program vendors that their programs can “translate” into or from various formats, experience indicates that problems are frequently encountered. These problems occur even when using the same program but on different platforms. For example, Ω and μ often are not transferred properly from one program or platform to another. The transmitter of information is advised to proceed with caution and to take every step available to ensure accurate transmission. The use of proprietary programs such as mentioned above or such as $T_EX$ or $L^AT_EX$ may provide a solution to this problem, but the users must be on their guard. In general, unformatted text files adhering to the guidance of 6.1 are the safest editable documents to import or export.

Copyright © 2004 IEEE. All rights reserved.


Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

# Annex A

(normative)

## Notation for expressing the reference of a level

The level representing a physical quantity $x$ with a reference quantity $x_{\text{ref}}$ may be indicated by

— $L_x(\text{re } x_{ref})$ or by $L_{x/xref}$

Examples, where the last example is for both a reference value and a weighting scale denoted as A:

a) The statement that the level of an electric current is 10 Np below 1 A can be written as

— $L_I(\text{re 1 A}) = -10$ Np

b) The statement that a certain power level is 7 dB above 1 mW can be written as

— $L_P(\text{re 1 mW}) = 7$ dB

c) The statement that a certain electric field strength is 50 Np above 1 μV/m can be written as

— $L_E(\text{re 1}\mu\text{V/m}) = 50$ Np

d) The statement that a certain sound pressure level is 15 dB above the level corresponding to a reference pressure of 20 μPa can be written as

— $L_p(\text{re 20 }\mu\text{Pa}) = 15$ dB

or as

— $L_{p/(20\ \mu\text{Pa})} = 15$ dB

e) The statement that a certain sound pressure level is 60 dB above the level correspoinding to a reference pressure of 20 μPa with the measurements weighted in accordance with the A scale:

— $L_{\text{A}}(\text{re 20 }\mu\text{Pa }) = 60$ dB

In presenting data, particularly in tabular form or in graphical symbols, a condensed notation is often needed for identifying the reference value. Then the following condensed form, illustrated by application to the above examples, may be used:

— –10 Np (1 A)

— 7 dB (1 mW)

— 50 Np (1 μV/m)

— 15 dB (20 μPa)

— 60 dB (A)

A “1” in the expression of a reference quantity is sometimes omitted. This is not recommended in cases where confusion could occur. When a constant reference quantity is used repeatedly in a given context and explained in the text, it may be omitted.


Copyright © 2004 IEEE. All rights reserved.

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS Not for Resale

# Annex B

(informative)

# Bibliography

[B1] ANSI X3.50-1986 (Reaff 1992), American National Standard for Information Systems-Representations for U.S. Customary, SI, and Other Units to Be Used in Systems with Limited Character Sets.[13]

[B2] BIPM. 1998. Le Système internationale d'unités (The International System of Units), 7th edition, referred to herein as "the SI brochure."

[B3] IEEE Std 1541™-2002, IEEE Standard for Prefixes for Binary Multiples.[14, 15]

[B4] ISO 31-0: 1992, Quantities and units—Part 0: General principles.[16]

[B5] ISO 31-1: 1992, Quantities and units—Part 1: Space and time.

[B6] ISO 31-2: 1992, Quantities and units—Part 2: Periodic and related phenomena.

[B7] ISO 31-3: 1992, Quantities and units—Part 3: Mechanics.

[B8] ISO 31-4: 1992, Quantities and units—Part 4: Heat.

[B9] ISO 31-5: 1979, Quantities and units—Part 5: Electricity and magnetism.

[B10] ISO 31-6: 1992, Quantities and units—Part 6: Light and related electromagnetic radiations.

[B11] ISO 31-7: 1992, Quantities and units—Part 7: Acoustics.

[B12] ISO 31-8: 1980, Quantities and units—Part 8: Physical chemistry and molecular physics.

[B13] ISO 1000: 1981, SI units and recommendations for the use of their multiples and of certain other units.

[B14] ISO 1683: 1983, Reference quantities for units expressed as levels in decibels.

[B15] ISO 2955: 1983, Information processing-Representation of SI and other units in systems with limited character sets.

[B16] NIST Special Publication 330 (2001), The International System of Units (SI).[17]

---

[13] ANSI publications are available from the Sales Department, American National Standards Institute, 11 West 42 Street, 13th Floor, New York, NY 10036, USA.

[14] IEEE publications are available from the Institute of Electrical and Electronics Engineers, Inc., 445 Hoes Lane, Piscataway, NJ 08854, USA (http://standards.ieee.org/).

[15] The IEEE standards or products referred to in this annex are trademarks of the Institute of Electrical and Electronics Engineers, Inc.

[16] ISO publications are available from ISO, Case Postale 56, 1 rue de Varembé, CH-1211, Genève 20, Switzerland/Suisse. ISO publications are also available in the United States from the Sales Department, American National Standards Institute, 11 West 42nd Street, 13th Floor, New York, NY 10036, USA.

[17] NIST publications are available from the Superintendent of Documents, US Government Printing Office, Washington, DC 20402, USA.

Copyright © 2004 IEEE. All rights reserved.


Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale