ANSI C136.11-1995
(Revision of ANSI C136.11-1988)

American National Standard for Roadway Lighting Equipment—Multiple Sockets

Sponsor

Accredited Standards Committee on Roadway Lighting Equipment, C136

accredited by the

American National Standards Institute

Secretariat

The Institute of Electrical and Electronics Engineers, Inc.

Approved October 16, 1995

American National Standards Institute

Abstract: Medium and mogul multiple sockets as used in luminaires designed and intended for use in lighting roadways and other areas open to general use by the pubic are covered. This standard provides interchangeability of lamps, minimum safety standards for operating personnel, and minimum performance criteria.
Keywords: lamps, lighting equipment, luminaires, medium sockets, multiple sockets, mogul sockets, roadway lighting equipment, sockets

---

The Institute of Electrical and Electronics Engineers, Inc.
345 East 47th Street, New York, NY 10017-2394, USA

Copyright © 1995 by the Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 1995. Printed in the United States of America.

ISBN 1-55937-550-7

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

IEEE Standards documents are developed within the Technical Committees of the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Board. Members of the committees serve voluntarily and without compensation. They are not necessarily members of the Institute. The standards developed within IEEE represent a consensus of the broad expertise on the subject within the Institute as well as those activities outside of IEEE that have expressed an interest in participating in the development of the standard.

Use of an IEEE Standard is wholly voluntary. The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE Standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard. Every IEEE Standard is subjected to review at least every five years for revision or reaffirmation. When a document is more than five years old and has not been reaffirmed, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE Standard.

Comments for revision of IEEE Standards are welcome from any interested party, regardless of membership affiliation with IEEE. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments.

Interpretations: Occasionally questions may arise regarding the meaning of portions of standards as they relate to specific applications. When the need for interpretations is brought to the attention of IEEE, the Institute will initiate action to prepare appropriate responses. Since IEEE Standards represent a consensus of all concerned interests, it is important to ensure that any interpretation has also received the concurrence of a balance of interests. For this reason IEEE and the members of its technical committees are not able to provide an instant response to interpretation requests except in those cases where the matter has previously received formal consideration.

Comments on standards and requests for interpretations should be addressed to:

Secretary, IEEE Standards Board
445 Hoes Lane
P.O. Box 1331
Piscataway, NJ 08855-1331
USA

IEEE Standards documents may involve the use of patented technology. Their approval by the Institute of Electrical and Electronics Engineers does not mean that using such technology for the purpose of conforming to such standards is authorized by the patent owner. It is the obligation of the user of such technology to obtain all necessary permissions.

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

Introduction

(This introduction is not a part of ANSI C136.11-1995, American National Standard for Roadway Lighting Equipment—Multiple Sockets.)

The Accredited Standards Committee on Roadway Lighting, C136, had the following members at the time this document was approved:

Organization Represented	*Name of Representative*
Alabama Power Company	Scott Thurman
Area Lighting Research, Inc.	George Duve
Cooper Lighting	Richard Snow
Dark to Light, Inc.	Jeff Walters John Powers (*Alt.*)
Detroit Edison Company	Donald Edwards
Duke Power Company	Stokes White
Edison Electric Institute	Matthew Mingioa
Entergy Services, Inc.	Al Maguire
Fisher-Pierce Corporation	Robert Broadbent Mark Martich (*Alt.*)
General Electric Company	Jim Havard William Alexander (*Alt.*)
Georgia Power Company	Mike Stevans
Hapco	Tom Fawley
Holophane Lighting Company	Randy Crothers
Hubbell, Inc.	Tom Hirt Kerry Evans (*Alt.*)
Illuminating Engineering Society	Richard E. Stark
Institute of Electrical and Electronics Engineers, Inc.	Anderw S. Kosiorek
Los Angeles City Department of Public Works	R. E. Beanblossom
M. H. Rhodes, Inc.	John Mills Stan Brym (*Alt.*)
National Electrical Contractors Association	Charles Williams
Penn Power and Light Company	Robert L. Nickel
PSI Energy, Inc.	Richard E. Hildreth

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

Sherman Utility Structures ..... Ricky Miskelley
Brad McCollum (*Alt*.)

Thomas & Betts Corporation ..... Rick Kauffman

Union Metal Corporation ..... Joe Brindlinger

Valmont Industries ..... Dennis Havranek

Virginia Power ..... Frank Hinkle

W. J. Whatley, Inc. ..... George Maybe

Mary Lynne Nielsen
IEEE Standards Project Editor

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

Contents

CLAUSE PAGE

1. Overview 1

1.1 Scope 1
1.2 Purpose 1

2. References 1

3. Classification 2

3.1 Voltage 2
3.2 Pulse 2

4. Rated wattage 2

5. Mechanical requirements 2

5.1 Guarded 2
5.2 Lamp insertion 2
5.3 Insert and removal torque—mogul 2
5.4 Insert and removal torque—medium 3

6. Screw shells 3

6.1 Conformance 3
6.2 Metal parts 3

7. Terminals and leads 3

8. Operating temperature 3

9. Insulating material 4

10. Alignment 4

11. Fatigue tests 4

--`,,`-`-`,,`,,`,`,,`---

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS

Not for Resale

--``,,-`-`,,`,,`,`,,`---

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS

Not for Resale

American National Standard for Roadway Lighting Equipment—Multiple Sockets

1. Overview

1.1 Scope

This standard covers medium and mogul multiple sockets as used in luminaires designed and intended for use in lighting roadways and other areas open to general use by the public.

1.2 Purpose

The purpose of this standard is to provide interchangeability of lamps, minimum safety standards for operating personnel, and minimum performance criteria.

2. References

This standard shall be used in conjunction with the following publications. When these standards are superseded by an approved revision, the revision shall apply.

ANSI C78 Series, Electric Lamps.[1]

ANSI C81 Series, Electric Lamp Bases and Holders.

ANSI C81.62-1991, American National Standard Lampholders for Electric Lamps.

ANSI C81.63-1991, American National Standard Gauges for Electric Lamp Bases and Lampholders.

ANSI C136 Series, Roadway Lighting Equipment.

ANSI C136.2-1985, American National Standard for Roadway Lighting—Luminaires—Voltage Classification.

[1]ANSI publications are available from the Sales Department, American National Standards Institute, 11 West 42nd Street, 13th Floor, New York, NY 10036, USA.

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

ASTM E1150-7 (93), Definitions of Terms Relating to Fatigue.[2]

3. Classification

3.1 Voltage

Sockets, when mounted on their supports, shall conform to the requirements for the 250 V or 600 V classification given in ANSI C136.2-1985.

3.2 Pulse

Sockets, when used with high-pressure sodium lamps, shall have a minimum pulse voltage rating of

4 kV—All medium sockets
4 kV—Mogul sockets when used with lamps 400 W and below
5 kV—Mogul sockets when used with lamps above 400 W

4. Rated wattage

Medium sockets shall be rated 660 W, and mogul sockets shall be rated 1500 W.

5. Mechanical requirements

5.1 Guarded

Parts that may be electrically energized shall be guarded to prevent accidental contact with metal parts during their installation, removal, or adjustment.

5.2 Lamp insertion

Sockets shall be designed so as to allow full insertion of all lamps that meet the requirements given in the ANSI C78 Series.[3]

5.3 Insert and removal torque—mogul

Sockets shall be designed so as to maintain contact pressure and retain the lamp without loosening under normal conditions of vibration. The torque required to insert and remove mogul base lamps shall be in accordance with table 1. The torque test shall be performed with a plug gauge having the dimensions given in Standard Sheets 3-190, 3-195, and 3-196 of ANSI C81.63-1991 and its supplements and in accordance with Standard Sheet 2-185 of ANSI C81.62-1991 and its supplements.

[2]ASTM publications are available from the Customer Service Department, American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103, USA.
[3]Information on references can be found in clause 2.

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS Not for Resale

Table 1—Insertion and removal torque*

Maximum insertion torque to test lamp	35 lbs-in (3.95 N·m)
Minimum removal torque	8 lbs-in (0.90 N·m)
Maximum removal torque	35 lbs-in (3.95 N·m)

*Applies to mogul sockets only.

5.4 Insert and removal torque—medium

Insertion and removal torque requirements for medium-base sockets are to be determined.

6. Screw shells

6.1 Conformance

Socket screw shells shall be in conformance with the applicable portions of ANSI C81.62-1991 and its supplements, except that threads may be deformed, cut, or partially replaced by springs to meet the removal torque requirements of 5.3. The screw-shell height and center contact placement shall be such as to ensure proper electrical contact with lamp bases meeting the requirements of Standard Sheets 2-157, 3-169, 3-170, and 3-171 for medium sockets and Standard Sheets 2-185, 2-190, 3-191, and 3-192 for mogul sockets of ANSI C81.62-1991, ANSI C81.63-1991, and their supplements.

6.2 Metal parts

Socket screw shells and other lamp-gripping metal parts shall be of copper or copper alloy and shall be plated with nickel or an equivalent corrosion-resistant metal. All other socket parts, except those of stainless steel, shall also be plated with nickel or an equivalent corrosion-resistant metal.

7. Terminals and leads

Socket terminals or permanently mounted leads shall be provided in accordance with the following:

a) Terminals for line connections shall be suitable for both copper and aluminum conductors from 14 AWG to 8 AWG, either solid or stranded.
b) Terminals, leads, and associated insulation for internal luminaire wiring (with a separate terminal block provided for line connections) shall be adequate for the wattage rating of the socket.

8. Operating temperature

The socket shall be capable of operating continuously when heated by a lamp whose operating base temperature is 210 °C for mogul sockets or 190 °C for medium sockets if electrical porcelain or other ceramic material is used. Other socket skirt materials may be used only if the operating temperature in the luminaire does not exceed the thermal limits of the material.

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale

9. Insulating material

Sockets shall include a body of porcelain or other suitable insulating material that encloses the sides and bottom of the screw shell sufficiently to meet the requirements of 5.1 and that extends beyond the depressed center contact in accordance with the following table.

Type of socket	Minimum distance (in)
Mogul	1-5/8 (41.3 mm)
Medium	15/16 (23.8 mm)

10. Alignment

Sockets shall be so designed that a deviation from the lamp base axis in any direction from the centerline (measured perpendicular to the socket mounting surface) will not exceed 3 degrees. The deviation shall be checked in all directions immediately after applying and slowly releasing a minimum moment load of 100 lbs-in (11.3 N·m) to a fully inserted lamp-base screw-shell gauge meeting the requirements of ANSI C81.63-1991 and its supplements.

11. Fatigue tests

Sockets shall be so designed that, when used in conjunction with the maximum weight lamp (or dummy lamp) for which they are intended and when subjected to a 1 G (9.8 $m \cdot s^2$) vibration stress in all planes, the material used in the socket construction shall not exceed the fatigue limit stress values for those materials as determined by ASTM E1150-7 (93). Fatigue tests shall be run at or below the resonant frequency of the socket and lamp (or dummy lamp), but the frequency shall not exceed 25 Hz.

Copyright The Institute of Electrical and Electronics Engineers, Inc.
Provided by IHS under license with IEEE
No reproduction or networking permitted without license from IHS
Not for Resale