INTERNATIONAL STANDARD ISO/IEC 10165-4:1992
TECHNICAL CORRIGENDUM 2

Published 2003-02-01

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

Information technology — Open Systems Interconnection — Structure of management information: Guidelines for the definition of managed objects

TECHNICAL CORRIGENDUM 2

Technologies de l'information — Interconnexion de systèmes ouverts — Structures des informations de gestion: Directives pour la définition des objets gérés

RECTIFICATIF TECHNIQUE 2

Technical Corrigendum 2 to ISO/IEC 10165-4:1992 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*.

ICS 35.100.70 **Ref. No. ISO/IEC 10165-4:1992/Cor.2:2003(E)**

© ISO/IEC 2003 – All rights reserved

Published in Switzerland

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

--`,,,`-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

INTERNATIONAL STANDARD

ITU-T RECOMMENDATION

INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION – STRUCTURE OF MANAGEMENT INFORMATION: GUIDELINES FOR THE DEFINITION OF MANAGED OBJECTS

TECHNICAL CORRIGENDUM 2

Revision of GDMO to include ASN.1:1997

1) Subclause 2.1

Apply the following changes:

Replace:

- ITU-T Recommendation X.680 (1995) | ISO/IEC 8824-1:1995, *Information technology – Abstract Syntax Notation One (ASN.1) – Specification of basic notation.*
- ITU-T Recommendation X.681 (1994) | ISO/IEC 8824-2:1995, *Information technology – Abstract Syntax Notation One (ASN.1) – Information object specification.*
- ITU-T Recommendation X.682 (1994) | ISO/IEC 8824-3:1995, *Information technology – Abstract Syntax Notation One (ASN.1) – Constraint specification.*
- ITU-T Recommendation X.683 (1994) | ISO/IEC 8824-4:1995, *Information technology – Abstract Syntax Notation One (ASN.1) – Parameterization of ASN.1 specifications.*
- ITU-T Recommendation X.690 (1994) | ISO/IEC 8825-1:1995, *Information technology – ASN.1 encoding rules – Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER).*
- ITU-T Recommendation X.691 (1995) | ISO/IEC 8825-2:1995, *Information technology – ASN.1 encoding rules – Specification of Packed Encoding Rules (PER).*

with:

- ITU-T Recommendation X.680 (1997) | ISO/IEC 8824-1:1998, *Information technology – Abstract Syntax Notation One (ASN.1): Specification of basic notation.*
- ITU-T Recommendation X.681 (1997) | ISO/IEC 8824-2:1998, *Information technology – Abstract Syntax Notation One (ASN.1): Information object specification.*
- ITU-T Recommendation X.682 (1997) | ISO/IEC 8824-3:1998, *Information technology – Abstract Syntax Notation One (ASN.1): Constraint specification.*
- ITU-T Recommendation X.710 (1997) | ISO/IEC 9595:1998, *Information technology – Open Systems Interconnection – Common Management Information service.*
- ITU-T Recommendation X.711 (1997) | ISO/IEC 9596-1:1998, *Information technology – Open Systems Interconnection – Common Management Information Protocol: Specification.*

2) Subclause 2.2

Remove the following paired references:

- CCITT Recommendation X.208 (1988), *Specification of abstract syntax notation one (ASN.1).*

  ISO/IEC 8824:1990, *Information technology – Open Systems Interconnection – Specification of Abstract Syntax Notation One (ASN.1).*
- CCITT Recommendation X.710 (1991), *Common Management Information Service Definition for CCITT Applications.*

  ISO/IEC 9595:1990, *Information technology – Open Systems Interconnection – Common management information service definition.*

--`,,`--`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

– CCITT Recommendation X.711 (1991), *Common Management Information Protocol Specification for CCITT Applications.*

ISO/IEC 9596-1:1991, *Information technology – Open Systems Interconnection – Common management information protocol – Part 1: Specification.*

3) Subclause 3.7

Replace CCITT Rec. X.208 and ISO/IEC 8824 *with* ITU-T Rec. X.680 | ISO/IEC 8824-1.

4) New subclause 3.8

Insert the following new subclause and renumber the following subclauses accordingly:

3.8 ASN.1 information object class definitions

This Recommendation | International Standard makes use of the following terms defined in ITU-T Rec. X.681 | ISO/IEC 8824-2:

a) information object class;

b) value set field;

c) variable-type.

5) Subclause 6.4

Replace all occurrences of CCITT Rec. X.208 and ISO/IEC 8824 *with* ITU-T Rec. X.680 | ISO/IEC 8824-1.

6) Clause 8

Insert the following paragraph between the title of clause 8 and the title of subclause 8.1:

The GDMO templates defined in this Recommendation | International Standard may be used to specify Action types, Attribute types, Event report types and their associated ASN.1 type definitions, as an alternative to using the Information Object Class definitions specified in ITU-T Rec. X.711 | ISO/IEC 9596-1.

7) Subclause 8.2, *item f)*

Replace both occurrences of CCITT Rec. X.208 and ISO/IEC 8824 *with* ITU-T Rec. X.680 | ISO/IEC 8824-1.

8) Subclause 8.5.1

Replace:

The type specified in a Parameter template is used to fill in an `ANY DEFINED BY x` construct in a management PDU, where `x` is a field in the PDU that carries the object identifier assigned to the parameter.

with:

The type specified in a Parameter template defines the type of the variable-type value set field in an information object class, as defined in ITU-T Rec. X.681 | ISO/IEC 8824-2. This field is carried in a management PDU when that PDU carries the object identifier value assigned to that template in the context specified in that template.

9) Subclause 8.5.1.1.1

Replace:

The context is unambiguously identified by the management PDU if and only if the ANY DEFINED BY construct appears in that PDU exactly once.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

with:

The context is unambiguously identified by the management PDU if and only if the PDU contains exactly one variable-type value set field.

10) Clause 9

Replace the following (including the footnote):

NOTE – ISO/IEC JTC 1/SC 21 rules dictate a periodic review for renewal of the ASN.1:1990 International Standards every one (1) year[1)]. National Bodies are asked to consider the above when reviewing the ASN.1:1990 standards. This ensures that the ASN.1:1990 standards are retained as long as needed.

Related footnote:

1) ISO/IEC JTC 1/SC 21 (SC21) reaffirmed the continuation of availability of the ASN.1:1990 standards for reasons of conformance and interpretability (in SC21 N 9001 rev). SC21 requested its WGs to continue to maintain these standards. An SC21 resolution to continue maintenance will be conducted at each SC21 meeting (currently, once a year).

with:

NOTE – ASN.1:1994 is used to mean the language specified by the 1994 or later versions of ITU-T Rec. X.680 | ISO/IEC 8824-1 and ASN.1:1990 means the language specified by CCITT Rec. X.208 and ISO/IEC 8824 which is now obsolete but previously was identified as "CCITT Recommendation X.208 (1988), *Specification of Abstract Syntax Notation One (ASN.1)*" or "ISO/IEC 8824:1990, *Information technology – Open Systems Interconnection – Specification of Abstract Syntax Notation One (ASN.1)*".

11) Subclause A.3

Replace the production for **SpecificErrorInfo** *with the following ASN.1 production:*

```
SpecificErrorInfo ::= SEQUENCE {
    errorId         CMIP-SPECIFICERROR.&id ({SpecificErrorSet}),
    errorInfo       CMIP-SPECIFICERROR.&Value ({SpecificErrorSet} {@.errorId}) }
```

12) Subclause B.6.1

Replace the following:

Any

ASN.1 allows a special type ANY which can contain any other ASN.1 type at all. Such a type is not allowed within Z and it would be difficult to extend it to include one. However given any known set of types, it is possible to define a Z free type which can include any of those other types. An alternative strategy is to define ANY as a given set for typechecking purposes. This is satisfactory as long as nothing else is done with it. The type *AttributeValues* usually replaces *ANY*. This is defined below.

with:

Open Types

ASN.1 allows open types which can contain any other ASN.1 type at all. Such a type is not allowed within Z and it would be difficult to extend Z to include open types. However, given any known set of types, it is possible to define a Z free type which can include any of those other types. An alternative strategy is to define open type as a given set for typechecking purposes. This is satisfactory as long as nothing else is done with it. The type *AttributeValues* usually replaces open type. This is defined below.

13) Subclause B.6.5

Replace:

As mentioned above, it is difficult to model ASN.1 type ANY in Z.

with:

As mentioned above, it is difficult to model ASN.1 open types in Z.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

STD.ISO 10165-4-ENGL 1992 ■ 4851903 0775808 1T9 ■

INTERNATIONAL STANDARD

ISO/IEC 10165-4

First edition
1992-09-01

AMENDMENT 3
1998-12-15

Information technology — Open Systems Interconnection — Structure of management information: Guidelines for the definition of managed objects

AMENDMENT 3: Guidelines for the use of Z in formalizing the behaviour of managed objects

Technologies de l'information — Interconnexion de systèmes ouverts — Structures des informations de gestion: Partie 4: Principes directeurs pour la définition des objets gérés

AMENDEMENT 3: Principes directeurs pour l'utilisation de Z dans la formalisation du comportement de l'objet géré

This material is reproduced from ISO documents under International Organization for Standardization (ISO) Copyright License Number IHS/ICC/1996. Not for resale. No part of these ISO documents may be reproduced in any form, electronic retrieval system or otherwise, except as allowed in the copyright law of the country of use, or with the prior written consent of ISO (Case postale 56, 1211 Geneva 20, Switzerland, Fax +41 22 734 10 79), IHS or the ISO Licensor's members.

Reference number
ISO/IEC 10165-4:1992/Amd.3:1998(E)

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Contents

Page

1) Table of contents 1

2) Subclause 2.1 1

3) New subclause 2.3 1

4) New Annex B 1

Annex B – Guidelines for the use of Z in formalizing the behaviour of Managed Objects 2

© ISO/IEC 1998

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

© ISO/IEC

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Amendment 3 to ISO/IEC 10165-4:1992 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 33, *Distributed application services*, in collaboration with ITU-T. The identical text is published as ITU-T Rec. X.722/Amd.3.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

INTERNATIONAL STANDARD

ITU-T RECOMMENDATION

INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION – STRUCTURE OF MANAGEMENT INFORMATION: GUIDELINES FOR THE DEFINITION OF MANAGED OBJECTS

AMENDMENT 3
Guidelines for the use of Z in formalizing the behaviour of managed objects

1) Table of contents

Add the following reference to the table of contents:

Annex B – Guidelines for the use of Z in formalizing the behaviour of managed objects

2) Subclause 2.1

Add the following reference to 2.1:

– CCITT Recommendation X.731 (1992) | ISO/IEC 10164-2:1992, *Information technology – Open Systems Interconnection – Systems Management: State management function.*

3) New subclause 2.3

Add a new subclause as follows:

2.3 Additional references

– ISO/IEC 13568:[1)], *Information technology – Z specification language.*

[1)] Presently at the stage of draft.

4) New Annex B

Add a new Annex B, as follows:

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Annex B

Guidelines for the use of Z in formalizing the behaviour of Managed Objects

(This annex does not form an integral part of this Recommendation | International Standard)

B.1 Introduction

This annex contains a technical guide on the use of the Z language for defining the behaviour of managed objects which support OSI management interworking. It is informative and not normative. It does not require Formal Definition Techniques (FDTs) to be used to specify MO behaviour. If FDTs are to be used, it does not require Z to be used; other languages such as SDL are also suitable. Even if Z is to be used, other ways of specifying MO behaviour are possible.

Formal specifications of MO behaviour can be directly valuable because they are clear and unambiguous. The act of producing a formal specification forces the details of the behaviour to be analysed closely. Thus, it can also be used as a tool to identify and correct ambiguities which might go undetected in a specification relying solely on natural language. For these reasons formal specification can be useful to improve behaviour specification.

This annex contains an illustrative example that demonstrates current best practice. It aims to establish a common basis and understanding of this particular formal approach which will help achieve consistency in similar developments. It should provide a useful starting point for GDMO users wishing to use Z to improve their behaviour specifications.

It is aimed at an audience familiar with the basic concepts of managed object specification using the GDMO templates, and the Z language.

For the remainder of this annex, the terms "managed object" and "MO" will be used to refer to a managed object class definition given using the GDMO templates.

B.2 Language issues

The Z notation is a formal specification notation based on set theory and predicate calculus. It possesses sufficient expressive power to be able to describe single classes of managed objects.

However, there exists no notion of encapsulation in Z. A Z specification typically consists of a model of some state and a collection of operations to modify the state. There is no method built into Z to parcel the state and its operations up into a single module and re-use it in another specification. The consequence of this becomes apparent when it becomes necessary to describe managed objects which inherit variables and behaviour from other managed object class definitions.

The effect of inheritance can be achieved by the technique of schema inclusion at the expense of some clarity. In all other respects Z is suitable for expressing single classes of managed objects.

B.3 What needs to be translated

The behaviour definitions, or parts there of, need to be translated from the informal description into Z. The extent to which the remaining parts of the GDMO templates need to be formalized depends largely on the needs of the specifier.

The GDMO templates already include a semi-formal definition of data types in ASN.1. It is possible to write a Z specification using these ASN.1 definitions as a basis for types used in the Z specification, and this saves a significant amount of work.

However, if a specification is written in this way, then it makes it a greater task for the specifier to ensure that it is syntactically correct. Without Z specifications of the ASN.1 definitions, it is not possible to use existing Z tools which provide support for checking the syntax and static semantics of a Z specification.

In summary, it is possible to improve the behaviour definitions by using Z without re-writing the ASN.1 data types, but there is a significant benefit to be gained by a full translation of the ASN.1 data types into Z. Examples of how to convert ASN.1 Basic Types into Z are provided in B.7.1.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

B.3.1 From GDMO templates to Z

This subclause contains general guidelines of how to go about translating a managed object from its informal description as given in this Recommendation | International Standard into Z. It should be stressed at the outset that such a translation can only be carried out informally since a formal translation would require, as a minimum, that both the source and target languages be formal.

Moreover, as with any mapping between two distinct languages, there is bound to be some mismatch between their constructs. The problem multiplies when one of the languages happens to be informal or to include informal components.

In this subclause some of the main features of the templates defined in this Recommendation | International Standard are listed together with the ways in which they differ from or correspond to constructs in Z. In the process, general ways of resolving the mismatch or advice on how they may be tackled individually on an ad-hoc basis is offered.

This annex will concentrate on what is necessary to describe the behaviour of a managed object. Additional information on how to convert ASN.1 types is provided in B.6.

B.3.2 Datatypes

The first step is to rewrite the datatypes from this Recommendation | International Standard as Z types. ASN.1 provides the usual facilities of datatyping but its constructors are biased towards the description of datastreams communicated between systems.

In ASN.1, the type constructors are defined as forms of list. In Z, types are sets. Although it is possible to model the ASN.1 type constructors as sequences in Z, it is sometimes more natural to consider the operations available on the ASN.1 types and to map them to Z types which more clearly describe their structure. The ASN.1 sequence and set types can be mapped to Z tuples. The ASN.1 sequence-of type can be mapped to a Z sequence. The ASN.1 set-of type can be mapped to a Z set.

ASN.1 includes special support for encoding, such as type labels and default values. This does not need to be represented in Z since it doesn't affect the behaviour definition.

Subclause B.6.2 provides additional information on how to convert ASN.1 types.

B.3.3 MO Attributes

Managed objects are defined to have certain management attributes. These attributes have a datatype defined in ASN.1. They are assigned object identifiers. They also may have a matches-for property. Two ways to model such attributes have been proposed:

- simple attribute types; and
- attribute types as schemas.

The simplest is to represent the MO attribute within the MO as a Z variable with the appropriate datatype. Then separately we will need a constant definition which represents the object identifier of that attribute. This constant will be related to the actual attribute by convention only. We can use the actual fixed matches-for property when matching operations are defined for that attribute. An example of this is given in B.6.3.

It is also possible to encapsulate all these properties of an attribute in a single schema type which will then be the type of the Z variable modelling the MO attribute. Thus, the schema will include the value of the attribute as well as the object identifier and the matches-for property if any. An example of this is given in B.6.4. Where matching rules other than equality are required, it is possible to define the matches-for parameter as a Z relation over the type of the value of the attribute. This allows the formal representation of arbitrary ad-hoc matching rules, which may be important for scoping, filtering and object selection.

It is difficult to model ASN.1 type ANY in Z. One case where this is common is to give lists of attribute values. Thus, a fully formal model will probably require a Z free type combining the attribute types already defined. An example of this can be found in B.6.1 and B.6.5.

Object identifiers are formally modelled by a given set.

[OBJECTID]

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

B.3.4 Other Object Identifiers

Many things besides attributes also have an Object Identifier. It is convenient to introduce them all as constants in axiomatic definitions. The convention of suffixing them with "Oid" will be used. Typically such constants will be needed for classes, packages and notifications.

An example is:

packagesPackageOid : OBJECTID
allomorphsPackageOid : OBJECTID
topClassOid : OBJECTID

B.3.5 Inheritance and Compatibility

Z can be used to build inheritance hierarchies of MOs by using schema inclusion to model inheritance and specialization. This does correctly model the behaviour of an MO class and its sub-types but it fails to make explicit the strong sub-typing relationship that is really present. For that, a language that models inheritance explicitly is needed.

Thus Z can be used to define individual MOs satisfactorily, but to be able to talk about inheritance and compatibility, the additional power of a language that models inheritance explicitly is needed.

Inheritance is not supported by Z. It can be modelled by simple schema inclusion of state schemas.

The definition of MO inheritance requires sub-classes to be compatible. Unfortunately this does not require the sub-classes to be sub-types in Z. Thus, typically an MO can report its actual class. Since the actual class attribute always reports an object's actual class, a sub-class cannot report the class of a super-class. Therefore a sub-class cannot exhibit the same behaviour as its super-class in returning the value of its actual class attribute (i.e. it is not substitutable), even if it is behaving allomorphically. Therefore managed object class sub-classing is not equivalent to Z sub-types, where a sub-type would exhibit the same behaviour as its super-type. However, a sub-class exhibits very little "unsubstitutable" behaviour.

In this way it can be seen that MO inheritance as defined in this Recommendation | International Standard allows specific behaviour in a parent which is inconsistent with the behaviour of its children. Since there is a very limited amount of this non-substitutable behaviour, an MO class can be represented by two class specifications. One captures the behaviour that any instance and also any extended MO must exhibit. The other is a specialization and captures that behaviour exhibited only by instances of the compatible class and not by any extensions. It is this latter specification that is instantiated to give the complete behaviour of an actual MO instance.

B.3.6 Packages

Many parts of the functionality of a class may be present in some individual MOs and not in others. This Recommendation | International Standard describes this process by grouping functionality into conditional packages. Then, each MO instantiates appropriate packages. In Z functionality cannot be provided in this conditional way but it is possible to make the behaviour of the MO depend on which packages are instantiated. This is straightforward because the MO must contain a management attribute called packages which lists the object identifiers of the packages actually instantiated. Thus, to model behaviour in a conditional package, the behaviour itself becomes conditional on the presence of the package identifier in the packages attribute.

B.3.7 The Class

To define an MO class it is necessary to represent its attributes and its operations. Attributes become part of the Z state schema and operations become Z operation schemas.

B.3.7.1 Attributes

The attributes of the managed object are declared in a state schema. Each attribute is given a type, which may be of a type declared in the ASN.1 part of the GDMO template, or which may use types declared in Z in a fully formal model.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

B.3.7.2 The Get operation

The manager may request a Get operation to be performed on an MO. The CMISE definition of M-Get has many parameters but most of these are concerned with access control and object selection and so on. In this instance Get may be modelled at the Managed Object Boundary ignoring these issues and replacing the single Get operation by a number of Get<name> operations, where <name> is a single attribute.

B.3.7.3 The GetAll operation

A GetAll operation, which has no input, is also modelled. It returns a non-empty set of Attribute Values.

B.3.7.4 Replace operations

Set on an individual MO is requested by the CMISE M-Set operation. This specification models the Replace Operations as seen at the MO Boundary instead. In this specification, Replace Operations refers to the attribute operations set, set to default, add and remove.

The consequence of this is that a Z schema to represent each modification is specified.

B.3.7.5 Notifications

Notifications are unrequested messages sent by the MO to report events within it. However they are not modelled as operations. Instead they are modelled as outputs from operations that happen on the MO. Thus, any operation (whether invoked by the manager or internally by the resource) can generate output and if it causes a notification that notification should be part of that operation's output.

This means that the output of a Z operation schema that can cause notifications should be a *set* of notifications. Then those occasions on which it does not emit a notification can be represented by giving an empty set as output.

The data in a notification consists of an EventType which is the object identifier of its standard definition. This is followed by various information relevant to that particular notification. The object identifier can typically be defined as a constant and the particular data as a schema-type. The behaviour of the notification is included in any object which can generate the notification.

B.3.7.6 Actions

Actions are operations performed by the manager on the MO. They are very naturally represented by Z operations.

B.3.8 Specification of the system of objects

The rest of the annex describes how to represent the behaviour of a single object. When considering object creation/deletion, name bindings, containment and naming, it is necessary to describe the state of the system where the objects reside. Object creation and deletion can be represented by a change of state of this system. Name binding and containment can be represented by a relation over the set of objects. Naming can then be defined in terms of this relation.

B.4 An example

In this subclause, example definitions for the MO class top and State Management attributes are given. Since the main concern of this guide is the modelling of behaviour, the creation of Z types from ASN.1 types is not presented in this subclause. A full formal definition is given in B.7.

B.4.1 top

The first class to be defined is *top*, which is the ultimate parent (in the inheritance hierarchy) of all MOs.

top has four management attributes, *objectClass, packages, allomorphs* and *nameBinding. objectClass* holds the object identifier of the class, while *packages* holds the object identifiers of the packages it instantiates. *nameBinding* holds the object identifier of the name binding used to instantiate the object and *allomorphs* holds the object identifiers of the classes to which the object can be allomorphic. Since management attributes can be in packages, the attributes present in MOs of a given class can vary. This is modelled by including an additional modelling attribute called *attributes*, which holds the object identifiers of the attributes that are actually instantiated in the individual MO. Note that all the attributes present in *top* are fixed for the lifetime of any individual MO.

Z does not explicitly model interfaces, and so it is not possible to formally define which operations are invoked internally or externally by the manager.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

TopState

allomorphs: $\mathbb{F}$ *OBJECTID*
objectClass: OBJECTID
nameBinding: OBJECTID
packages: $\mathbb{F}$ *OBJECTID*
attributes: $\mathbb{F}$ *OBJECTID*

$\{objectClassOid, nameBindingOid\} \subseteq attributes$
$allomorphsPackageOid \in packages \Rightarrow allomorphsOid \in attributes$
$packagesPackageOid \notin packages$
$packages \neq \varnothing \Rightarrow packagesOid \in attributes$

attributes is not an MO attribute but a new state component defined for convenience. It lists the MO attributes an MO includes. Thus, the invariant enforces that it must contain the object identifiers of the appropriate attributes as described in B.3.3 (and defined in B.7.4). *objectClass* and *nameBinding* are mandatory. *packages* is present if any registered package is instantiated apart from *packagesPackage*. In this case this means *allomorphsPackage*.

The operation *TopGetNameBinding* interrogates the MO and returns the value of the *nameBinding* attribute, without changing *TopState*. *TopGetNameBinding* is invoked by the manager.

TopGetNameBinding

Ξ *TopState*
result!: OBJECTID

---

result! = nameBinding

The operations *TopGetAllomorphs*, *TopGetObjectClass* and *TopGetPackages* have not been defined here. Note that there is no operation to get *attributes*, since *attributes* is not a real MO attribute as specified in the GDMO template.

TopGetAll gets all the attribute values of an object. It always returns values for *objectClass* and *nameBinding*. If conditional packages or allomorphs are present, then it gets those too. *TopGetAll* is invoked by the manager.

TopGetAll

Ξ *TopState*
result!: $\mathbb{P}$ *AttributeValues*

 # attributes = # result!
ObjectClassValue objectClass $\in$ *result!*
NameBindingValue nameBinding $\in$ *result!*
PackagesOid $\in$ *attributes* $\Rightarrow$ *packagesValue packages* $\in$ *result!*
AllomorphsOid $\in$ *attributes* $\Rightarrow$ *allomorphsValue allomorphs* $\in$ *result!*

TopEventReport is a way to model notifications. *TopEventReport* occurs spontaneously and represents the way event reports are not controlled by the manager.

TopEventReport

Ξ *TopState*
notification!: EventInfo

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

B.4.2 StateManagement class

This class does not reflect any specific MO class. Instead it reflects the behaviour of any object which includes any of certain standard attributes: *administrativeState*, *operationalState*, and *usageState*. It is more convenient within this framework to understand this inclusion as inheritance and it does serve as a useful example.

The state schema includes the *TopState* definitions and predicates, and defines some additional variables and predicate conjunctions.

StateManagementState

TopState
administrativeState:
AdministrativeState
operationalState: OperationalState
usageState: UsageState

$operationalState = disabled \Rightarrow usageState = idle$
$administrativeState = locked \Rightarrow usageState = idle$
$usageState = idle \Rightarrow administrativeState \neq shuttingDown$

State Management inherits the operations from Top. Although there is no mechanism built into Z to inherit operations, it is straightforward to redefine the operations in terms of the new state. The predicate part of *StateManagementState* follows from the definition of the State Management function in CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992 and CCITT Rec. X.731 (1992) | ISO/IEC 10164-2:1992.

The operation *SMGetNameBinding* can be easily defined, since it has no effect upon the new state variables declared in *StateManagementState*. The definition of *TopGetNameBinding* can be re-used:

SMGetNameBinding

TopGetNameBinding
Ξ *StateManagementState*

Definitions for operations to get the other attributes of *StateManagementState* have also been omitted from this example. The operations *SMGetAllomorphs*, *SMGetObjectClass* and *SMGetPackages* can re-use the definitions from Top as for *SMGetNameBinding*. New operations will need to be defined for *GetSMAdministrativeState*, *GetSMOperationalState* and *SMGetUsageState*. *SMEventReport* may also be re-used.

The *SMGetAll* schema also makes use of an operation defined on *TopState*. It includes the definition of *TopGetAll* and strengthens the postcondition.

SMGetAll

Ξ *StateManagementState*
TopGetAll

$administrativeStateOid \in attributes$
$\quad \Rightarrow administrativeStateValue\ administrativeState \in result!$
$OperationalStateOid \in attributes$
$\quad \Rightarrow operationalStateValue\ operationalState \in result!$
$UsageStateOid \in attributes$
$\quad \Rightarrow usageStateValue\ usageState \in result!$

The *SMReplaceAdministrativeState* operation describes behaviour specific to the State Management class whereby the administrative state is replaced by another value supplied as an input. Depending on the state of the object when the operation is carried out, the usage state may also be changed. The operational state is not altered by the operation.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

SMReplaceAdministrativeState

$$
\begin{array}{|l}
\Delta StateManagementState \\
\Xi TopState \\
input?: AdministrativeState \\
\hline
administrativeState' \in \\
\quad \textbf{IF}\ usageState \neq idle \\
\quad \textbf{THEN}\ \{\ unlocked \mapsto unlocked, locked \mapsto locked, \\
\qquad shuttingDown \mapsto locked, locked \mapsto shuttingDown, \\
\qquad shuttingDown \mapsto shuttingDown\}\ (\!|\{\ input?\}\ |\!) \\
\quad \textbf{ELSE}\ \{unlocked \mapsto unlocked,\ \ locked \mapsto locked, \\
\qquad shuttingDown \mapsto locked\}\ (\!|\{\ input?\}\ |\!) \\
administrativeState' = locked \Rightarrow usageState' = idle \\
administrativeState' \neq locked \Rightarrow usageState' = usageState \\
operationalState' = operationalState
\end{array}
$$

The behaviour specified in the predicate part of the schema is a formalization of the informal description in CCITT Rec. X.731 | ISO/IEC 10164-2. For completeness, operations to replace the operational state and the usage state should also be defined.

Finally there are a number of other operations which describe behaviour specific to the State Management class. These operations are not listed here, although they may be found in B.7. These operations include *SMCapacityDecrease*, *SMCapacityIncrease*, *SMDisable*, *SMEnable*, *SMNewUser* and *SMUserQuit*.

B.4.3 Instantiable classes

Neither of the classes described above can be instantiated. The procedure that has been followed can be continued. *StateManagement* can be re-used to define a class called *CIRCUIT*, which in turn can be used to define *ECIRCUIT* and hence the instantiable class *ActualECircuit*.

This has been omitted from the guide, since the procedures are exactly the same as those that have outlined and repetition adds nothing.

B.5 Outstanding Issues

In this subclause, the main issues encountered in the course of the translation from GDMO-based managed objects specifications to Z are listed. Where an issue relates to Z not having a corresponding construct for a particular feature of managed objects specification, the proposed informal treatment used in this annex will also be included.

B.5.1 Behaviour Definition in Managed Objects

In the templates, the term 'behaviour definition' is used for almost all entities whether they are data or processes. In the latter case, it may include information about the actual behaviour (in the strict sense), or just static information about the entity such as its intended use, or both. When translating, one needs to analyse the text which comes under this heading, and extract the relevant behavioural information for the entity concerned. This behavioural information will be used in the formal translation, while the actual text may be included as a comment inside the Z specification.

B.5.2 Internal operations in Z

An internal operation in a managed object represents the case where a notification is emitted spontaneously (with no management invocation involved). Internal operations are also a desired feature of many other systems. Currently, in Z, this feature is represented informally by a comment in the natural language text which is an important feature of any well-written Z specification.

B.5.3 Abstract classes in Z

Sometimes it is useful to identify abstract classes: i.e. classes with no instantiations of their own. Some MO classes (like *top*) cannot be instantiated. It would be helpful to be able to show which parts of the corresponding Z specifications represent classes that can be instantiated. This is taken care of by informal annotation at present.

B.5.4 PARAMETER semantics

The incorporation of PARAMETER semantics into objects is not considered in this Recommendation | International Standard.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

B.6 Converting ASN.1 Datatypes to Z

Issues for translation will be described for each ASN.1 constructor in turn.

B.6.1 Simple types

ASN.1 includes some simple types which are built-in. These do have a standardized structure but it is usually not interesting in the context of these specifications and so they can mostly be represented as given sets. There are a wide variety of character string types:

[NUMERICSTRING, PRINTABLESTRING, TELETEXSTRING,
VIDEOTEXSTRING,VISIBLESTRING, IA5STRING,
GRAPHICSTRING, GENERALSTRING]

Two of these have synonyms:

T61STRING == TELETEXSTRING
ISO64STRING == VISIBLESTRING

Of the other simple types, Integer can be represented by $\mathbb{Z}$, Boolean and Null by free types:
Boolean ::= btrue | bfalse
Null ::= null

Note that these free types also define the value notation for these types.

Real, Bit String, and Octet String, can usually be taken to be given sets (though it may sometimes be necessary to structure the Bit and Octet String types).

[REAL,BITSTRING,OCTETSTRING]

This Recommendation | International Standard also describes another special type which will be provided as a given set.

[OBJECTID]

Here *OBJECTID* represents an ASN.1 Object Identifier.

Object Identifiers are in fact non-empty sequences of $\mathbb{N}$ and it may be convenient to model them as such, instead of as a given set. In this case some thought must be given to an appropriate value notation.

There are also some "useful" types which are defined in ASN.1 within the ASN.1 standard. Thus, although they could be defined in terms of the other ASN.1 constructs, it is again convenient to provide them as given sets.

[GENERALIZEDTIME, UTCTIME, OBJECTDESCRIPTOR, EXTERNAL]

Any

ASN.1 allows a special type ANY which can contain any other ASN.1 type at all. Such a type is not allowed within Z and it would be difficult to extend it to include one. However given any known set of types, it is possible to define a Z free type which can include any of those other types. An alternative strategy is to define ANY as a given set for typechecking purposes. This is satisfactory as long as nothing else is done with it. The type *AttributeValues* usually replaces *ANY*. This is defined below.

B.6.2 Structured types

Other types in ASN.1 are built up by constructors.

Set

ASN.1 Sets can be represented as either tuples or schemas in Z. Z tuples do not allow components to be named and so schemas may be more appropriate. However the Z value notation for schemas is less convenient. Tagging is neither needed nor possible in Z since the components of the "set" can always be discriminated either by their position in a tuple or their component name in a schema.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Components in this and other structured types can be *OPTIONAL*. This can be represented in Z by augmenting the type of the optional component with a special "absent" value. *DEFAULT* values cannot be conveniently represented as a feature of a datatype. It is possible to represent behaviour implied by the default within any operations on that data.

Sequence

ASN.1 Sequences can be modelled in exactly the same way as ASN.1 Sets since the only difference is that there is an explicit order. Because this is the case, it could be argued that a tuple is more appropriate but schemas can also be used.

Set-of

ASN.1 Set-of types are actually bags and can be defined in Z as such. It should be noted that the MIM explicitly requires all such bags to be treated as sets and so it is in fact more appropriate to model the type as a Z set.

When subtyping of an ASN.1 type is required, it is usually necessary to add a predicate constraint to the type. In some cases, for example integer or schema sub-types, this can be done in the type definition itself. Otherwise (for example bag sub-types) the constraint must be applied to variables defined to be of that type.

Sequence-of

ASN.1 Sequence-of types can be conveniently modelled as Z sequences.

Choice

ASN.1 Choice types are straightforward enumerations and can be modelled by Z free types.

This type introduces a serious scoping problem. Within ASN.1 the constructors within a Choice are local to that type. Thus, a single constructor name can be used in more than one enumeration. In Z these names are global and cannot be re-used. This problem must usually be resolved by changing the names of the constructors, typically by prefixing them with the name of their type.

A similar problem arises when ASN.1 Types are generated that are synonyms for Integer (say) but with named values. These named values are local to the synonym type in ASN.1 but global synonyms for integers in Z. Again this must be fixed by changing the names of the constructors.

B.6.3 Simple attribute types

The simplest is to represent the MO attribute within the MO as a Z variable with the appropriate datatype. A constant definition which represents the *OBJECTID* of that attribute will be needed. When matching operations are defined for that attribute, the actual standardized value of the matches-for parameter can be used.

Thus consider the MO attribute administrativeState. We will have defined a type:

AdministrativeState ::= unlocked | locked | shuttingDown

A constant to represent the attribute's Object Identifier can be defined:

administrativeStateOid : OBJECTID

The actual value of the identifier can be presented a constraint on that axiomatic definition.

Then within the MO a state variable will be defined:

MOState

administrativeState: AdministrativeState

This solution is straightforward and convenient but does require lists of *OBJECTID* axiomatic definitions. It also makes the link between the name of the attribute and its *OBJECTID* purely syntactic. The convention of suffixing with *Oid* has been adopted.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

B.6.4 Attribute types as schemas

It is also possible to encapsulate these features of an attribute in a single schema type which will be the type of the Z variable modelling the MO attribute:

AdministrativeStateType

$$\begin{array}{|l} value : AdministrativeState \\ Oid : OBJECTID \\ \hline Oid = \langle 4, 3, 19, 27, 1, 3 \rangle \end{array}$$

It is important to provide a value for the *OBJECTID* here since it is necessary to imply that it cannot be changed even though the value can.

A structure for *OBJECTID* has not been defined, but writing:

$$OBJECTID == seq_1\ \mathbb{N}$$

is one possibility that would make the previous schema make sense. This schema could also hold the matches-for parameter if it was thought important to represent this within the specification.

Then the MO would contain an attribute with this type:

MOState

$$\begin{array}{|l} administrativeState : AdministrativeStateType \end{array}$$

Reference to its value or its Oid would be made via component selection as in *administrativeState.value*.

This technique conveniently gives semantics to the connection between an attribute and its *OBJECTID*. However, it may seem strange to specification readers that the Oid is present in the MO state even though it cannot change (and is in fact a global constant known at specification time).

B.6.5 AttributeValues type

As mentioned above, it is difficult to model ASN.1 type ANY in Z. One case where this is common is to give lists of attribute values. A Z free type definition combining the attribute types already defined will be required. This approach works as long as the set of attributes in use is fixed at specification time. Then, typically, it will look something like:

$$\begin{aligned} &AttributeValues ::= administrativeStateValue \langle\langle AdministrativeState \rangle\rangle \mid \\ &\quad objectClassValue \langle\langle OBJECTID \rangle\rangle \mid \\ &\quad nameBindingValue \langle\langle OBJECTID \rangle\rangle \mid \\ &\quad packagesValue \langle\langle \mathbb{P}\, OBJECTID \rangle\rangle \mid \\ &\quad allomorphsValue \langle\langle \mathbb{P}\, OBJECTID \rangle\rangle \mid \\ &\quad operationalStateValue \langle\langle OperationalState \rangle\rangle \mid \\ &\quad usageStateValue \langle\langle UsageState \rangle\rangle \end{aligned}$$

B.7 A full example

This subclause presents the full formal model on which the example in B.4 is based. It is presented in the traditional Z style of declaration before use: that is, the type definitions converted from ASN.1 appear at the start and the behaviour definitions appear at the end.

One point of specification style is worth commenting on. The definitions *AttributeValues* and *OBJECTINSTANCE* are mutually recursive. This is technically illegal in Z, and so the following has been done to permit the definition. *AttributeValues* has been introduced as a given set. *OBJECTINSTANCE* is then defined using the given set *AttributeValues*. This definition of *OBJECTINSTANCE* is then used to introduce the restrictions that *AttributeValues* is allowed to take. The proof obligation to show that such sets actually exist has been discharged, but is not presented.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

B.7.1 ASN.1 basic types

[NUMERICSTRING, PRINTABLESTRING, TELETEXSTRING, VIDEOTEXSTRING]
[VISIBLESTRING, IA5STRING, GRAPHICSTRING, GENERALSTRING]

T61STRING == TELETEXSTRING

ISO64STRING == VISIBLESTRING

Boolean ::= btrue | bfalse

Null ::= null

[REAL,BITSTRING,OCTETSTRING]

[OBJECTID]

[ANY]

[GENERALIZEDTIME,UTCTIME,OBJECTDESCRIPTOR,EXTERNAL]

B.7.2 MO Attributes

The following given set is a placeholder for a more complex and complete free type definition given incrementally as each new class is defined.

[AttributeValues]

AttributeValuesOptional ::= present ((AttributeValues)) | absent

RelativeDistinguishedName == AttributeValues

RDNSequence == seq RelativeDistinguishedName

DistinguishedName == RDNSequence

OBJECTINSTANCE ::= distinguishedName((DistinguishedName)) | nonSpecificForm((N))
| localDistinguishedName((RDNSequence))

B.7.3 Notifications

ProbableCause == OBJECTID

SpecificIdentifier ::= globalvalue((OBJECTID)) | localValue((N))

SpecificProblems == PSpecificIdentifier

SpecificProblemsOptional ::= sPPresent((SpecificProblems)) | sPAbsent

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

PerceivedSeverity ::= indeterminate | critical | major | minor | warning | cleared

BackedUpStatus == Boolean

BackedUpStatusOptional ::= bUSPresent《BackedUpStatus》| bUSAbsent

ObjectInstanceOptional ::= oIPresent《OBJECTINSTANCE》| oIAbsent

TrendIndication ::= lessSevere | noChange | moreSevere

TrendIndicationOptional ::= tIPresent《TrendIndication》| tIAbsent

ObservedValue ::= int《ℕ》| real《REAL》

ObservedValueOptional ::= oVPresent《ObservedValue》| oVAbsent

ThresholdLevelInd ::=
up《ObservedValue ×ObservedValueOptional》
| down《ObservedValue × ObservedValueOptional》

ThresholdLevelIndOptional ::= tLIPresent《ThresholdLevelInd》| tLIAbsent

ArmTimeOptional ::= aTPresent《GENERALIZEDTIME》| aTAbsent

ThresholdInfo ==
OBJECTID × ObservedValue × ThresholdLevelIndOptional × ArmTimeOptional

ThresholdInfoOptional ::= thIPresent《ThresholdInfo》| thIAbsent

NotificationIdentifier == ℕ

NotificationIdentifierOptional ::= nIPresent《NotificationIdentifier》| nIAbsent

CorrelatedNotifications == ℙ((ℙNotificationIdentifier) × ObjectInstanceOptional)

CorrelatedNotificationsOptional ::= cNPresent《CorrelatedNotifications》| cNAbsent

AttributeValueChangeDefinition == ℙ(OBJECTID × AttributeValuesOptional × AttributeValues)

AttributeValueChangeDefinitionOptional ::=
aVCDPresent《AttributeValueChangeDefinition》| aVCDAbsent

MonitoredAttributes == ℙOBJECTID

MonitoredAttributesOptional ::= mAPresent《MonitoredAttributes》| mAAbsent

ProposedRepairActions == ℙSpecificIdentifier

ProposedRepairActionsOptional ::= pRAPresent《ProposedRepairActions》| pRAAbsent

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

AdditionalTextOptional ::= adTPresent ⟪GRAPHICSTRING⟫ | aDTAbsent

ManagementExtension == OBJECTID × Boolean × ANY

AdditionalInformation == ℙ ManagementExtension

AdditionalInformationOptional ::= aIPresent ⟪AdditionalInformation ⟫ | aIAbsent

SourceIndicator ::= resourceOperation | managementOperation | sIUnknown

SourceIndicatorOptional ::= sIPresen ⟪SourceIndicator ⟫ | sIAbsent

AttributeIdentifierList == ℙ OBJECTID

AttributeIdentifierListOptional ::= atIPresent ⟪AttributeIdentifierList ⟫ | atIAbsent

Attribute == OBJECTID × AttributeValues

AttributeList == ℙ Attribute

AttributeListOptional ::= aLPresent ⟪AttributeList ⟫ | aLAbsent

AlarmInfo

probableCause: ProbableCause
specificProblems: SpecificProblemsOptional
perceivedSeverity: PerceivedSeverity
backedUpStatus: BackedUpStatusOptional
backUpObject: ObjectInstanceOptional
trendIndication: TrendIndicationOptional
thresholdInfo: ThresholdInfoOptional
notificationIdentifier: NotificationIdentifierOptional
correlatedNotifications: CorrelatedNotificationsOptional
stateChangeDefinition: AttributeValueChangeDefinitionOptional
monitoredAttributes: MonitoredAttributesOptional
proposedRepairActions: ProposedRepairActionsOptional
additionalText: AdditionalTextOptional
additionalInformation: AdditionalInformationOptional

AttributeValueChangeInfo

sourceIndicator: SourceIndicatorOptional
attributeIdentifierList: AttributeIdentifierListOptional
attributeValueChangeDefinition: AttributeValueChangeDefinitionOptional
notificationIdentifier: NotificationIdentifierOptional
correlatedNotifications: CorrelatedNotificationsOptional
additionalText: AdditionalTextOptional
additionalInformation: AdditionalInformationOptional

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

ObjectInfo

sourceIndicator: SourceIndicatorOptional
attributeList: AttributeListOptional
notificationIdentifier: NotificationIdentifierOptional
correlatedNotifications: CorrelatedNotificationsOptional
additionalText: AdditionalTextOptional
additionalInformation: AdditionalInformationOptional

RelationshipChangeInfo

sourceIndicator: SourceIndicatorOptional
attributeIdentifierList: AttributeIdentifierListOptional
relationshipChangeDefinition: AttributeValueChangeDefinitionOptional
notificationIdentifier: NotificationIdentifierOptional
correlatedNotifications: CorrelatedNotificationsOptional
additionalText: AdditionalTextOptional
additionalInformation: AdditionalInformationOptional

SecurityAlarmInfo

notificationIdentifier: NotificationIdentifierOptional
correlatedNotifications: CorrelatedNotificationsOptional
additionalText: AdditionalTextOptional
additionalInformation: AdditionalInformationOptional

StateChangeInfo

sourceIndicator: SourceIndicatorOptional
attributeIdentifierList: AttributeIdentifierListOptional
stateChangeDefinition: AttributeValueChangeDefinitionOptional
notificationIdentifier: NotificationIdentifierOptional
correlatedNotifications: CorrelatedNotificationsOptional
additionalText: AdditionalTextOptional
additionalInformation: AdditionalInformationOptional

EventInfo ::= attributeValueChange «AttributeValueChangeInfo»
| *communicationsAlarm «AlarmInfo»*
| *environmentalAlarm «AlarmInfo»*
| *equipmentAlarm «AlarmInfo»*
| *integrityViolation «SecurityAlarmInfo»*
| *objectCreation «ObjectInfo»*
| *objectDeletion «ObjectInfo»*
| *operationalViolation «SecurityAlarmInfo»*
| *physicalViolation «SecurityAlarmInfo»*
| *processingError «AlarmInfo»*
| *qualityOfServiceAlarm «AlarmInfo»*

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

| *relationshipChange ⟪RelationshipChangeInfo⟫*
| *securityServiceOrMechanismViolation ⟪SecurityAlarmInfo⟫*
| *stateChange ⟪StateChangeInfo⟫*
| *timeDomainViolation ⟪SecurityAlarmInfo⟫*

B.7.4 "CCITT Rec. X.721 (1992)" | ISO/IEC 10165-2:1992:Top

allomorphsOid: OBJECTID
nameBindingOid: OBJECTID
objectClassOid: OBJECTID
packagesOid: OBJECTID

---

allomorphsValue : (F OBJECTID) ⤖ AttributeValues
nameBindingValue : OBJECTID ⤖ AttributeValues
objectClassValue : OBJECTID ⤖ AttributeValues
packagesValue : (F OBJECTID) ⤖ AttributeValues

---

disjoint ⟨**ran** allomorphsValue, **ran** nameBindingValue,
ran objectClassValue, **ran** packagesValue ⟩

packagesPackageOid: OBJECTID
allomorphsPackageOid: OBJECTID

TopState

allomorphs: F OBJECTID
objectClass: OBJECTID
nameBinding: OBJECTID
packages: F OBJECTID
attributes: F OBJECTID

{ objectClassOid, nameBindingOid} ⊆ attributes
allomorphsPackageOid ∈ packages ⇒ allomorphsOid ∈ attributes
packagesPackageOid ∉ packages
packages ≠ ∅ ⇒ packagesOid ∈ attributes

TopGetNameBinding

Ξ TopState
result!: OBJECTID

---

result! = nameBinding

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

TopGetAll

ΞTopState
result!: ℙ AttributeValues

 # attributes = # result!
ObjectClassValue objectClass ∈ result!
NameBindingValue nameBinding ∈ result!
PackagesOid ∈ attributes ⇒ packagesValue packages ∈ result!
AllomorphsOid ∈ attributes ⇒ allomorphsValue allomorphs ∈ result!

TopEventReport

ΞTopState
notification!: EventInfo

B.7.5 StateManagement Class

administrativeStateOid: OBJECTID
operationalStateOid: OBJECTID
usageStateOid: OBJECTID

AdministrativeState ::= unlocked | locked | shuttingDown

OperationalState ::= enabled | disabled

UsageState ::= idle | active | busy

administrativeStateValue: AdministrativeState ⤖ AttributeValues
operationalStateValue: OperationalState ⤖ AttributeValues
usageStateValue: UsageState ⤖ AttributeValues

---

disjoint ⟨***ran*** *allomorphsValue,* ***ran*** *nameBindingValue,* ***ran*** *objectClassValue,*
ran *packagesValue,* ***ran*** *administrativeStateValue,*
ran *operationalStateValue,* ***ran*** *usageStateValue* ⟩

StateManagementState

TopState
administrativeState:
AdministrativeState
operationalState: OperationalState
usageState: UsageState

---

operationalState = disabled ⇒ usageState = idle
administrativeState = locked ⇒ usageState = idle
usageState = idle ⇒ administrativeState ≠ shuttingDown

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

SMGetNameBinding

TopGetNameBinding
ΞStateManagementState

SMEventReport

TopEventReport
ΞStateManagementState

SMGetAll

ΞStateManagementState
TopGetAll

administrativeStateOid ∈ attributes
⇒ administrativeStateValue administrativeState ∈ result!
OperationalStateOid ∈ attributes ⇒ operationalStateValue operationalState ∈ result!
UsageStateOid ∈ attributes ⇒ usageStateValue usageState ∈ result!

SMCapacityDecrease

ΔStateManagementState
ΞTopState

usageState = active ⇒ usageState' ∈ {active, busy}
usageState ≠ active ⇒ usageState' = usageState
administrativeState' = administrativeState
operationalState' = operationalState

SMCapacityIncrease

ΔStateManagementState
ΞTopState

usageState = busy ⇒ usageState' = active
usageState ≠ busy ⇒ usageState' = usageState
administrativeState' = administrativeState
operationalState' = operationalState

SMDisable

ΔStateManagementState
ΞTopState

administrativeState' =
IF administrativeState = shuttingDown
THEN locked
ELSE administrativeState
operationalState' = disabled
usageState' = idle

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

SMEnable

ΔStateManagementState
ΞTopState

operationalState = disabled
operationalState' = enabled
administrativeState' = administrativeState
usageState' = usageState

SMNewUser

ΔStateManagementState
ΞTopState

operationalState = enabled
administrativeState = unlocked
usageState ∈ { idle, active}
usageState' ∈ {active, busy}
administrativeState' = administrativeState
operationalState' = operationalState

SMUserQuit

ΔStateManagementState
ΞTopState

administrativeState = shuttingDown ∧ usageState' = idle
⇒ administrativeState' = locked
administrativeState ≠ shuttingDown ∨ usageState' ≠ idle
⇒ administrativeState' = administrativeState
usageState ∈ { active, busy}
usageState' ∈ {idle, active}
operationalState' = operationalState

SMReplaceAdministrativeState

ΔStateManagementState
ΞTopState

administrativeState' ∈
IF *usageState ≠ idle*
THEN *{ unlocked ↦ unlocked,locked ↦ locked,*
shuttingDown ↦ locked,locked ↦ shuttingDown,
shuttingDown ↦ shuttingDown}⨀{ input?} ⨀
ELSE *{ unlocked ↦ unlocked, locked ↦ locked,*
shuttingDown ↦ locked}⨀{ input?} ⨀
administrativeState' = locked ⇒ usageState' = idle
administrativeState' ≠ locked ⇒ usageState' = usageState
operationalState' = operationalState

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

© ISO/IEC

ICS 35.100.70

Price based on 19 pages

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

INTERNATIONAL STANDARD

ISO/IEC 10165-4

First edition
1992-09-01

AMENDMENT 2
1998-12-15

Information technology — Open Systems Interconnection — Structure of management information: Guidelines for the definition of managed objects

AMENDMENT 2: Addition of the NO-MODIFY syntax element and guideline extensions

Technologies de l'information — Interconnexion de systèmes ouverts — Structures des informations de gestion: Principes directeurs pour la définition des objets gérés

AMENDEMENT 2: Addition de l'élément de syntaxe «NO-MODIFY» et des extensions de principe directeur

This material is reproduced from ISO documents under International Organization for Standardization (ISO) Copyright License Number IHS/ICC/1996. Not for resale. No part of these ISO documents may be reproduced in any form, electronic retrieval system or otherwise, except as allowed in the copyright law of the country of use, or with the prior written consent of ISO (Case postale 56, 1211 Geneva 20, Switzerland, Fax +41 22 734 10 79), IHS or the ISO Licensor's members.

Reference number
ISO/IEC 10165-4:1992/Amd.2:1998(E)

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

Contents

		Page
1)	Subclause 2.1	1
2)	Subclause 8.2	1
3)	Subclause 8.4.2	1
4)	Subclause 8.4.3.2	1
5)	Index	2
6)	New clause 9	2
7)	New clause 10	7

© ISO/IEC 1998

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Amendment 2 to ISO/IEC 10165-4:1992 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 33, *Distributed application services*, in collaboration with ITU-T. The identical text is published as ITU-T Rec. X.722/Amd.2.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Introduction

This Amendment adds the NO-MODIFY syntax element to the attribute properties of the package template in order to clearly specify that an attribute cannot be modified in subclasses and compatible classes of the managed object class.

This Amendment proposes that the **use of ASN.1:1994 should not be forbidden** (i.e. normative specification of ASN.1:1994 may be employed) in new and developing OSI Systems Management standards for the following reasons:

- ASN.1:1990 bugs/defects;
- ASN.1:1994 enhancements.

ASN.1:1990 and ASN.1:1994 modules can be mixed and are completely compatible using the guidelines in A.2 of Rec. ITU-T X.680 | ISO/IEC 8824-1, ASN.1 Specification of Basic Notation. This "mixed mode" use of ASN.1 places certain restrictions on allowed productions of both ASN.1:1990 and ASN.1:1994. If these guidelines are maintained, not only are ASN.1:1990 and ASN.1:1994 completely compatible, they are virtually indistinguishable and have identical encoding. Using these guidelines, new and developing OSI Systems Management standards may use both ASN.1:1990 and ASN.1:1994 for normative specification of syntax.

This Amendment introduces conventions for the specification of ASN.1 and GDMO directives in order to clearly identify specification and user options associated with ASN.1 modules and GDMO templates.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

INTERNATIONAL STANDARD

ITU-T RECOMMENDATION

INFORMATION TECHNOLOGY - OPEN SYSTEMS INTERCONNECTION - STRUCTURE OF MANAGEMENT INFORMATION: GUIDELINES FOR THE DEFINITION OF MANAGED OBJECTS

AMENDMENT 2
Addition of the NO-MODIFY syntax element and guideline extensions

1) Subclause 2.1

Insert the following references by numerical order:

- ITU-T Recommendation X.680 (1994) | ISO/IEC 8824-1:1995, *Information technology – Abstract Syntax Notation One (ASN.1): Specification of basic notation.*
- ITU-T Recommendation X.681 (1994) | ISO/IEC 8824-2:1995, *Information technology – Abstract Syntax Notation One (ASN.1): Information object specification.*
- ITU-T Recommendation X.682 (1994) | ISO/IEC 8824-3:1995, *Information technology – Abstract Syntax Notation One (ASN.1): Constraint specification.*
- ITU-T Recommendation X.683 (1994) | ISO/IEC 8824-4:1995, *Information technology – Abstract Syntax Notation One (ASN.1): Parameterization of ASN.1 specifications.*
- ITU-T Recommendation X.690 (1994) | ISO/IEC 8825-1:1995, *Information technology – ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER).*
- ITU-T Recommendation X.691 (1995) | ISO/IEC 8825-2:1995, *Information technology – ASN.1 encoding rules: Specification of Packed Encoding Rules (PER).*

2) Subclause 8.2

Add the following to the end of item m):

(Guidelines for the Production of Equivalent ASN.1:1990 and ASN.1:1994 Modules are given in clause 9.)

3) Subclause 8.4.2

Add the following to this subclause, following the `[SET-BY-CREATE]` *property in the* `propertylist`. *(The* `[SET-BY-CREATE]` *property was added in by Amendment 1):*

```
[NO-MODIFY]
```

4) Subclause 8.4.3.2

Add the following two new paragraphs before the last paragraph:

The absence of the `REPLACE` property may be used to specify that an attribute cannot be replaced for instances of a class but this absence does not preclude subclasses adding the `REPLACE` property. The `NO-MODIFY` property is present to explicitly specify that an attribute cannot be modified (is read-only) in the class having this property and in all

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

subclasses and in all compatible managed objects (i.e. managed objects behaving allomorphically to the class). This property is inconsistent with and shall not be present in a managed object class definition that has any of the REPLACE, GET-REPLACE, ADD, REMOVE, or ADD-REMOVE properties on the same attribute.

NOTE 3 – The NO-MODIFY property is not necessarily inconsistent with the REPLACE-WITH-DEFAULT property because this operation is often used with a meaning of "reset" that can be consistent with a manager's inability to control the attribute's value.

NOTE 4 – Before the NO-MODIFY property was added to GDMO, the convention was to specify that property in BEHAVIOUR templates or in documents referenced in BEHAVIOUR templates.

If it is desired that part of the definition of an attribute is that the attribute shall not be replaced in any class that specifies the attribute, then this constraint shall be specified in a BEHAVIOUR template referenced by the ATTRIBUTE template.

5) Index

Add new index entry:

NO-MODIFY 26-27

Change these index entries:

BEHAVIOUR 25-26, 30-32, 34-35, 37-40

REPLACE 14, 26-27

6) New clause 9

Add a new clause 9, following 8.11.3.5:

9 Guidelines for production of equivalent ASN.1:1994 and ASN.1:1990 modules

It is possible in developing standards, that normative ASN.1:1994 modules be provided. In order to allow the use of ASN.1:1994, it is recommended that an equivalent normative ASN.1:1990 module be provided subject to the following:

1) it has the same object identifier as the ASN.1:1994 module;
2) it is normative but the standard states that in the event of discrepancies between the ASN.1:1990 and ASN.1:1994 modules, the ASN.1:1994 module take precedence;
3) the standard states that use of ASN.1:1990 will be retained as long as needed.

NOTE 1 – ISO/IEC JTC 1/SC 21 rules dictate a periodic review for renewal of the ASN.1:1990 International Standards every one (1) year[1]. National Bodies are asked to consider the above when reviewing the ASN.1:1990 standards. This ensures that the ASN.1:1990 standards are retained as long as needed.

Also to reduce errors, it is recommended that the ASN.1:1990 module be a machine generated transformation of the ASN.1:1994 module since this transformation can be easily automated.

NOTE 2 – If an editor desires to use a commercial tool (e.g. made available to the standards community at virtually no cost, vendor XXX's ASN.1 Tools) for converting ASN.1:1994 to ASN.1:1990 to reduce the possibility of errors, it has been suggested that the editor should add a comment at the top of the generated code that says something like:

-- XXX ASN.1 Tools used for conversion --
-- from ASN.1:1994 to ASN.1:1990 --

with the following Note:

NOTE – Although ISO cannot advertise that one software tool must be used as opposed to another, at present, XXX ASN.1 Tools is one of the software tools allowing the conversion from ASN.1:1994 to ASN.1:1990.

It should be noted that problems can be avoided if only the common subset of ASN.1:1990 and ASN.1:1994 is used. In this case, only the ASN.1:1994 module needs to be included in this standard.

---

[1] ISO/IEC JTC 1/SC 21 (SC21) reaffirmed the continuation of availability of the ASN.1:1990 standards for reasons of conformance and interpretability (in SC21 N 9001 rev). SC21 requested its WGs to continue to maintain these standards. An SC21 resolution to continue maintenance will be conducted at each SC21 meeting (currently, once a year).

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

9.1 Guidelines

The following guidelines must be followed:

1) A single systems management document may reference ASN.1 modules from both ASN.1:1990 and ASN.1:1994. However, any given module is required to completely conform to ***either*** ASN.1:1990 ***or*** ASN.1:1994, where directives defined in clause 10 are used to identify which version of the notation is being used in a particular module.

2) Type and value references may be imported in an ASN.1:1994 module from an ASN.1:1990 module as long as:

   a) ASN.1:1990 **MACROs** are not imported in an ASN.1:1994 module; therefore one cannot create an instance of a **MACRO** in an ASN.1:1994 module.

   b) Identifiers for **SET** and **SEQUENCE** and **CHOICE** values are present.

3) Also, type and value references may be imported in an ASN.1:1990 module from an ASN.1:1994 module as long as:

   – ASN.1:1994 **CHARACTER STRING, BMPStrings, UniversalStrings, EMBEDDED PDV** types are not imported. Since there is no ASN.1:1990 equivalent for these ASN.1:1994 types, their use is discouraged in ASN.1:1994 modules which require an equivalent ASN.1:1990 module. For this same reason, the use of the ASN.1:1994 **Tuple** type is forbidden in ASN.1:1994 modules which require an equivalent ASN.1:1990 module[2].

   NOTE 1 – If the proposed guidelines are maintained, there are no adverse implications of importing type and value references from one version of ASN.1 to another because equivalent constructs exist in all cases.

4) The following ASN.1:1994 module shall be used for definitions of ASN.1 information object classes that are imported into ASN.1:1994 modules:

```
-- <ASN1.Version 1994 SMModule {joint-iso-itu-t ms(9) smi(1) part4(4)
--          asn1Module(2) 2} >--

SMModule {joint-iso-itu-t ms(9) smi(1) part4(4) asn1Module(2) 2}

DEFINITIONS ::= BEGIN

REGISTERED-AS ::= TYPE-IDENTIFIER

-- TYPE-IDENTIFIER is defined in ISO/IEC 8824-1 and is available in any module
-- without the necessity for importing it and is defined as:
-- TYPE-IDENTIFIER::= CLASS
-- {
-- &id OBJECT IDENTIFIER UNIQUE,
-- &Type
-- }
-- WITH SYNTAX {&Type IDENTIFIED BY &id}

INFO-REPLY-IDENTIFIER ::= CLASS
        {
            &Info OPTIONAL,
            &Reply OPTIONAL,
            &registeredAs OBJECT IDENTIFIER UNIQUE
        }

WITH SYNTAX {INFO &Info REPLY &Reply IDENTIFIED BY &registeredAs}

RegisteredAsTable REGISTERED-AS ::= {...}

InfoReplyTable INFO-REPLY-IDENTIFIER ::= {...}

-- RegisteredAsTable to be filled in by GDMO ATTRIBUTE and PARAMETER
-- Templates
-- InfoReplyTable to be filled in by GDMO ACTION and NOTIFICATION Templates

END
```

---

[2] **Tuple** is the name of the ASN.1:1994 production that allows control characters to be inserted in the value notation of an IA5String, something that cannot be done in ASN.1:1990. For example, ... **greetings IA5String ::= {"hello", cr, "there"}** inserts a carriage return between **"hello"** and **"there"** (**cr** is imported from a module defined in ITU-T Rec. X.680 | ISO/IEC 8824-1 and is equated to a literal carriage return).

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

5) Editors define ASN.1:1994 modules as in the following example:

```
-- <ASN1.Version 1994 ExampleModule > --

ExampleModule {-- a valid object identifier goes here --}

DEFINITIONS ::= BEGIN

IMPORTS
REGISTERED-AS,
INFO-REPLY-IDENTIFIER,
RegisteredAsTable,
InfoReplyTable
FROM SMModule {joint-iso-itu-t ms(9) smi(1) part4(4) asn1Module(2) 2};

Foo::=    SEQUENCE {
          id1 REGISTERED-AS.&id ({RegisteredAsTable}),
          syntax1 REGISTERED-AS.&Type ({RegisteredAsTable} {@.id1})}

Bar::=    SEQUENCE {
          id2 REGISTERED-AS.&id ({RegisteredAsTable}),
          syntax2 SEQUENCE OF REGISTERED-AS.&Type ({RegisteredAsTable} {@id2})}

firstExtensionId OBJECT IDENTIFIER ::= {1 3 17 103 10 1}

FirstExtensionInfo ::= PrintableString

-- Illustrates use of a contained subtype constraint of an open type --

FooBar ::=    Foo (WITH COMPONENTS {
              id1 (firstExtensionId),
              syntax1(FirstExtensionInfo)} )
END
```

Note that since GDMO is being used in combination with the ASN.1 **REGISTERED-AS** information object class, **FooBar** is a duplication of information. That is, the GDMO specification plus **REGISTERED-AS** in ASN.1 is equivalent to the inner type constraint on **Foo. FooBar** simply illustrates that while an open type can be constrained to any type, an **ANY/ANY DEFINED BY** cannot be constrained to anything other than an **ANY/ANY DEFINED BY** type in ASN.1:1990 and it illustrates how to do a mapping from an open type so constrained in ASN.1:1994 to an ASN.1 comment in ASN.1:1990.

6) Editors convert ASN.1:1994 module using the following instructions to produce an equivalent ASN.1:1990 module:

a) Remove the portion of the **IMPORTS** statement that refers to module SMModule. This gets rid of the imported definitions of the information object classes **REGISTERED-AS** and **INFO-REPLY-IDENTIFIER**.

b) Convert all open-type references to **ANY** or **ANY DEFINED BY** types. To do so, convert all ASN.1 syntax of the form according to the following:

First, convert:

FROM	TO
REGISTERED-AS.&id	**OBJECT IDENTIFIER**

If "**REGISTERED-AS.&Type**" is a component of a **SET** or **SEQUENCE**

and it is defined in the same **SET** or **SEQUENCE** as "**id**"

then convert:

FROM	TO
REGISTERED-AS.&Type ({RegisteredAsTable} {@id1})	**ANY DEFINED BY id**
REGISTERED-AS.&Type ({RegisteredAsTable} {@.id1})	**ANY DEFINED BY id**

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

else convert:

FROM	TO
REGISTERED-AS.&Type ({RegisteredAsTable} {@id1})	**ANY**
REGISTERED-AS.&Type ({RegisteredAsTable} {@.id1})	**ANY**

c) If **AUTOMATIC TAGS** is in effect for the ASN.1:1994 module, apply 22.5-22.7 of ITU-T Rec. X.680 | ISO/IEC 8824-1, which describes how automatic tagging is applied to the components of a **SET**, **SEQUENCE** or **CHOICE** type, and remove the syntax "**AUTOMATIC TAGS**" from the module definition statement.

d) If an open type is constrained using the TypeConstraint subtype notation, remove the constraint, since **ANY** and **ANY DEFINED BY** cannot be constrained with anything but an **ANY** or **ANY DEFINED BY** in ASN.1:1990.

e) If the definition of an **ENUMERATED** type uses the syntax "**identifier**"

for its EnumerationItem, change it to "**identifier(number)**". For example, change:

ENUMERATED {a, b, c, d}

to

ENUMERATED {a(0), b(1), c(2), d(3)}

f) Remove all occurrences of extension markers (i.e. "..."). For example, change:

```
SEQUENCE {
        i       IA5String,
        b       BOOLEAN,
        ...
        }
```

to

```
SEQUENCE {
        i       IA5String,
        b       BOOLEAN
        }
```

g) Remove any occurrence of **EXTENSIBILITY IMPLIED** from the module definition statement.

h) Remove all whitespace and newline characters from within hstrings and bstrings, and remove all newline characters from within cstrings. For example, change:

```
b BIT STRING      ::= '0001 1100 1101 0110 1110 0111 1101 0101'B
o OCTET STRING    ::= '8F3CE483 0192B345 932D5EF2 8AA3E700'H
p PrintableString     ::= "Hello,
                           world!"
```

to

```
b BIT STRING      ::= '00011100110101101110011111010101'B
o OCTET STRING    ::= '8F3CE4830192B345932D5EF28AA3E700'H
p PrintableString ::= "Hello,world!"
```

i) Convert all CharacterStringList notations to their cstring equivalent. For example, change:

```
name PrintableString ::= {"This is a long string, that is
                           spread across two lines"}
```

to

```
name PrintableString ::= "This is a long string, that is spread across two lines"
```

j) Convert any value set references into references to constrained types. For example, change:

```
Ages INTEGER ::= {1 | 4 | 7..20}
```

to

```
Ages ::= INTEGER (1 | 4 | 7..20)
```

NOTE 2 – It is preferable to use constrained types instead of value sets unless parameterization and information object classes are being heavily used, for this is typically when value sets are particularly useful.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

k) Convert all occurrences of the **INSTANCE OF** type to their equivalent **SEQUENCE** type. For example, change:

```
A ::= INSTANCE OF REGISTERED-AS
```

to

```
A ::= SEQUENCE {
      type-id                 OBJECT IDENTIFIER,
      value                   [0]   ANY DEFINED BY type-id
}
```

l) Remove the identifiers "**mantissa**", "**base**" and "**exponent**" from any value of type **REAL**, and replace any inner type constraints present on **REAL** types with a comment. For example, change:

```
ten REAL ::= {mantissa 1, base 10, exponent 1}

DecimalReal ::= REAL (WITH COMPONENTS {..., base 10})
```

to

```
ten REAL ::= {1, 10, 1}

DecimalReal ::= REAL    -- Shall be encoded as base 10
```

m) Change all occurrences of the value notation for **EXTERNAL** to its ASN.1:1990 equivalent. For example, change:

```
extern1990 EXTERNAL ::= {
      direct-reference        { 1 2 3 4 5 6 },
      indirect-reference      3,
      encoding                single-ASN1-type : IA5String : "hello"
}
```

to

```
extern1994 EXTERNAL ::= {
      identification context-negotiation :  {
            presentation-context-id         3,
            transfer-syntax                 { 1 2 3 4 5 6 }
      },
      data-value              notation : IA5String : "hello"
}
```

n) Replace all ASN.1:1994 permitted alphabets with their ASN.1:1990 equivalents. For example, change:

```
UpperCaseAndSpaceOnly ::= PrintableString (FROM("A".."Z" | " "))
```

to

```
UpperCaseAndSpaceOnly ::= PrintableString (FROM("A" | "B" | "C" |
                          "D" | "E" | "F" | "G" | "H" | "I" | "J" | "K" |
                          "L" | "M" | "N" | "O" | "P" | "Q" | "R" | "S" |
                          "T" | "U" | "V" | "W" | "X" | "Y" | "Z" ))
```

o) Change all ASN.1:1994 set expressions used in the subtype notation to their ASN.1:1990 equivalent. For example, change:

```
PartNumber ::= NumericString (SIZE(8) ^ FROM("0".."9"))
```

to

```
PartNumber ::= NumericString (SIZE(8)) (FROM("0"|"1"|"2"|"3"|"4"|
"5"|"6"|"7"|"8"|"9"))
```

p) Where o) cannot be done because it results in an infinite set, replace the portion of the ASN.1:1994 subtype notation that results in an infinite set with a comment. For example, change:

```
AllButZeroToTen ::= INTEGER(ALL EXCEPT (0..10))
```

to

```
AllButZeroToTen ::= INTEGER    -- all integer values except 0 - 10
```

Applying the above conversion instructions to the ASN.1:1994 **ExampleModule** in guideline 5 produces:

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
-- <ASN1.Version 1990 ExampleModule > --

ExampleModule {-- a valid object identifier value goes here --}

DEFINITIONS ::= BEGIN

Foo::= SEQUENCE {
    id1 OBJECT IDENTIFIER,
    syntax1 ANY DEFINED BY id1}

Bar::= SEQUENCE {
    id2 OBJECT IDENTIFIER,
    syntax2 ANY }

-- Note that in the ASN.1:1994 ExampleModule, syntax2 in Bar is defined as a
-- SEQUENCE OF, not as an open type, and so cannot be
-- converted to an ANY DEFINED BY.

firstExtensionId OBJECT IDENTIFIER ::= {1 3 17 103 10 1}

FirstExtensionInfo ::= PrintableString

-- Note firstExtensionId and FirstExtensionInfo are to be used with the
-- Foo type where firstExtensionId is the value of the id1
-- (OBJECT IDENTIFIER) which indicates that the syntax1 has the
-- syntax type of FirstExtensionInfo (PrintableString).

END
```

7) New clause 10

Add a new clause 10, following clause 9:

10 Conventions for ASN.1 and GDMO directives

This clause introduces conventions to clearly identify specification and user options associated with GDMO templates and related ASN.1 modules. This is accomplished through the use of in-line directives. These conventions could also be useful as ASN.1 and GDMO compiler directives. If these conventions are used, they do not require a specifier to modify the ASN.1 and GDMO specifications in order to use these directives. That is, the directives may be in the same body of texts as the ASN.1 modules or GDMO templates, or in some other associated specification. Also, if these conventions are used, they do not alter the ASN.1 and GDMO specification. That is, these directives do not change the syntax of the ASN.1 and GDMO specification. These conventions are not required but are recommended.

These directives are structured to meet several requirements:

- Input files with directives (i.e. ASN.1 modules, GDMO libraries, and/or distinct directive files) must be acceptable to ASN.1 compilers and GDMO tools/compilers that do not recognize directives.
- Input files without directives must be acceptable to ASN.1 compilers and GDMO tools/compilers.

NOTE – These conventions permit extensions through the use of implementation specific directives.

Each directive specification is a structured comment that contains a single directive, which consists of a keyword qualified by a scope, and followed by zero or more operands. Case is significant. Thus, a directive is treated as a comment by any tool or compiler that does not support these directives.

The following conventions are used to describe directives:

- Text shown in bold (e.g. `--<` or **`ASN1`**) must be entered exactly as shown, without any added whitespace or change in case from that shown.
- Text shown in italics (e.g. *`keyword`*) should be replaced with appropriate text.
- Optional directive elements are enclosed in square brackets (e.g. **`[operands]`**).
- A directive element that may be repeated (any number of times) is followed by three periods (`...`) (e.g. **`[operands]`** `...`).

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

The general format of a directive is:

```
--< directive >--
```

where directive is:

```
Scope.keyword [operand ] [ , operand ] ...
```

That is, a directive is introduced by two consecutive hyphens and a less than symbol (--<), and terminated by a greater than symbol and two consecutive hyphens (>--). There must not be any whitespace between the hyphens and the less than or greater than symbols. Thus, a directive is treated as an ASN.1 or GDMO comment by any compiler that does not support these directives. A directive cannot contain any ASN.1 comments.

Each --< >-- construction is a structured comment that contains a single directive, which consists of a keyword qualified by a scope, and followed by zero or more operands. Case is significant.

Directives may be continued onto additional lines, with the first non-whitespace characters being two consecutive hyphens (--) on the continued line(s).

Operands are delimited by whitespace (one or more consecutive space or tab characters) for dissimilar items, and a comma for a list of similar items (such as working set names). White space (zero or more space or tab characters) may occur before or after other elements in a directive. In this context, carriage return, new line, or vertical tab characters are NOT considered whitespace, and are not allowed.

10.1 Conventions for ASN.1 directives

For an ASN.1 directive, the following additional conventions apply.

A directive may be in the same file as the ASN.1 item. When placed in the same file, the directive may be outside the scope of an ASN.1 module (before the start of a module or after the end of a module). A directive may occur within the body of a module, wherever whitespace is allowed. When placed within a module, each directive must occur before the ASN.1 item to which it applies.

For an ASN.1 directive, the Scope symbol is **ASN1**. Additionally, other scope symbols may be defined (e.g. implementation assigned).

The keyword can be one of the following:

- **Version.**

In general, an operand may be a:

- text string (without white space, comma, -- or >);
- number string (without white space, comma, -- or >);
- cstring ("xxxxx") all on same line;
- { *ObjectIdentifier* };
- potentially other ASN.1 constructions, e.g. bstring or hstring.

10.1.1 Version directive

The **Version** directive is used to indicate if an ASN.1 module is written according to the ASN1:1990 or ASN1:1994 standard.

This directive has the following format:

```
--<ASN1.Version version moduleName  [ oid ] >--
```

The elements shown in bold (e.g. **ASN1.Version**) are to be written as shown, and the elements in italics (e.g. *version*) are to be replaced as follows:

- *version* – Either **1990** or **1994** or **1990, 1994**.
- *moduleName* – The name of an ASN.1 module.
- oid – An optional ASN.1 Object Identifier value, used to unambiguously identify an ASN.1 module.

Only one **Version** directive should be provided for an ASN.1 module. The **Version** directive **1990, 1994** means that the ASN.1 module asserts conformance to both ASN.1:1990 and ASN.1:1994; a compiler may use its knowledge of either of these versions, or the common subset of both. If a **Version** directive is not provided for an ASN.1 module, an implementation may use some other way to identify the module version, such as command line compiler option, or the recognition of syntax that is unique to a particular version (such as an ASN1:1990 macro, or an ASN1:1994 information object).

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Examples:

```
--<ASN1.Version 1990 Attribute-ASN1Module
--    {joint-iso-itu-t ms(9) smi(3) part2(2) asn1Module(2) 1} >-

--<ASN1.Version 1994 SMModule
--    {joint-iso-itu-t ms(9) smi(3) part4(4) asn1Module(2) 2} >--
```

10.2 Conventions for GDMO directives

A GDMO directive has the following additional conventions.

A directive cannot contain any ASN.1 comments.

A directive may be in a file different than the file that contains the GDMO template the directive refers to, or it may be in the same file as the GDMO template. When placed in the same file, the directive may be outside the scope of a GDMO document (before the start of a document or after the end of a document). A directive may occur within the body of a document, wherever whitespace is allowed.

When placed within a document, each directive must occur before the GDMO template to which it applies. For a particular GDMO template, there may be at most one particular directive for that template, but there may be different directives for the same template. For example, the same template may be referenced by both Nickname and Working Set directives, but only one each. There may be Nickname directives for other ASN.1 items.

The Scope symbol is **GDMO**. Additionally, other scope symbols may be defined (e.g. implementation assigned).

The keyword can be one of those defined here:

- **Alias;**
- **Document;**
- **EndDocument;**
- **Version.**

In general, an operand may be a:

- text string (without white space, comma, -- or >);
- number string (without white space, comma, -- or >);
- cstring ("xxxxx") all on same line;
- { *ObjectIdentifier* };
- potentially other ASN.1 constructions, e.g. bstring or hstring.

10.2.1 Alias directive

The **Alias** directive is used to provide alternative or alias identifiers for a GDMO document. These aliases are used to reconcile references between GDMO documents, where short or inconsistent document identifiers are used.

The format of the directive is:

```
--<GDMO.Alias documentIdentifier documentAlias
-- [ , documentAlias ] ... >--
```

The elements shown in bold (e.g. **GDMO.Alias**) are to be written as shown, and the elements in italics (e.g. *documentIdentifier*) are to be replaced as described below.

Any number of documentAlias items may be provided, each separated with a comma.

- *documentIdentifier* – The identifier of a GDMO document, either in the form of a string, enclosed in quotes ("), or an Object Identifier, enclosed in curly braces ({ and }).
- *documentAlias* – An alternative identifier of a GDMO document, either in the form of a string, enclosed in quotes ("), or an Object Identifier, enclosed in curly braces ({ and }).

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Examples:

```
--<GDMO.Alias   "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992"
--  "Rec. X.721 | ISO/IEC 10165-2:1992",
--  "CCITT Rec. X.721 | ISO/IEC 10165-2 ",
--  "Rec. X.721| ISO/IEC 10165-2",
--  "CCITT Rec. X.721 (1992)",
--  "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992",
--  "DMI">--
--<GDMO.Alias  "Recommendation M.3100:1992"
--  "Rec. M.3100:1992",
--  "M.3100:1992",
--  "M.3100">--
```

10.2.2 Document directive

The **Document** directive provides the identifier of a GDMO "document", where the identifier is either a character string, or an Object Identifier, or both. The format of the directive can take one of three forms:

--<GDMO.Document *documentString* **>--**

--<GDMO.Document *documentOID* **>--**

--<GDMO.Document *documentString documentOID* **>--**

The elements shown in bold (e.g. **GDMO.Document**) are to be written as shown, and the elements in italics (e.g. *documentString*) are to be replaced as follows:

- *documentString* – The character string that identifies a GDMO document, enclosed in quotes (").
- *documentOID* – The ASN.1 Object Identifier assigned to a GDMO document.

A **Document** directive must come before the first GDMO template or ASN.1 module making up the document. That is, a GDMO document is considered to be composed of all the GDMO templates and ASN.1 modules following a **Document** directive, up to the corresponding **EndDocument** directive, to the next **Document** directive, or to the end of the file that contains the GDMO text.

The following rules for storing GDMO text in files have the corresponding directives:

- Each GDMO document should have a **Document** directive to provide the "correct" name of the document. If a **Document** directive is not provided, the name of the document is not defined, or is provided through some other mechanism.
- A **Document** directive should be in the same file as the GDMO text to which it applies.

The same GDMO document name may appear in several **Document** directives, to apply to several units of GDMO text, such as distinct files. In this case, all of the GDMO text in the different files are considered part of the same GDMO document. This is similar to the C++ namespace, which allows several distinct header files to contain material defined in the same namespace.

In general, there should be a single GDMO document per input file. The only case a file may contain more that one GDMO document is when the file has appropriate **Document** and **EndDocument** directives.

Whitespace (one or more consecutive space or tab characters) is not considered significant within a *documentIdentifier* or *documentAlias*.

Examples:

```
--<GDMO.Document  "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992">--
--<GDMO.Document  "Recommendation M.3100:1992">--
--<GDMO.Document  "OP1 Library Vol. 4">--
--<GDMO.Document  {iso(1) 2 124 360501 15 13 1} >--
--<GDMO.Document  "IIMC MIB Translation" {iso(1) 2 124 360501 15 13 1} >--
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

10.2.3 End Document directive

The **EndDocument** directive indicates the end of a GDMO "document". The format of the directive can take one of four forms:

```
--<GDMO.EndDocument >--
--<GDMO.EndDocument documentString >--
--<GDMO.EndDocument documentOID >--
--<GDMO.EndDocument documentString documentOID >--
```

The elements shown in bold (e.g. **GDMO.EndDocument**) are to be written as shown, and the elements in italics (e.g. *documentString*) are to be replaced as follows:

- *documentString* – The character string that identifies a GDMO document, enclosed in quotes (").
- *documentOID* – The ASN.1 Object Identifier assigned to a GDMO document, enclosed in curly braces ({ and }).

A GDMO document is considered to be composed of all the GDMO templates and ASN.1 modules following a **Document** directive, up to the corresponding **EndDocument** directive, to the next **Document** directive, or the end of the file that contains the GDMO text. That is, use of the **EndDocument** directive is not required. If used, an **EndDocument** directive must come after the last GDMO template or ASN.1 module making up the document. The *documentString* and/or *documentOID* in an **EndDocument** directive should match those of the preceding **Document** directive.

Examples:

```
--<GDMO.EndDocument  >--
--<GDMO.EndDocument  "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992">--
--<GDMO.EndDocument  "Recommendation M.3100:1992">--
--<GDMO.EndDocument  "OP1 Library Vol. 4">--
--<GDMO.EndDocument  {iso(1) 2 124 360501 15 13 1} >--
--<GDMO.EndDocument  "IIMC MIB Translation" {iso(1) 2 124 360501 15 13 1} >--
```

10.2.4 Version directive

The **Version** directive is used to indicate what version of GDMO a document is written to. It may take one of two formats:

```
--<GDMO.Version version >--
--<GDMO.Version version documentIdentifier >--
```

The elements shown in bold (e.g. **GDMO.Version**) are to be written as shown, and the elements in italics (e.g. *version*) are to be replaced as follows:

- *version* – The number indicating the GDMO version according to the following table:

Index	Version definition
1	GDMO, 1992
1.1	Amendment 1, **SET-BY-CREATE**
1.2	Amendment 2, **NO-MODIFY**, ASN.1:1994 and directives
1.3	Amendment 3, Use of Z in managed object class behaviour

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

A new version is defined as every time GDMO is updated (e.g. revision, corrigendum, amendment). Support of a given version is cumulative. That is, any GDMO document valid for version n will also be valid for all previous versions. For example, **GDMO.Version 1.2** indicates that the GDMO document supports GDMO 1992 (version **1**) and the SET-BY-CREATE amendment (version **1.1**), in addition to the NO-MODIFY, ASN.1:1994 and directives amendment (version **1.2**).

– *documentIdentifier* – The identifier of a GDMO document, either in the form of a string, enclosed in quotes ("), or an Object Identifier, enclosed in curly braces ({ and }).

The first form (without a documentIdentifier) must occur within a GDMO document, but before any GDMO templates.

Examples:

```
--<GDMO.Version 1 "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992" >--
--<GDMO.Version 1.1 "Recommendation M.3100" >--
--<GDMO.Version 1.2 >--
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

© ISO/IEC

ICS 35.100.70

Price based on 12 pages

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

STD.ISO 10165-4-ENGL 1992 ■ 4851903 0689552 171 ■

INTERNATIONAL STANDARD ISO/IEC 10165-4:1992
TECHNICAL CORRIGENDUM 1

Published 1996-12-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

Information technology — Open Systems Interconnection — Structure of management information: Guidelines for the definition of managed objects

TECHNICAL CORRIGENDUM 1

Technologies de l'information — Interconnexion de systèmes ouverts — Structure des informations de gestion: Principes directeurs pour la définition des objets gérés

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to International Standard ISO/IEC 10165-4:1992 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology,* Subcommittee SC 21, *Open systems interconnection, data management and open distributed processing.*

This material is reproduced from ISO documents under International Organization for Standardization (ISO) Copyright License number IHS/ICC/1996. Not for resale. No part of these ISO documents may be reproduced in any form, electronic retrieval system or otherwise, except as allowed in the copyright law of the country of use, or with the prior written consent of ISO (Case postale 56, 1211 Geneva 20, Switzerland, Fax +41 22 734 10 79), IHS or the ISO Licensor's members.

ICS 35.100.70 **Ref. No. ISO/IEC 10165-4:1992/Cor.1:1996(E)**

Descriptors: data processing, information interchange, network interconnection, open systems interconnection, application layer, management, information.

© **ISO/IEC 1996**

Printed in Switzerland
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

INTERNATIONAL STANDARD

ITU-T RECOMMENDATION

INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION – STRUCTURE OF MANAGEMENT INFORMATION: GUIDELINES FOR THE DEFINITION OF MANAGED OBJECTS

TECHNICAL CORRIGENDUM 1

1) Subclause 6.4.5

Add the following at the end of the current paragraph:

"A managed object identifies its actual class (see 7.4.3) by the value of its managed object class attribute."

2) Subclause 7.4

Add the following immediately after 7.4.2 as a new subclause:

"7.4.3 Actual class

A managed object class definition consists of the MANAGED OBJECT CLASS template (see 8.3) registered with the object identifier value for that class together with the set of templates referenced by that template and all templates referenced by templates in the set.

A managed object identifies its actual class by the value of its managed object class attribute which is the object identifier value used to register its MANAGED OBJECT CLASS template. Each managed object:

- supports all of the characteristics defined in its actual class definition in accord with the packages that are present;
- supports only operations that are defined in its actual class definition for packages that are present; and
- emits only notifications when a behaviour defined to trigger that notification in the actual class definition applies for packages that are present.

The absence of a GDMO construct for a characteristic in a managed object class definition specifically excludes that characteristic from that class definition. A subclass may add an excluded construct by explicit definition. Each subclass has its own registered object identifier value. For example, if REPLACE is not specified for a single-valued attribute, that attribute in instances of that class shall be regarded as read only; a subclass definition may extend this by adding the REPLACE construct to specify that the attribute can be replaced for instances of the subclass and instances that are compatible with the subclass."

3) Subclause 8.3.3.1

Add the following to 8.3.3.1 a) *before* "NOTE 2"*:*

"When behaviour is extended the stated or implied pre-conditions may only be weakened (the required pre-conditions shall remain the same or become fewer), the stated or implied post-conditions may only be strengthened (the same post-conditions shall be satisfied and additional post-conditions may be satisfied), and the stated or implied invariants remain unchanged but more invariants may be added. (Refer to 5.2.2.6 of CCITT Rec. X.720 | ISO/IEC 10165-1 of the Management Information Model.)"

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

4) Subclause 8.3.3.3

Add the following to the end of this subclause, as a new paragraph:

"Where there are specific conditions that preclude instantiation of a conditional package, these should be specified in a BEHAVIOUR template. The BEHAVIOUR template used for this may be in the conditional package itself or in a mandatory package of the class. If such specifications are present in textual behaviour definitions, it is recommended that the paragraph containing the specification be introduced with "<package-label> PRESENT ONLY IF:" as a textual convention."

5) Subclause 8.5.1.1.1

In 8.5.1.1.1 replace "9.5.3" *with* "8.5.3.1".

6) Index

Change these index entries:

"BEHAVIOUR 25-26, 30-32, 34-35, 37-40

REPLACE 14, 26-27"

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10165-4 92 ■ 4851903 0669538 TT5 ■

INTERNATIONAL STANDARD

ISO/IEC 10165-4

First edition
1992-09-01

AMENDMENT 1
1996-08-01

Information technology — Open Systems Interconnection — Structure of management information: Guidelines for the definition of managed objects

AMENDMENT 1: Set by Create and Component Registration

Technologies de l'information — Interconnexion de systèmes ouverts — Structure des informations de gestion: Principes directeurs pour la définition des objets gérés

AMENDEMENT 1: Réglage par enregistrement de création et de composant

Reference number
ISO/IEC 10165-4:1992/Amd.1:1996(E)

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Amendment 1 to International Standard ISO/IEC 10165-4:1992 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Sub-committee SC 21, *Open systems interconnection, data management and open distributed processing*, in collaboration with ITU-T. The identical text is published as ITU-T Rec. X.722/Amd.1.

© ISO/IEC 1996

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

INTERNATIONAL STANDARD

ITU-T RECOMMENDATION

INFORMATION TECHNOLOGY - OPEN SYSTEMS INTERCONNECTION - STRUCTURE OF MANAGEMENT INFORMATION: GUIDELINES FOR THE DEFINITION OF MANAGED OBJECTS

AMENDMENT 1
Set by Create and Component Registration

1) Add the following in 2.1 after the reference to CCITT Rec. X.701:

- ITU-T Recommendation X.702 (1995) | ISO/IEC 11587:1996, *Information technology – Open Systems Interconnection – Application context for systems management with transaction processing.*

2) Replace 3.8.2 with the following:

3.8.2 **template**: A standard format for the documentation of a definition of a management information element.

3) Add the following row to Table 1:

applicationContext(4)	Application contexts, ITU-T Rec. X.702 | ISO/IEC 11587 and subsequent parts.

4) Add the following rows to Table 13 and to Table 15:

relationshipClass(11)	Allocation of managed relationship class identifiers
relationshipMapping(12)	Allocation of relationship mapping identifiers
relationshipRole(13)	Allocation of relationship role identifiers

5) Add the following to the end of the propertylist supporting productions in 8.4.2:

[SET-BY-CREATE]

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

6) Add the following after Note 2 in 8.4.3.2:

The GET property is included if the value of the attribute may be retrieved with the Get attribute value operation.

The REPLACE property is included if the attribute may be set with the Replace attribute value operation and with the Create operation. Setting with the Create operation applies only if the Create operation is supported by the name binding of the managed object instance.

Inclusion of the GET-REPLACE property is the notation for specifying that both the GET property and the REPLACE property are included.

The ADD property is included if the attribute may be set with the Add member operation.

The REMOVE property is included if the attribute may be set with the Remove member operation.

Inclusion of the ADD-REMOVE property is the notation for specifying that both the ADD property and the REMOVE property are included.

The SET-BY-CREATE property is included if the attribute may be set by means of the Create operation. This property is only meaningful if the Create operation is supported by the name binding of the managed object instance. Since the REPLACE property is included if the attribute may be set by means of the Replace operation or the Create operation, the SET-BY-CREATE property does not have to be included if the REPLACE property is present. Similarly, the SET-BY-CREATE property does not have to be included if the ADD, REMOVE, or ADD-REMOVE property is present. Even if SET-BY-CREATE is absent, the attempt to set a value with the Create operation may succeed.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

© ISO

ICS 35.100.70

Descriptors: data processing, information interchange, network interconnection, open systems interconnection, management, information, general conditions.

Price based on 2 pages

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

10165 PT*4 92 ■ 4851903 0508094 T74 ■

INTERNATIONAL STANDARD

ISO/IEC 10165-4

First edition
1992-09-01

Information technology — Open Systems Interconnection — Structure of management information —

Part 4:
Guidelines for the definition of managed objects

Technologies de l'information — Interconnexion de systèmes ouverts — Structures des informations de gestion —

Partie 4: Principes directeurs pour la définition des objets gérés

Reference number
ISO/IEC 10165-4:1992(E)

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Contents

Page

1 Scope 1

2 Normative references 2

3 Definitions 3

4 Abbreviations 5

5 Conventions 5

6 Global issues 5

7 General principles for managed object definition 12

8 Notational tools for managed object definition 18

Annex A Examples of use of the guidelines 42

Index 48

© ISO/IEC 1992
All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case Postale 56 • CH-1211 Genève 20 • Switzerland
Printed in Switzerland

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 10165-4 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology,* in collaboration with the CCITT. The identical text is published as CCITT Recommendation X.722.

ISO/IEC 10165 consists of the following parts, under the general title *Information technology – Open Systems Interconnection – Structure of management information*:

– *Part 1: Management information model*

– *Part 2: Definition of management information*

– *Part 4: Guidelines for the definition of managed objects*

– *Part 5: Generic management information*

– *Part 6: Requirements and guidelines for implementation conformance statement proformas associated with management information*

Annex A is for information only.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Introduction

ISO/IEC 10165 is a multipart standard developed according to ISO 7498 and ISO/IEC 7498-4. ISO/IEC 10165 is related to the following International Standards

- ISO/IEC 9595 : 1990, *Information technology – Open Systems Interconnection – Common management information service definition*;
- ISO/IEC 9596 : 1990, *Information technology – Open Systems Interconnection – Common management information protocol*;
- ISO/IEC 10040 : 1992, *Information technology – Open Systems Interconnection – Systems management overview*;
- ISO/IEC 10164 : 1992, *Information technology – Open Systems Interconnection – Systems management*.

OSI management standardization inevitably involves coordinated work by a number of standards bodies. CCITT SGVII and ISO/IEC JTC1 SC21/WG4 are jointly responsible for the development of Recommendations | International Standards that describe the architecture for OSI management, the services, protocols and functions that are used for systems management, and the structure of management information. Other working groups, in CCITT, ISO/IEC JTC1 SC21, ISO/IEC JTC1 SC6 and elsewhere, are responsible for the development of Recommendations | International Standards that describe the management aspects of particular layers of the OSI Basic Reference Model; these may describe (N)-layer management protocols, management aspects of (N)-layer operation, and managed objects that provide a "management view" of aspects of the layer operation and are visible to systems management.

This Recommendation | International Standard provides the developers of managed object class definitions with the information and documentation tools required in order to produce complete managed object class definitions that are compatible with the OSI management standards developed jointly by ISO/IEC and CCITT. A beneficial side effect of the use of these guidelines will be that a common approach will be taken to the documentation of these Recommendations | International Standards, regardless of where the development takes place.

CCITT Rec. X.700 | ISO/IEC 7498-4 and CCITT Rec. X.701 | ISO/IEC 10040 define the architecture for OSI management, and describe the content of and relationships between OSI management standards.

CCITT Rec. X.720 | ISO/IEC 10165-1 describes the model of management information in terms of managed objects.

CCITT Rec. X.721 | ISO/IEC 10165-2 (DMI) defines generic managed object classes and characteristics. Where a suitable definition of management information exists in DMI, it is recommended that this definition be referenced in preference to defining a new information element with the same structure.

CCITT Rec. X.208 | ISO/IEC 8824 defines the notation used to express the abstract syntax of the data elements associated with managed object characteristics that shall be carried in systems management protocol.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

INTERNATIONAL STANDARD

CCITT RECOMMENDATION

INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION – STRUCTURE OF MANAGEMENT INFORMATION : GUIDELINES FOR THE DEFINITION OF MANAGED OBJECTS

1 Scope

This Recommendation | International Standard provides developers of Recommendations and International Standards that contain managed object definitions with guidance that will

a) encourage consistency between managed object definitions;

b) ensure the development of such definitions in a manner compatible with the OSI management Recommendations and International Standards;

c) reduce duplication of effort in other working groups by identifying commonly useful documentation layouts, procedures and definitions.

To this end, this Recommendation | International Standard specifies

a) the relationships between the relevant OSI management Recommendations and International Standards and the definition of managed object classes, and how those Recommendations and International Standards should be used by managed object class definitions;

b) the appropriate methods to be adopted for the definition of managed object classes and their attributes, notifications, actions and behaviour, including

1) a summary of aspects that shall be addressed in the definition;

2) the notational tools that are recommended to be used in the definition;

3) consistency guidelines that the definition may follow.

c) the relationship of managed object class definitions to management protocol, and what protocol-related definitions are required;

d) the recommended documentation structure for managed object class definitions.

This Recommendation | International Standard is applicable to the development of any Recommendation | International Standard which defines

a) management information which is to be transferred or manipulated by means of OSI management protocol;

b) the managed objects to which that information relates.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

This Recommendation | International Standard does not specify or imply

a) any constraints on the development of managed object class definitions in terms of their functionality, the Recommendations | International Standards to which they relate, or the uses to which they are put in a particular management environment;

b) guidelines for the definition of resources; it provides guidelines only for the definition of the managed objects which provide the management view of resources.

2 Normative references

The following CCITT Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and International Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and International Standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards. The CCITT Secretariat maintains a list of the currently valid CCITT Recommendations.

2.1 Identical CCITT Recommendations | International Standards

- CCITT Recommendation X.660[1] | ISO/IEC 9834-1[2], *Information technology – Open Systems Interconnection – Procedures for the operation of OSI registration authorities – Part 1: General procedures.*

- CCITT Recommendation X.701 (1992) | ISO/IEC 10040 : 1992, *Information technology – Open Systems Interconnection – Systems management overview.*

- CCITT Recommendation X.720 (1992) | ISO/IEC 10165-1 : 1992, *Information technology – Open Systems Interconnection – Structure of management information : Management information model.*

- CCITT Recommendation X.721 (1992) | ISO/IEC 10165-2 : 1992, *Information technology – Open Systems Interconnection – Structure of management information : Definition of management information.*

- CCITT Recommendation X.732 (1992) | ISO/IEC 10164-3 : 1992, *Information technology – Open Systems Interconnection – Systems management : Attributes for representing relationships.*

- CCITT Recommendation X.733 (1992) | ISO/IEC 10164-4 : 1992, *Information technology – Open Systems Interconnection – Systems management : Alarm reporting function.*

2.2 Paired CCITT Recommendations | International Standards equivalent in technical content

- CCITT Recommendation X.200 (1988), *Reference Model of Open Systems Interconnection for CCITT Applications.*

  ISO 7498 : 1984, *Information processing systems – Open Systems Interconnection – Basic Reference Model.*

- CCITT Recommendation X.208 (1988), *Specification of abstract syntax notation one (ASN.1).*

  ISO/IEC 8824 : 1990, *Information technology – Open Systems Interconnection – Specification of Abstract Syntax Notation One (ASN.1).*

- CCITT Recommendation X.501 (1989), *The Directory – Models.*

---

[1] Presently at state of draft Recommendation.

[2] To be published.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

ISO/IEC 9594-2 : 1990, *Information technology – Open Systems Interconnection – The Directory – Part 2: Models.*

– CCITT Recommendation X.650 (1992), *Naming and Addressing for Open Systems Interconnection (OSI) for CCITT Applications.*

ISO 7498-3 : 1989, *Information processing systems – Open Systems Interconnection – Basic Reference Model – Part 3: Naming and Addressing.*

– CCITT Recommendation X.700[1)], *Management Framework Definition for Open Systems Interconnection (OSI) for CCITT Applications.*

ISO/IEC 7498-4 : 1989, *Information processing systems – Open Systems Interconnection – Basic Reference Model – Part 4: Management framework.*

– CCITT Recommendation X.710 (1991), *Common Management Information Service Definition for CCITT Applications.*

ISO/IEC 9595 : 1990, *Information technology – Open Systems Interconnection – Common management information service definition.*

– CCITT Recommendation X.711 (1991), *Common Management Information Protocol Specification for CCITT Applications.*

ISO/IEC 9596-1 : 1991, *Information technology – Open Systems Interconnection – Common management information protocol – Part 1: Specification.*

3 Definitions

For the purposes of this Recommendation | International Standard, the following definitions apply.

3.1 Basic reference model definitions

This Recommendation | International Standard makes use of the following terms defined in CCITT Rec. X.200 | ISO 7498:

a) (N)-connection;
b) (N)-entity;
c) (N)-layer;
d) (N)-service-access-point;
e) open system;
f) systems management.

3.2 Naming and addressing definitions

This Recommendation | International Standard makes use of the following term defined in CCITT Rec. X.650 | ISO 7498-3:

(N)-selector

3.3 Management framework definitions

This Recommendation | International Standard makes use of the following terms defined in CCITT Rec. X.700 | ISO/IEC 7498-4:

a) managed object;
b) (N)-layer operation.

[1)] Presently at state of draft Recommendation.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

3.4 Systems management overview definitions

This Recommendation | International Standard makes use of the following terms defined in CCITT Rec. X.701 | ISO/IEC 10040:

a) agent;
b) generic definitions;
c) managed object class;
d) management information;
e) manager;
f) (N)-layer management protocol;
g) notification;
h) notification type;
i) (systems management) operation;
j) systems management (application) protocol.

3.5 Management information model definitions

This Recommendation | International Standard makes use of the following terms defined in CCITT Rec. X.720 | ISO/IEC 10165-1:

a) action;
b) actual class;
c) attribute group;
d) attribute identifier;
e) attribute type;
f) attribute value set;
g) behaviour;
h) characteristic;
i) conditional package;
j) containment;
k) inheritance;
l) inheritance hierarchy;
m) initial value managed object;
n) instantiation;
o) mandatory package;
p) multiple inheritance;
q) name binding;
r) package;
s) parameter;
t) permitted value set;
u) relative distinguished name;
v) required value set;
w) specialization;
x) subclass;
y) subordinate object;
z) superclass;
aa) superior object.

3.6 CMIS definitions

This Recommendation | International Standard makes use of the following terms defined in CCITT Rec. X.710 | ISO/IEC 9595:

a) attribute;
b) Common Management Information Services.

3.7 ASN.1 definitions

This Recommendation | International Standard makes use of the following terms defined in CCITT Rec. X.208 | ISO/IEC 8824:

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

a) object identifier;
b) sequence type;
c) sequence-of type;
d) set type;
e) set-of type;
f) subtype;
g) type;
h) type reference name;
i) value reference name.

3.8 Additional definitions

3.8.1 managed object class definition: A set of attribute, operation, notification and behaviour definitions to which a managed object class name has been allocated, documented by the use of a managed object class template and one or more other templates, of the types defined in this Recommendation | International Standard, which are directly or indirectly referenced by the managed object class template. The definition of a managed object class includes all elements of definition inherited from the superclass(es) of the managed object class and all elements of definition that constitute specialization(s) of the superclass(es).

3.8.2 template: A standard format for the documentation of name bindings, and managed object class definitions and their components, such as packages, parameters, attributes, attribute groups, behaviour definitions, actions or notifications.

3.8.3 directory object class: An object class, as defined in CCITT Rec. X.501 | ISO/IEC 9594-2.

4 Abbreviations

ASN.1	Abstract Syntax Notation One
CMIP	Common Management Information Protocol
CMIS	Common Management Information Services
DMI	Definition of Management Information
IVMO	Initial Value Managed Object
MOCS	Managed Object Conformance Statement
(N)-SAP	(N)-service-access-point
OSI	Open Systems Interconnection
PDU	Protocol Data Unit
SAP	Service Access Point
SDU	Service Data Unit
SMI	Structure of Management Information
RDN	Relative Distinguished Name

5 Conventions

Distinctive typefaces are used throughout this Recommendation | International Standard where the text makes use of **ASN.1 notation** or `the notational tools defined in clause 8`.

No externally defined conventions are used in this Recommendation | International Standard.

6 Global issues

6.1 Relationship integrity

When defining managed object classes, it is important to consider situations where there are consistency requirements that will apply to instances of those classes, for example, situations where the behaviour of a managed object is constrained by rules that depend not only upon its own state but also upon the state of other managed objects in the system. Any such constraints must be expressed as behaviour associated with the managed object classes concerned.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

A particular case where the definitions associated with the instantiation of a managed object shall explicitly define consistency rules is that of the Delete operation; for this operation, such consistency rules are specified in name binding(s) associated with the managed object class. The effect of a Delete operation shall be defined in such a way that it is clear under what circumstances deletion is permitted, and what the consequences of deletion are. In particular, the name binding shall specify whether deletion of an instance of the class is permitted when contained managed objects still exist, and what rules apply in cases where other (non-containment) relationships exist between the managed object being deleted and other managed objects, such as those that may exist as a consequence of the presence of relationship attributes as defined in CCITT Rec. X.732 | ISO/IEC 10164-3. The consistency rules that are applied for deletion shall be such that the delete operation cannot result in inconsistent relationships. As these consistency rules are specified as part of a name binding, the rules that apply to the deletion of a given managed object are established at the time that the managed object is instantiated.

6.2 Inherited characteristics

The process of inheritance results in the inclusion of all characteristics of the superclass(es) of a managed object class in the managed object class definition. This rule is applied recursively, terminating at the apex of the inheritance hierarchy, known as top. A given managed object class therefore includes all characteristics that are part of the definition of top, plus all characteristics that are added in the process of defining any subclasses of top that form part of the managed object class's inheritance hierarchy.

6.3 Optionality

In general, the provision of options in managed object class definitions is discouraged, on the grounds that interworking becomes more difficult as the number of options increases. As stated in CCITT Rec. X.720 | ISO/IEC 10165-1, the managed object class definition may include conditional packages which are present in an instance of the managed object class if the specified condition applies. It is the intention that the conditions applied to these packages should relate to standardized features of the resource to which the managed object class applies, or to optional management functions supported by the management system.

6.4 Registration

The process of defining managed object classes requires the assignment of globally unique identifiers, known as object identifiers, to various aspects of the managed object class, such as the managed object class name, attribute types, etc. The values of these identifiers are used in management protocols to uniquely identify aspects of managed objects and their associated attributes, operations and notifications. It is therefore a necessary precursor to the development of a managed object class definition that the standards body or organization concerned should identify or establish a suitable registration mechanism that is capable of issuing object identifier values for its use. CCITT Rec. X.208 | ISO/IEC 8824 specifies the structure of the object identifier and the values of the initial arcs; further information on the establishment of registration mechanisms and registration authorities may be found in CCITT Rec. X.660 |ISO/IEC 9834-1.

Once an item of management information has been assigned an object identifier value, it is a requirement that any revision of the definition of that item shall not alter the semantics of the information. In practice, this means that editorial changes to registered management information definitions are permissible, but the definitions shall not be changed in ways that would be visible in protocol.

All object identifier values registered in systems management Recommendations | International Standards are allocated under the arc

{joint-iso-ccitt ms(9)}

The allocation of arcs below **{joint-iso-ccitt ms(9)}** is defined by this Recommendation | International Standard. The arcs below **{joint-iso-ccitt ms(9)}** are allocated on a per-Systems-Management-standard basis, as shown in Table 1.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Table 1 – Allocation of arcs below {joint-iso-ccitt ms(9)}

Arc	Standard
smo(0)	Systems management overview, CCITT Rec. X.701 | ISO/IEC 10040
cmip(1)	Common management information protocol, CCITT Rec. X.711 | ISO/IEC 9596-1
function(2)	Systems management functions, CCITT Rec. X.7NN | ISO/IEC 10164-X, where X is the part number of the standard in the ISO/IEC numbering scheme, and X.7NN is the corresponding CCITT Recommendation number.
smi(3)	Structure of management information, CCITT Rec. X.72N | ISO/IEC 10165-X, where X is the part number of the standard in the ISO/IEC numbering scheme, and X.72N is the corresponding CCITT Recommendation number.

The allocation of arcs below this level is defined in 6.4.1 to 6.4.5. Further arcs required by existing or future systems management standards will be allocated, as required, by means of amendments to this Recommendation | International Standard.

NOTE – The scheme for the allocation of object identifier values described in this clause and its sub-clauses applies only to the allocation of object identifier values in the systems management standards developed jointly by ISO/IEC JTC1 SC21/WG4 and CCITT SGVII. It is necessary for other standards bodies or organizations that require to allocate object identifier values in the course of the development of management standards to establish their own allocation schemes under an appropriate registration authority. The structure adopted by the systems management standards activity may serve as a useful example of how a suitable allocation scheme may be established, but the final choice of allocation scheme is the responsibility of the organization concerned. In order to improve human readability of object identifier values, it is recommended that the name and number form for the representation of object identifier values, as defined in CCITT Rec. X.208 | ISO/IEC 8824, be used wherever possible.

6.4.1 Object identifier allocation for systems management overview

NOTE – The systems management overview is responsible for the allocation of these arcs; they are included for information only.

Below **{joint-iso-ccitt ms(9) smo(0)}**, the following arcs are allocated for the registration of application contexts, abstract syntaxes and ASN.1 module identifiers, as shown in Table 2.

Table 2 – Allocation of arcs below {joint-iso-ccitt ms(9) smo(0)}

Arc	Purpose
applicationContext(0)	Allocation of application context identifiers
negotiationAbstractSyntax(1)	Allocation of version identifiers to the negotiation abstract syntax
asn1Modules(2)	Allocation of ASN.1 module identifiers

Below **{joint-iso-ccitt ms(9) smo(0) applicationContext(0)}** further arcs are allocated, as specified by CCITT Rec. X.701 | ISO/IEC 10040, for the registration of particular application context identifiers, as shown in Table 3.

Table 3 – Allocation of arcs below {joint-iso-ccitt ms(9) smo(0) applicationContext(0)}

Arc	Purpose
systems-management(2)	Identifier of the Systems management application context

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Below {joint-iso-ccitt ms(9) smo(0) negotiationAbstractSyntax(1)} further arcs are allocated, as specified by CCITT Rec. X.701 | ISO/IEC 10040, for the registration of particular versions of the negotiation abstract syntax, as shown in Table 4.

Table 4 – Allocation of arcs below {joint-iso-ccitt ms(9) smo(0) negotiationAbstractSyntax(1)}

Arc	Purpose
version1(1)	Identifies version 1 of the negotiation abstract syntax

Below {joint-iso-ccitt ms(9) smo(0) asn1Modules(2)} further arcs are allocated, as specified by CCITT Rec. X.701 | ISO/IEC 10040, for the registration of particular ASN.1 module identifiers, as shown in Table 5.

Table 5 – Allocation of arcs below {joint-iso-ccitt ms(9) smo(0) asn1Modules(2)}

Arc	Purpose
negotiationDefinitions(0)	Allocation of version identifiers to the ASN.1 module that contains the definitions associated with the negotiation abstract syntax

Below {joint-iso-ccitt ms(9) smo(0) asn1Modules(2) negotiationDefinitions(0)} further arcs are allocated, as specified by CCITT Rec. X.701 | ISO/IEC 10040, for the registration of particular versions of the ASN.1 module, as shown in Table 6.

Table 6 – Allocation of arcs below {joint-iso-ccitt ms(9) smo(0) asn1Modules(2) negotiationDefinitions(0)}

Arc	Purpose
version1(1)	Identifies Version 1 of the ASN.1 module that contains the definitions associated with the negotiation abstract syntax

6.4.2 Object identifier allocation for CMIP

NOTE – CMIP is responsible for the allocation of these arcs; they are included for information only. CMIP version 1 is obsolete and has been superseded by version 2. Version 1 was documented in ISO/IEC 9596, for which there is no corresponding CCITT Recommendation.

Below {joint-iso-ccitt ms(9) cmip(1)}, arcs are allocated for each version of CMIP, as described in 6.4.2.1 and 6.4.2.2.

6.4.2.1 CMIP version 1

Below {joint-iso-ccitt ms(9) cmip(1)}, arcs are allocated for version 1 of CMIP, as shown in Table 7.

Table 7 – Allocation of arcs below {joint-iso-ccitt ms(9) cmip(1)} for CMIP version 1

Arc	Purpose
version1(1)	Allocation of object identifiers for CMIP version 1

Below {joint-iso-ccitt ms(9) cmip(1) version1(1)}, arcs are allocated for the purposes described in ISO/IEC 9596, as shown in Table 8.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Table 8 – Allocation of arcs below {joint-iso-ccitt ms(9) cmip(1) version1(1)}

Arc
aAssociateUserInfo(1)
aAbortUserInfo(2)
protocol(3)
abstractSyntax(4)

6.4.2.2 CMIP version 2

Below **{joint-iso-ccitt ms(9) cmip(1)}**, arcs are allocated for version 2 of CMIP, as shown in Table 9.

Table 9 – Allocation of arcs below {joint-iso-ccitt ms(9) cmip(1)} for CMIP version 2

Arc	Purpose
modules(0)	Allocation of object identifiers for CMIP ASN.1 modules
cmip-pci(1)	Allocation of object identifiers for CMIP protocol control information

Below **{joint-iso-ccitt ms(9) cmip(1) modules(0)}**, arcs are allocated for the purposes described in CCITT Rec. X.711 | ISO/IEC 9596-1, as shown in Table 10.

Table 10 – Allocation of arcs below {joint-iso-ccitt ms(9) cmip(1) modules(0)}

Arc
aAssociateUserInfo(1)
aAbortUserInfo(2)
protocol(3)

Below **{joint-iso-ccitt ms(9) cmip(1) cmip-pci(1)}**, arcs are allocated for the purposes described in CCITT Rec. X.711 | ISO/IEC 9596-1, as shown in Table 11.

Table 11 – Allocation of arcs below {joint-iso-ccitt ms(9) cmip(1) cmip-pci(1)}

Arc
reserved1(1)
reserved2(2)
reserved3(3)
abstractSyntax(4)

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

6.4.3 Object identifier allocation for function standards

Below **{joint-iso-ccitt ms(9) function(2)}**, arcs are allocated to identify each function Recommendation | International Standard as shown in Table 12.

Table 12 – Allocation of arcs below {joint-iso-ccitt ms(9) function(2)}

Arc	Standard
partX(X)	CCITT Rec. X.7NN | ISO/IEC 10164-X where X is the part number of the Systems Management Function in the ISO/IEC numbering scheme, and X.7NN is the corresponding CCITT Recommendation number.

Below **{joint-iso-ccitt ms(9) function(2) partX(X)}**, arcs are allocated as shown in Table 13.

Table 13 – Allocation of arcs below {joint-iso-ccitt ms(9) function(2) partX(X)}

Arc	Purpose
standardSpecificExtension(0)	Standard-specific extensions to the allocation scheme
functionalUnitPackage(1)	Allocation of functional unit package identifiers
asn1Module(2)	Allocation of ASN.1 module identifiers
managedObjectClass(3)	Allocation of managed object class identifiers
package(4)	Allocation of package identifiers
parameter(5)	Allocation of parameter identifiers
nameBinding(6)	Allocation of name binding identifiers
attribute(7)	Allocation of attribute identifiers
attributeGroup(8)	Allocation of attribute group identifiers
action(9)	Allocation of action types
notification(10)	Allocation of notification types

Within each function Recommendation | International Standard, further arcs may be allocated below this level (e.g., to allocate particular attribute identifiers), as required by the function Recommendation | International Standard.

6.4.4 Object identifier allocation for SMI standards

Below **{joint-iso-ccitt ms(9) smi(3)}**, arcs are allocated to identify each SMI Recommendation | International Standard as shown in Table 14.

Table 14 – Allocation of arcs below {joint-iso-ccitt ms(9) smi(3)}

Arc	Standard
partX(X)	CCITT Rec. X.72N | ISO/IEC 10165-X where X is the part number of the standard in the ISO/IEC numbering scheme, and X.72N is the corresponding CCITT Recommendation number.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Below **{joint-iso-ccitt ms(9) smi(3) partX(X)}**, arcs are allocated as shown in Table 15.

Table 15 – Allocation of arcs below {joint-iso-ccitt ms(9) smi(3) partX(X)}

Arc	Purpose
standardSpecificExtension(0)	Standard-specific extensions to the allocation scheme
asn1Module(2)	Allocation of ASN.1 module identifiers
managedObjectClass(3)	Allocation of managed object class identifiers
package(4)	Allocation of package identifiers
parameter(5)	Allocation of parameter identifiers
nameBinding(6)	Allocation of name binding identifiers
attribute(7)	Allocation of attribute identifiers
attributeGroup(8)	Allocation of attribute group identifiers
action(9)	Allocation of action types
notification(10)	Allocation of notification types

Within each Recommendation | International Standard, further arcs may be allocated below this level (e.g., to allocate particular attribute identifiers), as required by that Recommendation | International Standard.

6.4.5 Object identifier allocation for actual class

The object identifier value

{joint-iso-ccitt ms(9) smi(3) part4(4) managedObjectClass(3) actualClass(42)}

is allocated by this Recommendation | International Standard to convey the semantics of *actual class* as defined in CCITT Rec. X.720 | ISO/IEC 10165-1. When used to specify the base managed object class in a CMIS operation service request, this object identifier value indicates that the recipient of the systems management operation shall respond as a member of its actual class.

6.5 Conformance

CCITT Rec. X.701 | ISO/IEC 10040 specifies general conformance related requirements for management information standards.

6.6 Complexity of managed object definitions

Through the modelling process, complexity in the managed object definitions should be minimized. In any case, management operations should be no more complex than the corresponding properties of the OSI entity involved.

6.7 Managed object creation and deletion

Creation and deletion of managed object instances may occur in the following ways:

- managed objects may be created and deleted by management protocol interactions. Create and delete operations are defined for this purpose, with associated semantics;

- managed objects may be created and deleted as a result of the operation of the resource to which they relate, typically a protocol machine. Create and delete operations would not be defined in this case. An example is the representation for management purposes of connections;

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

- managed objects may be created and deleted by other means. Create and Delete operations are not defined for them. An example is a managed object which is always created automatically when a piece of equipment is initialized, and which cannot be deleted through management.

The choice among these three methods for managed object creation may differ from the choice for managed object deletion.

In some cases, there may be only one means by which a managed object of a particular class may be created or deleted; in other cases, there may be the possibility to create or delete managed objects of a particular class by means of more than one of these mechanisms.

6.7.1 Initial value managed objects

When a managed object is created, it may be desirable to provide the capability to allocate default values to be used on creation which are themselves subject to modification by management operation. This may be achieved by the specification of an Initial Value Managed Object (IVMO), whose attributes are modifiable by management operation, and which is capable of providing default values for corresponding attributes on the creation of instances of another managed object class.

When a new managed object is created using an IVMO, the values of attributes in the IVMO are used as initial values of corresponding attributes in the new managed object. The managed object class definition may specify how the IVMO is selected. The specification of the IVMO shall define the circumstances in which it provides the initial values, how it provides the initial values, and to which attributes the initial values it provides are applicable.

When management operations are used to modify the attributes of an IVMO, attributes of managed objects previously created using that IVMO are not affected. Similarly, management operations performed upon the attributes of managed objects created using an IVMO do not affect the attributes of the IVMO.

6.7.2 Sources of initial attribute values

Initial attribute values for managed objects, used at creation time, are obtained from a number of sources, as defined in CCITT Rec. X.720 | ISO/IEC 10165-1. When an attribute represents a specific value that must be consistent with an underlying resource, this value forms the mandatory initial value used at creation time.

7 General principles for managed object definition

The general principles described here are intended for the guidance of managed object definers, and to promote consistency between managed object definitions; for this reason, managed object definers are encouraged to apply the guidance offered wherever it is applicable.

7.1 Commonality

Managed object definers should strive to identify and use as a basis

- common managed object classes, defined in CCITT Recommendations | International Standards;
- common managed object classes and other properties as defined in CCITT Rec. X.721 | ISO/IEC 10165-2.

Managed object definers should also strive to consider and re-use definitions originating in other groups in order to increase commonality of definitions. This objective may be met by development of models of things to be managed that are common to a number of groups of managed object definers.

7.2 What to manage

The definition of managed object classes and their components should fulfil clearly justified requirements related to particular management objectives. Such requirements are likely to include the management of peer protocol aspects of the operation of a layer or sub-layer and perceived problems not specifically reported by the underlying service provider across the service boundary (e.g., Quality Of Service provided by underlying service not meeting acceptable levels). It is important to retain justification for each management objective during the development of the management

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

information definitions. Comments should be used to explain how each component of a management information definition, (e.g., managed object classes, attributes, operations, notifications, etc.) relates to this justification.

Things of interest to management should be recorded via the managed objects that represent the resources where the things happen. That is, if a managed object has been defined representing a particular resource (for example, a connection), then information concerning that resource should be reflected through the corresponding managed object(s) and not elsewhere.

7.3 Structuring

A number of techniques are available for representing structure in managed objects, to reflect groupings of data or functionality. Each of these techniques has advantages and disadvantages; the choice of the most appropriate technique(s) for a particular specification requirement depends on a number of criteria, as described below.

The structuring techniques described in CCITT Rec. X.720 | ISO/IEC 10165-1 include

- attribute groups;
- subclasses (specialization);
- multiple inheritance;
- contained managed objects;
- packages.

Groupings of attributes, operations and notifications may be defined which are present or absent based on a standardized condition, such as the choice of particular options in a base standard. Such groupings of functionality are either present or absent as a whole. Groupings of functionality may arise as a consequence of option selection in the layer Recommendation | International Standard for the resource (e.g., provision of Transport Class 4), leading to additional management requirements or capability, or as a consequence of support for a defined management function (e.g., accounting). These groupings of functionality are defined using the conditional package techniques provided by the managed object class template.

One important criterion in the choice of structuring techniques is the static or dynamic presence of the grouping. If the presence of the grouping is fixed at specification time, then the use of attribute groups, subclasses, multiple inheritance, or contained managed objects may be appropriate. If the presence is fixed at implementation, installation or instantiation time, then the use of contained managed objects or conditional packages may be appropriate. If the presence of the grouping can change through the life of the containing/encapsulating managed objects, then the use of contained managed objects that are dynamically created and deleted may be appropriate.

Another criterion is whether there are multiple instances of the grouping within the managed object. Where this is the case, the use of contained managed objects is appropriate; otherwise, any of the five structuring techniques may be appropriate.

7.4 Managed objects

7.4.1 Instantiation of superclasses

Managed object classes that are never instantiated may be defined to provide a common base from which to specialize subclasses; for example, a generic virtual circuit managed object class may be defined, of which permanent and switched virtual circuits could be subclasses.

In some cases, particularly where subclasses are defined in order to revise a standard, there may be superclasses of which instances may be created.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

7.4.2 Unrestricted superclasses

The rules for inheritance limit the ways in which the required value sets and permitted value sets of attributes of a managed object class can be modified when defining a subclass of that class. In the same way, the rules limit the ability to add parameters to actions and notifications. These limitations ensure that the subclass is compatible with the superclass.

For this reason, when defining a managed object class that is expected to be a superclass of subsequent managed object classes, it is useful to make provision for these kinds of extension. Although not all extensions can be anticipated and provided for, the following techniques allow for a wide variety of extensions while maintaining compatibility:

- define the syntax (type) of each attribute to include all values which might reasonably fit within the semantics of the attribute, even if some of those values are not immediately required or desired;
- provide extension capabilities in each action and notification definition;
- define an "unrestricted superclass" that includes these elements, without further restrictions, as the basis for defining more restricted subclasses. For attributes, this means an empty required value set and a permitted value set equal to the attribute syntax;
- define specific subclasses of this unrestricted superclass, which place the required restrictions on attributes, actions and notifications.

The managed object definer may choose to provide extension capabilities in only some of the attributes, actions and notifications of an unrestricted superclass.

7.5 Attributes

7.5.1 Attribute value sets

In some cases, options in the base Recommendation | International Standard permit the value set of an attribute to vary in accordance with implementation choices. A typical example of this would be where the base Recommendation | International Standard permits a wide range of packet sizes, but a conformant implementation of the Recommendation | International Standard may support a more limited range. Where this situation exists, the attribute behaviour definition shall identify what the possibilities are.

It may be necessary to define null values as permitted values in the value set of an attribute, or, in the case of attributes of an IVMO, it may be necessary to define attribute values to which particular semantics are attached, such as "create managed object with null as the value of the corresponding attribute" or "ignore this attribute as a source of an initial value". Techniques for defining such values include defining the abstract syntax as a choice type, where one choice defines the normal value set of the attribute and other choices define values to which particular semantics are attached.

Definition of the permitted value set of an attribute may be achieved in a number of ways, including

- defining the attribute value set statically, as part of the definition of the managed object class;
- defining a second attribute, whose value indicates the value set that the attribute may contain.

The former technique minimizes the number of attribute definitions associated with a managed object class; however, if a number of variants of the attribute are required, the latter technique avoids the necessity to define multiple subclasses to handle each possible value set variant.

7.5.2 Attribute types

Structured attributes, where the sequence type, sequence-of type or set type is used as the base type in attribute syntax definition, should only be used where it is not required to individually modify elements of the attribute, as these ASN.1 types correspond to single-valued attribute types. Where it is necessary to address a number of attributes together while maintaining the ability to manipulate each one individually, attribute groups may be defined, and if needed, action and behaviour definitions may be used to clarify any dependence between group members.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

NOTE – This does not imply that there is a behaviour specification specific to the attribute group itself that does not also apply to the attributes when treated individually.

7.6 Attribute value relationships

The value of an attribute may be constrained according to some function of other attribute values. All relationships of this nature shall be identified.

Where an attribute value is constrained by other attributes in the *same* managed object, a synchronization requirement may exist for a single management operation, where failure to change the value of one or more of the related attributes would result in the related attributes having illegal values. If such a requirement exists, it shall be documented as part of the behaviour definition of the managed object class.

Where an attribute value is constrained by other attributes in *different* managed objects, if a synchronization requirement also exists, it shall be documented in behaviour associated with the managed object class. In this case, and where the managed objects are all in the same managed system and a single management operation can modify the attributes, the requirement is enforced by the use of the atomic cross-object synchronization capability of CMIS.

The general problem of synchronization across multiple management operations, across different attributes in different managed objects or across multiple managed systems cannot be enforced by means of current systems management protocol alone.

7.7 Modelling of SAPs

There is a general requirement to represent, as part of the managed object structure associated with the layers, the relationship between (N)-entities, (N)-selectors and (N+1)-entities. A number of possible solutions exist, for example

- model the relationship as information contained in managed objects of the (N+1)-layer;
- model the relationship as information contained in managed objects of the (N)-layer;
- model the relationship as information contained in managed objects that do not belong to either layer, i.e., managed objects that are common to all layers.

The practice recommended by this Recommendation | International Standard is that the second approach should be adopted. Specifically, (N)-SAPs should be represented by individual managed objects, which would have address (and other) information as attributes, together with relationship attributes pointing to the (N)- and (N+1)-entity managed objects associated with the (N)-SAPs. In order to enforce the consistency requirements on selectors necessary to make OSI addressing unambiguous, it is proposed that (N)-SAP managed objects should be **contained within** the managed objects corresponding to the (N)-entities to which they are bound.

NOTE – The consistency requirement referred to here is the requirement that the address of an (N)-entity combined with an (N)-selector is required to uniquely identify an (N+1) entity (or a set of (N+1)-entities of the same type). Given that this requirement amounts to a uniqueness requirement placed on the allocation of (N)-selector values to be used in the context of a given (N)-entity, maintenance of this consistency requirement may be more simply achieved if such selector information is maintained by the (N)-entity rather than the (N+1)-entities.

7.8 Statistics

7.8.1 Consistency

Managed object definers should strive to achieve consistency of statistics across layers, by adopting some principles based on CCITT Rec. X.200 | ISO 7498, in particular, the concept of recording information that is of interest to management via managed objects that represent the resources to which the information relates.

Candidate features of the (N)-layer for which statistics may be recorded are

- local errors;
- successful peer-to-peer exchanges;

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

- peer-to-peer failures;
- service rejections.

For example, applying the previously defined principles in this document to the definition of a Connection in CCITT Rec. X.200 | ISO 7498 leads to the identification of the following primary statistics:

- number of (N)-entity connections established with other (N)-layer peer entities;
- number of (N)-entity connection establishment local failures;
- number of (N)-entity connection establishment peer-to-peer negotiation failures;
- number of underlying service provider (N-1)-connection establishment rejections.

This set of statistics provide a consistent view of what is happening at each layer (in the connection-oriented case) without duplication of counters.

NOTE – Similar models are required for errors, disconnections, etc.

7.8.2 PDU counters

Managed object definers should specify counters of (N)-layer PDUs (and PDU octets) rather than SDUs (and SDU octets).

NOTE – It is thought likely that it is only necessary to count the number of PDU octets at a limited number of (N)-layers.

7.8.3 Overlaps

Managed object definers should strive to achieve consistency and avoid unnecessary duplication or overlap of statistics. For example, maintain a count of first PDU send requests and a count of retry PDU send requests, so that it will not be necessary to increment both counters at the same time. The sum of these counters yields the total PDUs sent.

7.8.4 Non-resettable counters

Non-resettable counters are recommended, as they permit multiple observers without the need for complex interlocking mechanisms associated with reset co-ordination.

7.8.5 Event counters

A count should be maintained for managed resource events that result in the issuing of a notification, as the generation of a CMIS M-EVENT-REPORT may be suppressed by the event forwarding discriminators.

7.9 Counters

To manage a counter, its modulus must be known, otherwise a manager cannot determine the value at which the counter "wraps". There are therefore at least four possibilities when defining counters:

- counters never wrap;
- the modulus is fixed as part of the managed object class definition;
- the modulus is defined in a related attribute;
- the modulus is defined on a per-implementation basis and is specified in the MOCS.

NOTE – In the managed object classes defined by ISO/IEC JTC1 for layers 1 to 4, the approach of using counters that never wrap has been adopted.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

7.10 Timers

There are advantages to be gained in adhering to a common specification of the precision with which systems must store the values of timer attributes used in management communications. The relationship between these attribute values and the actual operation of the timers in the protocol is documented in behaviour statements.

NOTE – In the managed object classes defined by ISO/IEC JTC1 for layers 1 to 4, in order to encompass a large enough range without inordinate precision, a floating point representation is used to express timer values, with a mantissa length of 16 bits and an exponent length of up to 16 bits. (This does not imply a requirement that floating point *arithmetic* will be performed.) Systems are expected to be able to store values with this precision. Other constraints permitting, a request to set a timer attribute to that precision must be accepted.

7.11 Updating of attributes

Managed object class definers should ensure that, when defining attributes which can be updated both by management operation and by the normal operation of the resource, the effects of concurrent update are defined. In particular, the effect of a replace attribute value operation may be lost if the resource also updates the same attribute.

7.12 Precision of attributes

A managing system may attempt to set an attribute value to a higher precision than is supported by an agent system. Such higher precision values may be approximated to a neighbouring value of the defined precision.

7.13 Managed object identification

Each managed object class definition for which instances may exist shall include at least one attribute suitable for use as a naming attribute for the managed object. A suitable attribute is a mandatory attribute that is testable for equality, whose semantics permit its value to remain fixed for the lifetime of each managed object that uses it for naming, and whose identifier and value shall uniquely identify the managed object from all others named by the same superior object.

When a managed object is deleted, the value assigned to its naming attribute becomes available for re-use, to identify subsequent managed objects created within the same superior object.

If it is necessary to guarantee that one instance of a managed object class remains distinguishable from all other instances of that class after it has been deleted, it is necessary to define an additional attribute to be included in the managed object class definition - a *unique identification attribute* - whose semantics ensure unique identification is maintained over time. Managed object classes that do not have this requirement need not include a unique identification attribute in their definition.

The unique identification attribute shall be read-only and, when included in a managed object, be included in notifications emitted by that managed object.

7.14 Notifications

7.14.1 Denial of service

Notifications should not be issued regarding the withdrawal of an underlying service, as the managed object(s) representing the underlying service shall be responsible for reporting any abnormal reason for such termination. This is intended to inhibit an abnormal termination rippling up the layers and generating phantom notifications.

7.14.2 Information conservation

Notifications contain information associated with an event that may otherwise be lost by maintaining statistics only. For example

- the header field of a received PDU for which a protocol error has been detected;
- statistics for a connection that is about to be terminated, for a specific reason;
- timing of a sequence of particular events.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

7.15 Use of operations

A managed object class definition should include appropriate operations. For invocations by the managed system, notifications are specified. For invocations by the managing system, operations are specified according to their direct effect on managed objects in the managed system, as follows:

a) if the direct effect is to create an instance of a managed object class, the Create operation is used. The Create operation is not used for complex activities which require the coordinated creation of many managed objects, when a managed object is created as a side effect of a change in another managed object, or when support managed objects are created due to a change in the state of another managed object;

b) if the direct effect is to delete a managed object, then the Delete operation is used;

c) if the direct effect is to set the values of attribute(s) of a managed object to a specified value(s), then the Replace attribute value operation is used;

d) if the direct effect is to set the values of attribute(s) to default value(s) (provided such defaults have been defined), then the Replace with default value operation is used;

e) if the direct effect is to add or remove members of set-valued attribute(s) of a managed object, then the Add member or Remove member operations are used;

f) if the direct effect is to retrieve attribute value(s) from a managed object, then the Get attribute value operation is used;

g) in other cases, e.g., where there is no direct effect, or the direct effect is a combination of those listed, or where there is some other effect on the object as a whole, then an Action operation is used. Examples of where an action operation is used include

   1) where it is not possible to define the required operation on a set of managed objects by means of scoping and filtering techniques in conjunction with Get attribute value, Replace attribute value, Replace with default value, Create, Delete, Add member or Remove member operations;

   2) where creation of more than one managed object as an atomic operation is required;

   3) where several objects without common attributes are to be affected;

   4) where the request or response for the operation contains information that is not modelled by the attributes of managed objects.

The concepts of direct effect and indirect effect are discussed in CCITT Rec. X.720 | ISO/IEC 10165-1.

8 Notational tools for managed object definition

8.1 Overview of notational tools

The templates defined in this clause provide a common set of tools and a common notation for the representation of various aspects of a managed object class definition and its associated naming structure. Formal definitions of each template are contained in 8.3 to 8.11; the syntactic conventions used in these formal definitions are specified in 8.2. These formal definitions define the constructs that each template shall or may contain and the order in which the constructs shall appear within each template. Examples of the use of these tools are contained in Annex A.

The structure and behaviour of a managed object class is primarily defined by means of the Managed Object Class template. This template identifies the inheritance relationships that exist between the managed object class and other managed object classes, and the packages of behaviour, attributes, notifications and operations that are included in the managed object class definition. In order to allow re-use of parts of this specification in the specification of other managed object classes, additional templates are defined to provide for the specification of attributes (individual and group), behaviour, actions, notifications, parameters and packages. These further templates are "called up" by other templates by means of the referencing mechanism defined in 8.2; this mechanism allows references to be made in one standard to specifications that are contained in other standards, hence allowing generic definitions to be made available

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

for use in managed object class definitions in addition to local definitions. These further templates may also be included "in-line" if so desired.

The naming of a managed object class is defined by means of the Name Binding template. This template identifies the managed object class being named and defines a relative distinguished name that can be used to name instances of the class in the context of a particular superior class. This template also provides for the specification of relationships that exist between two object classes as a consequence of a particular name binding.

8.2 Conventions used in template definitions

The start of a template consists of a `template-label` and a `TEMPLATE-NAME`. A template contains one or more constructs, each of which is named by a `CONSTRUCT-NAME` and each may have a `construct-argument`. The `construct-argument` may in turn consist of a number of elements, as called for by the definition of the particular construct. Each instance of use of a template declares a unique `template-label` by which that instance may be referenced from other templates, and if the `REGISTERED AS` construct is present, assigns a value of an ASN.1 object identifier under which the instance has been registered. The semicolon character is used to mark the end of each construct (except `REGISTERED AS` and `DEFINED AS`) and to mark the end of a template.

In order to simplify the structure of the templates, for example where the same syntactic structure is repeated in a template definition, supporting syntactic definitions may be defined. If any such supporting syntactic definitions are required in order to complete the template definition, these are introduced by the keywords

```
supporting productions
```

at the end of the template definition, and consist of a number of productions of the form

```
<definition-label> -> <syntactic-definition>
```

The `definition-label` allows the definition to be referenced by the template definition or by other `supporting productions` and the `syntactic-definition` gives the expansion of the definition, using the syntactic conventions defined in the remainder of this sub-clause. In the case of a `syntactic-definition` that defines a number of alternative strings, references to the `supporting production` that contains it are assumed to be evaluated to a single string chosen from the list of alternatives.

The template definitions are based on the following syntactic conventions

a) all terminal symbols and keywords that form part of a template definition are case-sensitive;

b) where necessary in order to render the syntax of a template unambiguous, each element of a template shall be separated from adjacent elements by one or more delimiters. Valid delimiters are the space character, the end of a line, a blank line or a comment. One or more delimiters shall appear between

   1) a `template-label` and a `TEMPLATE-NAME`;

   2) a `TEMPLATE-NAME` and a `CONSTRUCT-NAME`;

   3) a `CONSTRUCT-NAME` and a `construct-argument`.

   One or more delimiters may be introduced between any other pair of elements within a template, and where a `construct-argument` consists of a number of distinct elements, delimiters may be introduced between them. Delimiters shall not otherwise be introduced within elements of the template unless the definition of the template explicitly permits their introduction;

c) spaces, blank lines, comments and the end of a line are significant only as delimiters;

d) a comment is introduced by the character pair

```
--
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

and is terminated either by the character pair

```
--
```

or by the end of a line, whichever occurs first. A comment is equivalent to a space for the purposes of interpreting the templates defined in this Recommendation | International Standard. Comments have no normative significance;

e) the character

```
;
```

shall be used to mark the end of each construct within a template (except `REGISTERED AS` and `DEFINED AS`) and to mark the end of a template;

f) the notation used for representing object identifiers shall be the value notation defined in CCITT Rec. X.208 | ISO/IEC 8824 for representing object identifier values; i.e., the production

```
object-identifier -> <ObjectIdentifierValue>
```

is assumed to be a supporting production for all template definitions in this document, where `ObjectIdentifierValue` refers to the corresponding notation defined in CCITT Rec. X.208 | ISO/IEC 8824;

g) strings surrounded by

```
[ ]
```

delimit parts of a template definition that may either be present or absent in each instance of use of the template. If the closing brace is followed by an asterisk, i.e.,

```
[ ]*
```

the contents of the braces may appear zero or more times. The circumstances under which these parts of the definition may be omitted or repeated are dependent upon the definition of the template type;

h) strings surrounded by

```
<>
```

delimit strings that shall be replaced in each instance of use of a template. The structure and meaning of the replacement string is dependent upon the string type;

i) upper case strings denote Keywords which are required to be present in each instance of use of a template, unless they are enclosed in

```
[ ]
```

to indicate that their presence is optional;

j) the character

```
¦
```

is used as a delimiter for alternative strings in the `syntactic-definition` of a `supporting production`. Where a `supporting production` is used to define alternative strings, the opening delimiter of the first alternative is the symbol `->`, the character ¦ is the closing and opening delimiter for subsequent alternatives, and the closing delimiter of the final alternative is the first end of line encountered following its opening delimiter;

k) a `template-label` shall be unique within the Recommendation | International Standard or document in which it is declared. In a multi-part Recommendation | International Standard or document where the

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

individual parts are normally maintained and distributed separately, a `template-label` shall be unique within the part in which it is declared.

The requirement for uniqueness of `template-labels` is independent of the type of the template being labelled. For example, if the label `label1` is used in a document to label an instance of use of a template, it is not permitted to use the label `label1` in the same document to label another instance of use of a template of the same type or of a different type.

Where a `template-label` is declared in document A and referenced in document B, the reference in document B shall be prefixed by the globally unique name of document A. In the case of documents named by an internationally recognised naming authority, such as CCITT or ISO/IEC, the registered alphanumeric designator of the document shall be used as the identifier, such as `"CCITT Rec. X.722 (1992) | ISO/IEC 10165-4 : 1992"`. The format of this string shall be as specified by the naming authority concerned for references to its documents. Where the document referenced is jointly developed and published by CCITT and ISO/IEC, the designator of the document shall include both the CCITT and the ISO/IEC document designators separated by a "|", as shown in this example. Where a globally unique name is not already available, it is permissible to assign the value of an object identifier to the referenced document, and use this value as a globally unique document name. The syntax of a `template-label`, defined using the above notation, is as follows

```
[document-identifier :] <label-string>

document-identifier -> "<standard-name>" | object-identifier
```

A `label-string` may include any number of the following characters

1) upper or lower case alphabetic characters;

2) the digits `0-9`;

3) the character

   `-`

4) the character

   `/`

in any order, commencing with a lower case alphabetic character, with the exception that the character pair

```
--
```

shall not appear in a label-string. For example, the following `template-label`

```
"CCITT Rec. X.722 (1992) | ISO/IEC 10165-4 : 1992":exampleObjectClass
```

constitutes a globally unique label for the definition of `exampleObjectClass` contained in Annex A.

Label references that are not prefixed by a `document-identifier` are assumed to be references to labels declared in the document in which the reference appears.

l) wherever a `template-label` is present in a template as a pointer to another template, it may be replaced by the entire text of the referenced template itself (including the template's label). This allows a template to include the templates it references (sub-templates) "in-line" while maintaining the ability for other templates to refer to the sub-templates so defined. In effect, the `supporting production`

```
template-label -> template-definition
```

is assumed for all instances of `template-label` and `template-definition`.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

m) wherever it is necessary to refer from a template to an ASN.1 type or value definition, the name of the ASN.1 type or value is prefixed by the module name of the ASN.1 module which contains the type or value definition. The module name used is assumed to refer to an ASN.1 module that is contained in the same document that contains the template from which the type or value reference is made. The supporting productions

```
type-reference   -> <module-name>.<type-name>
value-reference  -> <module-name>.<value-name>
```

are therefore assumed for all template definitions that refer to ASN.1 types or values, where `module-name` is the name assigned to an ASN.1 module contained in the document that makes the reference, and `type-name` and `value-name` are names assigned to ASN.1 type or value definitions contained in that module. Where it is necessary to refer to type or value definitions contained in other documents, this may be achieved by means of a local ASN.1 module which makes use of the ASN.1 `IMPORTS` mechanism to import the appropriate type or value definitions.

n) wherever it is necessary to include text in a template, the text is included in the form of a string of characters, optionally starting and ending with a `text-delimiter` character chosen from the following characters

```
! " # $ % ^ & * ' ` ~ ? @ \
```

If a `text-delimiter` character is used, the same character shall be used at the start and end of the string, and wherever that `text-delimiter` character appears in the body of the text string, it shall be replaced by two occurrences of that character. If a `text-delimiter` character is not used, then the text string shall not contain any punctuation character that is a valid successor to the text string in the template definition in which the text string is used.

The supporting productions

```
delimited-string ->    text-delimiter <text-string> text-delimiter |
                       <text-string>
text-delimiter ->      ! | " | # | $ | % | ^ | & | * | ' | ` | ~ |
                       ? | @ | \
```

are therefore assumed for all templates that permit the use of a `delimited-string`, where `text-string` is an arbitrary sequence of characters, and if the `text-delimiter` has been used, all occurrences of that delimiter character in `text-string` have been replaced by a pair of `text-delimiter` characters.

With the exception of the rules pertaining to the use of delimiters, the internal structure of a `text-string`, and in particular, the use of the comment structure defined in this Recommendation | International Standard, has no significance with respect to the provisions of this Recommendation | International Standard. The meaning of the entire `text-string` must therefore be assumed to carry normative significance, unless explicitly stated otherwise in the document in which the notation is used.

8.3 Managed object class template

8.3.1 Overview

The Managed Object Class template forms the basis of the formal definition of a managed object. Elements in the template allow the class to be placed at the appropriate node of the inheritance tree, the various characteristics of the class to be specified, and the behaviour of the class to be defined. The major elements of the definition are defined below.

8.3.1.1 Inheritance

Each managed object class defines the superclass(es) from which it has been derived. Characteristics of the superclass(es) are inherited by the subclass; the subclass definition may add to these characteristics (specialization) but may not remove any characteristics of the superclass. Ultimately, all classes are subclasses of top.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

8.3.1.2 Mandatory packages

The managed object class definition includes the packages of behaviour, attributes, operations and notifications that provide a complete specification of the behaviour that characterizes all instances of the class.

8.3.1.3 Conditional packages

The managed object class definition includes the specification of packages of behaviour, attributes, operations and notifications that are present in instances of that class as a consequence of a specified condition.

8.3.1.4 Class naming

The managed object class definition shall include a class name which may be used to refer to the class in management protocol. This is achieved by registration of an object identifier value which identifies to the managed object class definition.

8.3.2 Template structure

```
<class-label>    MANAGED OBJECT CLASS

       [DERIVED FROM          <class-label>
                              [,<class-label>]* ;
       ]
       [CHARACTERIZED BY      <package-label>
                              [,<package-label>]* ;
       ]
       [CONDITIONAL PACKAGES  <package-label>
                                 PRESENT IF condition-definition
                              [,<package-label>
                                 PRESENT IF condition-definition]* ;
       ]

REGISTERED AS object-identifier ;

supporting productions

condition-definition -> delimited-string
```

8.3.3 Supporting definitions

8.3.3.1 DERIVED FROM <class-label> [,<class-label>]*

The DERIVED FROM construct shall be present in all managed object class definitions other than top. It is therefore the case that top is a superclass of all managed object classes other than itself.

The class-label identifies a managed object class from which the managed object class has been derived; i.e., a managed object class which is one of the managed object class's immediate superclasses. As multiple inheritance is permitted, a managed object class may have more than one immediate superclass.

The process of inheritance (specialization) requires all the characteristics of the superclass(es) to be included in the definition of the subclass.

Characteristics that are inherited from a superclass shall not be repeated in the documentation of the subclass unless one of the techniques described in this Recommendation | International Standard for extending or modifying a definition inherited from a superclass is being used. The DERIVED FROM construct is therefore presumed to automatically import all characteristics from the superclass definition(s). These characteristics may be augmented or modified by elements defined within the CHARACTERIZED BY and CONDITIONAL PACKAGES constructs.

NOTE 1 – A list of all managed object classes that the managed object class definition inherits characteristics from should be included, as a comment, in the documentation of the managed object class definition.

Where multiple inheritance results in the same element definition being multiply imported (as could happen, for example, if two superclass definitions include the same attribute), the subclass is assumed to contain a single copy of the definition concerned.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

From the point of view of resolving any conflicts that may exist between the elements defined in the packages and conditional packages inherited or included in the managed object class definition by specialization, all packages that are to be included in a particular managed object class are treated identically. Each package defines a number of elements, which are treated as follows

a) BEHAVIOUR. Packages included in a subclass extend the inherited behaviour. The behaviour of a managed object class shall be expressed in a way that takes account of the possible presence or absence of conditional packages;

NOTE 2 – In some circumstances, subclasses may be defined where no additional behaviour definitions are required over and above those that are inherited from the superclass(es).

b) ATTRIBUTES. Attributes may be specified in the packages included in the subclass definition. Where the ATTRIBUTES construct of a package identifies an attribute that is multiply defined in the managed object class, the following rules apply:

1) a single attribute of that type shall be included in the instantiated managed object;

2) the resultant `propertylist` is the logical OR of the `propertylist` included in the subclass and the inherited `propertylist`(s), with the exception of PERMITTED VALUES, where the instantiated permitted value set is the set intersection of all permitted value specifications for that attribute type, and REQUIRED VALUES, where the instantiated required value set is the intersection of the instantiated permitted value set with the set union of all required value specifications for that attribute type. For DEFAULT VALUE or INITIAL VALUE, if conflicting values are specified for the attribute in the collected definitions, then a package included in the subclass shall resolve the conflict;

3) the parameters associated with a given attribute are the set union of all parameters associated with the Attribute template and all parameters associated with the attribute in any package that is instantiated.

If the managed object class is intended to be instantiated, there shall be at least one attribute defined as part of the class definition, as it is necessary to identify an attribute that can be used to name instances of a managed object;

NOTE 3 – Attributes used for naming may be chosen from any attributes that are part of the class definition. This includes all attributes that have been inherited from superclasses and all attributes that have been added to the class by the process of specialization.

c) ATTRIBUTE GROUPS. For an extensible attribute group, the membership of an attribute group in an instance of the subclass is the set union of all attributes defined in the Attribute Group template, plus all attributes added to that group in the superclass(es) or the subclass;

d) ACTIONS. Actions may be included in the subclass definition; these may be additional actions to those inherited from superclasses, or may include additional parameters for an inherited action. The parameters associated with a given action are the set union of all parameters associated with the Action template and all parameters associated with the action in any package that is instantiated;

e) NOTIFICATIONS. Notifications may be included in the subclass definition; these may be additional notifications to those inherited from superclasses, or may include additional parameters for an inherited notification. The parameters associated with a given notification are the set union of all parameters associated with the Notification template, and all parameters associated with the notification in any package that is instantiated.

If a package is included in a managed object class definition more than once, by inheritance and/or multiple inclusion in the Managed Object Class template, the resultant `condition-definition` associated with the package is the logical OR of all the `condition-definitions` in the collected set of definitions. For this purpose, packages included in CHARACTERIZED BY constructs (mandatory packages) are treated as if they had been included in a CONDITIONAL PACKAGES construct with a condition definition of PRESENT IF !TRUE!.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

The characteristics within a package (mandatory or conditional) shall only depend on the characteristics of other conditional packages if the associated package conditions ensure that the required characteristics will be present in all managed objects where the first package is present.

8.3.3.2 CHARACTERIZED BY <package-label> [,<package-label>]*

This construct, if present, allows one or more mandatory packages of behaviour, attributes, operations and notifications to be included in the managed object class definition, in addition to those that are part of the definition as a result of the DERIVED FROM construct. The package-label identifies the package definition that is to be included. Specifying the label of a package that is also included in the managed object class definition as a conditional package makes that package mandatory in this managed object class and its subclasses.

8.3.3.3 CONDITIONAL PACKAGES <package-label> PRESENT IF condition-definition [,<package-label> PRESENT IF condition-definition]*

Present if one or more conditional packages are to be included in the class. The package-label identifies the package definition that is applicable. The condition-definition is a description of the condition which, if true, requires that the package be included in an instance of the class. No restriction is placed on the structure or character set used to represent the condition-definition. The condition shall meet the requirements for conditional packages presented in CCITT Rec. X.720 | ISO/IEC 10165-1. For example

```
CONDITIONAL PACKAGES class-4-attributes PRESENT IF
      'the corresponding protocol entity supports Class 4 operation as
      specified in ISO/IEC XXXX' ;
```

would constitute a valid package declaration, provided that standard ISO/IEC XXXX defined Class 4 operation as a valid optional feature of the resource.

8.3.3.4 REGISTERED AS object-identifier

The object-identifier value provides a globally unique identifier for the object class definition. This value is used in management protocol when it is necessary to identify the object class.

8.4 Package template

8.4.1 Overview

This template allows a package consisting of a combination of behaviour definitions, attributes, attribute groups, operations, notifications and parameters to be defined for subsequent insertion into a Managed Object Class template under the CHARACTERIZED BY or CONDITIONAL PACKAGES constructs. The major elements of the definition are described below.

8.4.1.1 Behaviour

The package definition provides a complete specification of the behaviour that is included in the package. This includes

- the effect of the Operations upon a managed object, and the circumstances under which Notifications are generated;
- any constraints that are placed on operations in order to satisfy consistency rules, and in particular, the rules under which Creation and Deletion of managed objects may be performed and the consequences of these operations;
- a specification of how instances of a managed object class interact with other, related, managed objects of the same or of different class(es);
- identification of any attributes that correspond with information in notifications, if any. This includes identifying any mappings to particular notification fields that takes place or to the emission of a notification;
- specification of IVMO selection criteria, if any;

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

– a complete definition of any other aspects of the behaviour of the managed object class.

8.4.1.2 Contained attributes

The set of attributes that the package contains shall be specified.

8.4.1.3 Operations and Notifications

The package definition shall specify which notifications instances of the class that make use of this package shall be able to generate, which operations instances of the class shall be capable of performing, and in the case of attribute-related operations, which attributes shall be available to be operated upon. The package definition shall also specify any additional parameters that notifications and operations of instances of the managed object class that make use of this package shall be capable of carrying.

NOTES

1 The operations identified in the class definition are the operation types defined in CCITT Rec. X.720 | ISO/IEC 10165-1 (Get attribute value, Replace attribute value, Replace with default value, etc.). In the case of Actions and Notifications, further definitions are required in order to characterize their functionality, as described in 8.10 and 8.11. The Create and Delete operations are specified as part of the Name Binding template described in 8.6, as creation and deletion of a managed object is closely bound to the containment relationship between superior and subordinate objects, rather than to all instances of a managed object class.

2 Late binding, i.e. the allocation of additional parameters to actions or notifications of a managed object class, can be achieved by including in the managed object class a package that contains (only) the affected actions or notifications and their new parameters. The set union rule given in 8.3.3 for parameters of actions and notifications, means that the additional parameter(s) will be associated with the notification or action if the package is instantiated.

8.4.2 Template structure

```
<package-label> PACKAGE

        [BEHAVIOUR          <behaviour-definition-label>
                            [,<behaviour-definition-label>]* ;
        ]
        [ATTRIBUTES         <attribute-label> propertylist [<parameter-label>]*
                            [,<attribute-label> propertylist [<parameter-label>]*]*;
        ]
        [ATTRIBUTE GROUPS   <group-label> [<attribute-label>]*
                            [,<group-label> [<attribute-label>]*]* ;
        ]
        [ACTIONS            <action-label> [<parameter-label>]*
                            [,<action-label> [<parameter-label>]*]* ;
        ]
        [NOTIFICATIONS      <notification-label> [<parameter-label>]*
                            [,<notification-label> [<parameter-label>]*]* ;
        ]

[REGISTERED AS object-identifier] ;

supporting productions

propertylist     -> [REPLACE-WITH-DEFAULT]
                    [DEFAULT VALUE      value-specifier]
                    [INITIAL VALUE      value-specifier]
                    [PERMITTED VALUES   type-reference]
                    [REQUIRED VALUES    type-reference]
                    [get-replace]
                    [add-remove]
value-specifier  -> value-reference | DERIVATION RULE <behaviour-definition-label>
get-replace      -> GET | REPLACE | GET-REPLACE
add-remove       -> ADD | REMOVE  | ADD-REMOVE
```

8.4.3 Supporting definitions

8.4.3.1 BEHAVIOUR <behaviour-definition-label> [,<behaviour-definition-label>]*

The BEHAVIOUR construct allows the behaviour (semantics) associated with the package to be completely described. This construct relates the external view of aspects of a managed object (its operations and notifications) to its internal

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

operation. The behaviour-definition-label identifies an instance of use of the Behaviour template. In some circumstances, packages may be defined where no behaviour definitions are required.

8.4.3.2 ATTRIBUTES <attribute-label> propertylist [<parameter-label>]* [,<attribute-label> propertylist [<parameter-label>]*]*

This construct allows attributes to be included in the package definition. The propertylist that follows each attribute-label defines the set of operations that may be performed on the managed object with reference to the attribute, and defines any default, initial, permitted or required value(s) associated with the attribute.

The REPLACE-WITH-DEFAULT property is included if the attribute has a default value that may be set by means of the Replace with default value operation.

The DEFAULT VALUE property is included if the attribute has a default value, to be used to provide the value of the attribute in a Replace with default value operation, or to specify a default value that may be used for the attribute when the package is instantiated according to the rules defined in CCITT Rec. X.720 | ISO/IEC 10165-1. If a default value is unspecified and the REPLACE-WITH-DEFAULT property is present, the default value is determined by other means local to the managed system. The value may be specified either by means of a value-reference or by means of a DERIVATION RULE which specifies how the default value shall be determined.

The INITIAL VALUE property is included if the attribute has a mandatory initial value, to be used at create time to provide the initial value of the attribute. The value may be specified either by means of a value-reference or by means of a DERIVATION RULE which specifies how the initial value shall be determined.

If the PERMITTED VALUES property is present, the type-reference specifies any restrictions on the possible values that the attribute may take. The form of the specification referenced shall be a subtype of the attribute syntax type, defined using the ASN.1 subtype notation.

NOTE 1 – The PERMITTED VALUES construct is required only in attribute definitions where it is necessary to specify a restriction on the value set permitted by the specification of the attribute syntax, e.g., when modifying an existing attribute specification. Such restrictions on the value set of an attribute should only be made in circumstances where the restriction is based on a limitation inherent in the semantics of the attribute, rather than a restriction that is based on some arbitrary assumption as to what might constitute a reasonable value set.

If the REQUIRED VALUES property is present, the type-reference specifies any values that the attribute shall be capable of taking. The form of the specification referenced shall be a subtype of the attribute syntax type, defined using the ASN.1 subtype notation.

NOTE 2 – This property defines the value set required for conformance. For example, a modem managed object might have a data rate attribute with a permissible value set of 0 to 19,2K; however, conformance to the modem standard might require support for one particular data rate from the value set permitted. As with PERMITTED VALUES, such requirements on the supported value set of an attribute should only be made in circumstances where the requirement is based on a feature inherent in the semantics of the attribute, rather than a requirement that is based on some arbitrary assumption as to what might constitute a reasonable minimum value set.

If present, the parameter-labels identify managed object class specific error parameters associated with management operations on the attribute. These are reported as processing failures. The syntax of the error parameters are defined in the referenced templates.

8.4.3.3 ATTRIBUTE GROUPS <group-label> [<attribute-label>]* [,<group-label> [<attribute-label>]*]*

This construct allows a set of attribute groups to be identified as part of the package. In the case of extensible attribute groups, the original definition of an attribute group may be extended by the addition of further attribute-labels.

8.4.3.4 ACTIONS <action-label> [<parameter-label>]* [,<action-label> [<parameter-label>]*]*

If present, the action-labels identify the set of action definitions that are included in the package. The behaviour definitions shall specify the effect of these actions upon managed objects.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

If present, the `parameter-labels` identify any managed object class specific action information or reply parameters, or any managed object class specific error parameters associated with the action. The syntax of the parameters are defined in the referenced templates.

8.4.3.5 NOTIFICATIONS <notification-label> [<parameter-label>]* [,<notification-label> [<parameter-label>]*]*

Present if any notifications are included in the package. The `notification-labels` identify the notification definitions that are applicable. The behaviour definitions shall specify the circumstances under which these notifications are generated by a managed object.

If present, the `parameter-labels` identify any managed object class specific notification information or reply parameters, or any managed object class specific error parameters associated with the notification. These may be additional parameters used, for example, to populate the Additional information field of notifications defined in CCITT Rec. X.733 | ISO/IEC 10164-4. The syntax of the parameters are defined in the referenced templates.

8.4.3.6 REGISTERED AS object-identifier

The `object-identifier` value, if present, provides a globally unique identifier for the package definition, and registers the grouping of behaviour, attributes, attribute groups, actions and notifications that the package defines. The `object-identifier` value is the value that is included in the Packages attribute of any instances of the managed object class that are created, in accordance with the rules stated in CCITT Rec. X.720 | ISO/IEC 10165-1. This construct is required in cases where the package is referenced by a `CONDITIONAL PACKAGES` construct in a Managed Object Class template.

8.5 Parameter template

8.5.1 Overview

This template permits the specification and registration of parameter syntaxes and associated behaviour that may be associated with particular attributes, operations and notifications within the Package, Attribute, Action and Notification templates defined in 8.4, 8.7, 8.10 and 8.11. The type specified in a Parameter template is used to fill in an `ANY DEFINED BY x` construct in a management PDU, where `x` is a field in the PDU that carries the object identifier assigned to the parameter. This mechanism is, for example, applicable to the definition of

- processing failures;
- parameters of action requests/responses;
- parameters of notification requests/responses.

Use of the template in each of these contexts is described in 8.5.3.

The major elements of the definition are described below.

8.5.1.1 Context definition

The template specifies the context in which the parameter is applicable, that is, it specifies that the parameter is carried in a particular field in a management PDU.

8.5.1.1.1 Action information/reply, event information/reply, specific error

When the context is unambiguously identified by the management PDU in which the parameter is carried, the context may be indicated by one of the five predefined keywords specified in 9.5.3. The context is unambiguously identified by the management PDU if and only if the `ANY DEFINED BY` construct appears in that PDU exactly once.

8.5.1.1.2 Context keyword

When the context is not unambiguously identified by the management PDU in which the parameter is carried, a context keyword shall be specified. The context keyword shall identify the field in the management PDU in which the parameter may be carried.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Table 16 – Use of the Parameter template

Use	Possible contexts
ATTRIBUTES construct of Package template	SPECIFIC-ERROR
ACTIONS construct of Package template	context-keyword, SPECIFIC-ERROR, ACTION-INFO, ACTION-REPLY
NOTIFICATIONS construct of Package template	context-keyword, SPECIFIC-ERROR, EVENT-INFO, EVENT-REPLY
CREATE construct of Name Binding template	SPECIFIC-ERROR
DELETE construct of Name Binding template	SPECIFIC-ERROR
Attribute template	SPECIFIC-ERROR
Action template	context-keyword, SPECIFIC-ERROR, ACTION-INFO, ACTION-REPLY
Notification template	context-keyword, SPECIFIC-ERROR, EVENT-INFO, EVENT-REPLY

8.5.1.1.3 Usage in other templates

Table 16 shows where the Parameter template is referenced, with the allowed options.

When used as a qualifier in a package definition, the parameter may be "late bound" to the element that it qualifies, e.g., further parameters may be added to a previously defined notification at the time of package definition if the notification syntax is extensible.

8.5.1.2 Syntactic definition

The template permits an abstract syntax to be associated with the parameter.

8.5.1.3 Attribute reference

In place of an explicit syntactic definition and registration in the Parameter template, the template may specify these two items by referring to an Attribute template. The use of this construct has no effect on the meaning of the existing registered attribute.

8.5.1.4 Behaviour

The template defines any behaviour that applies to the use of the parameter.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

8.5.2 Template structure

```
<parameter-label>   PARAMETER

        CONTEXT         context-type ;

        syntax-or-attribute-choice ;

        [BEHAVIOUR      <behaviour-definition-label>
                        [,<behaviour-definition-label>]* ;
        ]

[REGISTERED AS object-identifier]  ;

supporting productions

context-type                    -> context-keyword |
                                   ACTION-INFO |
                                   ACTION-REPLY |
                                   EVENT-INFO |
                                   EVENT-REPLY |
                                   SPECIFIC-ERROR
context-keyword                 -> type-reference.<identifier>
syntax-or-attribute-choice      -> WITH SYNTAX  type-reference |
                                   ATTRIBUTE    <attribute-label>
```

8.5.3 Supporting definitions

8.5.3.1 CONTEXT context-type

This construct defines the context in which the parameter is applicable.The options are

- `context-keyword`: this option is a reference to a context defined externally to the template. The structure of the reference consists of a `type-reference` followed by an `identifier` which is the name of a field in the management PDU specified by the `type-reference`. It may therefore be used as a reference to a context defined in another document. This may be used to indicate, for example, that the parameter applies only to a specific field of the CMIS Event information parameter (e.g., CCITT Rec. X.733 | ISO/IEC 10164-4 Additional information field), or the CMIS Action reply parameter. If the parameter does not map to a specific field-name (e.g., Event information is defined to be a set of Parameter Identifier/Parameter Value pairs), one of the following, more general contexts can be specified;

- `ACTION-INFO`: this option defines the parameter as being applicable to the representation of a parameter that may be carried in the CMIS Action information parameter;

- `ACTION-REPLY`: this option defines the parameter as being applicable to the representation of a parameter that may be carried in a CMIS Action reply parameter;

- `EVENT-INFO`: this option defines the parameter as being applicable to the representation of a parameter that may be carried in the CMIS Event information parameter;

- `EVENT-REPLY`: this option defines the parameter as being applicable to the representation of a parameter that may be carried in the CMIS Event reply parameter;

- `SPECIFIC-ERROR`: this option defines the parameter as being applicable to the representation or generation of a CMIS processing failure error. When this option is used with parameters that apply to attributes, the managed object class definition shall specify whether, when this error occurs for a Replace attribute value or Replace with default value operation on one attribute, other attributes referenced in a single replace request are modified or not.

8.5.3.2 WITH SYNTAX type-reference

This construct, if present, identifies the ASN.1 type of the parameter, as carried in protocol.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

8.5.3.3 ATTRIBUTE <attribute-label>

If present, this construct identifies an Attribute template whose syntax and object identifier are used as the syntax and object identifier of the parameter, respectively.

8.5.3.4 BEHAVIOUR <behaviour-definition-label> [,<behaviour-definition-label>]*

If present, this construct permits the specification of any behaviour or semantics associated with the parameter. If the ATTRIBUTE construct is used, this construct does not modify the behaviour of the attribute.

8.5.3.5 REGISTERED AS object-identifier

The object-identifier value, if present, provides a globally unique identifier for the parameter definition. This value is used in management protocol when it is necessary to identify the parameter. This construct shall be present if and only if the WITH SYNTAX construct is present.

8.6 Name binding template

8.6.1 Overview

This template allows alternative naming structures to be defined for managed objects of a given managed object class by means of name bindings. A name binding allows an attribute to be selected as the naming attribute that shall be used when a subordinate object which is an instance of a specified managed object class is named by a superior object which is an instance of a specified managed object class or other object class, such as a Directory object class.

If a given name binding is used, the attribute identified as the naming attribute shall be present in the subordinate object. The naming attribute is used to construct the relative distinguished name (RDN) of subordinate objects of that class. An RDN is constructed from the object identifier assigned to that attribute type and the value of the instance of the attribute. The Distinguished Name of the subordinate object is obtained by appending its RDN to the Distinguished Name of its superior object.

Name bindings are not considered to be part of the definition of either of the classes that they reference. A given subordinate managed object class may have more than one name binding associated with it. The set of name bindings defines the set of possible naming relationships with superior objects and the set of managed object classes from which subordinate objects may be instantiated.

A name binding may also be defined to apply to all subclasses of the specified superior object class or all subclasses of the specified subordinate object class, or both.

NOTE – Name bindings may be specified for a managed object class subsequent to the specification of the managed object class itself.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

8.6.2 Template structure

```
<name-binding-label>   NAME BINDING

       SUBORDINATE OBJECT CLASS          <class-label> [AND SUBCLASSES];
       NAMED BY SUPERIOR OBJECT CLASS    <class-label> [AND SUBCLASSES];
       WITH ATTRIBUTE                    <attribute-label> ;
       [BEHAVIOUR                        <behaviour-definition-label>
                                         [,<behaviour-definition-label>]* ;
       ]
       [CREATE                           [create-modifier [,create-modifier]]
                                         [<parameter-label>]* ;
       ]
       [DELETE                           [delete-modifier]
                                         [<parameter-label>]* ;
       ]

REGISTERED AS object-identifier ;

supporting productions

create-modifier  -> WITH-REFERENCE-OBJECT |
                    WITH-AUTOMATIC-INSTANCE-NAMING
delete-modifier  -> ONLY-IF-NO-CONTAINED-OBJECTS |
                    DELETES-CONTAINED-OBJECTS
```

8.6.3 Supporting definitions

8.6.3.1 SUBORDINATE OBJECT CLASS <class-label> [AND SUBCLASSES]

This defines a managed object class whose instances may be named by instances of the object class defined by the NAMED BY SUPERIOR OBJECT CLASS construct. The name of an instance of this subordinate object class is constructed by concatenating the distinguished name of its superior object with the relative distinguished name of the subordinate object. If AND SUBCLASSES is specified, the name binding also applies to all subclasses of the specified managed object class.

8.6.3.2 NAMED BY SUPERIOR OBJECT CLASS <class-label> [AND SUBCLASSES]

This defines a managed object class or other object class, such as a Directory object class, whose instances may name instances of the managed object class defined by the SUBORDINATE OBJECT CLASS construct. If AND SUBCLASSES is specified, the name binding also applies to all subclasses of the specified object class.

8.6.3.3 WITH ATTRIBUTE <attribute-label>

This defines the attribute that shall be used, in the context of this name binding, to construct the relative distinguished name for instances of the managed object class defined by the SUBORDINATE OBJECT CLASS construct. Values of this attribute shall be represented by single-valued data types complying with the restrictions specified in CCITT Rec. X.720 | ISO/IEC 10165-1; if no suitable attribute is available for use as a naming attribute, managed object designers are encouraged to provide a naming attribute of type GraphicString.

8.6.3.4 BEHAVIOUR <behaviour-definition-label> [,<behaviour-definition-label>]*

If present, this construct permits any behavioural impact imposed as a consequence of the name binding to be defined. The behaviour-definition-label identifies the behaviour definition concerned.

NOTE 1 – This construct is intended for use as a means of describing behaviour specific to a name binding. Any behaviour that is applicable to all possible instances of a managed object class should be defined as part of the behaviour referenced by the Package template(s) that define the managed object class.

8.6.3.5 CREATE [<create-modifier> [,<create-modifier>]] [<parameter-label>]*

Present if it is permitted to create new instances of the managed object class referenced by the SUBORDINATE OBJECT CLASS construct in the context of this name binding, by means of systems management operation. The create-modifier values specify the options available on creation. The permitted create-modifier values are as follows

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

- WITH-REFERENCE-OBJECT. If present, a reference managed object may be specified on creation as a source of default values and to specify choice of conditional packages;

- WITH-AUTOMATIC-INSTANCE-NAMING. If present, the Create request may omit to specify the instance name of the new managed object.

The behaviour definitions shall specify what course of action is taken when there is a choice of Name Bindings that may be applied to the new managed object.

The sources of initial attribute values used at managed object creation time, and their associated precedence rules, are defined in CCITT Rec. X.720 | ISO/IEC 10165-1.

If present, the parameter-labels identify name binding specific error parameters associated with the Create operation. These are reported as processing failures. The syntax of the error parameters are defined in the referenced templates.

8.6.3.6 DELETE [<delete-modifier>] [<parameter-label>]*

Present if it is permitted to delete instances of the managed object class referenced by the SUBORDINATE OBJECT CLASS construct in the context of this name binding. The delete-modifier, if present, indicates the behaviour of a managed object of that class if the managed object is deleted. The permitted delete-modifiers are as follows

- ONLY-IF-NO-CONTAINED-OBJECTS. If specified, any contained managed objects shall be explicitly deleted by management operations prior to deletion of the containing managed object, i.e., a Delete request will cause an error if there are contained managed objects;

- DELETES-CONTAINED-OBJECTS. If a Delete request is applied to a managed object for which the DELETES-CONTAINED-OBJECTS modifier is specified, the Delete request will fail if any directly or indirectly contained managed object has the ONLY-IF-NO-CONTAINED-OBJECTS modifier specified and also has a contained managed object; otherwise, a successful Delete request will also have the effect of deleting contained managed objects.

Other rules which describe the behaviour with respect to deletion of contained managed objects may be specified in the BEHAVIOUR construct.

NOTE 2 – Given that the DELETES-CONTAINED-OBJECTS modifier permits the deletion of a managed object regardless of whether it contains other managed objects, it is advisable to use the ONLY-IF-NO-CONTAINED-OBJECTS modifier if there is any doubt as to which modifier is appropriate.

If there are constraints on deletion relative to other relationships or conditions that are generic to the managed object class, these shall be specified as part of the behaviour of the managed object class.

If present, the parameter-labels identify name binding specific error parameters associated with the Delete operation. These are reported as processing failures. The syntax of the error parameters are defined in the referenced templates.

8.6.3.7 REGISTERED AS object-identifier

The object-identifier value provides a globally unique identifier for the name binding definition. This value is used to identify the name binding for the purposes of knowledge management.

8.7 Attribute template

8.7.1 Overview

This template is used to define individual attribute types. These definitions may be further combined by the attribute group template where attribute groups are required. The major elements of the definition are described below.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

8.7.1.1 Derivation

The definition of an attribute type may modify or constrain the definition of another attribute type.

8.7.1.2 Attribute syntax

The definition of an attribute type shall include the definition of the syntax that shall be used to convey values of the attribute in management protocol. This definition is achieved by means of a reference to an ASN.1 Type Definition. The definition of an attribute syntax indicates whether the attribute value is a single- or set-valued attribute type. If the base type is SET OF, the attribute is a set-valued type, otherwise it is a single-valued type.

8.7.1.3 Value matching

The definition of an attribute type may include the valid ways in which the value of an instance of the type may be tested, i.e., whether the attribute may be tested for equality, magnitude, etc.. Value matching on some attribute types may require the specification of how a matching rule is defined to operate, as part of the attribute's behaviour definition. The absence of any matching rules in the attribute definition implies that matching of values is undefined.

8.7.1.4 Behaviour

The attribute definition may include definition of attribute-specific behaviour; i.e., behaviour that applies to an attribute type regardless of which managed object class contains instances of the attribute type.

8.7.1.5 Attribute identifier

An object identifier value shall be allocated to each attribute that is to be included in the definition of a managed object class. This value is used in management protocol to identify the attribute.

8.7.1.6 Parameters

The attribute definition may identify attribute-specific error parameters associated with management operations on the attribute type. The referenced templates map these to processing failures.

8.7.2 Template Structure

```
<attribute-label>   ATTRIBUTE

       derived-or-with-syntax-choice ;
       [MATCHES FOR qualifier
                    [, qualifier]* ;
       ]
       [BEHAVIOUR    <behaviour-definition-label>
                     [,<behaviour-definition-label>]* ;
       ]
       [PARAMETERS   <parameter-label>
                     [,<parameter-label>]* ;
       ]

[REGISTERED AS object-identifier] ;

supporting productions

qualifier                          -> EQUALITY ¦ ORDERING ¦ SUBSTRINGS ¦
                                      SET-COMPARISON ¦ SET-INTERSECTION
derived-or-with-syntax-choice      -> DERIVED FROM <attribute-label> ¦
                                      WITH ATTRIBUTE SYNTAX type-reference
```

8.7.3 Supporting definitions

8.7.3.1 DERIVED FROM <attribute-label>

If this construct is present, the attribute definition takes as a starting point all aspects of the definition referenced by `attribute-label`, including any that it may in turn have derived from other attribute definitions. The rules for interpreting the effect of presence of any of the other elements of the Attribute template under these circumstances are as follows

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

- MATCHES FOR: The resultant set of matching rules shall be the logical OR of the matching rules specified by this construct with any derived matching rules;

- BEHAVIOUR is assumed to extend any derived behaviour definitions;

- REGISTERED AS is assumed to replace any registration derived from other definitions.

This derivation mechanism permits

- the definition of an attribute based on an existing attribute definition;

- the addition of further constraints to an existing attribute definition.

8.7.3.2 WITH ATTRIBUTE SYNTAX type-reference

This construct, present only if the DERIVED FROM construct is absent, identifies the ASN.1 data type that describes how instances of the attribute value are carried in protocol.

The ASN.1 data type also defines the data type of the attribute itself. If the base type of the syntax is the set-of type, the attribute is a set-valued attribute. All other ASN.1 data types, including the set type, sequence type and sequence-of type, define single-valued attribute types.

8.7.3.3 MATCHES FOR qualifier [, qualifier]*

This construct defines the types of test that may be applied to a value of the attribute as part of a Filter operation. Matching for the presence of an attribute is implicitly permitted for all attributes. For other types of matching, if this construct is not present, matching is undefined and is therefore not permitted on the attribute. The options are

- EQUALITY. If present, the attribute value may be tested for equality against a given value;

- ORDERING. If present, the attribute value may be tested against a given value in order to determine which has the greater value;

- SUBSTRINGS. If present, the attribute value may be tested against a given substring value in order to determine its presence or absence in the attribute value;

- SET-COMPARISON. If present, the attribute value may be tested against a given value in order to determine subset/superset relationships between the values;

- SET-INTERSECTION. If present, the attribute value may be tested against a given value in order to determine the presence or absence of a non-null set intersection between the two values.

8.7.3.4 BEHAVIOUR <behaviour-definition-label> [,<behaviour-definition-label>]*

Any behaviour that is generic to this attribute type may be defined by means of this behaviour construct. The behaviour definition shall include any additional specification that is required in order to define how the chosen set of matching rules are applied to the attribute definition. Behaviour that is specific to the managed object class is defined in the behaviour construct of the Package template.

8.7.3.5 PARAMETERS <parameter-label> [,<parameter-label>]*

The parameter-labels allow parameters to be associated with the behaviour of an attribute type, for the definition of processing failures. For example, an attribute type might exhibit a "constraint violation" error under certain conditions. A parameter giving information about such an error could be specified using a Parameter template with CONTEXT SPECIFIC-ERROR, and referenced from the Attribute template.

8.7.3.6 REGISTERED AS object-identifier

The object-identifier value provides a globally unique identifier for the attribute definition; this includes all elements referenced either directly or indirectly by the DERIVED FROM, WITH ATTRIBUTE SYNTAX, MATCHES FOR and BEHAVIOUR constructs, where present. This value is used in management protocol when it is necessary to identify

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

the attribute type. If this construct is omitted, the attribute definition shall not be referenced in a managed object class definition. Where an attribute definition is derived from an existing attribute definition that includes a REGISTERED AS construct, the object-identifier value assigned to the existing definition is not a valid identifier for the derived definition. The REGISTERED AS construct shall therefore be included in the derived definition if it is to be referenced in a managed object class definition.

8.8 Attribute group template

8.8.1 Overview

This template allows attribute groupings to be defined; such groupings are applicable to situations where it is desirable to operate upon the collection of attributes that are members of the group. The behaviour definitions for a given managed object class define the meaning of Get attribute value and Replace with default value operations when applied to attribute groups. Each member of the group shall itself be defined as a single- or set-valued attribute type.

The Attribute Group template defines the minimum set of attributes that constitute the group and the object identifier value that is used to name the group. Each managed object class definition that references an attribute group may extend the membership of the group by adding new attributes to the group, unless the group has been defined to be of fixed membership; such extensions apply only to instances of the managed object class in which the extension is defined. The attributes identified in the Attribute Group template define the minimum membership of the group in all managed object class definitions that reference the group.

If an extensible attribute group is present in a managed object class definition, then all attributes defined for the group, either within the body of the Attribute Group template or added to the attribute group by the managed object class definition, shall be present in the package which references the group or in one of the mandatory packages of the managed object class.

If a fixed attribute group is present in a managed object class definition, then all attributes defined for the group shall be present in the package which references the group.

8.8.2 Template structure

```
<group-label>    ATTRIBUTE GROUP

        [GROUP ELEMENTS  <attribute-label>
                         [,<attribute-label>]* ;
        ]
        [FIXED ;
        ]
        [DESCRIPTION     delimited-string ;
        ]

REGISTERED AS object-identifier ;
```

8.8.3 Supporting definitions

8.8.3.1 GROUP ELEMENTS <attribute-label> [,<attribute-label>]*

When present, this construct defines the set of attribute-labels that identify the individual attributes that form those elements of the attribute group that shall be present in all instances of the attribute group, each of which shall be defined by means of the Attribute template. The behaviour definitions for a given managed object class define the meaning of Get attribute value and Replace with default value operations when applied to attribute groups.

NOTE 1 – This does not imply that there is a behaviour specification specific to the attribute group itself that does not also apply to the attributes when treated individually.

All attributes in a Group shall be members of the managed object class definition(s) which reference the group; i.e., each attribute that is a member of the group for a given managed object class shall be referenced by the Attributes construct in one or more of the packages that are referenced by the managed object class definition.

8.8.3.2 FIXED

When present, this construct indicates that the attribute group is defined to be of fixed membership.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

8.8.3.3 DESCRIPTION delimited-string

This construct allows a description of the semantics of the grouping to be expressed; e.g., 'Group of all state attributes in the managed object'. No restrictions are placed on the character set used to represent the DESCRIPTION and no further structure within the DESCRIPTION is defined.

This construct shall not be used as a means of defining behavioural aspects of the group or its members.

8.8.3.4 REGISTERED AS object-identifier

The object-identifier value provides a globally unique identifier for the attribute group definition. This value shall be used in management protocol when it is necessary to identify the attribute group. The attribute group identified by this object-identifier value in the context of a managed object includes any attributes defined in the body of the Attribute Group template, plus, for extensible attribute groups, any attributes added to the group as a consequence of the definition of the elements of the Managed Object Class template that applied to the instantiation of the managed object.

NOTE 2 – The Attribute Group template defines the set of attributes (which may be the empty set) that are always members of the group; in the case of an extensible attribute group, this set may be extended by the Attribute Groups construct in the Package template, in order to extend the set for the purposes of particular managed object class definitions. This technique may be appropriate where it is desirable to define an attribute group, members of which share some common semantic (such as "state attributes"), but where the number of attributes of that semantic type that may be present in a given managed object class is determined at instantiation time, or where different groupings of attributes with the same semantics are required in multiple managed object classes. In general, it is only possible to determine the composition of an extensible attribute group at managed object instantiation time, at which point it is known which packages, and therefore which attributes, have been instantiated.

8.9 Behaviour template

8.9.1 Overview

This template is used to define behavioural aspects of managed object classes, name bindings, parameters and attribute, action and notification types. The Behaviour template is intended to permit extension provisions, but behaviour specifications shall not change the semantics of previously-defined information. If information is left undefined, the behaviour definition shall be explicit about what is undefined.

NOTES

1 Behaviour templates should be used to convey semantics that are not completely described by other templates. Specifically, definers should not rely on labels to convey semantics.

2 A behaviour statement should be worded in terms of the managed object whose managed object class definition includes it.

8.9.2 Template structure

```
<behaviour-definition-label>  BEHAVIOUR

        DEFINED AS            delimited-string ;
```

8.9.3 Supporting definitions

8.9.3.1 DEFINED AS delimited-string

The text contained in the delimited-string gives a definition of an aspect of the behaviour of a managed object class or associated name bindings, parameters, attributes, actions or notifications. This definition may be documented by use of natural language text or by the use of formal description techniques. The text may be a textual reference to a clause or sub-clause of a document or Recommendation | International Standard. No restrictions are placed on the character set used to represent the delimited-string and no further structure within the text is defined.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

8.10 Action template

8.10.1 Overview

This template is used to define the behaviour and syntax associated with a particular Action type. Action types defined by means of this template may be carried by the M-ACTION service defined in CCITT Rec. X.710 | ISO/IEC 9595. The major elements of the definition are described below.

8.10.1.1 Behaviour

The definition of an Action type shall specify the functionality of the Action in terms of the effect that it has on the managed object class upon which it operates. Where the action may apply to more than one managed object class, the behavioural description should be limited to those features of the behaviour that are common to all managed object classes; further managed object class specific behaviour related to those Actions is described as part of the definition of the managed object class itself.

8.10.1.2 Mode of operation

The definition of an Action type shall indicate whether the action is always confirmed or whether it may be confirmed or unconfirmed at the manager's option.

8.10.1.3 Abstract syntax

The definition of the Action type shall specify any syntax that shall be used to convey the action information and action reply parameters of the M-ACTION service defined in CCITT Rec. X.710 | ISO/IEC 9595. These syntaxes are defined by means of ASN.1 data types.

NOTES

1 Unless it is specifically intended to preclude future extension of the arguments of an action, it is recommended that the information and reply syntaxes of the action should be defined in an extensible manner, by inclusion of the ASN.1 type **SET OF** `ManagementExtension` (as defined in CCITT Rec. X.721 | ISO/IEC 10165-2) as an optional field.

2 It is recommended that the base data type chosen for the information and reply syntax is the **SEQUENCE** type.

8.10.1.4 Action identifiers

The value of the object identifier associated with the Action type definition is used to identify the Action type in management protocol.

8.10.1.5 Parameters

The definition of the Action type may identify action information or action reply parameters, or specific error parameters associated with the Action type.

8.10.2 Template structure

```
<action-label>  ACTION

        [BEHAVIOUR                  <behaviour-definition-label>
                                    [,<behaviour-definition-label>]* ;
        ]
        [MODE CONFIRMED ;
        ]
        [PARAMETERS                 <parameter-label>
                                    [,<parameter-label>]* ;
        ]
        [WITH INFORMATION SYNTAX    type-reference ;
        ]
        [WITH REPLY SYNTAX          type-reference ;
        ]

REGISTERED AS object-identifier ;
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

8.10.3 Supporting definitions

8.10.3.1 BEHAVIOUR <behaviour-definition-label> [,<behaviour-definition-label>]*

When present, this defines the behaviour of the Action, the parameters that shall be specified with the Action, the results that the Action may generate and their meaning. The behaviour-definition-labels reference behaviour descriptions defined by use of the Behaviour template.

8.10.3.2 MODE CONFIRMED

If present, the action shall operate in confirmed mode. If absent, the action may be confirmed or unconfirmed at the discretion of the manager.

8.10.3.3 PARAMETERS <parameter-label> [,<parameter-label>]*

The parameter-labels identify action information or action reply parameters, or processing failures associated with the Action type. See clause A.7 for an example.

8.10.3.4 WITH INFORMATION SYNTAX type-reference

If present, the type-reference identifies the ASN.1 data type that describes the structure of the action information parameter that is carried in management protocol. If absent, there is no action-specific information associated with the action invocation.

8.10.3.5 WITH REPLY SYNTAX type-reference

If present, the type-reference identifies the ASN.1 data type that describes the structure of the action reply parameter that is carried in management protocol. If absent, there is no action-specific information associated with the action reply.

8.10.3.6 REGISTERED AS object-identifier

The object-identifier value provides a globally unique identifier for the action type definition. This value is used in management protocol when it is necessary to identify the action type.

8.11 Notification template

8.11.1 Overview

This template is used to define the behaviour and syntax associated with a particular Notification type. Notification types defined by means of this template may be carried in event reports by the M-EVENT REPORT service defined in CCITT Rec. X.710 | ISO/IEC 9595. The major elements of the definition are described below.

8.11.1.1 Behaviour

The definition of a Notification type shall specify the circumstances under which a notification of the type is generated.

8.11.1.2 Abstract syntax

The definition of the Notification type shall specify any syntax that shall be used to convey the event information and event reply parameters of the M-EVENT REPORT service defined in CCITT Rec. X.710 | ISO/IEC 9595. The template also permits the allocation of attribute values to fields in the syntax.

NOTES

1 Unless it is specifically intended to preclude future extension of the arguments of a notification, it is recommended that the information and reply syntaxes of the notification should be defined in an extensible manner, by inclusion of the ASN.1 type SET OF ManagementExtension (as defined in CCITT Rec. X.721 | ISO/IEC 10165-2) as an optional field.

2 It is recommended that the base data type chosen for the information and reply syntax is the SEQUENCE type.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

8.11.1.3 Notification naming

The value of the object identifier associated with the Notification definition is used to identify the Event type in management protocol.

8.11.1.4 Parameters

The definition of the Notification type may identify event information or event reply parameters, or specific error parameters associated with the Notification type.

8.11.2 Template structure

```
<notification-label> NOTIFICATION

        [BEHAVIOUR                  <behaviour-definition-label>
                                    [,<behaviour-definition-label>]* ;
        ]
        [PARAMETERS                 <parameter-label>
                                    [,<parameter-label>]* ;
        ]
        [WITH INFORMATION SYNTAX    type-reference
            [AND ATTRIBUTE IDS          <field-name> <attribute-label>
                                        [,<field-name> <attribute-label>]*
            ] ;
        ]
        [WITH REPLY SYNTAX          type-reference ;
        ]

REGISTERED AS object-identifier ;
```

8.11.3 Supporting definitions

8.11.3.1 BEHAVIOUR <behaviour-definition-label> [,<behaviour-definition-label>]*

If present, this construct defines the behaviour of the notification, the data that shall be specified with the notification, the results that the notification may generate and their meaning. The `behaviour-definition-label` references a behaviour description defined by use of the Behaviour template.

8.11.3.2 PARAMETERS <parameter-label> [,<parameter-label>]*

The `parameter-labels` identify event information or event reply parameters, or processing failures associated with the Notification type. See clause A.8 for an example.

8.11.3.3 WITH INFORMATION SYNTAX type-reference [AND ATTRIBUTE IDS <field-name> <attribute-label> [,<field-name> <attribute-label>]*]

If present, this construct identifies the ASN.1 data type that describes the structure of the notification information that is carried in management protocol, and permits the association of attribute identifiers with named fields in the abstract syntax. If absent, there is no notification-specific information associated with the notification invocation. If the `AND ATTRIBUTE IDS` option is present, the `field-name` shall be a label defined within the abstract syntax referenced by the `type-reference` that appears in the construct. The data type that is labelled by the `field-name` is used to carry values of the attribute referenced by `attribute-label`. The ASN.1 data type of the attribute shall be the same as the data type referenced by `field-name`.

No label within a `SET OF` or `SEQUENCE OF` type nor any label within the definition of such an element can be used as a field-name since labels within such repeating constructs cannot always refer unambiguously to a single instance of a data type. Similarly, no label of a component of a `CHOICE`, `SET` or `SEQUENCE` type nor any label within the definition of such a component can be used as a field-name if the labelled component appears multiple times within the type definition.

8.11.3.4 WITH REPLY SYNTAX type-reference

If present, this construct identifies the ASN.1 data type that describes the structure of the notification reply that is carried in management protocol. If absent, there is no notification-specific information associated with the notification reply.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

The reply syntax is used where a notification is sent using the confirmed mode of the CMIS M-EVENT-REPORT service. Event confirmations are not returned to the managed object. The decision whether to send a notification in the confirmed or unconfirmed mode is a matter for the agent to determine based on policies associated with the manager. When the `WITH REPLY SYNTAX` construct is omitted from a notification definition but the notification is sent in the confirmed mode, the confirmation will not include reply information.

8.11.3.5 `REGISTERED AS object-identifier`

The `object-identifier` value provides a globally unique identifier for the notification type definition. This value is used in management protocol when it is necessary to identify the notification type.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Annex A
Examples of use of the guidelines

(This annex does not form an integral part of this Recommendation | International Standard)

The examples shown in this Annex are intended to give examples of use of the template notation, not to provide definitions that are useful in real implementations. In particular, the behaviour definitions attached to these examples are, of necessity, somewhat artificial. Further examples of use of the notation that are of practical use in the development of managed object class definitions may be found in CCITT Rec. X.721 | ISO/IEC 10165-2.

A.1 Managed object class definition

```
exampleObjectClass MANAGED OBJECT CLASS

      DERIVED FROM          "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2 : 1992":top
;
      CHARACTERIZED BY      examplePackage2 ;
      CONDITIONAL PACKAGES
         examplePackage1      PACKAGE
            ACTIONS              qOSResetAction,
                                 activate ;
            NOTIFICATIONS        communicationError ;
         REGISTERED AS        {joint-iso-ccitt ms(9) smi(3) part4(4) package(4)
                              examplepack1(0)} ;
         PRESENT IF           !conformance class 2 of underlying resource implemented
                              as described in ISO/IEC XXXX! ;

REGISTERED AS     {joint-iso-ccitt ms(9) smi(3) part4(4) managedObjectClass(3)
                  exampleclass(0)} ;
```

NOTE – This template uses the in-line documentation option for documenting the conditional package.

A.2 Name binding definition

```
exampleNameBinding  NAME BINDING

      SUBORDINATE OBJECT CLASS   exampleObjectClass ;
      NAMED BY
      SUPERIOR OBJECT CLASS      "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2 :
                                 1992":system ;
      WITH ATTRIBUTE             objectName ;
      BEHAVIOUR
         containmentBehaviour    BEHAVIOUR
            DEFINED AS     !A maximum of 3 instances of exampleObjectClass may be
                           contained in any instance of "CCITT Rec. X.721 | ISO/IEC
                           10165-2":system.!
         ;
      ;
      CREATE     WITH-AUTOMATIC-INSTANCE-NAMING createErrorParameter ;
      DELETE     DELETES-CONTAINED-OBJECTS ;

REGISTERED AS     {joint-iso-ccitt    ms(9)    smi(3)    part4(4)    nameBinding(6)
                  examplenb(0)};
```

NOTE – This template uses the in-line documentation option for documenting the behaviour.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

A.3 Parameter definitions

```
pDUHeader PARAMETER

        CONTEXT         EVENT-INFO;
        WITH SYNTAX     ParameterModule.PDUString;
        BEHAVIOUR
            pDUHeaderBehaviour      BEHAVIOUR
                DEFINED AS    !PDU header. Carried in the CMIP eventInfo field.!
            ;
        ;
REGISTERED AS    {joint-iso-ccitt    ms(9)    smi(3)    part4(4)    parameter(5)
                 pduheaderparam(0)};


createErrorParameter    PARAMETER

        CONTEXT         SPECIFIC-ERROR ;
        WITH SYNTAX     ParameterModule.ErrorInfo1 ;
        BEHAVIOUR
            createErrorBehaviour    BEHAVIOUR
                DEFINED AS    !If    the    maximum    number    of    instances    of
                              exampleObjectClass exist within the containing managed
                              object, attempts to create additional instances will
                              result in the return of a CMIP Processing Failure error
                              where the SpecificErrorInfo field is of the form
                              SpecificErrorInfo ::= SEQUENCE {
                                    errorid       OBJECT IDENTIFIER,
                                    errorinfo     ANY DEFINED BY errorid }
                              The OBJECT IDENTIFIER carried in errorid shall be the
                              value under which this parameter definition is
                              registered. The type carried in errorinfo shall be the
                              type identified by the WITH SYNTAX construct of this
                              parameter definition. The value carried by this type
                              indicates the number of instances of this managed object
                              class that currently exist in the containing managed
                              object.!
            ;
        ;

REGISTERED AS    {joint-iso-ccitt ms(9) smi(3) part4(4) parameter(5) createerror(1)};


serviceProviderErrorResponseReason PARAMETER

        CONTEXT         ACTION-REPLY;
        WITH SYNTAX     ParameterModule.ServiceProviderErrorResponseReason;
        BEHAVIOUR
            serviceProviderErrorResponseReasonBehaviour BEHAVIOUR
                DEFINED AS    !Returned in the responseParameters field of the CMIP
                              actionReplyInfo   if   responseCode   has   the   value
                              serviceProviderErrorResponse.!
            ;
        ;
REGISTERED AS    {joint-iso-ccitt ms(9) smi(3) part4(4) parameter(5) sperrorrsp(2)};
```

NOTE – These templates use the in-line documentation option for documenting the behaviour.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

A.4 Package definition

```
examplePackage2  PACKAGE

          BEHAVIOUR              exampleClassBehaviour ;
          ATTRIBUTES             objectName
                                       GET ,
                                 qOS-Error-Cause
                                       GET ,
                                 qOS-Error-Counter
                                    PERMITTED VALUES AttributeModule.QOSCounterRange
                                    REQUIRED VALUES AttributeModule.QOSCounterRange
                                       GET ;
          ATTRIBUTE GROUPS       qOS-Group ;
          NOTIFICATIONS          protocolError;

REGISTERED AS    {joint-iso-ccitt ms(9) smi(3) part4(4) package(4) examplepack2(1)};
```

NOTE – As this template is not used as a conditional package, the REGISTERED AS construct is not strictly necessary, but it is easier to include the registration at specification time than it would be to add it later if it became necessary in the future to use this package as a conditional package.

A.5 Attribute definitions

```
objectName ATTRIBUTE

      WITH ATTRIBUTE SYNTAX  AttributeModule.ObjectName ;
      MATCHES FOR            EQUALITY ;

REGISTERED   AS {joint-iso-ccitt ms(9) smi(3) part4(4) attribute(7) objectname(0)};


qOS-Error-Cause ATTRIBUTE

      WITH ATTRIBUTE SYNTAX  AttributeModule.QOSErrorCause ;
      MATCHES FOR            EQUALITY ;
      BEHAVIOUR              qOSErrorBehaviour ;

REGISTERED AS    {joint-iso-ccitt ms(9) smi(3) part4(4) attribute(7) qoscause(1)};


qOS-Error-Counter ATTRIBUTE

      WITH ATTRIBUTE SYNTAX  AttributeModule.QOSErrorCounter ;
      MATCHES FOR            EQUALITY, ORDERING ;
      BEHAVIOUR              qOSCounterBehaviour ;

REGISTERED AS    {joint-iso-ccitt ms(9) smi(3) part4(4) attribute(7) qoscount(2)};
```

A.6 Attribute group definition

```
qOS-Group ATTRIBUTE GROUP

      GROUP ELEMENTS   qOS-Error-Cause, qOS-Error-Counter ;
      DESCRIPTION      !Attribute group that includes all QOS-related attributes in
                       a managed object class! ;

REGISTERED AS    {joint-iso-ccitt   ms(9)   smi(3)   part4(4)   attributeGroup(8)
                 qosgroup(0)} ;
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

A.7 Action definitions

```
qOSResetAction ACTION

        BEHAVIOUR
            reset BEHAVIOUR
                DEFINED AS    !<Definition of the reset behaviour and its effect on
                              the operation of the managed object, etc..>!
            ;
        ;
        MODE CONFIRMED ;

REGISTERED AS    {joint-iso-ccitt ms(9) smi(3) part4(4) action(9) reset(0)} ;
```

NOTE – This action definition makes use of the in-line documentation option for the action Behaviour template. No abstract syntaxes are defined for invoke or reply.

```
activate ACTION

        BEHAVIOUR
            activateBehaviour BEHAVIOUR
                DEFINED AS    !Enables the managed object for operation. If the action
                              succeeds, the value successResponse is returned in the
                              responseCode parameter of the CMIP actionReplyInfo. If
                              the action fails because of a problem with the
                              underlying service provider, responseCode is set to the
                              value serviceProviderErrorResponse and the parameter
                              serviceProviderErrorResponseReason returned to indicate
                              the cause of the problem.!
            ;
        ;
        MODE CONFIRMED;
        PARAMETERS            serviceProviderErrorResponseReason ;
        WITH REPLY SYNTAX     ActionModule.ActivateReply;
REGISTERED AS    {joint-iso-ccitt ms(9) smi(3) part4(4) action(9) activate(1)};
```

A.8 Notification definitions

```
communicationError NOTIFICATION

        BEHAVIOUR                    communicationErrorBehaviour ;
        WITH INFORMATION SYNTAX      NotificationModule.ErrorInfo ;
        WITH REPLY SYNTAX            NotificationModule.ErrorResult ;

REGISTERED AS    {joint-iso-ccitt    ms(9)    smi(3)    part4(4)    notification(10)
                 commerror(0)} ;

protocolError NOTIFICATION

        BEHAVIOUR
            protocolErrorBehaviour BEHAVIOUR
                DEFINED AS    !Generated when a protocol entity receives a PDU which
                              is invalid or contains a protocol error. The
                              notification includes the header of the received PDU.!
            ;
        ;
        PARAMETERS                   pDUHeader;
        WITH INFORMATION SYNTAX      NotificationModule.ProtocolError;

REGISTERED AS    {joint-iso-ccitt    ms(9)    smi(3)    part4(4)    notification(10)
                 protoerror(1)};
```

NOTE – This template uses the in-line documentation option for documenting the behaviour.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

A.9 Behaviour definitions

qOSCounterBehaviour BEHAVIOUR

DEFINED AS !The QOS Error Counter attribute is a wraparound counter that is incremented by one for every occurrence of a QOS Error. Its value is a positive integer, whose range is specified in any package that references this definition. When the counter reaches its maximum value, the next increment causes its value to return to zero.! ;

qOSErrorBehaviour BEHAVIOUR

DEFINED AS !The QOS Error Cause attribute indicates the reason for a failure in quality of service associated with the managed object.

NOTE – The relationship between the permitted attribute values and the operation of the managed object itself are defined by the behaviour definitions associated with the managed object class definition. !;

communicationErrorBehaviour BEHAVIOUR

DEFINED AS !The CommunicationError notification is generated by the managed object class when a communication error is detected by the managed object. The notification may contain any combination of the parameters Probable Cause, Severity, Trend Indication, Backed Up Status, Diagnostic Info, Proposed Repair Action, Threshold Info, State Change and Other Info.

NOTE – The precise definition of what constitutes a communication error and the parameter values that apply is managed object class specific. In a practical example, this Behaviour definition could, for example, refer to pieces of specification in a base standard in order to specify the behaviour. !;

exampleClassBehaviour BEHAVIOUR

DEFINED AS !<....Description of managed object class behaviour, including
- How its attributes attain particular values and what they mean,
- What circumstances cause notifications to be generated,
- Etc. >! ;

A.10 ASN.1 modules

```
AttributeModule {joint-iso-ccitt ms(9) smi(3) part4(4) asn1Module(2) attributes(0)}
DEFINITIONS ::= BEGIN

ObjectName ::= GraphicString

QOSErrorCause ::= INTEGER {
                    responseTimeExcessive          (0),
                    queueSizeExceeded              (1),
                    bandwidthReduced               (2),
                    retransmissionRateExcessive    (3) }

QOSErrorCounter ::= INTEGER

QOSCounterRange ::= QOSErrorCounter {0..4294967296}      -- Range is 32 bits

END
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
NotificationModule {joint-iso-ccitt ms(9) smi(3) part4(4) asn1Module(2) notifications(1)}
DEFINITIONS ::= BEGIN

IMPORTS

ProbableCause, PerceivedSeverity, TrendIndication, BackedUpStatus, ProposedRepairActions,
ThresholdInfo, ManagementExtension

FROM Attribute.ASN1Module {joint-iso-ccitt ms(9) smi(3) part2(2) asn1Module(2) 1} ;

ErrorInfo ::= SET{

        [0] ProbableCause           OPTIONAL,
        [1] PerceivedSeverity       OPTIONAL,
        [2] TrendIndication         OPTIONAL,
        [3] BackedUpStatus          OPTIONAL,
        [4] ProposedRepairActions   OPTIONAL,
        [5] ThresholdInfo           OPTIONAL,
        [6] OtherInfo               OPTIONAL }

ErrorResult ::= NULL

OtherInfo       ::= SET OF ManagementExtension

ProtocolError   ::= SET OF ManagementExtension

END

ActionModule {joint-iso-ccitt ms(9) smi(3) part4(4) asn1Module(2) actions(2)}
DEFINITIONS ::= BEGIN

IMPORTS

OperationalState, ManagementExtension

FROM Attribute.ASN1Module {joint-iso-ccitt ms(9) smi(3) part2(2) asn1Module(2) 1} ;

ActivateReply ::= SEQUENCE {
                operationalStatus   [0] OperationalState,
                responseCode        [1] INTEGER {successResponse                (0),
                                                 serviceProviderErrorResponse   (1) },
                responseParams      [2] SET OF ManagementExtension OPTIONAL }

END

ParameterModule {joint-iso-ccitt ms(9) smi(3) part4(4) asn1Module(2) parameters(3)}
DEFINITIONS ::= BEGIN

ErrorInfo1 ::= INTEGER

ServiceProviderErrorResponseReason ::= ENUMERATED {
        insufficientResources       (0),
        providerDoesNotExist        (1),
        providerNotAvailable        (2),
        requiredServiceNotAvailable (3) }

PDUString ::= OCTETSTRING

END
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Index

Page

General principles for managed object definition . . . 12
- Attribute types . . . 14
- Attribute value relationships . . . 15
- Attribute value sets . . . 14
- Attributes . . . 14
- Commonality . . . 12
- Consistency . . . 15
- Counters . . . 16
- Denial of service . . . 17
- Event counters . . . 16
- Information conservation . . . 17
- Instantiation of superclasses . . . 13
- Managed object identification . . . 17
- Managed objects . . . 13
- Modelling of SAPs . . . 15
- Non-resettable counters . . . 16
- Notifications . . . 17
- Overlaps . . . 16
- PDU counters . . . 16
- Precision of attributes . . . 17
- Statistics . . . 15
- Structuring . . . 13
- Timers . . . 17
- Unrestricted superclasses . . . 14
- Updating of attributes . . . 17
- Use of operations . . . 18
- What to Manage . . . 12

Global issues . . . 5
- Complexity of managed object definitions . . . 11
- Conformance . . . 11
- Inherited characteristics . . . 6
- Initial value managed objects . . . 12
- Managed object creation and deletion . . . 11
- Optionality . . . 6
- Registration . . . 6
- Relationship integrity . . . 5
- Sources of initial attribute values . . . 12

Notational tools for managed object definition . . . 18
- Action template . . . 38
- Attribute group template . . . 36
- Attribute template . . . 33
- Behaviour template . . . 37
- Conventions used in template definitions . . . 19
- Managed object class template . . . 22
- Name binding template . . . 31
- Notification template . . . 39
- Overview of notational tools . . . 18
- Package template . . . 25
- Parameter template . . . 28

Object identifier allocation
- for actual class . . . 11
- for CMIP . . . 8
- for function standards . . . 10
- for SMI standards . . . 10
- for Systems Management Overview . . . 7

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Template global symbol definitions

delimited-string . . . 22
document-identifier . . . 21
object-identifier . . . 20
supporting productions . . . 19
text-delimiter . . . 22
type-reference . . . 22
value-reference . . . 22

Template keywords

ACTION . . . 38
ACTION-INFO . . . 30
ACTION-REPLY . . . 30
ACTIONS . . . 26, 27
ADD-REMOVE . . . 26
AND ATTRIBUTE IDS . . . 40
AND SUBCLASSES . . . 32
ATTRIBUTE . . . 30, 31, 34
ATTRIBUTE GROUP . . . 36
ATTRIBUTE GROUPS . . . 26, 27
ATTRIBUTES . . . 26, 27
BEHAVIOUR . . . 26, 30-32, 34, 35, 37-40
CHARACTERIZED BY . . . 23, 25
CONDITIONAL PACKAGES . . . 23, 25
CONTEXT . . . 30
CREATE . . . 32
DEFAULT VALUE . . . 26
DEFINED AS . . . 20, 37
DELETE . . . 32, 33
DELETES-CONTAINED-OBJECTS . . . 32
DERIVATION RULE . . . 26
DERIVED FROM . . . 23, 34
DESCRIPTION . . . 36, 37
EQUALITY . . . 34, 35
EVENT-INFO . . . 30
EVENT-REPLY . . . 30
FIXED . . . 36
GET-REPLACE . . . 26
GROUP ELEMENTS . . . 36
INITIAL VALUE . . . 26
MATCHES FOR . . . 34, 35
MODE CONFIRMED . . . 38, 39
NAME BINDING . . . 32
NAMED BY SUPERIOR OBJECT CLASS . . . 32
NOTIFICATION . . . 40
NOTIFICATIONS . . . 26, 28
ORDERING . . . 34, 35
PACKAGE . . . 26
PARAMETER . . . 30
PARAMETERS . . . 34, 35, 38-40
PERMITTED VALUES . . . 26
PRESENT IF . . . 23, 25
REGISTERED AS . . . 20, 23, 25, 26, 28, 30-41
REMOVE . . . 26
REPLACE . . . 26
REPLACE-WITH-DEFAULT . . . 26
REQUIRED VALUES . . . 26
SET-COMPARISON . . . 34, 35
SET-INTERSECTION . . . 34, 35
SPECIFIC-ERROR . . . 30
SUBORDINATE OBJECT CLASS . . . 32

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

SUBSTRINGS 34, 35
WITH ATTRIBUTE 32
WITH ATTRIBUTE SYNTAX 34, 35
WITH INFORMATION SYNTAX 38-40
WITH REPLY SYNTAX 38-40
WITH SYNTAX 30
WITH-AUTOMATIC-INSTANCE-NAMING 32
WITH-REFERENCE-OBJECT 32

Template label references
action-label 26, 27
attribute-label 26, 27, 30, 32, 34, 36, 40
behaviour-definition-label 26, 30-32, 34, 35, 38-40
class-label 23, 32
group-label 26, 27
notification-label 26, 28
package-label 23, 25
parameter-label 26-28, 32-35, 38-40

Template labels
action-label 38
attribute-label 34
behaviour-definition-label 37
class-label 23
group-label 36
name-binding-label 32
notification-label 40
package-label 26
parameter-label 30

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

UDC 681.3:691.39

Descriptors: data processing, information interchange, network interconnection, open systems interconnection, management, information.

Price based on 50 pages

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale