**INTERNATIONAL STANDARD ISO/IEC 10165-5:1994**
TECHNICAL CORRIGENDUM 2

Published 2002-04-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

# Information technology — Open Systems Interconnection — Structure of management information: Generic management information

TECHNICAL CORRIGENDUM 2

*Technologies de l'information — Interconnexion de systèmes ouverts (OSI) — Structure des informations de gestion: Informations génériques de gestion*

*RECTIFICATIF TECHNIQUE 2*

Technical Corrigendum 2 to International Standard ISO/IEC 10165-5:1994 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*.

**ICS 35.100.70** **Ref. No. ISO/IEC 10165-5:1994/Cor.2:2002(E)**

© ISO/IEC 2002 – All rights reserved

Printed in Switzerland

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

**INTERNATIONAL STANDARD**
**ITU-T RECOMMENDATION**

# INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION – STRUCTURE OF MANAGEMENT INFORMATION: GENERIC MANAGEMENT INFORMATION

## TECHNICAL CORRIGENDUM 2

## 1) Subclause 2.1

*Insert the following reference alphanumerically:*

- ITU-T Recommendation X.200 (1994) | ISO/IEC 7498-1:1994, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model.*
- ITU-T Recommendation X.680 (1997) | ISO/IEC 8824-1:1998, *Information technology – Abstract Syntax Notation One (ASN.1): Specification of basic notation.*
- ITU-T Recommendation X.710 (1997) | ISO/IEC 9595:1998, *Information technology – Open Systems Interconnection – Common Management Information service.*
- ITU-T Recommendation X.711 (1997) | ISO/IEC 9596:1998, *Information technology – Open Systems Interconnection – Common Management Information Protocol: Specification.*

## 2) Subclause 2.2

*Remove the following paired references:*

- CCITT Recommendation X.208 (1988), *Specification of Abstract Syntax Notation One (ASN.1).*

  ISO/IEC 8824:1990, *Information technology – Open Systems Interconnection – Specification of Abstract Syntax Notation One (ASN.1).*

## 3) Clause 13

*Replace:*

```
-- NOTE – This Recommendation | International Standard imports RelativeDistinguishedName from
-- CCITT Rec. X.501 (1988) | ISO/IEC 9594-2:1990. The specification for this syntax can now be
-- found in an informative annex of ITU-T Rec. X.711 (1997) | ISO/IEC 9596-1:1998.
RelativeDistinguishedName
        FROM InformationFramework {joint-iso-ccitt(2) ds(5) modules(1) informationFramework(1)}
```

*with:*

```
RelativeDistinguishedName
        FROM CMIP-1 {joint-iso-itu-t(2) ms(9) cmip(1) modules(0) protocol(3)}
```

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

STD.ISO 10165-5-ENGL 1994 ■ 4851903 0775848 885 ■

**INTERNATIONAL STANDARD ISO/IEC 10165-5:1994**
TECHNICAL CORRIGENDUM 1

Published 1998-12-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ELECTROTECHNIQUE INTERNATIONALE

# Information technology — Open Systems Interconnection — Structure of management information: Generic management information

## TECHNICAL CORRIGENDUM 1

*Technologies de l'information — Interconnexion de systèmes ouverts (OSI) — Structure des informations de gestion: Information génériques de gestion*

*RECTIFICATIF TECHNIQUE 1*

Technical Corrigendum 1 to International Standard ISO/IEC 10165-5:1994 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology.*

**This material is reproduced from ISO documents under International Organization for Standardization (ISO) Copyright License Number IHS/ICC/1996. Not for resale. No part of these ISO documents may be reproduced in any form, electronic retrieval system or otherwise, except as allowed in the copyright law of the country of use, or with the prior written consent of ISO (Case postale 56, 1211 Geneva 20, Switzerland, Fax +41 22 734 10 79), IHS or the ISO Licensor's members.**

**ICS 35.100.70** **Ref. No. ISO/IEC 10165-5:1994/Cor.1:1998(E)**

© **ISO/IEC 1998**

Printed in Switzerland

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

**INTERNATIONAL STANDARD**

**ITU-T RECOMMENDATION**

# INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION – STRUCTURE OF MANAGEMENT INFORMATION: GENERIC MANAGEMENT INFORMATION

## TECHNICAL CORRIGENDUM 1

## 1) Clause 13

*Before* **IMPORTS FROM InformationFramework**, *add the following ASN.1 comment Note:*

```
-- NOTE – This Recommendation | International Standard imports RelativeDistinguishedName from
-- CCITT Rec. X.501 (1988) | ISO/IEC 9594-2:1990. The specification for this syntax can now be
-- found in an informative annex of ITU-T Rec. X.711 (1997) | ISO/IEC 9596-1:1998.
```



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10165 PT*5 94 ■ 4851903 0569938 77T ■

INTERNATIONAL STANDARD

# ISO/IEC 10165-5

First edition
1994-08-01

# Information technology — Open Systems Interconnection — Structure of management information: Generic management information

*Technologies de l'information — Interconnexion de systèmes ouverts (OSI) — Structure des informations de gestion: Informations de gestion génériques*




Reference number
ISO/IEC 10165-5:1994(E)

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

# CONTENTS


| | | *Page* |
|---|---|---|
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Definitions | 2 |
| 4 | Abbreviations | 3 |
| 5 | Conventions | 3 |
| 6 | Overview | 3 |
| 7 | Generic managed object class definitions | 4 |
| 8 | Name bindings | 9 |
| 9 | Attributes | 10 |
| 10 | Attribute Groups | 15 |
| 11 | Actions | 16 |
| 12 | Notifications | 17 |
| 13 | ASN.1 definitions | 18 |


© ISO/IEC 1994
All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10165 PT*5 94 ■ 4851903 0570073 319 ■



# Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 10165-5 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in collaboration with ITU-T. The identical text is published as ITU-T Recommendation X.723.

ISO/IEC 10165 consists of the following parts, under the general title *Information technology — Open Systems Interconnection — Structure of management information*:

— *Part 1: Management information model*

— *Part 2: Definition of management information*

— *Part 4: Guidelines for the definition of managed objects*

— *Part 5: Generic management information*

— *Part 6: Requirements and guidelines for implementation conformance statement proformas associated with management information*



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

# Introduction

ISO/IEC 10165 is a multipart standard developed according to ISO 7498 and ISO/IEC 7498-4. ISO/IEC 10165 is related to the following International Standards:

- ISO/IEC 9595:1990, *Information technology – Open Systems Interconnection – Common management information service definition*;
- ISO/IEC 9596:1990, *Information technology – Open Systems Interconnection – Common management information protocol*;
- ISO/IEC 10040:1992, *Information technology – Open Systems Interconnection – Systems management overview*;
- ISO/IEC 10164:1992, *Information technology – Open Systems Interconnection – Systems Management.*



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

INTERNATIONAL STANDARD

ITU-T RECOMMENDATION

# INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION – STRUCTURE OF MANAGEMENT INFORMATION: GENERIC MANAGEMENT INFORMATION

## 1 Scope

This Recommendation | International Standard provides developers of OSI Recommendations | International Standards that contain managed object definitions with generic definitions of managed object classes that will

- provide common superclass definitions from which layer- or resource- specific object class definitions may be derived;
- assist with the development of common elements of object class definitions across multiple layers or components of layers;
- reduce duplication of effort in other working groups by identifying commonly useful definitions.

To this end, this Recommendation | International Standard defines managed object classes which may be used as superclasses, using the template notation defined in CCITT Rec. X.722 | ISO/IEC 10165-4, including the definition of any packages, attributes, attribute groups, behaviour, actions, notifications and parameters that may be associated with the superclasses. It also defines functional units required by layer- or resource-specific management standards which are not defined in the CCITT Rec. X.73X | ISO/IEC 10164 series of systems management function standards.

This Recommendation | International Standard is applicable to the development of any OSI Recommendation | International Standard which defines managed object classes that may be refined from the managed object classes defined in this Recommendation | International Standard.

This Recommendation | International Standard does not specify or imply any constraints on the development of managed object definitions in terms of their inheritance relationships. Developers of managed object class definitions are encouraged to use the definitions contained in this Recommendation | International Standard to promote consistency between similar managed object classes; however, use of these definitions is not mandated.

## 2 Normative references

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and International Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and International Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The ITU-T maintains a list of the currently valid Recommendations.

### 2.1 Identical Recommendations | International Standards

- CCITT Recommendation X.701 (1992) | ISO/IEC 10040:1992, *Information technology – Open Systems Interconnection – Systems Management Overview.*
- CCITT Recommendation X.720 (1992) | ISO/IEC 10165-1:1992, *Information technology – Open Systems Interconnection – Structure of Management Information: Management Information Model.*
- CCITT Recommendation X.721 (1992) | ISO/IEC 10165-2:1992, *Information technology – Open Systems Interconnection – Structure of Management Information: Definition of Management Information.*



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

- CCITT Recommendation X.722 (1992) | ISO/IEC 10165-4:1992, *Information technology – Open Systems Interconnection – Structure of Management Information: Guidelines for the Definition of Managed Objects.*
- CCITT Recommendation X.731 (1992) | ISO/IEC 10164-2:1992, *Information technology – Open Systems Interconnection – Systems Management: State Management Function.*

### 2.2 Paired Recommendations | International Standards equivalent in technical content

- CCITT Recommendation X.200 (1989), *Reference Model of Open Systems Interconnection for CCITT Applications.*

  ISO 7498:1984, *Information processing systems – Open Systems Interconnection – Basic Reference Model.*
- CCITT Recommendation X.208 (1989), *Specification of abstract syntax notation one (ASN.1).*

  ISO/IEC 8824:1990, *Information technology – Open Systems Interconnection – Specification of Abstract Syntax Notation One (ASN.1).*
- CCITT Recommendation X.700 (1992), *Management Framework Definition for Open Systems Interconnection (OSI) for CCITT Applications.*

  ISO 7498-4:1989, *Information processing systems – Open Systems Interconnection – Basic Reference Model – Part 4: Management Framework.*
- CCITT Recommendation X.710 (1991), *Common Management Information Service Definition for CCITT Applications.*

  ISO/IEC 9595:1991, *Information technology – Open Systems Interconnection – Common management information service definition.*

## 3 Definitions

For the purposes of this Recommendation | International Standard, the following definitions apply.

### 3.1 Basic reference model definitions

This Recommendation | International Standard uses the following terms defined in CCITT Rec. X.200 | ISO 7498:

a) (N)-SAP;
b) open system;
c) systems management;
d) application process.

### 3.2 Management framework definitions

This Recommendation | International Standard uses the following terms defined in CCITT Rec. X.700 | ISO/IEC 7498-4:

managed object.

### 3.3 Systems management overview definitions

This Recommendation | International Standard uses the following terms defined in CCITT Rec. X.701 | ISO/IEC 10040:

a) generic definitions;
b) managed object class;
c) management information;
d) notification.

### 3.4 Management information model definitions

This Recommendation | International Standard uses the following terms defined in CCITT Rec. X.720 | ISO/IEC 10165-1:

a) allomorphism;
b) attribute type;
c) behaviour;
d) containment;



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

e) name binding;
f) package;
g) specialization;
h) subordinate object;
i) superclass;
j) superior object.

### 3.5 CMIS definitions

This Recommendation | International Standard uses the following terms defined in CCITT Rec. X.710 | ISO/IEC 9595:

attribute.

### 3.6 ASN.1 definitions

This Recommendation | International Standard uses the following terms defined in CCITT Rec. X.208 | ISO/IEC 8824:

a) object identifier;
b) sequence-of type;
c) sequence type;
d) set-of type;
e) set type;
f) type.

### 3.7 GDMO definitions

This Recommendation | International Standard uses the following terms defined in CCITT Rec. X.722 | ISO/IEC 10165-4:

a) managed object class definition;
b) template.

## 4 Abbreviations

| | |
|---|---|
| ASN.1 | Abstract Syntax Notation One |
| CL | Connectionless |
| CMIS | Common Management Information Service |
| CO | Connection Oriented |
| GDMO | Guidelines for the Definition of Managed Objects |
| GMI | Generic Management Information |
| OSI | Open Systems Interconnection |
| PDU | Protocol Data Unit |
| SAP | Service Access Point |
| SMI | Structure of Management Information |

## 5 Conventions

This Recommendation | International Standard uses the template notation defined in CCITT Rec. X.722 | ISO/IEC 10165-4 as the notation for defining managed object classes and the abstract syntax notation defined in CCITT Rec. X.208 | ISO/IEC 8824 as the means of defining ASN.1 data types associated with the use of the template notation.

Text based on these notational conventions is printed in a distinctive typeface.

## 6 Overview

The purpose of this Recommendation | International Standard is to document structures for managed object classes and management information types that are common to more than one open system resource, by defining those common structures as generic definitions of management information. Other work items, such as those concerned with the



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

management of individual OSI layers, may specialize these generic definitions in ways that are appropriate for the requirements of the layer or resource concerned. In the process of specialization, the generic managed object classes defined in this Recommendation | International Standard may be defined as superclasses of allomorphic classes where appropriate. The use of generic managed object classes in this way will help to ensure the consistency and completeness of managed object class definitions for such resources as layer entities, SAPs, connections, etc., and also take account of relationships between them. Similar advantages may be gained by defining managed object classes corresponding to components of OSI layers, such as subnetworks.

Definers of management information are also encouraged to use the definitions contained in CCITT Rec. X.721 | ISO/IEC 10165-2 where they are applicable to the managed object classes or other information types being defined.

# 7 Generic managed object class definitions

This clause contains managed object class definitions for generic managed object classes, along with their mandatory and conditional packages and behaviour definitions. The definitions have been documented "in-line" with the exception of the attribute definitions which are to be found in clause 9.

## 7.1 Application process

The applicationProcess managed object class is used to represent an element within a system which performs the information processing for a particular application. The supportEntityNames attribute contains a set of distinguished names of supporting entities which provide communication services to the application process.

The semantics and syntax of the operationalState attribute are defined in CCITT Rec. X.731 | ISO/IEC 10164-2 and CCITT Rec. X.721 | ISO/IEC 10165-2.

```
applicationProcess MANAGED OBJECT CLASS

    DERIVED FROM "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2 : 1992":top ;

    CHARACTERIZED BY

        applicationProcessP1        PACKAGE

            BEHAVIOUR
                applicationProcessB1   BEHAVIOUR
                    DEFINED AS
                        !An application process supports the disabled and enabled values of the operationalState attribute as
                        described in CCITT Rec. X.731 (1992) | ISO/IEC 10164-2:1992 as follows:
                        - an application process is disabled if it is inoperable or a resource on which it depends is inoperable,
                        - an application process is enabled if it is operable.!
                    ;
            ;
            ATTRIBUTES      applicationProcessId      GET,
                            applicationProcessTitle   GET,
                            supportEntityNames GET,
                            "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992":operationalState GET
            ;
        ;
    ;
REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) managedObjectClass(3) applicationProcess(8)} ;
```

## 7.2 Communications entity

The communications entity managed object class is used to represent an active functional element which performs communication processing functions within a system, e.g. Network Entity, Transport Entity, etc. The localSapNames attribute contains a set of distinguished names of layer (N-1) SAPs or ports at which services are provided to the entity.

NOTE 1 – Although the localSapNames attribute is for generality defined as a set valued attribute and may therefore contain zero or more SAP names, the set membership is, in most cases, limited to a single SAP name.



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

The semantics and syntax of the operationalState attribute are defined in CCITT Rec. X.731 (1992) | ISO/IEC 10164-2:1992 and CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992.

NOTE 2 – In circumstances where both connection oriented and connectionless services are available at a particular layer, the further refinement of the communications entity managed object class to distinguish between connection oriented and connectionless entities is discouraged, as it becomes unclear under some circumstances (particularly under error conditions) as to what belongs to the CO entity and what belongs to the CL entity (e.g. If a corrupted PDU is received, is it the CO counter of corrupted PDUs that is incremented, or is it the CL counter, or both?).

```
communicationsEntity        MANAGED OBJECT CLASS

    DERIVED FROM            "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992":top ;

    CHARACTERIZED BY

        communicationsEntityP1 PACKAGE

            BEHAVIOUR
                communicationsEntityB1 BEHAVIOUR
                    DEFINED AS
                        !A communications entity supports the disabled and enabled values of the operationalState attribute
                        as described in CCITT Rec. X.731 (1992) | ISO/IEC 10164-2:1992 as follows:
                        - an entity is disabled if it is inoperable or a resource on which it depends is inoperable,
                        - an entity is enabled if it is operable.!
                ;
            ;
            ATTRIBUTES      communicationsEntityId GET,
                            localSapNames GET,
                            "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992":operationalState GET
            ;
        ;
    ;
REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) managedObjectClass(3) communicationsEntity(0)} ;
```

## 7.3 Communications information record

The communicationsInformationRecord managed object class is used to define the information stored in a log as a result of receiving event reports or potential event reports with a communication information event type. The semantics of the managed object class, namely its attributes and behaviour, are derived from the communicationsInformation notification.

```
communicationsInformationRecord MANAGED OBJECT CLASS

    DERIVED FROM "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992":eventLogRecord;

    CHARACTERIZED BY
        communicationsInformationRecordP1 PACKAGE
            BEHAVIOUR
                communicationsInformationRecordB1 BEHAVIOUR
                    DEFINED AS
                        !Log record class for communicationsInformation events.!
                ;
            ;
            ATTRIBUTES      informationType GET;
    ;
    ;
    CONDITIONAL PACKAGES
        informationDataPackage PACKAGE
            ATTRIBUTES
                informationData GET
            ;
        REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) package(4) informationDataPackage(0)};
        PRESENT IF  !The informationData parameter is present in the communicationsInformation event report
                    corresponding to the instance of communicationsInformationRecord.!
    ;
REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) managedObjectClass(3) informationData(1)};
```



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

## 7.4 Connectionless-mode protocol machine

The connectionless-mode protocol machine managed object class is used to represent a protocol machine performing connectionless-mode communications functions within an entity.

```
clProtocolMachine   MANAGED OBJECT CLASS

    DERIVED FROM "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992":top ;

    CHARACTERIZED BY

    clProtocolMachineP1  PACKAGE

        BEHAVIOUR
          clProtocolMachineB1  BEHAVIOUR
              DEFINED AS
                  !A protocol machine which performs connectionless-mode communications functions.!
          ;
        ;
        ATTRIBUTES     clProtocolMachineId      GET,
                       "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992":operationalState    GET;
        ;
    ;
    CONDITIONAL PACKAGES
        clProtocolMachineP2 PACKAGE
          ATTRIBUTES totalRemoteSAPs   GET ;
        REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) package(4) clProtocolMachineP2(1)} ;
        PRESENT IF     !there is a requirement to keep statistics concerning remote connectionless protocol machines
                       that this protocol machine communicates with!
    ;
REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) managedObjectClass(3) clProtocolMachine(2)} ;
```

## 7.5 Connection-mode protocol machine

The connection-mode protocol machine managed object class is used to represent a protocol machine performing connection-mode communications functions within an entity.

```
coProtocolMachine   MANAGED OBJECT CLASS

    DERIVED FROM "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992":top ;

    CHARACTERIZED BY

        coProtocolMachineP1     PACKAGE

          BEHAVIOUR
             coProtocolMachineB1   BEHAVIOUR
                 DEFINED AS
                     !A protocol machine which performs connection-mode communications functions.!
             ;
          ;
          ATTRIBUTES      coProtocolMachineId      GET,
                          "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992":operationalState    GET
          ;
        ;
    ;
REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) managedObjectClass(3) coProtocolMachine(3)} ;
```

## 7.6 Sap 1

The sap1 managed object class is used to represent a service access point at which services are provided by an entity to the user entity, where the SAP address is dependent on the SAP address of the underlying layer.



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

The sap1Address attribute contains the selector which is contributed to the address of the SAP by this layer.

The userEntityNames attribute contains the distinguished names of the managed objects that represent the user entities that are using the SAP.

```
sap1        MANAGED OBJECT CLASS

   DERIVED FROM   "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992":top ;

   CHARACTERIZED BY

      sap1P1 PACKAGE

        BEHAVIOUR
          sap1B1 BEHAVIOUR
             DEFINED AS
                !This managed object represents the point at which an entity provides services to the user entity. Refer
                to the Basic Reference Model for the definition of (N)-SAP.!
          ;
        ;
        ATTRIBUTES      sapId GET,
                        sap1Address GET,
                        userEntityNames GET
        ;
      ;
   ;
REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) managedObjectClass(3) sap1(4)} ;
```

## 7.7 Sap 2

The sap2 managed object class is used to represent a service access point, the address of which is independent of the SAP address of the underlying layer.

The sap2Address attribute contains the address of the SAP.

The userEntityNames attribute contains the distinguished names of the managed objects that represent the user entities that are using the SAP.

The providerEntityNames attribute contains the distinguished names of the managed objects that represent the provider entities that are supporting the SAP.

```
sap2        MANAGED OBJECT CLASS

   DERIVED FROM "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992":top;

   CHARACTERIZED BY

      sap2P1   PACKAGE

        BEHAVIOUR
          sap2B1   BEHAVIOUR
             DEFINED AS
                !A service access point, the address of which is independent of the SAP address of the underlying
                layer.!
          ;
        ;
        ATTRIBUTES      sapId GET,
                        sap2Address GET,
                        userEntityNames GET,
                        providerEntityNames GET
        ;
      ;
   ;
REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) managedObjectClass(3) sap2(5)} ;
```



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

## 7.8 Single peer connection

The single peer connection managed object class is used to represent an association or a connection established between entities for the transfer of service or protocol data.

The underlyingConnectionNames attribute contains the distinguished names of the managed objects that represent the underlying connections or physical media used by the connection.

```
singlePeerConnection  MANAGED OBJECT CLASS

    DERIVED FROM   "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992":top ;

    CHARACTERIZED BY

        singlePeerConnectionP1 PACKAGE

            BEHAVIOUR
              singlePeerConnectionB1 BEHAVIOUR
                  DEFINED AS
                      !This managed object class represents a view of a single peer connection between a pair of entities.!
              ;
            ;
            ATTRIBUTES      connectionId GET,
                            underlyingConnectionNames GET
            ;
        ;
    ;
    CONDITIONAL PACKAGES
        singlePeerConnectionP2 PACKAGE
          ATTRIBUTES      supportedConnectionNames GET
          ;
        REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) package(4) spcP2(2)} ;
        PRESENT IF !The names of the connections supported by this connection can be provided!
    ;
REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) managedObjectClass(3) singlePeerConnection(6)} ;
```

## 7.9 Subsystem

The subsystem managed object class may be used as a common containment point for managed objects in a system that relate to the operation of a given layer. The choice of structuring within a system is dependent on what structure the system designer wishes to present externally for management purposes. The subsystemId attribute is used to identify the subsystem concerned.

```
subsystem           MANAGED OBJECT CLASS

    DERIVED FROM   "CCITT Rec. X.721 (1992) | ISO/IEC 10165-2:1992":top ;

    CHARACTERIZED BY

        subsystemP1 PACKAGE

            BEHAVIOUR
              subsystemB1 BEHAVIOUR
                  DEFINED AS
                      !This managed object class represents a portion of a system where components are named
                      independently of the components of other subsystems.!
              ;
            ;
            ATTRIBUTES      subsystemId GET
            ;
        ;
    ;
REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) managedObjectClass(3) subsystem(7)} ;
```



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

# 8 Name bindings

This clause provides definitions of name bindings that may be applicable to the generic managed object classes defined in this Recommendation | International Standard. Other name bindings may be defined and used with these managed object classes.

## 8.1 ApplicationProcess-System

applicationProcess-system NAME BINDING

| | |
|---|---|
| SUBORDINATE OBJECT CLASS | applicationProcess AND SUBCLASSES ; |
| NAMED BY SUPERIOR OBJECT CLASS | "CCITT Rec. X.721 (1992) \| ISO/IEC 10165-2:1992":system AND SUBCLASSES ; |
| WITH ATTRIBUTE | applicationProcessId ; |

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) nameBinding(6) ap-s(7)} ;

## 8.2 CLProtocolMachine-CommunicationsEntity

clProtocolMachine-entity NAME BINDING

| | |
|---|---|
| SUBORDINATE OBJECT CLASS | clProtocolMachine AND SUBCLASSES ; |
| NAMED BY SUPERIOR OBJECT CLASS | communicationsEntity AND SUBCLASSES ; |
| WITH ATTRIBUTE | clProtocolMachineId ; |

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) nameBinding(6) clpm-e(0)} ;

## 8.3 CommunicationsEntity-Subsystem

communicationsEntity-subsystem NAME BINDING

| | |
|---|---|
| SUBORDINATE OBJECT CLASS | communicationsEntity AND SUBCLASSES ; |
| NAMED BY SUPERIOR OBJECT CLASS | subsystem AND SUBCLASSES ; |
| WITH ATTRIBUTE | communicationsEntityId ; |

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) nameBinding(6) ce-s(1)} ;

## 8.4 COProtocolMachine-CommunicationsEntity

coProtocolMachine-entity NAME BINDING

| | |
|---|---|
| SUBORDINATE OBJECT CLASS | coProtocolMachine AND SUBCLASSES ; |
| NAMED BY SUPERIOR OBJECT CLASS | communicationsEntity AND SUBCLASSES ; |
| WITH ATTRIBUTE | coProtocolMachineId ; |

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) nameBinding(6) copm-e(2)} ;

## 8.5 Sap1-CommunicationsEntity

sap1-communicationsEntity NAME BINDING

| | |
|---|---|
| SUBORDINATE OBJECT CLASS | sap1 AND SUBCLASSES ; |
| NAMED BY SUPERIOR OBJECT CLASS | communicationsEntity AND SUBCLASSES ; |
| WITH ATTRIBUTE | sapId ; |

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) nameBinding(6) s1-ce(3)} ;



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

## 8.6 Sap2-Subsystem

sap2-subsystem NAME BINDING

| | |
|---|---|
| SUBORDINATE OBJECT CLASS | sap2 AND SUBCLASSES ; |
| NAMED BY SUPERIOR OBJECT CLASS | subsystem AND SUBCLASSES ; |
| WITH ATTRIBUTE | sapId ; |

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) nameBinding(6) s2-s(4)} ;

## 8.7 SinglePeerConnection-COProtocolMachine

singlePeerConnection-coProtocolMachine NAME BINDING

| | |
|---|---|
| SUBORDINATE OBJECT CLASS | singlePeerConnection AND SUBCLASSES ; |
| NAMED BY SUPERIOR OBJECT CLASS | coProtocolMachine AND SUBCLASSES ; |
| WITH ATTRIBUTE | connectionId ; |

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) nameBinding(6) spc-copm(5)} ;

## 8.8 Subsystem-System

subsystem-system NAME BINDING

| | |
|---|---|
| SUBORDINATE OBJECT CLASS | subsystem AND SUBCLASSES ; |
| NAMED BY SUPERIOR OBJECT CLASS | "CCITT Rec. X.721 (1992) \| ISO/IEC 10165-2:1992":system AND SUBCLASSES ; |
| WITH ATTRIBUTE | subsystemId ; |

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) nameBinding(6) su-s(6)} ;

# 9 Attributes

This clause defines attribute types that are referenced by the managed object class definitions contained in this Recommendation | International Standard.

## 9.1 ApplicationProcessId

The applicationProcessId attribute type is used in naming instances of the applicationProcess managed object class.

applicationProcessId ATTRIBUTE

| | |
|---|---|
| WITH ATTRIBUTE SYNTAX | GMI-AttributeModule.ApplicationProcessId ; |
| MATCHES FOR | EQUALITY ; |

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) applicationProcessId(16)} ;

## 9.2 ApplicationProcessTitle

The applicationProcessTitle attribute type is used to specify the object identifier name form or directory name form of an application process. If not known, the value of this attribute is set to null.

applicationProcessTitle ATTRIBUTE

| | |
|---|---|
| WITH ATTRIBUTE SYNTAX | GMI-AttributeModule.ApplicationProcessTitle ; |
| MATCHES FOR | EQUALITY ; |

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) applicationProcessTitle(17)} ;



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

## 9.3 CommunicationsEntityId

The communicationsEntityId attribute type is used in naming instances of the communicationsEntity managed object class.

communicationsEntityId ATTRIBUTE

| | |
|---|---|
| WITH ATTRIBUTE SYNTAX | GMI-AttributeModule.CommunicationsEntityId ; |
| MATCHES FOR | EQUALITY ; |

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) communicationsEntityId(0)} ;

## 9.4 ConnectionId

The connectionId attribute type is used in naming instances of the connection managed object class.

connectionId ATTRIBUTE

| | |
|---|---|
| WITH ATTRIBUTE SYNTAX | GMI-AttributeModule.ConnectionId ; |
| MATCHES FOR | EQUALITY ; |

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) connectionId(1)} ;

## 9.5 Connectionless-mode protocol machine Id

The clProtocolMachineId attribute type is used in naming instances of the connectionless-mode protocol machine managed object class.

clProtocolMachineId ATTRIBUTE

| | |
|---|---|
| WITH ATTRIBUTE SYNTAX | GMI-AttributeModule.ProtocolMachineId ; |
| MATCHES FOR | EQUALITY ; |

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) clProtocolMachineId(2)} ;

## 9.6 Connection-mode protocol machine Id

The coProtocolMachineId attribute type is used in naming instances of the connection-mode protocol machine managed object class.

coProtocolMachineId ATTRIBUTE

| | |
|---|---|
| WITH ATTRIBUTE SYNTAX | GMI-AttributeModule.ProtocolMachineId ; |
| MATCHES FOR | EQUALITY ; |

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) coProtocolMachineId(3)} ;

## 9.7 GenericNonWrappingCounter

This is a non-instantiable generic counter definition from which non-wrapping counters with specific characteristics may be derived.



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
genericNonWrappingCounter ATTRIBUTE
    WITH ATTRIBUTE SYNTAX     GMI-AttributeModule.GenericCounter;
    MATCHES FOR    EQUALITY, ORDERING;
    BEHAVIOUR
        genericNonWrappingCounterB BEHAVIOUR
          DEFINED AS
            !The counter shall have a mandatory initial value of zero and places an upper bound on the attribute value.
            The value of the counter shall be incremented by an amount as specified in other behaviour definitions
            associated with this attribute definition. When the counter value reaches the upper bound, its value is held at
            the value of the upper bound. This does not require the system to maintain a counter large enough to
            accommodate this maximum value if the characteristics of the implementation are such that all achievable
            count values are less than this maximum value.!;
    ;
;   -- NOTE – Since this attribute is never instantiated, there is no REGISTERED AS construct.
```

## 9.8 GenericWrappingCounter

This is a non-instantiable generic counter definition from which wrapping counters with specific characteristics may be derived.

```
genericWrappingCounter ATTRIBUTE
    WITH ATTRIBUTE SYNTAX GMI-AttributeModule.GenericCounter;
    MATCHES FOR EQUALITY ;
    BEHAVIOUR
        genericWrappingCounterB BEHAVIOUR
            DEFINED AS
                !The counter shall have a mandatory initial value of zero and places an upper bound on the attribute value.
                The value of the counter shall be incremented by an amount as specified in other behaviour definitions
                associated with this attribute definition. When the counter value reaches the upper bound, a further
                increment causes the counter value to wrap. This does not require the system to maintain a counter large
                enough to accommodate this maximum value if the characteristics of the implementation are such that all
                achievable count values are less than this maximum value.!
        ;
    ;
;   -- NOTE – Since this attribute is never instantiated, there is no REGISTERED AS construct.
```

## 9.9 InformationData

This attribute represents the structure of the information to be held in a communicationsInformationRecord managed object.

```
informationData ATTRIBUTE
    WITH ATTRIBUTE SYNTAX GMI-AttributeModule.InformationData;
REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) informationData(4)};
```

## 9.10 InformationType

This attribute represents the type of information to be held in a communicationsInformationRecord managed object.

```
informationType ATTRIBUTE
    WITH ATTRIBUTE SYNTAX GMI-AttributeModule.InformationType;
    MATCHES FOR EQUALITY;
REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) informationType(5)};
```

## 9.11 LocalSapNames

The semantics of the localSapNames attribute type are defined in 7.2.

```
localSapNames ATTRIBUTE

    WITH ATTRIBUTE SYNTAX     GMI-AttributeModule.GroupObjects ;
     MATCHES FOR      EQUALITY, SET-COMPARISON, SET-INTERSECTION ;

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) localSapNames(6)} ;
```



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

## 9.12 NonWrapping64BitCounter

This is a non-wrapping counter which has an upper bound of 2^64-1.

```
nonWrapping64BitCounter ATTRIBUTE

    WITH ATTRIBUTE SYNTAX GMI-AttributeModule.Generic64BitCounter ;
    MATCHES FOR EQUALITY, ORDERING ;
    BEHAVIOUR genericNonWrappingCounterB ;
;   -- As this attribute is never instantiated, there is no REGISTERED AS construct. Instantiable attribute
    -- definitions derived from this definition shall specify the circumstances under which the attribute value is
    -- incremented.
```

## 9.13 ProviderEntityNames

The semantics of the ProviderEntityNames attribute type are defined in 7.7.

```
providerEntityNames ATTRIBUTE

    WITH ATTRIBUTE SYNTAX     GMI-AttributeModule.GroupObjects ;
     MATCHES FOR      EQUALITY, SET-COMPARISON, SET-INTERSECTION ;
     BEHAVIOUR
        providerEntityNamesB        BEHAVIOUR
          DEFINED AS      !The distinguished names of the (N-1) layer entities which provide services to this SAP.!
        ;
    ;

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) providerEntityNames(7)} ;
```

## 9.14 Sap1Address

The semantics of the sap1Address attribute type are defined in 7.6.

```
sap1Address ATTRIBUTE

    WITH ATTRIBUTE SYNTAX     GMI-AttributeModule.Sap1Address ;
    MATCHES FOR               EQUALITY ;

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) sap1Address(8)} ;
```

## 9.15 Sap2Address

The semantics of the sap2Address attribute type are defined in 7.7.

```
sap2Address ATTRIBUTE

    WITH ATTRIBUTE SYNTAX     GMI-AttributeModule.Sap2Address ;
    MATCHES FOR    EQUALITY, SET-COMPARISON, SET-INTERSECTION ;
    BEHAVIOUR
        sap2AddressB        BEHAVIOUR
          DEFINED AS      !The set of addresses associated with an (N) SAP!
        ;
    ;

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) sap2Address(9)} ;
```

## 9.16 SapId

The sapId attribute type is used in naming instances of the sap1 and sap2 managed object classes.



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
sapId ATTRIBUTE

    WITH ATTRIBUTE SYNTAX     GMI-AttributeModule.SapId ;
    MATCHES FOR    EQUALITY ;

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) sapId(10)} ;
```

## 9.17 SubsystemId

The subsystemId attribute type is used in naming instances of the subsystem managed object class.

```
subsystemId ATTRIBUTE

    WITH ATTRIBUTE SYNTAX     GMI-AttributeModule.SubsystemId ;
    MATCHES FOR    EQUALITY ;

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) subsystemId(11)} ;
```

## 9.18 SupportedConnectionNames

```
supportedConnectionNames ATTRIBUTE

    WITH ATTRIBUTE SYNTAX     GMI-AttributeModule.GroupObjects ;
    MATCHES FOR    EQUALITY, SET-COMPARISON, SET-INTERSECTION ;
    BEHAVIOUR
        supportedConnectionNamesB BEHAVIOUR
            DEFINED AS
                !This attribute contains the distinguished names of managed objects that represent connections that are
                supported by the connection that has this attribute.!
        ;
    ;
REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) supportedConnectionNames(12)} ;
```

## 9.19 SupportEntityNames

The semantics of the supportEntityNames attribute type are defined in .

```
supportEntityNames ATTRIBUTE

    WITH ATTRIBUTE SYNTAX     GMI-AttributeModule.GroupObjects ;
     MATCHES FOR     EQUALITY, SET-COMPARISON, SET-INTERSECTION ;

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) supportEntityNames(18)} ;
```

## 9.20 Timer

The timer is a generic definition of an attribute designed to hold an interval timer value.

```
timer ATTRIBUTE

    WITH ATTRIBUTE SYNTAX GMI-AttributeModule.Timer;
    MATCHES FOR EQUALITY, ORDERING;
    BEHAVIOUR
        timerB BEHAVIOUR
            DEFINED AS
                !A timer whose value may be set and read to the precision implied by the syntax definition, but whose effect
                on the precision with which the protocol events controlled by this timer are generated is determined by the
                implementation. The details of this precision shall be stated in the MOCS. The value of the timer consists of
                two integer values, exponent and mantissa, and shall be interpreted as representing the value
                mantissa*10^exponent.!
        ;
    ;
;   -- Since this attribute is never instantiated, there is no REGISTERED AS construct. Timers derived from this definition
    -- shall specify the units of time that the timer value represents.
```



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

### 9.21 TotalRemoteSAPs

This attribute provides a count of the number of remote SAPs that a clProtocolMachine has communicated with during its lifetime.

```
totalRemoteSAPs  ATTRIBUTE
    DERIVED FROM wrapping64BitCounter ;
    BEHAVIOUR
        totalRemoteSAPsB BEHAVIOUR
            DEFINED AS
                !Counts the number of remote (N) SAPs that the containing clProtocolMachine has communicated with.
                Incremented by 1 every time communication with a remote (N) SAP is achieved.!
        ;
    ;
REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) totalRemoteSAPs(13)} ;
```

### 9.22 UnderlyingConnectionNames

The semantics of the underlyingConnectionNames attribute type are defined in 7.8.

```
underlyingConnectionNames ATTRIBUTE

    WITH ATTRIBUTE SYNTAX     GMI-AttributeModule.GroupObjects ;
     MATCHES FOR      EQUALITY, SET-COMPARISON, SET-INTERSECTION ;

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) underlyingConnectionNames(14)} ;
```

### 9.23 UserEntityNames

The semantics of the userEntityNames attribute type are defined in 7.6 and 7.7.

```
userEntityNames ATTRIBUTE

    WITH ATTRIBUTE SYNTAX     GMI-AttributeModule.GroupObjects ;
     MATCHES FOR      EQUALITY, SET-COMPARISON, SET-INTERSECTION ;

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attribute(7) userEntityNames(15)} ;
```

### 9.24 Wrapping64BitCounter

This is a wrapping counter which has an upper bound of 2^64-1.

```
wrapping64BitCounter ATTRIBUTE

    WITH ATTRIBUTE SYNTAX GMI-AttributeModule.Generic64BitCounter ;
     MATCHES FOR EQUALITY ;
     BEHAVIOUR genericWrappingCounterB ;
;    -- As this attribute is never instantiated, there is no REGISTERED AS construct. Instantiable attribute definitions
     -- derived from this definition shall specify the circumstances under which the attribute value is incremented.
```

## 10 Attribute Groups

This clause provides definitions of attribute groups.

### 10.1 Counters

This is an empty, extensible attribute group consisting of all counters that are part of a managed object class definition. Attributes are added to the group in the package definition(s) for the managed object class.

```
counters ATTRIBUTE GROUP
    DESCRIPTION
    !The group of all counter attributes.!
    ;
REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) attributeGroup(8) counters(0)};
```



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

# 11 Actions

## 11.1 Activate

The activate action provides a means of initializing a managed object.

```
activate ACTION
    BEHAVIOUR
        activateB BEHAVIOUR
            DEFINED AS
                !The activate action initializes the resource represented by the managed object so that it can perform its
                normal functions. Managed objects that support this action cannot always be created in the enabled state.

                Although the generic behaviour of the activate action is described with the CCITT Rec. X.721 (1992) |
                ISO/IEC 10164-2:1992 (State management function) attributes Operational state and Procedural status, this
                does not imply that either attribute need be made visible to management.

                This initialization procedure is needed to enable the managed object if the Procedural status attribute
                contains the value Initialization Required and the Operational state is Disabled.

                The activate action initiates a procedure that causes the resource to enter its normal functioning mode.

                If the resource is or can be enabled, the activate action completes successfully; if the resource cannot be
                enabled, the activate action returns a processingFailure error.

                While the initialization procedure is in progress, the Procedural status attribute contains the value Initializing.
                The Initialization Required condition is absent.

                If the initialization procedure completes successfully and the resource is operable and available for use, the
                Initializing condition is removed from the Procedural status attribute and the Operational state is Enabled. If
                the initialization procedure does not complete successfully, the Initializing condition is removed from the
                Procedural status attribute and the Initialization Required condition added. The Operational state is
                Disabled.!
        ;
    ;
    MODE CONFIRMED;
    WITH INFORMATION SYNTAX     GMI-AttributeModule.ActionInfo ;
    WITH REPLY SYNTAX           GMI-AttributeModule.ActionReply;
REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) action(9) activate(0)};
```

## 11.2 Deactivate

The deactivate action provides a means of abruptly terminating the operation of a managed object.

```
deactivate ACTION
    BEHAVIOUR
        deactivateB BEHAVIOUR
            DEFINED AS
                !The deactivate action permits the normal operation of the resource to be terminated by the manager.

                Although the generic behaviour of the deactivate action is described with the CCITT Rec. X.721
                (1992) | ISO/IEC 10164-2:1992 (State management function) attributes Operational state and Procedural
                status, this does not imply that either attribute be visible to management.

                The deactivate action initiates a procedure that causes the resource to cease its normal functioning mode.

                If the resource is or can be disabled, the deactivate action completes successfully; if the resource cannot be
                disabled, the deactivate action returns a processingFailure error.
```



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

While the termination procedure is in progress, the Procedural status attribute contains the value Terminating and the Operational state is Disabled. The Terminating condition is removed when the procedure completes.!

;

;

MODE CONFIRMED;

WITH INFORMATION SYNTAX GMI-AttributeModule.ActionInfo ;

WITH REPLY SYNTAX GMI-AttributeModule.ActionReply;

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) action(9) deactivate(1)};

### 11.3 DeactivateWhenNoUsers

The deactivateWhenNoUsers action provides a means of gracefully terminating the operation of a managed object.

deactivateWhenNoUsers ACTION

BEHAVIOUR

deactivateWhenNoUsersB BEHAVIOUR

DEFINED AS

!The deactivateWhenNoUsers action permits the normal operation of the resource represented by the managed object to be terminated by the manager when the number of instances of use of the resource is zero.

Although the generic behaviour of the deactivate action is described with the CCITT Rec. X.721 (1992) | ISO/IEC 10164-2:1992 (State management function) attributes Operational state and Procedural status, this does not imply that either attribute be visible to management.

The deactivateWhenNoUsers action initiates a procedure that causes the resource to cease its normal functioning mode when the number of instances of use is zero.

If at the time the resource has no existing users, or when, subsequently, the number of users drops to zero, the termination procedure is initiated and the Procedural status attribute is set to Terminating. If the resource is or can be disabled, the deactivateWhenNoUsers action completes successfully; if the resource cannot be disabled, the deactivateWhenNoUsers action returns a processingFailure error.

While the termination procedure is in progress, the Procedural status attribute contains the value Terminating. When the number of users drops to zero, the Operational state is Disabled. The Terminating condition is removed when the procedure completes.!

;

;

MODE CONFIRMED;

WITH INFORMATION SYNTAX GMI-AttributeModule.ActionInfo ;

WITH REPLY SYNTAX GMI-AttributeModule.ActionReply;

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) action(9) deactivateWhenNoUsers(2)};

## 12 Notifications

### 12.1 CommunicationsInformation

communicationsInformation NOTIFICATION

BEHAVIOUR

communicationsInformationB BEHAVIOUR

DEFINED AS

!This notification may be used to report the occurrence of events pertaining to the normal operation of a managed object. These are informational events; important enough to report, but not requiring any further action by a manager. Faults and abnormal conditions (which may require manager action) shall be reported using the event types defined in CCITT Rec. X.733 (1992) | ISO/IEC 10164-4:1992.!

;

;

WITH INFORMATION SYNTAX GMI-AttributeModule.CommunicationsInformation

AND ATTRIBUTE IDS

informationType informationType,

informationData informationData

;

REGISTERED AS {joint-iso-ccitt ms(9) smi(3) part5(5) notification(10) comsinfo(0)};



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

The following object identifier

{joint-iso-ccitt ms(9) smi(3) part5(5) functionalUnitPackage(1) informationEventReports(0)}

is assigned as a value of the ASN.1 type FunctionalUnitPackageId, defined in CCITT Rec. X.701 (1992) | ISO/IEC 10040:1992 to use for negotiating the following functional unit

0 communication information functional unit

where the number identifies the bit position assigned to the functional unit.

## 13 ASN.1 definitions

This clause defines the ASN.1 data types required by the attribute definitions in clause 9.

```
GMI-AttributeModule {joint-iso-ccitt ms(9) smi(3) part5(5) asn1Module(2) gmiAttributeModule(0)}
DEFINITIONS IMPLICIT TAGS ::= BEGIN

IMPORTS

    GroupObjects, ManagementExtension
        FROM Attribute-ASN1Module {joint-iso-ccitt ms(9) smi(3) part2(2) asn1Module(2) 1}

    RelativeDistinguishedName
        FROM InformationFramework {joint-iso-ccitt ds(5) modules(1) informationFramework(1)}

;-- End of IMPORTS

ActionInfo ::= SET OF ManagementExtension
ActionReply ::= SET OF ManagementExtension
ApplicationProcessId ::= GraphicString
ApplicationProcessTitle ::= CHOICE {
                                directory       [0] SEQUENCE OF RelativeDistinguishedName,
                                oid             [1] OBJECT IDENTIFIER,
                                notKnown            NULL }
CommunicationsEntityId ::= GraphicString
CommunicationsInformation ::= SEQUENCE {
    informationType InformationType,
    informationData InformationData OPTIONAL }
ConnectionId ::= GraphicString
GenericCounter ::= INTEGER
Generic64BitCounter ::= INTEGER (0..18446744073709551615)
InformationType ::= OBJECT IDENTIFIER
InformationData ::= SET OF ManagementExtension
ProtocolMachineId ::= GraphicString
Sap1Address ::= INTEGER
Sap2Address ::= SET OF OCTET STRING
SapId ::= GraphicString
SubsystemId ::= GraphicString
Timer ::= SEQUENCE {
        exponent [1] INTEGER (-62..63),
        mantissa [2] INTEGER (0..65535) }

END
```



Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

© ISO/IEC

**ICS 35.100.70**

**Descriptors:** data processing, information interchange, network interconnection, open systems interconnection, management, information.

Price based on 18 pages

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale