INTERNATIONAL STANDARD

ISO/IEC 14496-4

Second edition
2004-12-15

AMENDMENT 6
2005-09-01

Information technology — Coding of audio-visual objects —

Part 4: Conformance testing

AMENDMENT 6: Advanced Video Coding conformance

Technologies de l'information — Codage des objets audiovisuels —

Partie 4: Essai de conformité

AMENDEMENT 6: Conformité de codage vidéo avancé

Reference number
ISO/IEC 14496-4:2004/Amd.6:2005(E)

© ISO/IEC 2005

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO/IEC 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

© ISO/IEC 2005 – All rights reserved

Not for Resale

Contents

Page

Foreword iv

Introduction v

10 Advanced Video Coding 1
10.1 Scope 1
10.2 Normative references 1
10.3 Definitions 2
10.4 Abbreviations 2
10.5 Conventions 2
10.6 Conformance for ITU-T Rec. H.264 | ISO/IEC 14496-10 2

© ISO/IEC 2005 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 6 to ISO/IEC 14496-4:2004 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Introduction

This Recommendation | International Standard establishes conformance test requirements for conformance to ITU-T Rec. H.264 | ISO/IEC 14496-10 Advanced Video Coding.

This specification has been jointly developed by ITU-T Video Coding Experts Group (VCEG) and the ISO/IEC Moving Picture Experts Group. It is published as technically-aligned twin text in both organizations ITU-T and ISO/IEC.

This document is the text of the ITU-T Rec. H.264.1 | ISO/IEC 14496-4 conformance test of ITU-T Rec. H.264 | ISO/IEC 14496-10 video bitstreams and decoders. This specification is specifically applied to ITU-T Rec. H.264 | ISO/IEC 14496-10, Advanced Video Coding.

The following subclauses specify the normative tests for verifying conformance of ITU-T Rec. H.264 | 14496-10 video bitstreams and video decoders. These normative tests make use of test data (bitstream test suites) provided as an electronic annex to this document, and the reference software decoder specified in ITU-T Rec. H.264.2 | ISO/IEC 14496-5:2001/Amd.6 with source code available in electronic format.

--`,,```,,,,````-`-`,,`,,`,`,,`---
© ISO/IEC 2005 All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

Information technology — Coding of audio-visual objects —

Part 4: Conformance testing

Amendment 6: Advanced Video Coding conformance

Add the following after clause 9:

10 Advanced Video Coding

10.1 Scope

This clause specifies tests designed to verify whether bitstreams and decoders meet normative requirements specified in ITU-T Rec. H.264 | ISO/IEC 14496-10. An encoder can claim conformance to ITU-T Rec. H.264 | ISO/IEC 14496-10 if the bitstreams that it generates are conforming bitstreams.

Characteristics of coded bitstreams and decoders are defined for ITU-T Rec. H.264 | ISO/IEC 14496-10. The characteristics of a bitstream define the subset of the standard that is exploited in the bitstream. Examples are the applied values or range of the picture size and bit rate parameters. Decoder characteristics define the properties and capabilities of the applied decoding process. The capabilities of a decoder specify which bitstreams the decoder can decode and reconstruct, by defining the subset of the ITU-T Rec. H.264 | ISO/IEC 14496-10 standard that may be exploited in the bitstreams that it will decode. A bitstream can be decoded by a decoder if the characteristics of the bitstream are within the subset of the standard specified by the decoder capabilities.

Procedures are described for testing conformance of bitstreams and decoders to the requirements defined in ITU-T Rec. H.264 | ISO/IEC 14496-10. Given the set of characteristics claimed, the requirements that shall be met are fully determined by ITU-T Rec. H.264 | ISO/IEC 14496-10. This clause summarizes the requirements, cross references them to characteristics, and defines how conformance with them can be tested. Guidelines are given on constructing tests to verify bitstream and decoder conformance. This clause gives guidelines on how to construct bitstream test suites to check or verify decoder conformance. In addition, the test bitstreams implemented according to those guidelines are provided as an electronic annex to this document.

10.2 Normative references

10.2.1 General

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

© ISO/IEC 2005 All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.2.2 Identical Recommendations | International Standards

– None.

10.2.3 Paired Recommendations | International Standards equivalent in technical content

– ITU-T Recommendation H.264 (2004), *Advanced video coding for generic audiovisual services.*
ISO/IEC 14496-10, *Information technology – Coding of audiovisual objects – Part 10: Advanced video coding.*

– ITU-T Recommendation H.264.2 (2004), *Advanced video coding reference software.*
ISO/IEC 14496-5, *Information technology – Coding of audiovisual objects – Part 5: Reference software.*

10.2.4 Additional references

– None.

10.3 Definitions

10.3.1 For the purposes of this document, the terms, definitions, abbreviations and symbols specified in bitstream: An ITU-T Rec. H.264 | ISO/IEC 14496-10 video bitstream. A bitstream may contain IDR, I, P, B, SI, and SP slices.

10.3.2 decoder: An ITU-T Rec. H.264 | ISO/IEC 14496-10 video decoder, i.e., an embodiment of the decoding process specified by ITU-T Rec. H.264 | ISO/IEC 14496-10. The decoder does not include the display process, which is outside the scope of this standard.

10.3.3 reference software decoder: The software decoders contained in ITU-T Rec. H.264.2 | ISO/IEC 14496-5.

10.4 Abbreviations

For the purposes of this Recommendation | International Standard, relevant abbreviations are specified in clause 4 of ITU-T Rec. H.264 | ISO/IEC 14496-10.

10.5 Conventions

For the purposes of this Recommendation | International Standard, relevant conventions are specified in clause 5 in ITU-T Rec.264 | ISO/IEC 14496-10.

10.6 Conformance for ITU-T Rec. H.264 | ISO/IEC 14496-10

10.6.1 Introduction

The following subclauses specify the normative tests for verifying conformance of video bitstreams as well as decoders. Those normative tests make use of test data (bitstream test suites) provided as an electronic annex to this document, and the reference software decoder specified in ITU-T Rec. H.264.2 | ISO/IEC 14496-5 with source code included in electronic format.

10.6.2 Bitstream conformance

The bitstream conformance of ITU-T Rec. H.264 | ISO/IEC 14496-10 is specified by subclause C.3 in Annex C of ITU-T Rec. H.264 | ISO/IEC 14496-10.

© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.3 Decoder conformance

The decoder conformance of ITU-T Rec. H.264 | ISO/IEC 14496-10 is specified by subclause C.4 in Annex C of ITU-T Rec. H.264 | ISO/IEC 14496-10.

10.6.4 Procedure to test bitstreams

A bitstream that claims conformance with this standard shall pass the following normative test:

The bitstream shall be decoded by processing it with the reference software decoder specified in ITU-T Rec. H.264.2 | ISO/IEC 14496-5. When processed by the reference software decoder, the bitstream shall not cause any error or non-conformance messages to be reported by the reference software decoder. This test should not be applied to bitstreams that are known to contain errors introduced by transmission, as such errors are highly likely to result in bitstreams that lack conformance to ITU-T Rec. H.264 | ISO/IEC 14496-10.

Successfully passing the reference software decoder test provides only a strong presumption that the bitstream under test is conforming to the video layer, i.e. that it does indeed meet all the requirements for the video layer (except Annexes C, D and E) specified in ITU-T Rec. H.264 | ISO/IEC 14496-10 that are tested by the reference software decoder.

Additional tests may be necessary to more thoroughly check that the bitstream properly meets all the requirements specified in ITU-T Rec. H.264 | ISO/IEC 14496-10 including the HRD conformance (based on Annexes C, D and E). These complementary tests may be performed using other video bitstream verifiers that perform more complete tests than those implemented by the reference software decoder.

ITU-T Rec. H.264 | ISO/IEC 14496-10 contains several informative recommendations that are not an integral part of that Recommendation | International Standard. When testing a bitstream for conformance, it may also be useful to test whether or not the bitstream follows those recommendations.

To check correctness of a bitstream, it is necessary to parse the entire bitstream and to extract all the syntactic elements and other values derived from those syntactic elements and used by the decoding process specified in ITU-T Rec. H.264 | ISO/IEC 14496-10.

A verifier may not necessarily perform all stages of the decoding process described in ITU-T Rec. H.264 | ISO/IEC 14496-10 in order to verify bitstream correctness. Many tests can be performed on syntax elements in a state prior to their use in some processing stages.

10.6.5 Procedure to test decoder conformance

10.6.5.1 Conformance bitstreams

In this subclause, except where stated otherwise, the term "bitstream" refers to a conforming ITU-T Rec. H.264 | ISO/IEC 14496-10 video bitstream (as defined in this document), that has values of profile_idc, level_idc, and constraint_setX_flag values (where X is a number in the range of 0 to 2, inclusive) corresponding to a set of specified constraints on a bitstream for which a decoder conforming to a specified profile and level is required in Annex A of ITU-T Rec. H.264 | ISO/IEC 14496-10 to properly perform the decoding process.

10.6.5.2 Contents of bitstream file

The conformance bitstreams are included in this specification as an electronic attachment. The following information is included in a single zipped file for each such bitstream.

- ITU-T Rec. H.264 | ISO/IEC 14496-10 video bitstream
- Reconstructed pictures or hashes of decoded pictures
- Short description of the bitstream
- Trace file (the bitstream in ASCII format)

© ISO/IEC 2005 All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.5.3 Requirements on output of the decoding process and timing

Two classes of decoder conformance are specified:

- Output order conformance, and
- Output timing conformance

The output of the decoding process is specified by clause 8 and Annex C of ITU-T Rec. H.264 | ISO/IEC 14496-10.

For output order conformance, it is a requirement that all of the decoded pictures specified for output in Annex C of ITU-T Rec. H.264 | ISO/IEC 14496-10 shall be output by a conforming decoder in the specified order and that the values of the decoded samples in all of the pictures that are output shall be (exactly equal to) the values specified in clause 8 of ITU-T Rec. H.264 | ISO/IEC 14496-10.

For output timing conformance, it is a requirement that a conforming decoder shall also output the reconstructed samples at the rates and times specified in Annex C of ITU-T Rec. H.264 | ISO/IEC 14496-10.

The display process, which ordinarily follows the output of the decoding process, is outside the scope of this Recommendation | International Standard.

10.6.5.4 Recommendations (informative)

In addition to the requirements, it is desirable that conforming decoders implement various informative recommendations defined in ITU-T Rec. H.264 | ISO/IEC 14496-10 that are not an integral part of that Recommendation | International Standard. This subclause lists some of these recommendations.

It is recommended that a conforming decoder be able to resume the decoding process as soon as possible after the loss or corruption of part of a bitstream. In most cases it is possible to resume decoding at the next start code or slice header. It is recommended that a conforming decoder be able to perform concealment for the macroblocks or video packets for which all the coded data has not been received.

10.6.5.5 Static tests for output order conformance

Static tests of a video decoder require testing of the reconstructed samples. This subclause will explain how this test can be accomplished when the reconstructed samples at the output of the decoding process are available. It may not be possible to perform this type of test with a production decoder (due to the lack of an appropriate accessible interface in the design at which to perform the test). In that case this test should be performed by the manufacturer during the design and development phase. Static tests are used for testing the decoding process. The test will check that the values of the samples reconstructed by the decoder under test shall be identical to the values of the reference samples attached to the bitstream file, or shall be identical to the values of the samples reconstructed by the reference decoder in cases where the values of the samples are not attached to the bitstream file. When a hash of the values of the samples of the decoded pictures is attached to the bitstream file, a corresponding hash operation performed on the values of the samples of the decoded pictures produced by the decoder under test shall produce the same results.

10.6.5.6 Dynamic tests for output timing conformance

Dynamic tests are applied to check that all the reconstructed samples are output and that the timing of the output of the decoder's reconstructed samples conforms to the specification of clause 8 and Annex C of ITU-T Rec. H.264 | ISO/IEC 14496-10, and to verify that the HRD models (as defined by the CPB and DPB specification in Annex C of ITU-T Rec. H.264 | ISO/IEC 14496-10) are not violated when the bits are delivered at the proper rate.

The dynamic test is often easier to perform on a complete decoder system, which may include a systems decoder, a video decoder and a display process. It may be possible to record the output of the display process and to check that display order and timing of fields or frames are correct at the output of the display process. However, since the display process is not within the normative scope of ITU-T Rec. H.264 | ISO/IEC 14496-10, there may be cases where the output of the display process differs in timing or value even though the video

--`,,```,,,,````-`-`,,`,,`,`,,`---

© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

decoder is conforming. In this case, the output of the video decoder itself (before the display process) would need to be captured in order to perform the dynamic tests on the video decoder. In particular the field or frame order and timing shall be correct.

If buffering period SEI and picture timing SEI are included in the test bitstream, HRD conformance shall be verified using the values of initial_cpb_removal_delay, initial_cpb_removal_delay_offset, cpb_removal_delay and dpb_removal_delay that are included in the bitstream.

If buffering period SEI and picture timing SEI are not included in the bitstream, the following inferences shall be made to generate the missing parameters:

- fixed_frame_rate_flag shall be inferred to be 1.
- low_delay_hrd_flag shall be inferred to be 0.
- cbr_flag shall be inferred to be 0.
- The frame rate of the stream shall be inferred to be the frame rate value specified in Table AMD9-1. If this is missing, then a frame rate of either 25 or 30000 ÷ 1001 can be inferred.
- time_scale shall be set to 90,000 and the value of num_units_in_tick shall be computed based on field rate (twice the frame rate).
- The bit rate of the bitstream shall be inferred to be the maximum value for the level defined in Table A-1 in ITU-T Rec. H.264 | ISO/IEC 14496-10.
- CPB and DPB sizes shall be inferred to be the maximum value for the level defined in Table A-1 in ITU-T Rec. H.264 | ISO/IEC 14496-10.

With the above inferences, the HRD shall be operated as follows.

- The CPB is filled starting at time t = 0, until it is full, before removal of the first access unit. This means that the initial_cpb_removal_delay shall be inferred to be equal to the total CPB buffer size divided by the bit rate divided by 90000 (rounded downwards) and initial_cpb_removal_delay_offset shall be inferred to be equal to zero.
- The first access unit is removed at time t = initial_cpb_removal_delay ÷ 90000 and subsequent access units are removed at intervals based on the frame distance, i.e. cpb_removal_delay = 2 * (90000 ÷ num_units_in_tick) or the field distance i.e. cpb_removal_delay = (90000 / num_units_in_tick), depending whether the access unit is coded as a frame picture or field picture.
- Using these inferences, the CPB will not overflow or underflow and the DPB will not overflow.

10.6.5.7 Decoder conformance test of a particular profile-and-level

In order for a decoder of a particular profile-and-level to claim output order conformance to the standard as described by this specification, the decoder shall successfully pass the static test defined in subclause 10.6.5.5 with all the bitstreams of the normative test suite specified for testing decoders of this particular profile-and-level.

In order for a decoder of a particular profile and level to claim output timing conformance to the standard as described by this specification, the decoder shall successfully pass both the static test defined in subclause 10.6.5.5 and the dynamic test defined in subclause 10.6.5.6 with all the bitstreams of the normative test suite specified for testing decoders of this particular profile-and-level. Table AMD9-1 define the normative test suites for each profile-and-level combination. The test suite for a particular profile-and-level combination is the list of bitstreams that are marked with an 'X' in the column corresponding to that profile-and-level combination.

'X' indicates that the bitstream is designed to test both the dynamic and static conformance of the decoder.

The bitstream specification indicates the test bitstream specification used for each bitstream.

--`,,```,,,,````-`-`,,`,,`,`,,`---
© ISO/IEC 2005 All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.6 Specification of the test bitstreams

Some characteristics of each bitstream listed in Table AMD9-1 are described in the subclauses of this subclause. In Table AMD9-1, the value "29.97" shall be interpreted as an approximation of an exact value of 30000 ÷ 1001.

10.6.6.1 Test Bitstreams – General

10.6.6.1.1 Test bitstream #AVCNL-1, #AVCNL-2

Specification: All slices are coded as I slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I slices.

Purpose: Check that the decoder can properly decode I slices.

10.6.6.1.2 Test bitstream #AVCNL-3, #AVCNL-4

Specification: All slices are coded as I or P slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of P slices.

Purpose: Check that the decoder can properly decode P slices.

10.6.6.1.3 Test bitstream #AVCBA-1

Specification: All slices are coded as I slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I slices with the deblocking filter process enabled.

Purpose: Check that the decoder can properly decode I slices with the deblocking filter process enabled.

10.6.6.1.4 Test bitstream #AVCBA-2

Specification: All slices are coded as I slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 2. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I slices with the deblocking filter process enabled.

Purpose: Check that the decoder can properly decode I slices with the deblocking filter process enabled.

10.6.6.1.5 Test bitstream #AVCBA-3

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Functional stage: Decoding of P slices with the deblocking filter process enabled.

Purpose: Check that the decoder can properly decode P slice with the deblocking filter process enabled.

10.6.6.1.6 Test bitstream #AVCBA-4

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 2. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of P slices with the deblocking filter process enabled.

Purpose: Check that the decoder can properly decode P slices with the deblocking filter process enabled.

10.6.6.1.7 Test bitstream #AVCBA-5, #AVCBA-6

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of P slices with the deblocking filter process enabled.

Purpose: Check that the decoder can properly decode P slices with the deblocking filter process enabled.

10.6.6.1.8 Test bitstream #AVCBA-7, #AVCBA-8

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 2. Macroblock/sub-macroblock partition size is limited to 8x8 and above. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of P slices with the deblocking filter process enabled.

Purpose: Check that the decoder can properly decode P slices with the deblocking filter process enabled.

10.6.6.1.9 Test bitstream #AVCMQ-1

Specification: All slices are coded as I slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 1. mb_qp_delta is equal to a non-zero value to change the quantizer scale at each MB. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I slices with mb_qp_delta not equal to 0.

Purpose: Check that the decoder can properly decode I slices with mb_qp_delta not equal to 0.

10.6.6.1.10 Test bitstream #AVCMQ-2

Specification: All slices are coded as I or P slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 1. mb_qp_delta is equal to a non-zero value to change the quantizer scale at each MB. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of P slices with mb_qp_delta not equal to 0.

Purpose: Check that the decoder can properly decode P slices with mb_qp_delta not equal to 0.

© ISO/IEC 2005 All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.6.1.11 Test bitstream #AVCMQ-3

Specification: All slices are coded as I slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 1. Spatial direct prediction is used for direct prediction. mb_qp_delta is equal to a non-zero value to change the quantizer scale at each MB. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I slices with mb_qp_delta not equal to 0.

Purpose: Check that the decoder can properly decode I slices with mb_qp_delta not equal to 0.

10.6.6.1.12 Test bitstream #AVCMQ-4

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 1. Spatial direct prediction is used for direct prediction. mb_qp_delta is equal to a non-zero value to change the quantizer scale at some MBs. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of P slices with mb_qp_delta not equal to 0.

Purpose: Check that the decoder can properly decode P slices with mb_qp_delta not equal to 0.

10.6.6.1.13 Test bitstream #AVCSL-1

Specification: All slices are coded as I or P slices. Each picture contains more than one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 2. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I and P slices.

Purpose: Check that the decoder can properly decode pictures with multiple slices.

10.6.6.1.14 Test bitstream #AVCSL-2

Specification: All slices are coded as I or P slices. Each picture contains more than one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I and P slices.

Purpose: Check that the decoder can properly decode pictures with multiple slices.

10.6.6.1.15 Test bitstream #AVCSQ-1

Specification: All slices are coded as I slices. Each picture contains 20 slices. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Spatial direct prediction is used for direct prediction. slice_qp_delta is equal to a non-zero value to change the quantizer scale at each slice. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I slices with non-zero values of slice_qp_delta.

Purpose: Check that the decoder can properly decode I slices with non-zero values of slice_qp_delta.

© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.6.1.16 Test bitstream #AVCFM-1

Specification: All slices are coded as I or P slices. The number of slices and slice groups is greater than 1 in each picture. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10. Multiple parameter sets are included in the bitstream.

Functional stage: Slice groups.

Purpose: Check that the decoder handles multiple slice groups and parameter sets.

10.6.6.1.17 Test bitstream #AVCFM-2

Specification: All slices are coded as I or P slices. The number of slices and slice groups is greater than 1 in each picture. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Slice groups.

Purpose: Check that the decoder handles multiple slice groups and parameter sets.

10.6.6.1.18 Test bitstream #AVCFM-3

Specification: All slices are coded as I or P slices. The number of slices and slice groups is greater than 1 in each picture. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 2. Recovery point SEI is included in this bitstream. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Slice groups.

Purpose: Check that the decoder handles multiple slice groups and parameter sets.

10.6.6.1.19 Test bitstream #AVCCI-1

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. constrained_intra_pred_flag is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Constrained intra prediction.

Purpose: Check that the decoder handles constrained intra prediction.

10.6.6.1.20 Test bitstream #AVCCI-2

Specification: All slices are coded as I or P slices. Each picture contains more than one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. constrained_intra_pred_flag is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Constrained intra prediction

Purpose: Check that the decoder handles constrained intra prediction.

© ISO/IEC 2005 All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.6.1.21 Test bitstream #AVCCI-3

Specification: All slices are coded as I or P slices. Each picture contains more than one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 2. constrained_intra_pred_flag is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Constrained intra prediction

Purpose: Check that the decoder handles constrained intra prediction.

10.6.6.1.22 Test bitstream #AVCFC-1

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Decoded pictures are cropped with frame_croping_flag equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I and P slices with frame cropping.

Purpose: Check that the decoder can properly decode I and P slices with frame cropping.

10.6.6.1.23 Test bitstream #AVCAUD-1

Specification: All slices are coded as I slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Access unit delimiter NAL units are included in the bitstream. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I slices with Access unit delimiter NAL units.

Purpose: Check that the decoder can properly decode I slices with Access unit delimiter NAL units.

10.6.6.1.24 Test bitstream #AVCMIDR-1

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. IDR is inserted in every two frame. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I slices and more than one IDR.

Purpose: Check that the decoder can properly decode I slices with more than IDR in bitstream.

10.6.6.1.25 Test bitstream #AVCNRF-1

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Two non-reference pictures are present. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I and P slices with non-reference pictures.

Purpose: Check that the decoder can properly decode I and P slices with non-reference pictures.

© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.6.1.26 Test bitstream #AVCMPS-1

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Multiple parameter sets are included in this bitstream. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I and P slices with multiple parameter set.

Purpose: Check that the decoder can properly decode I and P slices with multiple parameter set.

10.6.6.1.27 Test bitstream #AVCBS-1

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of B slices with temporal direct prediction.

Purpose: Check that the decoder can properly decode B slices with temporal direct prediction.

10.6.6.1.28 Test bitstream #AVCBS-2

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Spatial direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of B slices with spatial direct prediction.

Purpose: Check that the decoder can properly decode B slices with spatial direct prediction.

10.6.6.1.29 Test bitstream #AVCBS-3

Specification: All slices are coded as I, P or B slices. Each picture contains more than one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of B slices with temporal direct prediction.

Purpose: Check that the decoder can properly decode B slices with temporal direct prediction.

10.6.6.1.30 Test bitstream #AVCBS-4

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Spatial direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of B slices with spatial direct prediction.

Purpose: Check that the decoder can properly decode B slices with spatial direct prediction.

--`,,```,,,,````-`-,,`,,`,`,,`---

© ISO/IEC 2005 All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.6.1.31 Test bitstream #AVCBS-5

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Spatial direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of B slices with spatial direct prediction.

Purpose: Check that the decoder can properly decode B slices with spatial direct prediction.

10.6.6.2 Test Bitstreams – I_PCM

10.6.6.2.1 Test bitstream #AVCPCM-1, AVCPCM-2

Specification: All slices are coded as I slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. mb_type is equal to I_PCM for some macroblocks. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of macroblocks with mb_type equal to I_PCM

Purpose: Check that the decoder can properly decode macroblocks with mb_type equal to I_PCM.

10.6.6.3 Test Bitstreams – Memory management control operation

10.6.6.3.1 Test bitstream #AVCMR-1

Specification: All slices are coded as I or P slices. Each picture contains more than one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 1. Reference picture list reordering and memory management control operations are used. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Reference picture list reordering and memory management control operations.

Purpose: Check that the decoder handles reference picture list reordering and memory management control operations.

10.6.6.3.2 Test bitstream #AVCMR-2

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 2. Reference picture list reordering and memory management control operations are used. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Reference picture list reordering and memory management control operations.

Purpose: Check that the decoder handles reference picture list reordering and memory management control operations.

10.6.6.3.3 Test bitstream #AVCMR-3

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 2. gaps_in_frame_num_value_allowed_flag is equal to 1. Reference picture list reordering and various

© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

memory management control operation is used. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Reference picture list reordering and memory management control operations.

Purpose: Check that the decoder handles gaps in frame_num, reference picture list reordering and memory management control operations.

10.6.6.3.4 Test bitstream #AVCMR-4

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. gaps_in_frame_num_value_allowed_flag is equal to 1. Reference picture list reordering and various memory management control operations are used. The decoding order is different from the output order. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Reference picture list reordering, memory management control operations and non-increasing PicOrderCnt values.

Purpose: Check that the decoder handles reference picture list reordering and memory management control operations. Test output order conformance for non-increasing PicOrderCnt values.

10.6.6.3.5 Test bitstream #AVCMR-5

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 1. gaps_in_frame_num_value_allowed_flag is equal to 1. Reference picture list reordering and various memory management control operation is used. The decoding order is different from the output order. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Reference picture list reordering, memory management control operation and non-increasing PicOrderCnt values.

Purpose: Check that the decoder handles gaps_in_frame_num_value_allowed_flag equal to 1, reference picture list reordering and memory management control operation. Test output order conformance for non-increasing PicOrderCnt values.

10.6.6.3.6 Test bitstream #AVCMR-6

Specification: All slices are coded as I or P slices. Each picture contains more than one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Reference picture list reordering is used. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Reference picture list reordering.

Purpose: Check that the decoder handles reference picture list reordering.

10.6.6.3.7 Test bitstream #AVCMR-7

Specification: All slices are coded as I or P slices. Each picture contains more than one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Memory management control operations are used. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Memory management control operations.

Purpose: Check that the decoder handles memory management control operations.

© ISO/IEC 2005 All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.6.4 Test Bitstreams – Weighted sample prediction process

10.6.6.4.1 Test bitstream #AVCWP-1

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 2. weighted_pred_flag is equal to 1. Plural reference indices are assigned to each reference picture. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Weighted sample prediction process for P slices with plural reference indices.

Purpose: Check that the decoder handles weighted sample prediction for P slices with plural reference indexes.

10.6.6.4.2 Test bitstream #AVCWP-2

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 2. weighted_pred_flag is equal to 1. All NAL units are encapsulated into the byte stream

Functional stage: Weighted sample prediction process for P slices.

Purpose: Check that the decoder handles weighted sample prediction for P slices.

10.6.6.4.3 Test bitstream #AVCWP-3

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Spatial direct prediction is used for direct prediction. weighted_bipred_idc is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Weighted sample prediction process for B slices with temporal direct prediction.

Purpose: Check that the decoder handles weighted sample prediction for B slices with temporal direct prediction.

10.6.6.4.4 Test bitstream #AVCWP-4

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Spatial direct prediction is used for direct prediction. weighted_bipred_idc is equal to 2. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Weighted sample prediction process for B slices with temporal direct prediction.

Purpose: Check that the decoder handles weighted sample prediction for B slices with temporal direct prediction.

10.6.6.5 Test Bitstreams – Slice of coded field

10.6.6.5.1 Test bitstream #AVCFI-1

Specification: All slices are coded as I or P slices. Each picture contains only one slice. Each slice is a coded field. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Functional stage: Slices of coded fields.

Purpose: Check that the decoder handles I and P slices of coded fields.

10.6.6.5.2 Test bitstream #AVCFI-2

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. Each slice is a coded field. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Spatial direct prediction is used for direct prediction. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Slices of coded fields with spatial direct prediction.

Purpose: Check that the decoder handles B slices of coded fields with spatial direct prediction.

10.6.6.5.3 Test bitstream #AVCFI-3

Specification: All slices are coded as I or P slices. Each picture contains only one slice. Each slice is a coded field. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Slices of coded fields

Purpose: Check that the decoder handles I and P slices of coded fields.

10.6.6.5.4 Test bitstream #AVCFI-4

Specification: All slices are coded as I or P slices. Each picture contains only one slice. Each slice is a coded field. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Slices of coded fields.

Purpose: Check that the decoder handles I and P slices of coded fields.

10.6.6.5.5 Test bitstream #AVCFI-5

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. Each slice is a coded field. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 1. Spatial direct prediction is used for direct prediction. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Slices of coded fields.

Purpose: Check that the decoder handles B slices of coded fields.

10.6.6.5.6 Test bitstream #AVCFI-6

Specification: All slices are coded as I or P slices. Each picture contains more than one slice. Each slice is a coded field. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

© ISO/IEC 2005 All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Functional stage: Slices of coded fields.

Purpose: Check that the decoder handles I and P slices of coded fields.

10.6.6.5.7 Test bitstream #AVCFI-7

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. Each slice is a coded field. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Slices of coded fields with temporal direct prediction.

Purpose: Check that the decoder handles B slices of coded fields with temporal direct prediction.

10.6.6.5.8 Test bitstream #AVCFI-8

Specification: All slices are coded as I slices. Only one slices is contained in each picture. Each slice is a coded field. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Slices of coded fields.

Purpose: Check that the decoder handles I slices of coded fields.

10.6.6.5.9 Test bitstream #AVCFI-9

Specification: All slices are coded as I or P slices. Each picture contains only one slice. Each slice is a coded field. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Slices of coded fields.

Purpose: Check that the decoder handles I and P slices of coded fields.

10.6.6.5.10 Test bitstream #AVCFI-10

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. Each slice is a coded field. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Slices of coded fields with temporal direct prediction.

Purpose: Check that the decoder handles B slices of coded fields with temporal direct prediction.

10.6.6.5.11 Test bitstream #AVCFI-11

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. Each slice is a coded field. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Spatial direct prediction is used for direct prediction. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Slices of coded fields with spatial direct prediction.

Purpose: Check that the decoder handles B slices of coded fields with spatial direct prediction.

--`,,```,,,,````-`-`,,`,,`,`,,`---
© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.6.5.12 Test bitstream #AVCFI-12

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. The number of motion vectors per tow consecutive MBs is equal to the maximum value specified in Annex A.3.1.m in ITU-T Rec. H.264 | ISO/IEC 14496-10. No intra, skip and direct MBs are included in P and B slices. Each slice is a coded field. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Slices of coded fields.

Purpose: Check that the decoder can properly decode slices of coded fields with maximum number of motion vectors per consecutive MBs.

10.6.6.6 Test Bitstreams – Frame/field coding

10.6.6.6.1 Test bitstream #AVCPA-1

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 1. Spatial direct prediction is used for direct prediction. Each slice is either a coded frame or a coded field. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Slices of coded frames/fields.

Purpose: Check that the decoder can properly decode slices of coded frames and fields.

10.6.6.6.2 Test bitstream #AVCPA-2

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. Each slice is either a coded frame or a coded field. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Slices of coded frames/fields.

Purpose: Check that the decoder can properly decode slices of coded frames and fields.

10.6.6.6.3 Test bitstream #AVCPA-3

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Spatial direct prediction is used for direct prediction. Each slice is either a coded frame or a coded field. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Slices of coded frames/fields.

Purpose: Check that the decoder can properly decode slices of coded frames and fields.

© ISO/IEC 2005 All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.6.7 Test bitstreams - Macroblock adaptive frame/field coding

10.6.6.7.1 Test bitstream #AVCMA-1

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Spatial direct prediction is used for direct prediction. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1.

10.6.6.7.2 Test bitstream #AVCMA-2

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1.

10.6.6.7.3 Test bitstream #AVCMA-3

Specification: All slices are coded as I slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1.

10.6.6.7.4 Test bitstream #AVCMA-4

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Spatial direct prediction is used for direct prediction. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1.

10.6.6.7.5 Test bitstream #AVCMA-5

Specification: All slices are coded as I, or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. mb_adaptive_frame_field_coding is equal to 1. mb_qp_delta is equal to a non-zero value to change the quantizer scale at some MBs. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1.

10.6.6.7.6 Test bitstream #AVCMA-6

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. mb_adaptive_frame_field_coding is equal to 1. mb_qp_delta is equal to a non-zero value to change the quantizer scale at some MBs. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1.

10.6.6.7.7 Test bitstream #AVCMA-7

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. Some slices are coded as a coded field. mb_adaptive_frame_field_coding equal to 1 in the rest of the frames. mb_qp_delta is equal to a non-zero value to change the quantizer scale at some MBs. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding and slices of a coded field.

Purpose: Check that the decoder can properly decode both slices of a coded frame with mb_adaptive_frame_field_flag=1 and slices of a coded field.

10.6.6.7.8 Test bitstream #AVCMA-8

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Spatial direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1.

10.6.6.7.9 Test bitstream #AVCMA-9

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. The number of motion vectors per tow consecutive MBs is equal to the maximum value specified in Annex A.3.1.m in ITU-T Rec. H.264 | ISO/IEC 14496-10. No intra, skip and direct MBs are included in P and B slices. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1 and with maximum number of motion vectors per consecutive MBs.

© ISO/IEC 2005 All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.6.8 Test Bitstreams – S picture

10.6.6.8.1 Test bitstream #AVCSP-1

Specification: All slices are coded as I, P and SP slice. Each picture contains more than one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 1. memory_management_operation is set to 5 on SP slice. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of SP slice.

Purpose: Check that the decoder can properly decode SP slice.

10.6.6.8.2 Test bitstream #AVCSP-2

Specification: All slices are coded as I, P and SP slice. Each picture contains more than one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 1. memory_management_operation is set to 5 on SP slice. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of SP slice.

Purpose: Check that the decoder can properly decode SP slice with deblocking filter.

10.6.6.9 Test Bitstreams – Long sequence

10.6.6.9.1 Test bitstream #AVCLS-1

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of picture order count for long sequence.

Purpose: Check that the decoder can properly decode picture order count for long sequence.

10.6.6.10 Test Bitstreams – SEI/VUI

10.6.6.10.1 Test bitstream #AVCSE-1

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. SEI (Buffering period SEI and Picture timing SEI with pic_struct) and VUI are included in the bitstream. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of SEI/VUI.

Purpose: Check that the decoder can properly decode SEI/VUI.

10.6.6.10.2 Test bitstream #AVCSE-2

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. SEI

© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

(Buffering period SEI and Picture timing SEI with pic_struct) and VUI are included in the bitstream. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of SEI/VUI.

Purpose: Check that the decoder can properly decode SEI/VUI.

10.6.6.10.3 Test bitstream #AVCSE-3

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. SEI (Buffering period SEI and Picture timing SEI with pic_struct) and VUI are included in the bitstream. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of SEI/VUI.

Purpose: Check that the decoder can properly decode SEI/VUI.

10.6.6.11 Test Bitstreams – CABAC: Basic features

10.6.6.11.1 Test bitstream #AVCCANL-1

Specification: All slices are coded as I slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 2. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I slice with CABAC parsing.

Purpose: Check that the decoder can properly decode I slices with CABAC parsing.

10.6.6.11.2 Test bitstream #AVCCANL-2

Specification: All slices are coded as I slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I slice with CABAC parsing.

Purpose: Check that the decoder can properly decode I slices with CABAC parsing.

10.6.6.11.3 Test bitstream #AVCCANL-3

Specification: All slices are coded as I or P slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of P slices with CABAC parsing.

Purpose: Check that the decoder can properly decode P slices with CABAC parsing.

© ISO/IEC 2005 All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.6.11.4 Test bitstream #AVCCANL-4

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Spatial direct prediction is used for direct prediction. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of B slices with CABAC parsing.

Purpose: Check that the decoder can properly decode B slices with CABAC parsing.

10.6.6.11.5 Test bitstream #AVCCANL-5

Specification: All slices are coded as I slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 2. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I slice with CABAC parsing.

Purpose: Check that the decoder can properly decode I slices with CABAC parsing.

10.6.6.11.6 Test bitstream #AVCCANL-6

Specification: All slices are coded as I slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I slice with CABAC parsing.

Purpose: Check that the decoder can properly decode I slices with CABAC parsing.

10.6.6.11.7 Test bitstream #AVCCANL-7

Specification: All slices are coded as I or P slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of P slices with CABAC parsing.

Purpose: Check that the decoder can properly decode P slices with CABAC parsing.

© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.6.11.8 Test bitstream #AVCCANL-8

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Spatial direct prediction is used for direct prediction. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of B slices with CABAC parsing.

Purpose: Check that the decoder can properly decode B slices with CABAC parsing.

10.6.6.11.9 Test bitstream #AVCCABA-1

Specification: All slices are coded as I slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I slice with the deblocking filter process enabled and CABAC.

Purpose: Check that the decoder can properly decode I slices with CABAC parsing.

10.6.6.11.10 Test bitstream #AVCCABA-2

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of P slices with CABAC parsing.

Purpose: Check that the decoder can properly decode P slices with CABAC parsing.

10.6.6.11.11 Test bitstream #AVCCABA-3

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of B slices with CABAC parsing.

Purpose: Check that the decoder can properly decode B slices with CABAC parsing.

10.6.6.11.12 Test bitstream #AVCCABA-4

Specification: All slices are coded as I, or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of P slices with CABAC parsing.

Purpose: Check that the decoder can properly decode P slices with CABAC parsing.

--`,,```,,,,````-`-`,,`,,`,`,,`---
© ISO/IEC 2005 All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.6.11.13 Test bitstream #AVCCABA-5

Specification: All slices are coded as I slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I slice with the deblocking filter process enabled and CABAC.

Purpose: Check that the decoder can properly decode I slices with CABAC parsing.

10.6.6.11.14 Test bitstream #AVCCABA-6

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of P slices with CABAC parsing.

Purpose: Check that the decoder can properly decode P slices with CABAC parsing.

10.6.6.11.15 Test bitstream #AVCCABA-7

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of B slices with CABAC parsing.

Purpose: Check that the decoder can properly decode B slices with CABAC parsing.

10.6.6.11.16 Test bitstream #AVCCABA-8

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of B slices with CABAC parsing.

Purpose: Check that the decoder can properly decode B slices with CABAC parsing.

10.6.6.12 Test Bitstreams – CABAC: Initialization

10.6.6.12.1 Test bitstream #AVCCAIN-1

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 0. cabac_init_idc is equal to 0, 1, or 2 in slice headers. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Initialization of CABAC.

Purpose: Check that the decoder can initialize CABAC with cabac_init_idc=0, 1, or 2.

© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.6.13 Test Bitstreams – CABAC: MB QP Delta

10.6.6.13.1 Test bitstream #AVCCAQP-1

Specification: All slices are coded as I slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 1. mb_qp_delta is equal to non-zero value to change the quantizer scale at each MB. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I slices with mb_qp_delta not equal to 0.

Purpose: Check that the decoder can properly decode I slices with mb_qp_delta not equal to 0.

10.6.6.13.2 Test bitstream #AVCCAQP-2

Specification: All slices are coded as I, P or B slices. Each picture contains more than one slice. Each slice has different size. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. mb_qp_delta is equal to non-zero value to change the quantizer scale at each MB. disable_deblocking_filter_idc is equal to 2. chroma_qp_index_offset is equal to non-zero value. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of I, P, and B slices with mb_qp_delta not equal to 0.

Purpose: Check that the decoder can properly decode I slices with mb_qp_delta not equal to 0, disable_deblocking_filter_idc equal to 2, and non-zero chroma_qp_index_offset.

10.6.6.14 Test Bitstreams – CABAC: Slice

10.6.6.14.1 Test bitstream #AVCCASL-1

Specification: All slices are coded as I, P or B slices. Each picture contains more than one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 0. Each picture contains more than one slice. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of different slice types in a picture with CABAC parsing.

Purpose: Check that the decoder can properly decode different slice types in a picture with CABAC parsing.

10.6.6.14.2 Test bitstream #AVCCASL-2

Specification: All slices are coded as I, P or B slices. Each picture contains more than one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 0. Slices with different slice types are included in a picture. Stored B slices are included in the bitstream. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of different slice types in a picture with CABAC parsing.

Purpose: Check that the decoder can properly decode different slice types in a picture with CABAC parsing.

© ISO/IEC 2005 All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.6.15 Test Bitstreams – CABAC: I_PCM

10.6.6.15.1 Test bitstream #AVCCAPCM-1

Specification: All slices are coded as I slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. mb_type is equal to I_PCM at some Macroblocks. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of Macroblock with mb_type equal to I_PCM.

Purpose: Check that the decoder can properly decode Macroblock with mb_type equal to I_PCM.

10.6.6.15.2 Test bitstream #AVCCAPCM-2

Specification: All slices are coded as I slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. mb_type is equal to I_PCM at some Macroblocks. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of Macroblock with mb_type equal to I_PCM.

Purpose: Check that the decoder can properly decode Macroblock with mb_type equal to I_PCM.

10.6.6.15.3 Test bitstream #AVCCAPCM-3

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. mb_type is equal to I_PCM at some Macroblocks. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of Macroblock with mb_type equal to I_PCM.

Purpose: Check that the decoder can properly decode macroblocks with mb_type equal to I_PCM.

10.6.6.16 Test Bitstreams – CABAC: Weighted sample prediction process

10.6.6.16.1 Test bitstream #AVCCAWP-1

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 2. weighted_pred_flag is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Weighted sample prediction process for P slice

Purpose: Check that the decoder handles weighted sample prediction for P slice.

10.6.6.16.2 Test bitstream #AVCCAWP-2

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 2. weighted_pred_flag is equal to 1. Plural reference indices are assigned to each reference picture. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Functional stage: Weighted sample prediction process for P slices with plural reference indices.

Purpose: Check that the decoder handles weighted sample prediction for P slices with plural reference indexes.

10.6.6.17 Test Bitstreams – CABAC: Field coding

10.6.6.17.1 Test bitstream #AVCCAFI-1

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. Each slice is a coded field. Stored B slices are included in the bitstream. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of coded fields.

Purpose: Check that the decoder can properly decode slice of coded field including stored B slice.

10.6.6.17.2 Test bitstream #AVCCAFI-2

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Spatial direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 0. Each slice is a coded field. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of coded fields.

Purpose: Check that the decoder can properly decode slice of coded field.

10.6.6.17.3 Test bitstream #AVCCAFI-3

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. Each slice is a coded field. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Decoding of coded fields.

Purpose: Check that the decoder can properly decode slice of coded field.

10.6.6.18 Test Bitstreams – CABAC: Frame/field decoding

10.6.6.18.1 Test bitstream #AVCCAPA-1

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 1. Spatial direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. Each slice is either a coded frame or a coded field. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Picture adaptive frame/field decoding.

Purpose: Check that the decoder can properly decode slices of coded frames and fields with direct_8x8_inference_flag=1.

© ISO/IEC 2005 All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.6.18.2 Test bitstream #AVCCAPA-2

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. Each slice is either a coded frame or a coded field. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Picture adaptive frame/field decoding.

Purpose: Check that the decoder can properly decode slices of coded frames and fields with direct_8x8_inference_flag=1.

10.6.6.18.3 Test bitstream #AVCCAPA-3

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. Each slice is either a coded frame or a coded field. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Picture adaptive frame/field decoding.

Purpose: Check that the decoder can properly decode slices of coded frames and fields with direct_8x8_inference_flag=1.

10.6.6.19 Test bitstreams - Macroblock adaptive frame/field decoding

10.6.6.19.1 Test bitstream #AVCCAMA-1

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Spatial direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1.

10.6.6.19.2 Test bitstream #AVCCAMA-2

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1.

--`,,```,,,,````-`-`,,`,,`,`,,`---
© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.6.19.3 Test bitstream #AVCCAMA-3

Specification: All slices are coded as I or P slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. num_ref_frames is equal to 1. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1.

10.6.6.19.4 Test bitstream #AVCCAMA-4

Specification: All slices are coded as I or P slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1.

10.6.6.19.5 Test bitstream #AVCCAMA-5

Specification: All slices are coded as I slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1.

10.6.6.19.6 Test bitstream #AVCCAMA-6

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Spatial direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1.

10.6.6.19.7 Test bitstream #AVCCAMA-7

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1.

© ISO/IEC 2005 All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.6.6.19.8 Test bitstream #AVCCAMA-8

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1.

10.6.6.19.9 Test bitstream #AVCCAMA-9

Specification: All slices are coded as I, P or B slices. Each picture contains more than one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1.

10.6.6.19.10 Test bitstream #AVCCAMA-10

Specification: All slices are coded as I, P or B slices. Each picture contains more than one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. direct_8x8_inference_flag is equal to 1. mb_adaptive_frame_field_coding is equal to 1. constrained_intra_pred_flag is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can handle constrained intra prediction with mb_adaptive_frame_field_flag=1.

10.6.6.19.11 Test bitstream #AVCCAMA-11

Specification: All slices are coded as I, P or B slices. Each picture contains more than one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. direct_8x8_inference_flag is equal to 1. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1.

10.6.6.19.12 Test bitstream #AVCCAMA-12 and AVCCAMA-13

Specification: All slices are coded as I, P or B slices. Each picture contains more than one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. The number of motion vectors per tow consecutive MBs is equal to the maximum value specified in Annex A.3.1.m in ITU-T Rec. H.264 | ISO/IEC 14496-10. No intra, skip and direct MBs are included in P and B slices. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding.

© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1 and with maximum number of motion vectors per consecutive MBs.

10.6.6.19.13 Test bitstream #AVCCAPAMA-1

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. Both coded frames and coded fields are included in the bitstream. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding and slices of a coded field.

Purpose: Check that the decoder can properly decode both slice of a coded frame with mb_adaptive_frame_field_flag=1 and slices of a coded field.

10.6.6.19.14 Test bitstream #AVCCAPAMA-2

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. The first field of the first frame only contains I slice and the second field only contains P slice. mb_adaptive_frame_field_coding is equal to 1 in the rest of the frames. The indicated display of this bitstream is bottom field first. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding and slices of a coded field.

Purpose: Check that the decoder can properly decode both slice of a coded frame with mb_adaptive_frame_field_flag=1 and slices of a coded field.

10.6.6.19.15 Test bitstream #AVCCAPAMA-3

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. The first field of the first frame only contains I slice and the second field only contains P slice. mb_adaptive_frame_field_coding is equal to 1 in the rest of the frames. The indicated display of this bitstream is top field first. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding and slices of a coded field.

Purpose: Check that the decoder can properly decode both slices of a coded frame with mb_adaptive_frame_field_flag=1 and slices of a coded field.

10.6.6.19.16 Test bitstream #AVCCAPAMA-4

Specification: All slices are coded as I, P or B slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. The first field of the first frame only contains I slice and the second field only contains P slice. mb_adaptive_frame_field_coding is equal to 1 in the rest of the frames. The indicated display of this bitstream is top field first. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

--`,,```,,,,````-`-`,,`,,`,`,,`---

© ISO/IEC 2005 All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Functional stage: Macroblock adaptive frame field decoding and slices of a coded field.

Purpose: Check that the decoder can properly decode both slices of a coded frame with mb_adaptive_frame_field_flag=1 and slices of a coded field.

10.6.6.19.17 Test bitstream #AVCCAMV-1

Specification: The bitstream conforms to MP@L3.0. Frame size is 720x480. All slices are coded as I, P or B slices. entropy_coding_mode_flag is equal to 1, specifying the CABAC parsing process. pic_order_cnt_type is equal to 0. Temporal direct prediction is used for direct prediction. direct_8x8_inference_flag is equal to 1. In P slices, each macroblock is coded as sixteen 4x4 blocks. Each block has one motion vector in 1/4 sample position. In B slices, each macroblock is coded as eight 8x4 blocks. Each block has two motion vectors, one for list0 the other for list1. Both vectors are in 1/4 sample position. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Prediction bandwidth.

Purpose: Check that the decoder handles the worse case of prediction bandwidth. Prediction bandwidth is at maximum due to largest number of motion vectors (in 1/4 sample position) per macroblock pair (32 as defined in standard). Non-integer position motion vectors require using 6-tap filter always.

10.6.6.19.18 Test bitstream #AVCCVCANLMA-1

Specification: All slices are coded as I or P slices. Each picture contains only one slice. disable_deblocking_filter_idc is equal to 1, specifying disabling of the deblocking filter process. Both entropy_coding_mode_flag equal to 0, specifying the CAVLC parsing process, and entropy_coding_mode_flag equal to 1, specifying the CABAC parsing process are present within the bitstream. pic_order_cnt_type is equal to 0. mb_adaptive_frame_field_coding is equal to 1. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.

Functional stage: Macroblock adaptive frame field decoding using both CAVLC and CABAC.

Purpose: Check that the decoder can properly decode slices with mb_adaptive_frame_field_flag=1 Check that the decoder can properly decode both CABAC and CAVLC.

10.6.7 Normative Test Suites for ITU-T Rec. H.264 | ISO/IEC 14496-10

Legend:

X – Bitstream is for static and dynamic test

Table AMD9-1 – Bitstreams included in this Specification

Categories	Bitstream	Donated by	File Name	Baseline	Extended	Main	Level	Frame Rate (Frame/Sec)
General	AVCNL-1	Sony	NL1_Sony_D	X	X	X	1.2 and higher	15
	AVCNL-2	SVA	SVA_NL1_B	X	X	X	2.1 and higher	29.97
	AVCNL-3	Sony	NL2_Sony_H	X	X	X	3.1 and higher	15
	AVCNL-4	SVA	SVA_NL2_E	X	X	X	2.1 and higher	29.97

--`,,```,,,,````-`-`,,`,,`,`,,`---
© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

	AVCBA-1	Sony	BA1_Sony_D	X	X	X	1.2 and higher	15
	AVCBA-2	SVA	SVA_BA1_B	X	X	X	2.1 and higher	29.97
	AVCBA-3	Sony	BA2_Sony_F	X	X	X	3.1 and higher	15
	AVCBA-4	SVA	SVA_BA2_D	X	X	X	2.1 and higher	29.97
	AVCBA-5	MCubeworks	BA_MW_D	X	X	X	1.0 and higher	15
	AVCBA-6	MCubeworks	BANM_MW_D	X	X	X	1.0 and higher	15
	AVCBA-7	France Telecom	BA1_FT_C	X	X	X	2.0 and higher	25
	AVCMQ-1	JVC	NLMQ1_JVC_C	X	X	X	2.0 and higher	25
	AVCMQ-2	JVC	NLMQ2_JVC_C	X	X	X	2.0 and higher	25
	AVCMQ-3	JVC	BAMQ1_JVC_C	X	X	X	2.0 and higher	25
	AVCMQ-4	JVC	BAMQ2_JVC_C	X	X	X	2.0 and higher	25
	AVCSL-1	SVA	SVA_Base_B	X	X	X	2.1 and higher	29.97
	AVCSL-2	SVA	SVA_FM1_E	X	X	X	2.1 and higher	29.97
	AVCSQ-1	Sony	BASQP1_Sony_C	X	X	X	2.1 and higher	15
	AVCFM-1	British Telecom	FM1_BT_B	X	X		1.0 and higher	5
	AVCFM-2	SVA	FM2_SVA_C	X	X		2.1 and higher	15
	AVCFM-3	France Telecom	FM1_FT_E	X	X		2.0 and higher	25
	AVCCI-1	MCubeworks	CI_MW_D	X	X	X	1.0 and higher	15
	AVCCI-2	SVA	SVA_CL1_E	X	X	X	2.1 and higher	29.97
	AVCCI-3	France Telecom	CI1_FT_B	X	X	X	2.0 and higher	25
	AVCFC-1	Sony	CVFC1_Sony_C	X	X	X	3.1 and higher	29.97
	AVCAUD-1	Mcubeworks	AUD_MW_E	X	X	X	1.0 and higher	15
	AVCMIDR-1	Mcubeworks	MIDR_MW_D	X	X	X	1.0 and higher	15
	AVCNRF-1	Mcubeworks	NRF_MW_E	X	X	X	1.0 and higher	15
	AVCMPS-1	Mcubeworks	MPS_MW_A	X	X	X	1.1 and higher	15
	AVCBS-1	Sony	CVBS3_Sony_C		X	X	1.2 and higher	15
	AVCBS-2	SVA	BA3_SVA_C		X	X	2.1 and higher	29.97

© ISO/IEC 2005 All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

	AVCBS-3	SVA	SL1_SVA_B			X	2.1 and higher	29.97
	AVCBS-4	SVA	NL3_SVA_E		X	X	1.1 and higher	29.97
	AVCBS-5	Motorola	cavlc_mot_frm0_full_B		X	X	2.2 and higher	29.97
I_PCM	AVCPCM-1	SVA	CVPCMNL1_SVA_C	X	X	X	4.0 and higher	29.97
	AVCPCM-2	SVA	CVPCMNL2_SVA_C	X	X	X	4.0 and higher	60
MMCO	AVCMR-1	British Telecom	MR1_BT_A	X	X	X	1.1 and higher	20
	AVCMR-2	Tandberg	MR2_Tandberg_E	X	X		3.1 and higher	29.97
	AVCMR-3	Tandberg	MR3_Tandberg_B	X	X		3.1 and higher	29.97
	AVCMR-4	Tandberg	MR4_Tandberg_C	X	X		3.1 and higher	29.97
	AVCMR-5	Tandberg	MR5_Tandberg_C	X	X		3.1 and higher	29.97
	AVCMR-6	Mcubeworks	MR1_MW_A	X	X	X	1.1 and higher	15
	AVCMR-7	Mcubeworks	MR2_MW_A	X	X	X	1.1 and higher	15
WP	AVCWP-1	Toshiba	CVWP5_TOSHIBA_E		X	X	2.0 and higher	7.5
	AVCWP-2	Toshiba	CVWP1_TOSHIBA_E			X	2.0 and higher	7.5
	AVCWP-3	Toshiba	CVWP2_TOSHIBA_E			X	2.0 and higher	7.5
	AVCWP-4	Toshiba	CVWP3_TOSHIBA_E			X	2.0 and higher	7.5
Field coding	AVCFI-1	Sony	CVNLFI1_Sony_C		X	X	3.1 and higher	29.97
	AVCFI-2	Sony	CVNLFI2_Sony_H		X	X	3.1 and higher	29.97
	AVCFI-3	Sharp Labs	Sharp_MP_Field1_B		X	X	3.0 and higher	29.97
	AVCFI-4	Sharp Labs	Sharp_MP_Field2_B		X	X	3.0 and higher	29.97
	AVCFI-5	Sharp Labs	Sharp_MP_Field3_B		X	X	3.0 and higher	29.97
	AVCFI-6	Sony	CVFI1_Sony_D		X	X	3.1 and higher	29.97
	AVCFI-7	Sony	CVFI2_Sony_H			X	3.1 and higher	29.97
	AVCFI-8	Sony	FI1_Sony_E		X	X	2.1 and higher	29.97
	AVCFI-9	SVA	CVFI1_SVA_C			X	3.0 and higher	29.97
	AVCFI-10	SVA	CVFI2_SVA_C		X	X	3.0 and higher	29.97
	AVCFI-11	Motorola	cavlc_mot_fld0_full_B		X	X	2.2 and higher	29.97
	AVCFI-12	Motorola	CVMP_MOT_FLD_ L30_B		X	X	3.0 and higher	29.97

© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Frame/field coding	AVCPA-1	Sharp Labs	Sharp_MP_PAFF_ 1r2		X	X	3.0 and higher	29.97
	AVCPA-2	Toshiba	CVPA1_TOSHIBA_B		X	X	2.1 and higher	25
	AVCPA-3	Motorola	cavlc_mot_picaff0_full_ B		X	X	2.2 and higher	29.97
MBAFF	AVCMA-1	Toshiba	CVMANL1_TOSHIBA_ B		X	X	2.1 and higher	25
	AVCMA-2	Toshiba	CVMANL2_TOSHIBA_ B		X	X	2.1 and higher	25
	AVCMA-3	Sony	CVMA1_Sony_D		X	X	3.1 and higher	29.97
	AVCMA-4	Toshiba	CVMA1_TOSHIBA_B		X	X	2.1 and higher	25
	AVCMA-5	Sony	CVMAQP2_Sony_G		X	X	3.1 and higher	29.97
	AVCMA-6	Sony	CVMAQP3_Sony_D		X	X	2.1 and higher	29.97
	AVCMA-7	Sony	CVMAPAQP3_Sony_E		X	X	3.1 and higher	29.97
	AVCMA-8	Motorola	cavlc_mot_mbaff0_ full_B		X	X	2.2 and higher	29.97
	AVCMA-9	Motorola	CVMP_MOT_FRM_L3 1_B		X	X	3.1 and higher	29.97
S Picture	AVCSP-1	British Telecom	SP1_BT_A		X		1.0 and higher	10
	AVCSP-2	British Telecom	SP2_BT_B		X		1.0 and higher	20
Long Sequence	AVCLS-1	SVA	LS_SVA_D	X	X	X	1.3 and higher	29.97
SEI/VUI	AVCSE-1	Sony	CVSE2_Sony_B		X	X	2.1 and higher	15
	AVCSE-2	Sony	CVSE3_Sony_H		X	X	2.1 and higher	15
	AVCSE-3	Sony	CVSEFDFT3_Sony_E		X	X	2.1 and higher	15
CABAC	AVCCANL-1	Toshiba	CANL1_TOSHIBA_G			X	1.2 and higher	29.97
	AVCCANL-2	Sony	CANL1_Sony_E			X	2.1 and higher	15
	AVCCANL-3	Sony	CANL2_Sony_E			X	2.1 and higher	15
	AVCCANL-4	Sony	CANL3_Sony_C			X	1.2 and higher	15
	AVCCANL-5	SVA	CANL1_SVA_B			X	2.1 and higher	29.97
	AVCCANL-6	SVA	CANL2_SVA_B			X	2.1 and higher	29.97
	AVCCANL-7	SVA	CANL3_SVA_B			X	2.1 and higher	29.97
	AVCCANL-8	SVA	CANL4_SVA_B			X	2.1 and higher	29.97

© ISO/IEC 2005 All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

	AVCCABA-1	Sony	CABA1_Sony_D			X	2.1 and higher	15
	AVCCABA-2	Sony	CABA2_Sony_E			X	2.1 and higher	15
	AVCCABA-3	Sony	CABA3_Sony_C			X	1.2 and higher	15
	AVCCABA-4	Toshiba	CABA3_TOSHIBA_E			X	1.2 and higher	29.97
	AVCCABA-5	SVA	CABA1_SVA_B			X	2.1 and higher	29.97
	AVCCABA-6	SVA	CABA2_SVA_B			X	2.1 and higher	29.97
	AVCCABA-7	SVA	CABA3_SVA_B			X	2.1 and higher	29.97
	AVCCABA-8	Motorola	cabac_mot_frm0_full			X	2.2 and higher	29.97
CABAC: Initialization	AVCCAIN-1	Sony	CABACI3_Sony_B			X	2.1 and higher	15
CABAC: MB QP Delta	AVCCAQP-1	Sony	CAQP1_Sony_B			X	1.2 and higher	15
	AVCCAQP-2	Sony	CACQP3_Sony_D			X	2.1 and higher	15
CABAC: Slice	AVCCASL-1	Sony	CABAST3_Sony_E			X	2.1 and higher	29.97
	AVCCASL-2	Sony	CABASTBR3_Sony_B			X	2.1 and higher	29.97
CABAC: I_PCM	AVCCAPCM-1	Broadcom	CAPCMNL1_Sand_E			X	4.0 and higher	29.97
	AVCCAPCM-2	Broadcom	CAPCM1_Sand_E			X	4.0 and higher	29.97
	AVCCAPCM-3	Sony	CAPM3_Sony_D			X	2.1 and higher	15
CABAC: WP	AVCCAWP-1	Toshiba	CAWP1_TOSHIBA_E			X	2.0 and higher	7.5
	AVCCAWP-2	Toshiba	CAWP5_TOSHIBA_E			X	2.0 and higher	7.5
CABAC: Field coding	AVCCAFI-1	Broadcom	CABREF3_Sand_D			X	4.0 and higher	29.97
	AVCCAFI-2	SVA	CAFI_SVA_C			X	3.0 and higher	29.97
	AVCCAFI-3	Motorola	cabac_mot_fld0_full			X	2.2 and higher	29.97
CABAC: Frame/Field Coding	AVCCAPA-1	Sharp Labs	Sharp_MP_PAFF_2r			X	3.0 and higher	29.97
	AVCCAPA-2	Toshiba	CAPA1_TOSHIBA_B			X	2.1 and higher	25
	AVCCAPA-3	Motorola	cabac_mot_paff0_full			X	2.2 and higher	29.97
CABAC: MBAFF	AVCCAMA-1	Toshiba	CAMANL1_TOSHIBA_B			X	2.1 and higher	25
	AVCCAMA-2	Toshiba	CAMANL2_TOSHIBA_B			X	2.1 and higher	25
	AVCCAMA-3	Sony	CANLMA2_Sony_C			X	3.1 and higher	29.97

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale
© ISO/IEC 2005 – All rights reserved

	AVCCAMA-4	Sony	CANLMA3_Sony_C			X	3.1 and higher	29.97
	AVCCAMA-5	Sony	CAMA1_Sony_C			X	3.1 and higher	29.97
	AVCCAMA-6	Toshiba	CAMA1_TOSHIBA_B			X	2.1 and higher	25
	AVCCAMA-7	Broadcom	CAMANL3_Sand_E			X	4.0 and higher	29.97
	AVCCAMA-8	Broadcom	CAMA3_Sand_E			X	4.0 and higher	29.97
	AVCCAMA-9	Sony	CAMASL3_Sony_B			X	2.1 and higher	29.97
	AVCCAMA-10	Sony	CAMACI3_Sony_C			X	2.1 and higher	29.97
	AVCCAMA-11	Motorola	cabac_mot_mbaff0_full			X	2.2 and higher	29.97
	AVCCAMA-12	Motorola	CAMP_MOT_MBAFF_L30			X	3.0 and higher	29.97
	AVCCAMA-13	Motorola	CAMP_MOT_MBAFF_L31			X	3.1 and higher	29.97
	AVCCAPAMA-1	Broadcom	CAPAMA3_Sand_F			X	4.0 and higher	29.97
	AVCCAPAMA-2	VideoTele.com	CAMA1_VTC_C			X	3.0 and higher	29.97
	AVCCAPAMA-3	VideoTele.com	CAMA2_VTC_B			X	3.0 and higher	25
	AVCCAPAMA-4	VideoTele.com	CAMA3_VTC_B			X	3.0 and higher	25
CABAC: Prediction Bandwidth	AVCCAMV-1	Broadcom	MV1_BRCM_D			X	3.0 and higher	29.97
CABAC/ CAVLC	AVCCVCANLMA-1	Sony	CVCANLMA2_Sony_C			X	3.1 and higher	29.97

Add the following at the end of Annex D:

Organisations providing patent rights licensing notices for ISO/IEC 14496-4:2004/Amd.6

Nokia

© ISO/IEC 2005 All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

ICS 35.040

Price based on 37 pages

© ISO/IEC 2005 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale