INTERNATIONAL STANDARD ISO/IEC 14496-4:2004/Amd.6:2005
TECHNICAL CORRIGENDUM 1

Published 2007-09-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

Information technology — Coding of audio-visual objects —

Part 4: Conformance testing

AMENDMENT 6: Advanced Video Coding conformance

TECHNICAL CORRIGENDUM 1

Technologies de l'information — Codage des objets audiovisuels —

Partie 4: Essai de conformité

AMENDEMENT 6: Conformité de codage vidéo avancé

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to ISO/IEC 14496-4:2004/Amd.6:2005 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

Replace:

10.6.6.1.8 Test bitstream #AVCBA-7, #AVCBA-8

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 2. Macroblock/sub-macroblock partition size is limited to 8x8 and above. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.
Functional stage: Decoding of P slices with the deblocking filter process enabled.
Purpose: Check that the decoder can properly decode P slices with the deblocking filter process enabled.

ICS 35.040 **Ref. No. ISO/IEC 14496-4:2004/Amd.6:2005/Cor.1:2007(E)**

© ISO/IEC 2007 – All rights reserved

Published in Switzerland

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

with:

10.6.6.1.8 Test bitstream #AVCBA-7, #AVCBA-8

10.6.6.1.8.1 Test bitstream #AVCBA-7

Specification: All slices are coded as I or P slices. Each picture contains more than one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 2. Macroblock/sub-macroblock partition size is limited to 8x8 and above. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.
Functional stage: Decoding of P slices with the deblocking filter process enabled.
Purpose: Check that the decoder can properly decode P slices with the deblocking filter process enabled.

10.6.6.1.8.2 Test bitstream #AVCBA-8

Specification: All slices are coded as I or P slices. Each picture contains only one slice. entropy_coding_mode_flag is equal to 0, specifying the CAVLC parsing process. pic_order_cnt_type is equal to 2. Macroblock/sub-macroblock partition size is limited to 8x8 and above. All NAL units are encapsulated into the byte stream format specified in Annex B in ITU-T Rec. H.264 | ISO/IEC 14496-10.
Functional stage: Decoding of P slices with the deblocking filter process enabled.
Purpose: Check that the decoder can properly decode P slices with the deblocking filter process enabled.

In Table AMD9-1, replace the following rows:

	AVCBS-5	Motorola	cavlc_mot_frm0_full_B		X	X	2.2 and higher	29.97
	AVCCABA-8	Motorola	cabac_mot_frm0_full			X	2.2 and higher	29.97

with:

	AVCBS-5	Motorola	cavlc_mot_frm0_full_B		X	X	3.0 and higher	29.97
	AVCCABA-8	Motorola	cabac_mot_frm0_full			X	3.0 and higher	29.97

Replace the following bitstreams with the electronic attachments to this Technical Corrigendum:

BA1_FT_C
BA1_Sony_D
BA2_Sony_F
BAMQ1_JVC_C
BAMQ2_JVC_C
BANM_MW_D
BASQP1_Sony_C
cabac_mot_fld0_full
cabac_mot_frm0_full
cabac_mot_mbaff0_full
cabac_mot_picaff0_full
cama1_vtc_c
cama2_vtc_b
cama3_vtc_b
CAMP_MOT_MBAFF_L30
CAMP_MOT_MBAFF_L31
CAPCM1_Sand_E

© ISO/IEC 2007 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

CAPCMNL1_Sand_E
cavlc_mot_frm0_full
cavlc_mot_fld0_full
cavlc_mot_mbaff0_full
cavlc_mot_picaff0_full
CI1_FT_B
CVFC1_Sony_C
CVMP_MOT_FLD_L30
CVMP_MOT_FRM_L31
CVPCMNL1_SVA_C
CVPCMNL2_SVA_C
CVSE2_Sony_B
FM1_FT_E
LS_SVA_D
NL1_Sony_D
NL2_Sony_H
NLMQ1_JVC_C
NLMQ2_JVC_C
SVA_BA1_B
SVA_BA2_D
SVA_Base_B
SVA_CL1_E
SVA_FM1_E
SVA_NL1_B
SVA_NL2_E

© ISO/IEC 2007 - All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale