INTERNATIONAL STANDARD

ISO/IEC 23360-4

First edition
2006-12-15

Linux Standard Base (LSB) core specification 3.1 —

Part 4: Specification for AMD64 architecture

Spécifications 3.1 relatives au noyau de base normalisé Linux (LSB) —

Partie 4: Spécifications pour l'architecture AMD64

Reference number
ISO/IEC 23360-4:2006(E)

© ISO/IEC 2006

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO/IEC 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

© ISO/IEC 2006 – All rights reserved

Not for Resale

Linux Standard Base Core Specification for AMD64 3.1
ISO/IEC 23360-4:2006(E)
Copyright © 2006 ISO/IEC

This standard includes material that has been provided by the Free Standards Group under the GNU Free Documentation License Version 1.1 published by the Free Software Foundation.

Portions of the text are copyrighted by the following parties:

- The Regents of the University of California
- Free Software Foundation
- Ian F. Darwin
- Paul Vixie
- BSDI (now Wind River)
- Andrew G Morgan
- Jean-loup Gailly and Mark Adler
- Massachusetts Institute of Technology

These excerpts are being used in accordance with their respective licenses.
Linux is the registered trademark of Linus Torvalds in the U.S. and other countries.
UNIX is a registered trademark of The Open Group.
LSB is a trademark of the Free Standards Group in the United States and other countries.
AMD is a trademark of Advanced Micro Devices, Inc.
Intel and Itanium are registered trademarks and Intel386 is a trademark of Intel Corporation.
PowerPC is a registered trademark and PowerPC Architecture is a trademark of the IBM Corporation.
S/390 is a registered trademark of the IBM Corporation.
OpenGL is a registered trademark of Silicon Graphics, Inc.

© ISO/IEC 2006 All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Contents

Foreword ..... **vii**
Introduction ..... **viii**
I Introductory Elements **0**
1 Scope 1
1.1 General 1
1.2 Module Specific Scope 1
2 References 2
2.1 Normative References 2
2.2 Informative References/Bibliography 4
3 Requirements 7
3.1 Relevant Libraries 7
3.2 LSB Implementation Conformance 7
3.3 LSB Application Conformance 8
4 Definitions 10
5 Terminology 11
6 Documentation Conventions 13
II Executable and Linking Format (ELF) **14**
7 Introduction 15
8 Low Level System Information 16
8.1 Machine Interface 16
8.2 Function Calling Sequence 17
8.3 Operating System Interface 18
8.4 Process Initialization 18
8.5 Coding Examples 18
8.6 C Stack Frame 19
8.7 Debug Information 19
9 Object Format 20
9.1 Introduction 20
9.2 ELF Header 20
9.3 Sections 20
9.4 Symbol Table 21
9.5 Relocation 21
10 Program Loading and Dynamic Linking 22
10.1 Introduction 22
10.2 Program Header 22
10.3 Program Loading 22
10.4 Dynamic Linking 22
III Base Libraries **24**
11 Libraries 25
11.1 Program Interpreter/Dynamic Linker 25
11.2 Interfaces for libc 25
11.3 Data Definitions for libc 40
11.4 Interfaces for libm 52
11.5 Data Definitions for libm 57
11.6 Interface Definitions for libm 58
11.7 Interfaces for libpthread 59
11.8 Data Definitions for libpthread 62
11.9 Interfaces for libgcc_s 62
11.10 Data Definitions for libgcc_s 63
11.11 Interface Definitions for libgcc_s 64
11.12 Interfaces for libdl 69
11.13 Data Definitions for libdl 70
11.14 Interfaces for libcrypt 70

© ISO/IEC 2006 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

IV Utility Libraries **71**
12 Libraries 72
12.1 Interfaces for libz 72
12.2 Data Definitions for libz 72
12.3 Interfaces for libncurses 72
12.4 Data Definitions for libncurses 73
12.5 Interfaces for libutil 73
V Package Format and Installation **75**
13 Software Installation 76
13.1 Package Dependencies 76
13.2 Package Architecture Considerations 76
A Alphabetical Listing of Interfaces **77**
A.1 libgcc_s 77
A.2 libm 77

© ISO/IEC 2006 All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

List of Tables

2-1 Normative References 2
2-2 Other References 4
3-1 Standard Library Names 7
8-1 Non Conforming Instructions 16
9-1 ELF Special Sections 20
9-2 Additional Special Sections 21
11-1 libc Definition 25
11-2 libc - RPC Function Interfaces 25
11-3 libc - System Calls Function Interfaces 26
11-4 libc - Standard I/O Function Interfaces 28
11-5 libc - Standard I/O Data Interfaces 29
11-6 libc - Signal Handling Function Interfaces 29
11-7 libc - Signal Handling Data Interfaces 30
11-8 libc - Localization Functions Function Interfaces 30
11-9 libc - Localization Functions Data Interfaces 31
11-10 libc - Socket Interface Function Interfaces 31
11-11 libc - Wide Characters Function Interfaces 32
11-12 libc - String Functions Function Interfaces 33
11-13 libc - IPC Functions Function Interfaces 34
11-14 libc - Regular Expressions Function Interfaces 34
11-15 libc - Character Type Functions Function Interfaces 34
11-16 libc - Time Manipulation Function Interfaces 35
11-17 libc - Time Manipulation Data Interfaces 35
11-18 libc - Terminal Interface Functions Function Interfaces 36
11-19 libc - System Database Interface Function Interfaces 36
11-20 libc - Language Support Function Interfaces 37
11-21 libc - Large File Support Function Interfaces 37
11-22 libc - Standard Library Function Interfaces 38
11-23 libc - Standard Library Data Interfaces 40
11-24 libm Definition 52
11-25 libm - Math Function Interfaces 53
11-26 libm - Math Data Interfaces 57
11-27 libpthread Definition 59
11-28 libpthread - Realtime Threads Function Interfaces 59
11-29 libpthread - Posix Threads Function Interfaces 60
11-30 libpthread - Thread aware versions of libc interfaces Function Interfaces 61
11-31 libgcc_s Definition 62
11-32 libgcc_s - Unwind Library Function Interfaces 63
11-33 libdl Definition 69
11-34 libdl - Dynamic Loader Function Interfaces 69
11-35 libcrypt Definition 70
11-36 libcrypt - Encryption Function Interfaces 70
12-1 libz Definition 72
12-2 libncurses Definition 73
12-3 libutil Definition 73
12-4 libutil - Utility Functions Function Interfaces 74
A-1 libgcc_s Function Interfaces 77
A-2 libm Function Interfaces 77

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
© ISO/IEC 2006 – All rights reserved
Not for Resale

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 23360-4 was prepared by the Free Standards Group and was adopted, under the PAS procedure, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 22, *Programming languages, their environments and system software interfaces*.

ISO/IEC 23360 consists of the following parts, under the general title *Linux Standard Base (LSB) core specification 3.1*:

— *Part 1: Generic specification*

— *Part 2: Specification for IA32 architecture*

— *Part 3: Specification for IA64 architecture*

— *Part 4: Specification for AMD64 architecture*

— *Part 5: Specification for PPC32 architecture*

— *Part 6: Specification for PPC64 architecture*

— *Part 7: Specification for S390 architecture*

— *Part 8: Specification for S390X architecture*

© ISO/IEC 2006 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Introduction

The LSB defines a binary interface for application programs that are compiled and packaged for LSB-conforming implementations on many different hardware architectures. Since a binary specification includes information specific to the computer processor architecture for which it is intended, it is not possible for a single document to specify the interface for all possible LSB-conforming implementations. Therefore, the LSB is a family of specifications, rather than a single one.

This document should be used in conjunction with the documents it references. This document enumerates the system components it includes, but descriptions of those components may be included entirely or partly in this document, partly in other documents, or entirely in other reference documents. For example, the section that describes system service routines includes a list of the system routines supported in this interface, formal declarations of the data structures they use that are visible to applications, and a pointer to the underlying referenced specification for information about the syntax and semantics of each call. Only those routines not described in standards referenced by this document, or extensions to those standards, are described in detail. Information referenced in this way is as much a part of this document as is the information explicitly included here.

The specification carries a version number of either the form `x.y` or `x.y.z`. This version number carries the following meaning:

- The first number (`x`) is the major version number. All versions with the same major version number should share binary compatibility. Any addition or deletion of a new library results in a new version number. Interfaces marked as `deprecated` may be removed from the specification at a major version change.
- The second number (`y`) is the minor version number. Individual interfaces may be added if all certified implementations already had that (previously undocumented) interface. Interfaces may be marked as `deprecated` at a minor version change. Other minor changes may be permitted at the discretion of the LSB workgroup.
- The third number (`z`), if present, is the editorial level. Only editorial changes should be included in such versions.

Since this specification is a descriptive Application Binary Interface, and not a source level API specification, it is not possible to make a guarantee of 100% backward compatibility between major releases. However, it is the intent that those parts of the binary interface that are visible in the source level API will remain backward compatible from version to version, except where a feature marked as `deprecated` in one release may be removed from a future release.

Implementors are strongly encouraged to make use of symbol versioning to permit simultaneous support of applications conforming to different releases of this specification.

This is version 3.1 of the Linux Standard Base Core Specification. This specification is part of a family of specifications under the general title "Linux Standard Base (LSB) core specification 3.1". Developers of applications or implementations interested in using the LSB trademark should see the Free Standards Group Certification Policy for details.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale
© ISO/IEC 2006 – All rights reserved

I Introductory Elements

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Linux Standard Base (LSB) core specification 3.1 —

Part 4: Specification for AMD64 architecture

1 Scope

1.1 General

The Linux Standard Base (LSB) defines a system interface for compiled applications and a minimal environment for support of installation scripts. Its purpose is to enable a uniform industry standard environment for high-volume applications conforming to the LSB.

These specifications are composed of two basic parts: A common specification ("LSB-generic" or "generic LSB"), ISO/IEC 23360-1, describing those parts of the interface that remain constant across all implementations of the LSB, and an architecture-specific part ("LSB-arch" or "archLSB") describing the parts of the interface that vary by processor architecture. Together, the LSB-generic and the relevant architecture-specific part of ISO/IEC 23360 for a single hardware architecture provide a complete interface specification for compiled application programs on systems that share a common hardware architecture.

ISO/IEC 23360-1, the LSB-generic document, is be used in conjunction with an architecture-specific part. Whenever a section of the LSB-generic specification is supplemented by architecture-specific information, the LSB-generic document includes a reference to the architecture part. Architecture-specific parts of ISO/IEC 23360 may also contain additional information that is not referenced in the LSB-generic document.

The LSB contains both a set of Application Program Interfaces (APIs) and Application Binary Interfaces (ABIs). APIs may appear in the source code of portable applications, while the compiled binary of that application may use the larger set of ABIs. A conforming implementation provides all of the ABIs listed here. The compilation system may replace (e.g. by macro definition) certain APIs with calls to one or more of the underlying binary interfaces, and may insert calls to binary interfaces as needed.

The LSB is primarily a binary interface definition. Not all of the source level APIs available to applications may be contained in this specification.

1.2 Module Specific Scope

This is the AMD64 architecture-specific Core part of the Linux Standard Base (LSB). It supplements the generic LSB Core module with those interfaces that differ between architectures.

Interfaces described in this part of ISO/IEC 23360 are mandatory except where explicitly listed otherwise. Core interfaces may be supplemented by other modules; all modules are built upon the core.

© 2006 ISO/IEC — All rights reserved

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

2 References

2.1 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

Note: Where copies of a document are available on the World Wide Web, a Uniform Resource Locator (URL) is given for informative purposes only. This may point to a more recent copy of the referenced specification, or may be out of date. Reference copies of specifications at the revision level indicated may be found at the Free Standards Group's Reference Specifications (http://refspecs.freestandards.org) site.

Table 2-1 Normative References

Name	Title	URL
ISO/IEC 23360-1	ISO/IEC 23360-1:2006, *Linux Standard Base (LSB) core specification 3.1— Part 1: Generic Specification*	http://www.linuxbase.org/spec/
AMD64 Architecture Programmer's Manual, Volume 1	AMD64 Architecture Programmer's Manual, Volume 1: Application Programming 24592 3.08	http://www.amd.com/us-en/Processors/DevelopWithAMD/
AMD64 Architecture Programmer's Manual, Volume 2	AMD64 Architecture Programmer's Manual, Volume 2: System Programming 24593 3.08	http://www.amd.com/us-en/Processors/DevelopWithAMD/
AMD64 Architecture Programmer's Manual, Volume 3	AMD64 Architecture Programmer's Manual, Volume 3: General Purpose and System Instructions 24594 3.03	http://www.amd.com/us-en/Processors/DevelopWithAMD/
AMD64 Architecture Programmer's Manual, Volume 4	AMD64 Architecture Programmer's Manual, Volume 4: 128-bit Media Instructions 26568 3.04	http://www.amd.com/us-en/Processors/DevelopWithAMD/
AMD64 Architecture Programmer's Manual, Volume 5	AMD64 Architecture Programmer's Manual, Volume 5: 64-bit Media and x87 Floating-Point Instructions 26569 3.03	http://www.amd.com/us-en/Processors/DevelopWithAMD/

 © 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Name	Title	URL
ISO C (1999)	ISO/IEC 9899: 1999, *Programming Languages — C*	
ISO POSIX (2003)	ISO/IEC 9945-1:2003, *Information technology — Portable Operating System Interface (POSIX) — Part 1: Base Definitions* ISO/IEC 9945-2:2003, *Information technology — Portable Operating System Interface (POSIX) — Part 2: System Interfaces* ISO/IEC 9945-3:2003, *Information technology — Portable Operating System Interface (POSIX) — Part 3: Shell and Utilities* ISO/IEC 9945-4:2003, *Information technology — Portable Operating System Interface (POSIX) — Part 4: Rationale*	http://www.unix.org/version3/
Large File Support	Large File Support	http://www.UNIX-systems.org/version2/whatsnew/lfs20mar.html
SUSv2	CAE Specification, January 1997, System Interfaces and Headers (XSH), Issue 5 (ISBN: 1-85912-181-0, C606)	http://www.opengroup.org/publications/catalog/un.htm
SVID Issue 3	American Telephone and Telegraph Company, System V Interface Definition, Issue 3; Morristown, NJ, UNIX Press, 1989. (ISBN 0201566524)	
SVID Issue 4	System V Interface Definition, Fourth Edition	

© 2006 ISO/IEC — All rights reserved

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Name	Title	URL
System V ABI	System V Application Binary Interface, Edition 4.1	http://www.caldera.com/developers/devspecs/gabi41.pdf
System V ABI Update	System V Application Binary Interface - DRAFT - 17 December 2003	http://www.caldera.com/developers/gabi/2003-12-17/contents.html
System V Application Binary Interface AMD64 Architecture Processor Supplement	System V Application Binary Interface AMD64 Architecture Processor Supplement, Draft Version 0.95	http://www.x86-64.org/documentation/abi-0.95.pdf
X/Open Curses	CAE Specification, May 1996, X/Open Curses, Issue 4, Version 2 (ISBN: 1-85912-171-3, C610), plus Corrigendum U018	http://www.opengroup.org/publications/catalog/un.htm

2.2 Informative References/Bibliography

In addition, the specifications listed below provide essential background information to implementors of this specification. These references are included for information only.

Table 2-2 Other References

Name	Title	URL
DWARF Debugging Information Format, Revision 2.0.0	DWARF Debugging Information Format, Revision 2.0.0 (July 27, 1993)	http://refspecs.freestandards.org/dwarf/dwarf-2.0.0.pdf
DWARF Debugging Information Format, Revision 3.0.0 (Draft)	DWARF Debugging Information Format, Revision 3.0.0 (Draft)	http://refspecs.freestandards.org/dwarf/
IEC 60559/IEEE 754 Floating Point	IEC 60559:1989, *Binary floating-point arithmetic for microprocessor systems*	http://www.ieee.org/
ISO/IEC TR 14652	ISO/IEC TR 14652:2004, *Information technology — Specification method for cultural conventions*	

 © 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Name	Title	URL
ITU-T V.42	International Telecommunication Union Recommendation V.42 (2002): Error-correcting procedures for DCEs using asynchronous-to-synchronous convention ITUV	http://www.itu.int/rec/recommendation.asp?type=folders&lang=e&parent=T-REC-V.42
Li18nux Globalization Specification	LI18NUX 2000 Globalization Specification, Version 1.0 with Amendment 4	http://www.li18nux.org/docs/html/LI18NUX-2000-amd4.htm
Linux Allocated Device Registry	LINUX ALLOCATED DEVICES	http://www.lanana.org/docs/device-list/devices.txt
PAM	Open Software Foundation, Request For Comments: 86.0, October 1995, V. Samar & R. Schemers (SunSoft)	http://www.opengroup.org/tech/rfc/mirror-rfc/rfc86.0.txt
RFC 1321: The MD5 Message-Digest Algorithm	IETF RFC 1321: The MD5 Message-Digest Algorithm	http://www.ietf.org/rfc/rfc1321.txt
RFC 1831/1832 RPC & XDR	IETF RFC 1831 & 1832	http://www.ietf.org/
RFC 1833: Binding Protocols for ONC RPC Version 2	IETF RFC 1833: Binding Protocols for ONC RPC Version 2	http://www.ietf.org/rfc/rfc1833.txt
RFC 1950: ZLIB Compressed Data Format Specication	IETF RFC 1950: ZLIB Compressed Data Format Specification	http://www.ietf.org/rfc/rfc1950.txt
RFC 1951: DEFLATE Compressed Data Format Specification	IETF RFC 1951: DEFLATE Compressed Data Format Specification version 1.3	http://www.ietf.org/rfc/rfc1951.txt
RFC 1952: GZIP File Format Specification	IETF RFC 1952: GZIP file format specification version 4.3	http://www.ietf.org/rfc/rfc1952.txt
RFC 2440: OpenPGP Message Format	IETF RFC 2440: OpenPGP Message Format	http://www.ietf.org/rfc/rfc2440.txt

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Name	Title	URL
RFC 2821: Simple Mail Transfer Protocol	IETF RFC 2821: Simple Mail Transfer Protocol	http://www.ietf.org/rfc/rfc2821.txt
RFC 2822: Internet Message Format	IETF RFC 2822: Internet Message Format	http://www.ietf.org/rfc/rfc2822.txt
RFC 791: Internet Protocol	IETF RFC 791: Internet Protocol Specification	http://www.ietf.org/rfc/rfc791.txt
RPM Package Format	RPM Package Format V3.0	http://www.rpm.org/max-rpm/s1-rpm-file-format-rpm-file-format.html
SUSv2 Commands and Utilities	The Single UNIX Specification (SUS) Version 2, Commands and Utilities (XCU), Issue 5 (ISBN: 1-85912-191-8, C604)	http://www.opengroup.org/publications/catalog/un.htm
zlib Manual	zlib 1.2 Manual	http://www.gzip.org/zlib/

 © 2006 ISO/IEC — All rights reserved

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

3 Requirements

3.1 Relevant Libraries

The libraries listed in Table 3-1 shall be available on x86-64 Linux Standard Base systems, with the specified runtime names. These names override or supplement the names specified in the generic LSB (ISO/IEC 23360-1) specification. The specified program interpreter, referred to as proginterp in this table, shall be used to load the shared libraries specified by `DT_NEEDED` entries at run time.

Table 3-1 Standard Library Names

Library	Runtime Name
libm	libm.so.6
libdl	libdl.so.2
libcrypt	libcrypt.so.1
libz	libz.so.1
libncurses	libncurses.so.5
libutil	libutil.so.1
libc	libc.so.6
libpthread	libpthread.so.0
proginterp	/lib64/ld-lsb-x86-64.so.3
libgcc_s	libgcc_s.so.1

These libraries will be in an implementation-defined directory which the dynamic linker shall search by default.

3.2 LSB Implementation Conformance

A conforming implementation is necessarily architecture specific, and must provide the interfaces specified by both the generic LSB Core specification (ISO/IEC 23360-1) and the relevant architecture specific part of ISO/IEC 23360.

> **Rationale:** An implementation must provide *at least* the interfaces specified in these specifications. It may also provide additional interfaces.

A conforming implementation shall satisfy the following requirements:

- A processor architecture represents a family of related processors which may not have identical feature sets. The architecture specific parts of ISO/IEC 23360 that supplement this specification for a given target processor architecture describe a minimum acceptable processor. The implementation shall provide all features of this processor, whether in hardware or through emulation transparent to the application.
- The implementation shall be capable of executing compiled applications having the format and using the system interfaces described in this document.
- The implementation shall provide libraries containing the interfaces specified by this document, and shall provide a dynamic linking mechanism that allows

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

these interfaces to be attached to applications at runtime. All the interfaces shall behave as specified in this document.

- The map of virtual memory provided by the implementation shall conform to the requirements of this document.
- The implementation's low-level behavior with respect to function call linkage, system traps, signals, and other such activities shall conform to the formats described in this document.
- The implementation shall provide all of the mandatory interfaces in their entirety.
- The implementation may provide one or more of the optional interfaces. Each optional interface that is provided shall be provided in its entirety. The product documentation shall state which optional interfaces are provided.
- The implementation shall provide all files and utilities specified as part of this document in the format defined here and in other referenced documents. All commands and utilities shall behave as required by this document. The implementation shall also provide all mandatory components of an application's runtime environment that are included or referenced in this document.
- The implementation, when provided with standard data formats and values at a named interface, shall provide the behavior defined for those values and data formats at that interface. However, a conforming implementation may consist of components which are separately packaged and/or sold. For example, a vendor of a conforming implementation might sell the hardware, operating system, and windowing system as separately packaged items.
- The implementation may provide additional interfaces with different names. It may also provide additional behavior corresponding to data values outside the standard ranges, for standard named interfaces.

3.3 LSB Application Conformance

A conforming application is necessarily architecture specific, and must conform to both the generic LSB Core specification (ISO/IEC 23360-1)and the relevant architecture specific part of ISO/IEC 23360.

A conforming application shall satisfy the following requirements:

- Its executable files shall be either shell scripts or object files in the format defined for the Object File Format system interface.
- Its object files shall participate in dynamic linking as defined in the Program Loading and Linking System interface.
- It shall employ only the instructions, traps, and other low-level facilities defined in the Low-Level System interface as being for use by applications.
- If it requires any optional interface defined in this document in order to be installed or to execute successfully, the requirement for that optional interface shall be stated in the application's documentation.
- It shall not use any interface or data format that is not required to be provided by a conforming implementation, unless:
  - If such an interface or data format is supplied by another application through direct invocation of that application during execution, that application shall be in turn an LSB conforming application.

 © 2006 ISO/IEC — All rights reserved

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

- The use of that interface or data format, as well as its source, shall be identified in the documentation of the application.

- It shall not use any values for a named interface that are reserved for vendor extensions.

A strictly conforming application shall not require or use any interface, facility, or implementation-defined extension that is not defined in this document in order to be installed or to execute successfully.

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

4 Definitions

For the purposes of this document, the following definitions, as specified in the *ISO/IEC Directives, Part 2, 2004, 5th Edition*, apply:

can

be able to; there is a possibility of; it is possible to

cannot

be unable to; there is no possibilty of; it is not possible to

may

is permitted; is allowed; is permissible

need not

it is not required that; no...is required

shall

is to; is required to; it is required that; has to; only...is permitted; it is necessary

shall not

is not allowed [permitted] [acceptable] [permissible]; is required to be not; is required that...be not; is not to be

should

it is recommended that; ought to

should not

it is not recommended that; ought not to

 © 2006 ISO/IEC — All rights reserved

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

5 Terminology

For the purposes of this document, the following terms apply:

archLSB

The architectural part of the LSB Specification which describes the specific parts of the interface that are platform specific. The archLSB is complementary to the gLSB.

Binary Standard

The total set of interfaces that are available to be used in the compiled binary code of a conforming application.

gLSB

The common part of the LSB Specification that describes those parts of the interface that remain constant across all hardware implementations of the LSB.

implementation-defined

Describes a value or behavior that is not defined by this document but is selected by an implementor. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence of the value or behavior. An application that relies on such a value or behavior cannot be assured to be portable across conforming implementations. The implementor shall document such a value or behavior so that it can be used correctly by an application.

Shell Script

A file that is read by an interpreter (e.g., awk). The first line of the shell script includes a reference to its interpreter binary.

Source Standard

The set of interfaces that are available to be used in the source code of a conforming application.

undefined

Describes the nature of a value or behavior not defined by this document which results from use of an invalid program construct or invalid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

unspecified

Describes the nature of a value or behavior not specified by this document which results from use of a valid program construct or valid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

© 2006 ISO/IEC — All rights reserved

--`,,```,,,,````-`-`,,`,,`,`,,`---
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Other terms and definitions used in this document shall have the same meaning as defined in Chapter 3 of the Base Definitions volume of ISO POSIX (2003).

 © 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

6 Documentation Conventions

Throughout this document, the following typographic conventions are used:

`function()`

the name of a function

command

the name of a command or utility

`CONSTANT`

a constant value

`parameter`

a parameter

`variable`

a variable

Throughout this specification, several tables of interfaces are presented. Each entry in these tables has the following format:

name

the name of the interface

(symver)

An optional symbol version identifier, if required.

[*`refno`*]

A reference number indexing the table of referenced specifications that follows this table.

For example,

forkpty(GLIBC_2.0) [SUSv3]

refers to the interface named `forkpty()` with symbol version `GLIBC_2.0` that is defined in the `SUSv3` reference.

Note: Symbol versions are defined in the architecture specific parts of ISO/IEC 23360 only.

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

II Executable and Linking Format (ELF)

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

7 Introduction

Executable and Linking Format (ELF) defines the object format for compiled applications. This specification supplements the information found in System V ABI Update and System V Application Binary Interface AMD64 Architecture Processor Supplement, and is intended to document additions made since the publication of that document.

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

8 Low Level System Information

8.1 Machine Interface

8.1.1 Processor Architecture

The AMD64 Architecture is specified by the following documents

- AMD64 Architecture Programmer's Manual, Volume 1
- AMD64 Architecture Programmer's Manual, Volume 2
- AMD64 Architecture Programmer's Manual, Volume 3
- AMD64 Architecture Programmer's Manual, Volume 4
- AMD64 Architecture Programmer's Manual, Volume 5
- System V Application Binary Interface AMD64 Architecture Processor Supplement

Applications conforming to this specification must provide feedback to the user if a feature that is required for correct execution of the application is not present. Applications conforming to this specification should attempt to execute in a diminished capacity if a required instruction set feature is not present. In particular, applications should not rely on the availability of the 3DNow!™ technology. In addition, a conforming application shall not use any instruction from Table 8-1.

> **Note:** Although this specification carries the attribution "AMD64", it is intended to apply to the entire `x86_64` set of processors, including those based on Intel ® Extended Memory 64 Technology (EM64T). However, this specification defers to the AMD architecture specified above.

Table 8-1 Non Conforming Instructions

LAHF	SAHF
SYSCALL	SYSRET
SYSENTER	SYSEXIT
CMPXCHG16B	FFXSR

Conforming applications may use only instructions which do not require elevated privileges.

Conforming applications shall not invoke the implementations underlying system call interface directly. The interfaces in the implementation base libraries shall be used instead.

> **Rationale:** Implementation-supplied base libraries may use the system call interface but applications must not assume any particular operating system or kernel version is present.

This specfication does not provide any performance guarantees of a conforming system. A system conforming to this specification may be implemented in either hardware or software.

 © 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

8.1.2 Data Representation

8.1.2.1 Introduction

LSB-conforming applications shall use the data representation as defined in Section 3.1.2 of System V Application Binary Interface AMD64 Architecture Processor Supplement.

> **Note:** The System V Application Binary Interface AMD64 Architecture Processor Supplement specification is itself layered on top of the System V Application Binary Interface - Intel386™ Architecture Processor Supplement.

8.1.2.2 Byte Ordering

LSB-conforming applications shall use the byte ordering defined in Section 3.1.2 of System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.1.2.3 Fundamental Types

LSB-conforming applications shall use only the fundamental types described in Section 3.1.2 of System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.1.2.4 Aggregates and Unions

LSB-conforming applications shall use alignment for aggregates and unions as described in Section 3.1.2 of System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.1.2.5 Bit Fields

LSB-conforming applications utilizing bit-fields shall follow the requirements of Section 3.1.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.2 Function Calling Sequence

8.2.1 Introduction

LSB-conforming applications shall use only the following features of the function calling sequence as defined in Section 3.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.2.2 Registers

LSB-conforming applications shall use only the registers described in Section 3.2.1 (Registers and the Stack Frame) of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.2.3 Floating Point Registers

LSB-conforming applications shall use only the floating point registers described in Section 3.2.1 (Registers and the Stack Frame) of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.2.4 Stack Frame

LSB-conforming applications shall use stack frames as described in Section 3.2.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

8.2.5 Arguments

LSB-conforming applications shall pass parameters to functions as described in Section 3.2.3 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.2.6 Return Values

Values are returned from functions as described in Section 3.3.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.3 Operating System Interface

LSB-conforming applications shall use only the following features of the Operating System Interfaces as defined in Section 3.3 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.3.1 Exception Interface

Synchronous and floating point or coprocessor exceptions shall behave as described in Section 3.3.1 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.3.2 Virtual Address Space

LSB-Conforming applications shall use only the virtual address space described in Section 3.3.2 and 3.3.4 of the System V Application Binary Interface AMD64 Architecture Processor Supplement. Virtual memory page sizes shall be subject to the limitations described in Section 3.3.3 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.4 Process Initialization

LSB-conforming applications shall use only the following features of the Process Initialization as defined in Section 3.4 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.4.1 Special Registers

During process initialization, the special registers shall be initalized as described in Section 3.4.1 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.4.2 Process Stack (on entry)

The process stack shall be initialized as described in Section 3.4.1 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.4.3 Auxiliary Vector

The auxiliary vector shall be initialized as described in Section 3.4.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.5 Coding Examples

LSB-conforming applications may use the coding examples given in Section 3.5 of the System V Application Binary Interface AMD64 Architecture Processor Supplement to guide implemention of fundamental operations in the following areas.

 © 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

8.5.1 Code Model Overview/Architecture Constraints

Section 3.5.1 of the System V Application Binary Interface AMD64 Architecture Processor Supplement describes a number of code models. LSB-Conforming applications may use any of these models except the Kernel and Large code models.

8.5.2 Position-Independent Function Prologue

LSB-conforming applications may follow the position-independent function prologue example in Section 3.5.3 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.5.3 Data Objects

LSB-conforming applications may follow the data objects examples in Section 3.5.4 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.5.4 Function Calls

LSB-conforming applications may follow the function call examples in Section 3.5.5 of the System V Application Binary Interface AMD64 Architecture Processor Supplement. See Chapter 3 of System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.5.5 Branching

LSB-conforming applications may follow the branching examples in Section 3.5.6 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.6 C Stack Frame

8.6.1 Variable Argument List

LSB-Conforming applications shall only use variable arguments to functions in the manner described in Section 3.5.7 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

8.7 Debug Information

LSB-Conforming applications may include DWARF debugging information. The DWARF Release Number and Register Number Mapping shall be as described in Section 3.6 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

© 2006 ISO/IEC — All rights reserved

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

9 Object Format

9.1 Introduction

LSB-conforming implementations shall support the Executable and Linking Format (ELF) object file , as defined by the System V ABI , System V ABI Update , System V Application Binary Interface AMD64 Architecture Processor Supplement and as supplemented by the generic LSB specification and ISO/IEC 23360-1.

9.2 ELF Header

9.2.1 Machine Information

LSB-conforming applications shall identify the Machine Information as defined in Section 4.1.1 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

9.3 Sections

9.3.1 Introduction

In addition to the requirements for ELF sections described in the generic LSB Core specification, conforming implementations shall support architecture specific sections as described below.

Note: The System V Application Binary Interface AMD64 Architecture Processor Supplement specifies some architecture specific section flags and section types that are not required by LSB-conforming systems.

9.3.2 Special Sections

The following architecture-specific sections are defined in the System V Application Binary Interface AMD64 Architecture Processor Supplement.

Table 9-1 ELF Special Sections

Name	Type	Attributes
.got	SHT_PROGBITS	SHF_ALLOC+SHF_WRITE
.plt	SHT_PROGBITS	SHF_ALLOC+SHF_EXECINSTR

.got

This section holds the global offset table

.plt

This section holds the procedure linkage table.

Note: Since LSB-conforming implementations are not required to support the large code model, it is not necessary for them to provide support for the additional special sections for the large code model described in the System V Application Binary Interface AMD64 Architecture Processor Supplement.

Also, the System V Application Binary Interface AMD64 Architecture Processor Supplement specifies a section `.eh_frame`, with a type of `SHT_AMD64_UNWIND`. This

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

section is described in the generic LSB-Core specification, but with type `SHT_PROGBITS`. This specification does not require support for the `SHT_AMD64_UNWIND` section type.

9.3.3 Additional Special Sections

The following additional sections are defined here.

Table 9-2 Additional Special Sections

Name	Type	Attributes
.rela.dyn	SHT_RELA	SHF_ALLOC
.rela.plt	SHT_RELA	SHF_ALLOC

.rela.dyn

This section holds RELA type relocation information for all sections of a shared library except the PLT

.rela.plt

This section holds RELA type relocation information for the PLT section of a shared library or dynamically linked application

9.4 Symbol Table

LSB-conforming applications shall use Symbol Tables as defined in Section 4.3 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

9.5 Relocation

LSB-conforming implementation shall support the required relocation types defined in Section 4.4.1 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

Note: Since LSB-conforming implementations are not required to support the large code model, it is not necessary for them to provide support for the additional relocation types for the large code model described in the System V Application Binary Interface AMD64 Architecture Processor Supplement.

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

10 Program Loading and Dynamic Linking

10.1 Introduction

LSB-conforming implementations shall support the object file information and system actions that create running programs as specified in the System V ABI , System V ABI Update , System V Application Binary Interface AMD64 Architecture Processor Supplement and as supplemented by the generic LSB specification and ISO/IEC 23360-1.

10.2 Program Header

LSB-conforming implementations are not required to support the additional types and flags for this architecture as defined in Section 5.1 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

> **Note:** The System V Application Binary Interface AMD64 Architecture Processor Supplement specification is itself layered on top of the System V Application Binary Interface - Intel386™ Architecture Processor Supplement. As such, the requirements of that specification are still requirements of this specification.

10.3 Program Loading

LSB-conforming implementations shall map file pages to virtual memory pages as described in Section 5.1 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

10.4 Dynamic Linking

10.4.1 Introduction

LSB-conforming implementations shall provide dynamic linking as specified in Section 5.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement, except as described in the following sections.

> **Note:** Since LSB-conforming implementations are not required to support the large model, support for dynamic linking of large model code is not required.

10.4.2 Dynamic Section

Dynamic section entries give information to the dynamic linker. The following dynamic entry types shall be supported:

DT_JMPREL

This entry is associated with a table of relocation entries for the procedure linkage table. This entry is mandatory both for executable and shared object files

DT_PLTGOT

This entry's d_ptr member gives the address of the first byte in the procedure linkage table

DT_RELACOUNT

The number of relative relocations in .rela.dyn

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.4.3 Global Offset Table

LSB-conforming implementations shall support a Global Offset Table as described in Section 5.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

10.4.4 Function Addresses

Function addresses shall behave as described in Section 5.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

10.4.5 Procedure Linkage Table

LSB-conforming implementations shall support a Procedure Linkage Table as described in Section 5.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

10.4.6 Initialization and Termination Functions

LSB-conforming implementations shall support initialization and termination functions as specified in Section 5.2.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

III Base Libraries

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

11 Libraries

An LSB-conforming implementation shall support some base libraries which provide interfaces for accessing the operating system, processor and other hardware in the system.

Interfaces that are unique to the AMD64 platform are defined here. This section should be used in conjunction with the corresponding section in the Linux Standard Base Specification.

11.1 Program Interpreter/Dynamic Linker

The Program Interpreter shall be `/lib64/ld-lsb-x86-64.so.3`.

11.2 Interfaces for libc

Table 11-1 defines the library name and shared object name for the libc library

Table 11-1 libc Definition

Library:	libc
SONAME:	libc.so.6

The behavior of the interfaces in this library is specified by the following specifications:

[LFS] Large File Support
[LSB] ISO/IEC 23360-1
[SUSv2] SUSv2
[SUSv3] ISO POSIX (2003)
[SVID.3] SVID Issue 3
[SVID.4] SVID Issue 4

11.2.1 RPC

11.2.1.1 Interfaces for RPC

An LSB conforming implementation shall provide the architecture specific functions for RPC specified in Table 11-2, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-2 libc - RPC Function Interfaces

authnone_create(GLIBC_2.2.5) [SVID.4]	clnt_create(GLIBC_2.2.5) [SVID.4]	clnt_pcreateerror(GLIBC_2.2.5) [SVID.4]	clnt_perrno(GLIBC_2.2.5) [SVID.4]
clnt_perror(GLIBC_2.2.5) [SVID.4]	clnt_spcreateerror(GLIBC_2.2.5) [SVID.4]	clnt_sperrno(GLIBC_2.2.5) [SVID.4]	clnt_sperror(GLIBC_2.2.5) [SVID.4]
key_decryptsession(GLIBC_2.2.5) [SVID.3]	pmap_getport(GLIBC_2.2.5) [LSB]	pmap_set(GLIBC_2.2.5) [LSB]	pmap_unset(GLIBC_2.2.5) [LSB]
svc_getreqset(GLIBC_2.2.5) [SVID.3]	svc_register(GLIBC_2.2.5) [LSB]	svc_run(GLIBC_2.2.5) [LSB]	svc_sendreply(GLIBC_2.2.5) [LSB]

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

svcerr_auth(GLIBC_2.2.5) [SVID.3]	svcerr_decode(GLIBC_2.2.5) [SVID.3]	svcerr_noproc(GLIBC_2.2.5) [SVID.3]	svcerr_noprog(GLIBC_2.2.5) [SVID.3]
svcerr_progvers(GLIBC_2.2.5) [SVID.3]	svcerr_systemerr(GLIBC_2.2.5) [SVID.3]	svcerr_weakauth(GLIBC_2.2.5) [SVID.3]	svctcp_create(GLIBC_2.2.5) [LSB]
svcudp_create(GLIBC_2.2.5) [LSB]	xdr_accepted_reply(GLIBC_2.2.5) [SVID.3]	xdr_array(GLIBC_2.2.5) [SVID.3]	xdr_bool(GLIBC_2.2.5) [SVID.3]
xdr_bytes(GLIBC_2.2.5) [SVID.3]	xdr_callhdr(GLIBC_2.2.5) [SVID.3]	xdr_callmsg(GLIBC_2.2.5) [SVID.3]	xdr_char(GLIBC_2.2.5) [SVID.3]
xdr_double(GLIBC_2.2.5) [SVID.3]	xdr_enum(GLIBC_2.2.5) [SVID.3]	xdr_float(GLIBC_2.2.5) [SVID.3]	xdr_free(GLIBC_2.2.5) [SVID.3]
xdr_int(GLIBC_2.2.5) [SVID.3]	xdr_long(GLIBC_2.2.5) [SVID.3]	xdr_opaque(GLIBC_2.2.5) [SVID.3]	xdr_opaque_auth(GLIBC_2.2.5) [SVID.3]
xdr_pointer(GLIBC_2.2.5) [SVID.3]	xdr_reference(GLIBC_2.2.5) [SVID.3]	xdr_rejected_reply(GLIBC_2.2.5) [SVID.3]	xdr_replymsg(GLIBC_2.2.5) [SVID.3]
xdr_short(GLIBC_2.2.5) [SVID.3]	xdr_string(GLIBC_2.2.5) [SVID.3]	xdr_u_char(GLIBC_2.2.5) [SVID.3]	xdr_u_int(GLIBC_2.2.5) [LSB]
xdr_u_long(GLIBC_2.2.5) [SVID.3]	xdr_u_short(GLIBC_2.2.5) [SVID.3]	xdr_union(GLIBC_2.2.5) [SVID.3]	xdr_vector(GLIBC_2.2.5) [SVID.3]
xdr_void(GLIBC_2.2.5) [SVID.3]	xdr_wrapstring(GLIBC_2.2.5) [SVID.3]	xdrmem_create(GLIBC_2.2.5) [SVID.3]	xdrrec_create(GLIBC_2.2.5) [SVID.3]
xdrrec_eof(GLIBC_2.2.5) [SVID.3]			

11.2.2 System Calls

11.2.2.1 Interfaces for System Calls

An LSB conforming implementation shall provide the architecture specific functions for System Calls specified in Table 11-3, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-3 libc - System Calls Function Interfaces

__fxstat(GLIBC_2.2.5) [LSB]	__getpgid(GLIBC_2.2.5) [LSB]	__lxstat(GLIBC_2.2.5) [LSB]	__xmknod(GLIBC_2.2.5) [LSB]
__xstat(GLIBC_2.2.5) [LSB]	access(GLIBC_2.2.5) [SUSv3]	acct(GLIBC_2.2.5) [LSB]	alarm(GLIBC_2.2.5) [SUSv3]
brk(GLIBC_2.2.5) [SUSv2]	chdir(GLIBC_2.2.5) [SUSv3]	chmod(GLIBC_2.2.5) [SUSv3]	chown(GLIBC_2.2.5) [SUSv3]

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

chroot(GLIBC_2.2.5) [SUSv2]	clock(GLIBC_2.2.5) [SUSv3]	close(GLIBC_2.2.5) [SUSv3]	closedir(GLIBC_2.2.5) [SUSv3]
creat(GLIBC_2.2.5) [SUSv3]	dup(GLIBC_2.2.5) [SUSv3]	dup2(GLIBC_2.2.5) [SUSv3]	execl(GLIBC_2.2.5) [SUSv3]
execle(GLIBC_2.2.5) [SUSv3]	execlp(GLIBC_2.2.5) [SUSv3]	execv(GLIBC_2.2.5) [SUSv3]	execve(GLIBC_2.2.5) [SUSv3]
execvp(GLIBC_2.2.5) [SUSv3]	exit(GLIBC_2.2.5) [SUSv3]	fchdir(GLIBC_2.2.5) [SUSv3]	fchmod(GLIBC_2.2.5) [SUSv3]
fchown(GLIBC_2.2.5) [SUSv3]	fcntl(GLIBC_2.2.5) [LSB]	fdatasync(GLIBC_2.2.5) [SUSv3]	flock(GLIBC_2.2.5) [LSB]
fork(GLIBC_2.2.5) [SUSv3]	fstatvfs(GLIBC_2.2.5) [SUSv3]	fsync(GLIBC_2.2.5) [SUSv3]	ftime(GLIBC_2.2.5) [SUSv3]
ftruncate(GLIBC_2.2.5) [SUSv3]	getcontext(GLIBC_2.2.5) [SUSv3]	getegid(GLIBC_2.2.5) [SUSv3]	geteuid(GLIBC_2.2.5) [SUSv3]
getgid(GLIBC_2.2.5) [SUSv3]	getgroups(GLIBC_2.2.5) [SUSv3]	getitimer(GLIBC_2.2.5) [SUSv3]	getloadavg(GLIBC_2.2.5) [LSB]
getpagesize(GLIBC_2.2.5) [SUSv2]	getpgid(GLIBC_2.2.5) [SUSv3]	getpgrp(GLIBC_2.2.5) [SUSv3]	getpid(GLIBC_2.2.5) [SUSv3]
getppid(GLIBC_2.2.5) [SUSv3]	getpriority(GLIBC_2.2.5) [SUSv3]	getrlimit(GLIBC_2.2.5) [SUSv3]	getrusage(GLIBC_2.2.5) [SUSv3]
getsid(GLIBC_2.2.5) [SUSv3]	getuid(GLIBC_2.2.5) [SUSv3]	getwd(GLIBC_2.2.5) [SUSv3]	initgroups(GLIBC_2.2.5) [LSB]
ioctl(GLIBC_2.2.5) [LSB]	kill(GLIBC_2.2.5) [LSB]	killpg(GLIBC_2.2.5) [SUSv3]	lchown(GLIBC_2.2.5) [SUSv3]
link(GLIBC_2.2.5) [LSB]	lockf(GLIBC_2.2.5) [SUSv3]	lseek(GLIBC_2.2.5) [SUSv3]	mkdir(GLIBC_2.2.5) [SUSv3]
mkfifo(GLIBC_2.2.5) [SUSv3]	mlock(GLIBC_2.2.5) [SUSv3]	mlockall(GLIBC_2.2.5) [SUSv3]	mmap(GLIBC_2.2.5) [SUSv3]
mprotect(GLIBC_2.2.5) [SUSv3]	msync(GLIBC_2.2.5) [SUSv3]	munlock(GLIBC_2.2.5) [SUSv3]	munlockall(GLIBC_2.2.5) [SUSv3]
munmap(GLIBC_2.2.5) [SUSv3]	nanosleep(GLIBC_2.2.5) [SUSv3]	nice(GLIBC_2.2.5) [SUSv3]	open(GLIBC_2.2.5) [SUSv3]
opendir(GLIBC_2.2.5) [SUSv3]	pathconf(GLIBC_2.2.5) [SUSv3]	pause(GLIBC_2.2.5) [SUSv3]	pipe(GLIBC_2.2.5) [SUSv3]
poll(GLIBC_2.2.5) [SUSv3]	read(GLIBC_2.2.5) [SUSv3]	readdir(GLIBC_2.2.5) [SUSv3]	readdir_r(GLIBC_2.2.5) [SUSv3]
readlink(GLIBC_2.2.5) [SUSv3]	readv(GLIBC_2.2.5) [SUSv3]	rename(GLIBC_2.2.5) [SUSv3]	rmdir(GLIBC_2.2.5) [SUSv3]
sbrk(GLIBC_2.2.5) [SUSv2]	sched_get_priority_max(GLIBC_2.2.5) [SUSv3]	sched_get_priority_min(GLIBC_2.2.5) [SUSv3]	sched_getparam(GLIBC_2.2.5) [SUSv3]
sched_getschedu	sched_rr_get_int	sched_setparam(	sched_setschedul

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

ler(GLIBC_2.2.5) [SUSv3]	erval(GLIBC_2.2.5) [SUSv3]	GLIBC_2.2.5) [SUSv3]	er(GLIBC_2.2.5) [SUSv3]
sched_yield(GLIBC_2.2.5) [SUSv3]	select(GLIBC_2.2.5) [SUSv3]	setcontext(GLIBC_2.2.5) [SUSv3]	setegid(GLIBC_2.2.5) [SUSv3]
seteuid(GLIBC_2.2.5) [SUSv3]	setgid(GLIBC_2.2.5) [SUSv3]	setitimer(GLIBC_2.2.5) [SUSv3]	setpgid(GLIBC_2.2.5) [SUSv3]
setpgrp(GLIBC_2.2.5) [SUSv3]	setpriority(GLIBC_2.2.5) [SUSv3]	setregid(GLIBC_2.2.5) [SUSv3]	setreuid(GLIBC_2.2.5) [SUSv3]
setrlimit(GLIBC_2.2.5) [SUSv3]	setrlimit64(GLIBC_2.2.5) [LFS]	setsid(GLIBC_2.2.5) [SUSv3]	setuid(GLIBC_2.2.5) [SUSv3]
sleep(GLIBC_2.2.5) [SUSv3]	statvfs(GLIBC_2.2.5) [SUSv3]	stime(GLIBC_2.2.5) [LSB]	symlink(GLIBC_2.2.5) [SUSv3]
sync(GLIBC_2.2.5) [SUSv3]	sysconf(GLIBC_2.2.5) [SUSv3]	time(GLIBC_2.2.5) [SUSv3]	times(GLIBC_2.2.5) [SUSv3]
truncate(GLIBC_2.2.5) [SUSv3]	ulimit(GLIBC_2.2.5) [SUSv3]	umask(GLIBC_2.2.5) [SUSv3]	uname(GLIBC_2.2.5) [SUSv3]
unlink(GLIBC_2.2.5) [LSB]	utime(GLIBC_2.2.5) [SUSv3]	utimes(GLIBC_2.2.5) [SUSv3]	vfork(GLIBC_2.2.5) [SUSv3]
wait(GLIBC_2.2.5) [SUSv3]	wait4(GLIBC_2.2.5) [LSB]	waitpid(GLIBC_2.2.5) [LSB]	write(GLIBC_2.2.5) [SUSv3]
writev(GLIBC_2.2.5) [SUSv3]			

11.2.3 Standard I/O

11.2.3.1 Interfaces for Standard I/O

An LSB conforming implementation shall provide the architecture specific functions for Standard I/O specified in Table 11-4, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-4 libc - Standard I/O Function Interfaces

_IO_feof(GLIBC_2.2.5) [LSB]	_IO_getc(GLIBC_2.2.5) [LSB]	_IO_putc(GLIBC_2.2.5) [LSB]	_IO_puts(GLIBC_2.2.5) [LSB]
asprintf(GLIBC_2.2.5) [LSB]	clearerr(GLIBC_2.2.5) [SUSv3]	ctermid(GLIBC_2.2.5) [SUSv3]	fclose(GLIBC_2.2.5) [SUSv3]
fdopen(GLIBC_2.2.5) [SUSv3]	feof(GLIBC_2.2.5) [SUSv3]	ferror(GLIBC_2.2.5) [SUSv3]	fflush(GLIBC_2.2.5) [SUSv3]
fflush_unlocked(GLIBC_2.2.5) [LSB]	fgetc(GLIBC_2.2.5) [SUSv3]	fgetpos(GLIBC_2.2.5) [SUSv3]	fgets(GLIBC_2.2.5) [SUSv3]
fgetwc_unlocked(GLIBC_2.2.5) [LSB]	fileno(GLIBC_2.2.5) [SUSv3]	flockfile(GLIBC_2.2.5) [SUSv3]	fopen(GLIBC_2.2.5) [SUSv3]
fprintf(GLIBC_2.	fputc(GLIBC_2.2.	fputs(GLIBC_2.2.	fread(GLIBC_2.2.

© 2006 ISO/IEC — All rights reserved

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

2.5) [SUSv3]	5) [SUSv3]	5) [SUSv3]	5) [SUSv3]
freopen(GLIBC_2.2.5) [SUSv3]	fscanf(GLIBC_2.2.5) [LSB]	fseek(GLIBC_2.2.5) [SUSv3]	fseeko(GLIBC_2.2.5) [SUSv3]
fsetpos(GLIBC_2.2.5) [SUSv3]	ftell(GLIBC_2.2.5) [SUSv3]	ftello(GLIBC_2.2.5) [SUSv3]	fwrite(GLIBC_2.2.5) [SUSv3]
getc(GLIBC_2.2.5) [SUSv3]	getc_unlocked(GLIBC_2.2.5) [SUSv3]	getchar(GLIBC_2.2.5) [SUSv3]	getchar_unlocked(GLIBC_2.2.5) [SUSv3]
getw(GLIBC_2.2.5) [SUSv2]	pclose(GLIBC_2.2.5) [SUSv3]	popen(GLIBC_2.2.5) [SUSv3]	printf(GLIBC_2.2.5) [SUSv3]
putc(GLIBC_2.2.5) [SUSv3]	putc_unlocked(GLIBC_2.2.5) [SUSv3]	putchar(GLIBC_2.2.5) [SUSv3]	putchar_unlocked(GLIBC_2.2.5) [SUSv3]
puts(GLIBC_2.2.5) [SUSv3]	putw(GLIBC_2.2.5) [SUSv2]	remove(GLIBC_2.2.5) [SUSv3]	rewind(GLIBC_2.2.5) [SUSv3]
rewinddir(GLIBC_2.2.5) [SUSv3]	scanf(GLIBC_2.2.5) [LSB]	seekdir(GLIBC_2.2.5) [SUSv3]	setbuf(GLIBC_2.2.5) [SUSv3]
setbuffer(GLIBC_2.2.5) [LSB]	setvbuf(GLIBC_2.2.5) [SUSv3]	snprintf(GLIBC_2.2.5) [SUSv3]	sprintf(GLIBC_2.2.5) [SUSv3]
sscanf(GLIBC_2.2.5) [LSB]	telldir(GLIBC_2.2.5) [SUSv3]	tempnam(GLIBC_2.2.5) [SUSv3]	ungetc(GLIBC_2.2.5) [SUSv3]
vasprintf(GLIBC_2.2.5) [LSB]	vdprintf(GLIBC_2.2.5) [LSB]	vfprintf(GLIBC_2.2.5) [SUSv3]	vprintf(GLIBC_2.2.5) [SUSv3]
vsnprintf(GLIBC_2.2.5) [SUSv3]	vsprintf(GLIBC_2.2.5) [SUSv3]		

An LSB conforming implementation shall provide the architecture specific data interfaces for Standard I/O specified in Table 11-5, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-5 libc - Standard I/O Data Interfaces

stderr(GLIBC_2.2.5) [SUSv3]	stdin(GLIBC_2.2.5) [SUSv3]	stdout(GLIBC_2.2.5) [SUSv3]	

11.2.4 Signal Handling

11.2.4.1 Interfaces for Signal Handling

An LSB conforming implementation shall provide the architecture specific functions for Signal Handling specified in Table 11-6, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-6 libc - Signal Handling Function Interfaces

__libc_current_sigrtmax(GLIBC_2.2.5) [LSB]	__libc_current_sigrtmin(GLIBC_2.2.5) [LSB]	__sigsetjmp(GLIBC_2.2.5) [LSB]	__sysv_signal(GLIBC_2.2.5) [LSB]
bsd_signal(GLIB	psignal(GLIBC_2	raise(GLIBC_2.2.	sigaction(GLIBC

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

C_2.2.5) [SUSv3]	.2.5) [LSB]	5) [SUSv3]	_2.2.5) [SUSv3]
sigaddset(GLIBC_2.2.5) [SUSv3]	sigaltstack(GLIBC_2.2.5) [SUSv3]	sigandset(GLIBC_2.2.5) [LSB]	sigdelset(GLIBC_2.2.5) [SUSv3]
sigemptyset(GLIBC_2.2.5) [SUSv3]	sigfillset(GLIBC_2.2.5) [SUSv3]	sighold(GLIBC_2.2.5) [SUSv3]	sigignore(GLIBC_2.2.5) [SUSv3]
siginterrupt(GLIBC_2.2.5) [SUSv3]	sigisemptyset(GLIBC_2.2.5) [LSB]	sigismember(GLIBC_2.2.5) [SUSv3]	siglongjmp(GLIBC_2.2.5) [SUSv3]
signal(GLIBC_2.2.5) [SUSv3]	sigorset(GLIBC_2.2.5) [LSB]	sigpause(GLIBC_2.2.5) [SUSv3]	sigpending(GLIBC_2.2.5) [SUSv3]
sigprocmask(GLIBC_2.2.5) [SUSv3]	sigqueue(GLIBC_2.2.5) [SUSv3]	sigrelse(GLIBC_2.2.5) [SUSv3]	sigreturn(GLIBC_2.2.5) [LSB]
sigset(GLIBC_2.2.5) [SUSv3]	sigsuspend(GLIBC_2.2.5) [SUSv3]	sigtimedwait(GLIBC_2.2.5) [SUSv3]	sigwait(GLIBC_2.2.5) [SUSv3]
sigwaitinfo(GLIBC_2.2.5) [SUSv3]			

An LSB conforming implementation shall provide the architecture specific data interfaces for Signal Handling specified in Table 11-7, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-7 libc - Signal Handling Data Interfaces

_sys_siglist(GLIBC_2.3.3) [LSB]			

11.2.5 Localization Functions

11.2.5.1 Interfaces for Localization Functions

An LSB conforming implementation shall provide the architecture specific functions for Localization Functions specified in Table 11-8, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-8 libc - Localization Functions Function Interfaces

bind_textdomain_codeset(GLIBC_2.2.5) [LSB]	bindtextdomain(GLIBC_2.2.5) [LSB]	catclose(GLIBC_2.2.5) [SUSv3]	catgets(GLIBC_2.2.5) [SUSv3]
catopen(GLIBC_2.2.5) [SUSv3]	dcgettext(GLIBC_2.2.5) [LSB]	dcngettext(GLIBC_2.2.5) [LSB]	dgettext(GLIBC_2.2.5) [LSB]
dngettext(GLIBC_2.2.5) [LSB]	gettext(GLIBC_2.2.5) [LSB]	iconv(GLIBC_2.2.5) [SUSv3]	iconv_close(GLIBC_2.2.5) [SUSv3]
iconv_open(GLIBC_2.2.5) [SUSv3]	localeconv(GLIBC_2.2.5) [SUSv3]	ngettext(GLIBC_2.2.5) [LSB]	nl_langinfo(GLIBC_2.2.5) [SUSv3]

 © 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

setlocale(GLIBC_2.2.5) [SUSv3]	textdomain(GLIBC_2.2.5) [LSB]		

An LSB conforming implementation shall provide the architecture specific data interfaces for Localization Functions specified in Table 11-9, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-9 libc - Localization Functions Data Interfaces

_nl_msg_cat_cntr (GLIBC_2.2.5) [LSB]			

11.2.6 Socket Interface

11.2.6.1 Interfaces for Socket Interface

An LSB conforming implementation shall provide the architecture specific functions for Socket Interface specified in Table 11-10, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-10 libc - Socket Interface Function Interfaces

__h_errno_location(GLIBC_2.2.5) [LSB]	accept(GLIBC_2.2.5) [SUSv3]	bind(GLIBC_2.2.5) [SUSv3]	bindresvport(GLIBC_2.2.5) [LSB]
connect(GLIBC_2.2.5) [SUSv3]	gethostid(GLIBC_2.2.5) [SUSv3]	gethostname(GLIBC_2.2.5) [SUSv3]	getpeername(GLIBC_2.2.5) [SUSv3]
getsockname(GLIBC_2.2.5) [SUSv3]	getsockopt(GLIBC_2.2.5) [LSB]	if_freenameindex(GLIBC_2.2.5) [SUSv3]	if_indextoname(GLIBC_2.2.5) [SUSv3]
if_nameindex(GLIBC_2.2.5) [SUSv3]	if_nametoindex(GLIBC_2.2.5) [SUSv3]	listen(GLIBC_2.2.5) [SUSv3]	recv(GLIBC_2.2.5) [SUSv3]
recvfrom(GLIBC_2.2.5) [SUSv3]	recvmsg(GLIBC_2.2.5) [SUSv3]	send(GLIBC_2.2.5) [SUSv3]	sendmsg(GLIBC_2.2.5) [SUSv3]
sendto(GLIBC_2.2.5) [SUSv3]	setsockopt(GLIBC_2.2.5) [LSB]	shutdown(GLIBC_2.2.5) [SUSv3]	sockatmark(GLIBC_2.2.5) [SUSv3]
socket(GLIBC_2.2.5) [SUSv3]	socketpair(GLIBC_2.2.5) [SUSv3]		

11.2.7 Wide Characters

11.2.7.1 Interfaces for Wide Characters

An LSB conforming implementation shall provide the architecture specific functions for Wide Characters specified in Table 11-11, with the full mandatory functionality as described in the referenced underlying specification.

© 2006 ISO/IEC — All rights reserved

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Table 11-11 libc - Wide Characters Function Interfaces

__wcstod_internal(GLIBC_2.2.5) [LSB]	__wcstof_internal(GLIBC_2.2.5) [LSB]	__wcstol_internal(GLIBC_2.2.5) [LSB]	__wcstold_internal(GLIBC_2.2.5) [LSB]
__wcstoul_internal(GLIBC_2.2.5) [LSB]	btowc(GLIBC_2.2.5) [SUSv3]	fgetwc(GLIBC_2.2.5) [SUSv3]	fgetws(GLIBC_2.2.5) [SUSv3]
fputwc(GLIBC_2.2.5) [SUSv3]	fputws(GLIBC_2.2.5) [SUSv3]	fwide(GLIBC_2.2.5) [SUSv3]	fwprintf(GLIBC_2.2.5) [SUSv3]
fwscanf(GLIBC_2.2.5) [LSB]	getwc(GLIBC_2.2.5) [SUSv3]	getwchar(GLIBC_2.2.5) [SUSv3]	mblen(GLIBC_2.2.5) [SUSv3]
mbrlen(GLIBC_2.2.5) [SUSv3]	mbrtowc(GLIBC_2.2.5) [SUSv3]	mbsinit(GLIBC_2.2.5) [SUSv3]	mbsnrtowcs(GLIBC_2.2.5) [LSB]
mbsrtowcs(GLIBC_2.2.5) [SUSv3]	mbstowcs(GLIBC_2.2.5) [SUSv3]	mbtowc(GLIBC_2.2.5) [SUSv3]	putwc(GLIBC_2.2.5) [SUSv3]
putwchar(GLIBC_2.2.5) [SUSv3]	swprintf(GLIBC_2.2.5) [SUSv3]	swscanf(GLIBC_2.2.5) [LSB]	towctrans(GLIBC_2.2.5) [SUSv3]
towlower(GLIBC_2.2.5) [SUSv3]	towupper(GLIBC_2.2.5) [SUSv3]	ungetwc(GLIBC_2.2.5) [SUSv3]	vfwprintf(GLIBC_2.2.5) [SUSv3]
vfwscanf(GLIBC_2.2.5) [LSB]	vswprintf(GLIBC_2.2.5) [SUSv3]	vswscanf(GLIBC_2.2.5) [LSB]	vwprintf(GLIBC_2.2.5) [SUSv3]
vwscanf(GLIBC_2.2.5) [LSB]	wcpcpy(GLIBC_2.2.5) [LSB]	wcpncpy(GLIBC_2.2.5) [LSB]	wcrtomb(GLIBC_2.2.5) [SUSv3]
wcscasecmp(GLIBC_2.2.5) [LSB]	wcscat(GLIBC_2.2.5) [SUSv3]	wcschr(GLIBC_2.2.5) [SUSv3]	wcscmp(GLIBC_2.2.5) [SUSv3]
wcscoll(GLIBC_2.2.5) [SUSv3]	wcscpy(GLIBC_2.2.5) [SUSv3]	wcscspn(GLIBC_2.2.5) [SUSv3]	wcsdup(GLIBC_2.2.5) [LSB]
wcsftime(GLIBC_2.2.5) [SUSv3]	wcslen(GLIBC_2.2.5) [SUSv3]	wcsncasecmp(GLIBC_2.2.5) [LSB]	wcsncat(GLIBC_2.2.5) [SUSv3]
wcsncmp(GLIBC_2.2.5) [SUSv3]	wcsncpy(GLIBC_2.2.5) [SUSv3]	wcsnlen(GLIBC_2.2.5) [LSB]	wcsnrtombs(GLIBC_2.2.5) [LSB]
wcspbrk(GLIBC_2.2.5) [SUSv3]	wcsrchr(GLIBC_2.2.5) [SUSv3]	wcsrtombs(GLIBC_2.2.5) [SUSv3]	wcsspn(GLIBC_2.2.5) [SUSv3]
wcsstr(GLIBC_2.2.5) [SUSv3]	wcstod(GLIBC_2.2.5) [SUSv3]	wcstof(GLIBC_2.2.5) [SUSv3]	wcstoimax(GLIBC_2.2.5) [SUSv3]
wcstok(GLIBC_2.2.5) [SUSv3]	wcstol(GLIBC_2.2.5) [SUSv3]	wcstold(GLIBC_2.2.5) [SUSv3]	wcstoll(GLIBC_2.2.5) [SUSv3]
wcstombs(GLIBC_2.2.5) [SUSv3]	wcstoq(GLIBC_2.2.5) [LSB]	wcstoul(GLIBC_2.2.5) [SUSv3]	wcstoull(GLIBC_2.2.5) [SUSv3]
wcstoumax(GLIBC_2.2.5) [SUSv3]	wcstouq(GLIBC_2.2.5) [LSB]	wcswcs(GLIBC_2.2.5) [SUSv3]	wcswidth(GLIBC_2.2.5) [SUSv3]
wcsxfrm(GLIBC_2.2.5) [SUSv3]	wctob(GLIBC_2.2.5) [SUSv3]	wctomb(GLIBC_2.2.5) [SUSv3]	wctrans(GLIBC_2.2.5) [SUSv3]

© 2006 ISO/IEC — All rights reserved

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

wctype(GLIBC_2.2.5) [SUSv3]	wcwidth(GLIBC_2.2.5) [SUSv3]	wmemchr(GLIBC_2.2.5) [SUSv3]	wmemcmp(GLIBC_2.2.5) [SUSv3]
wmemcpy(GLIBC_2.2.5) [SUSv3]	wmemmove(GLIBC_2.2.5) [SUSv3]	wmemset(GLIBC_2.2.5) [SUSv3]	wprintf(GLIBC_2.2.5) [SUSv3]
wscanf(GLIBC_2.2.5) [LSB]			

11.2.8 String Functions

11.2.8.1 Interfaces for String Functions

An LSB conforming implementation shall provide the architecture specific functions for String Functions specified in Table 11-12, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-12 libc - String Functions Function Interfaces

__mempcpy(GLIBC_2.2.5) [LSB]	__rawmemchr(GLIBC_2.2.5) [LSB]	__stpcpy(GLIBC_2.2.5) [LSB]	__strdup(GLIBC_2.2.5) [LSB]
__strtod_internal(GLIBC_2.2.5) [LSB]	__strtof_internal(GLIBC_2.2.5) [LSB]	__strtok_r(GLIBC_2.2.5) [LSB]	__strtol_internal(GLIBC_2.2.5) [LSB]
__strtold_internal(GLIBC_2.2.5) [LSB]	__strtoll_internal(GLIBC_2.2.5) [LSB]	__strtoul_internal(GLIBC_2.2.5) [LSB]	__strtoull_internal(GLIBC_2.2.5) [LSB]
bcmp(GLIBC_2.2.5) [SUSv3]	bcopy(GLIBC_2.2.5) [SUSv3]	bzero(GLIBC_2.2.5) [SUSv3]	ffs(GLIBC_2.2.5) [SUSv3]
index(GLIBC_2.2.5) [SUSv3]	memccpy(GLIBC_2.2.5) [SUSv3]	memchr(GLIBC_2.2.5) [SUSv3]	memcmp(GLIBC_2.2.5) [SUSv3]
memcpy(GLIBC_2.2.5) [SUSv3]	memmove(GLIBC_2.2.5) [SUSv3]	memrchr(GLIBC_2.2.5) [LSB]	memset(GLIBC_2.2.5) [SUSv3]
rindex(GLIBC_2.2.5) [SUSv3]	stpcpy(GLIBC_2.2.5) [LSB]	stpncpy(GLIBC_2.2.5) [LSB]	strcasecmp(GLIBC_2.2.5) [SUSv3]
strcasestr(GLIBC_2.2.5) [LSB]	strcat(GLIBC_2.2.5) [SUSv3]	strchr(GLIBC_2.2.5) [SUSv3]	strcmp(GLIBC_2.2.5) [SUSv3]
strcoll(GLIBC_2.2.5) [SUSv3]	strcpy(GLIBC_2.2.5) [SUSv3]	strcspn(GLIBC_2.2.5) [SUSv3]	strdup(GLIBC_2.2.5) [SUSv3]
strerror(GLIBC_2.2.5) [SUSv3]	strerror_r(GLIBC_2.2.5) [LSB]	strfmon(GLIBC_2.2.5) [SUSv3]	strftime(GLIBC_2.2.5) [SUSv3]
strlen(GLIBC_2.2.5) [SUSv3]	strncasecmp(GLIBC_2.2.5) [SUSv3]	strncat(GLIBC_2.2.5) [SUSv3]	strncmp(GLIBC_2.2.5) [SUSv3]
strncpy(GLIBC_2.2.5) [SUSv3]	strndup(GLIBC_2.2.5) [LSB]	strnlen(GLIBC_2.2.5) [LSB]	strpbrk(GLIBC_2.2.5) [SUSv3]
strptime(GLIBC_2.2.5) [LSB]	strrchr(GLIBC_2.2.5) [SUSv3]	strsep(GLIBC_2.2.5) [LSB]	strsignal(GLIBC_2.2.5) [LSB]

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

strspn(GLIBC_2.2.5) [SUSv3]	strstr(GLIBC_2.2.5) [SUSv3]	strtof(GLIBC_2.2.5) [SUSv3]	strtoimax(GLIBC_2.2.5) [SUSv3]
strtok(GLIBC_2.2.5) [SUSv3]	strtok_r(GLIBC_2.2.5) [SUSv3]	strtold(GLIBC_2.2.5) [SUSv3]	strtoll(GLIBC_2.2.5) [SUSv3]
strtoq(GLIBC_2.2.5) [LSB]	strtoull(GLIBC_2.2.5) [SUSv3]	strtoumax(GLIBC_2.2.5) [SUSv3]	strtouq(GLIBC_2.2.5) [LSB]
strxfrm(GLIBC_2.2.5) [SUSv3]	swab(GLIBC_2.2.5) [SUSv3]		

11.2.9 IPC Functions

11.2.9.1 Interfaces for IPC Functions

An LSB conforming implementation shall provide the architecture specific functions for IPC Functions specified in Table 11-13, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-13 libc - IPC Functions Function Interfaces

ftok(GLIBC_2.2.5) [SUSv3]	msgctl(GLIBC_2.2.5) [SUSv3]	msgget(GLIBC_2.2.5) [SUSv3]	msgrcv(GLIBC_2.2.5) [SUSv3]
msgsnd(GLIBC_2.2.5) [SUSv3]	semctl(GLIBC_2.2.5) [SUSv3]	semget(GLIBC_2.2.5) [SUSv3]	semop(GLIBC_2.2.5) [SUSv3]
shmat(GLIBC_2.2.5) [SUSv3]	shmctl(GLIBC_2.2.5) [SUSv3]	shmdt(GLIBC_2.2.5) [SUSv3]	shmget(GLIBC_2.2.5) [SUSv3]

11.2.10 Regular Expressions

11.2.10.1 Interfaces for Regular Expressions

An LSB conforming implementation shall provide the architecture specific functions for Regular Expressions specified in Table 11-14, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-14 libc - Regular Expressions Function Interfaces

regcomp(GLIBC_2.2.5) [SUSv3]	regerror(GLIBC_2.2.5) [SUSv3]	regexec(GLIBC_2.3.4) [LSB]	regfree(GLIBC_2.2.5) [SUSv3]

11.2.11 Character Type Functions

11.2.11.1 Interfaces for Character Type Functions

An LSB conforming implementation shall provide the architecture specific functions for Character Type Functions specified in Table 11-15, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-15 libc - Character Type Functions Function Interfaces

__ctype_get_mb_cur_max(GLIBC_2.2.5) [LSB]	_tolower(GLIBC_2.2.5) [SUSv3]	_toupper(GLIBC_2.2.5) [SUSv3]	isalnum(GLIBC_2.2.5) [SUSv3]
isalpha(GLIBC_2	isascii(GLIBC_2.2	iscntrl(GLIBC_2.	isdigit(GLIBC_2.

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

.2.5) [SUSv3]	.5) [SUSv3]	2.5) [SUSv3]	2.5) [SUSv3]
isgraph(GLIBC_2 .2.5) [SUSv3]	islower(GLIBC_2 .2.5) [SUSv3]	isprint(GLIBC_2. 2.5) [SUSv3]	ispunct(GLIBC_2 .2.5) [SUSv3]
isspace(GLIBC_2. 2.5) [SUSv3]	isupper(GLIBC_2 .2.5) [SUSv3]	iswalnum(GLIBC _2.2.5) [SUSv3]	iswalpha(GLIBC _2.2.5) [SUSv3]
iswblank(GLIBC _2.2.5) [SUSv3]	iswcntrl(GLIBC_ 2.2.5) [SUSv3]	iswctype(GLIBC _2.2.5) [SUSv3]	iswdigit(GLIBC_ 2.2.5) [SUSv3]
iswgraph(GLIBC _2.2.5) [SUSv3]	iswlower(GLIBC _2.2.5) [SUSv3]	iswprint(GLIBC_ 2.2.5) [SUSv3]	iswpunct(GLIBC _2.2.5) [SUSv3]
iswspace(GLIBC _2.2.5) [SUSv3]	iswupper(GLIBC _2.2.5) [SUSv3]	iswxdigit(GLIBC _2.2.5) [SUSv3]	isxdigit(GLIBC_2 .2.5) [SUSv3]
toascii(GLIBC_2. 2.5) [SUSv3]	tolower(GLIBC_ 2.2.5) [SUSv3]	toupper(GLIBC_ 2.2.5) [SUSv3]	

11.2.12 Time Manipulation

11.2.12.1 Interfaces for Time Manipulation

An LSB conforming implementation shall provide the architecture specific functions for Time Manipulation specified in Table 11-16, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-16 libc - Time Manipulation Function Interfaces

adjtime(GLIBC_2 .2.5) [LSB]	asctime(GLIBC_2 .2.5) [SUSv3]	asctime_r(GLIBC _2.2.5) [SUSv3]	ctime(GLIBC_2.2 .5) [SUSv3]
ctime_r(GLIBC_2 .2.5) [SUSv3]	difftime(GLIBC_ 2.2.5) [SUSv3]	gmtime(GLIBC_ 2.2.5) [SUSv3]	gmtime_r(GLIBC _2.2.5) [SUSv3]
localtime(GLIBC _2.2.5) [SUSv3]	localtime_r(GLIB C_2.2.5) [SUSv3]	mktime(GLIBC_ 2.2.5) [SUSv3]	tzset(GLIBC_2.2. 5) [SUSv3]
ualarm(GLIBC_2 .2.5) [SUSv3]			

An LSB conforming implementation shall provide the architecture specific data interfaces for Time Manipulation specified in Table 11-17, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-17 libc - Time Manipulation Data Interfaces

__daylight(GLIB C_2.2.5) [LSB]	__timezone(GLIB C_2.2.5) [LSB]	__tzname(GLIBC _2.2.5) [LSB]	daylight(GLIBC_ 2.2.5) [SUSv3]
timezone(GLIBC _2.2.5) [SUSv3]	tzname(GLIBC_2 .2.5) [SUSv3]		

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

11.2.13 Terminal Interface Functions

11.2.13.1 Interfaces for Terminal Interface Functions

An LSB conforming implementation shall provide the architecture specific functions for Terminal Interface Functions specified in Table 11-18, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-18 libc - Terminal Interface Functions Function Interfaces

cfgetispeed(GLIBC_2.2.5) [SUSv3]	cfgetospeed(GLIBC_2.2.5) [SUSv3]	cfmakeraw(GLIBC_2.2.5) [LSB]	cfsetispeed(GLIBC_2.2.5) [SUSv3]
cfsetospeed(GLIBC_2.2.5) [SUSv3]	cfsetspeed(GLIBC_2.2.5) [LSB]	tcdrain(GLIBC_2.2.5) [SUSv3]	tcflow(GLIBC_2.2.5) [SUSv3]
tcflush(GLIBC_2.2.5) [SUSv3]	tcgetattr(GLIBC_2.2.5) [SUSv3]	tcgetpgrp(GLIBC_2.2.5) [SUSv3]	tcgetsid(GLIBC_2.2.5) [SUSv3]
tcsendbreak(GLIBC_2.2.5) [SUSv3]	tcsetattr(GLIBC_2.2.5) [SUSv3]	tcsetpgrp(GLIBC_2.2.5) [SUSv3]	

11.2.14 System Database Interface

11.2.14.1 Interfaces for System Database Interface

An LSB conforming implementation shall provide the architecture specific functions for System Database Interface specified in Table 11-19, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-19 libc - System Database Interface Function Interfaces

endgrent(GLIBC_2.2.5) [SUSv3]	endprotoent(GLIBC_2.2.5) [SUSv3]	endpwent(GLIBC_2.2.5) [SUSv3]	endservent(GLIBC_2.2.5) [SUSv3]
endutent(GLIBC_2.2.5) [LSB]	endutxent(GLIBC_2.2.5) [SUSv3]	getgrent(GLIBC_2.2.5) [SUSv3]	getgrgid(GLIBC_2.2.5) [SUSv3]
getgrgid_r(GLIBC_2.2.5) [SUSv3]	getgrnam(GLIBC_2.2.5) [SUSv3]	getgrnam_r(GLIBC_2.2.5) [SUSv3]	getgrouplist(GLIBC_2.2.5) [LSB]
gethostbyaddr(GLIBC_2.2.5) [SUSv3]	gethostbyname(GLIBC_2.2.5) [SUSv3]	getprotobyname(GLIBC_2.2.5) [SUSv3]	getprotobynumber(GLIBC_2.2.5) [SUSv3]
getprotoent(GLIBC_2.2.5) [SUSv3]	getpwent(GLIBC_2.2.5) [SUSv3]	getpwnam(GLIBC_2.2.5) [SUSv3]	getpwnam_r(GLIBC_2.2.5) [SUSv3]
getpwuid(GLIBC_2.2.5) [SUSv3]	getpwuid_r(GLIBC_2.2.5) [SUSv3]	getservbyname(GLIBC_2.2.5) [SUSv3]	getservbyport(GLIBC_2.2.5) [SUSv3]
getservent(GLIBC_2.2.5) [SUSv3]	getutent(GLIBC_2.2.5) [LSB]	getutent_r(GLIBC_2.2.5) [LSB]	getutxent(GLIBC_2.2.5) [SUSv3]

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

getutxid(GLIBC_2.2.5) [SUSv3]	getutxline(GLIBC_2.2.5) [SUSv3]	pututxline(GLIBC_2.2.5) [SUSv3]	setgrent(GLIBC_2.2.5) [SUSv3]
setgroups(GLIBC_2.2.5) [LSB]	setprotoent(GLIBC_2.2.5) [SUSv3]	setpwent(GLIBC_2.2.5) [SUSv3]	setservent(GLIBC_2.2.5) [SUSv3]
setutent(GLIBC_2.2.5) [LSB]	setutxent(GLIBC_2.2.5) [SUSv3]	utmpname(GLIBC_2.2.5) [LSB]	

11.2.15 Language Support

11.2.15.1 Interfaces for Language Support

An LSB conforming implementation shall provide the architecture specific functions for Language Support specified in Table 11-20, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-20 libc - Language Support Function Interfaces

__libc_start_main(GLIBC_2.2.5) [LSB]			

11.2.16 Large File Support

11.2.16.1 Interfaces for Large File Support

An LSB conforming implementation shall provide the architecture specific functions for Large File Support specified in Table 11-21, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-21 libc - Large File Support Function Interfaces

__fxstat64(GLIBC_2.2.5) [LSB]	__lxstat64(GLIBC_2.2.5) [LSB]	__xstat64(GLIBC_2.2.5) [LSB]	creat64(GLIBC_2.2.5) [LFS]
fgetpos64(GLIBC_2.2.5) [LFS]	fopen64(GLIBC_2.2.5) [LFS]	freopen64(GLIBC_2.2.5) [LFS]	fseeko64(GLIBC_2.2.5) [LFS]
fsetpos64(GLIBC_2.2.5) [LFS]	fstatvfs64(GLIBC_2.2.5) [LFS]	ftello64(GLIBC_2.2.5) [LFS]	ftruncate64(GLIBC_2.2.5) [LFS]
ftw64(GLIBC_2.2.5) [LFS]	getrlimit64(GLIBC_2.2.5) [LFS]	lockf64(GLIBC_2.2.5) [LFS]	mkstemp64(GLIBC_2.2.5) [LFS]
mmap64(GLIBC_2.2.5) [LFS]	nftw64(GLIBC_2.3.3) [LFS]	readdir64(GLIBC_2.2.5) [LFS]	statvfs64(GLIBC_2.2.5) [LFS]
tmpfile64(GLIBC_2.2.5) [LFS]	truncate64(GLIBC_2.2.5) [LFS]		

11.2.17 Standard Library

11.2.17.1 Interfaces for Standard Library

An LSB conforming implementation shall provide the architecture specific functions for Standard Library specified in Table 11-22, with the full mandatory functionality as described in the referenced underlying specification.

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Table 11-22 libc - Standard Library Function Interfaces

_Exit(GLIBC_2.2.5) [SUSv3]	__assert_fail(GLIBC_2.2.5) [LSB]	__cxa_atexit(GLIBC_2.2.5) [LSB]	__errno_location(GLIBC_2.2.5) [LSB]
__fpending(GLIBC_2.2.5) [LSB]	__getpagesize(GLIBC_2.2.5) [LSB]	__isinf(GLIBC_2.2.5) [LSB]	__isinff(GLIBC_2.2.5) [LSB]
__isinfl(GLIBC_2.2.5) [LSB]	__isnan(GLIBC_2.2.5) [LSB]	__isnanf(GLIBC_2.2.5) [LSB]	__isnanl(GLIBC_2.2.5) [LSB]
__sysconf(GLIBC_2.2.5) [LSB]	_exit(GLIBC_2.2.5) [SUSv3]	_longjmp(GLIBC_2.2.5) [SUSv3]	_setjmp(GLIBC_2.2.5) [SUSv3]
a64l(GLIBC_2.2.5) [SUSv3]	abort(GLIBC_2.2.5) [SUSv3]	abs(GLIBC_2.2.5) [SUSv3]	atof(GLIBC_2.2.5) [SUSv3]
atoi(GLIBC_2.2.5) [SUSv3]	atol(GLIBC_2.2.5) [SUSv3]	atoll(GLIBC_2.2.5) [SUSv3]	basename(GLIBC_2.2.5) [SUSv3]
bsearch(GLIBC_2.2.5) [SUSv3]	calloc(GLIBC_2.2.5) [SUSv3]	closelog(GLIBC_2.2.5) [SUSv3]	confstr(GLIBC_2.2.5) [SUSv3]
cuserid(GLIBC_2.2.5) [SUSv2]	daemon(GLIBC_2.2.5) [LSB]	dirname(GLIBC_2.2.5) [SUSv3]	div(GLIBC_2.2.5) [SUSv3]
drand48(GLIBC_2.2.5) [SUSv3]	ecvt(GLIBC_2.2.5) [SUSv3]	erand48(GLIBC_2.2.5) [SUSv3]	err(GLIBC_2.2.5) [LSB]
error(GLIBC_2.2.5) [LSB]	errx(GLIBC_2.2.5) [LSB]	fcvt(GLIBC_2.2.5) [SUSv3]	fmtmsg(GLIBC_2.2.5) [SUSv3]
fnmatch(GLIBC_2.2.5) [SUSv3]	fpathconf(GLIBC_2.2.5) [SUSv3]	free(GLIBC_2.2.5) [SUSv3]	freeaddrinfo(GLIBC_2.2.5) [SUSv3]
ftrylockfile(GLIBC_2.2.5) [SUSv3]	ftw(GLIBC_2.2.5) [SUSv3]	funlockfile(GLIBC_2.2.5) [SUSv3]	gai_strerror(GLIBC_2.2.5) [SUSv3]
gcvt(GLIBC_2.2.5) [SUSv3]	getaddrinfo(GLIBC_2.2.5) [SUSv3]	getcwd(GLIBC_2.2.5) [SUSv3]	getdate(GLIBC_2.2.5) [SUSv3]
getenv(GLIBC_2.2.5) [SUSv3]	getlogin(GLIBC_2.2.5) [SUSv3]	getlogin_r(GLIBC_2.2.5) [SUSv3]	getnameinfo(GLIBC_2.2.5) [SUSv3]
getopt(GLIBC_2.2.5) [LSB]	getopt_long(GLIBC_2.2.5) [LSB]	getopt_long_only(GLIBC_2.2.5) [LSB]	getsubopt(GLIBC_2.2.5) [SUSv3]
gettimeofday(GLIBC_2.2.5) [SUSv3]	glob(GLIBC_2.2.5) [SUSv3]	glob64(GLIBC_2.2.5) [LSB]	globfree(GLIBC_2.2.5) [SUSv3]
globfree64(GLIBC_2.2.5) [LSB]	grantpt(GLIBC_2.2.5) [SUSv3]	hcreate(GLIBC_2.2.5) [SUSv3]	hdestroy(GLIBC_2.2.5) [SUSv3]
hsearch(GLIBC_2.2.5) [SUSv3]	htonl(GLIBC_2.2.5) [SUSv3]	htons(GLIBC_2.2.5) [SUSv3]	imaxabs(GLIBC_2.2.5) [SUSv3]

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

imaxdiv(GLIBC_2.2.5) [SUSv3]	inet_addr(GLIBC_2.2.5) [SUSv3]	inet_ntoa(GLIBC_2.2.5) [SUSv3]	inet_ntop(GLIBC_2.2.5) [SUSv3]
inet_pton(GLIBC_2.2.5) [SUSv3]	initstate(GLIBC_2.2.5) [SUSv3]	insque(GLIBC_2.2.5) [SUSv3]	isatty(GLIBC_2.2.5) [SUSv3]
isblank(GLIBC_2.2.5) [SUSv3]	jrand48(GLIBC_2.2.5) [SUSv3]	l64a(GLIBC_2.2.5) [SUSv3]	labs(GLIBC_2.2.5) [SUSv3]
lcong48(GLIBC_2.2.5) [SUSv3]	ldiv(GLIBC_2.2.5) [SUSv3]	lfind(GLIBC_2.2.5) [SUSv3]	llabs(GLIBC_2.2.5) [SUSv3]
lldiv(GLIBC_2.2.5) [SUSv3]	longjmp(GLIBC_2.2.5) [SUSv3]	lrand48(GLIBC_2.2.5) [SUSv3]	lsearch(GLIBC_2.2.5) [SUSv3]
makecontext(GLIBC_2.2.5) [SUSv3]	malloc(GLIBC_2.2.5) [SUSv3]	memmem(GLIBC_2.2.5) [LSB]	mkstemp(GLIBC_2.2.5) [SUSv3]
mktemp(GLIBC_2.2.5) [SUSv3]	mrand48(GLIBC_2.2.5) [SUSv3]	nftw(GLIBC_2.3.3) [SUSv3]	nrand48(GLIBC_2.2.5) [SUSv3]
ntohl(GLIBC_2.2.5) [SUSv3]	ntohs(GLIBC_2.2.5) [SUSv3]	openlog(GLIBC_2.2.5) [SUSv3]	perror(GLIBC_2.2.5) [SUSv3]
posix_memalign(GLIBC_2.2.5) [SUSv3]	posix_openpt(GLIBC_2.2.5) [SUSv3]	ptsname(GLIBC_2.2.5) [SUSv3]	putenv(GLIBC_2.2.5) [SUSv3]
qsort(GLIBC_2.2.5) [SUSv3]	rand(GLIBC_2.2.5) [SUSv3]	rand_r(GLIBC_2.2.5) [SUSv3]	random(GLIBC_2.2.5) [SUSv3]
realloc(GLIBC_2.2.5) [SUSv3]	realpath(GLIBC_2.3) [SUSv3]	remque(GLIBC_2.2.5) [SUSv3]	seed48(GLIBC_2.2.5) [SUSv3]
setenv(GLIBC_2.2.5) [SUSv3]	sethostname(GLIBC_2.2.5) [LSB]	setlogmask(GLIBC_2.2.5) [SUSv3]	setstate(GLIBC_2.2.5) [SUSv3]
srand(GLIBC_2.2.5) [SUSv3]	srand48(GLIBC_2.2.5) [SUSv3]	srandom(GLIBC_2.2.5) [SUSv3]	strtod(GLIBC_2.2.5) [SUSv3]
strtol(GLIBC_2.2.5) [SUSv3]	strtoul(GLIBC_2.2.5) [SUSv3]	swapcontext(GLIBC_2.2.5) [SUSv3]	syslog(GLIBC_2.2.5) [SUSv3]
system(GLIBC_2.2.5) [LSB]	tdelete(GLIBC_2.2.5) [SUSv3]	tfind(GLIBC_2.2.5) [SUSv3]	tmpfile(GLIBC_2.2.5) [SUSv3]
tmpnam(GLIBC_2.2.5) [SUSv3]	tsearch(GLIBC_2.2.5) [SUSv3]	ttyname(GLIBC_2.2.5) [SUSv3]	ttyname_r(GLIBC_2.2.5) [SUSv3]
twalk(GLIBC_2.2.5) [SUSv3]	unlockpt(GLIBC_2.2.5) [SUSv3]	unsetenv(GLIBC_2.2.5) [SUSv3]	usleep(GLIBC_2.2.5) [SUSv3]
verrx(GLIBC_2.2.5) [LSB]	vfscanf(GLIBC_2.2.5) [LSB]	vscanf(GLIBC_2.2.5) [LSB]	vsscanf(GLIBC_2.2.5) [LSB]
vsyslog(GLIBC_2.2.5) [LSB]	warn(GLIBC_2.2.5) [LSB]	warnx(GLIBC_2.2.5) [LSB]	wordexp(GLIBC_2.2.5) [SUSv3]
wordfree(GLIBC_2.2.5) [SUSv3]			

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

An LSB conforming implementation shall provide the architecture specific data interfaces for Standard Library specified in Table 11-23, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-23 libc - Standard Library Data Interfaces

__environ(GLIBC_2.2.5) [LSB]	_environ(GLIBC_2.2.5) [LSB]	_sys_errlist(GLIBC_2.3) [LSB]	environ(GLIBC_2.2.5) [SUSv3]
getdate_err(GLIBC_2.2.5) [SUSv3]	optarg(GLIBC_2.2.5) [SUSv3]	opterr(GLIBC_2.2.5) [SUSv3]	optind(GLIBC_2.2.5) [SUSv3]
optopt(GLIBC_2.2.5) [SUSv3]			

11.3 Data Definitions for libc

This section defines global identifiers and their values that are associated with interfaces contained in libc. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

11.3.1 ctype.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.2 dirent.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.3 errno.h

```
#define EDEADLOCK       EDEADLK
```

11.3.4 fcntl.h

```
#define F_GETLK64       5
#define F_SETLK64       6
```


© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
#define F_SETLKW64      7
```

11.3.5 fnmatch.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.6 ftw.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.7 getopt.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.8 glob.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.9 iconv.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.10 inttypes.h

```
typedef long int intmax_t;
typedef unsigned long int uintptr_t;
typedef unsigned long int uintmax_t;
typedef unsigned long int uint64_t;
```

11.3.11 langinfo.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.12 limits.h

```
#define LONG_MAX        0x7FFFFFFFFFFFFFFFL
#define ULONG_MAX       0xFFFFFFFFFFFFFFFFUL
```

© 2006 ISO/IEC – All rights reserved

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
#define CHAR_MAX        127
#define CHAR_MIN        SCHAR_MIN

#define PTHREAD_STACK_MIN       16384
```

11.3.13 locale.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.14 net/if.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.15 netdb.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.16 netinet/in.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.17 netinet/ip.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.18 netinet/tcp.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.19 netinet/udp.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.20 nl_types.h

© 2006 ISO/IEC – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.21 pwd.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.22 regex.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.23 rpc/auth.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.24 rpc/clnt.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.25 rpc/rpc_msg.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.26 rpc/svc.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.27 rpc/types.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.28 rpc/xdr.h

© 2006 ISO/IEC – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.29 sched.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.30 search.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.31 setjmp.h

```
typedef long int __jmp_buf[8];
```

11.3.32 signal.h

```
#define SIGEV_PAD_SIZE  ((SIGEV_MAX_SIZE/sizeof(int))-4)

#define SI_PAD_SIZE     ((SI_MAX_SIZE/sizeof(int))-4)

struct sigaction {
    union {
        sighandler_t _sa_handler;
        void (*_sa_sigaction) (int, siginfo_t *, void *);
    } __sigaction_handler;
    sigset_t sa_mask;
    int sa_flags;
    void (*sa_restorer) (void);
};

#define MINSIGSTKSZ     2048
#define SIGSTKSZ        8192

struct _fpxreg {
    unsigned short significand[4];
    unsigned short exponent;
    unsigned short padding[3];
};
struct _xmmreg {
    uint32_t element[4];
};

struct _fpstate {
    uint16_t cwd;
    uint16_t swd;
    uint16_t ftw;
    uint16_t fop;
    uint64_t rip;
    uint64_t rdp;
    uint32_t mxcsr;
    uint32_t mxcr_mask;
    struct _fpxreg _st[8];
```

 © 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
    struct _xmmreg _xmm[16];
    uint32_t padding[24];
};

struct sigcontext {
    unsigned long int r8;
    unsigned long int r9;
    unsigned long int r10;
    unsigned long int r11;
    unsigned long int r12;
    unsigned long int r13;
    unsigned long int r14;
    unsigned long int r15;
    unsigned long int rdi;
    unsigned long int rsi;
    unsigned long int rbp;
    unsigned long int rbx;
    unsigned long int rdx;
    unsigned long int rax;
    unsigned long int rcx;
    unsigned long int rsp;
    unsigned long int rip;
    unsigned long int eflags;
    unsigned short cs;
    unsigned short gs;
    unsigned short fs;
    unsigned short __pad0;
    unsigned long int err;
    unsigned long int trapno;
    unsigned long int oldmask;
    unsigned long int cr2;
    struct _fpstate *fpstate;
    unsigned long int __reserved1[8];
};
```

11.3.33 stddef.h

```
typedef long int ptrdiff_t;
typedef unsigned long int size_t;
```

11.3.34 stdio.h

```
#define __IO_FILE_SIZE  216
```

11.3.35 stdlib.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.36 sys/file.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.37 sys/ioctl.h

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
#define TIOCGWINSZ      0x5413
#define FIONREAD        0x541B
#define TIOCNOTTY       21538
```

11.3.38 sys/ipc.h

```
struct ipc_perm {
    key_t __key;
    uid_t uid;
    gid_t gid;
    uid_t cuid;
    uid_t cgid;
    unsigned short mode;
    unsigned short __pad1;
    unsigned short __seq;
    unsigned short __pad2;
    unsigned long int __unused1;
    unsigned long int __unused2;
};
```

11.3.39 sys/mman.h

```
#define MCL_CURRENT     1
#define MCL_FUTURE      2
```

11.3.40 sys/msg.h

```
typedef unsigned long int msgqnum_t;
typedef unsigned long int msglen_t;

struct msqid_ds {
    struct ipc_perm msg_perm;
    time_t msg_stime;
    time_t msg_rtime;
    time_t msg_ctime;
    unsigned long int __msg_cbytes;
    msgqnum_t msg_qnum;
    msglen_t msg_qbytes;
    pid_t msg_lspid;
    pid_t msg_lrpid;
    unsigned long int __unused4;
    unsigned long int __unused5;
};
```

11.3.41 sys/param.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.42 sys/poll.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

 © 2006 ISO/IEC – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

11.3.43 sys/resource.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.44 sys/sem.h

```
struct semid_ds {
    struct ipc_perm sem_perm;
    time_t sem_otime;
    unsigned long int __unused1;
    time_t sem_ctime;
    unsigned long int __unused2;
    unsigned long int sem_nsems;
    unsigned long int __unused3;
    unsigned long int __unused4;
};
```

11.3.45 sys/shm.h

```
#define SHMLBA  (__getpagesize())

typedef unsigned long int shmatt_t;

struct shmid_ds {
    struct ipc_perm shm_perm;
    size_t shm_segsz;
    time_t shm_atime;
    time_t shm_dtime;
    time_t shm_ctime;
    pid_t shm_cpid;
    pid_t shm_lpid;
    shmatt_t shm_nattch;
    unsigned long int __unused4;
    unsigned long int __unused5;
};
```

11.3.46 sys/socket.h

```
typedef uint64_t __ss_aligntype;

#define SO_RCVLOWAT     18
#define SO_SNDLOWAT     19
#define SO_RCVTIMEO     20
#define SO_SNDTIMEO     21
```

11.3.47 sys/stat.h

```
#define _STAT_VER       1

struct stat {
    dev_t st_dev;
    ino_t st_ino;
    nlink_t st_nlink;
    mode_t st_mode;
    uid_t st_uid;
    gid_t st_gid;
    int pad0;
```

© 2006 ISO/IEC – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
    dev_t st_rdev;
    off_t st_size;
    blksize_t st_blksize;
    blkcnt_t st_blocks;
    struct timespec st_atim;
    struct timespec st_mtim;
    struct timespec st_ctim;
    unsigned long int __unused[3];
};
struct stat64 {
    dev_t st_dev;
    ino64_t st_ino;
    nlink_t st_nlink;
    mode_t st_mode;
    uid_t st_uid;
    gid_t st_gid;
    int pad0;
    dev_t st_rdev;
    off_t st_size;
    blksize_t st_blksize;
    blkcnt64_t st_blocks;
    struct timespec st_atim;
    struct timespec st_mtim;
    struct timespec st_ctim;
    unsigned long int __unused[3];
};
```

11.3.48 sys/statvfs.h

```
struct statvfs64 {
    unsigned long int f_bsize;
    unsigned long int f_frsize;
    fsblkcnt64_t f_blocks;
    fsblkcnt64_t f_bfree;
    fsblkcnt64_t f_bavail;
    fsfilcnt64_t f_files;
    fsfilcnt64_t f_ffree;
    fsfilcnt64_t f_favail;
    unsigned long int f_fsid;
    unsigned long int f_flag;
    unsigned long int f_namemax;
    int __f_spare[6];
};
struct statvfs {
    unsigned long int f_bsize;
    unsigned long int f_frsize;
    fsblkcnt_t f_blocks;
    fsblkcnt_t f_bfree;
    fsblkcnt_t f_bavail;
    fsfilcnt_t f_files;
    fsfilcnt_t f_ffree;
    fsfilcnt_t f_favail;
    unsigned long int f_fsid;
    unsigned long int f_flag;
    unsigned long int f_namemax;
    int __f_spare[6];
};
```

11.3.49 sys/time.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

 © 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

11.3.50 sys/timeb.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.51 sys/times.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.52 sys/types.h

```
typedef long int int64_t;

typedef int64_t ssize_t;

#define __FDSET_LONGS   16
```

11.3.53 sys/un.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.54 sys/utsname.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.55 sys/wait.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.56 syslog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.57 termios.h

```
#define OLCUC   0000002
#define ONLCR   0000004
#define XCASE   0000004
#define NLDLY   0000400
```

© 2006 ISO/IEC – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
#define CR1     0001000
#define IUCLC   0001000
#define CR2     0002000
#define CR3     0003000
#define CRDLY   0003000
#define TAB1    0004000
#define TAB2    0010000
#define TAB3    0014000
#define TABDLY  0014000
#define BS1     0020000
#define BSDLY   0020000
#define VT1     0040000
#define VTDLY   0040000
#define FF1     0100000
#define FFDLY   0100000

#define VSUSP   10
#define VEOL    11
#define VREPRINT        12
#define VDISCARD        13
#define VWERASE 14
#define VEOL2   16
#define VMIN    6
#define VSWTC   7
#define VSTART  8
#define VSTOP   9

#define IXON    0002000
#define IXOFF   0010000

#define CS6     0000020
#define CS7     0000040
#define CS8     0000060
#define CSIZE   0000060
#define CSTOPB  0000100
#define CREAD   0000200
#define PARENB  0000400
#define PARODD  0001000
#define HUPCL   0002000
#define CLOCAL  0004000
#define VTIME   5

#define ISIG    0000001
#define ICANON  0000002
#define ECHOE   0000020
#define ECHOK   0000040
#define ECHONL  0000100
#define NOFLSH  0000200
#define TOSTOP  0000400
#define ECHOCTL 0001000
#define ECHOPRT 0002000
#define ECHOKE  0004000
#define FLUSHO  0010000
#define PENDIN  0040000
#define IEXTEN  0100000
```

11.3.58 ucontext.h

```
struct _libc_fpxreg {
    unsigned short significand[4];
    unsigned short exponent;
    unsigned short padding[3];
};

typedef long int greg_t;
```

 © 2006 ISO/IEC — All rights reserved

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
#define NGREG   23

typedef greg_t gregset_t[23];

struct _libc_xmmreg {
    uint32_t element[4];
};
struct _libc_fpstate {
    uint16_t cwd;
    uint16_t swd;
    uint16_t ftw;
    uint16_t fop;
    uint64_t rip;
    uint64_t rdp;
    uint32_t mxcsr;
    uint32_t mxcr_mask;
    struct _libc_fpxreg _st[8];
    struct _libc_xmmreg _xmm[16];
    uint32_t padding[24];
};
typedef struct _libc_fpstate *fpregset_t;

typedef struct {
    gregset_t gregs;
    fpregset_t fpregs;
    unsigned long int __reserved1[8];
} mcontext_t;

typedef struct ucontext {
    unsigned long int uc_flags;
    struct ucontext *uc_link;
    stack_t uc_stack;
    mcontext_t uc_mcontext;
    sigset_t uc_sigmask;
    struct _libc_fpstate __fpregs_mem;
} ucontext_t;
```

11.3.59 ulimit.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.60 unistd.h

```
typedef long int intptr_t;
```

11.3.61 utime.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.62 utmp.h

```
struct lastlog {
    int32_t ll_time;
    char ll_line[UT_LINESIZE];
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
    char ll_host[UT_HOSTSIZE];
};

struct utmp {
    short ut_type;
    pid_t ut_pid;
    char ut_line[UT_LINESIZE];
    char ut_id[4];
    char ut_user[UT_NAMESIZE];
    char ut_host[UT_HOSTSIZE];
    struct exit_status ut_exit;
    int ut_session;
    struct {
        int32_t tv_sec;
        int32_t tv_usec;
    } ut_tv;
    int32_t ut_addr_v6[4];
    char __unused[20];
};
```

11.3.63 utmpx.h

```
struct utmpx {
    short ut_type;
    pid_t ut_pid;
    char ut_line[UT_LINESIZE];
    char ut_id[4];
    char ut_user[UT_NAMESIZE];
    char ut_host[UT_HOSTSIZE];
    struct exit_status ut_exit;
    int32_t ut_session;
    struct {
        int32_t tv_sec;
        int32_t tv_usec;
    } ut_tv;
    int32_t ut_addr_v6[4];
    char __unused[20];
};
```

11.3.64 wctype.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.3.65 wordexp.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.4 Interfaces for libm

Table 11-24 defines the library name and shared object name for the libm library

Table 11-24 libm Definition

Library:	libm

 © 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

SONAME:	libm.so.6

The behavior of the interfaces in this library is specified by the following specifications:

[ISOC99] ISO C (1999)
[LSB] ISO/IEC 23360-1
[SUSv2] SUSv2
[SUSv3] ISO POSIX (2003)
[SVID.3] SVID Issue 3

11.4.1 Math

11.4.1.1 Interfaces for Math

An LSB conforming implementation shall provide the architecture specific functions for Math specified in Table 11-25, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-25 libm - Math Function Interfaces

__finite(GLIBC_2.2.5) [ISOC99]	__finitef(GLIBC_2.2.5) [ISOC99]	__finitel(GLIBC_2.2.5) [ISOC99]	__fpclassify(GLIBC_2.2.5) [LSB]
__fpclassifyf(GLIBC_2.2.5) [LSB]	__fpclassifyl(GLIBC_2.2.5) [LSB]	__signbitl(GLIBC_2.2.5) [ISOC99]	acos(GLIBC_2.2.5) [SUSv3]
acosf(GLIBC_2.2.5) [SUSv3]	acosh(GLIBC_2.2.5) [SUSv3]	acoshf(GLIBC_2.2.5) [SUSv3]	acoshl(GLIBC_2.2.5) [SUSv3]
acosl(GLIBC_2.2.5) [SUSv3]	asin(GLIBC_2.2.5) [SUSv3]	asinf(GLIBC_2.2.5) [SUSv3]	asinh(GLIBC_2.2.5) [SUSv3]
asinhf(GLIBC_2.2.5) [SUSv3]	asinhl(GLIBC_2.2.5) [SUSv3]	asinl(GLIBC_2.2.5) [SUSv3]	atan(GLIBC_2.2.5) [SUSv3]
atan2(GLIBC_2.2.5) [SUSv3]	atan2f(GLIBC_2.2.5) [SUSv3]	atan2l(GLIBC_2.2.5) [SUSv3]	atanf(GLIBC_2.2.5) [SUSv3]
atanh(GLIBC_2.2.5) [SUSv3]	atanhf(GLIBC_2.2.5) [SUSv3]	atanhl(GLIBC_2.2.5) [SUSv3]	atanl(GLIBC_2.2.5) [SUSv3]
cabs(GLIBC_2.2.5) [SUSv3]	cabsf(GLIBC_2.2.5) [SUSv3]	cabsl(GLIBC_2.2.5) [SUSv3]	cacos(GLIBC_2.2.5) [SUSv3]
cacosf(GLIBC_2.2.5) [SUSv3]	cacosh(GLIBC_2.2.5) [SUSv3]	cacoshf(GLIBC_2.2.5) [SUSv3]	cacoshl(GLIBC_2.2.5) [SUSv3]
cacosl(GLIBC_2.2.5) [SUSv3]	carg(GLIBC_2.2.5) [SUSv3]	cargf(GLIBC_2.2.5) [SUSv3]	cargl(GLIBC_2.2.5) [SUSv3]
casin(GLIBC_2.2.5) [SUSv3]	casinf(GLIBC_2.2.5) [SUSv3]	casinh(GLIBC_2.2.5) [SUSv3]	casinhf(GLIBC_2.2.5) [SUSv3]
casinhl(GLIBC_2.2.5) [SUSv3]	casinl(GLIBC_2.2.5) [SUSv3]	catan(GLIBC_2.2.5) [SUSv3]	catanf(GLIBC_2.2.5) [SUSv3]
catanh(GLIBC_2.2.5) [SUSv3]	catanhf(GLIBC_2.2.5) [SUSv3]	catanhl(GLIBC_2.2.5) [SUSv3]	catanl(GLIBC_2.2.5) [SUSv3]
cbrt(GLIBC_2.2.5	cbrtf(GLIBC_2.2.	cbrtl(GLIBC_2.2.	ccos(GLIBC_2.2.5

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

) [SUSv3]	5) [SUSv3]	5) [SUSv3]	) [SUSv3]
ccosf(GLIBC_2.2.5) [SUSv3]	ccosh(GLIBC_2.2.5) [SUSv3]	ccoshf(GLIBC_2.2.5) [SUSv3]	ccoshl(GLIBC_2.2.5) [SUSv3]
ccosl(GLIBC_2.2.5) [SUSv3]	ceil(GLIBC_2.2.5) [SUSv3]	ceilf(GLIBC_2.2.5) [SUSv3]	ceill(GLIBC_2.2.5) [SUSv3]
cexp(GLIBC_2.2.5) [SUSv3]	cexpf(GLIBC_2.2.5) [SUSv3]	cexpl(GLIBC_2.2.5) [SUSv3]	cimag(GLIBC_2.2.5) [SUSv3]
cimagf(GLIBC_2.2.5) [SUSv3]	cimagl(GLIBC_2.2.5) [SUSv3]	clog(GLIBC_2.2.5) [SUSv3]	clog10(GLIBC_2.2.5) [ISOC99]
clog10f(GLIBC_2.2.5) [ISOC99]	clog10l(GLIBC_2.2.5) [ISOC99]	clogf(GLIBC_2.2.5) [SUSv3]	clogl(GLIBC_2.2.5) [SUSv3]
conj(GLIBC_2.2.5) [SUSv3]	conjf(GLIBC_2.2.5) [SUSv3]	conjl(GLIBC_2.2.5) [SUSv3]	copysign(GLIBC_2.2.5) [SUSv3]
copysignf(GLIBC_2.2.5) [SUSv3]	copysignl(GLIBC_2.2.5) [SUSv3]	cos(GLIBC_2.2.5) [SUSv3]	cosf(GLIBC_2.2.5) [SUSv3]
cosh(GLIBC_2.2.5) [SUSv3]	coshf(GLIBC_2.2.5) [SUSv3]	coshl(GLIBC_2.2.5) [SUSv3]	cosl(GLIBC_2.2.5) [SUSv3]
cpow(GLIBC_2.2.5) [SUSv3]	cpowf(GLIBC_2.2.5) [SUSv3]	cpowl(GLIBC_2.2.5) [SUSv3]	cproj(GLIBC_2.2.5) [SUSv3]
cprojf(GLIBC_2.2.5) [SUSv3]	cprojl(GLIBC_2.2.5) [SUSv3]	creal(GLIBC_2.2.5) [SUSv3]	crealf(GLIBC_2.2.5) [SUSv3]
creall(GLIBC_2.2.5) [SUSv3]	csin(GLIBC_2.2.5) [SUSv3]	csinf(GLIBC_2.2.5) [SUSv3]	csinh(GLIBC_2.2.5) [SUSv3]
csinhf(GLIBC_2.2.5) [SUSv3]	csinhl(GLIBC_2.2.5) [SUSv3]	csinl(GLIBC_2.2.5) [SUSv3]	csqrt(GLIBC_2.2.5) [SUSv3]
csqrtf(GLIBC_2.2.5) [SUSv3]	csqrtl(GLIBC_2.2.5) [SUSv3]	ctan(GLIBC_2.2.5) [SUSv3]	ctanf(GLIBC_2.2.5) [SUSv3]
ctanh(GLIBC_2.2.5) [SUSv3]	ctanhf(GLIBC_2.2.5) [SUSv3]	ctanhl(GLIBC_2.2.5) [SUSv3]	ctanl(GLIBC_2.2.5) [SUSv3]
dremf(GLIBC_2.2.5) [ISOC99]	dreml(GLIBC_2.2.5) [ISOC99]	erf(GLIBC_2.2.5) [SUSv3]	erfc(GLIBC_2.2.5) [SUSv3]
erfcf(GLIBC_2.2.5) [SUSv3]	erfcl(GLIBC_2.2.5) [SUSv3]	erff(GLIBC_2.2.5) [SUSv3]	erfl(GLIBC_2.2.5) [SUSv3]
exp(GLIBC_2.2.5) [SUSv3]	exp2(GLIBC_2.2.5) [SUSv3]	exp2f(GLIBC_2.2.5) [SUSv3]	exp2l(GLIBC_2.2.5) [SUSv3]
expf(GLIBC_2.2.5) [SUSv3]	expl(GLIBC_2.2.5) [SUSv3]	expm1(GLIBC_2.2.5) [SUSv3]	expm1f(GLIBC_2.2.5) [SUSv3]
expm1l(GLIBC_2.2.5) [SUSv3]	fabs(GLIBC_2.2.5) [SUSv3]	fabsf(GLIBC_2.2.5) [SUSv3]	fabsl(GLIBC_2.2.5) [SUSv3]
fdim(GLIBC_2.2.5) [SUSv3]	fdimf(GLIBC_2.2.5) [SUSv3]	fdiml(GLIBC_2.2.5) [SUSv3]	feclearexcept(GLIBC_2.2.5) [SUSv3]

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

fegetenv(GLIBC_2.2.5) [SUSv3]	fegetexceptflag(GLIBC_2.2.5) [SUSv3]	fegetround(GLIBC_2.2.5) [SUSv3]	feholdexcept(GLIBC_2.2.5) [SUSv3]
feraiseexcept(GLIBC_2.2.5) [SUSv3]	fesetenv(GLIBC_2.2.5) [SUSv3]	fesetexceptflag(GLIBC_2.2.5) [SUSv3]	fesetround(GLIBC_2.2.5) [SUSv3]
fetestexcept(GLIBC_2.2.5) [SUSv3]	feupdateenv(GLIBC_2.2.5) [SUSv3]	finite(GLIBC_2.2.5) [SUSv2]	finitef(GLIBC_2.2.5) [ISOC99]
finitel(GLIBC_2.2.5) [ISOC99]	floor(GLIBC_2.2.5) [SUSv3]	floorf(GLIBC_2.2.5) [SUSv3]	floorl(GLIBC_2.2.5) [SUSv3]
fma(GLIBC_2.2.5) [SUSv3]	fmaf(GLIBC_2.2.5) [SUSv3]	fmal(GLIBC_2.2.5) [SUSv3]	fmax(GLIBC_2.2.5) [SUSv3]
fmaxf(GLIBC_2.2.5) [SUSv3]	fmaxl(GLIBC_2.2.5) [SUSv3]	fmin(GLIBC_2.2.5) [SUSv3]	fminf(GLIBC_2.2.5) [SUSv3]
fminl(GLIBC_2.2.5) [SUSv3]	fmod(GLIBC_2.2.5) [SUSv3]	fmodf(GLIBC_2.2.5) [SUSv3]	fmodl(GLIBC_2.2.5) [SUSv3]
frexp(GLIBC_2.2.5) [SUSv3]	frexpf(GLIBC_2.2.5) [SUSv3]	frexpl(GLIBC_2.2.5) [SUSv3]	gamma(GLIBC_2.2.5) [SUSv2]
gammaf(GLIBC_2.2.5) [ISOC99]	gammal(GLIBC_2.2.5) [ISOC99]	hypot(GLIBC_2.2.5) [SUSv3]	hypotf(GLIBC_2.2.5) [SUSv3]
hypotl(GLIBC_2.2.5) [SUSv3]	ilogb(GLIBC_2.2.5) [SUSv3]	ilogbf(GLIBC_2.2.5) [SUSv3]	ilogbl(GLIBC_2.2.5) [SUSv3]
j0(GLIBC_2.2.5) [SUSv3]	j0f(GLIBC_2.2.5) [ISOC99]	j0l(GLIBC_2.2.5) [ISOC99]	j1(GLIBC_2.2.5) [SUSv3]
j1f(GLIBC_2.2.5) [ISOC99]	j1l(GLIBC_2.2.5) [ISOC99]	jn(GLIBC_2.2.5) [SUSv3]	jnf(GLIBC_2.2.5) [ISOC99]
jnl(GLIBC_2.2.5) [ISOC99]	ldexp(GLIBC_2.2.5) [SUSv3]	ldexpf(GLIBC_2.2.5) [SUSv3]	ldexpl(GLIBC_2.2.5) [SUSv3]
lgamma(GLIBC_2.2.5) [SUSv3]	lgamma_r(GLIBC_2.2.5) [ISOC99]	lgammaf(GLIBC_2.2.5) [SUSv3]	lgammaf_r(GLIBC_2.2.5) [ISOC99]
lgammal(GLIBC_2.2.5) [SUSv3]	lgammal_r(GLIBC_2.2.5) [ISOC99]	llrint(GLIBC_2.2.5) [SUSv3]	llrintf(GLIBC_2.2.5) [SUSv3]
llrintl(GLIBC_2.2.5) [SUSv3]	llround(GLIBC_2.2.5) [SUSv3]	llroundf(GLIBC_2.2.5) [SUSv3]	llroundl(GLIBC_2.2.5) [SUSv3]
log(GLIBC_2.2.5) [SUSv3]	log10(GLIBC_2.2.5) [SUSv3]	log10f(GLIBC_2.2.5) [SUSv3]	log10l(GLIBC_2.2.5) [SUSv3]
log1p(GLIBC_2.2.5) [SUSv3]	log1pf(GLIBC_2.2.5) [SUSv3]	log1pl(GLIBC_2.2.5) [SUSv3]	log2(GLIBC_2.2.5) [SUSv3]
log2f(GLIBC_2.2.5) [SUSv3]	log2l(GLIBC_2.2.5) [SUSv3]	logb(GLIBC_2.2.5) [SUSv3]	logbf(GLIBC_2.2.5) [SUSv3]

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

logbl(GLIBC_2.2.5) [SUSv3]	logf(GLIBC_2.2.5) [SUSv3]	logl(GLIBC_2.2.5) [SUSv3]	lrint(GLIBC_2.2.5) [SUSv3]
lrintf(GLIBC_2.2.5) [SUSv3]	lrintl(GLIBC_2.2.5) [SUSv3]	lround(GLIBC_2.2.5) [SUSv3]	lroundf(GLIBC_2.2.5) [SUSv3]
lroundl(GLIBC_2.2.5) [SUSv3]	matherr(GLIBC_2.2.5) [SVID.3]	modf(GLIBC_2.2.5) [SUSv3]	modff(GLIBC_2.2.5) [SUSv3]
modfl(GLIBC_2.2.5) [SUSv3]	nan(GLIBC_2.2.5) [SUSv3]	nanf(GLIBC_2.2.5) [SUSv3]	nanl(GLIBC_2.2.5) [SUSv3]
nearbyint(GLIBC_2.2.5) [SUSv3]	nearbyintf(GLIBC_2.2.5) [SUSv3]	nearbyintl(GLIBC_2.2.5) [SUSv3]	nextafter(GLIBC_2.2.5) [SUSv3]
nextafterf(GLIBC_2.2.5) [SUSv3]	nextafterl(GLIBC_2.2.5) [SUSv3]	nexttoward(GLIBC_2.2.5) [SUSv3]	nexttowardf(GLIBC_2.2.5) [SUSv3]
nexttowardl(GLIBC_2.2.5) [SUSv3]	pow(GLIBC_2.2.5) [SUSv3]	pow10(GLIBC_2.2.5) [ISOC99]	pow10f(GLIBC_2.2.5) [ISOC99]
pow10l(GLIBC_2.2.5) [ISOC99]	powf(GLIBC_2.2.5) [SUSv3]	powl(GLIBC_2.2.5) [SUSv3]	remainder(GLIBC_2.2.5) [SUSv3]
remainderf(GLIBC_2.2.5) [SUSv3]	remainderl(GLIBC_2.2.5) [SUSv3]	remquo(GLIBC_2.2.5) [SUSv3]	remquof(GLIBC_2.2.5) [SUSv3]
remquol(GLIBC_2.2.5) [SUSv3]	rint(GLIBC_2.2.5) [SUSv3]	rintf(GLIBC_2.2.5) [SUSv3]	rintl(GLIBC_2.2.5) [SUSv3]
round(GLIBC_2.2.5) [SUSv3]	roundf(GLIBC_2.2.5) [SUSv3]	roundl(GLIBC_2.2.5) [SUSv3]	scalb(GLIBC_2.2.5) [SUSv3]
scalbf(GLIBC_2.2.5) [ISOC99]	scalbl(GLIBC_2.2.5) [ISOC99]	scalbln(GLIBC_2.2.5) [SUSv3]	scalblnf(GLIBC_2.2.5) [SUSv3]
scalblnl(GLIBC_2.2.5) [SUSv3]	scalbn(GLIBC_2.2.5) [SUSv3]	scalbnf(GLIBC_2.2.5) [SUSv3]	scalbnl(GLIBC_2.2.5) [SUSv3]
significand(GLIBC_2.2.5) [ISOC99]	significandf(GLIBC_2.2.5) [ISOC99]	significandl(GLIBC_2.2.5) [ISOC99]	sin(GLIBC_2.2.5) [SUSv3]
sincos(GLIBC_2.2.5) [ISOC99]	sincosf(GLIBC_2.2.5) [ISOC99]	sincosl(GLIBC_2.2.5) [ISOC99]	sinf(GLIBC_2.2.5) [SUSv3]
sinh(GLIBC_2.2.5) [SUSv3]	sinhf(GLIBC_2.2.5) [SUSv3]	sinhl(GLIBC_2.2.5) [SUSv3]	sinl(GLIBC_2.2.5) [SUSv3]
sqrt(GLIBC_2.2.5) [SUSv3]	sqrtf(GLIBC_2.2.5) [SUSv3]	sqrtl(GLIBC_2.2.5) [SUSv3]	tan(GLIBC_2.2.5) [SUSv3]
tanf(GLIBC_2.2.5) [SUSv3]	tanh(GLIBC_2.2.5) [SUSv3]	tanhf(GLIBC_2.2.5) [SUSv3]	tanhl(GLIBC_2.2.5) [SUSv3]
tanl(GLIBC_2.2.5) [SUSv3]	tgamma(GLIBC_2.2.5) [SUSv3]	tgammaf(GLIBC_2.2.5) [SUSv3]	tgammal(GLIBC_2.2.5) [SUSv3]
trunc(GLIBC_2.2.5) [SUSv3]	truncf(GLIBC_2.2.5) [SUSv3]	truncl(GLIBC_2.2.5) [SUSv3]	y0(GLIBC_2.2.5) [SUSv3]

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

y0f(GLIBC_2.2.5) [ISOC99]	y0l(GLIBC_2.2.5) [ISOC99]	y1(GLIBC_2.2.5) [SUSv3]	y1f(GLIBC_2.2.5) [ISOC99]
y1l(GLIBC_2.2.5) [ISOC99]	yn(GLIBC_2.2.5) [SUSv3]	ynf(GLIBC_2.2.5) [ISOC99]	ynl(GLIBC_2.2.5) [ISOC99]

An LSB conforming implementation shall provide the architecture specific data interfaces for Math specified in Table 11-26, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-26 libm - Math Data Interfaces

signgam(GLIBC_2.2.5) [SUSv3]			

11.5 Data Definitions for libm

This section defines global identifiers and their values that are associated with interfaces contained in libm. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

11.5.1 complex.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.5.2 fenv.h

```
#define FE_INVALID      0x01
#define FE_DIVBYZERO    0x04
#define FE_OVERFLOW     0x08
#define FE_UNDERFLOW    0x10
#define FE_INEXACT      0x20

#define FE_ALL_EXCEPT   \
        (FE_INEXACT | FE_DIVBYZERO | FE_UNDERFLOW | FE_OVERFLOW |
FE_INVALID)

#define FE_TONEAREST    0
#define FE_DOWNWARD     0x400
#define FE_UPWARD       0x800
#define FE_TOWARDZERO   0xc00
```

© 2006 ISO/IEC — All rights reserved

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

```
typedef unsigned short fexcept_t;

typedef struct {
    unsigned short __control_word;
    unsigned short __unused1;
    unsigned short __status_word;
    unsigned short __unused2;
    unsigned short __tags;
    unsigned short __unused3;
    unsigned int __eip;
    unsigned short __cs_selector;
    unsigned int __opcode:11;
    unsigned int __unused4:5;
    unsigned int __data_offset;
    unsigned short __data_selector;
    unsigned short __unused5;
    unsigned int __mxcsr;
} fenv_t;

#define FE_DFL_ENV      ((__const fenv_t *) -1)
```

11.5.3 math.h

```
#define fpclassify(x)   \
        (sizeof (x) == sizeof (float) ? __fpclassifyf (x) :sizeof (x)
== sizeof (double) ? __fpclassify (x) : __fpclassifyl (x))
#define signbit(x)      \
        (sizeof (x) == sizeof (float)? __signbitf (x): sizeof (x) ==
sizeof (double)? __signbit (x) : __signbitl (x))

#define FP_ILOGB0       -2147483648
#define FP_ILOGBNAN     -2147483648

extern long double exp2l(long double);
extern int __fpclassifyl(long double);
extern int __signbitl(long double);
```

11.6 Interface Definitions for libm

The interfaces defined on the following pages are included in libm and are defined by this specification. Unless otherwise noted, these interfaces shall be included in the source standard.

Other interfaces listed in Section 11.4 shall behave as described in the referenced base document.

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

__fpclassifyl

Name

__fpclassifyl — test for infinity

Synopsis

```
int __fpclassifyl(long double arg);
```

Description

__fpclassifyl() has the same specification as fpclassifyl() in ISO POSIX (2003), except that the argument type for __fpclassifyl() is known to be long double.

__fpclassifyl() is not in the source standard; it is only in the binary standard.

11.7 Interfaces for libpthread

Table 11-27 defines the library name and shared object name for the libpthread library

Table 11-27 libpthread Definition

Library:	libpthread
SONAME:	libpthread.so.0

The behavior of the interfaces in this library is specified by the following specifications:

[LFS] Large File Support
[LSB] ISO/IEC 23360-1
[SUSv3] ISO POSIX (2003)

11.7.1 Realtime Threads

11.7.1.1 Interfaces for Realtime Threads

An LSB conforming implementation shall provide the architecture specific functions for Realtime Threads specified in Table 11-28, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-28 libpthread - Realtime Threads Function Interfaces

pthread_attr_getinheritsched(GLIBC_2.2.5) [SUSv3]	pthread_attr_getschedpolicy(GLIBC_2.2.5) [SUSv3]	pthread_attr_getscope(GLIBC_2.2.5) [SUSv3]	pthread_attr_setinheritsched(GLIBC_2.2.5) [SUSv3]
pthread_attr_setschedpolicy(GLIBC_2.2.5) [SUSv3]	pthread_attr_setscope(GLIBC_2.2.5) [SUSv3]	pthread_getschedparam(GLIBC_2.2.5) [SUSv3]	pthread_setschedparam(GLIBC_2.2.5) [SUSv3]

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

11.7.2 Advanced Realtime Threads

11.7.2.1 Interfaces for Advanced Realtime Threads

No external functions are defined for libpthread - Advanced Realtime Threads in this part of the specification. See also the generic specification, ISO/IEC 23360-1.

11.7.3 Posix Threads

11.7.3.1 Interfaces for Posix Threads

An LSB conforming implementation shall provide the architecture specific functions for Posix Threads specified in Table 11-29, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-29 libpthread - Posix Threads Function Interfaces

_pthread_cleanup_pop(GLIBC_2.2.5) [LSB]	_pthread_cleanup_push(GLIBC_2.2.5) [LSB]	pthread_attr_destroy(GLIBC_2.2.5) [SUSv3]	pthread_attr_getdetachstate(GLIBC_2.2.5) [SUSv3]
pthread_attr_getguardsize(GLIBC_2.2.5) [SUSv3]	pthread_attr_getschedparam(GLIBC_2.2.5) [SUSv3]	pthread_attr_getstack(GLIBC_2.2.5) [SUSv3]	pthread_attr_getstackaddr(GLIBC_2.2.5) [SUSv3]
pthread_attr_getstacksize(GLIBC_2.2.5) [SUSv3]	pthread_attr_init(GLIBC_2.2.5) [SUSv3]	pthread_attr_setdetachstate(GLIBC_2.2.5) [SUSv3]	pthread_attr_setguardsize(GLIBC_2.2.5) [SUSv3]
pthread_attr_setschedparam(GLIBC_2.2.5) [SUSv3]	pthread_attr_setstackaddr(GLIBC_2.2.5) [SUSv3]	pthread_attr_setstacksize(GLIBC_2.2.5) [SUSv3]	pthread_cancel(GLIBC_2.2.5) [SUSv3]
pthread_cond_broadcast(GLIBC_2.3.2) [SUSv3]	pthread_cond_destroy(GLIBC_2.3.2) [SUSv3]	pthread_cond_init(GLIBC_2.3.2) [SUSv3]	pthread_cond_signal(GLIBC_2.3.2) [SUSv3]
pthread_cond_timedwait(GLIBC_2.3.2) [SUSv3]	pthread_cond_wait(GLIBC_2.3.2) [SUSv3]	pthread_condattr_destroy(GLIBC_2.2.5) [SUSv3]	pthread_condattr_getpshared(GLIBC_2.2.5) [SUSv3]
pthread_condattr_init(GLIBC_2.2.5) [SUSv3]	pthread_condattr_setpshared(GLIBC_2.2.5) [SUSv3]	pthread_create(GLIBC_2.2.5) [SUSv3]	pthread_detach(GLIBC_2.2.5) [SUSv3]
pthread_equal(GLIBC_2.2.5) [SUSv3]	pthread_exit(GLIBC_2.2.5) [SUSv3]	pthread_getconcurrency(GLIBC_2.2.5) [SUSv3]	pthread_getspecific(GLIBC_2.2.5) [SUSv3]
pthread_join(GLIBC_2.2.5) [SUSv3]	pthread_key_create(GLIBC_2.2.5) [SUSv3]	pthread_key_delete(GLIBC_2.2.5) [SUSv3]	pthread_kill(GLIBC_2.2.5) [SUSv3]
pthread_mutex_destroy(GLIBC_2.2.5) [SUSv3]	pthread_mutex_init(GLIBC_2.2.5) [SUSv3]	pthread_mutex_lock(GLIBC_2.2.5) [SUSv3]	pthread_mutex_trylock(GLIBC_2.2.5) [SUSv3]

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

pthread_mutex_unlock(GLIBC_2.2.5) [SUSv3]	pthread_mutexattr_destroy(GLIBC_2.2.5) [SUSv3]	pthread_mutexattr_getpshared(GLIBC_2.2.5) [SUSv3]	pthread_mutexattr_gettype(GLIBC_2.2.5) [SUSv3]
pthread_mutexattr_init(GLIBC_2.2.5) [SUSv3]	pthread_mutexattr_setpshared(GLIBC_2.2.5) [SUSv3]	pthread_mutexattr_settype(GLIBC_2.2.5) [SUSv3]	pthread_once(GLIBC_2.2.5) [SUSv3]
pthread_rwlock_destroy(GLIBC_2.2.5) [SUSv3]	pthread_rwlock_init(GLIBC_2.2.5) [SUSv3]	pthread_rwlock_rdlock(GLIBC_2.2.5) [SUSv3]	pthread_rwlock_timedrdlock(GLIBC_2.2.5) [SUSv3]
pthread_rwlock_timedwrlock(GLIBC_2.2.5) [SUSv3]	pthread_rwlock_tryrdlock(GLIBC_2.2.5) [SUSv3]	pthread_rwlock_trywrlock(GLIBC_2.2.5) [SUSv3]	pthread_rwlock_unlock(GLIBC_2.2.5) [SUSv3]
pthread_rwlock_wrlock(GLIBC_2.2.5) [SUSv3]	pthread_rwlockattr_destroy(GLIBC_2.2.5) [SUSv3]	pthread_rwlockattr_getpshared(GLIBC_2.2.5) [SUSv3]	pthread_rwlockattr_init(GLIBC_2.2.5) [SUSv3]
pthread_rwlockattr_setpshared(GLIBC_2.2.5) [SUSv3]	pthread_self(GLIBC_2.2.5) [SUSv3]	pthread_setcancelstate(GLIBC_2.2.5) [SUSv3]	pthread_setcanceltype(GLIBC_2.2.5) [SUSv3]
pthread_setconcurrency(GLIBC_2.2.5) [SUSv3]	pthread_setspecific(GLIBC_2.2.5) [SUSv3]	pthread_sigmask(GLIBC_2.2.5) [SUSv3]	pthread_testcancel(GLIBC_2.2.5) [SUSv3]
sem_close(GLIBC_2.2.5) [SUSv3]	sem_destroy(GLIBC_2.2.5) [SUSv3]	sem_getvalue(GLIBC_2.2.5) [SUSv3]	sem_init(GLIBC_2.2.5) [SUSv3]
sem_open(GLIBC_2.2.5) [SUSv3]	sem_post(GLIBC_2.2.5) [SUSv3]	sem_timedwait(GLIBC_2.2.5) [SUSv3]	sem_trywait(GLIBC_2.2.5) [SUSv3]
sem_unlink(GLIBC_2.2.5) [SUSv3]	sem_wait(GLIBC_2.2.5) [SUSv3]		

11.7.4 Thread aware versions of libc interfaces

11.7.4.1 Interfaces for Thread aware versions of libc interfaces

An LSB conforming implementation shall provide the architecture specific functions for Thread aware versions of libc interfaces specified in Table 11-30, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-30 libpthread - Thread aware versions of libc interfaces Function Interfaces

lseek64(GLIBC_2	open64(GLIBC_2	pread(GLIBC_2.2	pread64(GLIBC_

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

.2.5) [LFS]	.2.5) [LFS]	.5) [SUSv3]	2.2.5) [LFS]
pwrite(GLIBC_2.2.5) [SUSv3]	pwrite64(GLIBC_2.2.5) [LFS]		

11.8 Data Definitions for libpthread

This section defines global identifiers and their values that are associated with interfaces contained in libpthread. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

11.8.1 pthread.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.8.2 semaphore.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.9 Interfaces for libgcc_s

Table 11-31 defines the library name and shared object name for the libgcc_s library

Table 11-31 libgcc_s Definition

Library:	libgcc_s
SONAME:	libgcc_s.so.1

The behavior of the interfaces in this library is specified by the following specifications:

[LSB] ISO/IEC 23360-1

© 2006 ISO/IEC — All rights reserved

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

11.9.1 Unwind Library

11.9.1.1 Interfaces for Unwind Library

An LSB conforming implementation shall provide the architecture specific functions for Unwind Library specified in Table 11-32, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-32 libgcc_s - Unwind Library Function Interfaces

_Unwind_Backtrace(GCC_3.3) [LSB]	_Unwind_DeleteException(GCC_3.0) [LSB]	_Unwind_FindEnclosingFunction(GCC_3.3) [LSB]	_Unwind_Find_FDE(GCC_3.0) [LSB]
_Unwind_ForcedUnwind(GCC_3.0) [LSB]	_Unwind_GetCFA(GCC_3.3) [LSB]	_Unwind_GetDataRelBase(GCC_3.0) [LSB]	_Unwind_GetGR(GCC_3.0) [LSB]
_Unwind_GetIP(GCC_3.0) [LSB]	_Unwind_GetLanguageSpecificData(GCC_3.0) [LSB]	_Unwind_GetRegionStart(GCC_3.0) [LSB]	_Unwind_GetTextRelBase(GCC_3.0) [LSB]
_Unwind_RaiseException(GCC_3.0) [LSB]	_Unwind_Resume(GCC_3.0) [LSB]	_Unwind_Resume_or_Rethrow(GCC_3.3) [LSB]	_Unwind_SetGR(GCC_3.0) [LSB]
_Unwind_SetIP(GCC_3.0) [LSB]			

11.10 Data Definitions for libgcc_s

This section defines global identifiers and their values that are associated with interfaces contained in libgcc_s. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

11.10.1 unwind.h

```
extern void _Unwind_DeleteException(struct _Unwind_Exception *);
extern fde *_Unwind_Find_FDE(void *, struct dwarf_eh_base *);
extern _Unwind_Ptr _Unwind_ForcedUnwind(struct _Unwind_Exception *,
                                        _Unwind_Stop_Fn, void *);
extern  _Unwind_Ptr  _Unwind_GetDataRelBase(struct  _Unwind_Context
*);
extern _Unwind_Word _Unwind_GetGR(struct _Unwind_Context *, int);
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
extern _Unwind_Ptr _Unwind_GetIP(struct _Unwind_Context *);
extern _Unwind_Ptr _Unwind_GetLanguageSpecificData(void);
extern  _Unwind_Ptr  _Unwind_GetRegionStart(struct  _Unwind_Context
*);
extern  _Unwind_Ptr  _Unwind_GetTextRelBase(struct  _Unwind_Context
*);
extern      _Unwind_Reason_Code      _Unwind_RaiseException(struct
_Unwind_Exception
                                                    *);
extern void _Unwind_Resume(struct _Unwind_Exception *);
extern void _Unwind_SetGR(struct _Unwind_Context *, int, u_int64_t);
extern void _Unwind_SetIP(struct _Unwind_Context *, _Unwind_Ptr);
extern _Unwind_Reason_Code _Unwind_Backtrace(_Unwind_Trace_Fn, void
*);
extern  _Unwind_Reason_Code  _Unwind_GetCFA(struct  _Unwind_Context
*);
extern _Unwind_Reason_Code _Unwind_Resume_or_Rethrow(struct

_Unwind_Exception *);
extern void *_Unwind_FindEnclosingFunction(void *);
```

11.11 Interface Definitions for libgcc_s

The interfaces defined on the following pages are included in libgcc_s and are defined by this specification. Unless otherwise noted, these interfaces shall be included in the source standard.

Other interfaces listed in Section 11.9 shall behave as described in the referenced base document.

_Unwind_DeleteException

Name

`_Unwind_DeleteException` — private C++ error handling method

Synopsis

```
void _Unwind_DeleteException(struct _Unwind_Exception * object);
```

Description

`_Unwind_DeleteException()` deletes the given exception *`object`*. If a given runtime resumes normal execution after catching a foreign exception, it will not know how to delete that exception. Such an exception shall be deleted by calling `_Unwind_DeleteException()`. This is a convenience function that calls the function pointed to by the *exception_cleanup* field of the exception header.

_Unwind_Find_FDE

Name

`_Unwind_Find_FDE` — private C++ error handling method

Synopsis

```
fde * _Unwind_Find_FDE(void * pc, struct dwarf_eh_bases * bases);
```

Description

`_Unwind_Find_FDE()` looks for the object containing *`pc`*, then inserts into *`bases`*.

 © 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

_Unwind_ForcedUnwind

Name

_Unwind_ForcedUnwind — private C++ error handling method

Synopsis

```
_Unwind_Reason_Code _Unwind_ForcedUnwind(struct _Unwind_Exception *
object, _Unwind_Stop_Fn stop, void * stop_parameter);
```

Description

_Unwind_ForcedUnwind() raises an exception for forced unwinding, passing along the given exception *object*, which should have its *exception_class* and *exception_cleanup* fields set. The exception *object* has been allocated by the language-specific runtime, and has a language-specific format, except that it shall contain an _Unwind_Exception struct.

Forced unwinding is a single-phase process. *stop* and *stop_parameter* control the termination of the unwind process instead of the usual personality routine query. *stop* is called for each unwind frame, with the parameteres described for the usual personality routine below, plus an additional *stop_parameter*.

Return Value

When *stop* identifies the destination frame, it transfers control to the user code as appropriate without returning, normally after calling _Unwind_DeleteException(). If not, then it should return an _Unwind_Reason_Code value.

If *stop* returns any reason code other than _URC_NO_REASON, then the stack state is indeterminate from the point of view of the caller of _Unwind_ForcedUnwind(). Rather than attempt to return, therefore, the unwind library should use the *exception_cleanup* entry in the exception, and then call abort().

_URC_NO_REASON

This is not the destination from. The unwind runtime will call frame's personality routine with the _UA_FORCE_UNWIND and _UA_CLEANUP_PHASE flag set in *actions*, and then unwind to the next frame and call the stop() function again.

_URC_END_OF_STACK

In order to allow _Unwind_ForcedUnwind() to perform special processing when it reaches the end of the stack, the unwind runtime will call it after the last frame is rejected, with a NULL stack pointer in the context, and the stop() function shall catch this condition. It may return this code if it cannot handle end-of-stack.

_URC_FATAL_PHASE2_ERROR

The stop() function may return this code for other fatal conditions like stack corruption.

© 2006 ISO/IEC — All rights reserved

--`,,```,,,,````-`-`,,`,,`,`,,`---
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

_Unwind_GetDataRelBase

Name

`_Unwind_GetDataRelBase` — private IA64 C++ error handling method

Synopsis

```
_Unwind_Ptr _Unwind_GetDataRelBase(struct _Unwind_Context * context);
```

Description

`_Unwind_GetDataRelBase()` returns the global pointer in register one for *`context`*.

_Unwind_GetGR

Name

`_Unwind_GetGR` — private C++ error handling method

Synopsis

```
_Unwind_Word _Unwind_GetGR(struct _Unwind_Context * context, int index);
```

Description

`_Unwind_GetGR()` returns data at *`index`* found in *`context`*. The register is identified by its index: `0` to `31` are for the fixed registers, and `32` to `127` are for the stacked registers.

During the two phases of unwinding, only GR1 has a guaranteed value, which is the global pointer of the frame referenced by the unwind *`context`*. If the register has its NAT bit set, the behavior is unspecified.

_Unwind_GetIP

Name

`_Unwind_GetIP` — private C++ error handling method

Synopsis

```
_Unwind_Ptr _Unwind_GetIP(struct _Unwind_Context * context);
```

Description

`_Unwind_GetIP()` returns the instruction pointer value for the routine identified by the unwind *`context`*.

 © 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

_Unwind_GetLanguageSpecificData

Name

`_Unwind_GetLanguageSpecificData` — private C++ error handling method

Synopsis

```
_Unwind_Ptr _Unwind_GetLanguageSpecificData(struct _Unwind_Context *
context, uint value);
```

Description

`_Unwind_GetLanguageSpecificData()` returns the address of the language specific data area for the current stack frame.

_Unwind_GetRegionStart

Name

`_Unwind_GetRegionStart` — private C++ error handling method

Synopsis

```
_Unwind_Ptr _Unwind_GetRegionStart(struct _Unwind_Context * context);
```

Description

`_Unwind_GetRegionStart()` routine returns the address (i.e., `0`) of the beginning of the procedure or code fragment described by the current unwind descriptor block.

_Unwind_GetTextRelBase

Name

`_Unwind_GetTextRelBase` — private IA64 C++ error handling method

Synopsis

```
_Unwind_Ptr _Unwind_GetTextRelBase(struct _Unwind_Context * context);
```

Description

`_Unwind_GetTextRelBase()` calls the abort method, then returns.

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

_Unwind_RaiseException

Name

`_Unwind_RaiseException` — private C++ error handling method

Synopsis

```
_Unwind_Reason_Code _Unwind_RaiseException(struct _Unwind_Exception *
object);
```

Description

`_Unwind_RaiseException()` raises an exception, passing along the given exception *`object`*, which should have its *`exception_class`* and *`exception_cleanup`* fields set. The exception object has been allocated by the language-specific runtime, and has a language-specific format, exception that it shall contain an `_Unwind_Exception`.

Return Value

`_Unwind_RaiseException()` does not return unless an error condition is found. If an error condition occurs, an `_Unwind_Reason_Code` is returnd:

_URC_END_OF_STACK

The unwinder encountered the end of the stack during phase one without finding a handler. The unwind runtime will not have modified the stack. The C++ runtime will normally call `uncaught_exception()` in this case.

_URC_FATAL_PHASE1_ERROR

The unwinder encountered an unexpected error during phase one, because of something like stack corruption. The unwind runtime will not have modified the stack. The C++ runtime will normally call `terminate()` in this case.

_URC_FATAL_PHASE2_ERROR

The unwinder encountered an unexpected error during phase two. This is usually a *throw*, which will call `terminate()`.

_Unwind_Resume

Name

`_Unwind_Resume` — private C++ error handling method

Synopsis

```
void _Unwind_Resume(struct _Unwind_Exception * object);
```

Description

`_Unwind_Resume()` resumes propagation of an existing exception *`object`*. A call to this routine is inserted as the end of a landing pad that performs cleanup, but does not resume normal execution. It causes unwinding to proceed further.

 © 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

_Unwind_SetGR

Name

_Unwind_SetGR — private C++ error handling method

Synopsis

```
void _Unwind_SetGR(struct _Unwind_Context * context, int index, uint value);
```

Description

_Unwind_SetGR() sets the *value* of the register *index*ed for the routine identified by the unwind *context*.

_Unwind_SetIP

Name

_Unwind_SetIP — private C++ error handling method

Synopsis

```
void _Unwind_SetIP(struct _Unwind_Context * context, uint value);
```

Description

_Unwind_SetIP() sets the *value* of the instruction pointer for the routine identified by the unwind *context*

11.12 Interfaces for libdl

Table 11-33 defines the library name and shared object name for the libdl library

Table 11-33 libdl Definition

Library:	libdl
SONAME:	libdl.so.2

The behavior of the interfaces in this library is specified by the following specifications:

[LSB] ISO/IEC 23360-1
[SUSv3] ISO POSIX (2003)

11.12.1 Dynamic Loader

11.12.1.1 Interfaces for Dynamic Loader

An LSB conforming implementation shall provide the architecture specific functions for Dynamic Loader specified in Table 11-34, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-34 libdl - Dynamic Loader Function Interfaces

dladdr(GLIBC_2.2.5) [LSB]	dlclose(GLIBC_2.2.5) [SUSv3]	dlerror(GLIBC_2.2.5) [SUSv3]	dlopen(GLIBC_2.2.5) [LSB]
dlsym(GLIBC_2.			

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

2.5) [LSB]			

11.13 Data Definitions for libdl

This section defines global identifiers and their values that are associated with interfaces contained in libdl. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

11.13.1 dlfcn.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

11.14 Interfaces for libcrypt

Table 11-35 defines the library name and shared object name for the libcrypt library

Table 11-35 libcrypt Definition

Library:	libcrypt
SONAME:	libcrypt.so.1

The behavior of the interfaces in this library is specified by the following specifications:

[SUSv3] ISO POSIX (2003)

11.14.1 Encryption

11.14.1.1 Interfaces for Encryption

An LSB conforming implementation shall provide the architecture specific functions for Encryption specified in Table 11-36, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-36 libcrypt - Encryption Function Interfaces

crypt(GLIBC_2.2.5) [SUSv3]	encrypt(GLIBC_2.2.5) [SUSv3]	setkey(GLIBC_2.2.5) [SUSv3]	

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

IV Utility Libraries

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

12 Libraries

An LSB-conforming implementation shall also support some utility libraries which are built on top of the interfaces provided by the base libraries. These libraries implement common functionality, and hide additional system dependent information such as file formats and device names.

12.1 Interfaces for libz

Table 12-1 defines the library name and shared object name for the libz library

Table 12-1 libz Definition

Library:	libz
SONAME:	libz.so.1

12.1.1 Compression Library

12.1.1.1 Interfaces for Compression Library

No external functions are defined for libz - Compression Library in this part of the specification. See also the generic specification, ISO/IEC 23360-1.

12.2 Data Definitions for libz

This section defines global identifiers and their values that are associated with interfaces contained in libz. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C . The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

12.2.1 zlib.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

12.3 Interfaces for libncurses

Table 12-2 defines the library name and shared object name for the libncurses library

 © 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Table 12-2 libncurses Definition

Library:	libncurses
SONAME:	libncurses.so.5

12.3.1 Curses

12.3.1.1 Interfaces for Curses

No external functions are defined for libncurses - Curses in this part of the specification. See also the generic specification, ISO/IEC 23360-1.

12.4 Data Definitions for libncurses

This section defines global identifiers and their values that are associated with interfaces contained in libncurses. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C . The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

12.4.1 curses.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

12.5 Interfaces for libutil

Table 12-3 defines the library name and shared object name for the libutil library

Table 12-3 libutil Definition

Library:	libutil
SONAME:	libutil.so.1

The behavior of the interfaces in this library is specified by the following specifications:

[LSB] ISO/IEC 23360-1

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

12.5.1 Utility Functions

12.5.1.1 Interfaces for Utility Functions

An LSB conforming implementation shall provide the architecture specific functions for Utility Functions specified in Table 12-4, with the full mandatory functionality as described in the referenced underlying specification.

Table 12-4 libutil - Utility Functions Function Interfaces

forkpty(GLIBC_2.2.5) [LSB]	login(GLIBC_2.2.5) [LSB]	login_tty(GLIBC_2.2.5) [LSB]	logout(GLIBC_2.2.5) [LSB]
logwtmp(GLIBC_2.2.5) [LSB]	openpty(GLIBC_2.2.5) [LSB]		

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

V Package Format and Installation

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

13 Software Installation

13.1 Package Dependencies

The LSB runtime environment shall provde the following dependencies.

lsb-core-amd64

This dependency is used to indicate that the application is dependent on features contained in the LSB-Core specification.

These dependencies shall have a version of 3.0.

Other LSB modules may add additional dependencies; such dependencies shall have the format `lsb-`*`module`*`-amd64`.

13.2 Package Architecture Considerations

All packages must specify an architecture of `x86_64`. An LSB runtime environment must accept an architecture of `x86_64` even if the native architecture is different.

The `archnum` value in the Lead Section shall be 0x0001.

© 2006 ISO/IEC — All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Annex A Alphabetical Listing of Interfaces

A.1 libgcc_s

The behavior of the interfaces in this library is specified by the following Standards.

ISO/IEC 23360-1 [LSB]

Table A-1 libgcc_s Function Interfaces

_Unwind_Backtrace[LSB]	_Unwind_GetDataRelBase[LSB]	_Unwind_RaiseException[LSB]
_Unwind_DeleteException[LSB]	_Unwind_GetGR[LSB]	_Unwind_Resume[LSB]
_Unwind_FindEnclosingFunction[LSB]	_Unwind_GetIP[LSB]	_Unwind_Resume_or_Rethrow[LSB]
_Unwind_Find_FDE[LSB]	_Unwind_GetLanguageSpecificData[LSB]	_Unwind_SetGR[LSB]
_Unwind_ForcedUnwind[LSB]	_Unwind_GetRegionStart[LSB]	_Unwind_SetIP[LSB]
_Unwind_GetCFA[LSB]	_Unwind_GetTextRelBase[LSB]	

A.2 libm

The behavior of the interfaces in this library is specified by the following Standards.

ISO C (1999) [ISOC99]
ISO/IEC 23360-1 [LSB]
ISO POSIX (2003) [SUSv3]

Table A-2 libm Function Interfaces

__fpclassifyl[LSB]	__signbitl[ISOC99]	exp2l[SUSv3]

© 2006 ISO/IEC — All rights reserved

--`,,```,,,,````-`-`,,`,,`,`,,`---
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

ICS 35.080

Price based on 77 pages

© ISO/IEC 2006 – All rights reserved
--`,,```,,,,````-`-`,,`,,`,`,,`---
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale