FINAL
DRAFT

INTERNATIONAL STANDARD

ISO/IEC FDIS 9594-7

ISO/IEC JTC **1**

Secretariat: **ANSI**

Voting begins on:
2009-03-05

Voting terminates on:
2009-05-05

Information technology — Open Systems Interconnection — The Directory: Selected object classes

Technologies de l'information — Interconnexion de systèmes ouverts (OSI) — L'annuaire: Classes d'objets sélectionnées

Please see the administrative notes on page ii-1

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

Reference number
ISO/IEC FDIS 9594-7:2008(E)

© ISO/IEC 2008

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

Copyright notice

This ISO document is a Draft International Standard and is copyright-protected by ISO. Except as permitted under the applicable laws of the user's country, neither this ISO draft nor any extract from it may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission being secured.

Requests for permission to reproduce should be addressed to either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Reproduction may be subject to royalty payments or a licensing agreement.

Violators may be prosecuted.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

© ISO/IEC 2008 – All rights reserved

Not for Resale

In accordance with the provisions of Council Resolution 21/1986, this document is **circulated in the English language only**.

-`,,```,,,,````-`-`,,`,,`,`,,`---

© ISO/IEC 2008 All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Blank page

--`,,```,,,,````-`-`,,`,,`,`,,`---

© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

CONTENTS

Page

1 Scope 1
2 Normative references 1
2.1 Identical Recommendations | International Standards 1
3 Definitions 2
3.1 Communication Model definitions 2
3.2 Directory Model definitions 2
4 Conventions 2
5 Definition of useful attribute sets 4
5.1 Telecommunication attribute set 4
5.2 Postal attribute set 4
5.3 Locale attribute set 4
5.4 Organizational attribute set 4
6 Definition of selected object classes 5
6.1 Country 5
6.2 Locality 5
6.3 Organization 5
6.4 Organizational Unit 5
6.5 Person 6
6.6 Organizational Person 6
6.7 Organizational Role 6
6.8 Group of Names 7
6.9 Group of Unique Names 7
6.10 Residential Person 7
6.11 Application Process 8
6.12 Application Entity 8
6.13 DSA 8
6.14 Device 9
6.15 Strong Authentication User 9
6.16 User Security Information 9
6.17 Certification Authority 10
6.18 Certification Authority-V2 10
6.19 DMD 10
6.20 OID Obj1 10
6.21 OID Obj2 11
6.22 OID ObjC 11
6.23 UII to URN 11
6.24 URN to URL 11
7 Definition of selected name forms 12
7.1 Country name form 12
7.2 Locality name form 12
7.3 State or Province name form 12
7.4 Organization name form 12
7.5 Organizational Unit name form 12
7.6 Person name form 13
7.7 Organizational Person name form 13
7.8 Organizational Role name form 13
7.9 Group of Names name form 13
7.10 Residential Person name form 13
7.11 Application Process name form 14
7.12 Application Entity name form 14
7.13 DSA name form 14

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

7.14 Device name form 14
7.15 DMD name form 14
7.16 OIDC1 name form 14
7.17 OIDC2 name form 15
7.18 OIDC name form 15
Annex A Selected object classes and name forms in ASN.1 16
Annex B Suggested name forms and DIT structures 27
B.1 Country 27
B.2 Organization 28
B.3 Locality 28
B.4 Organizational Unit 29
B.5 Organizational Person 29
B.6 Organizational Role 30
B.7 Group of Names 30
B.8 Residential Person 30
B.9 Application Entity 31
B.10 Device 31
B.11 Application Process 31
B.12 Alternative Structure Rule for Locality 31
Annex C Amendments and corrigenda 33

© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 9594-7:2008 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems,* in collaboration with ITU-T. The identical text is published as ITU-T Rec. X.521 (11/2008).

This sixth edition cancels and replaces the fifth edition (ISO/IEC 9594-7:2005), which has been technically revised.

ISO/IEC 9594 consists of the following parts, under the general title *Information technology — Open Systems Interconnection — The Directory*:

— *Part 1: Overview of concepts, models and services*

— *Part 2: Models*

— *Part 3: Abstract service definition*

— *Part 4: Procedures for distributed operation*

— *Part 5: Protocol specifications*

— *Part 6: Selected attribute types*

— *Part 7: Selected object classes*

— *Part 8: Public-key and attribute certificate frameworks*

— *Part 9: Replication*

— *Part 10: Use of systems management for administration of the Directory*

--`,,```,,,,````-`-`,,`,,`,`,,`---

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Introduction

This Recommendation | International Standard, together with other Recommendations | International Standards, has been produced to facilitate the interconnection of information processing systems to provide directory services. A set of such systems, together with the directory information that they hold, can be viewed as an integrated whole, called the *Directory*. The information held by the Directory, collectively known as the Directory Information Base (DIB), is typically used to facilitate communication between, with or about objects such as application entities, people, terminals, and distribution lists.

The Directory plays a significant role in Open Systems Interconnection, whose aim is to allow, with a minimum of technical agreement outside of the interconnection standards themselves, the interconnection of information processing systems:

- from different manufacturers;
- under different managements;
- of different levels of complexity; and
- of different ages.

This Recommendation | International Standard defines a number of attribute sets and object classes which may be found useful across a range of applications of the Directory.

This Recommendation | International Standard provides the foundation frameworks upon which industry profiles can be defined by other standards groups and industry forums. Many of the features defined as optional in these frameworks may be mandated for use in certain environments through profiles. This sixth edition technically revises and enhances, but does not replace, the fifth edition of this Recommendation | International Standard. Implementations may still claim conformance to the fifth edition. However, at some point, the fifth edition will not be supported (i.e., reported defects will no longer be resolved). It is recommended that implementations conform to this sixth edition as soon as possible.

This sixth edition specifies versions 1 and 2 of the Directory protocols.

The first and second editions specified only version 1. Most of the services and protocols specified in this edition are designed to function under version 1. However some enhanced services and protocols, e.g., signed errors, will not function unless all Directory entities involved in the operation have negotiated version 2. Whichever version has been negotiated, differences between the services and between the protocols defined in the six editions, except for those specifically assigned to version 2, are accommodated using the rules of extensibility defined in ITU-T Rec. X.519 | ISO/IEC 9594-5.

Annex A, which is an integral part of this Recommendation | International Standard, provides an ASN.1 module containing all of the type and value definitions which appear in this Recommendation | International Standard.

Annex B, which is not an integral part of this Recommendation | International Standard, provides some common naming and structure rules which may or may not be used by administrative authorities.

Annex C, which is not an integral part of this Recommendation | International Standard, lists the amendments and defect reports that have been incorporated to form this edition of this Recommendation | International Standard.

--`,,```,,,,````-`-`,,`,,`,`,,`---

© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

INTERNATIONAL STANDARD
ITU-T RECOMMENDATION

Information technology – Open Systems Interconnection – The Directory: Selected object classes

SECTION 1 – GENERAL

1 Scope

This Recommendation | International Standard defines a number of object classes and name forms which may be found useful across a range of applications of the Directory. The definition of an object class involves listing a number of attribute types which are relevant to objects of that class. The definition of a name form involves naming the object class to which it applies and listing the attributes to be used in forming names for objects of that class. These definitions are used by the administrative authority which is responsible for the management of the directory information.

Any administrative authority can define its own object classes or subclasses and name forms for any purpose.

NOTE 1 – Those definitions may or may not use the notation specified in ITU-T Rec. X.501 | ISO/IEC 9594-2.

NOTE 2 – It is recommended that an object class defined in this Recommendation | International Standard, or a subclass derived from one, or a name form defined in this Recommendation | International Standard, be used in preference to the generation of a new one, whenever the semantics is appropriate for the application.

Administrative authorities may support some or all the selected object classes and name forms, and may also add additional ones.

All administrative authorities shall support the object classes which the directory uses for its own purpose (the top, alias and DSA object classes).

2 Normative references

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent editions of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

2.1 Identical Recommendations | International Standards

- ITU-T Recommendation X.200 (1994) | ISO/IEC 7498-1:1994, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model.*
- ITU-T Recommendation X.500 (2008) | ISO/IEC 9594-1:2008, *Information technology – Open Systems Interconnection – The Directory: Overview of concepts, models and services.*
- ITU-T Recommendation X.501 (2008) | ISO/IEC 9594-2:2008, *Information technology – Open Systems Interconnection – The Directory: Models.*
- ITU-T Recommendation X.509 (2008) | ISO/IEC 9594-8:2008, *Information technology – Open Systems Interconnection – The Directory: Public-key and attribute certificate frameworks.*
- ITU-T Recommendation X.511 (2008) | ISO/IEC 9594-3:2008, *Information technology – Open Systems Interconnection – The Directory: Abstract service definition.*
- ITU-T Recommendation X.518 (2008) | ISO/IEC 9594-4:2008, *Information technology – Open Systems Interconnection – The Directory: Procedures for distributed operation.*
- ITU-T Recommendation X.519 (2008) | ISO/IEC 9594-5:2008, *Information technology – Open Systems Interconnection – The Directory: Protocol specifications.*

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

- ITU-T Recommendation X.520 (2008) | ISO/IEC 9594-6:2008, *Information technology – Open Systems Interconnection – The Directory: Selected attribute types.*
- ITU-T Recommendation X.525 (2008) | ISO/IEC 9594-9:2008, *Information technology – Open Systems Interconnection – The Directory: Replication.*
- ITU-T Recommendation X.530 (2008) | ISO/IEC 9594-10:2008, *Information technology – Open Systems Interconnection – The Directory: Use of systems management for administration of the Directory.*
- ITU-T Recommendation X.668 (2008) | ISO/IEC 9834-9:2008, *Information technology – Open Systems Interconnection – Procedures for the operation of OSI Registration Authorities: Registration of object identifier arcs for applications and services using tag-based identification.*
- ITU-T Recommendation X.680 (2008) | ISO/IEC 8824-1:2008, *Information technology – Abstract Syntax Notation One (ASN.1): Specification of basic notation.*
- ITU-T Recommendation X.681 (2008) | ISO/IEC 8824-2:2008, *Information technology – Abstract Syntax Notation One (ASN.1): Information object specification.*
- ITU-T Recommendation X.682 (2008) | ISO/IEC 8824-3:2008, *Information technology – Abstract Syntax Notation One (ASN.1): Constraint specification.*
- ITU-T Recommendation X.683 (2008) | ISO/IEC 8824-4:2008, *Information technology – Abstract Syntax Notation One (ASN.1): Parameterization of ASN.1 specifications.*

3 Definitions

For the purposes of this Recommendation | International Standard, the following definitions apply.

3.1 Communication Model definitions

The following terms are defined in ITU-T Rec. X.519 | ISO/IEC 9594-5.

a) *application-entity*;

b) *application process*.

3.2 Directory Model definitions

The following terms are defined in ITU-T Rec. X.501 | ISO/IEC 9594-2:

a) *attribute*;

b) *attribute type*;

c) *Directory Information Tree (DIT)*;

d) *Directory System Agent (DSA)*;

e) *attribute set*;

f) *entry*;

g) *name*;

h) *object class*;

i) *subclass*;

j) *name form*;

k) *structure rule*.

4 Conventions

The term "Directory Specification" (as in "this Directory Specification") shall be taken to mean ITU-T Rec. X.521 | ISO/IEC 9594-7. The term "Directory Specifications" shall be taken to mean the X.500-series Recommendations and all parts of ISO/IEC 9594.

This Directory Specification uses the term *first edition systems* to refer to systems conforming to the first edition of the Directory Specifications, i.e., the 1988 edition of the series of CCITT X.500 Recommendations and the ISO/IEC 9594:1990 edition.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

This Directory Specification uses the term *second edition systems* to refer to systems conforming to the second edition of the Directory Specifications, i.e., the 1993 edition of the series of ITU-T X.500 Recommendations and the ISO/IEC 9594:1995 edition.

This Directory Specification uses the term *third edition systems* to refer to systems conforming to the third edition of the Directory Specifications, i.e., the 1997 edition of the series of ITU-T X.500 Recommendations and the ISO/IEC 9594:1998 edition.

This Directory Specification uses the term *fourth edition systems* to refer to systems conforming to the fourth edition of the Directory Specifications, i.e., the 2001 editions of ITU-T Recs X.500, X.501, X.511, X.518, X.519, X.520, X.521, X.525, and X.530, the 2000 edition of ITU-T Rec. X.509, and parts 1-10 of the ISO/IEC 9594:2001 edition.

This Directory Specification uses the term *fifth edition systems* to refer to systems conforming to the fifth edition of the Directory Specifications, i.e., the 2005 editions of the series of ITU-T X.500 Recommendations and the ISO/IEC 9594:2005 edition.

This Directory Specification uses the term *sixth edition systems* to refer to systems conforming to the sixth edition of the Directory Specifications, i.e., the 2008 editions of the series of ITU-T X.500 Recommendations and the ISO/IEC 9594:2008 edition.

This Directory Specification presents ASN.1 notation in the bold Helvetica typeface. When ASN.1 types and values are referenced in normal text, they are differentiated from normal text by presenting them in the bold Helvetica typeface. The names of procedures, typically referenced when specifying the semantics of processing, are differentiated from normal text by displaying them in bold Times. Access control permissions are presented in italicized Times.

Object classes and name forms are defined in this Directory Specification as values of the **OBJECT-CLASS** and **NAME-FORM** information object classes defined in ITU-T Rec. X.501 | ISO/IEC 9594-2.

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

SECTION 2 – SELECTED OBJECT CLASSES

5 Definition of useful attribute sets

5.1 Telecommunication attribute set

This set of attributes is used to define those which are commonly used for business communications.

```
TelecommunicationAttributeSet ATTRIBUTE ::= {
        facsimileTelephoneNumber |
        internationalISDNNumber |
        telephoneNumber |
--      teletexTerminalIdentifier |          Attribute type has been deleted
        telexNumber |
        preferredDeliveryMethod |
        destinationIndicator |
        registeredAddress |
        x121Address }
```

5.2 Postal attribute set

This set of attributes is used to define those which are directly associated with postal delivery.

```
PostalAttributeSet ATTRIBUTE ::= {
        physicalDeliveryOfficeName |
        postalAddress |
        postalCode |
        postOfficeBox |
        streetAddress }
```

5.3 Locale attribute set

This set of attributes is used to define those which are commonly used for search purposes to indicate the locale of an object.

```
LocaleAttributeSet ATTRIBUTE ::= {
        localityName |
        stateOrProvinceName |
        streetAddress }
```

5.4 Organizational attribute set

This set of attributes is used to define the attributes that an organization or organizational unit may typically possess.

```
OrganizationalAttributeSet ATTRIBUTE ::= {
        description |
        LocaleAttributeSet |
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

PostalAttributeSet |

TelecommunicationAttributeSet |

businessCategory |

seeAlso |

searchGuide |

userPassword }

6 Definition of selected object classes

6.1 Country

A *Country* object class is used to define country entries in the DIT.

country OBJECT-CLASS ::= {

SUBCLASS OF	**{ top }**
MUST CONTAIN	**{ countryName }**
MAY CONTAIN	**{ description | searchGuide }**
ID	**id-oc-country }**

6.2 Locality

The *Locality* object class is used to define locality in the DIT.

locality OBJECT-CLASS ::= {

SUBCLASS OF	**{ top }**
MAY CONTAIN	**{ description |**
	searchGuide |
	LocaleAttributeSet |
	seeAlso }
ID	**id-oc-locality }**

At least one of Locality Name or State or Province Name shall be present.

6.3 Organization

The *Organization* object class is used to define organization entries in the DIT.

organization OBJECT-CLASS ::= {

SUBCLASS OF	**{ top }**
MUST CONTAIN	**{ organizationName }**
MAY CONTAIN	**{ OrganizationalAttributeSet }**
ID	**id-oc-organization }**

6.4 Organizational Unit

The *Organizational Unit* object class is used to define entries representing subdivisions of organizations.

organizationalUnit OBJECT-CLASS ::= {

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

SUBCLASS OF **{ top }**

MUST CONTAIN **{ organizationalUnitName }**

MAY CONTAIN **{ OrganizationalAttributeSet }**

ID **id-oc-organizationalUnit }**

6.5 Person

The *Person* object class is used to define entries representing people generically.

person OBJECT-CLASS ::= {

SUBCLASS OF **{ top }**

MUST CONTAIN **{ commonName | surname }**

MAY CONTAIN **{ description |**
telephoneNumber |
userPassword |
seeAlso }

ID **id-oc-person }**

6.6 Organizational Person

The *Organizational Person* object class is used to define entries representing people employed by, or in some other important way associated with, an organization.

organizationalPerson OBJECT-CLASS ::= {

SUBCLASS OF **{ person }**

MAY CONTAIN **{ LocaleAttributeSet |**
PostalAttributeSet |
TelecommunicationAttributeSet |
organizationalUnitName |
title }

ID **id-oc-organizationalPerson }**

6.7 Organizational Role

The *Organizational Role* object class is used to define entries representing an organizational role, i.e., a position or role within an organization. An organizational role is normally considered to be filled by a particular organizational person. Over its lifetime, however, an organizational role may be filled by a number of different organizational people in succession. In general, an organizational role may be filled by a person or a non-human entity.

organizationalRole OBJECT-CLASS ::= {

SUBCLASS OF **{ top }**

MUST CONTAIN **{ commonName }**

MAY CONTAIN **{ description |**
LocaleAttributeSet |
organizationalUnitName |
PostalAttributeSet |
preferredDeliveryMethod |
roleOccupant |

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
                    seeAlso |
                    TelecommunicationAttributeSet }
    ID              id-oc-organizationalRole }
```

6.8 Group of Names

The *Group Of Names* object class is used to define entries representing an unordered set of names which represent individual objects or other groups of names. The membership of a group is static, i.e., it is explicitly modified by administrative action, rather than dynamically determined each time the group is referred to.

The membership of a group can be reduced to a set of individual object's names by replacing each group with its membership. This process could be carried out recursively until all constituent group names have been eliminated, and only the names of individual objects remain.

```
groupOfNames  OBJECT-CLASS  ::= {
    SUBCLASS OF     { top }
    MUST CONTAIN    { commonName | member }
    MAY CONTAIN     { description |
                    organizationName |
                    organizationalUnitName |
                    owner |
                    seeAlso |
                    businessCategory }
    ID              id-oc-groupOfNames }
```

6.9 Group of Unique Names

The *Group Of Unique Names* object class is used to define entries representing an unordered set of names whose integrity can be assured and which represent individual objects or other groups of names. The membership of a group is static, i.e., it is explicitly modified by administrative action, rather than dynamically determined each time the group is referred to.

```
groupOfUniqueNames  OBJECT-CLASS  ::= {
    SUBCLASS OF     { top }
    MUST CONTAIN    { commonName | uniqueMember }
    MAY CONTAIN     { description |
                    organizationName |
                    organizationalUnitName |
                    owner |
                    seeAlso |
                    businessCategory }
    ID              id-oc-groupOfUniqueNames }
```

6.10 Residential Person

The *Residential Person* object class is used to define entries representing a person in the residential environment.

```
residentialPerson  OBJECT-CLASS  ::= {
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

SUBCLASS OF **{ person }**

MUST CONTAIN **{ localityName }**

MAY CONTAIN **{ LocaleAttributeSet |**
PostalAttributeSet |
preferredDeliveryMethod |
TelecommunicationAttributeSet |
businessCategory }

ID **id-oc-residentialPerson }**

6.11 Application Process

The *Application Process* object class is used to define entries representing application processes. An application process is an element within a real open-system which performs the information processing for a particular application (see ITU-T Rec. X.200 | ISO/IEC 7498-1).

applicationProcess OBJECT-CLASS ::= {

SUBCLASS OF **{ top }**

MUST CONTAIN **{ commonName }**

MAY CONTAIN **{ description |**
localityName |
organizationalUnitName |
seeAlso }

ID **id-oc-applicationProcess }**

6.12 Application Entity

The *Application Entity* object class is used to define entries representing application-entities. An application-entity consists of those aspects of an application process pertinent to communications.

applicationEntity OBJECT-CLASS ::= {

SUBCLASS OF **{ top }**

MUST CONTAIN **{ commonName | presentationAddress }**

MAY CONTAIN **{ description |**
localityName |
organizationName |
organizationalUnitName |
seeAlso |
supportedApplicationContext }

ID **id-oc-applicationEntity }**

NOTE – If an application-entity is represented as a Directory object that is distinct from an application process, the **commonName** attribute is used to carry the value of the Application Entity Qualifier.

6.13 DSA

The *DSA* object class is used to define entries representing DSAs. A DSA is as defined in ITU-T Rec. X.501 | ISO/IEC 9594-2.

dSA OBJECT-CLASS ::= {

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

SUBCLASS OF **{ applicationEntity }**

MAY CONTAIN **{ knowledgeInformation }**

ID **id-oc-dSA }**

6.14 Device

The *Device* object class is used to define entries representing devices. A device is a physical unit which can communicate, such as a modem, disk drive, etc.

device OBJECT-CLASS ::= {

SUBCLASS OF **{ top }**

MUST CONTAIN **{ commonName }**

MAY CONTAIN **{ description |**

localityName |

organizationName |

organizationalUnitName |

owner |

seeAlso |

serialNumber }

ID **id-oc-device }**

NOTE – At least one of **localityName**, **serialNumber**, **owner**, should be included. The choice is dependent on device type.

6.15 Strong Authentication User

The *Strong Authentication User* object class is used to define entries for objects which participate in strong authentication, as defined in ITU-T Rec. X.509 | ISO/IEC 9594-8.

strongAuthenticationUser OBJECT-CLASS ::= {

SUBCLASS OF **{ top }**

KIND **auxiliary**

MUST CONTAIN **{ userCertificate }**

ID **id-oc-strongAuthenticationUser }**

NOTE – Use of this object class has been deprecated in favour of the **pkiUser** and **pkiCA** object classes defined in ITU-T Rec. X.509 | ISO/IEC 9594-8. Implementations that use **strongAuthenticationUser**, **certificationAuthority** and **certificationAuthorityv2** object classes are still conformant to the standard, although new implementations are strongly recommended to move to the **pkiUser** and **pkiCA** object classes.

6.16 User Security Information

The *User Security Information* object class is used to define entries for objects which need to indicate security information associated with them as defined in ITU-T Rec. X.509 | ISO/IEC 9594-8.

userSecurityInformation OBJECT-CLASS ::= {

SUBCLASS OF **{ top }**

KIND **auxiliary**

MAY CONTAIN **{ supportedAlgorithms }**

ID **id-oc-userSecurityInformation }**

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

6.17 Certification Authority

The *Certification Authority* object class is used to define entries for objects which act as certification authorities, as defined in ITU-T Rec. X.509 | ISO/IEC 9594-8.

certificationAuthority OBJECT-CLASS ::= {

SUBCLASS OF **{ top }**

KIND **auxiliary**

MUST CONTAIN **{ cACertificate |**

certificateRevocationList |

authorityRevocationList }

MAY CONTAIN **{ crossCertificatePair }**

ID **id-oc-certificationAuthority }**

NOTE – Use of this object class has been deprecated in favour of the **pkiUser** and **pkiCA** object classes defined in ITU-T Rec. X.509 | ISO/IEC 9594-8. Implementations that use **strongAuthenticationUser**, **certificationAuthority** and **certificationAuthorityv2** object classes are still conformant to the standard, although new implementations are strongly recommended to move to the **pkiUser** and **pkiCA** object classes.

6.18 Certification Authority-V2

The *Certification Authority-V2* object class is used to define entries for objects which act as certification authorities and can support the delta revocation list as defined in ITU-T Rec. X.509 | ISO/IEC 9594-8.

certificationAuthority-V2 OBJECT-CLASS ::= {

SUBCLASS OF **{ certificationAuthority }**

KIND **auxiliary**

MAY CONTAIN **{ deltaRevocationList }**

ID **id-oc-certificationAuthority-V2 }**

NOTE – Use of this object class has been deprecated in favour of the **pkiUser** and **pkiCA** object classes defined in ITU-T Rec. X.509 | ISO/IEC 9594-8. Implementations that use **strongAuthenticationUser**, **certificationAuthority** and **certificationAuthorityv2** object classes are still conformant to the standard, although new implementations are strongly recommended to move to the **pkiUser** and **pkiCA** object classes.

6.19 DMD

The *DMD* object class is used to define DMD entries in the DIT.

dMD OBJECT-CLASS ::= {

SUBCLASS OF **{ top }**

MUST CONTAIN **{ dmdName }**

MAY CONTAIN **{ OrganizationalAttributeSet }**

ID **id-oc-dmd }**

6.20 OID Obj1

The *OID Obj1* object class is used to define a top level object identifier component entry in the DIT.

oidC1obj OBJECT-CLASS ::= {

SUBCLASS OF **{ top }**

MUST CONTAIN **{ oidC1 }**

ID **id-oc-oidC1obj }**

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

6.21 OID Obj2

The *OID Obj2* object class is used to define second level object identifier component entries in the DIT.

oidC2obj OBJECT-CLASS ::= {

SUBCLASS OF	**{ top }**
MUST CONTAIN	**{ oidC2 }**
ID	**id-oc-oidC2obj }**

6.22 OID ObjC

The *OID ObjC* object class is used to define the third or lower level object identifier component entries in the DIT.

NOTE – A tag-based object identifier typically only have only three levels, where the first two values are { 2 27 }.

oidCobj OBJECT-CLASS ::= {

SUBCLASS OF	**{ top }**
MUST CONTAIN	**{ oidC }**
ID	**id-oc-oidCobj }**

6.23 UII to URN

The *UII to URN* auxiliary object class may used to together with the **oidCobj** object class to provide entry support for tag-based identification (see Annex G of ITU-T Rec. X.520 | ISO/IEC 9594-6). If this auxiliary object class is not used together with the **oidCobj** object class, the **tagOid** attribute shall be present. It provides information about how a UII may be formatted to be globally unique in URN format.

uiiToUrn OBJECT-CLASS ::= {

SUBCLASS OF	**{ top }**
KIND	**auxiliary**
MUST CONTAIN	**{ uiiFormat }**
MAY CONTAIN	**{ tagOid }**
ID	**id-oc-uiiToUrn }**

6.24 URN to URL

The *URN to URL* auxiliary object class is used to add attributes to an entry holding a URL to associated information content related to an identifier and/or the associated information content itself.

urnToUrl OBJECT-CLASS ::= {

SUBCLASS OF	**{ top }**
KIND	**auxiliary**
MUST CONTAIN	**{ uiiInUrn | contentUrl }**
MAY CONTAIN	**{ tagOid }**
ID	**id-oc-urnToUrl }**

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

SECTION 3 – SELECTED NAME FORMS

7 Definition of selected name forms

7.1 Country name form

The *Country* name form specifies how entries of object class **country** may be named.

```
countryNameForm  NAME-FORM  ::= {
        NAMES                   country
        WITH ATTRIBUTES         { countryName }
        ID                      id-nf-countryNameForm }
```

7.2 Locality name form

The *Locality* name form specifies how entries of object class **locality** may be named.

```
locNameForm  NAME-FORM  ::= {
        NAMES                   locality
        WITH ATTRIBUTES         { localityName }
        ID                      id-nf-locNameForm }
```

7.3 State or Province name form

The *State or Province* name form specifies how entries of object class **locality** may be named.

```
sOPNameForm  NAME-FORM  ::= {
        NAMES                   locality
        WITH ATTRIBUTES         { stateOrProvinceName }
        ID                      id-nf-sOPNameForm }
```

7.4 Organization name form

The *Organization* name form specifies how entries of object class **organization** may be named.

```
orgNameForm  NAME-FORM  ::= {
        NAMES                   organization
        WITH ATTRIBUTES         { organizationName }
        ID                      id-nf-orgNameForm }
```

7.5 Organizational Unit name form

The *Organizational Unit* name form specifies how entries of object class **organizationalUnit** may be named.

```
orgUnitNameForm  NAME-FORM  ::= {
        NAMES                   organizationalUnit
        WITH ATTRIBUTES         { organizationalUnitName }
        ID                      id-nf-orgUnitNameForm }
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

7.6 Person name form

The *Person* name form specifies how entries of object class **person** may be named.

```
personNameForm  NAME-FORM  ::= {
        NAMES                   person
        WITH ATTRIBUTES         { commonName }
        ID                      id-nf-personNameForm }
```

7.7 Organizational Person name form

The *Organizational Person* name form specifies how entries of object class **organizationalPerson** may be named.

```
orgPersonNameForm  NAME-FORM  ::= {
        NAMES                   organizationalPerson
        WITH ATTRIBUTES         { commonName }
        AND OPTIONALLY { organizationalUnitName }
        ID                      id-nf-orgPersonNameForm }
```

7.8 Organizational Role name form

The *Organizational Role* name form specifies how entries of object class **organizationalRole** may be named.

```
orgRoleNameForm  NAME-FORM  ::= {
        NAMES                   organizationalRole
        WITH ATTRIBUTES         { commonName }
        ID                      id-nf-orgRoleNameForm }
```

7.9 Group of Names name form

The *Group of Names* name form specifies how entries of object class **groupOfNames** may be named.

```
gONNameForm  NAME-FORM  ::= {
        NAMES                   groupOfNames
        WITH ATTRIBUTES         { commonName }
        ID                      id-nf-gONNameForm }
```

7.10 Residential Person name form

The *Residential Person* name form specifies how entries of object class **residentialPerson** may be named.

```
resPersonNameForm  NAME-FORM  ::= {
        NAMES                   residentialPerson
        WITH ATTRIBUTES         { commonName }
        AND OPTIONALLY { streetAddress }
        ID                      id-nf-resPersonNameForm }
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

7.11 Application Process name form

The *Application Process* name form specifies how entries of object class **applicationProcess** may be named.

applProcessNameForm NAME-FORM ::= {

NAMES	**applicationProcess**
WITH ATTRIBUTES	**{ commonName }**
ID	**id-nf-applProcessNameForm }**

7.12 Application Entity name form

The *Application Entity* name form specifies how entries of object class **applicationEntity** may be named.

applEntityNameForm NAME-FORM ::= {

NAMES	**applicationEntity**
WITH ATTRIBUTES	**{ commonName }**
ID	**id-nf-applEntityNameForm }**

7.13 DSA name form

The *DSA* name form specifies how entries of object class **dSA** may be named.

dSANameForm NAME-FORM ::= {

NAMES	**dSA**
WITH ATTRIBUTES	**{ commonName }**
ID	**id-nf-dSANameForm }**

7.14 Device name form

The *Device* name form specifies how entries of object class **device** may be named.

deviceNameForm NAME-FORM ::= {

NAMES	**device**
WITH ATTRIBUTES	**{ commonName }**
ID	**id-nf-deviceNameForm }**

7.15 DMD name form

The *DMD* name form specifies how entries of object class **dMD** may be named.

dMDNameForm NAME-FORM ::= {

NAMES	**dMD**
WITH ATTRIBUTES	**{ dmdName }**
ID	**id-nf-dMDNameForm }**

7.16 OIDC1 name form

The *OIDC1* name form specifies how the entry of object class **oidObj1** shall be named.

oidC1NameForm NAME-FORM ::= {

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

NAMES **oidC1obj**

WITH ATTRIBUTES **{ oidC1 }**

ID **id-nf-oidC1NameForm }**

7.17 OIDC2 name form

The *OIDC2* name form specifies how entries of object class **oidObj2** shall be named.

oidC2NameForm NAME-FORM ::= {

NAMES **oidC2obj**

WITH ATTRIBUTES **{ oidC2 }**

ID **id-nf-oidC2NameForm }**

7.18 OIDC name form

The *OIDC* name form specifies how entries of object class **oidObjC** shall be named.

oidCNameForm NAME-FORM ::= {

NAMES **oidCobj**

WITH ATTRIBUTES **{ oidC }**

ID **id-nf-oidNameForm }**

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Annex A

Selected object classes and name forms in ASN.1

(This annex forms an integral part of this Recommendation | International Standard)

This annex includes all of the ASN.1 type and value definitions contained in this Directory Specification in the form of the ASN.1 module **SelectedObjectClasses**.

```
SelectedObjectClasses {joint-iso-itu-t ds(5) module(1) selectedObjectClasses(6) 6}

DEFINITIONS ::=

BEGIN

-- EXPORTS All --
-- The types and values defined in this module are exported for use in the other ASN.1 modules contained
-- within the Directory Specifications, and for the use of other applications which will use them to access
-- Directory services. Other applications may use them for their own purposes, but this will not constrain
-- extensions and modifications needed to maintain or improve the Directory service.

IMPORTS

-- from ITU-T Rec. X.501 | ISO/IEC 9594-2

    authenticationFramework, certificateExtensions, id-nf, id-oc,informationFramework,
    objectClass, selectedAttributeTypes
        FROM  UsefulDefinitions {joint-iso-itu-t ds(5) module(1) usefulDefinitions(0) 6}

    alias, ATTRIBUTE, NAME-FORM, OBJECT-CLASS, top
        FROM  InformationFramework informationFramework

-- from ITU-T Rec. X.520 | ISO/IEC 9594-6

    businessCategory, commonName, contentUri, countryName, description, destinationIndicator,
    dmdName, facsimileTelephoneNumber, internationalISDNNumber, knowledgeInformation,
    localityName, member, organizationalUnitName, organizationName, owner,
    physicalDeliveryOfficeName,          postalAddress, postalCode, postOfficeBox, preferredDeliveryMethod,
    presentationAddress, registeredAddress, roleOccupant, searchGuide, seeAlso, serialNumber,
    stateOrProvinceName, streetAddress, supportedApplicationContext, surname, tagOid,
    telephoneNumber, telexNumber, title, uiiFormat, uiiInUrn, uniqueMember, x121Address
        FROM SelectedAttributeTypes selectedAttributeTypes

-- from ITU-T Rec. X.509 | ISO/IEC 9594-8

    authorityRevocationList, cACertificate, certificateRevocationList, crossCertificatePair,
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
        deltaRevocationList, supportedAlgorithms, userCertificate, userPassword
                FROM AuthenticationFramework authenticationFramework

-- from ITU-T Rec. X.660 | ISO/IEC 9834-1

        oidC, oidC1, oidC2
                FROM OidDirectoryNameDef {joint-iso-itu-t registration-procedures(17) module(1)
                        oidDirectoryNameDef(1)}     ;


-- Attribute sets --

TelecommunicationAttributeSet ATTRIBUTE ::= {
        facsimileTelephoneNumber |
        internationalISDNNumber |
        telephoneNumber |
--      teletexTerminalIdentifier |     Attribute type has been deleted
        telexNumber |
        preferredDeliveryMethod |
        destinationIndicator |
        registeredAddress |
        x121Address }

PostalAttributeSet ATTRIBUTE ::= {
        physicalDeliveryOfficeName |
        postalAddress |
        postalCode |
        postOfficeBox |
        streetAddress }

LocaleAttributeSet ATTRIBUTE ::= {
        localityName |
        stateOrProvinceName |
        streetAddress }

OrganizationalAttributeSet ATTRIBUTE ::= {
        description |
        LocaleAttributeSet |
        PostalAttributeSet |
        TelecommunicationAttributeSet |
        businessCategory |
        seeAlso |
```


--`,,```,,,,````-`-`,,`,,`,`,,`---
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
        searchGuide |
        userPassword }

-- Object classes --

country OBJECT-CLASS ::= {
        SUBCLASS OF     { top }
        MUST CONTAIN    { countryName }
        MAY CONTAIN     { description | searchGuide }
        ID              id-oc-country }

locality OBJECT-CLASS ::= {
        SUBCLASS OF     { top }
        MAY CONTAIN     { description |
                          searchGuide |
                          LocaleAttributeSet |
                          seeAlso }
        ID              id-oc-locality }

organization OBJECT-CLASS ::= {
        SUBCLASS OF     { top }
        MUST CONTAIN    { organizationName }
        MAY CONTAIN     { OrganizationalAttributeSet }
        ID              id-oc-organization }

organizationalUnit OBJECT-CLASS ::= {
        SUBCLASS OF     { top }
        MUST CONTAIN    { organizationalUnitName }
        MAY CONTAIN     { OrganizationalAttributeSet }
        ID              id-oc-organizationalUnit }

person OBJECT-CLASS ::= {
        SUBCLASS OF     { top }
        MUST CONTAIN    { commonName | surname }
        MAY CONTAIN     { description |
                          telephoneNumber |
                          userPassword |
                          seeAlso }
        ID              id-oc-person }

organizationalPerson OBJECT-CLASS ::= {
        SUBCLASS OF     { person }
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
        MAY CONTAIN     { LocaleAttributeSet |
                          PostalAttributeSet |
                          TelecommunicationAttributeSet |
                          organizationalUnitName |
                          title }
        ID              id-oc-organizationalPerson }

organizationalRole  OBJECT-CLASS  ::=  {
        SUBCLASS OF     { top }
        MUST CONTAIN    { commonName }
        MAY CONTAIN     { description |
                          LocaleAttributeSet |
                          organizationalUnitName |
                          PostalAttributeSet |
                          preferredDeliveryMethod |
                          roleOccupant |
                          seeAlso |
                          TelecommunicationAttributeSet }
        ID              id-oc-organizationalRole }

groupOfNames  OBJECT-CLASS  ::=  {
        SUBCLASS OF     { top }
        MUST CONTAIN    { commonName | member }
        MAY CONTAIN     { description |
                          organizationName |
                          organizationalUnitName |
                          owner |
                          seeAlso |
                          businessCategory }
        ID              id-oc-groupOfNames }

groupOfUniqueNames  OBJECT-CLASS  ::=  {
        SUBCLASS OF     { top }
        MUST CONTAIN    { commonName | uniqueMember }
        MAY CONTAIN     { description |
                          organizationName |
                          organizationalUnitName |
                          owner |
                          seeAlso |
                          businessCategory }
        ID              id-oc-groupOfUniqueNames }
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
residentialPerson  OBJECT-CLASS  ::=  {
        SUBCLASS OF       { person }
        MUST CONTAIN      { localityName }
        MAY CONTAIN       { LocaleAttributeSet |
                          PostalAttributeSet |
                          preferredDeliveryMethod |
                          TelecommunicationAttributeSet |
                          businessCategory }
        ID                id-oc-residentialPerson }

applicationProcess  OBJECT-CLASS  ::=  {
        SUBCLASS OF       { top }
        MUST CONTAIN      { commonName }
        MAY CONTAIN       { description |
                          localityName |
                          organizationalUnitName |
                          seeAlso }
        ID                id-oc-applicationProcess }

applicationEntity  OBJECT-CLASS  ::=  {
        SUBCLASS OF       { top }
        MUST CONTAIN      { commonName | presentationAddress }
        MAY CONTAIN       { description |
                          localityName |
                          organizationName |
                          organizationalUnitName |
                          seeAlso |
                          supportedApplicationContext }
        ID                id-oc-applicationEntity }

dSA  OBJECT-CLASS  ::=  {
        SUBCLASS OF       { applicationEntity }
        MAY CONTAIN       { knowledgeInformation }
        ID                id-oc-dSA }

device  OBJECT-CLASS  ::=  {
        SUBCLASS OF       { top }
        MUST CONTAIN      { commonName }
        MAY CONTAIN       { description |
                          localityName |
                          organizationName |
                          organizationalUnitName |
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
                    owner |
                    seeAlso |
                    serialNumber }
    ID              id-oc-device }

strongAuthenticationUser OBJECT-CLASS ::= {
    SUBCLASS OF     { top }
    KIND            auxiliary
    MUST CONTAIN    { userCertificate }
    ID              id-oc-strongAuthenticationUser }

userSecurityInformation OBJECT-CLASS ::= {
    SUBCLASS OF     { top }
    KIND            auxiliary
    MAY CONTAIN     { supportedAlgorithms }
    ID              id-oc-userSecurityInformation }

certificationAuthority OBJECT-CLASS ::= {
    SUBCLASS OF     { top }
    KIND            auxiliary
    MUST CONTAIN    { cACertificate |
                    certificateRevocationList |
                    authorityRevocationList }
    MAY CONTAIN     { crossCertificatePair }
    ID              id-oc-certificationAuthority }

certificationAuthority-V2 OBJECT-CLASS ::= {
    SUBCLASS OF     { certificationAuthority }
    KIND            auxiliary
    MAY CONTAIN     { deltaRevocationList }
    ID              id-oc-certificationAuthority-V2 }

dMD OBJECT-CLASS ::= {
    SUBCLASS OF     { top }
    MUST CONTAIN    { dmdName }
    MAY CONTAIN     { OrganizationalAttributeSet }
    ID              id-oc-dmd }

oidC1obj OBJECT-CLASS ::= {
    SUBCLASS OF     { top }
    MUST CONTAIN    { oidC1 }
    ID              id-oc-oidC1obj }
```

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
oidC2obj  OBJECT-CLASS  ::=  {
        SUBCLASS OF       { top }
        MUST CONTAIN      { oidC2 }
        ID                id-oc-oidC2obj }

oidCobj  OBJECT-CLASS  ::=  {
        SUBCLASS OF       { top }
        MUST CONTAIN      { oidC }
        ID                id-oc-oidCobj }

uiiToUrn  OBJECT-CLASS  ::=  {
        SUBCLASS OF       { top }
        KIND              auxiliary
        MUST CONTAIN      { uiiFormat }
        MAY CONTAIN       { tagOid }
        ID                id-oc-uiiToUrn }

urnToUrl  OBJECT-CLASS  ::=  {
        SUBCLASS OF       { top }
        KIND              auxiliary
        MUST CONTAIN      { uiiInUrn | contentUri }
        MAY CONTAIN       { tagOid }
        ID                id-oc-urnToUri }

-- Name forms --

countryNameForm  NAME-FORM  ::=  {
        NAMES             country
        WITH ATTRIBUTES   { countryName }
        ID                id-nf-countryNameForm }

locNameForm  NAME-FORM  ::=  {
        NAMES             locality
        WITH ATTRIBUTES   { localityName }
        ID                id-nf-locNameForm }

sOPNameForm  NAME-FORM  ::=  {
        NAMES             locality
        WITH ATTRIBUTES   { stateOrProvinceName }
        ID                id-nf-sOPNameForm }
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
orgNameForm NAME-FORM ::= {
        NAMES                   organization
        WITH ATTRIBUTES         { organizationName }
        ID                      id-nf-orgNameForm }

orgUnitNameForm NAME-FORM ::= {
        NAMES                   organizationalUnit
        WITH ATTRIBUTES         { organizationalUnitName }
        ID                      id-nf-orgUnitNameForm }

personNameForm NAME-FORM ::= {
        NAMES                   person
        WITH ATTRIBUTES         { commonName }
        ID                      id-nf-personNameForm }

orgPersonNameForm NAME-FORM ::= {
        NAMES                   organizationalPerson
        WITH ATTRIBUTES         { commonName }
        AND OPTIONALLY { organizationalUnitName }
        ID                      id-nf-orgPersonNameForm }

orgRoleNameForm NAME-FORM ::= {
        NAMES                   organizationalRole
        WITH ATTRIBUTES         { commonName }
        ID                      id-nf-orgRoleNameForm }

gONNameForm NAME-FORM ::= {
        NAMES                   groupOfNames
        WITH ATTRIBUTES         { commonName }
        ID                      id-nf-gONNameForm }

resPersonNameForm NAME-FORM ::= {
        NAMES                   residentialPerson
        WITH ATTRIBUTES         { commonName }
        AND OPTIONALLY { streetAddress }
        ID                      id-nf-resPersonNameForm }

applProcessNameForm NAME-FORM ::= {
        NAMES                   applicationProcess
        WITH ATTRIBUTES         { commonName }
        ID                      id-nf-applProcessNameForm }
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
applEntityNameForm  NAME-FORM  ::= {
        NAMES                   applicationEntity
        WITH ATTRIBUTES         { commonName }
        ID                      id-nf-applEntityNameForm }

dSANameForm  NAME-FORM  ::= {
        NAMES                   dSA
        WITH ATTRIBUTES         { commonName }
        ID                      id-nf-dSANameForm }

deviceNameForm  NAME-FORM  ::= {
        NAMES                   device
        WITH ATTRIBUTES         { commonName }
        ID                      id-nf-deviceNameForm }

dMDNameForm  NAME-FORM  ::= {
        NAMES                   dMD
        WITH ATTRIBUTES         { dmdName }
        ID                      id-nf-dMDNameForm }

oidC1NameForm  NAME-FORM  ::= {
        NAMES                   oidC1obj
        WITH ATTRIBUTES         { oidC1 }
        ID                      id-nf-oidC1NameForm }

oidC2NameForm  NAME-FORM  ::= {
        NAMES                   oidC2obj
        WITH ATTRIBUTES         { oidC2 }
        ID                      id-nf-oidC2NameForm }

oidCNameForm  NAME-FORM  ::= {
        NAMES                   oidCobj
        WITH ATTRIBUTES         { oidC }
        ID                      id-nf-oidCNameForm }

-- Object identifier assignments --
-- object identifiers assigned in other modules are shown in comments

-- Object classes --

-- id-oc-top                    OBJECT IDENTIFIER ::=   {id-oc 0}Defined in ITU-T Rec. X.501 |
--                                                                                  ISO/IEC 9594-2
```

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
-- id-oc-alias                    OBJECT IDENTIFIER ::= {id-oc 1}Defined in ITU-T Rec. X.501 |
--                                                                                ISO/IEC 9594-2

id-oc-country                     OBJECT IDENTIFIER ::= {id-oc 2}
id-oc-locality                    OBJECT IDENTIFIER ::= {id-oc 3}
id-oc-organization                OBJECT IDENTIFIER ::= {id-oc 4}
id-oc-organizationalUnit          OBJECT IDENTIFIER ::= {id-oc 5}
id-oc-person                      OBJECT IDENTIFIER ::= {id-oc 6}
id-oc-organizationalPerson        OBJECT IDENTIFIER ::= {id-oc 7}
id-oc-organizationalRole          OBJECT IDENTIFIER ::= {id-oc 8}
id-oc-groupOfNames                OBJECT IDENTIFIER ::= {id-oc 9}
id-oc-residentialPerson           OBJECT IDENTIFIER ::= {id-oc 10}
id-oc-applicationProcess          OBJECT IDENTIFIER ::= {id-oc 11}
id-oc-applicationEntity           OBJECT IDENTIFIER ::= {id-oc 12}
id-oc-dSA                         OBJECT IDENTIFIER ::= {id-oc 13}
id-oc-device                      OBJECT IDENTIFIER ::= {id-oc 14}
id-oc-strongAuthenticationUser    OBJECT IDENTIFIER ::= {id-oc 15}    -- Deprecated, see 6.15
id-oc-certificationAuthority      OBJECT IDENTIFIER ::= {id-oc 16}    -- Deprecated, see 6.17
id-oc-certificationAuthority-V2   OBJECT IDENTIFIER ::= {id-oc 16 2}  -- Deprecated, see 6.18
id-oc-groupOfUniqueNames          OBJECT IDENTIFIER ::= {id-oc 17}
id-oc-userSecurityInformation     OBJECT IDENTIFIER ::= {id-oc 18}
-- id-oc-cRLDistributionPoint     OBJECT IDENTIFIER ::= {id-oc 19}    Defined in ITU-T Rec. X.509 |
--                                                                                ISO/IEC 9594-8
id-oc-dmd                         OBJECT IDENTIFIER ::= {id-oc 20}
-- id-oc-pkiUser                  OBJECT IDENTIFIER ::= {id-oc 21}    Defined in ITU-T Rec. X.509 |
--                                                                                ISO/IEC 9594-8
-- id-oc-pkiCA                    OBJECT IDENTIFIER ::= {id-oc 22}    Defined in ITU-T Rec. X.509 |
--                                                                                ISO/IEC 9594-8
-- id-oc-deltaCRL                 OBJECT IDENTIFIER ::= {id-oc 23}    Defined in ITU-T Rec. X.509 |
--                                                                                ISO/IEC 9594-8
-- id-oc-pmiUser                  OBJECT IDENTIFIER ::= {id-oc 24}    Defined in ITU-T Rec. X.509 |
--                                                                                ISO/IEC 9594-8
-- id-oc-pmiAA                    OBJECT IDENTIFIER ::= {id-oc 25}    Defined in ITU-T Rec. X.509 |
--                                                                                ISO/IEC 9594-8
-- id-oc-pmiSOA                   OBJECT IDENTIFIER ::= {id-oc 26}    Defined in ITU-T Rec. X.509 |
--                                                                                ISO/IEC 9594-8
-- id-oc-attCertCRLDistributionPts OBJECT IDENTIFIER ::= {id-oc 27}   Defined in ITU-T Rec. X.509 |
--                                                                                ISO/IEC 9594-8
-- id-oc-parent                   OBJECT IDENTIFIER ::= {id-oc 28}    Defined in ITU-T Rec. X.501 |
--                                                                                ISO/IEC 9594-2
-- id-oc-child                    OBJECT IDENTIFIER ::= {id-oc 29}    Defined in ITU-T Rec. X.501 |
--                                                                                ISO/IEC 9594-2
-- id-oc-cpCps                    OBJECT IDENTIFIER ::= {id-oc 30}    Defined in ITU-T Rec. X.509 |
--                                                                                ISO/IEC 9594-8
-- id-oc-pkiCertPath              OBJECT IDENTIFIER ::= {id-oc 31}    Defined in ITU-T Rec. X.509 |
--                                                                                ISO/IEC 9594-8
-- id-oc-privilegePolicy          OBJECT IDENTIFIER ::= {id-oc 32}    Defined in ITU-T Rec. X.509 |
--                                                                                ISO/IEC 9594-8
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
-- id-oc-pmiDelegationPath      OBJECT IDENTIFIER ::=  {id-oc 33}      Defined in ITU-T Rec. X.509 |
--                                                                                    ISO/IEC 9594-8
-- id-oc-protectedPrivilegePolicy  OBJECT IDENTIFIER ::=  {id-oc 34}  Defined in ITU-T Rec. X.509 |
--                                                                                    ISO/IEC 9594-8
id-oc-oidC1obj          OBJECT IDENTIFIER  ::=  {id-oc 35}
id-oc-oidC2obj          OBJECT IDENTIFIER  ::=  {id-oc 36}
id-oc-oidCobj           OBJECT IDENTIFIER  ::=  {id-oc 37}
id-oc-uiiToUrn          OBJECT IDENTIFIER  ::=  {id-oc 38}
id-oc-urnToUri          OBJECT IDENTIFIER  ::=  {id-oc 39}
-- id-oc-integrityInfo          OBJECT IDENTIFIER ::=  {id-oc 40}      Defined in ITU-T Rec. X.501 |
--                                                                                    ISO/IEC 9594-2

-- Name forms --

id-nf-countryNameForm       OBJECT IDENTIFIER  ::=  {id-nf 0}
id-nf-locNameForm           OBJECT IDENTIFIER  ::=  {id-nf 1}
id-nf-sOPNameForm           OBJECT IDENTIFIER  ::=  {id-nf 2}
id-nf-orgNameForm           OBJECT IDENTIFIER  ::=  {id-nf 3}
id-nf-orgUnitNameForm       OBJECT IDENTIFIER  ::=  {id-nf 4}
id-nf-personNameForm        OBJECT IDENTIFIER  ::=  {id-nf 5}
id-nf-orgPersonNameForm     OBJECT IDENTIFIER  ::=  {id-nf 6}
id-nf-orgRoleNameForm       OBJECT IDENTIFIER  ::=  {id-nf 7}
id-nf-gONNameForm           OBJECT IDENTIFIER  ::=  {id-nf 8}
id-nf-resPersonNameForm     OBJECT IDENTIFIER  ::=  {id-nf 9}
id-nf-applProcessNameForm   OBJECT IDENTIFIER  ::=  {id-nf 10}
id-nf-applEntityNameForm    OBJECT IDENTIFIER  ::=  {id-nf 11}
id-nf-dSANameForm           OBJECT IDENTIFIER  ::=  {id-nf 12}
id-nf-deviceNameForm        OBJECT IDENTIFIER  ::=  {id-nf 13}
-- id-nf-cRLDistPtNameForm     OBJECT IDENTIFIER  ::=  {id-nf 14}
id-nf-dMDNameForm           OBJECT IDENTIFIER  ::=  {id-nf 15}
-- id-nf-subentryNameForm      OBJECT IDENTIFIER  ::=  {id-nf 16}
id-nf-oidC1NameForm         OBJECT IDENTIFIER  ::=  {id-nf 17}
id-nf-oidC2NameForm         OBJECT IDENTIFIER  ::=  {id-nf 18}
id-nf-oidCNameForm          OBJECT IDENTIFIER  ::=  {id-nf 19}

END -- SelectedObjectClasses
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Annex B

Suggested name forms and DIT structures

(This annex does not form an integral part of this Recommendation | International Standard)

This annex suggests a DIT structure shown in Figure B.1 and related DIT structure rules using the name forms defined in clause 3. The rules cover an unconstrained DIT structure. This example is for illustrative purposes only, and is not intended to limit the types of names that can be validly constructed in the Directory.

The integer identifiers assigned in this annex and used in Figure B.1 are arbitrary and have no global (or standardized) significance. A particular structure rule identifier only has significance within the scope of the subschema in which it applied. Each DMD is responsible for creating its own DIT structure and structure rules that may differ from this example.




Figure B.1 – Example DIT structure

B.1 Country

Attribute **countryName** is used for naming.

The root is the immediate superior to entries of object class **country**.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

sr1 STRUCTURE-RULE ::= {

NAME FORM countryNameForm

ID 1 }

B.2 Organization

Attribute **organizationName** is used for naming.

The root, **country** or **locality** can be the immediate superior of entries of object class **organization**.

NOTE – When the organization is directly under the root, this denotes an international organization. The naming values of the **organizationName** attribute for international organizations must all be distinct.

sr2 STRUCTURE-RULE ::= {

NAME FORM orgNameForm

ID 2 }

sr3 STRUCTURE-RULE ::= {

NAME FORM orgNameForm

SUPERIOR RULES { sr1 }

ID 3 }

sr4 STRUCTURE-RULE ::= {

NAME FORM orgNameForm

SUPERIOR RULES { sr5 | sr6 | sr7 | sr8 | sr9 }

ID 4 }

B.3 Locality

Attribute **localityName** or **stateOrProvinceName** is used for naming.

NOTE – For naming locality using **stateOrProvinceName**, see B.12.

The root, **country**, **locality**, **organization** or **organizationalUnit** can be the immediate superior of entries of object class **locality**.

sr5 STRUCTURE-RULE ::= {

NAME FORM locNameForm

ID 5 }

sr6 STRUCTURE-RULE ::= {

NAME FORM locNameForm

SUPERIOR RULES { sr1 }

ID 6 }

sr7 STRUCTURE-RULE ::= {

NAME FORM locNameForm

SUPERIOR RULES { sr5 | sr6 | sr7 | sr8 | sr9 }

ID 7 }

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

sr8 STRUCTURE-RULE ::= {

NAME FORM locNameForm

SUPERIOR RULES { sr2 | sr3 | sr4 }

ID 8 }

sr9 STRUCTURE-RULE ::= {

NAME FORM locNameForm

SUPERIOR RULES { sr10 | sr11 | sr12 }

ID 9 }

B.4 Organizational Unit

Attribute **organizationalUnitName** is used for naming.

organization, **organizationalUnit**, **locality** or **domainComponent** can be the immediate superior of entries of object class **organizationalUnit**.

sr10 STRUCTURE-RULE ::= {

NAME FORM orgUnitNameForm

SUPERIOR RULES { sr2 | sr3 | sr4 }

ID 10 }

sr11 STRUCTURE-RULE ::= {

NAME FORM orgUnitNameForm

SUPERIOR RULES { sr10 | sr11 | sr12 }

ID 11 }

sr12 STRUCTURE-RULE ::= {

NAME FORM orgUnitNameForm

SUPERIOR RULES { sr5 | sr6 | sr7 | sr8 | sr9 }

ID 12 }

B.5 Organizational Person

Attribute **commonName** and optionally **organizationalUnitName** is used for naming.

organization or **organizationalUnit** can be the immediate superior of entries of object class **organizationalPerson**.

sr13 STRUCTURE-RULE ::= {

NAME FORM orgPersonNameForm

SUPERIOR RULES { sr2 | sr3 | sr4 }

ID 13 }

sr14 STRUCTURE-RULE ::= {

NAME FORM orgPersonNameForm

SUPERIOR RULES { sr10 | sr11 | sr12 }

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

ID **14 }**

B.6 Organizational Role

Attribute **commonName** is used for naming.

organization or **organizationalUnit** can be the immediate superior of entries of object class **organizationalRole**.

sr15 STRUCTURE-RULE ::= {
NAME FORM **orgRoleNameForm**
SUPERIOR RULES { sr2 | sr3 | sr4 }
ID **15 }**

sr16 STRUCTURE-RULE ::= {
NAME FORM **orgRoleNameForm**
SUPERIOR RULES { sr10 | sr11 | sr12 }
ID **16 }**

B.7 Group of Names

Attribute **commonName** is used for naming.

locality, **organization** or **organizationalUnit** can be the immediate superior of entries of object class **groupOfNames**.

sr17 STRUCTURE-RULE ::= {
NAME FORM **gonNameForm**
SUPERIOR RULES { sr5 | sr6 | sr7 | sr8 | sr9 }
ID **17 }**

sr18 STRUCTURE-RULE ::= {
NAME FORM **gonNameForm**
SUPERIOR RULES { sr2 | sr3 | sr4 }
ID **18 }**

sr19 STRUCTURE-RULE ::= {
NAME FORM **gonNameForm**
SUPERIOR RULES { sr10 | sr11 | sr12 }
ID **19 }**

B.8 Residential Person

Attribute **commonName** and optionally **streetAddress** is used for naming.

locality is the immediate superior of entries of object class **residentialPerson**.

sr20 STRUCTURE-RULE ::= {
NAME FORM **resPersonNameForm**
SUPERIOR RULES { sr5 | sr6 | sr7 | sr8 | sr9 }
ID **20 }**

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

B.9 Application Entity

Attribute **commonName** is used for naming.

applicationProcess is the immediate superior of entries of object class **applicationEntity**.

sr21 STRUCTURE-RULE ::= {
NAME FORM applEntityNameForm
SUPERIOR RULES { sr24 | sr25 }
ID 21 }

B.10 Device

Attribute **commonName** is used for naming.

organization or **organizationalUnit** can be the immediate superior of entries of object class **device**.

sr22 STRUCTURE-RULE ::= {
NAME FORM deviceNameForm
SUPERIOR RULES { sr2 | sr3 | sr4 }
ID 22 }

sr23 STRUCTURE-RULE ::= {
NAME FORM deviceNameForm
SUPERIOR RULES { sr10 | sr11 | sr12 }
ID 23 }

B.11 Application Process

Attribute **commonName** is used for naming.

organization or **organizationalUnit** can be the immediate superior of entries of object class **applicationProcess**.

sr24 STRUCTURE-RULE ::= {
NAME FORM applProcessNameForm
SUPERIOR RULES { sr2 | sr3 | sr4 }
ID 24 }

sr25 STRUCTURE-RULE ::= {
NAME FORM applProcessNameForm
SUPERIOR RULES { sr10 | sr11 | sr12 }
ID 25 }

B.12 Alternative Structure Rule for Locality

If the **stateOrProvinceName** attribute is used for naming locality and locality constrained to existing only as an immediate subordinate of country, then one additional structure rule is required to define this.

sr26 STRUCTURE-RULE ::= {
NAME FORM sOPNameForm

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

SUPERIOR RULES { sr1 }

ID 26 }

In addition the structure rules **sr4**, **sr7**, **sr12**, **sr17**, and **sr20** must be modified to include **sr26** within their respective list of superior structure rule as follows.

sr4 STRUCTURE-RULE ::= {

NAME FORM orgNameForm

SUPERIOR RULES { sr5 | sr6 | sr7 | sr8 | sr9 | sr26 }

ID 4 }

sr7 STRUCTURE-RULE ::= {

NAME FORM locNameForm

SUPERIOR RULES { sr5 | sr6 | sr7 | sr8 | sr9 | sr26 }

ID 7 }

sr12 STRUCTURE-RULE ::= {

NAME FORM orgUnitNameForm

SUPERIOR RULES { sr5 | sr6 | sr7 | sr8 | sr9 | sr26 }

ID 12 }

sr17 STRUCTURE-RULE ::= {

NAME FORM gonNameForm

SUPERIOR RULES { sr5 | sr6 | sr7 | sr8 | sr9 | sr26 }

ID 17 }

sr20 STRUCTURE-RULE ::= {

NAME FORM resPersonNameForm

SUPERIOR RULES { sr5 | sr6 | sr7 | sr8 | sr9 | sr26 }

ID 20 }

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Annex C

Amendments and corrigenda

(This annex does not form an integral part of this Recommendation | International Standard)

This edition of this Directory Specification includes the following amendment to the previous edition that was balloted and approved by ISO/IEC:

– Amendment 3 for Communications support enhancements.

This edition of this Directory Specification does not include any technical corrigenda.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

ICS 35.100.70

Price based on 33 pages

© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale