INTERNATIONAL STANDARDIZED PROFILE

ISO/IEC ISP 10609-24

First edition
1995-12-15

Information technology — International Standardized Profiles TB, TC, TD and TE — Connection-mode Transport Service over connection-mode Network Service —

Part 24:

Subnetwork-type dependent requirements for Network Layer and Data Link Layer for Data Transfer concerning a packet switched mode Integrated Services Digital Network using virtual calls: D-channel access case

Technologies de l'information — Profils normalisés internationaux TB, TC, TD et TE — Service de transport en mode connexion sur service de réseau en mode connexion —

Partie 24: Prescriptions dépendantes du type de sous-réseau pour la couche réseau et la couche liaison de données pour le transfert de données concernant un réseau numérique de services intégré en mode de commutation de paquets employant des appels virtuels: cas d'accès sur canal D

Reference number
ISO/IEC ISP 10609-24:1995(E)

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Contents

Page

Foreword iii

Introduction vii

1 Scope 1

2 Normative references 1

3 Definitions 2

4 Abbreviations 2

5 Subnetwork-type dependent requirements for Network Layer 2

5.1 Static conformance requirements 3

5.2 Dynamic conformance requirements 3

6 Subnetwork-type dependent requirements for Data Link Layer 3

Annex A IPRL 4

Introduction 4

A.1 Notation 4

A.2 Network Layer IPRL 5

© ISO/IEC 1995
All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève • Switzerland

Printed in Switzerland

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. In addition to developing International Standards, ISO/IEC JTC 1 has created a Special Group on Functional Standardization for the processing of International Standardized Profiles.

An International Standardized Profile is an internationally agreed, harmonized document which identifies a standard or group of standards, together with options and parameters, necessary to accomplish a function or set of functions.

Draft International Standardized Profiles are circulated to national bodies for voting. Publication as an International Standardized Profile requires approval by at least 75% of the national bodies casting a vote.

International Standardized Profile ISO/IEC ISP 10609-24 was prepared with the collaboration of

- Asia-Oceania Workshop (AOW);
- European Workshop for Open Systems (EWOS);
- Open Systems Environment Implementors' Workshop (OIW).

ISO/IEC ISP 10609 consists of the following parts, under the general title *Information technology - International Standardized Profiles TB, TC, TD and TE - Connection-mode Transport Service over connection-mode Network Service*:

Part 1: Subnetwork-type independent requirements for Group TB

Part 2: Subnetwork-type independent requirements for Group TC

Part 3: Subnetwork-type independent requirements for Group TD

Part 4: Subnetwork-type independent requirements for Group TE

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Part 5: Definition of profiles TB1111/TB1121

Part 6: Definition of profiles TC1111/TC1121

Part 7: Definition of profiles TD1111/TD1121

Part 8: Definition of profiles TE1111/TE1121

Part 9: Subnetwork-type dependent requirements for Network Layer, Data Link Layer and Physical Layer concerning permanent access to a packet switched data network using virtual calls

Part 10: LAN subnetwork-dependent, media-independent requirements

Part 11: CSMA/CD LAN subnetwork-dependent, media-dependent requirements

Part 12: Definition of profile TC51, provision of the OSI connection-mode Transport Service using the OSI connection-mode Network Service in an End System attached to a CSMA/CD LAN

Part 14: Definition of profile TC53, provision of the OSI connection-mode Transport Service using the OSI connection-mode Network Service in an End System attached to a Token Ring LAN

Part 15: Definition of profile TC54, provision of the OSI connection-mode Transport Service using the OSI connection-mode Network Service in an End System attached to an FDDI LAN

Part 20: Overview of the generalized multi-part ISP structure for TC and TD Group profiles for OSI usage of ISDN

Part 21: Subnetwork-type dependent requirements for Network Layer and Data Link Layer for ISDN B-channel X.25 DTE to DTE operation

Part 22: Subnetwork-type dependent requirements for Network Layer and Data Link Layer for ISDN B-channel X.25 DTE to DCE operation

Part 23: Subnetwork-type dependent requirements for Network Layer and Data Link Layer for Data Transfer concerning a packet switched mode Integrated Services Digital Network using virtual calls: B-channel access case

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Part 24: Subnetwork-type dependent requirements for Network Layer and Data Link Layer for Data Transfer concerning a packet switched mode Integrated Services Digital Network using virtual calls: D-channel access case

Part 25: Subnetwork-type dependent requirements for Q.931 circuit-switched operation

Part 26: Subnetwork-type dependent requirements for Network Layer for Call Control procedures concerning the outgoing call of a packet switched mode Integrated Services Digital Network in case B using virtual calls

Part 27: Subnetwork-type dependent requirements for Network Layer for Call Control procedures concerning the incoming call of a packet switched mode Integrated Services Digital Network in case B using virtual calls

Part 28: Subnetwork-type dependent requirements for Data Link Layer for end systems attached to an ISDN subnetwork

Part 30: Definition of profile TC1131

Part 31: Definition of profile TC1231

Part 32: Definition of profile TC4111

Part 33: Definition of profile TC4211

Part 34: Definition of profile TC43111

Part 35: Definition of profile TC43112

Part 36: Definition of profile TC43211

Part 37: Definition of profile TC43212

Part 38: Definition of profile TC4331

Part 40: Definition of profile TD1131

Part 41: Definition of profile TD1231

Part 42: Definition of profile TD4111

Part 43: Definition of profile TD4211

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Part 44: Definition of profile TD43111

Part 45: Definition of profile TD43112

Part 46: Definition of profile TD43211

Part 47: Definition of profile TD43212

Part 48: Definition of profile TD4331

Annex A forms an integral part of this part of ISO/IEC ISP 10609.

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Introduction

This International Standardized Profile (ISP) is defined in accordance with the principles specified by ISO/IEC Technical Report 10000, "Information Technology - Framework and taxonomy of International Standardized Profiles".

The context of Functional Standardization is one area in the overall field of Information Technology (IT) standardization activities, covering base standards, profiles, and registration mechanisms. A profile defines a combination of base standards that collectively perform a specific well-defined IT function. Profiles standardize the use of options and other variations in the base standards, and provide a basis for the development of uniform, internationally recognized system tests.

ISPs are produced not simply to 'legitimize' a particular choice of base standards and options, but to promote real system interoperability. One of the most important roles for an ISP is to serve as the basis for the development (by organizations other than ISO and IEC) of internationally recognized test methods. The development and widespread acceptance of tests based on this and other ISPs is crucial to the successful realization of this goal.

ISO/IEC ISP 10609 consists of several parts of which this is part 24. This part of ISO/IEC ISP 10609 specifies subnetwork-dependent and media-dependent requirements. There are further parts which specify the profile requirements that are subnetwork-independent. In addition, for each individual profile there is a part of ISO/IEC ISP 10609 which identifies the specific requirements of that profile, making reference to appropriate material from part 1 and from the subnetwork dependent parts of ISO/IEC ISP 10609.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Information technology - International Standardized Profiles TB, TC, TD and TE - Connection-mode Transport Service over connection-mode Network Service

Part 24:

Subnetwork-type dependent requirements for Network Layer and Data Link Layer for Data Transfer concerning a packet switched mode Integrated Services Digital Network using virtual calls: D-channel access case

1 Scope

ISO/IEC ISP 10609 is applicable to end systems concerned with operating in the Open Systems Interconnection (OSI) environment. It specifies a combination of OSI standards, which collectively provide the connection-mode Transport Service using the connection-mode Network Service.

This part of ISO/IEC ISP 10609 specifies the subnetwork-type dependent requirements for

(1) the Network Layer concerning packet switched signalling and data transfer using virtual calls

(2) the data Link Layer concerning data transfer.

2 Normative References

The following documents contain provisions which, through reference in this text, constitute provisions of this part of ISO/IEC ISP 10609. At the time of publication, the editions indicated were valid. All documents are subject to revision, and parties to agreements based on this part of ISO/IEC ISP 10609 are warned against automatically applying any more recent editions of the documents listed below, since the nature of references made by ISPs to such documents is that they may be specific to a particular edition. Members of IEC and ISO maintain registers of currently valid International Standards and ISPs, and ITU-T maintains published editions of its current Recommendations.

ISO/IEC 9574:1992, *Information technology - Provision of the OSI connection-mode network service by packet mode terminal equipment connected to an integrated*

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

services digital network (ISDN). (See also CCITT Recommendation X.612-1992).

ISO/IEC ISP 10609-9:1992, *Information technology - International Standardized Profiles TB, TC, TD and TE - Connection-mode Transport Service over connection-mode Network Service - Part 9: Subnetwork-type dependent requirements for Network Layer, Data Link Layer and Physical Layer concerning permanent access to a packet switched data network using virtual calls.*

ISO/IEC ISP 10609-28:1995, *Information technology - International Standardized Profiles TB, TC, TD and TE - Connection-mode Transport Service over connection-mode Network Service - Part 28: Subnetwork-type dependent requirements for Data Link Layer for end systems attached to an ISDN subnetwork.*

3 Definitions

All of the terms used in this part of ISO/IEC ISP 10609 are defined in the referenced base standards (see clause 2).

4 Abbreviations

ISDN: Integrated Services Digital Network
SAPI: Service Access Point Identifier

5 Subnetwork-type dependent requirements for Network Layer

This clause specifies subnetwork-type dependent requirements for end system operation regarding packet switched signalling and data transfer when the end system is connected to an ISDN at the S/T reference point and supports packet mode operation in case B using virtual calls, to provide connection-mode Network Service as defined by ISO/IEC 8348.

This clause covers the D-channel access case of case B as defined in ISO/IEC 9574.

A conforming implementation's constraints on supported functions and parameters for the Network Layer concerning packet switched signalling and data transfer are the same as the specifications given in ISO/IEC ISP 10609-9, clause A.2, except for ISO/IEC 8208 requirements listed in clause A.2 which are required by ISO/IEC 9574.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

5.1 Static conformance requirements

The specifications given in ISO/IEC ISP 10609-9, subclause 5.1 for the static conformance requirements are to be used.

5.2 Dynamic conformance requirements

The specifications given in ISO/IEC ISP 10609-9, subclause 5.2 for the dynamic conformance requirements are to be used.

6 Subnetwork-type dependent requirements for Data Link Layer

A conforming implementation shall support the ISDN layer 2 protocol using SAPI=16 as described in CCITT Rec. Q.921.

A conforming implementation's constraints on functions and parameters for LAPD using SAPI=16 are specified in ISO/IEC ISP 10609-28.

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Annex A
(normative)
International Standardized Profile Implementation Conformance Statement Requirements List (IPRL)

Introduction

A conforming implementation shall satisfy the mandatory conformance requirements of the base standard referenced in this part of ISO/IEC ISP 10609, and shall satisfy the requirement of ISO/IEC ISP 10609-9 with regard to items not mentioned in this annex.

This IPRL in the annex specifies the only different requirements for implementation of Network Layer from those given in ISO/IEC ISP 10609-9, clause A.2.

Network Layer IPRL in this clause follows the proforma specified in ISO/IEC 8208/Amd.3.

A.1 Notation

The following table defines the parameter value supported for each group for which conformance is claimed. Any key indicating the conformance requirements is not used.

--`,,```,,,,````-`-`,,`,,`,`,,`---
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

A.2 Network Layer ISPICS Requirements List

A.2.1 Values for flow control parameters and throughput class, Virtual call service

Base Standard Features				Profile Features	
Item	Parameter	References	Status	ISP References	Status
	What values are supported for:			clause 6	
V1s	- Default Packet sizes, sending (octets)?	16.2.2.5	16 32 64 128 256 512 1024 2048 4096		16 32 64 128 256
V1r	- Default Packet sizes, receiving (octets)?	16.2.2.5	16 32 64 128 256 512 1024 2048 4096		16 32 64 128 256
V3s	- Default throughput classes, sending (bits per second)?	16.2.2.7, table 23	75 150 300 600 1200 2400 4800 9600 19200 48000 64000		75 150 300 600 1200 2400 4800 9600 (Note)
V3r	- Default throughput classes, receiving (bits per second)?	16.2.2.7, table 23	75 150 300 600 1200 2400 4800 9600 19200 48000 64000		75 150 300 600 1200 2400 4800 9600 (Note)

NOTE - The restriction of using the above throughput classes applies only to a basic access. There are no restrictions to a primary rate access.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Base Standard Features				Profile Features	
Item	Parameter	References	Status	ISP References	Status
	What values are supported in Flow Control Parameter Negotiation, for:			clause 6	
V9s	- Packet sizes negotiable, sending (octets)?	15.2.2.1.1	16 32 64 128 256 512 1024 2048 4096		16 32 64 128 256
V9r	- Packet sizes negotiable, receiving (octets)?	15.2.2.1.1	16 32 64 128 256 512 1024 2048 4096		16 32 64 128 256
V11s	- Throughput classes negotiable, sending (bits per second)? <Basic Access>	15.2.2.2, table 18	75 150 300 600 1200 2400 4800 9600 19200 48000 64000		75 150 300 600 1200 2400 4800 9600 (Note)
V11r	- Throughput classes negotiable, receiving (bits per second)? <Basic Access>	15.2.2.2, table 18	75 150 300 600 1200 2400 4800 9600 19200 48000 64000		75 150 300 600 1200 2400 4800 9600 (Note)

NOTE - The restriction of using the above throughput classes applies only to a basic access. There are no restrictions to a primary rate access.

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

© ISO/IEC

ICS 35.100

Descriptors: data processing, information interchange, network interconnection, open systems interconnection, data transmission, connection oriented transmission, packet transmission, services, profiles, network layer, data link layer.

Price based on 6 pages

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale