INTERNATIONAL STANDARDIZED PROFILE

ISO/IEC ISP 10613-14

First edition
1995-12-15

Information technology — International Standardized Profile RA — Relaying the Connectionless-mode Network Service —

Part 14:
Definition of profile RA54.54, relaying the Connectionless-mode Network Service between FDDI LAN subnetworks

Technologies de l'information — Profil normalisé international RA — Relais de service de réseau en mode sans connexion —

Partie 14: Définition du profil RA54.54, relais de service de réseau en mode sans connexion entre sous-réseaux FDDI LAN

Reference number
ISO/IEC ISP 10613-14:1995(E)

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

Contents **Page**

Foreword iii

Introduction v

1 Scope 1
- 1.1 General 1
- 1.2 Position within the taxonomy 1
- 1.3 Scenario 2

2 Normative references 3

3 Definitions 4

4 Abbreviations 4

5 Requirements 4
- 5.1 Static conformance requirements 4
- 5.2 Dynamic conformance requirements 4

Annex A: ISPICS requirements list 5
- A.1 General options of the profile 5
- A.2 Base standards selected and combined in the profile 5
- A.3 Constraints on base standards 5

© ISO/IEC 1995
All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office · Case postale 56 · CH-1211 Genève · Switzerland

Printed in Switzerland

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. In addition to developing International Standards, ISO/IEC JTC 1 has created a Special Group on Functional Standardization for the elaboration of International Standardized Profiles.

An International Standardized Profile is an internationally agreed, harmonized document which identifies a standard or group of standards, together with options and parameters, necessary to accomplish a function or a set of functions.

Draft International Standardized Profiles are circulated to national bodies for voting. Publication as an International Standardized Profile requires approval by at least 75 % of the national bodies casting a vote.

This part of ISO/IEC ISP 10613 was prepared with the collaboration of:

- Asia-Oceania Workshop (AOW);

- European Workshop for Open Systems (EWOS);

- Open Systems Environment Implementors' Workshop (OIW).

ISO/IEC ISP 10613 consists of several parts, under the general title *Information technology - International Standardized Profile RA - Relaying the Connectionless-mode Network Service:*

- *Part 1: Subnetwork-independent requirements*

- *Part 2: LAN subnetwork-dependent, media-independent requirements*

- *Part 3: CSMA/CD LAN subnetwork-dependent, media-dependent requirements*

- *Part 4: FDDI LAN subnetwork-dependent, media-dependent requirements*

- *Part 5: Definition of profile RA51.51, relaying the Connectionless-mode Network Service between CSMA/CD LAN subnetworks*

- *Part 6: Definition of profile RA51.54, relaying the Connectionless-mode Network Service between CSMA/CD LAN subnetworks and FDDI LAN subnetworks*

- *Part 7: PSDN subnetwork-dependent, media-dependent requirements for virtual calls over a permanent access*

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

- *Part 8: Definition of profile RA51.1111, relaying the Connectionless-mode Network Service between CSMA/CD LAN subnetworks and PSDNs using virtual calls over a PSTN leased line permanent access*

- *Part 9: Definition of profile RA51.1121, relaying the Connectionless-mode Network Service between CSMA/CD LAN subnetworks and PSDNs using virtual calls over a digital data circuit/CSDN leased line permanent access*

- *Part 10: Token Ring LAN subnetwork-dependent, media-dependent requirements*

- *Part 11: Definition of profile RA51.53, relaying the Connectionless-mode Network Service between CSMA/CD LAN subnetworks and Token Ring LAN subnetworks*

- *Part 12: Definition of profile RA53.53, relaying the Connectionless-mode Network Service between Token Ring LAN subnetworks*

- *Part 13: Definition of profile RA53.54, relaying the Connectionless-mode Network Service between Token Ring LAN subnetworks and FDDI LAN subnetworks*

- *Part 14: Definition of profile RA54.54, relaying the Connectionless-mode Network Service between FDDI LAN subnetworks*

- *Part 15: Definition of profile RA53.1111, relaying the Connectionless-mode Network Service between Token Ring LAN subnetworks and PSDNs using virtual calls over a PSTN leased line permanent access*

- *Part 16: Definition of profile RA53.1121, relaying the Connectionless-mode Network Service between Token Ring LAN subnetworks and PSDNs using virtual calls over a digital data circuit/CSDN leased line permanent access*

- *Part 17: Definition of profile RA54.1111, relaying the Connectionless-mode Network Service between FDDI LAN subnetworks and PSDNs using virtual calls over a PSTN leased line permanent access*

- *Part 18: Definition of profile RA54.1121, relaying the Connectionless-mode Network Service between FDDI LAN subnetworks and PSDNs using virtual calls over a digital data circuit/CSDN leased line permanent access*

Annex A forms an integral part of this part of ISO/IEC ISP 10613.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Introduction

ISO/IEC ISP 10613 is defined in accordance with the principles specified by ISO/IEC Technical Report 10000.

The context of Functional Standardization is one area in the overall field of Information Technology (IT) standardization activities, covering base standards, profiles, and registration mechanisms. A profile defines a combination of base standards that collectively perform a specific well-defined IT function. Profiles standardize the use of options and other variations in the base standards, and provide a basis for the development of uniform, internationally recognized system tests.

ISPs are produced not simply to 'legitimize' a particular choice of base standards and options, but to promote real system interoperability. One of the most important roles for an ISP is to serve as the basis for the development (by organizations other than ISO and IEC) of internationally recognized test methods. The development and widespread acceptance of tests based on this and other ISPs is crucial to the successful realization of this goal.

ISO/IEC ISP 10613 consists of several parts of which this is part 14. ISO/IEC ISP 10613-1 specifies the profile requirements that are subnetwork-independent. There are further parts which specify subnetwork-dependent and media-dependent requirements. In addition, for each individual profile there is a part of ISO/IEC ISP 10613 which identifies the specific requirements of that profile, making reference to appropriate material from part 1 and from the subnetwork-dependent parts of ISO/IEC ISP 10613. This part of ISO/IEC ISP 10613 is the one which identifies the specific requirements for profile RA54.54.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

blank page

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Information technology - International Standardized Profile RA - Relaying the Connectionless-mode Network Service -

Part 14:
Definition of profile RA54.54, relaying the Connectionless-mode Network Service between FDDI LAN subnetworks

1 Scope

1.1 General

ISO/IEC ISP 10613 is applicable to interworking units concerned with operating in the Open Systems Interconnection (OSI) environment. It specifies a combination of OSI base standards that collectively provide a network-relay function for the connectionless-mode Network Service.

This part of ISO/IEC ISP 10613 defines the RA54.54 profile, which is applicable to interworking units operating between FDDI LAN subnetworks.

1.2 Position within the taxonomy

The taxonomy of profiles is defined in ISO/IEC TR 10000-2. This part of ISO/IEC ISP 10613 defines the profile

RA54.54 Relaying the Connectionless-mode Network Service between FDDI LAN subnetworks.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

1.3 Scenario

Figure 1 illustrates the configuration of systems to which the RA54.54 profile is applicable. The figure shows two reference points, but an implementation of this profile may include any number of attachments to FDDI LAN subnetworks, with a reference point corresponding at each.



** other compatible network equipment
- OSI relays
- OSI end systems
- other equipment

Figure 1 - Scenario of applicability of the RA54.54 profile

As this profile is a member of the RA group, it is intended that a conforming implementation is capable of interworking with other profiles of the RA group and with End Systems implementing profiles from the TA or UA groups, provided that suitable relays are in place in the case of those members of these groups which relate to different elements of the subnetwork taxonomy.

This part of ISO/IEC ISP 10613 specifies the required functions from the supporting protocol stack shown in figure 2.



Figure 2 - Profile protocol stack for RA54.54 intermediate system

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

2 Normative references

The following documents contain provisions which, through reference in this text, constitute provisions of this part of ISO/IEC ISP 10613. At the time of publication, the editions indicated were valid. All documents are subject to revision, and parties to agreements based on this part of ISO/IEC ISP 10613 are warned against automatically applying any more recent editions of the documents listed below, since the nature of references made by ISPs to such documents is that they may be specific to a particular edition. Members of IEC and ISO maintain registers of currently valid International Standards and ISPs, and ITU-T maintains published editions of its current Recommendations.

NOTE - ISO 8473:1988 and ISO 8802-2:1989 have been superseded by new editions (ISO/IEC 8473-1:1994 and ISO/IEC 8802-2:1994 respectively). However, when this part of ISO/IEC ISP 10613 was under development, the previous editions were valid and this part of ISO/IEC ISP 10613 is therefore based on these editions.

ISO 8473:1988, *Information processing systems - Data communications - Protocol for providing the connectionless-mode network service.*

ISO 8802-2:1989, *Information processing systems - Local area networks - Part 2: Logical link control.*

ISO 9314-1:1989, *Information processing systems - Fibre Distributed Data Interface (FDDI) - Part 1: Token Ring Physical Layer Protocol (PHY).*

ISO 9314-2:1989, *Information processing systems - Fibre Distributed Data Interface (FDDI) - Part 2: Token Ring Media Access Control (MAC).*

ISO/IEC 9314-3:1990, *Information processing systems - Fiber Distributed Data Interface (FDDI) - Part 3: Physical Layer Medium Dependent (PMD).*

ISO 9542:1988, *Information processing systems - Telecommunications and information exchange between systems - End system to Intermediate system routeing exchange protocol for use in conjunction with the Protocol for providing the connectionless-mode network service (ISO 8473).*

ISO 9542/Cor.1:-[1], *Information processing systems - Telecommunications and information exchange between systems - End system to Intermediate system routeing exchange protocol for use in conjunction with the Protocol for providing the connectionless-mode network service (ISO 8473) - Technical Corrigendum 1.*

NOTE - This Technical Corrigendum to ISO 9542 is to apply throughout in this part of ISO/IEC ISP 10613, wherever ISO 9542 itself is referenced.

ISO/IEC TR 10000-1:1992, *Information technology - Framework and taxonomy of International Standardized Profiles - Part 1: Framework.*

ISO/IEC TR 10000-2:1994, *Information technology - Framework and taxonomy of International Standardized Profiles - Part 2: Principles and Taxonomy for OSI Profiles.*

ISO/IEC ISP 10613-1:1994, *Information technology - International Standardized Profile RA - Relaying the Connectionless-mode Network Service - Part 1: Subnetwork-independent requirements.*

1) To be published.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

ISO/IEC ISP 10613-2:1994, *Information technology - International Standardized Profile RA - Relaying the Connectionless-mode Network Service - Part 2: LAN subnetwork-dependent, media-independent requirements.*

ISO/IEC ISP 10613-4:1995, *Information technology - International Standardized Profile RA - Relaying the Connectionless-mode Network Service - Part 4: FDDI LAN subnetwork-dependent, media-dependent requirements.*

Additional normative references are found in each of the ISP parts listed above. These additional normative references are base standards used for development of the relevant ISP parts.

3 Definitions

All the terms used in this part of ISO/IEC ISP 10613 are defined in the documents that are referenced in clause 2.

4 Abbreviations

All abbreviations, including acronyms, are used in this part of ISO/IEC ISP 10613 as defined in the documents that are referenced in clause 2.

5 Requirements

5.1 Static conformance requirements

An implementation conforming to the profile defined in this part of ISO/IEC ISP 10613 shall support two or more points of attachment to ISO/IEC 9314 FDDI LAN subnetworks, through which it shall support all the features specified as static conformance requirements in parts 1, 2 and 4 of ISO/IEC ISP 10613, and shall implement all the features identified as requirements in the ISPICS requirements list in annex A of this part of ISO/IEC ISP 10613.

5.2 Dynamic conformance requirements

An implementation conforming to the profile defined in this part of ISO/IEC ISP 10613 shall carry out the supported functions according to the applicable dynamic conformance requirements in parts 1, 2 and 4 of ISO/IEC ISP 10613. It shall behave in accordance with the requirements of the ISPICS requirements list in annex A of this part of ISO/IEC ISP 10613.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Annex A
(normative)

ISPICS requirements list

A.1 General options of the profile

There are no general options in this part of ISO/IEC ISP 10613.

A.2 Base standards selected and combined in the profile

The profile defined in this part of ISO/IEC ISP 10613 makes use of the following base standards:

- ISO 8473
- ISO 9542
- ISO 8802-2
- ISO 9314-1
- ISO 9314-2
- ISO/IEC 9314-3

A.3 Constraints on base standards

A conforming implementation of this part of ISO/IEC ISP 10613 shall:

a) meet all the subnetwork-type independent relaying constraints on the operation of ISO 8473 and ISO 9542 which are specified in the ISPICS requirements list in ISO/IEC ISP 10613-1;

b) for operation of the attachments to FDDI LAN subnetworks, meet all the constraints on the operation of ISO 8473, ISO 9542, ISO 8802-2, ISO 9314-1, ISO 9314-2 and ISO/IEC 9314-3 which are specified in the ISPICS requirements lists in parts 2 and 4 of ISO/IEC ISP 10613.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

© ISO/IEC

ICS 35.100

Descriptors: data processing, information interchange, network interconnection, open systems interconnection, local area networks, network layer, data transmission, connection oriented transmission, services, profiles.

Price based on 5 pages

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale