ISO/IEC 11801

Edition 2.0 2008-04

INTERNATIONAL STANDARD

AMENDMENT 1

Information technology – Generic cabling for customer premises



ISO/IEC 11801 A1:2008(E)

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2008 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,…). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

ISO/IEC 11801

Edition 2.0 2008-04

INTERNATIONAL STANDARD

AMENDMENT 1

Information technology – Generic cabling for customer premises

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE P

ICS 35.200

ISBN 2-8318-9715-7

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

FOREWORD

Amendment 1 to International Standard ISO/IEC 11801:2002 was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

INTRODUCTION to Amendment 1

This amendment provides requirements for new Class E_A and F_A channels plus additions and corrections to ISO/IEC 11801:2002. Amendment 2 of ISO/IEC 11801:2002 will provide balanced cabling models, requirements and normative references for Category 6_A and 7_A components, requirements for Class E_A and F_A links, together with amendments to the requirements for optical fibre cabling.

Update references to Tables, the numbers of which have been changed.

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Page 6

Replace, in the list of figures, the title of Figure 10 by the following new title:

Figure 10 – Balanced cabling: channel, permanent link and CP link.

Page 13

2 Normative references

Replace, on page 14 to 17, the following references by the updated references as indicated below:

IEC 60512-25-5, *Connectors for electronic equipment – Basic tests and measurements – Part 25-5: Test 25e – Return loss*[1]

IEC/PAS 60793-1-49:2002, *Optical fibres – Part 1-49: Measurement methods and test procedures – Differential mode delay*

IEC 60794-2:1989, *Optical fibre cables – Part 2: Product specification (indoor cable)* [2]
Amendment 1 (1998)

IEC/PAS 61076-3-104:2002, *Connectors for electronic equipment – Part 3-104: Detail specification for 8-way, shielded free and fixed connectors, for data transmissions with frequencies up to 600 MHz*

IEC 61935-1:2000, *Generic cabling systems – Specifications for the testing of balanced communication cabling in accordance with ISO/IEC 11801 – Part 1: Installed cabling*
Amendment 1 (under consideration)

IEC 61935-2, *Generic cabling systems – Specification for the testing of balanced communication cabling in accordance with ISO/IEC 11801 – Part 2: Patch cords and work area cords*[1)]

ISO/IEC TR 14763-1, *Information technology – Implementation and operation of customer premises cabling – Part 1: Administration*

ISO/IEC 18010:2002, *Information technology – Pathways and spaces for customer premises cabling*

Updated references:

IEC 60512-25-5, *Connectors for electronic equipment – Tests and measurements – Part 25-5: Test 25e – Return loss*

1 To be published.

2 There exists a consolidated Edition 4.1 (1998) of IEC 60794-2 that includes Edition 4.0 (1989) and its amendment 1 (1998).

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

IEC 60793-1-49, *Optical fibres – Part 1-49: Measurement methods and test procedures – Differential mode delay*

IEC 60794-2, *Optical fibre cables – Part 2: Indoor cables – Sectional specification*

IEC 61076-3-104, *Connectors for electronic equipment – Product requirements – Part 3-104: Detail specification for 8-way, shielded free and fixed connectors for data transmissions with frequencies up to 600 MHz minimum*[3]

IEC 61935-1, *Testing of balanced communication cabling in accordance with ISO/IEC 11801 – Part 1: Installed cabling*)

IEC 61935-2, *Testing of balanced communication cabling in accordance with ISO/IEC 11801 – Part 2: Patch cords and work area cords*

ISO/IEC 14763-1, *Information technology – Implementation and operation of customer premises cabling – Part 1: Administration*

ISO/IEC 18010, *Information technology – Pathways and spaces for customer premises cabling*

Page 17

3 Definitions, abbreviations and symbols

3.1 Definitions

Replace the existing titles by the following new titles:

3 Terms and definitions, abbreviations and symbols

3.1 Terms and definitions

Page 20

3.1.35
Replace the existing term number, term, definition and NOTE by the following new term number, term, definition and NOTE:

3.1.45
insertion loss
loss incurred by inserting a device between a source and load of equal impedance. The device itself may have a different impedance from the load and source impedance

NOTE The terms operational attenuation or operational insertion loss are sometimes associated with this definition.

3.1.36
Replace the existing term number and definition by the following new term number and definition:

3.1.46
insertion loss deviation
difference between the measured insertion loss of cascaded components and the insertion loss determined by the sum of the individual component insertion losses

3 A new edition (edition 3.0) to support measurements up to 1 000 MHz is under consideration.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Page 21

3.1.41
Replace the existing term number and definition by the following new term number and definition:

3.1.51
link
transmission path between two cabling system interfaces, including the connections at each end

Pages 17 to 23

***Insert**, in the existing list of terms and definitions, the following new terms and definitions in alphabetical order and renumber the existing terms and definitions accordingly:*

3.1.2
alien (exogenous) crosstalk
signal coupling from a disturbing pair of a channel to a disturbed pair of another channel

NOTE This also applies to the signal coupling from a disturbing pair within a permanent link or component, used to create a channel, to a disturbed pair within a permanent link or component, used to create another channel.

3.1.3
alien (exogenous) far-end crosstalk loss (AFEXT)
signal isolation between a disturbing pair of a channel and a disturbed pair of another channel, measured at the far-end

NOTE This also applies to the measurement of the signal isolation between a disturbing pair within a permanent link or component, used to create a channel, and a disturbed pair within a permanent link or component, used to create another channel.

3.1.4
alien (exogenous) near-end crosstalk loss (ANEXT)
signal isolation between a disturbing pair of a channel and a disturbed pair of another channel, measured at the near-end

NOTE This also applies to the measurement of signal isolation between a disturbing pair within a permanent link or component, used to create a channel, and a disturbed pair within a permanent link or component, used to create another channel.

3.1.7
attenuation to alien (exogenous) crosstalk ratio at the far-end (AACR-F)
difference, in dB, between the alien far-end crosstalk loss from a disturbing pair of a channel and the insertion loss of a disturbed pair in another channel

NOTE This also applies to the calculation using the alien far-end crosstalk loss from a disturbing pair within a permanent link or component, used to create a channel, and the insertion of a disturbed pair within a permanent link or component, used to create another channel.

3.1.8
attenuation to alien (exogenous) crosstalk ratio at the near-end (AACR-N)
difference, in dB, between the alien near-end crosstalk loss from a disturbing pair of a channel and the insertion loss of a disturbed pair in another channel

NOTE This also applies to the calculation using the alien near-end crosstalk loss from a disturbing pair within a permanent link or component, used to create a channel, and the insertion loss of a disturbed pair within a permanent link or component, used to create another channel.

3.1.9
attenuation to crosstalk ratio at the far-end (ACR-F)
difference, in dB, between the far-end crosstalk loss from a disturbing pair of a channel and the insertion loss of a disturbed pair of the same channel

--`,,```,,,,````-`-`,,`,,`,`,,`---
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

NOTE This also applies to the calculation using the far-end crosstalk loss from a disturbing pair within a permanent link or component, used to create a channel, and the insertion loss of a disturbed pair within the permanent link or component, of the same channel.

3.1.10
attenuation to crosstalk ratio at the near-end (ACR-N)
difference, in dB, between the near-end crosstalk loss from a disturbing pair of a channel and the insertion loss of a disturbed pair of the same channel

NOTE This also applies to the calculation using the near-end crosstalk loss from a disturbing pair within a permanent link or component, used to create a channel, and the insertion loss of a disturbed pair within the permanent link or component, of the same channel.

3.1.11
average power sum alien (exogenous) near-end crosstalk loss
the calculated average of the power sum alien near-end crosstalk loss of the pairs of a disturbed channel

NOTE This also applies to the calculation using the pairs within a permanent link used to create a channel.

3.1.12
average power sum attenuation to alien (exogenous) crosstalk ratio far-end
the calculated average of the power sum attenuation to alien crosstalk ratio at the far-end of the pairs of a disturbed channel

NOTE This also applies to the calculation using the pairs within a permanent link used to create a channel.

3.1.35
equal level far-end crosstalk ratio (ELFEXT)
difference, in dB, between the far-end crosstalk loss from a disturbing pair of a channel and the insertion loss of a disturbing pair of the same channel

NOTE This also applies to the calculation using the far-end crosstalk loss from a disturbing pair within a permanent link or component, used to create a channel, and the insertion loss of a disturbing pair within a permanent link or component, of the same channel.

3.1.55
operating temperature
stabilised temperature of the cabling combining ambient temperature with any increase due to the application being supported

3.1.64
power sum alien (exogenous) far-end crosstalk loss (PS AFEXT)
power sum of the signal isolation between multiple disturbing pairs of one or more channels and a disturbed pair of another channel, measured at the far-end

NOTE This also applies to the calculation using the multiple disturbing pairs within one or more permanent links or components and a disturbed pair within a permanent link or component, used to create another channel.

3.1.65
power sum alien (exogenous) near-end crosstalk loss (PS ANEXT)
power sum of the signal isolation between multiple disturbing pairs of one or more channels and a disturbed pair of another channel, measured at the near-end

NOTE This also applies to the calculation using the multiple disturbing pairs within one or more permanent links or components and a disturbed pair within a permanent link or component, used to create another channel.

3.1.66
power sum attenuation to alien (exogenous) crosstalk ratio at the far-end (PS AACR-F)
difference, in dB, between the power sum alien far-end crosstalk loss from multiple disturbing pairs of one or more channels and the insertion loss of a disturbed pair in another channel

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

NOTE This also applies to the calculation using the power sum alien far-end crosstalk loss from multiple disturbing pairs within one or more permanent links or components and the insertion loss of a disturbed pair within a permanent link or component, used to create another channel.

3.1.67
power sum attenuation to alien (exogenous) crosstalk ratio at the near-end (PS AACR-N)
difference, in dB, between the power sum alien near-end crosstalk loss from multiple disturbing pairs of one or more channels and the insertion loss of a disturbed pair in another channel

NOTE This also applies to the calculation using the power sum alien near-end crosstalk loss from multiple disturbing pairs within one or more permanent links or components, and the insertion loss of a disturbed pair within a permanent link or component, used to create another channel.

3.1.68
power sum attenuation to crosstalk ratio at the far-end (PS ACR-F)
difference, in dB, between the power sum far-end crosstalk loss from multiple disturbing pairs of a channel and the insertion loss of a disturbed pair in the same channel

NOTE This also applies to the calculation using the power sum far-end crosstalk loss from multiple disturbing pairs within one or more permanent links or components, used to create a channel, and the insertion loss of a disturbed pair within a permanent link or component, of the same channel.

3.1.69
power sum attenuation to crosstalk ratio at the near-end (PS ACR-N)
difference, in dB, between the power sum near-end crosstalk loss from multiple disturbing pairs of a channel and the insertion loss of a disturbed pair in the same channel

NOTE This also applies to the calculation using the multiple disturbing pairs within one or more permanent links or components, used to create a channel, and the insertion loss of a disturbed pair within a permanent link or component, of the same channel.

3.1.70
power sum equal level far-end crosstalk ratio (PS ELFEXT)
power sum of all disturbing pairs of a channel, of the difference, in dB, between the far-end crosstalk loss and the insertion loss of each disturbing pair

NOTE This also applies to the calculation using the multiple disturbing pairs within one or more permanent links or components, used to create a channel, and the insertion loss of a disturbing pair within a permanent link or component, of the same channel.

Update the reference numbers to the terms and definitions throughout the document.

Pages 23 to 24

3.2 Abbreviations

Replace the existing items as follows:

ISO	International Standardisation Organisation
ELFEXT	Equal level far-end crosstalk attenuation (loss)
PS NEXT	Power sum NEXT attenuation (loss)
PS ELFEXT	Power sum ELFEXT attenuation (loss)
PS FEXT	Power sum FEXT attenuation (loss)

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

by the following amended items:

ELFEXT	Equal level FEXT
ISO	International Organization for Standardization
PS ELFEXT	Power sum ELFEXT
PS FEXT	Power sum FEXT (loss)
PS NEXT	Power sum NEXT (loss)

Insert, in the existing Table, the following new abbreviations in alphabetical sequence:

AACR-F	Attenuation to alien crosstalk ratio at the far-end
ACR-F	Attenuation to crosstalk ratio at the far-end
ACR-N	Attenuation to crosstalk ratio at the near-end
AFEXT	Alien far-end crosstalk (loss)
ANEXT	Alien near-end crosstalk (loss)
ELTCTL	Equal level TCTL
PS AACR-F	Power sum attenuation to alien crosstalk ratio at the far-end
PS AACR-F_{avg}	Average power sum attenuation to alien crosstalk ratio at the far-end
PS ACR-F	Power sum attenuation to crosstalk ratio at the far-end
PS ACR-N	Power sum attenuation to crosstalk ratio at the near-end
PS AFEXT	Power sum alien far-end crosstalk (loss)
PS $AFEXT_{norm}$	Normalized power sum alien far-end crosstalk (loss)
PS ANEXT	Power sum alien near-end crosstalk (loss)
PS $ANEXT_{avg}$	Average power sum alien near-end crosstalk (loss)

Pages 24 and 25

3.3.1 Variables

Insert, in the existing list, the following new variables in alphabetical order:

l number of the disturbing channel

N number of disturbing channels

Page 25

3.3.2 Indices

Insert, in the existing list, the following new indices in alphabetical order:

avg index to denominate average of the associated parameter across all of the pairs in the same channel or permanent link

norm index to denominate scaling of the associated parameter

Page 25

4 Conformance

Replace the entire text of this clause by the following text.

For a cabling installation to conform to this International Standard the following applies.

a) The configuration and structure shall conform to the requirements outlined in Clause 5.

b) The performance of balanced channels shall meet the requirements specified in Clause 6.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

This shall be achieved by one of the following:

1) a channel design and implementation ensuring that the prescribed channel performance is met;
2) attachment of appropriate components to a permanent link or CP link design meeting the prescribed performance class of Clause 6 and Annex A. Channel performance shall be assured where a channel is created by adding more than one cord to either end of a link meeting the requirements of Clause 6 and Annex A;
3) using the reference implementations of Clause 7 and compatible cabling components conforming to the requirements of Clauses 9, 10 and 13, based upon a statistical approach of performance modelling.

Until amendment 2[4] of ISO/IEC 11801:2002 has been published:

- conformance for Classes D, E and F with regards to TCL, ELTCTL and coupling attenuation can only be achieved by option 1) above;
- conformance for Classes E_A and F_A can only be achieved by option 1) above.

c) The implementation and performance of optical fibre cabling channels shall meet the requirements specified in Clause 8.

d) The interfaces to the cabling at the TO shall conform to the requirements of Clause 10 with respect to mating interfaces and performance.

e) Connecting hardware at other places in the cabling structure shall meet the performance requirements specified in Clause 10.

f) If present, screens shall be handled as specified in Clause 11.

g) System administration shall meet the requirements of Clause 12.

h) Regulations on safety and EMC applicable at the location of the installation shall be met.

In the absence of the channel, the conformance of the link shall be used to verify conformance with the standard.

Specifications marked "f.f.s." are preliminary specifications, and are not required for conformance to this International Standard.

Page 30

5.5 Accommodation of functional elements

Replace the existing text of the last paragraph of this subclause by the following new text:

Telecommunications outlets are typically located in the work area.

4 Amendment 2 to ISO/IEC 11801 is under consideration.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Page 37

Figure 10

Replace the title of this Figure by the following new title:

Figure 10 – Balanced cabling: channel, permanent link and CP link

Page 38

6.2 Layout

Replace the existing text of the third paragraph by the following new text and note:

The performance limits for balanced cabling channels are given in 6.4. These limits are derived from the component performance limits of Clause 9 and 10 using reference implementations specified in Clause 7.

NOTE Component performance requirements for Category 6_A and Category 7_A will be available in amendment 2 to ISO/IEC 11801:2002.

Replace, on page 39, the existing text of the first paragraph by the following new text:

The performance limits for balanced cabling permanent links and CP links are given in Annex A. These limits are derived from the component performance limits of Clauses 9 and 10 using reference implementations specified in Clause 7.

NOTE Permanent link and CP link requirements for Class E_A and Class F_A will be available in amendment 2 to ISO/IEC 11801:2002.

Page 39

6.3 Classification of balanced cabling

Replace, in the existing list, Class E and Class F by the following:

Class E is specified up to 250 MHz.

Class E_A is specified up to 500 MHz.

Class F is specified up to 600 MHz.

Class F_A is specified up to 1 000 MHz.

Page 39

6.4.1 General

Add, at the end of the second paragraph, the following new sentence:

For the purposes of this standard, insertion loss is measured with source and load impedances of 100 Ω.

Add, at the end of the third paragraph, the following new sentence:

When required for assessment, channels shall be measured according to IEC 61935-1, unless otherwise specified in this clause.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Page 39

6.4.2 Return loss

Replace, on page 40, the existing Tables 2 and 3, by the following new Tables 2 and 3:

Table 2 – Return loss for channel

Class	Frequency MHz	Minimum return loss dB
C	$1 \le f \le 16$	15,0
D	$1 \le f < 20$	17,0
	$20 \le f \le 100$	$30 - 10\lg(f)$
E	$1 \le f < 10$	19,0
	$10 \le f < 40$	$24 - 5\lg(f)$
	$40 \le f \le 250$	$32 - 10\lg(f)$
E_A	$1 \le f < 10$	19,0
	$10 \le f < 40$	$24 - 5\lg(f)$
	$40 \le f < 398.1$	$32 - 10\lg(f)$
	$398.1 \le f \le 500$	6,0
F	$1 \le f < 10$	19,0
	$10 \le f < 40$	$24 - 5\lg(f)$
	$40 \le f < 251,2$	$32 - 10\lg(f)$
	$251,2 \le f \le 600$	8,0
F_A	$1 \le f < 10$	19,0
	$10 \le f < 40$	$24 - 5\lg(f)$
	$40 \le f < 251,2$	$32 - 10\lg(f)$
	$251,2 \le f < 631$	8,0
	$631 \le f \le 1\,000$	$36 - 10\lg(f)$

Table 3 – Informative return loss values for channel at key frequencies

Frequency MHz	Minimum return loss dB					
	Class C	Class D	Class E	Class E_A	Class F	Class F_A
1	15,0	17,0	19,0	19,0	19,0	19,0
16	15,0	17,0	18,0	18,0	18,0	18,0
100	N/A	10,0	12,0	12,0	12,0	12,0
250	N/A	N/A	8,0	8,0	8,0	8,0
500	N/A	N/A	N/A	6,0	8,0	8,0
600	N/A	N/A	N/A	N/A	8,0	8,0
1 000	N/A	N/A	N/A	N/A	N/A	6,0

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

6.4.3 Insertion loss/attenuation

Replace, on page 41, the existing Tables 4 and 5, by the following new Tables 4 and 5:

Table 4 – Insertion loss for channel

Class	**Frequency** MHz	**Maximum insertion loss** [a] dB
A	$f = 0{,}1$	16,0
B	$f = 0{,}1$	5,5
	$f = 1$	5,8
C	$1 \le f \le 16$	$1{,}05 \times \left(3{,}23\sqrt{f}\right) + 4 \times 0{,}2$
D	$1 \le f \le 100$	$1{,}05 \times \left(1{,}910\,8\sqrt{f} + 0{,}022\,2 \times f + 0{,}2/\sqrt{f}\right) + 4 \times 0{,}04 \times \sqrt{f}$
E	$1 \le f \le 250$	$1{,}05 \times \left(1{,}82\sqrt{f} + 0{,}016\,9 \times f + 0{,}25/\sqrt{f}\right) + 4 \times 0{,}02 \times \sqrt{f}$
E_A	$1 \le f \le 500$	$1{,}05 \times \left(1{,}82\sqrt{f} + 0{,}009\,1 \times f + 0{,}25/\sqrt{f}\right) + 4 \times 0{,}02 \times \sqrt{f}$
F	$1 \le f \le 600$	$1{,}05 \times \left(1{,}8\sqrt{f} + 0{,}01 \times f + 0{,}2/\sqrt{f}\right) + 4 \times 0{,}02 \times \sqrt{f}$
F_A	$1 \le f \le 1\,000$	$1{,}05 \times \left(1{,}8\sqrt{f} + 0{,}005 \times f + 0{,}25/\sqrt{f}\right) + 4 \times 0{,}02 \times \sqrt{f}$
[a] Insertion loss (*IL*) at frequencies that correspond to calculated values of less than 4,0 dB shall revert to a maximum requirement of 4,0 dB.		

Table 5 – Informative insertion loss values for channel at key frequencies

Frequency MHz	**Maximum insertion loss** dB							
	Class A	**Class B**	**Class C**	**Class D**	**Class E**	**Class E_A**	**Class F**	**Class F_A**
0,1	16,0	5,5	N/A	N/A	N/A	N/A	N/A	N/A
1	N/A	5,8	4,2	4,0	4,0	4,0	4,0	4,0
16	N/A	N/A	14,4	9,1	8,3	8,2	8,1	8,0
100	N/A	N/A	N/A	24,0	21,7	20,9	20,8	20,3
250	N/A	N/A	N/A	N/A	35,9	33,9	33,8	32,5
500	N/A	N/A	N/A	N/A	N/A	49,3	49,3	46,7
600	N/A	N/A	N/A	N/A	N/A	N/A	54,6	51,4
1 000	N/A	N/A	N/A	N/A	N/A	N/A	N/A	67,6

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Page 41

6.4.4.1 Pair-to-pair NEXT

Replace, on page 42, the existing Tables 6 and 7, by the following new Tables 6 and 7:

Table 6 – NEXT for channel

Class	Frequency MHz	Minimum NEXT [a] dB
A	$f = 0{,}1$	27,0
B	$0{,}1 \le f \le 1$	$25 - 15\lg(f)$
C	$1 \le f \le 16$	$39{,}1 - 16{,}4\lg(f)$
D	$1 \le f \le 100$	$-20\lg\left(10^{\frac{65{,}3 - 15\lg(f)}{-20}} + 2\times 10^{\frac{83 - 20\lg(f)}{-20}}\right)$
E	$1 \le f \le 250$	$-20\lg\left(10^{\frac{74{,}3 - 15\lg(f)}{-20}} + 2\times 10^{\frac{94 - 20\lg(f)}{-20}}\right)$
E_A	$1 \le f \le 500$	$-20\lg\left(10^{\frac{74{,}3 - 15\lg(f)}{-20}} + 2\times 10^{\frac{94 - 20\lg(f)}{-20}}\right)$ [b, d]
F	$1 \le f \le 600$	$-20\lg\left(10^{\frac{102{,}4 - 15\lg(f)}{-20}} + 2\times 10^{\frac{102{,}4 - 15\lg(f)}{-20}}\right)$
F_A	$1 \le f \le 1\,000$	$-20\lg\left(10^{\frac{105{,}4 - 15\lg(f)}{-20}} + 2\times 10^{\frac{116{,}3 - 20\lg(f)}{-20}}\right)$ [c, d]

[a] *NEXT* at frequencies that correspond to calculated values of greater than 65,0 dB shall revert to a minimum requirement of 65,0 dB.

[b] Whenever the Class E_A channel insertion loss at 450 MHz is less than 12 dB, subtract the term $1{,}4((f-450)/50)$ to the equation stated above for the range of 450 MHz to 500 MHz.

[c] Whenever the Class F_A channel insertion loss at 900 MHz is less than 17 dB, subtract the term $2{,}8((f-900)/100)$ to the equation stated above for the range of 900 MHz to 1 000 MHz.

[d] The terms in the equations are not intended to imply component performance.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Table 7 – Informative NEXT values for channel at key frequencies

Frequency MHz	Minimum channel NEXT dB							
	Class A	Class B	Class C	Class D	Class E	Class E_A	Class F	Class F_A
0,1	27,0	40,0	N/A	N/A	N/A	N/A	N/A	N/A
1	N/A	25,0	39,1	63,3	65,0	65,0	65,0	65,0
16	N/A	N/A	19,4	43,6	53,2	53,2	65,0	65,0
100	N/A	N/A	N/A	30,1	39,9	39,9	62,9	65,0
250	N/A	N/A	N/A	N/A	33,1	33,1	56,9	59,1
500	N/A	N/A	N/A	N/A	N/A	27,9	52,4	53,6
600	N/A	N/A	N/A	N/A	N/A	N/A	51,2	52,1
1 000	N/A	N/A	N/A	N/A	N/A	N/A	N/A	47,9

Page 42

6.4.4.2 Pair-to-pair NEXT

Replace, on page 43, the existing Tables 8 and 9, by the following new Tables 8 and 9:

Table 8 – PS NEXT for channel

Class	Frequency MHz	Minimum PS NEXT [a] dB
D	$1 \le f \le 100$	$-20\lg\left(10^{\frac{62,3-15\lg(f)}{-20}}+2\times10^{\frac{80-20\lg(f)}{-20}}\right)$
E	$1 \le f \le 250$	$-20\lg\left(10^{\frac{72,3-15\lg(f)}{-20}}+2\times10^{\frac{90-20\lg(f)}{-20}}\right)$
E_A	$1 \le f \le 500$	$-20\lg\left(10^{\frac{72,3-15\lg(f)}{-20}}+2\times10^{\frac{90-20\lg(f)}{-20}}\right)$ [b, d]
F	$1 \le f \le 600$	$-20\lg\left(10^{\frac{99,4-15\lg(f)}{-20}}+2\times10^{\frac{99,4-15\lg(f)}{-20}}\right)$
F_A	$1 \le f \le 1\,000$	$-20\lg\left(10^{\frac{102,4-15\lg(f)}{-20}}+2\times10^{\frac{113,3-20\lg(f)}{-20}}\right)$ [c, d]

[a] *PS NEXT* at frequencies that correspond to calculated values of greater than 62,0 dB shall revert to a minimum requirement of 62,0 dB.

[b] Whenever the Class E_A channel insertion loss at 450 MHz is less than 12 dB, subtract the term $1,4((f - 450)/50)$ from the equation stated above for the range of 450 MHz to 500 MHz.

[c] Whenever the Class F_A channel insertion loss at 900 MHz is less than 17 dB, subtract the term $2,8((f - 900)/100)$ from the equation stated above for the range of 900 MHz to 1 000 MHz.

[d] The terms in the equations are not intended to imply component performance.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Table 9 – Informative PS NEXT values for channel at key frequencies

Frequency MHz	Minimum PS NEXT dB				
	Class D	Class E	Class E_A	Class F	Class F_A
1	60,3	62,0	62,0	62,0	62,0
16	40,6	50,6	50,6	62,0	62,0
100	27,1	37,1	37,1	59,9	62,0
250	N/A	30,2	30,2	53,9	56,1
500	N/A	N/A	24,8	49,4	50,6
600	N/A	N/A	N/A	48,2	49,1
1 000	N/A	N/A	N/A	N/A	44,9

Page 44

6.4.5 Attenuation to crosstalk ratio (ACR)

Replace the title and the entire existing text and tables 10 and 11 of subclause 6.4.5 as follows:

6.4.5 Attenuation to crosstalk ratio at the near-end (ACR-N)

6.4.5.1 General

ACR-N requirements are applicable to Classes D, E, E_A, F and F_A only.

In prior editions of this standard, the term *ACR* was used. Except for the name, the definition and equations for *ACR-N* are identical to those used for *ACR* in prior editions of this standard.

6.4.5.2 Pair-to-pair ACR-N

Pair-to-pair *ACR-N* is the difference between the pair-to-pair *NEXT* and the insertion loss (*IL*) of the disturbed pair in dB.

The *ACR-N* of each pair combination of a channel shall meet the difference of the *NEXT* requirement of Table 6 and the insertion loss (*IL*) requirement of Table 4 of the respective class.

The *ACR-N* requirements shall be met at both ends of the cabling.

$ACR\text{-}N_{ik}$ of pairs *i* and *k* is computed as follows:

$$ACR\text{-}N_{ik} = NEXT_{ik} - IL_k \quad (2)$$

where

i is the number of the disturbing pair;

k is the number of the disturbed pair;

$NEXT_{ik}$ is the near-end crosstalk loss coupled from pair *i* into pair *k*;

IL_k is the insertion loss of pair *k*.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Table 10 – Informative ACR-N values for channel at key frequencies

Frequency MHz	Minimum ACR-N dB				
	Class D	Class E	Class E_A	Class F	Class F_A
1	59,3	61,0	61,0	61,0	61,0
16	34,5	44,9	45,0	56,9	57,0
100	6,1	18,2	19,0	42,1	44,7
250	N/A	−2,8	−0,8	23,1	26,7
500	N/A	N/A	−21,4	3,1	6,9
600	N/A	N/A	N/A	-3,4	0,7
1 000	N/A	N/A	N/A	N/A	−19,6

6.4.5.3 Power sum ACR-N (PS ACR-N)

The *PS ACR-N* of each pair of a channel shall meet the difference of the *PS NEXT* requirement of Table 8 and the insertion loss (*IL*) requirement of Table 4 of the respective class. The *PS ACR-N* requirements shall be met at both ends of the cabling.

PS ACR-N$_k$ of pair *k* is computed as follows:

$$PS\ ACR\text{-}N_k = PS\ NEXT_k - IL_k \tag{3}$$

where

k is the number of the disturbed pair;

PS NEXT$_k$ is the power sum near-end crosstalk loss of pair *k*;

IL$_k$ is the insertion loss of pair *k.*

Table 11 – Informative PS ACR-N values for channel at key frequencies

Frequency MHz	Minimum PS ACR-N dB				
	Class D	Class E	Class E_A	Class F	Class F_A
1	56,3	58,0	58,0	58,0	58,0
16	31,5	42,3	42,4	53,9	54,0
100	3,1	15,4	16,2	39,1	41,7
250	N/A	−5,8	−3,7	20,1	23,7
500	N/A	N/A	−24,5	0,1	3,9
600	N/A	N/A	N/A	−6,4	−2,3
1 000	N/A	N/A	N/A	N/A	−22,6

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Pages 45 to 47

6.4.6 ELFEXT

Replace the title and the entire existing text and tables 12, 13, 14 and 15 of this subclause as follows:

6.4.6 Attenuation to crosstalk ratio at the far-end (ACR-F)

6.4.6.1 General

ACR-F requirements are applicable to Classes D, E, E_A, F and F_A only.

NOTE *ACR-F* and *PS ACR-F* replace parameters *ELFEXT* and *PS ELFEXT* respectively, which were specified in prior editions of this standard. Whereas *ELFEXT* is computed using the insertion loss of the disturbing pair, *ACR-F* is computed using the insertion loss of the disturbed pair. Because both disturbing pairs and disturbed pairs are subject to the same insertion loss requirements (see Table 4), the specified requirements in Table 12 and Table 14 for Classes D, E and F have not been changed.

6.4.6.2 Pair-to-pair ACR-F

The *ACR-F* of each pair combination of a channel shall meet the requirements derived by the equations in Table 12.

$ACR\text{-}F_{ik}$ of pairs *i* and *k* is computed as follows:

$$ACR\text{-}F_{ik} = FEXT_{ik} - IL_k \quad (4)$$

where

i is the number of the disturbing pair;

k is the number of the disturbed pair;

$FEXT_{ik}$ is the far-end crosstalk loss coupled from pair *i* into pair *k;*

IL_k is the insertion loss of pair *k.*

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Table 12 – ACR-F for channel

Class	Frequency MHz	Minimum ACR-F [a, b] dB
D	$1 \le f \le 100$	$-20\lg\left(10^{\frac{63,8-20\lg(f)}{-20}}+4\times10^{\frac{75,1-20\lg(f)}{-20}}\right)$
E	$1 \le f \le 250$	$-20\lg\left(10^{\frac{67,8-20\lg(f)}{-20}}+4\times10^{\frac{83,1-20\lg(f)}{-20}}\right)$
E_A	$1 \le f \le 500$	$-20\lg\left(10^{\frac{67,8-20\lg(f)}{-20}}+4\times10^{\frac{83,1-20\lg(f)}{-20}}\right)$
F	$1 \le f \le 600$	$-20\lg\left(10^{\frac{94-20\lg(f)}{-20}}+4\times10^{\frac{90-15\lg(f)}{-20}}\right)$
F_A	$1 \le f \le 1\,000$	$-20\lg\left(10^{\frac{95,3-20\lg(f)}{-20}}+4\times10^{\frac{103,9-20\lg(f)}{-20}}\right)$

[a] *ACR-F* at frequencies that correspond to measured FEXT values of greater than 70,0 dB are for information only.
[b] The *ACR-F* limit at frequencies that correspond to calculated values of greater than 65,0 dB shall revert to a minimum requirement of 65,0 dB.

Table 13 – Informative ACR-F values for channel at key frequencies

Frequency MHz	Minimum ACR-F dB				
	Class D	Class E	Class E_A	Class F	Class F_A
1	57,4	63,3	63,3	65,0	65,0
16	33,3	39,2	39,2	57,5	63,3
100	17,4	23,3	23,3	44,4	47,4
250	N/A	15,3	15,3	37,8	39,4
500	N/A	N/A	9,3	32,6	33,4
600	N/A	N/A	N/A	31,3	31,8
1 000	N/A	N/A	N/A	N/A	27,4

6.4.6.3 Power sum ACR-F (PS ACR-F)

The *PS ACR-F* of each pair of a channel shall meet the requirements derived by the equation in Table 14.

PS ACR-F$_k$ of pair *k* is computed as follows:

$$PS\ ACR\text{-}F_k = \left(-10\lg \sum_{i=1,\, i\neq k}^{n} 10^{\frac{-FEXT_{ik}}{10}} \right) - IL_k \qquad (5)$$

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

where

i is the number of the disturbing pair;

k is the number of the disturbed pair;

n is the number of disturbing pairs in the channel;

$FEXT_{ik}$ is the far-end crosstalk loss coupled from pair *i* into pair *k;*

IL_k is the insertion loss of pair *k.*

Table 14 – PS ACR-F for channel

Class	Frequency MHz	Minimum PS ACR-F [a, b] dB
D	$1 \le f \le 100$	$-20\lg\left(10^{\frac{60{,}8-20\lg(f)}{-20}}+4\times10^{\frac{72{,}1-20\lg(f)}{-20}}\right)$
E	$1 \le f \le 250$	$-20\lg\left(10^{\frac{64{,}8-20\lg(f)}{-20}}+4\times10^{\frac{80{,}1-20\lg(f)}{-20}}\right)$
E_A	$1 \le f \le 500$	$-20\lg\left(10^{\frac{64{,}8-20\lg(f)}{-20}}+4\times10^{\frac{80{,}1-20\lg(f)}{-20}}\right)$
F	$1 \le f \le 600$	$-20\lg\left(10^{\frac{91-20\lg(f)}{-20}}+4\times10^{\frac{87-15\lg(f)}{-20}}\right)$
F_A	$1 \le f \le 1\,000$	$-20\lg\left(10^{\frac{92{,}3-20\lg(f)}{-20}}+4\times10^{\frac{100{,}9-20\lg(f)}{-20}}\right)$

[a] *PS ACR-F* at frequencies that correspond to calculated *PS FEXT* values of greater than 67,0 dB are for information only.

[b] The *PS ACR-F* limit at frequencies that correspond to calculated values of greater than 62,0 dB shall revert to a minimum requirement of 62,0 dB.

Table 15 – Informative PS ACR-F values for channel at key frequencies

Frequency MHz	Minimum PS ACR-F dB				
	Class D	Class E	Class E_A	Class F	Class F_A
1	54,4	60,3	60,3	62,0	62,0
16	30,3	36,2	36,2	54,5	60,3
100	14,4	20,3	20,3	41,4	44,4
250	N/A	12,3	12,3	34,8	36,4
500	N/A	N/A	6,3	29,6	30,4
600	N/A	N/A	N/A	28,3	28,8
1 000	N/A	N/A	N/A	N/A	24,4

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Page 47

6.4.7 Direct current (d.c.) loop resistance

Replace the existing Table 16 by the following new table:

Table 16 – Direct current (d.c.) loop resistance for channel

Maximum d.c. loop resistance Ω			
Class A	**Class B**	**Class C**	**Class D, E, E_A, F, F_A**
560	170	40	25

Page 48

6.4.8 Direct current (d.c.) resistance unbalance

Replace the existing text by the following new text:

For all cabling classes, the d.c. resistance unbalance between the two conductors within each pair of a channel shall not exceed 3 % or 0,200 Ω, whichever is greater. This requirement shall be achieved by design. The maximum d.c. resistance unbalance between pairs within a channel is f.f.s.

6.4.10 Operating voltage

Replace the existing title and text of this subclause as follows:

6.4.10 Dielectric withstand

Dielectric withstand of Classes D, E, E_A, F and F_A channels shall be a minimum of 1 000 V d.c. conductor-to-conductor and shall be a minimum of 1 000 V d.c. conductor-to-screen or conductor to earth, if a screen is not present. This requirement shall be met by design.

6.4.11 Power capacity

Replace the existing text of this subclause by the word void.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Page 48

6.4.12 Propagation delay

Replace the the existing tables 17 and 18 by the new tables 17 and 18 as follows:

Table 17 – Propagation delay for channel

Class	**Frequency** MHz	**Maximum propagation delay** μs
A	$f = 0{,}1$	20,000
B	$0{,}1 \leq f \leq 1$	5,000
C, D, E, E_A, F, F_A	$1 \leq f \leq$ NOTE 1	$0{,}534 + 0{,}036/\sqrt{f} + 4 \times 0{,}002\ 5$
NOTE The equation for propagation delay applies to the upper frequency of the class		

Table 18 – Informative propagation delay values for channel at key frequencies

Frequency MHz	**Maximum propagation delay** μs							
	Class A	**Class B**	**Class C**	**Class D**	**Class E**	**Class E_A**	**Class F**	**Class F_A**
0,1	20,000	5,000	N/A	N/A	N/A	N/A	N/A	N/A
1	N/A	5,000	0,580	0,580	0,580	0,580	0,580	0,580
16	N/A	N/A	0,553	0,553	0,553	0,553	0,553	0,553
100	N/A	N/A	N/A	0,548	0,548	0,548	0,548	0,548
250	N/A	N/A	N/A	N/A	0,546	0,546	0,546	0,546
500	N/A	N/A	N/A	N/A	N/A	0,546	0,546	0,546
600	N/A	N/A	N/A	N/A	N/A	N/A	0,545	0,545
1 000	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0,545

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Page 48

6.4.13 Delay skew

Replace the the existing table 19 by the following new table 19:

Table 19 – Delay skew for channel

Class	Frequency MHz	Maximum delay skew μs
A	$f = 0{,}1$	N/A
B	$0{,}1 \leq f \leq 1$	N/A
C	$1 \leq f \leq 16$	0,050 [a]
D	$1 \leq f \leq 100$	0,050 [a, c]
E	$1 \leq f \leq 250$	0,050 [a, c]
E_A	$1 \leq f \leq 500$	0,050 [a, c]
F	$1 \leq f \leq 600$	0,030 [b, c]
F_A	$1 \leq f \leq 1\,000$	0,030 [b, c]

[a] This is the result of the calculation 0,045 + 4 × 0,001 25.

[b] This is the result of the calculation 0,025 + 4 × 0,001 25.

[c] Delay skew of any given installed cabling channel shall not vary by more than 0,010 μs within this requirement, due to effects such as the daily temperature variation.

Page 49

6.4.14 Unbalance attenuation

Replace the title, the entire existing text and table 20 of this subclause as follows:

6.4.14 Unbalance attenuation and coupling attenuation

6.4.14.1 General

This standard specifies unbalance attenuation (TCL and ELTCTL) for unscreened systems and coupling attenuation for screened systems. For further information on these parameters see Annex D.

6.4.14.2 Unbalance attenuation, near-end

The unbalance attenuation near-end is measured as transverse conversion loss (*TCL*). The TCL of a channel shall meet the requirements in Table 20. The TCL requirements shall be met at both ends of the cabling.

Performance requirements for TCL are applicable to Class A, B, C, D, E, E_A, F and F_A channels and shall be achieved by design and installation in accordance with manufacturer's instructions.

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Table 20 – TCL for channel for unscreened systems

Class	Frequency MHz	Minimum TCL [a] dB
A	$f = 0{,}1$	30
B	$f = 0{,}1$	45
	$f = 1$	20
C	$1 \le f \le 16$	$30 - 5\lg(f)$
D, E, E_A, F, F_A	$1 \le f < 30$	$53 - 15\lg(f)$
	$30 \le f \le$ NOTE [b]	$60{,}3 - 20\lg(f)$
NOTE This equation for TCL applies to upper frequency of the class.		
[a] *TCL* at frequencies that correspond to calculated values of greater than 40,0 dB shall revert to a minimum requirement of 40,0 dB.		
[b] TCL at frequencies above 250 MHz are for information only.		

It is possible to assess TCL by laboratory measurements of representative samples of channels assembled using their component and connector termination practices.

6.4.14.3 Unbalance attenuation, far-end

The unbalance attenuation far-end is measured as equal level transverse conversion transfer loss (ELTCTL). The ELTCTL of a channel shall meet the requirements as indicated in Table 21. The ELTCTL requirements shall be met at both ends of the cabling.

Performance requirements for ELTCTL are applicable to Class D, E, E_A, F and F_A channels and shall be achieved by design and installation in accordance with manufacturer's instructions.

Table 21 – ELTCTL for channel for unscreened systems

Class	Frequency MHz	Minimum ELTCTL dB
D, E, E_A, F, F_A	$1 \le f \le 30$	$30 - 20\lg(f)$

It is possible to assess ELTCTL by laboratory measurements of representative samples of channels assembled using their component and connector termination practices.

6.4.14.4 Coupling attenuation

The coupling attenuation of a channel shall meet the requirements in Table 22 at both ends.

Performance requirements for coupling attenuation are applicable to Class D, E, E_A, F and F_A systems and shall be achieved by design and installation in accordance with manufacturer's instructions.

It is possible to assess coupling attenuation by laboratory measurements of representative samples of channels assembled using their component and connector termination practices.

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Table 22 – Coupling attenuation for channel for screened systems

Class	Frequency MHz	Minimum Coupling Attenuation [a] dB
D, E, E_A, F, F_A	$30 \le f \le$ NOTE	$80 - 20\lg(f)$
NOTE Coupling attenuation is measured to 1 000 MHz but the limit applies to the upper frequency of the class under test.		
[a] Calculated values of greater than 40 dB shall revert to a minimum requirement of 40 dB.		

Page 50

6.4.15 Coupling attenuation

Replace the title and the entire existing text as follows:

6.4.15 Alien crosstalk

6.4.15.1 General

The following alien crosstalk requirements are applicable only to Classes E_A and F_A. Alien crosstalk of Class F is considered to be as good as the alien crosstalk performance specified for Class E_A. For information on alien crosstalk performance of Class E systems, see ISO/IEC TR 24750.

If coupling attenuation for Class E_A or F channels is 10 dB better than Table 22 or for Class F_A channels is 25 dB better than Table 22, then *PS ANEXT* and *PS AACR-F* are met by design.

6.4.15.2 Power sum alien NEXT (PS ANEXT)

The *PS ANEXT* of each pair of a channel shall meet the requirements derived by the equation in Table 23.

The *PS ANEXT* requirements shall be met at both ends of the channel.

PS ANEXT$_k$ of pair *k* is computed as follows:

$$PS\,ANEXT_k = -10\lg\left[\sum_{l=1}^{N}\sum_{i=1}^{n} 10^{\frac{-ANEXT_{l,i,k}}{10}}\right] \quad (6)$$

where

k is the number of the disturbed pair in the disturbed channel;

i is the number of the disturbing pair in a disturbing channel l;

l is the number of the disturbing channel;

N is the number of disturbing channels;

n is the number of disturbing pairs in disturbing channel l;

ANEXT$_{l,i,k}$ is the alien near-end crosstalk loss coupled from pair I of disturbing channel (l) to the pair *k* of the disturbed channel.

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Table 23 – PS ANEXT for channel

Class	Frequency MHz	Minimum PS ANEXT [a] dB
E_A [b, c]	$1 \le f < 100$	$80 - 10\lg(f)$
	$100 \le f \le 500$	$90 - 15\lg(f)$
F_A	$1 \le f < 100$	$95 - 10\lg(f)$
	$100 \le f \le 1\,000$	$105 - 15\lg(f)$

[a] *PS ANEXT* at frequencies that correspond to calculated values of greater than 67,0 dB shall revert to a minimum requirement of 67,0 dB.

[b] If the average insertion loss of all disturbed pairs at 100 MHz, $IL_{100MHz,avg}$, is less than 7 dB, then subtract the following for $f \ge 100$ MHz:

$$\text{minimum}\left\{7 \cdot \frac{f-100}{400} \cdot \frac{7 - IL_{100MHz,avg}}{IL_{100MHz,avg}},\ 6 \cdot \frac{f-100}{400}\right\}$$

where

f is the frequency in MHz;

$$IL_{100MHz,avg} = \frac{1}{4}\sum_{i=1}^{4} IL_{100MHz,i};$$

$IL_{100MHz,i}$ is the insertion loss of a pair I at 100 MHz.

[c] If coupling attenuation is at least 10 dB better than the requirements in Table 22, the calculation in [b] is not required.

Table 24 – Informative PS ANEXT values for channel at key frequencies

Frequency MHz	Minimum PS ANEXT dB	
	Class E_A	Class F_A
1	67,0	67,0
100	60,0	67,0
250	54,0	67,0
500	49,5	64,5
1 000	N/A	60,0

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

6.4.15.3 PS ANEXT$_{avg}$

The *PS ANEXT*$_{avg}$ of a channel shall meet the requirements derived by the equations in Table 25.

The *PS ANEXT*$_{avg}$ requirements shall be met at both ends of the channel.

PS ANEXT$_{avg}$ is computed as follows:

$$PS\ ANEXT_{\text{avg}} = \frac{1}{n}\left[\sum_{k=1}^{n} PS\ ANEXT_k\right] \quad (7)$$

where

k is the number of the disturbed pair in the disturbed channel;

n is the number of disturbed pairs in the disturbed channel;

PS ANEXT$_k$ is the power sum alien near-end crosstalk loss coupled to pair *k* of the disturbed channel.

Table 25 – PS ANEXT$_{avg}$ for channel

Class	Frequency MHz	Minimum PS ANEXT$_{avg}$ [a, b, c, d] dB
E_A	$1 \le f < 100$	$82{,}25 - 10\lg(f)$
	$100 \le f \le 500$	$92{,}25 - 15\lg(f)$

[a] *PS ANEXT*$_{avg}$ at frequencies that correspond to calculated values of greater than 67,0 dB shall revert to a minimum requirement of 67,0 dB.

[b] If the average insertion loss of all disturbed pairs at 100 MHz, $IL_{100\text{MHz,avg}}$, is less than 7 dB, then subtract the following for $f \ge 100$ MHz:

$$\text{minimum}\left\{7 \cdot \frac{f-100}{400} \cdot \frac{7 - IL_{100\text{MHz,avg}}}{IL_{100\text{MHz,avg}}},\ 6 \cdot \frac{f-100}{400}\right\}$$

where

f is the frequency in MHz;

$$IL_{100\text{MHz,avg}} = \frac{1}{4}\sum_{i=1}^{4} IL_{100\text{MHz},i};$$

$IL_{100\text{MHz},i}$ is the insertion loss of a pair *i* at 100 MHz.

[c] If coupling attenuation is at least 10 dB better than the requirements in Table 22, the calculation in Footnote b is not required.

[d] *PS ANEXT*$_{avg}$ for Class F_A channels is met if the Class F_A PS ANEXT requirements in Table 23 are met.

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Table 26 – Informative PS ANEXT$_{avg}$ values for channel at key frequencies

Frequency MHz	**Minimum Class E$_A$ PS ANEXT$_{avg}$** dB
1	67,0
100	62,3
250	56,3
500	51,8

6.4.15.4 Power sum alien ACR-F (PS AACR-F)

The *PS AACR-F* of each pair of a channel shall meet the requirements in Table 27.

The *PS AACR-F* shall be met at both ends of the channel.

The *PS AACR-F* is computed based on *AFEXT*, and insertion losses of disturbing and disturbed channels.

6.4.15.5 PS AFEXT for Class E$_A$ channels

The *PS AFEXT* for Class E_A is computed as follows:

If coupling attenuation is at least 10 dB better than the requirements in Table 22, then the *PS AFEXT* is determined by equation (13).

The measured pair-to-pair alien FEXT values of a wire pair *k* in a disturbed channel from the disturbing channel l are normalized by the difference of the insertion losses of disturbing and disturbed channels

$AFEXT_{\text{norm}}$ is computed from Equations 8 to 11 as follows

If

$$IL_k - IL_{l,i} > 0 \tag{8}$$

then

$$AFEXT_{\text{norm}\,l,i,k} = AFEXT_{l,i,k} - IL_{l,i} + IL_k - 10\lg\left(\frac{IL_k}{IL_{l,i}}\right) \tag{9}$$

If

$$IL_k - IL_{l,i} \leq 0 \tag{10}$$

then

$$AFEXT_{\text{norm}\,l,i,k} = AFEXT_{l,i,k} \tag{11}$$

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

where

k is the number of the disturbed pair in the disturbed channel;

i is the number of the disturbing pair in a disturbing channel l;

l is the number of the disturbing channel;

$AFEXT_{l,I,k}$ is the alien far-end crosstalk loss coupled from pair *I* of disturbing channel (l) to the pair *k* of the disturbed channel;

IL_k is the measured insertion loss of pair *k* in the disturbed channel;

$IL_{l,I}$ is the measured insertion loss of pair *I* of disturbing channel l.

The *PS AFEXT* is determined according to Equation 12.

$$PS\,AFEXT_k = -10\lg\left(\sum_{l=1}^{N}\sum_{i=1}^{n} 10^{\frac{-\left(AFEXT_{\mathrm{norm}}l,i,k\right)}{10}}\right) \quad (12)$$

where

N is the number of disturbing channels;

n is the number of disturbing pairs in disturbing channel l;

k is the number of the disturbed pair in the disturbed channel;

i is the number of the disturbing pair in a disturbing channel l;

l is the number of the disturbing channel.

6.4.15.6 PS AFEXT for Class F_A channels

The *PS AFEXT* is determined according to Equation 13.

$$PS\,AFEXT_k = -10\lg\left(\sum_{l=1}^{N}\sum_{i=1}^{n} 10^{\frac{-\left(AFEXT_{l,i,k}\right)}{10}}\right) \quad (13)$$

where

N is the number of disturbing channels;

n is the number of disturbing pairs in disturbing channel l;

k is the number of the disturbed pair in the disturbed channel;

i is the number of the disturbing pair in a disturbing channel l;

l is the number of the disturbing channel;

$AFEXT_{l,i,k}$ is the alien far-end crosstalk loss coupled from pair *I* of disturbing channel (l) to the pair *k* of the disturbed channel.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

6.4.15.7 PS AACR-F for Class E_A and Class F_A channels

For Class E_A and F_A, the *PS AACR-F*$_k$ of disturbed pair *k* is determined according to Equation 14.

The *PS AACR-F* requirements shall be met at both ends of the channel.

$$PS\,AACR\text{-}F_k = PS\,AFEXT_k - IL_k \tag{14}$$

where

IL_k is the measured insertion loss of pair *k* in the disturbed channel;

$PS\,AFEXT_k$ is the power sum alien far-end crosstalk loss coupled to pair *k*.

Table 27 – PS AACR-F for channel

Class	Frequency MHz	Minimum PS AACR-F [a] dB
E_A	$1 \le f \le 500$	$77 - 20\lg(f)$
F_A	$1 \le f \le 1\,000$	$92 - 20\lg(f)$
[a] *PS AACR-F* at frequencies that correspond to calculated *PS AFEXT* values of greater than 67,0 dB or 102-15*lg(f) dB shall be for information only.		

Table 28 – Informative PS AACR-F values for channel at key frequencies

Frequency MHz	Minimum PS AACR-F dB	
	Class E_A	Class F_A
1[a]	64,7	64,8
100	37,0	52,0
250	29,0	44,0
500	23,0	38,0
1 000	N/A	32,0
[a] *PS AACR-F* values at 1MHz are affected by the computed insertion loss.		

6.4.15.8 PS AACR-F_{avg} for Class E_A and Class F_A channels

The *PS AACR-F*$_{avg}$ of a channel shall meet the requirements in Table 29.

The *PS AACR-F*$_{avg}$ requirements shall be met at both ends of the channel.

PS AACR-F$_{avg}$ is computed as follows:

$$PS\,AACR\text{-}F_{avg} = \frac{1}{n}\left[\sum_{k=1}^{n} PS\,AACR\text{-}F_k\right] \tag{15}$$

where

k is the number of the disturbed pair in the disturbed channel;

n is the number of disturbed pairs in the disturbed channel;

PS AACR-F$_k$ is the power sum alien far-end crosstalk loss coupled to pair *k* of the disturbed channel relative to insertion loss of pair *k* of the disturbed channel.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Table 29 – PS AACR-F_{avg} for channel

Class	Frequency MHz	Minimum PS AACR-F_{avg} [a, b] dB
E_A	$1 \le f \le 500$	$81 - 20\lg(f)$
[a] *PS AACR-F_{avg}* at frequencies that correspond to *PS AFEXT* values of greater than 67,0 dB or 102-15×lg(f) dB shall be for information only.		
[b] The *PS AACR-F_{avg}* limit for Class F_A channels is equal to PS AACR-F specified in Table 27.		

Table 30 – Informative PS AACR-F_{avg} values for channel at key frequencies

Frequency MHz	Minimum Class E_A PS AACR-F_{avg} dB
1[a]	64,7
100	41,0
250	33,0
500	27,0
[a] *PS AACR-F_{avg}* values at 1 MHz are affected by the computed insertion loss	

Renumber all the following tables consecutively, including all the additional tables from this Amendment, and update the cross-references.

Page 50

7.2.2.1 Component choice

Insert, after the first paragraph, the following new paragraph:

The balanced cabling reference implementations described in this clause contain reductions in channel length where operating temperatures are in excess of 20 °C. In order to maintain specific channel lengths under such conditions (due to the effect of ambient temperature and/or the impact of applications supported by the cabling) it may be necessary to either:

- specify cables with lower insertion loss specifications than those detailed in this clause;
- provide appropriate protection to reduce the operating temperature of the channel.

Insert, on page 51, in the bulleted list, the following new lines after Category 6 and Category 7, respectively:

- Category 6_A components provide Class E_A balanced cabling performance
- Category 7_A components provide Class F_A balanced cabling performance

Page 51

7.2.2.2 Dimensions

Add, on page 53, after the second paragraph below Figure 12, the following new text and table.:

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Table 31 contains the length assumptions used in the models shown in Figure 12. Channel performance can be met using components specified in Clauses 9, 10 and 13 when configured within the range of implementations provided by Figure 12 and Table 31.

Table 31 – Minimum and maximum length

Segment	Minimum m	Maximum m
FD-CP	15	85
CP-TO	5	-
FD-TO (no CP)	15	90
Work area cord [a]	2	5
Patch cord	2	-
Equipment cord [b]	2	5
All cords	-	10

[a] If there is no CP, the minimum length of the work area cord is 1 m.

[b] If there is no cross-connect, the minimum length of the equipment cord is 1 m.

Replace, on page 53, the existing Table 21 by new Table 32 as follows:

Table 32 – Horizontal link length equations

Model	Figure	Implementation Equation		
		Class D channels	**Class E and E_A channels**	**Class F and F_A channels**
Interconnect - TO	12a	$H = 109 - FX$	$H = 107 - 3^{a} - FX$	$H = 107 - 2^{a} - FX$
Cross-connect - TO	12b	$H = 107 - FX$	$H = 106 - 3^{a} - FX$	$H = 106 - 3^{a} - FX$
Interconnect - CP -TO	12c	$H = 107 - FX - CY$	$H = 106 - 3^{a} - FX - CY$	$H = 106 - 3^{a} - FX - CY$
Cross-connect - CP - TO	12d	$H = 105 - FX - CY$	$H = 105 - 3^{a} - FX - CY$	$H = 105 - 3^{a} - FX - CY$

H the maximum length of the fixed horizontal cable (m)

F combined length of patch cords/jumpers, equipment and work area cords (m)

C the length of the CP cable (m)

X the ratio of cord cable insertion loss (dB/m) to fixed horizontal cable insertion loss (dB/m) – see Clause 9

Y the ratio of CP cable insertion loss (dB/m) to fixed horizontal cable insertion loss (dB/m) – see Clause 9

NOTE For operating temperatures above 20 °C, H should be reduced by 0,2 % per °C for screened cables; 0,4 % per °C (20 °C to 40 °C) and 0,6 % per °C (>40 °C to 60 °C) for unscreened cables.

[a] This length reduction is to provide an allocated margin to accommodate insertion loss deviation.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Page 55

Replace existing Table 22 with new Table 33 below:

Table 33 – Backbone link length equations

	Class					
Component Category	**A** [a]	**B** [a]	**C** [a]	**D** [a]	**E** [a] **and** E_A [a]	**F** [a] **and** F_A [a]
5	2 000	$B = 250 - FX$	$B = 170 - FX$	$B = 105 - FX$	–	–
6	2 000	$B = 260 - FX$	$B = 185 - FX$	$B = 111 - FX$	$B = 105 - 3$ [b] $- FX$	–
7	2 000	$B = 260 - FX$	$B = 190 - FX$	$B = 115 - FX$	$B = 107 - 3$ [b] $- FX$	$B = 105 - 3$ [b] $- FX$

B the maximum length of the backbone cable (m)

F combined length of patch cords/jumpers and equipment cords (m)

X the ratio of cord cable insertion loss (dB/m) to backbone cable insertion loss (dB/m) – see Clause 9.

NOTE 1 Where channels contain a different number of connections than in the model shown in Figure 13, the fixed cable length shall be reduced (where more connections exist) or may be increased (where fewer connections exist) by 2 m per connection for category 5 cables and 1 m per connection for Category 6 and 7 cables. Additionally, the *NEXT*, return loss (*RL*) and *ELFEXT* performance should be verified.

NOTE 2 For operating temperatures above 20 °C, *B* should be reduced by 0,2 % per °C for screened cables; 0,4 % per °C (20 °C to 40 °C) and 0,6 % per °C (>40 °C to 60 °C) for unscreened cables.

[a] Applications limited by propagation delay or delay skew may not be supported if channel lengths exceed 100 m.

[b] This length reduction is to provide an allocated margin to accommodate insertion loss deviation.

Renumber Tables 23 to Table 49 accordingly and update the cross-references to these Tables.

Page 132

Bibliography

Add, on page 134, the following new reference:

ISO/IEC 24750, *Information technology – Assessment and mitigation of installed balanced cabling channels in order to support 10GBASE-T*

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

3, rue de Varembé
P.O. Box 131
CH-1211 Geneva 20
Switzerland

Tel: + 41 22 919 02 11
Fax: + 41 22 919 03 00
info@iec.ch
www.iec.ch

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale