INTERNATIONAL STANDARD

ISO/IEC 19757-2

Second edition
2008-12-15

Information technology — Document Schema Definition Language (DSDL) —

Part 2: Regular-grammar-based validation — RELAX NG

Technologies de l'information — Langage de définition de schéma de documents (DSDL) —

Partie 2: Validation de grammaire orientée courante — RELAX NG

Reference number
ISO/IEC 19757-2:2008(E)

© ISO/IEC 2008

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

© ISO/IEC 2008 – All rights reserved

Not for Resale

Contents

Page

Foreword ... iii

Introduction ... iv

1 Scope ... 1

2 Normative references ... 1

3 Terms and definitions ... 1

4 Notation ... 4
4.1 EBNF ... 4
4.2 Inference rules ... 4
4.2.1 Variables ... 4
4.2.2 Propositions ... 5
4.2.3 Expressions ... 6

5 Data model ... 7

6 Full syntax ... 8

7 Simplification ... 9
7.1 General ... 9
7.2 Annotations ... 9
7.3 Whitespace ... 9
7.4 `datatypeLibrary` attribute ... 9
7.5 `type` attribute of `value` element ... 10
7.6 `href` attribute ... 10
7.7 `externalRef` element ... 10
7.8 `include` element ... 10
7.9 `name` attribute of `element` and `attribute` elements ... 11
7.10 `ns` attribute ... 11
7.11 QNames ... 11
7.12 `div` element ... 11
7.13 Number of child elements ... 11
7.14 `mixed` element ... 12
7.15 `optional` element ... 12
7.16 `zeroOrMore` element ... 12
7.17 Constraints ... 12
7.18 `combine` attribute ... 13
7.19 `grammar` element ... 13
7.20 `define` and `ref` elements ... 13
7.21 `notAllowed` element ... 14
7.22 `empty` element ... 14

8 Simple syntax ... 14

9 Semantics ... 15
9.1 Inference rules ... 15
9.2 Name classes ... 15
9.3 Patterns ... 16
9.3.1 `choice` pattern ... 16
9.3.2 `group` pattern ... 16
9.3.3 `empty` pattern ... 16
9.3.4 `text` pattern ... 16
9.3.5 `oneOrMore` pattern ... 17
9.3.6 `interleave` pattern ... 17
9.3.7 `element` and `attribute` pattern ... 17
9.3.8 `data` and `value` pattern ... 18
9.3.9 Built-in datatype library ... 18
9.3.10 `list` pattern ... 19
9.4 Validity ... 19

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10 Restrictions 19
10.1 General 19
10.2 Prohibited paths 19
10.2.1 General 19
10.2.2 `attribute` pattern 20
10.2.3 `oneOrMore` pattern 20
10.2.4 `list` pattern 20
10.2.5 `except` element in `data` pattern 20
10.2.6 `start` element 21
10.3 String sequences 21
10.4 Restrictions on attributes 23
10.5 Restrictions on `interleave` 23

11 Conformance 23

Annex A (normative) **RELAX NG schema for RELAX NG** 24

Annex B (informative) **Examples** 30
B.1 Data model 30
B.2 Full syntax example 31
B.3 Simple syntax example 31
B.4 Validation example 32

Annex C (normative) **RELAX NG Compact syntax** 34
C.1 Introduction 34
C.2 Syntax 34
C.3 Lexical structure 36
C.4 Declarations 37
C.5 Annotations 39
C.5.1 Support for annotations 39
C.5.2 Initial annotations 39
C.5.3 Documentation shorthand 39
C.5.4 Following annotations 40
C.5.5 Grammar annotations 40
C.6 Conformance 40
C.6.1 Types of conformance 40
C.6.2 Validator 41
C.6.3 Structure preserving translator 41
C.6.4 Non-structure preserving translator 41
C.7 Media type registration template for the RELAX NG Compact Syntax 41

Bibliography 43

© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 19757-2 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 34, *Document description and processing languages*.

This second edition cancels and replaces the first edition (ISO/IEC 19757-2:2003), of which it constitutes a minor revision. It also incorporates the Amendment ISO/IEC 19757-2:2003/Amd.1:2006.

ISO/IEC 19757 consists of the following parts, under the general title *Information technology — Document Schema Definition Language (DSDL)*:

— *Part 2: Regular-grammar-based validation — RELAX NG*

— *Part 3: Rule-based validation — Schematron*

— *Part 4: Namespace-based validation dispatching language — NVDL*

— *Part 8: Document semantics renaming language — DSRL*

— *Part 9: Namespace and datatype declaration in Document Type Definitions (DTDs)*

The following parts are under preparation:

— *Part 1: Overview*

— *Part 5: Extensible Datatypes*

— *Part 7: Character Repertoire Description Language (CREPDL)*

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Introduction

The structure of this part of ISO/IEC 19757 is as follows. Clause 5 describes the data model, which is the abstraction of an XML document used throughout the rest of the document. Clause 6 describes the syntax of a RELAX NG schema. Clause 7 describes a sequence of transformations that are applied to simplify a RELAX NG schema, and also specifies additional requirements on a RELAX NG schema. Clause 8 describes the syntax that results from applying the transformations; this simple syntax is a subset of the full syntax. Clause 9 describes the semantics of a correct RELAX NG schema that uses the simple syntax; the semantics specify when an element is valid with respect to a RELAX NG schema. Clause 10 describes requirements that apply to a RELAX NG schema after it has been transformed into simple form. Finally, Clause 11 describes conformance requirements for RELAX NG validators.

This part of ISO/IEC 19757 is based on the RELAX NG Specification[1], and the compact syntax shown in Annex C is based on the RELAX NG Compact Syntax[3]. A tutorial for RELAX NG is available separately (see the RELAX NG Tutorial[2]).

© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Information technology — Document Schema Definition Language (DSDL) —

Part 2:
Regular-grammar-based validation — RELAX NG

1 Scope

This part of ISO/IEC 19757 specifies RELAX NG, a schema language for XML. A RELAX NG schema specifies a pattern for the structure and content of an XML document. The pattern is specified by using a regular tree grammar. This part of ISO/IEC 19757 establishes requirements for RELAX NG schemas and specifies when an XML document matches the pattern specified by a RELAX NG schema.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE Each of the following documents has a unique identifier that is used to cite the document in the text. The unique identifier consists of the part of the reference up to the first comma.

W3C XML, *Extensible Markup Language (XML) 1.0 (Second Edition)*, W3C Recommendation, 6 October 2000, available at http://www.w3.org/TR/2000/REC-xml-20001006

W3C XML-Names, *Namespaces in XML*, W3C Recommendation, 14 January 1999, available at http://www.w3.org/TR/1999/REC-xml-names-19990114/

W3C XLink, *XML Linking Language (XLink) Version 1.0*, W3C Recommendation, 27 June 2001, available at http://www.w3.org/TR/2001/REC-xlink-20010627/

W3C XML-Infoset, *XML Information Set*, W3C Recommendation, 24 October 2001, available at http://www.w3.org/TR/2001/REC-xml-infoset-20011024/

IETF RFC 2045, *Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies*, Internet Standards Track Specification, November 1996, available at http://www.ietf.org/rfc/rfc2045.txt

IETF RFC 2046, *Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types*, Internet Standards Track Specification, November 1996, available at http://www.ietf.org/rfc/rfc2046.txt

IETF RFC 2396, *Uniform Resource Identifiers (URI): Generic Syntax*, Internet Standards Track Specification, August 1998, available at http://www.ietf.org/rfc/rfc2396.txt

IETF RFC 2732, *Format for Literal IPv6 Addresses in URL's*, Internet Standards Track Specification, December 1999, available at http://www.ietf.org/rfc/rfc2732.txt

IETF RFC 3023, *XML Media Types*, Internet Standards Track Specification, August 1998, available at http://www.ietf.org/rfc/rfc3023.txt

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1
resource
something with identity, potentially addressable by a URI

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

3.2
URI
compact string of characters that uses the syntax defined in IETF RFC 2396 to identify an abstract or physical resource

3.3
URI reference
URI or relative URI and optional fragment identifier

3.4
relative URI
form of URI reference that can be resolved with respect to a base URI to produce another URI

3.5
base URI
URI used to resolve relative URIs

3.6
fragment identifier
additional information in a URI reference used by a user agent after the retrieval action on a URI has been successfully performed

3.7
instance
XML document that is being validated with respect to a RELAX NG schema

3.8
space character
character with the code value #x20

3.9
whitespace character
character with the code value #x20, #x9, #xA or #xD

3.10
name
pair of a URI and a local name

3.11
namespace URI
URI that is part of a name

3.12
local name
NCName that is part of a name

3.13
NCName
string that matches the NCName production of W3C XML-Names

3.14
name class
part of a schema that can be matched against a name

3.15
pattern
part of a schema that can be matched against a set of attributes and a sequence of elements and strings

--`,,```,,,,````-`-`,,`,,`,`,,`---
© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

3.16
foreign attribute
attribute with a name whose namespace URI is neither the empty string nor the RELAX NG namespace URI

3.17
foreign element
element with a name whose namespace URI is not the RELAX NG namespace URI

3.18
full syntax
syntax of a RELAX NG grammar before simplification

3.19
simple syntax
syntax of a RELAX NG grammar after simplification

3.20
simplification
transformation of a RELAX NG schema in the full syntax to a schema in the simple syntax

3.21
datatype library
mapping from local names to datatypes

NOTE A datatype library is identified by a URI.

3.22
datatype
set of strings together with an equivalence relation on that set

3.23
axiom
proposition that is provable unconditionally

3.24
inference rule
rule consisting of one or more positive or negative antecendents and exactly one consequent, which makes the consequent provable if all the positive antecedents are provable and none of the negative antecendents is provable

3.25
valid with respect to a schema
member of the set of XML documents described by the schema

3.26
schema
specification of a set of XML documents

3.27
grammar
start pattern together with a mapping from NCNames to patterns

3.28
correct schema
schema that satisfies all the requirements of this part of ISO/IEC 19757

3.29
validator
software module that determine whether a schema is correct and whether an instance is valid with respect to a schema

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

3.30
path
list of NCNames separated by `/` or `//`

3.31
infoset
an abstraction of an XML document defined by W3C XML-Infoset

3.32
information item
constituent of an information set

3.33
data model
abstract representation of an XML document defined by this part of ISO/IEC 19757

3.34
XML document
string that is a well-formed XML document as defined in W3C XML

3.35
EBNF
Extended BNF
notation used to described context-free grammars

3.36
weak matching
kind of matching specified in detail in 9.3.7

3.37
in-scope grammar
nearest ancestor `grammar` element

3.38
content-type
one of the three values empty, complex, or simple

3.39
mixed sequence
sequence that may contain both elements and strings

4 Notation

4.1 EBNF

This part of ISO/IEC 19757 uses EBNF notation to describe the full syntax and the simple syntax of RELAX NG. A description of a grammar in EBNF consists of one or more production rules. Each production rule consists of the name of a non-terminal, followed by ::=, followed by a list of alternatives separated by |. Within an alternative, italic type is used to reference a non-terminal, concatenation indicates sequencing, [] indicates optionality, + indicates repetition one or more times and * indicates repetition zero or more times; other characters in normal type stand for themselves.

4.2 Inference rules

4.2.1 Variables

The symbol used for a variable indicates the variable's range as follows:

— *n* ranges over names

--`,,```,,,,````-`-`,,`,,`,`,,`---
© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

— *nc* ranges over name classes

— *ln* ranges over local names; a local name is a string that matches the NCName production of W3C XML-Names, that is, a name with no colons

— *u* ranges over URIs

— *cx* ranges over contexts (as defined in Clause 5)

— *a* ranges over sets of attributes; a set with a single member is considered the same as that member

— *m* ranges over sequences of elements and strings; a sequence with a single member is considered the same as that member; the sequences ranged over by *m* may contain consecutive strings and may contain strings that are empty

NOTE There are sequences ranged over by *m* that cannot occur as the children of an element.

— *p* ranges over patterns (elements matching the pattern production)

— *s* ranges over strings

— *ws* ranges over the empty sequence and strings that consist entirely of whitespace

— *params* ranges over sequences of parameters

— *e* ranges over elements

— *ct* ranges over content-types

4.2.2 Propositions

The following notation is used for propositions:

— *n* in *nc* means that name *n* is a member of name class *nc*

— $cx \vdash a; m =\sim p$ means that with respect to context *cx*, the attributes *a* and the sequence of elements and strings *m* matches the pattern *p*

— disjoint(a_1, a_2) means that there is no name that is the name of both an attribute in a_1 and of an attribute in a_2

— m_1 interleaves m_2; m_3 means that m_1 is an interleaving of m_2 and m_3

— $cx \vdash a; m =\sim_{weak} p$ means that with respect to context *cx*, the attributes *a* and the sequence of elements and strings *m* weakly matches the pattern *p*

— okAsChildren(*m*) means that the mixed sequence *m* can occur as the children of an element: it does not contain any member that is an empty string, nor does it contain two consecutive members that are both strings

— deref(*ln*) = <element> *nc p* </element> means that the grammar contains <define name="*ln*"> <element> *nc p* </element> </define>

— datatypeAllows(*u*, *ln*, *params*, *s*, *cx*) means that in the datatype library identified by URI *u*, the string *s* interpreted with context *cx* is a legal value of datatype *ln* with parameters *params*

— datatypeEqual(*u*, *ln*, s_1, cx_1, s_2, cx_2) means that in the datatype library identified by URI *u*, string s_1 interpreted with context cx_1 represents the same value of the datatype *ln* as the string s_2 interpreted in the context of cx_2

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

— $s_1 = s_2$ means that s_1 and s_2 are identical

— valid(*e*) means that the element *e* is valid with respect to the grammar

— start() = *p* means that the grammar contains <start> *p* </start>

— groupable(ct_1, ct_2) means that the content-types ct_1 and ct_2 are groupable

— $p :_c ct$ means that pattern *p* has content-type *ct*

— incorrectSchema() means that the schema is incorrect

4.2.3 Expressions

The following notation is used for expressions in propositions:

— name(*u*, *ln*) returns a name with URI *u* and local name *ln*

— m_1, m_2 returns the concatenation of the sequences m_1 and m_2

— $a_1 + a_2$ returns the union of a_1 and a_2

— ( ) returns an empty sequence

— { } returns an empty set

— "" returns an empty string

— attribute(*n*, *s*) returns an attribute with name *n* and value *s*

— element(*n*, *cx*, *a*, *m*) returns an element with name *n*, context *cx*, attributes *a* and mixed sequence *m* as children

— max(ct_1, ct_2) returns the maximum of ct_1 and ct_2 where the content-types in increasing order are empty( ), complex( ), simple( )

— normalizeWhiteSpace(*s*) returns the string *s*, with leading and trailing whitespace characters removed, and with each other maximal sequence of whitespace characters replaced by a single space character

— split(*s*) returns a sequence of strings one for each whitespace delimited token of *s*; each string in the returned sequence will be non-empty and will not contain any whitespace

— context(*u*, *cx*) returns a context which is the same as *cx* except that the default namespace is *u*; if *u* is the empty string, then there is no default namespace in the constructed context

— empty( ) returns the empty content-type

— complex( ) returns the complex content-type

— simple( ) returns the simple content-type

— [*cx*] within the start-tag of a pattern refers to the context of the pattern element

--`,,```,,,,````-`-`,,`,,`,`,,`---
© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

5 Data model

RELAX NG deals with XML documents representing both schemas and instances through an abstract data model. XML documents representing schemas and instances shall be well-formed in conformance with W3C XML and shall conform to the constraints of W3C XML-Names.

An XML document is represented by an element. An element consists of

— a name

— a context

— a set of attributes

— an ordered sequence of zero or more children; each child is either an element or a non-empty string; the sequence never contains two consecutive strings

A name consists of

— a string representing the namespace URI; the empty string has special significance, representing the absence of any namespace

— a string representing the local name; this string matches the NCName production of W3C XML-Names

A context consists of

— a base URI

— a namespace map; this maps prefixes to namespace URIs, and also may specify a default namespace URI (as declared by the `xmlns` attribute)

An attribute consists of

— a name

— a string representing the value

A string consists of a sequence of zero or more characters, where a character is as defined in W3C XML.

The element for an XML document is constructed from the infoset (see W3C XML-Infoset) of the XML document as follows. The notation [*x*] refers to the value of the *x* property of an information item. An element is constructed from a document information item by constructing an element from the [document element]. An element is constructed from an element information item by constructing the name from the [namespace name] and [local name], the context from the [base URI] and [in-scope namespaces], the attributes from the [attributes], and the children from the [children]. The attributes of an element are constructed from the unordered set of attribute information items by constructing an attribute for each attribute information item. The children of an element are constructed from the list of child information items first by removing information items other than element information items and character information items, and then by constructing an element for each element information item in the list and a string for each maximal sequence of character information items. An attribute is constructed from an attribute information item by constructing the name from the [namespace name] and [local name], and the value from the [normalized value]. When constructing the name of an element or attribute from the [namespace name] and [local name], if the [namespace name] property is not present, then the name is constructed from an empty string and the [local name]. A string is constructed from a sequence of character information items by constructing a character from the [character code] of each character information item.

It is possible for there to be multiple distinct infosets for a single XML document. This is because XML parsers are not required to process all DTD declarations or expand all external parsed general entities. Amongst these multiple infosets, there is exactly one infoset for which [all declarations processed] is true and which does not contain any

--`,,```,,,,````-`-`,,`,,`,`,,`---
© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

unexpanded entity reference information items. This is the infoset that is the basis for defining the RELAX NG data model.

6 Full syntax

The following grammar in EBNF notation summarizes the syntax of RELAX NG. Although the notation is based on the XML representation of an RELAX NG schema as a sequence of characters, the grammar operates at the data model level. For example, although the syntax uses `<text/>`, an instance or schema can use `<text></text>` instead, because they both represent the same element at the data model level. All elements shown in the grammar are qualified with the namespace URI:

```
http://relaxng.org/ns/structure/1.0
```

The symbols QName and NCName are defined in W3C XML-Names. The anyURI symbol indicates a string that, after escaping of disallowed values as described in Section 5.4 of W3C XLink, is a URI reference as defined in IETF RFC 2396 (as modified by IETF RFC 2732). The symbol string matches any string.

In addition to the attributes shown explicitly, any element can have an `ns` attribute and any element can have a `datatypeLibrary` attribute. The `ns` attribute can have any value. The value of the `datatypeLibrary` attribute shall match the anyURI symbol as described in the previous paragraph; in addition, it shall not use the relative form of URI reference and shall not have a fragment identifier; as an exception to this, the value may be the empty string.

Any element can also have foreign attributes in addition to the attributes shown in the grammar. A foreign attribute is an attribute with a name whose namespace URI is neither the empty string nor the RELAX NG namespace URI. Any element that cannot have string children (that is, any element other than `value`, `param` and `name`) may have foreign child elements in addition to the child elements shown in the grammar. A foreign element is an element with a name whose namespace URI is not the RELAX NG namespace URI. There are no constraints on the relative position of foreign child elements with respect to other child elements.

Any element can also have as children strings that consist entirely of whitespace characters, where a whitespace character is one of #x20, #x9, #xD or #xA. There are no constraints on the relative position of whitespace string children with respect to child elements.

Leading and trailing whitespace is allowed for value of each `name`, `type` and `combine` attribute and for the content of each `name` element.

pattern ::=
    <element name="*QName*"> *pattern*+ </element>
  | <element> *nameClass pattern*+ </element>
  | <attribute name="*QName*"> [*pattern*] </attribute>
  | <attribute> *nameClass* [*pattern*] </attribute>
  | <group> *pattern*+ </group>
  | <interleave> *pattern*+ </interleave>
  | <choice> *pattern*+ </choice>
  | <optional> *pattern*+ </optional>
  | <zeroOrMore> *pattern*+ </zeroOrMore>
  | <oneOrMore> *pattern*+ </oneOrMore>
  | <list> *pattern*+ </list>
  | <mixed> *pattern*+ </mixed>
  | <ref name="*NCName*"/>
  | <parentRef name="*NCName*"/>
  | <empty/>
  | <text/>
  | <value [type="*NCName*"]> *string* </value>
  | <data type="*NCName*"> *param** [*exceptPattern*] </data>
  | <notAllowed/>
  | <externalRef href="*anyURI*"/>
  | <grammar> *grammarContent** </grammar>
param ::=

© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
    <param name="NCName"> string </param>
exceptPattern ::=
    <except> pattern+ </except>
grammarContent ::=
    start
    | define
    | <div> grammarContent* </div>
    | <include href="anyURI"> includeContent* </include>
includeContent ::=
    start
    | define
    | <div> includeContent* </div>
start ::=
    <start [combine="method"]> pattern </start>
define ::=
    <define name="NCName" [combine="method"]> pattern+ </define>
method ::=
    choice
    | interleave
nameClass ::=
    <name> QName </name>
    | <anyName> [exceptNameClass] </anyName>
    | <nsName> [exceptNameClass] </nsName>
    | <choice> nameClass+ </choice>
exceptNameClass ::=
    <except> nameClass+ </except>
```

An alternative compact syntax is described in Annex C.

7 Simplification

7.1 General

The full syntax given in the previous clause is transformed into a simpler syntax by applying the following transformation rules in order. The effect shall be as if each rule was applied to all elements in the schema before the next rule is applied. A transformation rule may also specify constraints that shall be satisfied by a correct schema. The transformation rules are applied at the data model level. Before the transformations are applied, the schema is parsed into an element in the data model.

7.2 Annotations

Foreign attributes and elements are removed.

NOTE It is safe to remove `xml:base` attributes at this stage because `xml:base` attributes are used in determining the [base URI] of an element information item, which is in turn used to construct the base URI of the context of an element. Thus, after a document has been parsed into an element in the data model, `xml:base` attributes can be discarded.

7.3 Whitespace

For each element other than `value` and `param`, each child that is a string containing only whitespace characters is removed.

Leading and trailing whitespace characters are removed from the value of each `name`, `type` and `combine` attribute and from the content of each `name` element.

7.4 `datatypeLibrary` attribute

The value of each `datatypeLibary` attribute is transformed by escaping disallowed characters as specified in Section 5.4 of W3C XLink.

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

For any data or value element that does not have a datatypeLibrary attribute, a datatypeLibrary attribute is added. The value of the added datatypeLibrary attribute is the value of the datatypeLibrary attribute of the nearest ancestor element that has a datatypeLibrary attribute, or the empty string if there is no such ancestor. Then, any datatypeLibrary attribute that is on an element other than data or value is removed.

7.5 type attribute of value element

For any value element that does not have a type attribute, a type attribute is added with a value of token and the value of the datatypeLibrary attribute is changed to the empty string.

7.6 href attribute

The value of the href attribute on an externalRef or include element is first transformed by escaping disallowed characters as specified in Section 5.4 of W3C XLink. The URI reference is then resolved into an absolute form as described in Section 5.2 of IETF RFC 2396 using the base URI from the context of the element that bears the href attribute.

The value of the href attribute is used to construct an element (as specified in Clause 5). This shall be done as follows. The URI reference consists of the URI itself and an optional fragment identifier. The resource identified by the URI is retrieved. The result is a MIME entity (see IETF RFC 2045): a sequence of bytes labeled with a MIME media type (see IETF RFC 2046). The media type determines how an element is constructed from the MIME entity and optional fragment identifier. When the media type is application/xml or text/xml, the MIME entity shall be parsed as an XML document in accordance with the applicable RFC (at the term of writing IETF RFC 3023) and an element constructed from the result of the parse as specified in Clause 5. In particular, the charset parameter shall be handled as specified by the RFC. This specification does not define the handling of media types other than application/xml and text/xml. The href attribute shall not include a fragment identifier unless the registration of the media type of the resource identified by the attribute defines the interpretation of fragment identifiers for that media type.

NOTE IETF RFC 3023 does not define the interpretation of fragment identifiers for application/xml or text/xml.

7.7 externalRef element

An externalRef element is transformed as follows. An element is constructed using the URI reference that is the value of href attribute as specified in 7.6. This element shall match the syntax for pattern. The element is transformed by recursively applying the rules from this subclauses and from previous subclauses of this clause. This shall not result in a loop. In other words, the transformation of the referenced element shall not require the dereferencing of an externalRef element with an href attribute with the same value.

Any ns attribute on the externalRef element is transferred to the referenced element if the referenced element does not already have an ns attribute. The externalRef element is then replaced by the referenced element.

7.8 include element

An include element is transformed as follows. An element is constructed using the URI reference that is the value of href attribute as specified in 7.6. This element shall be a grammar element, matching the syntax for grammar.

This grammar element is transformed by recursively applying the rules from this subclause and from previous subclauses of this clause. This shall not result in a loop. In other words, the transformation of the grammar element shall not require the dereferencing of an include element with an href attribute with the same value.

Define the components of an element to be the children of the element together with the components of any div child elements. If the include element has a start component, then the grammar element shall have at least one start component; it is then transformed by removing all start components. If the include element has a define component, then the grammar element shall have at least one define component with the same name; it is then transformed by removing all such define components.

The include element is transformed into a div element. The attributes of the div element are the attributes of the include element other than the href attribute. The children of the div element are the grammar element (after

© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

the removal of the start and define components described by the preceding paragraph) followed by the children of the include element. The grammar element is then renamed to div.

7.9 name attribute of element and attribute elements

The name attribute on an element or attribute element is transformed into a name child element.

If an attribute element has a name attribute but no ns attribute, then an ns="" attribute is added to the name child element.

7.10 ns attribute

For any name, nsName or value element that does not have an ns attribute, an ns attribute is added. The value of the added ns attribute is the value of the ns attribute of the nearest ancestor element that has an ns attribute, or the empty string if there is no such ancestor. Then, any ns attribute that is on an element other than name, nsName or value is removed.

NOTE 1 The value of the ns attribute is not transformed either by escaping disallowed characters, or in any other way, because the value of the ns attribute is compared against namespace URIs in the instance, which are not subject to any transformation.

NOTE 2 Since include and externalRef elements are resolved after datatypeLibrary attributes are added but before ns attributes are added, ns attributes are inherited into external schemas but datatypeLibrary attributes are not.

7.11 QNames

For any name element containing a prefix, the prefix is removed and an ns attribute is added replacing any existing ns attribute. The value of the added ns attribute is the value to which the namespace map of the context of the name element maps the prefix. The context shall have a mapping for the prefix.

7.12 div element

Each div element is replaced by its children.

7.13 Number of child elements

A define, oneOrMore, zeroOrMore, optional, list or mixed element is transformed so that it has exactly one child element. If it has more than one child element, then its child elements are wrapped in a group element.

An element element is transformed so that it has exactly two child elements, the first being a name class and the second being a pattern. If it has more than two child elements, then the child elements other than the first are wrapped in a group element.

A except element is transformed so that it has exactly one child element. If it has more than one child element, then its child elements are wrapped in a choice element.

If an attribute element has only one child element (a name class), then a text element is added.

A choice, group or interleave element is transformed so that it has exactly two child elements. If it has one child element, then it is replaced by its child element. If it has more than two child elements, then the first two child elements are combined into a new element with the same name as the parent element and with the first two child elements as its children. For example,

```
<choice> p1 p2 p3 </choice>
```

is transformed to

```
<choice> <choice> p1 p2 </choice> p3 </choice>
```

--`,,```,,,,````-`-`,,`,,`,`,,`---

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

This reduces the number of child elements by one. The transformation is applied repeatedly until there are exactly two child elements.

7.14 `mixed` element

A `mixed` element is transformed into an interleaving with a `text` element:

```
<mixed> p </mixed>
```

is transformed into

```
<interleave> p <text/> </interleave>
```

7.15 `optional` element

An `optional` element is transformed into a `choice` element with two children, one child being the child of the `optional` element and the other child being an `empty` element:

```
<optional> p </optional>
```

is transformed into

```
<choice> p <empty/> </choice>
```

7.16 `zeroOrMore` element

A `zeroOrMore` element is transformed into a `choice` element with two children, one child being a `oneOrMore` element whose only child is the child of the `zeroOrMore` element and the other child being an `empty` element:

```
<zeroOrMore> p </zeroOrMore>
```

is transformed into

```
<choice> <oneOrMore> p </oneOrMore> <empty/> </choice>
```

7.17 Constraints

In this rule, no transformation is performed, but various constraints are checked.

NOTE 1 The constraints in this subclause, unlike the constraints specified in Clause 10, can be checked without resolving any `ref` elements, and are accordingly applied even to patterns that will disappear during later stages of simplification because they are not reachable (see 7.20) or because of `notAllowed` (see 7.21).

An `except` element that is a child of an `anyName` element shall not have any `anyName` descendant elements. An `except` element that is a child of an `nsName` element shall not have any `nsName` or `anyName` descendant elements.

A `name` element that occurs as the first child of an `attribute` element or as the descendant of the first child of an `attribute` element and that has an `ns` attribute with value equal to the empty string shall not have content equal to `xmlns`.

A `name` or `nsName` element that occurs as the first child of an `attribute` element or as the descendant of the first child of an `attribute` element shall not have an `ns` attribute with value `http://www.w3.org/2000/xmlns`.

NOTE 2 The W3C XML-Infoset defines the namespace URI of namespace declaration attributes to be `http://www.w3.org/2000/xmlns`.

A `data` or `value` element shall be correct in its use of datatypes. Specifically, the `type` attribute shall identify a datatype within the datatype library identified by the value of the `datatypeLibrary` attribute. For a `data` element, the parameter list shall be one that is allowed by the datatype (see 9.3.8).

© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

7.18 `combine` attribute

For each `grammar` element, all `define` elements with the same name are combined together. For any name, there shall not be more than one `define` element with that name that does not have a `combine` attribute. For any name, if there is a `define` element with that name that has a `combine` attribute with the value `choice`, then there shall not also be a `define` element with that name that has a `combine` attribute with the value `interleave`. Thus, for any name, if there is more than one `define` element with that name, then there is a unique value for the `combine` attribute for that name. After determining this unique value, the `combine` attributes are removed. A pair of definitions

```
<define name="n">
  p1
</define>
<define name="n">
  p2
</define>
```

is combined into

```
<define name="n">
  <c>
    p1
    p2
  </c>
</define>
```

where *c* is the value of the `combine` attribute. Pairs of definitions are combined until there is exactly one `define` element for each name.

Similarly, for each `grammar` element all `start` elements are combined together. There shall not be more than one `start` element that does not have a `combine` attribute. If there is a `start` element that has a `combine` attribute with the value `choice`, there shall not also be a `start` element that has a `combine` attribute with the value `interleave`.

7.19 `grammar` element

In this rule, the schema is transformed so that its top-level element is `grammar` and so that it has no other `grammar` elements.

Define the in-scope grammar for an element to be the nearest ancestor `grammar` element. A `ref` element refers to a `define` element if the value of their `name` attributes is the same and their in-scope grammars are the same. A `parentRef` element refers to a `define` element if the value of their `name` attributes is the same and the in-scope grammar of the in-scope grammar of the `parentRef` element is the same as the in-scope grammar of the `define` element. Every `ref` or `parentRef` element shall refer to a `define` element. A `grammar` shall have a `start` child element.

First, transform the top-level pattern *p* into `<grammar><start>`*p*`</start></grammar>`. Next, rename `define` elements so that no two `define` elements anywhere in the schema have the same name. To rename a `define` element, change the value of its `name` attribute and change the value of the `name` attribute of all `ref` and `parentRef` elements that refer to that `define` element. Next, move all `define` elements to be children of the top-level `grammar` element, replace each nested `grammar` element by the child of its `start` element and rename each `parentRef` element to `ref`.

7.20 `define` and `ref` elements

In this rule, the grammar is transformed so that every `element` element is the child of a `define` element, and the child of every `define` element is an `element` element.

First, remove any `define` element that is not reachable. A `define` element is reachable if there is reachable `ref` element referring to it. A `ref` element is reachable if it is the descendant of the `start` element or of a reachable

--`,,```,,,,````-`-`,,`,,`,`,,`---

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

`define` element. Now, for each `element` element that is not the child of a `define` element, add a `define` element to the `grammar` element, and replace the `element` element by a `ref` element referring to the added `define` element. The value of the `name` attribute of the added `define` element shall be different from value of the `name` attribute of all other `define` elements. The child of the added `define` element is the `element` element.

Define a `ref` element to be expandable if it refers to a `define` element whose child is not an `element` element. For each `ref` element that is expandable and is a descendant of a `start` element or an `element` element, expand it by replacing the `ref` element by the child of the `define` element to which it refers and then recursively expanding any expandable `ref` elements in this replacement. This shall not result in a loop. In other words expanding the replacement of a `ref` element having a `name` with value *n* shall not require the expansion of `ref` element also having a `name` with value *n*. Finally, remove any `define` element whose child is not an `element` element.

7.21 `notAllowed` element

In this rule, the grammar is transformed so that a `notAllowed` element occurs only as the child of a `start` or `element` element. An `attribute`, `list`, `group`, `interleave`, or `oneOrMore` element that has a `notAllowed` child element is transformed into a `notAllowed` element. A `choice` element that has two `notAllowed` child elements is transformed into a `notAllowed` element. A `choice` element that has one `notAllowed` child element is transformed into its other child element. An `except` element that has a `notAllowed` child element is removed. The preceding transformations are applied repeatedly until none of them is applicable any more. Any `define` element that is no longer reachable is removed.

7.22 `empty` element

In this rule, the grammar is transformed so that an `empty` element does not occur as a child of a `group`, `interleave`, or `oneOrMore` element or as the second child of a `choice` element. A `group`, `interleave` or `choice` element that has two `empty` child elements is transformed into an `empty` element. A `group` or `interleave` element that has one `empty` child element is transformed into its other child element. A `choice` element whose second child element is an `empty` element is transformed by interchanging its two child elements. A `oneOrMore` element that has an `empty` child element is transformed into an `empty` element. The preceding transformations are applied repeatedly until none of them is applicable any more.

8 Simple syntax

After applying all the rules in Clause 7, the schema will match the grammar described by the following EBNF notation:

```
grammar  ::=
    <grammar> <start> top </start> define* </grammar>
define  ::=
    <define name="NCName"> <element> nameClass top </element> </define>
top  ::=
    <notAllowed/>
    | pattern
pattern  ::=
    <empty/>
    | nonEmptyPattern
nonEmptyPattern  ::=
    <text/>
    | <data type="NCName" datatypeLibrary="anyURI"> param* [exceptPattern] </data>
    | <value datatypeLibrary="anyURI" type="NCName" ns="string"> string </value>
    | <list> pattern </list>
    | <attribute> nameClass pattern </attribute>
    | <ref name="NCName"/>
    | <oneOrMore> nonEmptyPattern </oneOrMore>
    | <choice> pattern nonEmptyPattern </choice>
    | <group> nonEmptyPattern nonEmptyPattern </group>
    | <interleave> nonEmptyPattern nonEmptyPattern </interleave>
param  ::=
    <param name="NCName"> string </param>
```


© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

exceptPattern ::=
    <except> *pattern* </except>
nameClass ::=
    <anyName> [*exceptNameClass*] </anyName>
    | <nsName ns="*string*"> [*exceptNameClass*] </nsName>
    | <name ns="*string*"> *NCName* </name>
    | <choice> *nameClass nameClass* </choice>
exceptNameClass ::=
    <except> *nameClass* </except>

With this grammar, no elements or attributes are allowed other than those explicitly shown.

NOTE The simple syntax is purely an internal artifact of this part of ISO/IEC 19757. The simple syntax is not an alternative interchange syntax for RELAX NG. A correct RELAX NG schema is always required to be in the full syntax and is never required to be in the simple syntax.

9 Semantics

9.1 Inference rules

This clause defines the semantics of a correct RELAX NG schema that has been transformed into the simple syntax. The semantics of a RELAX NG schema consist of a specification of what XML documents are valid with respect to that schema. The semantics are described formally. The formalism uses axioms and inference rules. Axioms are propositions that are provable unconditionally. An inference rule consists of one or more antecedents and exactly one consequent. An antecedent is either positive or negative. If all the positive antecedents of an inference rule are provable and none of the negative antecedents are provable, then the consequent of the inference rule is provable. An XML document is valid with respect to a RELAX NG schema if and only if the proposition that the element representing it in the data model is valid is provable in the formalism specified in this clause.

NOTE This kind of formalism is similar to a proof system. However, a traditional proof system only has positive antecedents.

The notation for inference rules separates the antecedents from the consequent by a horizontal line: the antecedents are above the line; the consequent is below the line. If an antecedent is of the form not(*p*), then it is a negative antecedent; otherwise, it is a positive antecedent. Both axioms and inferences rules may use variables. A variable has a name and optionally a subscript. The name of a variable is italicized. Each variable has a range that is determined by its name. If an axiom or inference rule contains multiple variables with the same range, then subscripts are used to distinguish them. Axioms and inference rules are implicitly universally quantified over the variables they contain. We explain this further below.

The possibility that an inference rule or axiom may contain more than one occurrence of a particular variable requires that an identity relation be defined on each kind of object over which a variable can range. The identity relation for all kinds of object is value-based. Two objects of a particular kind are identical if the constituents of the objects are identical. For example, two attributes are considered the same if they have the same name and the same value. Two characters are identical if their Unicode character codes are the same.

9.2 Name classes

The main semantic concept for name classes is that of a name belonging to a name class. A name class is an element that matches the production nameClass. A name is as defined in Clause 5: it consists of a namespace URI and a local name.

The first axiom is called (anyName 1):

(anyName 1) *n* in <anyName/>

NOTE 1 The (anyName 1) axiom says that for any name *n*, *n* belongs to the name class <anyName/>, in other words <anyName/> matches any name. Note the effect of the implicit universal quantification over the variables in the axiom: this is what makes the axiom apply for any name *n*.

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

The first inference rule is almost as simple:

(anyName 2) $$\frac{\text{not}(n \text{ in } nc)}{n \text{ in <anyName> <except> } nc \text{ </except> </anyName>}}$$

NOTE 2 The (anyName 2) inference rule says that for any name *n* and for any name class *nc*, if *n* does not belong to *nc*, then *n* belongs to <anyName> <except> *nc* </except> </anyName>. In other words, <anyName> <except> *nc* </except> </anyName> matches any name that does not match *nc*.

The remaining axioms and inference rules for name classes are as follows:

(nsName 1) name(*u*, *ln*) in <nsName ns="*u*"/>

(nsName 2) $$\frac{\text{not(name(} u, ln \text{) in } nc)}{\text{name(} u, ln \text{) in <nsName ns="} u \text{"> <except> } nc \text{ </except> </nsName>}}$$

(name) name(*u*, *ln*) in <name ns="*u*"> *ln* </name>

(name choice 1) $$\frac{n \text{ in } nc_1}{n \text{ in <choice> } nc_1\ nc_2 \text{ </choice>}}$$

(name choice 2) $$\frac{n \text{ in } nc_2}{n \text{ in <choice> } nc_1\ nc_2 \text{ </choice>}}$$

9.3 Patterns

9.3.1 `choice` pattern

The semantics of the `choice` pattern are as follows:

(choice 1) $$\frac{cx \vdash a; m =\sim p_1}{cx \vdash a; m =\sim \text{<choice> } p_1\ p_2 \text{ </choice>}}$$

(choice 2) $$\frac{cx \vdash a; m =\sim p_2}{cx \vdash a; m =\sim \text{<choice> } p_1\ p_2 \text{ </choice>}}$$

9.3.2 `group` pattern

The semantics of the `group` pattern are as follows:

(group) $$\frac{cx \vdash a_1; m_1 =\sim p_1 \qquad cx \vdash a_2; m_2 =\sim p_2}{cx \vdash a_1 + a_2; m_1, m_2 =\sim \text{<group> } p_1\ p_2 \text{ </group>}}$$

NOTE The restriction in 10.4 ensures that the set of attributes constructed in the consequent will not have multiple attributes with the same name.

9.3.3 `empty` pattern

The semantics of the `empty` pattern are as follows:

(empty) $cx \vdash \{\}; (\,) =\sim$ <empty/>

9.3.4 `text` pattern

The semantics of the `text` pattern are as follows:

© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

(text 1) $cx \vdash \{\}; (\,) =\sim$ <text/>

(text 2) $$\frac{cx \vdash \{\}; m =\sim \text{<text/>}}{cx \vdash \{\}; m, s =\sim \text{<text/>}}$$

The effect of the above rule is that a `text` element matches zero or more strings.

9.3.5 `oneOrMore` pattern

The semantics of the `oneOrMore` pattern are as follows:

(oneOrMore 1) $$\frac{cx \vdash a; m =\sim p}{cx \vdash a; m =\sim \text{<oneOrMore>}\ p\ \text{</oneOrMore>}}$$

(oneOrMore 2) $$\frac{cx \vdash a_1; m_1 =\sim p \quad cx \vdash a_2; m_2 =\sim \text{<oneOrMore>}\ p\ \text{</oneOrMore>} \quad \text{disjoint}(a_1, a_2)}{cx \vdash a_1 + a_2; m_1, m_2 =\sim \text{<oneOrMore>}\ p\ \text{</oneOrMore>}}$$

9.3.6 `interleave` pattern

The semantics of interleaving are defined by the following rules.

(interleaves 1) $(\,)$ interleaves $(\,); (\,)$

(interleaves 2) $$\frac{m_1 \text{ interleaves } m_2; m_3}{m_4, m_1 \text{ interleaves } m_4, m_2; m_3}$$

(interleaves 3) $$\frac{m_1 \text{ interleaves } m_2; m_3}{m_4, m_1 \text{ interleaves } m_2; m_4, m_3}$$

For example, the interleavings of <a/><a/> and <b/> are <a/><a/><b/>, <a/><b/><a/>, and <b/><a/><a/>.

The semantics of the `interleave` pattern are as follows:

(interleave) $$\frac{cx \vdash a_1; m_1 =\sim p_1 \quad cx \vdash a_2; m_2 =\sim p_2 \quad m_3 \text{ interleaves } m_1; m_2}{cx \vdash a_1 + a_2; m_3 =\sim \text{<interleave>}\ p_1\ p_2\ \text{</interleave>}}$$

NOTE The restriction in 10.4 ensures that the set of attributes constructed in the consequent will not have multiple attributes with the same name.

9.3.7 `element` and `attribute` pattern

The value of an attribute is always a single string, which may be empty. Thus, the empty sequence is not a possible attribute value. On the other hand, the children of an element can be an empty sequence and cannot consist of an empty string. In order to ensure that validation handles attributes and elements consistently, a variant of matching called weak matching is used. Weak matching is used when matching the pattern for the value of an attribute or for the attributes and children of an element.

The semantics of weak matching are as follows:

(weak match 1) $$\frac{cx \vdash a; m =\sim p}{cx \vdash a; m =\sim_{\text{weak}} p}$$

(weak match 2) $$\frac{cx \vdash a; (\,) =\sim p}{cx \vdash a; ws =\sim_{\text{weak}} p}$$

--`,,```,,,,````-`-`,,`,,`,`,,`---
© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

(weak match 3) $$\frac{cx \vdash a; \text{""} =\sim p}{cx \vdash a; (\,) =\sim_{\text{weak}} p}$$

The semantics of the `attribute` pattern are as follows:

(attribute) $$\frac{cx \vdash \{\,\}; s =\sim_{\text{weak}} p \qquad n \text{ in } nc}{cx \vdash \text{attribute}(\, n, s\,); (\,) =\sim \text{<attribute> } nc\ p\ \text{</attribute>}}$$

The semantics of the `element` pattern are as follows:

(element) $$\frac{cx_1 \vdash a; m =\sim_{\text{weak}} p \quad n \text{ in } nc \quad \text{okAsChildren}(m) \quad \text{deref}(ln) = \text{<element> } nc\ p\ \text{</element>}}{cx_2 \vdash \{\,\}; ws_1, \text{element}(\, n, cx_1, a, m\,), ws_2 =\sim \text{<ref name="}ln\text{"/>}}$$

9.3.8 `data` and `value` pattern

RELAX NG relies on datatype libraries to perform datatyping. A datatype library is identified by a URI. A datatype within a datatype library is identified by an NCName. A datatype library provides two services.

— It can determine whether a string is a legal representation of a datatype. This service accepts a list of zero or more parameters. For example, a string datatype might have a parameter specifying the length of a string. The datatype library determines what parameters are applicable for each datatype.

— It can determine whether two strings represent the same value of a datatype. This service does not have any parameters.

Both services may make use of the context of a string. For example, a datatype representing a QName would use the namespace map.

The datatypeEqual function shall be reflexive, transitive and symmetric, that is, the following inference rules shall hold:

(datatypeEqual reflexive) $$\frac{\text{datatypeAllows}(u, ln, params, s, cx)}{\text{datatypeEqual}(u, ln, s, cx, s, cx)}$$

(datatypeEqual transitive) $$\frac{\text{datatypeEqual}(u, ln, s_1, cx_1, s_2, cx_2) \quad \text{datatypeEqual}(u, ln, s_2, cx_3, s_3, cx_3)}{\text{datatypeEqual}(u, ln, s_1, cx_1, s_3, cx_3)}$$

(datatypeEqual symmetric) $$\frac{\text{datatypeEqual}(u, ln, s_1, cx_1, s_2, cx_2)}{\text{datatypeEqual}(u, ln, s_2, cx_2, s_1, cx_1)}$$

The semantics of the `data` and `value` patterns are as follows:

(value) $$\frac{\text{datatypeEqual}(u_1, ln, s_1, cx_1, s_2, \text{context}(\, u_2, cx_2\,))}{cx_1 \vdash \{\,\}; s_1 =\sim \text{<value datatypeLibrary="}u_1\text{" type="}ln\text{" ns="}u_2\text{" [}cx_2\text{]> } s_2\ \text{</value>}}$$

(data 1) $$\frac{\text{datatypeAllows}(u, ln, params, s, cx)}{cx \vdash \{\,\}; s =\sim \text{<data datatypeLibrary="}u\text{" type="}ln\text{"> } params\ \text{</data>}}$$

(data 2) $$\frac{\text{datatypeAllows}(u, ln, params, s, cx) \qquad \text{not}(cx \vdash a; s =\sim p)}{cx \vdash \{\,\}; s =\sim \text{<data datatypeLibrary="}u\text{" type="}ln\text{"> } params\ \text{<except> } p\ \text{</except> </data>}}$$

9.3.9 Built-in datatype library

The empty URI identifies a special built-in datatype library. This provides two datatypes, `string` and `token`. No parameters are allowed for either of these datatypes.

© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

The semantics of the two built-in datatypes are as follows:

(string allows) datatypeAllows("", "string", ( ), *s*, *cx*)

(string equal) datatypeEqual("", "string", *s*, cx_1, *s*, cx_2)

(token allows) datatypeAllows("", "token", ( ), *s*, *cx*)

(token equal) $$\frac{\text{normalizeWhiteSpace}(s_1) = \text{normalizeWhiteSpace}(s_2)}{\text{datatypeEqual}(\text{""}, \text{"token"}, s_1, cx_1, s_2, cx_2)}$$

9.3.10 `list` pattern

The semantics of the `list` pattern are as follows:

(list) $$\frac{cx \vdash \{\}; \text{split}(s) =\sim p}{cx \vdash \{\}; s =\sim \text{<list> } p \text{ </list>}}$$

NOTE It is crucial in the above inference rule that the sequence that is matched against a pattern can contain consecutive strings.

9.4 Validity

An element is valid with respect to a schema if the element together with an empty set of attributes it matches the `start` pattern of the schema's grammar.

(valid) $$\frac{\text{start}() = p \quad cx \vdash \{\}; e =\sim p}{\text{valid}(e)}$$

10 Restrictions

10.1 General

The following constraints are all checked after the grammar has been transformed to the simple form described in Clause 8.

NOTE The purpose of these restrictions is to catch user errors and to facilitate implementation.

10.2 Prohibited paths

10.2.1 General

This clause describes restrictions on where elements are allowed in the schema based on the names of the ancestor elements. The concept of a prohibited path is used to describe these restrictions. A path is a sequence of NCNames separated by `/` or `//`.

— An element matches a path *x*, where *x* is an NCName, if and only if the local name of the element is *x*

— An element matches a path *x*`/`*p*, where *x* is an NCName and *p* is a path, if and only if the local name of the element is *x* and the element has a child that matches *p*

— An element matches a path *x*`//`*p*, where *x* is an NCName and *p* is a path, if and only if the local name of the element is *x* and the element has a descendant that matches *p*

For example, the element

```
<foo>
  <bar>
```

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
      <baz/>
    </bar>
  </foo>
```

matches the paths `foo`, `foo/bar`, `foo//bar`, `foo//baz`, `foo/bar/baz`, `foo/bar//baz` and `foo//bar/baz`, but not `foo/baz` or `foobar`.

A correct RELAX NG schema shall be such that, after transformation to the simple form, it does not contain any element that matches a prohibited path.

10.2.2 `attribute` pattern

The following paths are prohibited:

— `attribute//ref`

— `attribute//attribute`

10.2.3 `oneOrMore` pattern

The following paths are prohibited:

— `oneOrMore//group//attribute`

— `oneOrMore//interleave//attribute`

10.2.4 `list` pattern

The following paths are prohibited:

— `list//list`

— `list//ref`

— `list//attribute`

— `list//text`

— `list//interleave`

10.2.5 `except` element in `data` pattern

The following paths are prohibited:

— `data/except//attribute`

— `data/except//ref`

— `data/except//text`

— `data/except//list`

— `data/except//group`

— `data/except//interleave`

— `data/except//oneOrMore`

© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

— `data/except//empty`

NOTE This implies that an `except` element with a `data` parent can contain only `data`, `value` and `choice` elements.

10.2.6 `start` element

The following paths are prohibited:

— `start//attribute`

— `start//data`

— `start//value`

— `start//text`

— `start//list`

— `start//group`

— `start//interleave`

— `start//oneOrMore`

— `start//empty`

10.3 String sequences

RELAX NG does not allow a pattern such as:

```
<element name="foo">
  <group>
    <data type="int"/>
    <element name="bar">
      <empty/>
    </element>
  </group>
</element>
```

Nor does it allow a pattern such as:

```
<element name="foo">
  <group>
    <data type="int"/>
    <text/>
  </group>
</element>
```

NOTE 1 For clarity, the above two examples have not been transformed to the simple syntax. This does not affect the requirement that the constraint in this sub-clause, as with all other constraints in this clause, is checked after the grammar has been transformed to the simple syntax.

More generally, if the pattern for the content of an element or attribute contains

— a pattern that can match a child (that is, an `element`, `data`, `value`, `list` or `text` pattern), and

— a pattern that matches a single string (that is, a `data`, `value` or `list` pattern),

then the two patterns shall be alternatives to each other.

--`,,```,,,,````-`-`,,`,,`,`,,`---
© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

This rule does not apply to patterns occurring within a `list` pattern.

To formalize this, the concept of a content-type is used. A pattern that is allowable as the content of an element has one of three content-types: empty, complex and simple.

The empty content-type is groupable with anything. In addition, the complex content-type is groupable with the complex content-type. The following rules formalize this.

(group empty 1) groupable(empty( ), *ct*)

(group empty 2) groupable(*ct*, empty( ))

(group complex) groupable(complex( ), complex( ))

Some patterns have a content-type. The following rules define when a pattern has a content-type and, if so, what it is.

(value) <value datatypeLibrary="u_1" type="*ln*" ns="u_2"> *s* </value> :$_c$ simple( )

(data 1) <data datatypeLibrary="*u*" type="*ln*"> *params* </data> :$_c$ simple( )

(data 2) $$\frac{p :_c ct}{\text{<data datatypeLibrary="}u\text{" type="}ln\text{"> } params \text{ <except> } p \text{ </except> </data>} :_c \text{ simple( )}}$$

(list) <list> *p* </list> :$_c$ simple( )

(text) <text/> :$_c$ complex( )

(ref) <ref name="*ln*"/> :$_c$ complex( )

(empty) <empty/> :$_c$ empty( )

(attribute) $$\frac{p :_c ct}{\text{<attribute> } nc\ p \text{ </attribute>} :_c \text{ empty( )}}$$

(group) $$\frac{p_1 :_c ct_1 \quad p_2 :_c ct_2 \quad \text{groupable}(ct_1, ct_2)}{\text{<group> } p_1\ p_2 \text{ </group>} :_c \max(\ ct_1, ct_2\ )}$$

(interleave) $$\frac{p_1 :_c ct_1 \quad p_2 :_c ct_2 \quad \text{groupable}(ct_1, ct_2)}{\text{<interleave> } p_1\ p_2 \text{ </interleave>} :_c \max(\ ct_1, ct_2\ )}$$

(oneOrMore) $$\frac{p :_c ct \quad \text{groupable}(ct, ct)}{\text{<oneOrMore> } p \text{ </oneOrMore>} :_c ct}$$

(choice) $$\frac{p_1 :_c ct_1 \quad p_2 :_c ct_2}{\text{<choice> } p_1\ p_2 \text{ </choice>} :_c \max(\ ct_1, ct_2\ )}$$

NOTE 2 The antecedent in the (data 2) rule above is in fact redundant because of the prohibited paths in 10.2.5.

Now the restriction can be described. All patterns occurring as the content of an element pattern shall have a content-type.

(element) $$\frac{\text{deref}(ln) = \text{<element> } nc\ p \text{ </element>} \quad \text{not}(p :_c ct)}{\text{incorrectSchema()}}$$

© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

10.4 Restrictions on attributes

Duplicate attributes are not allowed. More precisely, for a pattern <group> *p1 p2* </group> or <interleave> *p1 p2* </interleave>, there shall not be a name that belongs to both the name class of an `attribute` pattern occurring in *p1* and the name class of an `attribute` pattern occurring in *p2*. A pattern *p1* is defined to occur in a pattern *p2* if

— *p1* is *p2*, or

— *p2* is a `choice`, `interleave`, `group` or `oneOrMore` element and *p1* occurs in one or more children of *p2*.

Attributes using infinite name classes shall be repeated. More precisely, an `attribute` element that has an `anyName` or `nsName` descendant element shall have a `oneOrMore` ancestor element.

NOTE 1 This restriction is necessary for closure under negation.

Attributes using infinite name classes shall have `text` as their value. More precisely, an `attribute` element that has an `anyName` or `nsName` descendant element shall have a `text` child element.

NOTE 2 This restriction is necessary for closure under negation.

10.5 Restrictions on `interleave`

In order to facilitate implementation, an element of a particular name shall be allowed by at most one operand of an `interleave` pattern; similarly, a `text` pattern shall occur in at most one operand of an `interleave` pattern. More precisely, for a pattern <interleave> *p1 p2* </interleave>,

— there shall not be a name that belongs to both the name class of an `element` pattern referenced by a `ref` pattern occurring in *p1* and the name class of an `element` pattern referenced by a `ref` pattern occurring in *p2*, and

— a `text` pattern shall not occur in both *p1* and *p2*.

10.4 defines when one pattern is considered to occur in another pattern.

11 Conformance

A conforming RELAX NG validator shall be able to determine for any XML document whether it is a correct RELAX NG schema. A conforming RELAX NG validator shall be able to determine for any XML document and for any correct RELAX NG schema whether the document is valid with respect to the schema.

However, the requirements in the preceding paragraph do not apply if the schema uses a datatype library that the validator does not support. A conforming RELAX NG validator is only required to support the built-in datatype library described in 9.3.9. A validator that claims conformance to RELAX NG should document which datatype libraries it supports. The requirements in the preceding paragraph also do not apply if the schema includes `externalRef` or `include` elements and the validator is unable to retrieve the resource identified by the URI or is unable to construct an element from the retrieved resource. A validator that claims conformance to RELAX NG should document its capabilities for handling URI references.

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Annex A
(normative)

RELAX NG schema for RELAX NG

A correct RELAX NG schema shall be valid with respect to the following schema.

```
<grammar datatypeLibrary="http://www.w3.org/2001/XMLSchema-datatypes"
  ns="http://relaxng.org/ns/structure/1.0"
  xmlns="http://relaxng.org/ns/structure/1.0">

  <start>
    <ref name="pattern"/>
  </start>

  <define name="pattern">
    <choice>
      <element name="element">
        <choice>
          <attribute name="name">
            <data type="QName"/>
          </attribute>
          <ref name="open-name-class"/>
        </choice>
        <ref name="common-atts"/>
        <ref name="open-patterns"/>
      </element>
      <element name="attribute">
        <ref name="common-atts"/>
        <choice>
          <attribute name="name">
            <data type="QName"/>
          </attribute>
          <ref name="open-name-class"/>
        </choice>
        <interleave>
          <ref name="other"/>
          <optional>
            <ref name="pattern"/>
          </optional>
        </interleave>
      </element>
      <element name="group">
        <ref name="common-atts"/>
        <ref name="open-patterns"/>
      </element>
      <element name="interleave">
        <ref name="common-atts"/>
        <ref name="open-patterns"/>
      </element>
      <element name="choice">
        <ref name="common-atts"/>
        <ref name="open-patterns"/>
      </element>
      <element name="optional">
        <ref name="common-atts"/>
```


© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
  <ref name="open-patterns"/>
</element>
<element name="zeroOrMore">
  <ref name="common-atts"/>
  <ref name="open-patterns"/>
</element>
<element name="oneOrMore">
  <ref name="common-atts"/>
  <ref name="open-patterns"/>
</element>
<element name="list">
  <ref name="common-atts"/>
  <ref name="open-patterns"/>
</element>
<element name="mixed">
  <ref name="common-atts"/>
  <ref name="open-patterns"/>
</element>
<element name="ref">
  <attribute name="name">
    <data type="NCName"/>
  </attribute>
  <ref name="common-atts"/>
  <ref name="other"/>
</element>
<element name="parentRef">
  <attribute name="name">
    <data type="NCName"/>
  </attribute>
  <ref name="common-atts"/>
  <ref name="other"/>
</element>
<element name="empty">
  <ref name="common-atts"/>
  <ref name="other"/>
</element>
<element name="text">
  <ref name="common-atts"/>
  <ref name="other"/>
</element>
<element name="value">
  <optional>
    <attribute name="type">
      <data type="NCName"/>
    </attribute>
  </optional>
  <ref name="common-atts"/>
  <text/>
</element>
<element name="data">
  <attribute name="type">
    <data type="NCName"/>
  </attribute>
  <ref name="common-atts"/>
  <interleave>
    <ref name="other"/>
    <group>
      <zeroOrMore>
        <element name="param">
          <attribute name="name">
```

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
                <data type="NCName"/>
              </attribute>
              <ref name="common-atts"/>
              <text/>
            </element>
          </zeroOrMore>
          <optional>
            <element name="except">
              <ref name="common-atts"/>
              <ref name="open-patterns"/>
            </element>
          </optional>
        </group>
      </interleave>
    </element>
    <element name="notAllowed">
      <ref name="common-atts"/>
      <ref name="other"/>
    </element>
    <element name="externalRef">
      <attribute name="href">
        <data type="anyURI"/>
      </attribute>
      <ref name="common-atts"/>
      <ref name="other"/>
    </element>
    <element name="grammar">
      <ref name="common-atts"/>
      <ref name="grammar-content"/>
    </element>
  </choice>
</define>

<define name="grammar-content">
  <interleave>
    <ref name="other"/>
    <zeroOrMore>
      <choice>
        <ref name="start-element"/>
        <ref name="define-element"/>
        <element name="div">
          <ref name="common-atts"/>
          <ref name="grammar-content"/>
        </element>
        <element name="include">
          <attribute name="href">
            <data type="anyURI"/>
          </attribute>
          <ref name="common-atts"/>
          <ref name="include-content"/>
        </element>
      </choice>
    </zeroOrMore>
  </interleave>
</define>

<define name="include-content">
  <interleave>
    <ref name="other"/>
    <zeroOrMore>
```


© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
      <choice>
        <ref name="start-element"/>
        <ref name="define-element"/>
        <element name="div">
          <ref name="common-atts"/>
          <ref name="include-content"/>
        </element>
      </choice>
    </zeroOrMore>
  </interleave>
</define>

<define name="start-element">
  <element name="start">
    <ref name="combine-att"/>
    <ref name="common-atts"/>
    <ref name="open-pattern"/>
  </element>
</define>

<define name="define-element">
  <element name="define">
    <attribute name="name">
      <data type="NCName"/>
    </attribute>
    <ref name="combine-att"/>
    <ref name="common-atts"/>
    <ref name="open-patterns"/>
  </element>
</define>

<define name="combine-att">
  <optional>
    <attribute name="combine">
      <choice>
        <value>choice</value>
        <value>interleave</value>
      </choice>
    </attribute>
  </optional>
</define>

<define name="open-patterns">
  <interleave>
    <ref name="other"/>
    <oneOrMore>
      <ref name="pattern"/>
    </oneOrMore>
  </interleave>
</define>

<define name="open-pattern">
  <interleave>
    <ref name="other"/>
    <ref name="pattern"/>
  </interleave>
</define>

<define name="name-class">
  <choice>
```

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
    <element name="name">
      <ref name="common-atts"/>
      <data type="QName"/>
    </element>
    <element name="anyName">
      <ref name="common-atts"/>
      <ref name="except-name-class"/>
    </element>
    <element name="nsName">
      <ref name="common-atts"/>
      <ref name="except-name-class"/>
    </element>
    <element name="choice">
      <ref name="common-atts"/>
      <ref name="open-name-classes"/>
    </element>
  </choice>
</define>

<define name="except-name-class">
  <interleave>
    <ref name="other"/>
    <optional>
      <element name="except">
        <ref name="open-name-classes"/>
      </element>
    </optional>
  </interleave>
</define>

<define name="open-name-classes">
  <interleave>
    <ref name="other"/>
    <oneOrMore>
      <ref name="name-class"/>
    </oneOrMore>
  </interleave>
</define>

<define name="open-name-class">
  <interleave>
    <ref name="other"/>
    <ref name="name-class"/>
  </interleave>
</define>

<define name="common-atts">
  <optional>
    <attribute name="ns"/>
  </optional>
  <optional>
    <attribute name="datatypeLibrary">
      <data type="anyURI"/>
    </attribute>
  </optional>
  <zeroOrMore>
    <attribute>
      <anyName>
        <except>
          <nsName/>
```

--`,,```,,,,````-`-`,,`,,`,`,,`---

© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
            <nsName ns=""/>
          </except>
        </anyName>
      </attribute>
    </zeroOrMore>
  </define>

  <define name="other">
    <zeroOrMore>
      <element>
        <anyName>
          <except>
            <nsName/>
          </except>
        </anyName>
        <zeroOrMore>
          <choice>
            <attribute>
              <anyName/>
            </attribute>
            <text/>
            <ref name="any"/>
          </choice>
        </zeroOrMore>
      </element>
    </zeroOrMore>
  </define>

  <define name="any">
    <element>
      <anyName/>
      <zeroOrMore>
        <choice>
          <attribute>
            <anyName/>
          </attribute>
          <text/>
          <ref name="any"/>
        </choice>
      </zeroOrMore>
    </element>
  </define>

</grammar>
```

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Annex B
(informative)

Examples

B.1 Data model

Suppose the document `http://www.example.com/doc.xml` is as follows:

```
<?xml version="1.0"?>
<foo><pre1:bar1 xmlns:pre1="http://www.example.com/n1"/><pre2:bar2
  xmlns:pre2="http://www.example.com/n2"/></foo>
```

The element representing this document has

— a name which has
  — the empty string as the namespace URI, representing the absence of any namespace
  — `foo` as the local name
— a context which has
  — `http://www.example.com/doc.xml` as the base URI
  — a namespace map which
    — maps the prefix `xml` to the namespace URI `http://www.w3.org/XML/1998/namespace` (the `xml` prefix is implicitly declared by every XML document)
    — specifies the empty string as the default namespace URI
— an empty set of attributes
— a sequence of children consisting of an element which has
  — a name which has
    — `http://www.example.com/n1` as the namespace URI
    — `bar1` as the local name
  — a context which has
    — `http://www.example.com/doc.xml` as the base URI
    — a namespace map which
      — maps the prefix `pre1` to the namespace URI `http://www.example.com/n1`
      — maps the prefix `xml` to the namespace URI `http://www.w3.org/XML/1998/namespace`
      — specifies the empty string as the default namespace URI
  — an empty set of attributes

© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

— an empty sequence of children

followed by an element which has

— a name which has

  — `http://www.example.com/n2` as the namespace URI

  — `bar2` as the local name

— a context which has

  — `http://www.example.com/doc.xml` as the base URI

  — a namespace map which

    — maps the prefix `pre2` to the namespace URI `http://www.example.com/n2`

    — maps the prefix `xml` to the namespace URI `http://www.w3.org/XML/1998/namespace`

    — specifies the empty string as the default namespace URI

— an empty set of attributes

— an empty sequence of children

B.2 Full syntax example

Here is an example of a schema in the full syntax for the document in B.1.

```
<?xml version="1.0"?>
<element name="foo"
         xmlns="http://relaxng.org/ns/structure/1.0"
         xmlns:a="http://relaxng.org/ns/annotation/1.0"
         xmlns:ex1="http://www.example.com/n1"
         xmlns:ex2="http://www.example.com/n2">
  <a:documentation>A foo element.</a:documentation>
  <element name="ex1:bar1">
    <empty/>
  </element>
  <element name="ex2:bar2">
    <empty/>
  </element>
</element>
```

B.3 Simple syntax example

The schema in B.2 could be transformed into the simple syntax:

```
<?xml version="1.0"?>
<grammar xmlns="http://relaxng.org/ns/structure/1.0">
  <start>
    <ref name="foo.element"/>
  </start>

  <define name="foo.element">
    <element>
      <name ns="">foo</name>
      <group>
```

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
        <ref name="bar1.element"/>
        <ref name="bar2.element"/>
      </group>
    </element>
  </define>

  <define name="bar1.element">
    <element>
      <name ns="http://www.example.com/n1">bar1</name>
      <empty/>
    </element>
  </define>

  <define name="bar2.element">
    <element>
      <name ns="http://www.example.com/n2">bar2</name>
      <empty/>
    </element>
  </define>
</grammar>
```

NOTE Strictly speaking, the result of simplification is an element in the data model rather than an XML document. For convenience, an XML document is used to represent an element in the data model.

B.4 Validation example

Let e_0 be

element(name("", "foo"), cx_0, { }, m)

where m is

e_1, e_2

and e_1 is

element(name("http://www.example.com/n1", "bar1"), cx_1, { }, ( ))

and e_2 is

element(name("http://www.example.com/n2", "bar2"), cx_2, { }, ( ))

Assuming appropriate definitions of cx_0, cx_1 and cx_2, this represents the document in B.1.

We now show how e_0 can be shown to be valid with respect to the schema in B.3. The schema is equivalent to the following propositions:

start() = <ref name="foo"/>

deref("foo.element") = <element> <name ns=""> "foo" </name> <group> <ref name="bar1"/> <ref name="bar2"/> </group> </element>

deref("bar1.element") = <element> <name ns="http://www.example.com/n1"> "bar1" </name> <empty/> </element>

deref("bar2.element") = <element> <name ns="http://www.example.com/n2"> "bar2" </name> <empty/> </element>

Let name class nc_1 be

© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

<name ns="http://www.example.com/n1"> "bar1" </name>

and let nc_2 be

<name ns="http://www.example.com/n2"> "bar2" </name>

Then, by the inference rule (name) in 9.2, we have

name("http://www.example.com/n1", "bar1") in nc_1

and

name("http://www.example.com/n2", "bar2") in nc_2

By the inference rule (empty) in 9.3.3, we have

cx_1 ⊢ { }; ( ) =~ <empty/>

and

cx_2 ⊢ { }; ( ) =~ <empty/>

Thus by the inference rule (element) in 9.3.7, we have

cx_0 ⊢ { }; e_1 =~ <ref name="bar1"/>

Note that we have chosen cx_0, since any context is allowed.

Likewise, we have

cx_0 ⊢ { }; e_2 =~ <ref name="bar2"/>

By the inference rule (group) in 9.3.1, we have

cx_0 ⊢ { }; e_1, e_2 =~ <group> <ref name="bar1"/> <ref name="bar2"/> </group>

By the inference rule (element) in 9.3.7, we have

cx_3 ⊢ { }; element(name("", "foo"), cx_0, { }, m) =~ <ref name="foo"/>

Here cx_3 is an arbitrary context.

Thus we can apply the inference rule (valid) in 9.4 and obtain

valid(e_0)

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Annex C
(normative)

RELAX NG Compact syntax

C.1 Introduction

This Annex describes a compact, non-XML syntax for RELAX NG.

The goals of the compact syntax are to:

— maximize readability;

— support all features of RELAX NG; it must be possible to translate a schema from the XML syntax to the compact syntax and back without losing significant information;

— support separate translation; a RELAX NG schema may be spread amongst multiple files; it must be possible to represent each of the files separately in the compact syntax; the representation of each file must not depend on the other files.

C.2 Syntax

The following is a summary of the syntax in EBNF. Square brackets are used to indicate optionality. The start symbol is topLevel.

```
topLevel ::=
    decl* (pattern | grammarContent*)
decl ::=
    ("namespace" identifierOrKeyword "=" namespaceURILiteral)
    | ("default" "namespace" [identifierOrKeyword] "=" namespaceURILiteral)
    | ("datatypes" identifierOrKeyword "=" literal)
pattern ::=
    ("element" nameClass "{" pattern "}")
    | ("attribute" nameClass "{" pattern "}")
    | (pattern ("," pattern)+)
    | (pattern ("&" pattern)+)
    | (pattern ("|" pattern)+)
    | (pattern "?")
    | (pattern "*")
    | (pattern "+")
    | ("list" "{" pattern "}")
    | ("mixed" "{" pattern "}")
    | identifier
    | ("parent" identifier)
    | "empty"
    | "text"
    | ([datatypeName] datatypeValue)
    | (datatypeName ["{" param* "}"] [exceptPattern])
    | "notAllowed"
    | ("external" anyURILiteral [inherit])
    | ("grammar" "{" grammarContent* "}")
    | ("(" pattern ")")
param ::=
    identifierOrKeyword "=" literal
exceptPattern ::=
```


© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
    "-" pattern
grammarContent ::=
    start
    | define
    | ("div" "{" grammarContent* "}")
    | ("include" anyURILiteral [inherit] ["{" includeContent* "}"])
includeContent ::=
    define
    | start
    | ("div" "{" includeContent* "}")
start ::=
    "start" assignMethod pattern
define ::=
    identifier assignMethod pattern
assignMethod ::=
    "="
    | "|="
    | "&="
nameClass ::=
    name
    | (nsName [exceptNameClass])
    | (anyName [exceptNameClass])
    | (nameClass "|" nameClass)
    | ("(" nameClass ")")
name ::=
    identifierOrKeyword
    | CName
exceptNameClass ::=
    "-" nameClass
datatypeName ::=
    CName
    | "string"
    | "token"
datatypeValue ::=
    literal
anyURILiteral ::=
    literal
namespaceURILiteral ::=
    literal
    | "inherit"
inherit ::=
    "inherit" "=" identifierOrKeyword
identifierOrKeyword ::=
    identifier
    | keyword
identifier ::=
    (NCName - keyword)
    | quotedIdentifier
quotedIdentifier ::=
    "\" NCName
CName ::=
    NCName ":" NCName
nsName ::=
    NCName ":*"
anyName ::=
    "*"
literal ::=
    literalSegment ("~" literalSegment)+
literalSegment ::=
    ('"' (Char - ('"' | newline))* '"')
```

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
    | ("'" (Char - ("'" | newline))* "'")
    | ('"""' (['"'] ['"'] (Char - '"')* '"""')
    | ("''''" (["'"] ["'"] (Char - "'")* "''''")
keyword  ::=
    "attribute"
   |"default"
   |"datatypes"
   |"div"
   |"element"
   |"empty"
   |"external"
   |"grammar"
   |"include"
   |"inherit"
   |"list"
   |"mixed"
   |"namespace"
   |"notAllowed"
   |"parent"
   |"start"
   |"string"
   |"text"
   |"token"
```

NCName is defined in W3C XML-Names. Char is defined in W3C XML.

In order to use a keyword as an identifier, it must be quoted with `\`. It is not necessary to quote a keyword that is used as the name of an element or attribute or as datatype parameter.

The value of a literal is the concatenation of the values of its constituent literalSegments. A literalSegment is always terminated only by an occurrence of the same delimiter that began it. The delimiter used to begin a literalSegment may be either one or three occurrences of a single or double quote character. Newlines are allowed only in literalSegments delimited by three quote characters. The value of a literal segment consists of the characters between its delimiters. One way to get a literal whose value contains both a single and a double quote is to divide the literal into multiple literalSegments so that the single and double quote are in separate literalSegments. Another way is to use a literalSegment delimited by three single or double quotes.

Annotations can be specified as described in C.5.

There is no notion of operator precedence. It is an error for patterns to combine the `|`, `&`, `,` and `-` operators without using parentheses to make the grouping explicit. For example, `foo | bar, baz` is not allowed; instead, either `(foo | bar), baz` or `foo | (bar, baz)` must be used. A similar restriction applies to name classes and the use of the `|` and `-` operators. These restrictions are not expressed in the above EBNF.

The value of an anyURILiteral specified with `include` or `external` is a URI reference to a grammar in the compact syntax.

C.3 Lexical structure

Whitespace is allowed between tokens. Tokens are the strings occurring in double quotes in the EBNF in C.2, except that literalSegment, nsName, CName, identifier and quotedIdentifer are single tokens.

Comments are also allowed between tokens. Comments start with a # and continue to the end of the line. Comments starting with ## are treated specially; see C.5.

A Unicode character with hex code *N* can be represented by the escape sequence `\x{`*N*`}`. Using such an escape sequence is completely equivalent to the entering the corresponding character directly. For example,

© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
element \x{66}\x{6f}\x{6f} { empty }
```

is equivalent to

```
element foo { empty }
```

C.4 Declarations

A `datatypes` declaration declares a prefix used in a QName identifying a datatype. For example,

```
datatypes xsd = "http://www.w3.org/2001/XMLSchema-datatypes"
element height { xsd:double }
```

In fact, in the above example, the `datatypes` declaration is not required: the `xsd` prefix is predeclared to the above URI.

A `namespace` declaration declares a prefix used in a QName specifying the name of an element or attribute. For example,

```
namespace rng = "http://relaxng.org/ns/structure/1.0"
element rng:text { empty }
```

As in XML, the `xml` prefix is predeclared.

A `default namespace` declaration declares the namespace used for unprefixed names specifying the name of an element (but not of an attribute). For example,

```
default namespace = "http://example.com"
element foo { attribute bar { string } }
```

is equivalent to

```
namespace ex = "http://example.com"
element ex:foo { attribute bar { string } }
```

A `default namespace` declaration may have a prefix as well. For example,

```
default namespace ex = "http://example.com"
```

is equivalent to

```
default namespace = "http://example.com"
namespace ex = "http://example.com"
```

The URI may be empty. This makes the prefix stand for the absent namespace URI. This is necessary for specifying a name class that matches any name with an absent namespace URI. For example,

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
namespace local = ""
element foo { attribute * - local:* { string }* }
```

is equivalent to

```
<element xmlns="http://relaxng.org/ns/structure/1.0""
         name="foo"
         ns="http://example.com">
  <zeroOrMore>
    <attribute>
      <anyName>
 <except>
   <nsName ns=""/>
 </except>
      </anyName>
      <data type="string"/>
    </attribute>
  <zeroOrMore>
</element>
```

RELAX NG has the feature that if a file does not specify an `ns` attribute then the `ns` attribute can be inherited from the including file. To support this feature, the keyword `inherit` can be specified in place of the namespace URI in a namespace declaration. For example,

```
default namespace this = inherit
element foo { element * - this:* { string }* }
```

is equivalent to

```
<element xmlns="http://relaxng.org/ns/structure/1.0"
         name="foo">
  <zeroOrMore>
    <element>
      <anyName>
 <except>
   <nsName/>
 </except>
      </anyName>
      <data type="string"/>
    </element>
  <zeroOrMore>
</element>
```

In addition, the `include` and `external` patterns can specify `inherit =` *`prefix`* to specify the namespace to be inherited by the referenced file. For example,

```
namespace x = "http://www.example.com"
external "foo.rng" inherit = x
```

is equivalent to

```
<externalRef href="foo.rng"
```


© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
      ns="http://www.example.com"
      xmlns="http://relaxng.org/ns/structure/1.0"/>
```

In the absence of an `inherit` parameter on `include` or `external`, the default namespace will be inherited by the referenced file.

In the absence of a `default namespace` declaration, a declaration of

```
default namespace = inherit
```

is assumed.

C.5 Annotations

C.5.1 Support for annotations

The RELAX NG XML syntax allows foreign elements and attributes to be used to annotate a RELAX NG schema. A schema in the compact syntax can also have annotations, which will turn into foreign elements and attributes when the schema is translated into XML syntax. The way these annotations are specified depends on where the foreign elements and attributes are to appear in the translated schema. There is also a special shorthand syntax when the foreign element is a `documentation` element.

C.5.2 Initial annotations

An annotation in square brackets can be inserted immediately before a pattern, param, nameClass, grammarContent or includeContent. It has the following syntax:

annotation ::=
    "[" *annotationAttribute* annotationElement** "]"
annotationAttribute ::=
    name "=" *literal*
annotationElement ::=
    name "[" *annotationAttribute** (*annotationElement* | *literal*)* "]"

Each of the annotationAttributes will turn into attributes on the corresponding RELAX NG element. Each of the annotationElements will turn into initial children of the corresponding RELAX NG element, except in the case where the RELAX NG element cannot have children, in which case they will turn into following elements.

C.5.3 Documentation shorthand

Comments starting with `##` are used to specify `documentation` elements from the `http://relaxng.org/ns/compatibility/annotations/1.0` namespace. For example,

```
## Represents a language
element lang {
  ## English
  "en" |
  ## Japanese
  "jp"
}
```

turns into

```
<element name="lang"
    xmlns:a="http://relaxng.org/ns/compatibility/annotations/1.0"
    xmlns="http://relaxng.org/ns/structure/1.0">
```

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
      <a:documentation>Represents a language</a:documentation>
      <choice>
        <value>en</value>
        <a:documentation>English</a:documentation>
        <value>jp</value>
        <a:documentation>Japanese</a:documentation>
      </choice>
    </element>
```

comments can only be used immediately before a pattern, nameClass, grammarContent or includeContent. Multiple ## comments are allowed. Multiple adjacent ## comments without any intervening blank lines are merged into a single `documentation` element. Any ## comments must precede any annotation in square brackets.

C.5.4 Following annotations

A pattern or nameClass may be followed by any number of followAnnotations with the following syntax:

followAnnotation ::=
"`>>`" *annotationElement*

Each such annotationElement turns into a following sibling of the RELAX NG element representing the pattern or nameClass.

C.5.5 Grammar annotations

An annotationElement may be used in any place where grammarContent or includeContent is allowed. For example,

```
namespace x = "http://www.example.com"

start = foo

x:entity [ name="picture" systemId="picture.jpeg" notation="jpeg" ]

foo = element foo { empty }
```

turns into

```
<grammar xmlns:x="http://www.example.com"
         xmlns="http://relaxng.org/ns/structure/1.0">
  <start>
    <ref name="foo"/>
  </start>
  <x:entity name="picture" systemId="picture.jpeg" notation="jpeg"/>
  <define name="foo">
    <element name="foo">
      <empty/>
    </element>
  </define>
</grammar>
```

If the name of such an element is a keyword, then it must be quoted with `\`.

C.6 Conformance

C.6.1 Types of conformance

There are three types of conformant implementation of the compact syntax.

--`,,```,,,,````-`-`,,`,,`,`,,`---
© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

C.6.2 Validator

A validator conforming to this specification must be able to determine whether a textual object is a correct RELAX NG Compact Syntax schema as specified in this Annex. It must also be able to determine for any XML document and for any correct RELAX NG Compact Syntax schema whether the document is valid (as defined in Clause 9) with respect to the translation of the schema into XML syntax. It need not be able to output a representation of the translation of the schema into XML syntax.

The requirements in the preceding paragraph are subject to the provisions of the second paragraph of Clause 11.

C.6.3 Structure preserving translator

A structure preserving translator must be able to translate any correct RELAX NG Compact Syntax schema into an XML document whose data model is strictly equivalent to the translation specified in this Annex. For this purpose, two instances of the data model (as specified in Clause 5) are considered strictly equivalent if they are identical after applying the simplifications specified in Sections 7.2, 7.3, 7.4, 7.8, 7.9 and 7.10, with the exception that the base URI in the context of elements may differ.

NOTE The RELAX NG compact syntax is not a representation of the XML syntax of a RELAX NG schema; rather it is a representation of the semantics of a RELAX NG schema. Details of the XML syntax that were judged to be insignificant are not captured in the compact syntax. For example, in the XML syntax if the name class for an `element` or `attribute` pattern consists of just a single name, it can be expressed either as a `name` attribute or as a `name` element; however, in the compact syntax, there is only one way to express such a name class. The simplifications listed in the previous paragraph correspond to those syntactic details that are not captured in the compact syntax.

When comparing two `include` or `externalRef` patterns in the XML source for strict equivalence, the value of the `href` attributes are not compared; instead the referenced XML documents are compared for strict equivalence.

C.6.4 Non-structure preserving translator

A non-structure preserving translator must be able to translate any correct RELAX NG Compact Syntax schema into an XML document whose data model is loosely equivalent to the translation specified in this Annex. For this purpose, two instances of the data model (as specified in Clause 5) are considered loosely equivalent if they are such that, after applying all the simplifications specified in Section 7 of this part of ISO/IEC 19757, one can be transformed into the other merely by reordering and renaming definitions. After the simplifications have been applied, the context of elements is ignored when comparing the two instances.

NOTE A validator for the compact syntax can be implemented as a combination of a non-structure preserving translator for the compact syntax and a validator for the XML syntax.

C.7 Media type registration template for the RELAX NG Compact Syntax

This registration template is registered at IANA.

```
MIME media type name: application

MIME subtype name: relax-ng-compact-syntax

Required parameters: none

Optional parameters: none

Encoding considerations: UTF-8 or UTF-16 shall be used for this media type.
Security considerations: When the RELAX NG validator retrieves a schema
in the RELAX NG compact syntax, it may further retrieve external schemas
that are referenced from the schema directly or indirectly.  Although
the RELAX NG validator is required not to retrieve an infinite number of
schemas, a large number of external schemas may be retrieved, thus
wasting the network, disk, and CPU power.
```

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
Interoperability considerations: RELAX NG has been widely used as an XML
schema language.  A notable example is the Open Document specification of
OASIS.

Published specification:
  ISO/IEC 19757-2, Document Schema Definition Language (DSDL)
  Part 2 - Regular-grammar-based validation -- RELAX NG,
  Amendment 1: Compact Syntax
  OASIS Committee Specification, RELAX NG Compact Syntax
  21 November 2002

Applications which use this media type: validators, schema authoring
tools, and so forth

Additional information:
  Magic number(s): none
  File extension(s): rnc
  Macintosh File Type Code(s): "TEXT"

Person & email address to contact for further information:
  MURATA Makoto (FAMILY Given), International University of Japan,
  eb2m-mrt@asahi-net.or.jp

Intended usage: COMMON

Author/Change controller: ISO/IEC JTC1/SC34
```


--`,,```,,,,````-`-`,,`,,`,`,,`---
© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Bibliography

[1] *RELAX NG Specification*, OASIS Committee Specification, 3 December 2001, available at http://www.oasis-open.org/committees/relax-ng/spec-20011203.html

[2] *RELAX NG Tutorial*, OASIS Committee Specification, 3 December 2001, available at http://www.oasis-open.org/committees/relax-ng/tutorial-20011203.html

[3] *RELAX NG Compact Syntax*, Oasis Committee Specification, 21 November 2002, available at http://www.oasis-open.org/committees/relax-ng/compact-20021121.html

© ISO/IEC 2008 – All rights reserved

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

ICS 35.240.30

Price based on 43 pages

© ISO/IEC 2008 – All rights reserved
Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale