ISO/IEC 29341-5-11

Edition 1.0 2008-11

INTERNATIONAL STANDARD

Information technology – UPnP Device Architecture – Part 5-11: Digital Security Camera Device Control Protocol – Digital Security Camera Settings Service



ISO/IEC 29341-5-11:2008(E)

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2008 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,…). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

ISO/IEC 29341-5-11

Edition 1.0 2008-11

INTERNATIONAL STANDARD

Information technology – UPnP Device Architecture – Part 5-11: Digital Security Camera Device Control Protocol – Digital Security Camera Settings Service

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE H

ICS 35.200

ISBN 2-8318-1007-2

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

CONTENTS

FOREWORD 4
ORIGINAL UPNP DOCUMENTS (informative) 6
1. Overview and Scope 8
2. Service Modeling Definitions 9
2.1. ServiceType 9
2.2. State Variables 9
2.2.1. AutomaticWhiteBalance 9
2.2.2. FixedWhiteBalance 9
2.2.3. AvailableRotations 9
2.2.4. DefaultRotation 10
2.2.5. Brightness 10
2.2.6. ColorSaturation 10
2.3. Eventing and Moderation 11
2.4. Actions 12
2.4.1. SetAutomaticWhiteBalance 12
2.4.2. GetAutomaticWhiteBalance 12
2.4.3. SetFixedWhiteBalance 13
2.4.4. GetFixedWhiteBalance 13
2.4.5. GetAvailableRotations 13
2.4.6. SetDefaultRotation 14
2.4.7. GetDefaultRotation 14
2.4.8. SetBrightness 14
2.4.9. GetBrightness 15
2.4.10. IncreaseBrightness 15
2.4.11. DecreaseBrightness 15
2.4.12. SetColorSaturation 16
2.4.13. GetColorSaturation 16
2.4.14. IncreaseColorSaturation 16
2.4.15. DecreaseColorSaturation 17
2.4.16. Non-Standard Actions Implemented by a UPnP Vendor 17
2.4.17. Common Error Codes 17
2.5. Theory of Operation 18
3. XML Service Description 19
4. Test 22

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

LIST OF TABLES

Table 1: State Variables 9
Table 2: Event Moderation 11
Table 3: Actions 12
Table 4: Arguments for *SetAutomaticWhiteBalance* 12
Table 5: Arguments for *GetAutomaticWhiteBalance* 13
Table 6: Arguments for *SetFixedWhiteBalance* 13
Table 7: Arguments for *GetFixedWhiteBalance* 13
Table 8: Arguments for *GetAvailableRotations* 13
Table 9: Arguments for *SetDefaultRotation* 14
Table 10: Arguments for *GetDefaultRotation* 14
Table 11: Arguments for *SetBrightness* 14
Table 12: Arguments for *GetBrightness* 15
Table 13: Arguments for *SetColorSaturation* 16
Table 14: Arguments for *GetColorSaturation* 16
Table 15: Common Error Codes 17

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

INFORMATION TECHNOLOGY – UPNP DEVICE ARCHITECTURE –

Part 5-11: Digital Security Camera Device Control Protocol – Digital Security Camera Settings Service

FOREWORD

1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.

2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.

4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.

5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.

6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.

7) All users should ensure that they have the latest edition of this publication.

8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.

9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

IEC and ISO draw attention to the fact that it is claimed that compliance with this document may involve the use of patents as indicated below.

ISO and IEC take no position concerning the evidence, validity and scope of the putative patent rights. The holders of the putative patent rights have assured IEC and ISO that they are willing to negotiate free licences or licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of the putative patent rights are registered with IEC and ISO.

Intel Corporation has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Intel Corporation
Standards Licensing Department
5200 NE Elam Young Parkway
MS: JFS-98
USA – Hillsboro, Oregon 97124

Microsoft Corporation has informed IEC and ISO that it has patent applications or granted patents as listed below:

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

6101499 / US; 6687755 / US; 6910068 / US; 7130895 / US; 6725281 / US; 7089307 / US; 7069312 / US; 10/783 524 /US

Information may be obtained from:

Microsoft Corporation
One Microsoft Way
USA – Redmond WA 98052

Philips International B.V. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Philips International B.V. – IP&S
High Tech campus, building 44 3A21
NL – 5656 Eindhoven

NXP B.V. (NL) has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

NXP B.V. (NL)
High Tech campus 60
NL – 5656 AG Eindhoven

Matsushita Electric Industrial Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Matsushita Electric Industrial Co. Ltd.
1-3-7 Shiromi, Chuoh-ku
JP – Osaka 540-6139

Hewlett Packard Company has informed IEC and ISO that it has patent applications or granted patents as listed below:

5 956 487 / US; 6 170 007 / US; 6 139 177 / US; 6 529 936 / US; 6 470 339 / US; 6 571 388 / US; 6 205 466 / US

Information may be obtained from:

Hewlett Packard Company
1501 Page Mill Road
USA – Palo Alto, CA 94304

Samsung Electronics Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Digital Media Business, Samsung Electronics Co. Ltd.
416 Maetan-3 Dong, Yeongtang-Gu,
KR – Suwon City 443-742

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC and ISO shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 29341-5-11 was prepared by UPnP Implementers Corporation and adopted, under the PAS procedure, by joint technical committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

The list of all currently available parts of the ISO/IEC 29341 series, under the general title *Universal plug and play (UPnP) architecture*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

ORIGINAL UPNP DOCUMENTS
(informative)

Reference may be made in this document to original UPnP documents. These references are retained in order to maintain consistency between the specifications as published by ISO/IEC and by UPnP Implementers Corporation. The following table indicates the original UPnP document titles and the corresponding part of ISO/IEC 29341:

UPnP Document Title	**ISO/IEC 29341 Part**
UPnP Device Architecture 1.0	ISO/IEC 29341-1
UPnP Basic:1 Device	ISO/IEC 29341-2
UPnP AV Architecture:1	ISO/IEC 29341-3-1
UPnP MediaRenderer:1 Device	ISO/IEC 29341-3-2
UPnP MediaServer:1 Device	ISO/IEC 29341-3-3
UPnP AVTransport:1 Service	ISO/IEC 29341-3-10
UPnP ConnectionManager:1 Service	ISO/IEC 29341-3-11
UPnP ContentDirectory:1 Service	ISO/IEC 29341-3-12
UPnP RenderingControl:1 Service	ISO/IEC 29341-3-13
UPnP MediaRenderer:2 Device	ISO/IEC 29341-4-2
UPnP MediaServer:2 Device	ISO/IEC 29341-4-3
UPnP AV Datastructure Template:1	ISO/IEC 29341-4-4
UPnP AVTransport:2 Service	ISO/IEC 29341-4-10
UPnP ConnectionManager:2 Service	ISO/IEC 29341-4-11
UPnP ContentDirectory:2 Service	ISO/IEC 29341-4-12
UPnP RenderingControl:2 Service	ISO/IEC 29341-4-13
UPnP ScheduledRecording:1	ISO/IEC 29341-4-14
UPnP DigitalSecurityCamera:1 Device	ISO/IEC 29341-5-1
UPnP DigitalSecurityCameraMotionImage:1 Service	ISO/IEC 29341-5-10
UPnP DigitalSecurityCameraSettings:1 Service	ISO/IEC 29341-5-11
UPnP DigitalSecurityCameraStillImage:1 Service	ISO/IEC 29341-5-12
UPnP HVAC_System:1 Device	ISO/IEC 29341-6-1
UPnP HVAC_ZoneThermostat:1 Device	ISO/IEC 29341-6-2
UPnP ControlValve:1 Service	ISO/IEC 29341-6-10
UPnP HVAC_FanOperatingMode:1 Service	ISO/IEC 29341-6-11
UPnP FanSpeed:1 Service	ISO/IEC 29341-6-12
UPnP HouseStatus:1 Service	ISO/IEC 29341-6-13
UPnP HVAC_SetpointSchedule:1 Service	ISO/IEC 29341-6-14
UPnP TemperatureSensor:1 Service	ISO/IEC 29341-6-15
UPnP TemperatureSetpoint:1 Service	ISO/IEC 29341-6-16
UPnP HVAC_UserOperatingMode:1 Service	ISO/IEC 29341-6-17
UPnP BinaryLight:1 Device	ISO/IEC 29341-7-1
UPnP DimmableLight:1 Device	ISO/IEC 29341-7-2
UPnP Dimming:1 Service	ISO/IEC 29341-7-10
UPnP SwitchPower:1 Service	ISO/IEC 29341-7-11
UPnP InternetGatewayDevice:1 Device	ISO/IEC 29341-8-1
UPnP LANDevice:1 Device	ISO/IEC 29341-8-2
UPnP WANDevice:1 Device	ISO/IEC 29341-8-3
UPnP WANConnectionDevice:1 Device	ISO/IEC 29341-8-4
UPnP WLANAccessPointDevice:1 Device	ISO/IEC 29341-8-5
UPnP LANHostConfigManagement:1 Service	ISO/IEC 29341-8-10
UPnP Layer3Forwarding:1 Service	ISO/IEC 29341-8-11
UPnP LinkAuthentication:1 Service	ISO/IEC 29341-8-12
UPnP RadiusClient:1 Service	ISO/IEC 29341-8-13
UPnP WANCableLinkConfig:1 Service	ISO/IEC 29341-8-14
UPnP WANCommonInterfaceConfig:1 Service	ISO/IEC 29341-8-15
UPnP WANDSLLinkConfig:1 Service	ISO/IEC 29341-8-16
UPnP WANEthernetLinkConfig:1 Service	ISO/IEC 29341-8-17
UPnP WANIPConnection:1 Service	ISO/IEC 29341-8-18
UPnP WANPOTSLinkConfig:1 Service	ISO/IEC 29341-8-19
UPnP WANPPPConnection:1 Service	ISO/IEC 29341-8-20
UPnP WLANConfiguration:1 Service	ISO/IEC 29341-8-21
UPnP Printer:1 Device	ISO/IEC 29341-9-1
UPnP Scanner:1.0 Device	ISO/IEC 29341-9-2
UPnP ExternalActivity:1 Service	ISO/IEC 29341-9-10
UPnP Feeder:1.0 Service	ISO/IEC 29341-9-11
UPnP PrintBasic:1 Service	ISO/IEC 29341-9-12
UPnP Scan:1 Service	ISO/IEC 29341-9-13
UPnP QoS Architecture:1.0	ISO/IEC 29341-10-1
UPnP QosDevice:1 Service	ISO/IEC 29341-10-10
UPnP QosManager:1 Service	ISO/IEC 29341-10-11
UPnP QosPolicyHolder:1 Service	ISO/IEC 29341-10-12
UPnP QoS Architecture:2	ISO/IEC 29341-11-1
UPnP QOS v2 Schema Files	ISO/IEC 29341-11-2

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

UPnP Document Title	ISO/IEC 29341 Part
UPnP QosDevice:2 Service	ISO/IEC 29341-11-10
UPnP QosManager:2 Service	ISO/IEC 29341-11-11
UPnP QosPolicyHolder:2 Service	ISO/IEC 29341-11-12
UPnP RemoteUIClientDevice:1 Device	ISO/IEC 29341-12-1
UPnP RemoteUIServerDevice:1 Device	ISO/IEC 29341-12-2
UPnP RemoteUIClient:1 Service	ISO/IEC 29341-12-10
UPnP RemoteUIServer:1 Service	ISO/IEC 29341-12-11
UPnP DeviceSecurity:1 Service	ISO/IEC 29341-13-10
UPnP SecurityConsole:1 Service	ISO/IEC 29341-13-11

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

1. Overview and Scope

This service definition is compliant with the UPnP Device Architecture version *1.0*.

This service provides *control* of the basic setting of the actual image generating part of the security camera. Security Camera Settings are global to the device and will affect the Security Camera Still and Motion Image services contained within the Security Camera device.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

2. Service Modeling Definitions

2.1. ServiceType

A service that is compliant with this template is identified with the following service type: **urn:schemas-upnp-org:service:** *DigitalSecurityCameraSettings:1*.

2.2. State Variables

Table 1: State Variables

Variable Name	Req. or Opt. [1]	Data Type	Allowed Value	Default Value	Eng. Units
AutomaticWhiteBalance	*O*	*boolean*	*1,0*	*1*	
FixedWhiteBalance	*R*	*ui4*	*[0..]*	*3000*	*K*
AvailableRotations	*O*	*string*			
DefaultRotation	*O*	*string*			
Brightness	*R*	*ui1*	*0..100*	*50*	*%*
ColorSaturation	*R*	*ui1*	*0..100*	*50*	*%*
Non-standard state variables implemented by an UPnP vendor go here.	X	*TBD*	*TBD*	*TBD*	*TBD*

[1] R = Required, O = Optional, X = Non-standard.

2.2.1. AutomaticWhiteBalance

White Balance describes what the eye perceives as white. This differs with ambient light. For instance an object does not have the same color if it is placed in a room lit by light bulbs which gives a rather red light as it would if the object was placed outdoors in bright sunlight (rather blue). The human eye automatically compensates for this difference in perceived color. Cameras must in a similar manner compensate for ambient light to avoid objects being reproduced with incorrect colors.

If automatic is ON white balance should be handled automatically by the camera.

If no automatic white balance is available in the device fixed white balance value shall be used.

2.2.2. FixedWhiteBalance

Fixed White balance is used in environments of known or constant light environments. The unit used is the temperature of the light in Kelvin.

2.2.3. AvailableRotations

The rotation in degrees of the image calculated from what is considered normal upright positioning (0) of the camera.

The value of this string should be a comma delimited list of all supported rotations.

The list order should be the lowest compression level first.

Example: 0, 90, 180, 270

This is a read only property.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

2.2.4. DefaultRotation

The value of this string must be one of the supported rotations specified in AvailableRotations.

2.2.5. Brightness

Brightness is the attribute of a visual sensation according to which an area appears to emit more or less light. It is a relative value and the definition of the normal value is left to the manufacturer.

The Value 50 is the device specific normal value. This single value must be supported.

The value 100 shall give maximum brightness.

The value 0 shall give maximum darkness.

If the full range 0..100 is unsupported, the legal values shall be a sequence of numbers appropriately mapped onto the 1..100 scale. For instance: 2, 34,45,50,74,87.

The Actions up and down shall make a complete step to the next supported legal value.

The response to an attempt to set an unsupported but legal value shall result in the nearest *supported* legal value.

2.2.6. ColorSaturation

Color Saturation describes the colorfulness of an area judged in proportion to its brightness.

At least the value 0 or the value 50 must be supported.

0 means Black and white and is the only value that must be supported by black and white cameras.

50 means device specific normal color, if no color control is available in a color camera this value is the only supported legal value.

The value 100 means very colorful images

The value 0 means black and white images only.

If the full range 0..100 is unsupported, the legal values shall be a sequence of numbers appropriately mapped onto the 1..100 scale. For instance: 2, 34,45,50,74,87.

The Actions up and down shall make a complete step to the next supported legal value.

The response to an attempt to set an unsupported but legal value shall result in the nearest *supported* legal value.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

2.3. Eventing and Moderation

Table 2: Event Moderation

Variable Name	Evented	Moderated Event	Max Event Rate [1]	Logical Combination	Min Delta per Event [2]
AutomaticWhiteBalance	*Yes*	*Yes*	*1*		*None*
FixedWhiteBalance	*Yes*	*Yes*	*1*		*None*
AvailableRotations	*No*	*No*	*N/A*		*N/A*
DefaultRotation	*Yes*	*Yes*	*1*		*None*
Brightness	*Yes*	*Yes*	*1*		*None*
ColorSaturation	*Yes*	*Yes*	*1*		*None*
Non-standard state variables implemented by an UPnP vendor go here.	*TBD*	*TBD*	*TBD*	*TBD*	*TBD*

[1] Determined by N, where Rate = (Event)/(N secs).
[2] (N) * (allowedValueRange Step).

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

2.4. Actions

Immediately following this table is detailed information about these actions, including short descriptions of the actions, the effects of the actions on state variables, and error codes defined by the actions.

Table 3: Actions

Name	Req. or Opt. [1]
SetAutomaticWhiteBalance	*O*
GetAutomaticWhiteBalance	*O*
SetFixedWhiteBalance	*R*
GetFixedWhiteBalance	*R*
GetAvailableRotations	*O*
SetDefaultRotation	*O*
GetDefaultRotation	*O*
SetBrightness	*R*
GetBrightness	*R*
IncreaseBrightness	*R*
DecreaseBrightness	*R*
SetColorSaturation	*R*
GetColorSaturation	*R*
IncreaseColorSaturation	*R*
DecreaseColorSaturation	*R*
Non-standard actions implemented by an UPnP vendor go here.	X

[1] R = Required, O = Optional, X = Non-standard.

2.4.1. SetAutomaticWhiteBalance

Enable or disable Automatic White Balance algorithm. When disabled the current fixed white balance value will be used.

2.4.1.1. Arguments

Table 4: Arguments for *SetAutomaticWhiteBalance*

Argument	Direction	relatedStateVariable
NewAutomaticWhiteBalance	*IN*	*AutomaticWhiteBalance*

2.4.1.2. Effect on State

Changes the value of AutomaticWhiteBalance to NewAutomaticWhiteBalance.

2.4.2. GetAutomaticWhiteBalance

Get AutomaticWhiteBalance.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

2.4.2.1. Arguments

Table 5: Arguments for *GetAutomaticWhiteBalance*

Argument	Direction	relatedStateVariable
RetAutomaticWhiteBalance	*OUT*	*AutomaticWhiteBalance*

2.4.3. SetFixedWhiteBalance

Set the value of the FixedWhiteBalance to NewFixedWhiteBalance.

2.4.3.1. Arguments

Table 6: Arguments for *SetFixedWhiteBalance*

Argument	Direction	relatedStateVariable
NewFixedWhiteBalance	*IN*	*FixedWhiteBalance*

2.4.3.2. Effect on State

Changes the value of FixedWhiteBalance to NewFixedWhiteBalance.
AutomaticWhiteBalance is set to false.

2.4.4. GetFixedWhiteBalance

Get FixedWhiteBalance.

2.4.4.1. Arguments

Table 7: Arguments for *GetFixedWhiteBalance*

Argument	Direction	relatedStateVariable
RetFixedWhiteBalance	*OUT*	*FixedWhiteBalance*

2.4.5. GetAvailableRotations

Get the list of supported rotations.

2.4.5.1. Arguments

Table 8: Arguments for *GetAvailableRotations*

Argument	Direction	relatedStateVariable
RetAvailableRotations	*OUT*	*AvailableRotations*

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

2.4.6. SetDefaultRotation

Set the default rotation of the image.

2.4.6.1. Arguments

Table 9: Arguments for *SetDefaultRotation*

Argument	Direction	relatedStateVariable
NewRotation	*IN*	*DefaultRotation*

2.4.6.2. Effect on State

Changes the value of DefaultRotation to NewRotation.

2.4.6.3. Errors

errorCode	errorDescription	Description
700	*NewRotation not supported*	NewRotation is not one of the supported rotations specified in AvailableRotations.

2.4.7. GetDefaultRotation

Get the default rotation.

2.4.7.1. Arguments

Table 10: Arguments for *GetDefaultRotation*

Argument	Direction	relatedStateVariable
RetRotation	*OUT*	*DefaultRotation*

2.4.8. SetBrightness

Set the value of the target brightness of the image. If set to a legal but by the device unsupported value the nearest supported value shall be set.

2.4.8.1. Arguments

Table 11: Arguments for *SetBrightness*

Argument	Direction	relatedStateVariable
NewBrightness	*IN*	*Brightness*

2.4.8.2. Effect on State

Changes the value of Brightness to NewBrightness.

2.4.8.3. Errors

errorCode	errorDescription	Description
701	*NewBrightness not supported*	NewBrightness is not a supported value.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

2.4.9. GetBrightness

Get the brightness.

2.4.9.1. Arguments

Table 12: Arguments for *GetBrightness*

Argument	Direction	relatedStateVariable
RetBrightness	*OUT*	*Brightness*

2.4.10.IncreaseBrightness

Increase brightness of the image to the nearest higher *supported* legal value.

2.4.10.1.Arguments

(None.)

2.4.10.2.Effect on State

The value of Brightness is being increased.

2.4.10.3.Errors

errorCode	errorDescription	Description
701	*NewBrightness not supported*	NewBrightness is not a supported value.

2.4.11.DecreaseBrightness

Decrease brightness of the image to the nearest lower *supported* legal value.

2.4.11.1.Arguments

(None.)

2.4.11.2.Effect on State

The value of Brightness is being decreased.

2.4.11.3.Errors

errorCode	errorDescription	Description
701	*NewBrightness not supported*	NewBrightness is not a supported value.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

2.4.12.SetColorSaturation

Set the value of the target Color Saturation of the image. If set to a legal but by the device unsupported value the nearest supported value shall be set.

2.4.12.1.Arguments

Table 13: Arguments for *SetColorSaturation*

Argument	Direction	relatedStateVariable
NewColorSaturation	*IN*	*ColorSaturation*

2.4.12.2.Effect on State

The value of ColorSaturation is changed to NewColorSaturation.

2.4.12.3.Errors

errorCode	errorDescription	Description
702	*NewColorSaturation not supported*	NewColorSaturation is not a supported value.

2.4.13.GetColorSaturation

Get the Color Saturation.

2.4.13.1.Arguments

Table 14: Arguments for *GetColorSaturation*

Argument	Direction	relatedStateVariable
RetColorSaturation	*OUT*	*ColorSaturation*

2.4.14.IncreaseColorSaturation

Increase ColorSaturation of the image to the nearest higher *supported* legal value.

2.4.14.1.Arguments

(None.)

2.4.14.2.Effect on State

The value of ColorSaturation is being increased.

2.4.14.3.Errors

errorCode	errorDescription	Description
702	*NewColorSaturation not supported*	NewColorSaturation is not a supported value.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

2.4.15.DecreaseColorSaturation

Decrease brightness of the image to the nearest lower *supported* legal value.

2.4.15.1.Arguments

(None.)

2.4.15.2.Effect on State

The value of ColorSaturation is being decreased.

2.4.15.3.Errors

errorCode	errorDescription	Description
702	*NewColorSaturation not supported*	NewColorSaturation is not a supported value.

2.4.16.Non-Standard Actions Implemented by a UPnP Vendor

To facilitate certification, non-standard actions implemented by UPnP vendors should be included in this service template. The UPnP Device Architecture lists naming requirements for non-standard actions (see the section on Description).

2.4.17.Common Error Codes

The following table lists error codes common to actions for this service type. If an action results in multiple errors, the most specific error should be returned.

Table 15: Common Error Codes

errorCode	errorDescription	Description
401	Invalid Action	See UPnP Device Architecture section on Control.
402	Invalid Args	See UPnP Device Architecture section on Control.
404	Invalid Var	See UPnP Device Architecture section on Control.
501	Action Failed	See UPnP Device Architecture section on Control.
600-699	TBD	Common action errors. Defined by UPnP Forum Technical Committee.
700	*NewRotation not supported*	NewRotation is not one of the supported rotations specified in AvailableRotations.
701	*NewBrightness not supported*	NewBrightness is not a supported value.
702	*NewColorSaturation not supported*	NewColorSaturation is not a supported value.
800-899	*TBD*	*(Specified by UPnP vendor.)*

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

2.5. Theory of Operation

An instance of Digital Security Camera Settings Services may be embedded into a Digital Security Camera Device or other devices requiring this service.

This service provides control of basic settings of the actual image generating part of for instance a security camera. Settings are global to the device and will affect images generated by the device regardless of retrieval method. For instance if a device is equipped with an instance of the *Digital Security Camera Motion Image Service* and an instance of the *Digital Security Camera Still Image Service*, images "retrieved" using either of these services will all be affected by changes in the here described *Settings Service*

The algorithm and functionality of *Automatic White Balance* is vendor specific, this service description document does not set any requirements on the actual implementation.

The algorithms and functionality behind *Brightness and Color Saturation* are vendor specific, this service description document does not set any requirements on the actual implementation given that they are able to produce "normal" responses at the value 50, lowest at 0 and highest at 100.

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

3. XML Service Description

```
<?xml version="1.0"?>
<scpd xmlns="urn:schemas-upnp-org:service-1-0">
  <specVersion>
    <major>1</major>
    <minor>0</minor>
  </specVersion>
  <actionList>
    <action>
    <name>SetAutomaticWhiteBalance</name>
      <argumentList>
        <argument>
          <name>NewAutomaticWhiteBalance</name>
          <relatedStateVariable>AutomaticWhiteBalance
          </relatedStateVariable>
          <direction>in</direction>
        </argument>
      </argumentList>
    </action>
    <action>
    <name>GetAutomaticWhiteBalance</name>
      <argumentList>
        <argument>
          <name>RetAutomaticWhiteBalance</name>
          <relatedStateVariable>AutomaticWhiteBalance
          </relatedStateVariable>
          <direction>out</direction>
        </argument>
      </argumentList>
    </action>
    <action>
    <name>SetFixedWhiteBalance</name>
      <argumentList>
        <argument>
          <name>NewFixedWhiteBalance</name>
          <relatedStateVariable>FixedWhiteBalance
          </relatedStateVariable>
          <direction>in</direction>
        </argument>
      </argumentList>
    </action>
    <action>
    <name>GetFixedWhiteBalance</name>
      <argumentList>
        <argument>
          <name>RetFixedWhiteBalance</name>
          <relatedStateVariable>FixedWhiteBalance
          </relatedStateVariable>
          <direction>out</direction>
        </argument>
      </argumentList>
    </action>
    <action>
    <name>GetAvailableRotations</name>
      <argumentList>
        <argument>
          <name>RetAvailableRotations</name>
         <relatedStateVariable>AvailableRotations</relatedStateVariable>
          <direction>out</direction>
        </argument>
      </argumentList>
    </action>
```

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
<action>
 <name>SetDefaultRotation</name>
   <argumentList>
     <argument>
       <name>NewRotation</name>
      <relatedStateVariable>DefaultRotation</relatedStateVariable>
       <direction>in</direction>
     </argument>
   </argumentList>
 </action>
<action>
 <name>GetDefaultRotation</name>
   <argumentList>
     <argument>
       <name>RetRotation</name>
      <relatedStateVariable>DefaultRotation</relatedStateVariable>
       <direction>out</direction>
     </argument>
   </argumentList>
 </action>
 <action>
 <name>SetBrightness</name>
   <argumentList>
     <argument>
       <name>NewBrightness</name>
      <relatedStateVariable>Brightness</relatedStateVariable>
       <direction>in</direction>
     </argument>
   </argumentList>
 </action>
 <action>
 <name>GetBrightness</name>
   <argumentList>
     <argument>
       <name>RetBrightness</name>
      <relatedStateVariable>Brightness</relatedStateVariable>
       <direction>out</direction>
     </argument>
   </argumentList>
 </action>
 <action>
 <name>IncreaseBrightness</name>
 </action>
 <action>
 <name>DecreaseBrightness</name>
 </action>
 <action>
 <name>SetColorSaturation</name>
   <argumentList>
     <argument>
       <name>NewColorSaturation</name>
      <relatedStateVariable>ColorSaturation</relatedStateVariable>
       <direction>in</direction>
     </argument>
   </argumentList>
 </action>
 <action>
 <name>GetColorSaturation</name>
   <argumentList>
     <argument>
       <name>RetColorSaturation</name>
      <relatedStateVariable>ColorSaturation</relatedStateVariable>
       <direction>out</direction>
     </argument>
```

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
      </argumentList>
    </action>
    <action>
    <name>IncreaseColorSaturation</name>
    </action>
    <action>
    <name>DecreaseColorSaturation</name>
    </action>
  </actionList>
  <serviceStateTable>
    <stateVariable sendEvents="yes">
      <name>AutomaticWhiteBalance</name>
      <dataType>boolean</dataType>
      <defaultValue>1</defaultValue>
      <allowedValueList>
        <allowedValue>1</allowedValue>
        <allowedValue>0</allowedValue>
      </allowedValueList>
    </stateVariable>
    <stateVariable sendEvents="yes">
      <name>FixedWhiteBalance</name>
      <dataType>ui4</dataType>
      <defaultValue>3000</defaultValue>
      <allowedValueRange>
        <minimum>0</minimum>
        <maximum>maximum</maximum>
        <step>1</step>
      </allowedValueRange>
    </stateVariable>
    <stateVariable sendEvents="no">
      <name>AvailableRotations</name>
      <dataType>string</dataType>
    </stateVariable>
    <stateVariable sendEvents="yes">
      <name>DefaultRotation</name>
      <dataType>string</dataType>
    </stateVariable>
    <stateVariable sendEvents="yes">
      <name>Brightness</name>
      <dataType>ui1</dataType>
      <defaultValue>50</defaultValue>
      <allowedValueRange>
        <minimum>0</minimum>
        <maximum>100</maximum>
        <step>1</step>
      </allowedValueRange>
    </stateVariable>
    <stateVariable sendEvents="yes">
      <name>ColorSaturation</name>
      <dataType>ui1</dataType>
      <defaultValue>50</defaultValue>
      <allowedValueRange>
        <minimum>0</minimum>
        <maximum>100</maximum>
        <step>1</step>
      </allowedValueRange>
    </stateVariable>
  </serviceStateTable>
</scpd>
```

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

4. Test

Testing of the UPnP functions Addressing, Discovery, Description, Control (Syntax) and Eventing are performed by the UPnP Test Tool v1.1 based on the following documents:

- UPnP Device Architecture v1.0
- The Service Definitions in chapter 2 of this document
- The XML Service Description in chapter 3 of this document
- The UPnP Test Tool service template test file: ***DigitalSecurityCameraSettings1.xml***
- The UPnP Test Tool service template test file: ***DigitalSecurityCameraSettings1.SyntaxTests.xml***

The test suite does not include tests for Control Semantics, since it is felt that such tests would not provide a higher level of interoperability.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

--`,,```,,,,````-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

3, rue de Varembé
PO Box 131
CH-1211 Geneva 20
Switzerland

Tel: + 41 22 919 02 11
Fax: + 41 22 919 03 00
info@iec.ch
www.iec.ch

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale