INTERNATIONAL STANDARD ISO/IEC 9596-1:1998
TECHNICAL CORRIGENDUM 2

Published 2002-12-01

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

Information technology — Open Systems Interconnection — Common management information protocol —

Part 1: Specification

TECHNICAL CORRIGENDUM 2

Technologies de l'information — Interconnexion de systèmes ouverts (OSI) — Protocole commun d'information de gestion —

Partie 1: Spécification

RECTIFICATIF TECHNIQUE 2

Technical Corrigendum 2 to ISO/IEC 9596-1:1998 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*.

ICS 35.100.70 **Ref. No. ISO/IEC 9596-1:1998/Cor.2:2002(E)**

© ISO/IEC 2002 – All rights reserved

Published in Switzerland

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

INTERNATIONAL STANDARD

ITU-T RECOMMENDATION

INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION – COMMON MANAGEMENT INFORMATION PROTOCOL: SPECIFICATION

TECHNICAL CORRIGENDUM 2

Revision to include ASN.1: 1997

1) Subclause 2.1

Insert the following references into this subclause:

- ITU-T Recommendation X.680 (1997) | ISO/IEC 8824-1:1998, *Information technology – Abstract Syntax Notation One (ASN.1): Specification of basic notation.*
- ITU-T Recommendation X.681 (1997) | ISO/IEC 8824-2:1998, *Information technology – Abstract Syntax Notation One (ASN.1): Information object specification.*
- ITU-T Recommendation X.682 (1997) | ISO/IEC 8824-3:1998, *Information technology – Abstract Syntax Notation One (ASN.1): Constraint specification.*
- ITU-T Recommendation X.690 (1997) | ISO/IEC 8825-1:1998, *Information technology – ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER).*
- ITU-T Recommendation X.691 (1997) | ISO/IEC 8825-2:1998, *Information technology – ASN.1 encoding rules: Specification of Packed Encoding Rules (PER).*
- ITU-T Recommendation X.880 (1994) | ISO/IEC 13712-1:1995, *Information technology – Remote Operations: Concepts, model and notation.*
- ITU-T Recommendation X.881 (1994) | ISO/IEC 13712-2:1995, *Information technology – Remote Operations: OSI realizations – Remote Operations Service Element (ROSE) service definition.*
- ITU-T Recommendation X.882 (1994) | ISO/IEC 13712-3:1995, *Information technology – Remote Operations: OSI realizations – Remote Operations Service Element (ROSE) protocol specification.*

2) Subclause 2.2

Replace subclause 2.2 with the following:

2.2 Paired Recommendations | International Standards equivalent in technical content

- CCITT Recommendation X.700 (1992), *Management framework for Open Systems Interconnection (OSI) for CCITT applications.*

  ISO/IEC 7498-4:1989, *Information processing systems – Open Systems Interconnection – Basic Reference Model – Part 4: Management framework.*

3) Subclause 3.3

Replace subclause 3.3 with the following:

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

3.3 Remote Operations definitions

This Recommendation | International Standard makes use of the following term defined in ITU-T Rec. X.880 | ISO/IEC 13172-1:

a) linked-operation.

This Recommendation | International Standard makes use of the following terms defined in ITU-T Rec. X.881 | ISO/IEC 13172-2:

a) association-initiator;

b) association-responder;

c) Remote Operation Service Element;

d) invoker;

e) performer.

4) Subclause 5.2

Replace the first paragraph with the following:

This Recommendation | International Standard uses the RO-INVOKE, RO-RESULT, RO-ERROR and RO-REJECT-U services of the Remote Operations Service Element (ROSE) defined in ITU-T Rec. X.880 | ISO/IEC 13712-1. ROSE assumes the use of the presentation service defined in ITU-T Rec. X.216 | ISO/IEC 8822. The confirmed operations of CMIP are asynchronous or synchronous as required by the application. The choice of asynchronous or synchronous is a local matter implemented by the application. The unconfirmed operations of CMIP are asynchronous, outcome not reported. Both the association-initiating and the association-responding application entities can invoke operations.

5) Subclause 5.2.2

Replace CCITT Rec. X.229 and ISO/IEC 9072-2 *with* ITU-T Rec. X.882 | ISO/IEC 13712-3.

6) Subclause 6.2.1

Replace CCITT Rec. X.229 and ISO/IEC 9072-2 *with* ITU-T Rec. X.882 | ISO/IEC 13712-3.

Replace InvokeID *with* invokeId *in Table 2.*

Replace Linked-ID *with* linkedId *in Table 2.*

7) Subclause 6.4.3

Replace linked-ID *with* linkedId *(occurs 4 times).*

8) Subclause 6.4.4

Replace linked-ID *with* linkedId *(occurs twice).*

9) Subclause 6.5.3

Replace linked-ID *with* linkedId *(occurs 4 times).*

10) Subclause 6.5.4

Replace linked-ID *with* linkedId *(occurs twice).*

11) Subclause 6.6.3

Replace linked-ID *with* linkedId *(occurs 4 times).*

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

12) Subclause 6.6.4

Replace linked-ID with linkedId *(occurs twice).*

13) Subclause 6.8.3

Replace linked-ID *with* linkedId *(occurs 4 times).*

14) Subclause 6.8.4

Replace linked-ID *with* linkedId *(occurs twice).*

15) Subclause 7.1

Replace the first paragraph with the following:

The abstract syntax is defined using the notation specified in ITU-T Rec. X.680 | ISO/IEC 8824-1.

16) Subclause 7.2

Replace Linked-ID *with* linkedId *in Table 4.*

Remove the last line of Table 4.

17) Subclause 7.4

Replace with the following:

7.4 CMIP data units

The protocol is described in terms of Common Management Information Protocol Data Units exchanged between the peer CMISEs. The PDUs are specified using ASN.1 and the ROSE information objects defined in ITU-T Rec. X.880 | ISO/IEC 13712-1.

```
-- Common Management Information Protocol (CMIP)

CMIP-1 {joint-iso-itu-t ms(9) cmip(1) modules(0) protocol(3)}

DEFINITIONS ::= BEGIN

-- This ASN.1 specification has been checked for conformance with the ASN.1 standard by the OSS ASN.1 Tools

IMPORTS

ERROR, OPERATION
    FROM Remote-Operations-Information-Objects
        {joint-iso-itu-t remote-operations(4) informationObjects(5) version1(0)}

ROS{}, InvokeId, noInvokeId
    FROM Remote-Operations-Generic-ROS-PDUs
        {joint-iso-itu-t remote-operations(4) generic-ROS-PDUs(6) version1(0)};

CMIP-Operations OPERATION ::= {
    m-Action                |
    m-Action-Confirmed      |
    m-CancelGet             |
    m-Create                |
    m-Delete                |
    m-EventReport           |
    m-EventReport-Confirmed |
    m-Get                   |
    m-Linked-Reply          |
    m-Set                   |
    m-Set-Confirmed         }
```

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

```
CMIP-Confirmed-Operations OPERATION ::= {
      m-Action-Confirmed          |
      m-CancelGet                 |
      m-Create                    |
      m-Delete                    |
      m-EventReport-Confirmed     |
      m-Get                       |
      m-Set-Confirmed             }

-- CMISE error definitions


accessDenied ERROR ::= {
      PRIORITY        {0}
      CODE            local : 2 }

classInstanceConflict ERROR ::= {
      PARAMETER       BaseManagedObjectId
      PRIORITY        {1}
      CODE            local : 19 }

complexityLimitation ERROR ::= {
      PARAMETER       ComplexityLimitation OPTIONAL TRUE
      PRIORITY        {1}
      CODE            local : 20 }

duplicateManagedObjectInstance ERROR ::= {
      PARAMETER       ObjectInstance
      PRIORITY        {1}
      CODE            local : 11 }

getListError ERROR ::= {
      PARAMETER       GetListError
      PRIORITY        {1}
      CODE            local : 7 }

invalidArgumentValue ERROR ::= {
      PARAMETER       InvalidArgumentValue
      PRIORITY        {1}
      CODE            local : 15 }

invalidAttributeValue ERROR ::= {
      PARAMETER       Attribute
      PRIORITY        {1}
      CODE            local : 6 }

invalidFilter ERROR ::= {
      PARAMETER       CMISFilter
      PRIORITY        {1}
      CODE            local : 4 }

invalidObjectInstance ERROR ::= {
      PARAMETER       ObjectInstance
      PRIORITY        {1}
      CODE            local : 17 }

invalidScope ERROR ::= {
      PARAMETER       Scope
      PRIORITY        {1}
      CODE            local : 16 }

missingAttributeValue ERROR ::= {
      PARAMETER       SET OF AttributeId
      PRIORITY        {1}
      CODE            local : 18 }

mistypedOperation ERROR ::= {
      PRIORITY        {1}
      CODE            local : 21 }
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
noSuchAction ERROR ::= {
    PARAMETER     NoSuchAction
    PRIORITY      {1}
    CODE          local : 9 }

noSuchArgument ERROR ::= {
    PARAMETER     NoSuchArgument
    PRIORITY      {1}
    CODE          local : 14 }

noSuchAttribute ERROR ::= {
    PARAMETER     AttributeId
    PRIORITY      {1}
    CODE          local : 5 }

noSuchEventType ERROR ::= {
    PARAMETER     NoSuchEventType
    PRIORITY      {1}
    CODE          local : 13 }

noSuchInvokeId ERROR ::= {
    PARAMETER     InvokeIDType
    PRIORITY      {1}
    CODE          local : 22 }

noSuchObjectClass ERROR ::= {
    PARAMETER     ObjectClass
    PRIORITY      {1}
    CODE          local : 0 }

noSuchObjectInstance ERROR ::= {
    PARAMETER     ObjectInstance
    PRIORITY      {1}
    CODE          local : 1 }

noSuchReferenceObject ERROR ::= {
    PARAMETER     ObjectInstance
    PRIORITY      {1}
    CODE          local : 12 }

operationCancelled ERROR ::= {
    PRIORITY      {1}
    CODE          local : 23 }

processingFailure ERROR ::= {
    PARAMETER     ProcessingFailure OPTIONAL TRUE
    PRIORITY      {1}
    CODE          local : 10 }

setListError ERROR ::= {
    PARAMETER     SetListError
    PRIORITY      {1}
    CODE          local : 8 }

syncNotSupported ERROR ::= {
    PARAMETER     CMISSync
    PRIORITY      {1}
    CODE          local : 3 }

-- CMISE operations

-- Action operation (M-ACTION)

m-Action OPERATION ::= {
    ARGUMENT            ActionArgument
    RETURN RESULT       FALSE
    ALWAYS RESPONDS     FALSE
    CODE                local : 6 }

m-Action-Confirmed OPERATION ::= {
    ARGUMENT      ActionArgument
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
    RESULT              ActionResult OPTIONAL TRUE      -- this result is conditional;
                                                        -- for conditions see 8.3.3.2.9 of ITU-T Rec. X.710
    ERRORS              {accessDenied | classInstanceConflict | complexityLimitation | invalidScope |
                         invalidArgumentValue | invalidFilter | noSuchAction | noSuchArgument |
                         noSuchObjectClass | noSuchObjectInstance | processingFailure | syncNotSupported}
    LINKED              {m-Linked-Reply}
    CODE                local : 7 }
```

-- Cancel get operation (M-CANCEL-GET)

```
m-CancelGet OPERATION ::= {
    ARGUMENT        InvokeIDType
    RETURN RESULT   TRUE
    ERRORS          {mistypedOperation | noSuchInvokeId | processingFailure}
    CODE            local : 10 }
```

-- Create operation (M-CREATE)

```
m-Create OPERATION ::= {
    ARGUMENT        CreateArgument
    RESULT          CreateResult OPTIONAL TRUE      -- this result is conditional;
                                                    -- for conditions see 8.3.4.1.3 of ITU-T Rec. X.710
    ERRORS          {accessDenied | classInstanceConflict | duplicateManagedObjectInstance |
                     invalidAttributeValue | invalidObjectInstance | missingAttributeValue | noSuchAttribute |
                     noSuchObjectClass | noSuchObjectInstance | noSuchReferenceObject | processingFailure}
    CODE            local : 8 }
```

-- Delete operation (M-DELETE)

```
m-Delete OPERATION ::= {
    ARGUMENT        DeleteArgument
    RESULT          DeleteResult OPTIONAL TRUE      -- this result is conditional;
                                                    -- for conditions see 8.3.5.2.8 of ITU-T Rec. X.710
    ERRORS          {accessDenied | classInstanceConflict | complexityLimitation | invalidFilter | invalidScope |
                     noSuchObjectClass | noSuchObjectInstance | processingFailure | syncNotSupported}
    LINKED          {m-Linked-Reply}
    CODE            local : 9 }
```

-- Event Reporting operations (M-EVENT-REPORT)

```
m-EventReport OPERATION ::= {
    ARGUMENT        EventReportArgument
    RETURN RESULT       FALSE
    ALWAYS RESPONDS     FALSE
    CODE                local : 0 }

m-EventReport-Confirmed OPERATION ::= {
    ARGUMENT        EventReportArgument
    RESULT              EventReportResult OPTIONAL TRUE
    ERRORS              {invalidArgumentValue | noSuchArgument | noSuchEventType |
                         noSuchObjectClass | noSuchObjectInstance | processingFailure}
    CODE                local : 1 }
```

-- Get operation (M-GET)

```
m-Get OPERATION ::= {
    ARGUMENT        GetArgument
    RESULT              GetResult OPTIONAL TRUE     -- this result is conditional;
                                                    -- for conditions see 8.3.1.2.8 of ITU-T Rec. X.710
    ERRORS              {accessDenied | classInstanceConflict | complexityLimitation | getListError |
                         invalidFilter |
                         invalidScope | noSuchObjectClass | noSuchObjectInstance | operationCancelled|
                         processingFailure | syncNotSupported}
    LINKED              {m-Linked-Reply}
    CODE                local : 3 }
```

-- Linked operation to M-GET, M-SET (Confirmed), M-ACTION (Confirmed), and M-DELETE

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
m-Linked-Reply OPERATION ::= {
    ARGUMENT            LinkedReplyArgument
    CODE                local : 2 }

-- Set operations (M-SET)

m-Set OPERATION ::= {
    ARGUMENT            SetArgument
    RETURN RESULT       FALSE
    ALWAYS RESPONDS     FALSE
    CODE                local : 4 }

m-Set-Confirmed OPERATION ::= {
    ARGUMENT            SetArgument
    RESULT              SetResult OPTIONAL TRUE   -- this result is conditional;
                                                  -- for conditions see 8.3.2.2.9 of ITU-T Rec. X.710
    ERRORS              {accessDenied | classInstanceConflict | complexityLimitation | invalidFilter |
                        invalidScope |
                        noSuchObjectClass | noSuchObjectInstance | processingFailure | setListError |
                        syncNotSupported}
    LINKED              {m-Linked-Reply}
    CODE                local : 5 }

-- INFORMATION OBJECT definitions
-- While it is possible to use the Information object class definitions defined below to specify
-- Action types, Attribute types, Event Report types, and their associated ASN.1 type definitions,
-- the alternative approach using GDMO templates, as defined in ITU-T Rec. X.722 | ISO/IEC 10165-4,
-- continues to be available for use with this Recommendation | International Standard.

CMIP-ACTION ::= CLASS {
    &id             ActionTypeId UNIQUE,
    &Value                              }
    WITH SYNTAX  {TYPE   &Value
                  ID     &id }

CMIP-ATTRIBUTE ::= CLASS {
    &id             AttributeId UNIQUE,
    &Value                              }
    WITH SYNTAX  {TYPE   &Value
                  ID     &id }

CMIP-AVA ::= CLASS {
    &id             OBJECT IDENTIFIER UNIQUE,
    &Value                                    }

CMIP-EVENT ::= CLASS {
    &id             EventTypeId UNIQUE,
    &Value                              }
    WITH SYNTAX  {TYPE   &Value
                  ID     &id }

CMIP-SPECIFICERROR ::= CLASS {
    &id             OBJECT IDENTIFIER UNIQUE,
    &Value                                    }
    WITH SYNTAX  {TYPE   &Value
                  ID     &id }

-- Supporting type definitions

AccessControl       ::= EXTERNAL

ActionArgument      ::= SEQUENCE {
    COMPONENTS OF   BaseManagedObjectId,
    accessControl   [5] AccessControl OPTIONAL,
    synchronization [6] IMPLICIT CMISSync DEFAULT bestEffort,
    scope           [7] Scope DEFAULT namedNumbers : baseObject,
```

--`,,`-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
    filter                  CMISFilter DEFAULT and : {},
    actionInfo              [12] IMPLICIT ActionInfo,
    ...
    }

ActionError    ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance   ObjectInstance OPTIONAL,
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    actionErrorInfo         [6] ActionErrorInfo,
    ...
    }

ActionErrorInfo     ::= SEQUENCE {
    errorStatus   ENUMERATED {accessDenied              (2),
                              noSuchAction              (9),
                              noSuchArgument            (14),
                              invalidArgumentValue      (15),
                              ... },
    errorInfo           CHOICE {
        actionType          CMIP-ACTION.&id ({ActionSet}),
        actionArgument      [0] NoSuchArgument,
        argumentValue       [1] InvalidArgumentValue
    },
    ... }

ActionInfo      ::= SEQUENCE {
    actionType          CMIP-ACTION.&id ({ActionSet}),
    actionInfoArg       [4] CMIP-ACTION.&Value ({ActionSet} {@.actionType}) OPTIONAL
    }

ActionReply     ::= SEQUENCE {
    actionType          CMIP-ACTION.&id ({ActionSet}),
    actionReplyInfo     [4] CMIP-ACTION.&Value ({ActionSet} {@.actionType})
    }

ActionResult    ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance   ObjectInstance OPTIONAL,
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    actionReply             [6] IMPLICIT ActionReply OPTIONAL,
    ...
    }

ActionSet CMIP-ACTION ::= {...}

ActionTypeId  ::= CHOICE {
    globalForm          [2] IMPLICIT OBJECT IDENTIFIER,
    localForm           [3] IMPLICIT INTEGER
    }
-- This Recommendation | International Standard does not allocate any values for localForm.
-- Where this alternative is used, the permissible values for the integers and their meanings shall be defined
-- as part of the application context in which they are used

Attribute ::= SEQUENCE {
    id              CMIP-ATTRIBUTE.&id          ({AttributeSet}),
    value           CMIP-ATTRIBUTE.&Value       ({AttributeSet} {@.id})
    }

AttributeError::= SEQUENCE {
    errorStatus             ENUMERATED {    accessDenied                (2),
                                            noSuchAttribute             (5),
                                            invalidAttributeValue       (6),
                                            invalidOperation            (24),
                                            invalidOperator             (25),
                                            ... },
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
    modifyOperator   [2] IMPLICIT ModifyOperator OPTIONAL,        -- present for invalidOperator
                                                                  -- and invalidOperation
    attributeId      CMIP-ATTRIBUTE.&id ({AttributeSet}),
    attributeValue   CMIP-ATTRIBUTE.&Value ({AttributeSet} {@.attributeId}) OPTIONAL
                                                                  -- value is absent for setToDefault
    }

AttributeId    ::= CHOICE {
    globalForm   [0] IMPLICIT OBJECT IDENTIFIER,
    localForm    [1] IMPLICIT INTEGER
    }
-- This Recommendation | International Standard does not allocate any values for localForm.
-- Where this alternative is used, the permissible values for the integers and their meanings shall be defined
-- as part of the application context in which they are used

AttributeIdError    ::= SEQUENCE {
    errorStatus   ENUMERATED {accessDenied      (2),
                              noSuchAttribute   (5),
                              ... },
    attributeId   AttributeId,
    ...
    }

AttributeSet CMIP-ATTRIBUTE ::= {...}

AttributeValueAssertion  ::= SEQUENCE {
    id       CMIP-AVA.&id      ({AvaSet}),
    value    CMIP-AVA.&Value   ({AvaSet} {@.id})
    }

AvaSet CMIP-AVA ::= {...}

BaseManagedObjectId    ::= SEQUENCE {
    baseManagedObjectClass       ObjectClass,
    baseManagedObjectInstance        ObjectInstance
    }

CMISFilter    ::= CHOICE {
    item      [8] FilterItem,
    and       [9] IMPLICIT SET OF CMISFilter,
    or        [10] IMPLICIT SET OF CMISFilter,
    not       [11] CMISFilter
    }

CMISSync      ::= ENUMERATED {        bestEffort    (0),
                                      atomic        (1) }

ComplexityLimitation    ::= SET {
    scope     [0] Scope OPTIONAL,
    filter[1] CMISFilter OPTIONAL,
    sync      [2] CMISSync OPTIONAL,
    ...
    }

CreateArgument    ::= SEQUENCE {
    managedObjectClass                  ObjectClass,
    managedOrSuperiorObjectInstance  CHOICE {
        managedObjectInstance                ObjectInstance,
        superiorObjectInstance               [8] ObjectInstance } OPTIONAL,

accessControl                        [5] AccessControl OPTIONAL,
    referenceObjectInstance          [6] ObjectInstance OPTIONAL,
    attributeList                    [7] IMPLICIT SET OF Attribute OPTIONAL,
    ...
    }
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
CreateResult ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance   ObjectInstance OPTIONAL,   -- shall be returned if omitted from CreateArgument
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    attributeList           [6] IMPLICIT SET OF Attribute OPTIONAL,
    ...
    }

DeleteArgument ::= SEQUENCE {
    COMPONENTS OF  BaseManagedObjectId,
    accessControl          [5] AccessControl OPTIONAL,
    synchronization        [6] IMPLICIT CMISSync DEFAULT bestEffort,
    scope                  [7] Scope DEFAULT namedNumbers : baseObject,
    filter              CMISFilter DEFAULT and : {},
    ...
    }

DeleteError ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance   ObjectInstance OPTIONAL,
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    deleteErrorInfo         [6] ENUMERATED { accessDenied      (2),
                                             ... },
    ... }

DeleteResult ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance   ObjectInstance OPTIONAL,
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    ...
    }

DistinguishedName ::= RDNSequence

EventReply ::= SEQUENCE {
    eventType          CMIP-EVENT.&id ({EventSet}),
    eventReplyInfo [8] CMIP-EVENT.&Value ({EventSet} {@.eventType}) OPTIONAL
    }

EventReportArgument ::= SEQUENCE {
    managedObjectClass      ObjectClass,
    managedObjectInstance   ObjectInstance,
    eventTime               [5] IMPLICIT GeneralizedTime OPTIONAL,
    eventType               CMIP-EVENT.&id ({EventSet}),
    eventInfo               [8] CMIP-EVENT.&Value ({EventSet} {@.eventType}) OPTIONAL,
    ...
    }

EventReportResult ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance   ObjectInstance OPTIONAL,
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    eventReply              EventReply OPTIONAL,
    ...
    }

EventSet CMIP-EVENT ::= {...}

EventTypeId ::= CHOICE {
    globalForm  [6] IMPLICIT OBJECT IDENTIFIER,
    localForm [7] IMPLICIT INTEGER
    }
-- This Recommendation | International Standard does not allocate any values for localForm.
-- Where this alternative is used, the permissible values for the integers and their meanings shall be defined
-- as part of the application context in which they are used
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
FilterItem      ::= CHOICE {
    equality                [0] IMPLICIT Attribute,
    substrings              [1] IMPLICIT SEQUENCE OF CHOICE {
        initialString           [0] IMPLICIT Attribute,
        anyString               [1] IMPLICIT Attribute,
        finalString             [2] IMPLICIT Attribute },
    greaterOrEqual          [2] IMPLICIT Attribute,   -- asserted value ≥ attribute value
    lessOrEqual             [3] IMPLICIT Attribute,   -- asserted value ≤ attribute value
    present                 [4] AttributeId,
    subsetOf                [5] IMPLICIT Attribute,   -- asserted value is a subset of attribute value
    supersetOf              [6] IMPLICIT Attribute,   -- asserted value is a superset of attribute value
    nonNullSetIntersection[7] IMPLICIT Attribute
    }

GetArgument     ::= SEQUENCE {
    COMPONENTS OF   BaseManagedObjectId,
    accessControl           [5] AccessControl OPTIONAL,
    synchronization         [6] IMPLICIT CMISSync DEFAULT bestEffort,
    scope                   [7] Scope DEFAULT namedNumbers : baseObject,
    filter              CMISFilter DEFAULT and : {},
    attributeIdList         [12] IMPLICIT SET OF AttributeId OPTIONAL,
    ...
    }

GetInfoStatus       ::= CHOICE {
    attributeIdError  [0] IMPLICIT AttributeIdError,
    attribute         [1] IMPLICIT Attribute
    }

GetListError        ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance   ObjectInstance OPTIONAL,
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    getInfoList             [6] IMPLICIT SET OF GetInfoStatus,
    ...
    }

GetResult           ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance   ObjectInstance OPTIONAL,
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    attributeList           [6] IMPLICIT SET OF Attribute OPTIONAL,
    ...
    }

InvalidArgumentValue        ::= CHOICE {
    actionValue       [0] IMPLICIT ActionInfo,
    eventValue        [1] IMPLICIT SEQUENCE {
        eventType         CMIP-EVENT.&id ({EventSet}),
        eventInfo             [8] CMIP-EVENT.&Value ({EventSet} {@.eventType}) OPTIONAL}
    }

InvokeIDType ::= InvokeId (ALL EXCEPT absent : NULL)

LinkedReplyArgument   ::= CHOICE {
    getResult               [0] IMPLICIT GetResult,
    getListError            [1] IMPLICIT GetListError,
    setResult               [2] IMPLICIT SetResult,
    setListError            [3] IMPLICIT SetListError,
    actionResult            [4] IMPLICIT ActionResult,
    processingFailure       [5] IMPLICIT ProcessingFailure,
    deleteResult            [6] IMPLICIT DeleteResult,
    actionError             [7] IMPLICIT ActionError,
    deleteError             [8] IMPLICIT DeleteError
    }
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
ModifyOperator      ::= INTEGER {       replace         (0),
                                        addValues       (1),
                                        removeValues    (2),
                                        setToDefault    (3) }

NoSuchAction        ::= SEQUENCE {
    managedObjectClass      ObjectClass,
    actionType              CMIP-ACTION.&id ({ActionSet}),
    ...
    }

NoSuchArgument      ::= CHOICE {
    actionId        [0] IMPLICIT SEQUENCE {
        managedObjectClass  ObjectClass OPTIONAL,
        actionType          CMIP-ACTION.&id ({ActionSet}) },
    eventId         [1] IMPLICIT SEQUENCE {
        managedObjectClass  ObjectClass OPTIONAL,
        eventType           CMIP-EVENT.&id ({EventSet}) }
    }

NoSuchEventType     ::= SEQUENCE {
    managedObjectClass  ObjectClass,
    eventType           CMIP-EVENT.&id ({EventSet}),
    ...
    }

ObjectClass         ::= CHOICE {
    globalForm      [0] IMPLICIT OBJECT IDENTIFIER,
    localForm       [1] IMPLICIT INTEGER
    }

-- This Recommendation | International Standard does not allocate any values for localForm.
-- Where this alternative is used, the permissible values for the integers and their meanings shall be defined
-- as part of the application context in which they are used

ObjectInstance      ::= CHOICE {
    distinguishedName           [2] IMPLICIT DistinguishedName,
    nonSpecificForm             [3] IMPLICIT OCTET STRING,
    localDistinguishedName      [4] IMPLICIT RDNSequence
    }

-- localDistinguishedName is that portion of the distinguished name that is necessary to unambiguously identify the
-- managed object within the context of communication between the open systems

ProcessingFailure   ::= SEQUENCE {
    managedObjectClass      ObjectClass,
    managedObjectInstance   ObjectInstance OPTIONAL,
    specificErrorInfo       [5] SpecificErrorInfo,
    ...
    }

RDNSequence ::= SEQUENCE OF RelativeDistinguishedName

RelativeDistinguishedName ::= SET OF AttributeValueAssertion

Scope       ::= CHOICE { namedNumbers   INTEGER {   baseObject     (0),
                                                    firstLevelOnly  (1),
                                                    wholeSubtree    (2) },
    individualLevels    [1] IMPLICIT INTEGER,   -- POSITIVE integer indicates the level to be selected
    baseToNthLevel      [2] IMPLICIT INTEGER } -- POSITIVE integer N indicates that the range of levels
                                                -- (0-N) is to be selected
-- with individualLevels and baseToNthLevel, a value of 0 has the same semantics as baseObject
-- with individualLevels, a value of 1 has the same semantics as firstLevelOnly
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
SetArgument ::= SEQUENCE {
    COMPONENTS OF       BaseManagedObjectId,
    accessControl       [5] AccessControl OPTIONAL,
    synchronization     [6] IMPLICIT CMISSync DEFAULT bestEffort,
    scope               [7] Scope DEFAULT namedNumbers : baseObject,
    filter              CMISFilter DEFAULT and : {},
    modificationList    [12] IMPLICIT SET OF SEQUENCE {
        modifyOperator      [2] IMPLICIT ModifyOperator DEFAULT replace,
        attributeId         CMIP-ATTRIBUTE.&id ({AttributeSet}),
        attributeValue      CMIP-ATTRIBUTE.&Value ({AttributeSet} {@.attributeId}) OPTIONAL },
                                                    -- value is absent for setToDefault
    ... }

SetInfoStatus       ::= CHOICE {
    attributeError  [0] IMPLICIT AttributeError,
    attribute       [1] IMPLICIT Attribute
    }

SetListError ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance   ObjectInstance OPTIONAL,
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    setInfoList             [6] IMPLICIT SET OF SetInfoStatus,
    ...
    }

SetResult ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance   ObjectInstance OPTIONAL,
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    attributeList           [6] IMPLICIT SET OF Attribute OPTIONAL,
    ...
    }

SpecificErrorInfo ::= SEQUENCE {
    errorId     CMIP-SPECIFICERROR.&id ({SpecificErrorSet}),
    errorInfo   CMIP-SPECIFICERROR.&Value ({SpecificErrorSet} {@.errorId})
    }

SpecificErrorSet CMIP-SPECIFICERROR ::= {...}

-- the following type specifies the constraints to be applied when using ROSE to support CMIP

ROSEapdus ::= ROS{{InvokeIDType}, {CMIP-Operations}, {CMIP-Confirmed-Operations}}

END         -- End of CMIP syntax definitions
```

18) Subclause 7.5

Replace Remote-Operations-APDUs.ROSEapdus *with* Remote-Operations-Generic-ROS-PDUs.ROS.

Replace CCITT Rec. X.229 and ISO/IEC 9072-2 *with* ITU-T Rec. X.880 | ISO/IEC 13712-1.

Replace CCITT Rec. X.209 and ISO/IEC 8825 *with* ITU-T Rec. X.690 | ISO/IEC 8825-1.

19) Subclause 8.1

Replace CCITT Rec. X.209 and ISO/IEC 8825 *with* ITU-T Rec. X.690 | ISO/IEC 8825-1.

Replace CCITT Rec. X.229 and ISO/IEC 9072-2 *with* ITU-T Rec. X.880 | ISO/IEC 13712-1.

Replace item f) with the following:

f) support the ability of both the association-initiating and the association-responding application entities to invoke operations;

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

20) Annex B

Replace with the following:

Annex B

Expanded ASN.1 syntax

(This annex does not form an integral part of this Recommendation | International Standard)

This annex describes how the OPERATION and ERROR information objects of ITU-T Rec. X.880 | ISO/IEC 13712-1 are expanded into ASN.1 data types and subtypes.

If any inconsistencies exist between these definitions and the definitions in clause 7, then the definitions in clause 7 take precedence.

```
-- Common Management Information Protocol (CMIP)

CMIP-1 {joint-iso-itu-t ms(9) cmip(1) modules(0) protocol(3)}

DEFINITIONS ::= BEGIN

-- This ASN.1 specification has been checked for conformance with the ASN.1 standard by the OSS ASN.1 Tools

IMPORTS

ERROR, OPERATION
    FROM Remote-Operations-Information-Objects
        {joint-iso-itu-t remote-operations(4) informationObjects(5) version1(0)}

ROS{}, InvokeId, noInvokeId
    FROM Remote-Operations-Generic-ROS-PDUs
        {joint-iso-itu-t remote-operations(4) generic-ROS-PDUs(6) version1(0)};

CMIP-Operations OPERATION ::= {
    m-Action                    |
    m-Action-Confirmed          |
    m-CancelGet                 |
    m-Create                    |
    m-Delete                    |
    m-EventReport               |
    m-EventReport-Confirmed     |
    m-Get                       |
    m-Linked-Reply              |
    m-Set                       |
    m-Set-Confirmed             }
CMIP-Confirmed-Operations OPERATION ::= {
    m-Action-Confirmed          |
    m-CancelGet                 |
    m-Create                    |
    m-Delete                    |
    m-EventReport-Confirmed     |
    m-Get                       |
    m-Set-Confirmed             }

-- INFORMATION OBJECT definitions
-- While it is possible to use the Information object class definitions defined below to specify
-- Action types, Attribute types, Event Report types, and their associated ASN.1 type definitions,
-- the alternative approach using GDMO templates, as defined in ITU-T Rec. X.722 | ISO/IEC 10165-4,
-- continues to be available for use with this Recommendation | International Standard.

CMIP-ACTION ::= CLASS {
    &id             ActionTypeId UNIQUE,
    &Value                                  }
    WITH SYNTAX  {TYPE   &Value
                  ID     &id }
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
CMIP-ATTRIBUTE ::= CLASS {
    &id             AttributeId UNIQUE,
    &Value                              }
    WITH SYNTAX  {TYPE   &Value
                  ID     &id }

CMIP-AVA ::= CLASS {
    &id             OBJECT IDENTIFIER UNIQUE,
    &Value                                    }

CMIP-EVENT ::= CLASS {
    &id             EventTypeId UNIQUE,
    &Value                              }
    WITH SYNTAX  {TYPE   &Value
                  ID     &id }

CMIP-SPECIFICERROR ::= CLASS {
    &id             OBJECT IDENTIFIER UNIQUE,
    &Value                                    }
    WITH SYNTAX  {TYPE   &Value
                  ID     &id }
-- the following type specifies the constraints to be applied when using ROSE to support CMIP

ROSEapdus ::= ROS{{InvokeIDType}, {CMIP-Operations}, {CMIP-Confirmed-Operations}}
-- CMISE operations
-- The following part of the ASN.1 specification provides a definition of ROIVapdu and RORSapdu subtypes used by CMIP.
-- The subtypes of the ROIVapdu define the allowed values of the operation-value and argument defined by that
-- operation-value for all CMIP notifications and operations. The subtypes of the RORSapdu define the allowed
-- values of the operation-value and result defined by that operation-value for all CMIP notifications and operations.

m-Action OPERATION.&operationCode ::= local : 6

ROIV-m-Action ::= ROSEapdus (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId      (InvokeIDtype),
        linkedId      ABSENT,
        opcode        (m-Action),
        argument      (ActionArgument) } )
    })

m-Action-Confirmed OPERATION.&operationCode ::= local : 7

ROIV-m-Action-Confirmed ::= ROSEapdus (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId      (InvokeIDtype),
        linkedId      ABSENT,
        opcode        (m-Action-Confirmed),
        argument      (ActionArgument) } )
    })

RORS-m-Action-Confirmed ::= ROSEapdus (WITH COMPONENTS {
    returnResult (WITH COMPONENTS {
        invokeId      (InvokeIDtype),
        result        (WITH COMPONENTS {
            opcode        (m-Action-Confirmed),
            result        (ActionResult) } ) OPTIONAL } )
            -- required only if there is a single reply to the ROIV-m-Action-Confirmed ROSEapdu
            -- and data is to be returned in the ROSEapdu
    } )

m-Cancel-Get OPERATION.&operationCode ::= local : 10

ROIV-m-Cancel-Get ::= ROSEapdus (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId      (InvokeIDtype),
        linkedId      ABSENT,
        opcode        (m-Cancel-Get),
        argument      (InvokeIDType) } )
    } )
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
RORS-m-Cancel-Get ::= ROSEapdus (WITH COMPONENTS {
    returnResult (WITH COMPONENTS {
        invokeId        (InvokeIDtype) } )
        -- There is no result sequence for RORS-m-Cancel-Get
    } )

m-Create OPERATION.&operationCode ::= local : 8

ROIV-m-Create ::= ROSEapdus (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId        (InvokeIDtype),
        linkedId        ABSENT,
        opcode          (m-Create),
        argument        (CreateArgument) } )
    } )

RORS-m-Create ::= ROSEapdus (WITH COMPONENTS {
    returnResult (WITH COMPONENTS {
        invokeId        (InvokeIDtype),
        result          (WITH COMPONENTS {
            opcode          (m-Create),
            result          (CreateResult) } ) } )
    } )

m-Delete OPERATION.&operationCode ::= local : 9

ROIV-m-Delete ::= ROSEapdus (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId        (InvokeIDtype),
        linkedId        ABSENT,
        opcode          (m-Delete),
        argument        (DeleteArgument) } )
    } )

RORS-m-Delete ::= ROSEapdus (WITH COMPONENTS {
    returnResult (WITH COMPONENTS {
        invokeId        (InvokeIDtype),
        result          (WITH COMPONENTS {
            opcode          (m-Delete),
            result          (DeleteResult) } ) OPTIONAL } )
            -- required only if there is a single reply to the ROIV-m-DeleteROSEapdu
            -- and data is to be returned in the ROSEapdu
    } )

m-EventReport OPERATION.&operationCode ::= local : 0

ROIV-m-EventReport ::= ROSEapdus (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId        (InvokeIDtype),
        linkedId        ABSENT,
        opcode          (m-EventReport),
        argument        (EventReportArgument) } )
    } )

m-EventReport-Confirmed OPERATION.&operationCode ::= local : 1

ROIV-m-EventReport-Confirmed ::= ROSEapdus (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId        (InvokeIDtype),
        linkedId        ABSENT,
        opcode          (m-EventReport-Confirmed),
        argument        (EventReportArgument) } )
    } )

RORS-m-EventReport-Confirmed ::= ROSEapdus (WITH COMPONENTS {
    returnResult (WITH COMPONENTS {
        invokeId        (InvokeIDtype),
        result          (WITH COMPONENTS {
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
            opcode          (m-EventReport-Confirmed),
            result          (EventReportResult) } ) OPTIONAL } )
            -- required only if data is to be returned in the ROSEapdu
    } )

m-Get OPERATION.&operationCode ::= local : 3

ROIV-m-Get ::= ROSEapdus (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId        (InvokeIDtype),
        linkedId        ABSENT,
        opcode          (m-Get),
        argument        (GetArgument) } )
    } )

RORS-m-Get ::= ROSEapdus (WITH COMPONENTS {
    returnResult (WITH COMPONENTS {
        invokeId        (InvokeIDtype),
        result          (WITH COMPONENTS {
            opcode          (m-Get),
            result          (GetResult) } ) OPTIONAL } )
            -- required only if there is a single reply to the ROIV-m-Get ROSEapdus
    } )

m-Linked-Reply OPERATION.&operationCode ::= local : 2

ROIV-m-Linked-Reply ::= ROSEapdus (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId        (InvokeIDtype),
        linkedId        PRESENT,
        opcode          (m-Linked-Reply),
        argument        (LinkedReplyArgument) } )
    } )
-- This part of the ASN.1 specification provides a definition of ROIV-m-Linked-Reply subtypes used by CMIP.
-- The subtypes of the ROIV-m-Linked-Reply ROSEapdus define the allowed values of the argument defined by
-- the opcode for the specific CMIP linked reply operations.

ROIV-m-Linked-Reply-Action ::= ROIV-m-Linked-Reply (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId        (InvokeIDtype),
        linkedId        PRESENT,
        opcode          (m-Linked-Reply),
        argument        (LinkedReplyArgument (WITH COMPONENTS {
            invoke (WITH COMPONENTS {
                getResult           ABSENT,
                getListError        ABSENT,
                setResult           ABSENT,
                setListError        ABSENT,
                actionResult        PRESENT,
                processingFailure   PRESENT,
                deleteResult        ABSENT,
                actionError         PRESENT,
                deleteError         ABSENT } )
        } ) )
    } ) } )

ROIV-m-Linked-Reply-Delete ::= ROIV-m-Linked-Reply (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId        (InvokeIDtype),
        linkedId        PRESENT,
        opcode          (m-Linked-Reply),
        argument        (LinkedReplyArgument (WITH COMPONENTS {
            invoke (WITH COMPONENTS {
                getResult           ABSENT,
                getListError        ABSENT,
                setResult           ABSENT,
                setListError        ABSENT,
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
                actionResult        ABSENT,
                processingFailure PRESENT,
                deleteResult        PRESENT,
                actionError         ABSENT,
                deleteError         PRESENT } )
        } ) )
    } ) } )

ROIV-m-Linked-Reply-Get ::= ROIV-m-Linked-Reply (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId        (InvokeIDtype),
        linkedId        PRESENT,
        opcode          (m-Linked-Reply),
        argument        (LinkedReplyArgument (WITH COMPONENTS {
            invoke (WITH COMPONENTS {
                getResult           PRESENT,
                getListError        PRESENT,
                setResult           ABSENT,
                setListError        ABSENT,
                actionResult        ABSENT,
                processingFailure PRESENT,
                deleteResult        ABSENT,
                actionError         ABSENT,
                deleteError         ABSENT } )
        } ) )
    } ) } )

ROIV-m-Linked-Reply-Set ::= ROIV-m-Linked-Reply (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId        (InvokeIDtype),
        linkedId        PRESENT,
        opcode          (m-Linked-Reply),
        argument        (LinkedReplyArgument (WITH COMPONENTS {
            invoke (WITH COMPONENTS {
                getResult           ABSENT,
                getListError        ABSENT,
                setResult           PRESENT,
                setListError        PRESENT,
                actionResult        ABSENT,
                processingFailure PRESENT,
                deleteResult        ABSENT,
                actionError         ABSENT,
                deleteError         ABSENT } )
        } ) )
    } ) } )

m-Set OPERATION.&operationcode ::= local : 4

ROIV-m-Set ::= ROSEapdus (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId        (InvokeIDtype),
        linkedId        ABSENT,
        opcode          (m-Set),
        argument        (SetArgument) } )
    } )

m-Set-Confirmed OPERATION.&operationCode ::= local : 5

ROIV-m-Set-Confirmed ::= ROSEapdus (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId        (InvokeIDtype),
        linkedId        ABSENT,
        opcode          (m-Set-Confirmed),
        argument        (SetArgument) } )
    } )
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
RORS-m-Set-Confirmed ::= ROSEapdus (WITH COMPONENTS {
    returnResult (WITH COMPONENTS {
        invokeId        (InvokeIDtype),
        result          (WITH COMPONENTS {
            opcode          (m-Set-Confirmed),
            result          (SetResult) } ) OPTIONAL } )
            -- required only if there is a single reply to the ROIV-m-Set-Confirmed ROSEapdu
            -- and data is to be returned in the ROSEapdu
    } )

-- The following part of the ASN.1 specification provides a definition of ROERapdu subtypes used by CMIP.
-- The subtypes of the ROERapdu define the allowed values of the error value and parameter defined by that
-- error-value for all CMIP notifications and operations.

accessDenied ERROR.&errorCode ::= local : 2

ROER-accessDenied ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId        PRESENT,
        errcode         (accessDenied) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Get, ROIV-m-Set-Confirmed,
-- ROIV-m-Action-Confirmed, ROIV-m-Create and ROIV-m-Delete ROIVapdus
    } )

classInstanceConflict ERROR.&errorCode ::= local : 19

ROER-classInstanceConflict ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId        PRESENT,
        errcode         (classInstanceConflict),
        parameter       (INCLUDES BaseManagedObjectId) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Get, ROIV-m-Set-Confirmed,
-- ROIV-m-Action-Confirmed, ROIV-m-Create and ROIV-m-Delete ROIVapdus
    } )

complexityLimitation ERROR.&errorCode ::= local : 20

ROER-complexityLimitation ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId        PRESENT,
        errcode         (complexityLimitation),
        parameter       (INCLUDES ComplexityLimitation) OPTIONAL } )
-- This ROERapdu may only be returned in response to the ROIV-m-Get, ROIV-m-Set-Confirmed,
-- ROIV-m-Action-Confirmed and ROIV-m-Delete ROIVapdus
    } )

duplicateManagedObjectInstance ERROR.&errorCode ::= local : 11

ROER-duplicateManagedObjectInstance ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId        PRESENT,
        errcode         (duplicateManagedObjectInstance),
        parameter       (INCLUDES ObjectInstance) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Create ROIVapdu
    } )

getListError ERROR.&errorCode ::= local : 7

ROER-getListError ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId        PRESENT,
        errcode         (getListError),
        parameter       (INCLUDES GetListError) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Get ROIVapdu
    } )

invalidArgumentValue ERROR.&errorCode ::= local : 15
```

--`,,`-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
ROER-invalidArgumentValue ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (invalidArgumentValue),
        parameter   (INCLUDES InvalidArgumentValue) } )
-- This ROERapdu may only be returned in response to the ROIV-m-EventReport-Confirmed
-- and ROIV-m-Action-Confirmed ROIVapdus
    } )

invalidAttributeValue ERROR.&errorCode ::= local : 6

ROER-invalidAttributeValue ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (invalidAttributeValue),
        parameter   (INCLUDES Attribute) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Create ROIVapdu
    } )

invalidFilter ERROR.&errorCode ::= local : 4

ROER-invalidFilter ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (invalidFilter),
        parameter   (INCLUDES CMISFilter) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Get, ROIV-m-Set-Confirmed,
-- ROIV-m-Action-Confirmed and ROIV-m-Delete ROIVapdus
    } )

invalidObjectInstance ERROR.&errorCode ::= local : 17

ROER-invalidObjectInstance ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (invalidObjectInstance),
        parameter   (INCLUDES ObjectInstance) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Create ROIVapdu
    } )

invalidScope ERROR.&errorCode ::= local : 16

ROER-invalidScope ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (invalidScope),
        parameter   (INCLUDES Scope) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Get, ROIV-m-Set-Confirmed,
-- ROIV-m-Action-Confirmed and ROIV-m-Delete ROIVapdus
    } )

missingAttributeValue ERROR.&errorCode ::= local : 18

ROER-missingAttributeValue ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (missingAttributeValue),
        parameter   (INCLUDES SET OF AttributeId) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Create ROIVapdu
    } )

mistypedOperation ERROR.&errorCode ::= local : 21

ROER-mistypedOperation ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (mistypedOperation) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Cancel-Get ROIVapdu
    } )
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
noSuchAction ERROR.&errorCode ::= local : 9

ROER-noSuchAction ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (noSuchAction),
        parameter   (INCLUDES NoSuchAction) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Action-Confirmed ROIVapdu
    } )

noSuchArgument ERROR.&errorCode ::= local : 14

ROER-noSuchArgument ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (noSuchArgument),
        parameter   (INCLUDES NoSuchArgument) } )
-- This ROERapdu may only be returned in response to the ROIV-m-EventReport-Confirmed and
-- ROIV-m-Action-Confirmed ROIVapdus
    } )

noSuchAttribute ERROR.&errorCode ::= local : 5

ROER-noSuchAttribute ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (noSuchAttribute),
        parameter   (INCLUDES AttributeId) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Create ROIVapdu
    } )

noSuchEventType ERROR.&errorCode ::= local : 13

ROER-noSuchEventType ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (noSuchEventType),
        parameter   (INCLUDES NoSuchEventType) } )
-- This ROERapdu may only be returned in response to the ROIV-m-EventReport-Confirmed ROIVapdu
    } )

noSuchInvokeId ERROR.&errorCode ::= local : 22

ROER-noSuchInvokeId ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (noSuchInvokeId),
        parameter   (INCLUDES InvokeIDType) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Cancel-Get ROIVapdu
    } )

noSuchObjectClass ERROR.&errorCode ::= local : 0

ROER-noSuchObjectClass ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (noSuchObjectClass ),
        parameter   (INCLUDES ObjectClass) } )
-- This ROERapdu may only be returned in response to the ROIV-m-EventReport-Confirmed, ROIV-m-Get,
-- ROIV-m-Set-Confirmed, ROIV-m-Action-Confirmed, ROIV-m-Create, and ROIV-m-Delete ROIVapdus
    } )

noSuchObjectInstance ERROR.&errorCode ::= local : 1

ROER-noSuchObjectInstance ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (noSuchObjectInstance),
        parameter   (INCLUDES ObjectInstance) } )
```

--`,,`-`-`,,`,,`,`,,`---

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

```
-- This ROERapdu may only be returned in response to the ROIV-m-EventReport-Confirmed, ROIV-m-Get,
-- ROIV-m-Set-Confirmed, ROIV-m-Action-Confirmed, ROIV-m-Create, and ROIV-m-Delete ROIVapdus
    } )

noSuchReferenceObject ERROR.&errorCode ::= local : 12

ROER-noSuchReferenceObject ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (noSuchReferenceObject),
        parameter   (INCLUDES ObjectInstance) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Create ROIVapdu
    } )

operationCancelled ERROR.&errorCode ::= local : 23

ROER-operationCancelled ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (operationCancelled) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Get ROIVapdu
    } )

processingFailure ERROR.&errorCode ::= local : 10

ROER-processingFailure ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (processingFailure),
        parameter   (INCLUDES ProcessingFailure) OPTIONAL } )
-- This ROERapdu may only be returned in response to the ROIV-m-EventReport-Confirmed, ROIV-m-Get,
-- ROIV-m-Set-Confirmed, ROIV-m-Action-Confirmed, ROIV-m-Create, and ROIV-m-Delete ROIVapdus
    } )

setListError ERROR.&errorCode ::= local : 8

ROER-setListError  ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (setListError),
        parameter   (INCLUDES SetListError) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Set-Confirmed ROIVapdu
    } )

syncNotSupported ERROR.&errorCode ::= local : 3

ROER-syncNotSupported ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId    PRESENT,
        errcode     (syncNotSupported),
        parameter   (INCLUDES CMISSync) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Get, ROIV-m-Set-Confirmed,
-- ROIV-m-Action-Confirmed and ROIV-m-Delete ROIVapdus
    } )

-- To complete the abstract syntax specification provided in this annex, the definitions of the supporting types in 7.4
-- are incorporated by reference

END -- of CMIP syntax definitions
```

21) Annexes C and D

Remove both annexes.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

STD.ISO 9596-1-ENGL 1998 ■ 4851903 0812541 466 ■

INTERNATIONAL STANDARD ISO/IEC 9596-1:1998
TECHNICAL CORRIGENDUM 1

Published 1999-12-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

Information technology — Open Systems Interconnection — Common management information protocol —

Part 1: Specification

TECHNICAL CORRIGENDUM 1

Technologies de l'information — Interconnexion de systèmes ouverts (OSI) — Protocole commun d'information de gestion —

Partie 1: Spécification

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to International Standard ISO/IEC 9596-1:1998 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology.*

ICS 35.100.70 **Ref. No. ISO/IEC 9596-1:1998/Cor.1:1999(E)**

© ISO/IEC 1999 – All rights reserved

Printed in Switzerland

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

INTERNATIONAL STANDARD

ITU-T RECOMMENDATION

INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION – COMMON MANAGEMENT INFORMATION PROTOCOL: SPECIFICATION

TECHNICAL CORRIGENDUM 1

1) Subclause 7.4

In ASN.1 production for FilterItem in CMIP-1:

Replace

lessOrEqual **[3] IMPLICIT Attribute,** -- *asserted value ≥ attribute value*

With:

lessOrEqual **[3] IMPLICIT Attribute,** -- *asserted value ≤ attribute value*

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

STD.ISO 9596-1-ENGL 1998 ■ 4851903 0761117 278 ■

INTERNATIONAL STANDARD

ISO/IEC 9596-1

Third edition
1998-10-15

Information technology — Open Systems Interconnection — Common management information protocol —

Part 1: Specification

Technologies de l'information — Interconnexion de systèmes ouverts (OSI) — Protocole commun d'information de gestion —

Partie 1: Spécification

This material is reproduced from ISO documents under International Organization for Standardization (ISO) Copyright License number IHS/ICC/1996. Not for resale. No part of these ISO documents may be reproduced in any form, electronic retrieval system or otherwise, except as allowed in the copyright law of the country of use, or with the prior written consent of ISO (Case postale 56, 1211 Geneva 20, Switzerland, Fax +41 22 734 10 79), IHS or the ISO Licensor's members.

Reference number
ISO/IEC 9596-1:1998(E)

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

Contents

		Page
1	Scope	1
2	Normative references	1
2.1	Identical Recommendations | International Standards	1
2.2	Paired Recommendations | International Standards equivalent in technical content	2
3	Definitions	2
3.1	Basic Reference Model definitions	2
3.2	Management Framework definitions	2
3.3	Remote Operations definitions	2
3.4	CMIS definitions	3
3.5	ACSE definitions	3
3.6	Presentation definitions	3
4	Symbols and abbreviations	3
5	Overview	4
5.1	Service provided	4
5.2	Underlying services	4
5.3	Management information definitions	5
5.4	Protocol version	5
6	Elements of procedure	5
6.1	Association establishment	5
6.2	Remote operations	5
6.3	Event reporting procedure	6
6.4	Get procedure	6
6.5	Set procedure	8
6.6	Action procedure	8
6.7	Create procedure	9
6.8	Delete procedure	10
6.9	Association orderly release	10
6.10	Association abrupt release	10
7	Abstract syntax	11
7.1	Conventions	11
7.2	Correspondence between CMISE primitives and CMIP operations	11
7.3	ACSE user data	12
7.4	CMIP data units	13
7.5	Definition of abstract syntax for CMIP	20
8	Conformance	21
8.1	Static requirements	21
8.2	Dynamic requirements	22

© ISO/IEC 1998

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale

Annex A – Association rules for CMISE 23
A.1 ACSE, session and presentation requirements 23
A.2 Association initialization rules 23
A.3 Association release rules 24
A.4 Association abort rules 24
Annex B – Expanded ASN.1 syntax 26
Annex C – Examples of CMISE ROSE APDUs 34
Annex D – Directory abstract syntax 35

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 9596-1 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 33, *Distributed application services*, in collaboration with ITU-T. The identical text is published as ITU-T Recommendation X.711.

This third edition cancels and replaces the second edition (ISO/IEC 9596-1:1991), which has been technically revised. It also incorporates Technical Corrigendum 1:1992, Technical Corrigendum 2:1992, Technical Corrigendum 3:1992, Technical Corrigendum 4:1993 and Technical Corrigendum 5:1994.

ISO/IEC 9596 consists of the following parts, under the general title *Information technology — Open Systems Interconnection — Common management information protocol*:

— *Part 1: Specification*

— *Part 2: Protocol Implementation Conformance Statement (PICS) proforma*

Annexes A to D of this part of ISO/IEC 9596 are for information only.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

ISO/IEC 9596-1 : 1998 (E)

INTERNATIONAL STANDARD

ITU-T RECOMMENDATION

INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION – COMMON MANAGEMENT INFORMATION PROTOCOL: SPECIFICATION

1 Scope

This Recommendation | International Standard specifies a protocol which is used by application layer entities to exchange management information.

This Recommendation | International Standard specifies:

- procedures for the transmission of management information between application entities;
- the abstract syntax of the Common Management Information Protocol (CMIP) and the associated encoding rules to be applied;
- procedures for the correct interpretation of protocol control information;
- the conformance requirements to be met by implementation of this Recommendation | International Standard.

This Recommendation | International Standard does not specify:

- the structure or meaning of the management information that is transmitted by means of CMIP;
- the manner in which management is accomplished as a result of CMIP exchanges;
- the interactions which result in the use of CMIP.

2 Normative references

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

2.1 Identical Recommendations | International Standards

- ITU-T Recommendation X.200 (1994) | ISO/IEC 7498-1:1994, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model.*
- ITU-T Recommendation X.215 (1995) | ISO/IEC 8326:1996, *Information technology – Open Systems Interconnection – Session service definition.*
- ITU-T Recommendation X.216 (1994) | ISO/IEC 8822:1994, *Information technology – Open Systems Interconnection – Presentation service definition.*
- ITU-T Recommendation X.217 (1995) | ISO/IEC 8649:1996, *Information technology – Open Systems Interconnection – Service definition for the Association Control Service Element.*
- ITU-T Recommendation X.226 (1994) | ISO/IEC 8823-1:1994, *Information technology – Open Systems Interconnection – Connection-oriented presentation protocol: Protocol specification.*
- ITU-T Recommendation X.227 (1995) | ISO/IEC 8650-1:1996, *Information technology – Open Systems Interconnection – Connection-oriented protocol for the Association Control Service Element: Protocol specification.*

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

- ITU-T Recommendation X.710 (1997) | ISO/IEC 9595:1998, *Information technology – Open Systems Interconnection – Common management information service.*
- CCITT Recommendation X.712 (1992) | ISO/IEC 9596-2:1993, *Information technology – Open Systems Interconnection – Common management information protocol: Protocol Implementation Conformance Statement (PICS) proforma.*

2.2 Paired Recommendations | International Standards equivalent in technical content

- CCITT Recommendation X.208 (1988), *Specification of Abstract Syntax Notation One (ASN.1).*

  ISO/IEC 8824:1990, *Information technology – Open Systems Interconnection – Specification of Abstract Syntax Notation One (ASN.1).*
- CCITT Recommendation X.209 (1988), *Specification of basic encoding rules for Abstract Syntax Notation One (ASN.1).*

  ISO/IEC 8825:1990, *Information technology – Open Systems Interconnection – Specification of Basic Encoding Rules for Abstract Syntax Notation One (ASN.1).*
- CCITT Recommendation X.219 (1988), *Remote operations: Model, notation and service definition.*

  ISO/IEC 9072-1:1989, *Information processing systems – Text communication – Remote Operations – Part 1: Model, notation and service definition.*
- CCITT Recommendation X.229 (1988), *Remote operations: Protocol specification.*

  ISO/IEC 9072-2:1989, *Information processing systems – Text communication – Remote Operations – Part 2: Protocol specification.*
- CCITT Recommendation X.700 (1992), *Management framework for Open Systems Interconnection (OSI) for CCITT applications.*

  ISO/IEC 7498-4:1989, *Information processing systems – Open Systems Interconnection – Basic Reference Model – Part 4: Management framework.*

3 Definitions

For the purposes of this Recommendation | International Standard, the following definitions apply.

3.1 Basic Reference Model definitions

This Recommendation | International Standard makes use of the following terms defined in ITU-T Rec. X.200 | ISO/IEC 7498-1:

a) application-service-element;

b) application-process;

c) real open system;

d) systems-management.

3.2 Management Framework definitions

This Recommendation | International Standard makes use of the following terms defined in CCITT Rec. X.700 | ISO/IEC 7498-4:

a) managed object;

b) management information;

c) management information base;

d) systems management application-entity.

3.3 Remote Operations definitions

This Recommendation | International Standard makes use of the following terms defined in CCITT Rec. X.219 | ISO/IEC 9072-1:

a) association-initiator;

b) association-responder;

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

c) linked-operations;

d) Remote Operations;

e) Remote Operation Service Element;

f) invoker;

g) performer;

h) Association Class;

i) Operation Class.

3.4 CMIS definitions

This Recommendation | International Standard makes use of the following terms defined in ITU-T Rec. X.710 | ISO/IEC 9595:

a) attribute;

b) common management information service element;

c) common management information services;

d) CMISE-service-provider;

e) CMISE-service-user;

f) invoking CMISE-service-user;

g) performing CMISE-service-user.

3.5 ACSE definitions

This Recommendation | International Standard makes use of the following terms defined in ITU-T Rec. X.217 | ISO/IEC 8649:

a) application context;

b) application-association;

c) association.

3.6 Presentation definitions

This Recommendation | International Standard makes use of the following terms defined in ITU-T Rec. X.216 | ISO/IEC 8822:

a) abstract syntax;

b) transfer syntax.

4 Symbols and abbreviations

For the purposes of this Recommendation | International Standard, the following abbreviations apply:

ACSE	Association Control Service Element
APDU	Application Protocol Data Unit
ASE	Application Service Element
ASN.1	Abstract Syntax Notation One
CMIP	Common Management Information Protocol
CMIPM	Common Management Information Protocol Machine
CMIS	Common Management Information Services
CMISE	Common Management Information Service Element
DCS	Defined Context Set
PCI	Protocol Control Information
PDU	Protocol Data Unit

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

PICS	Protocol Implementation Conformance Statement
RO	Remote Operations
ROSE	Remote Operations Service Element
SMAE	Systems Management Application-Entity

5 Overview

The Common Management Information Protocol (CMIP) specifies protocol elements that may be used to provide the operation and notification services described in ITU-T Rec. X.710 | ISO/IEC 9595, which defines the Common Management Information Services (CMIS).

5.1 Service provided

The protocol specified in this Recommendation | International Standard supports the services defined in ITU-T Rec. X.710 | ISO/IEC 9595. These services are summarized in Table 1.

Table 1 – Common management information services

Service	Type
M-CANCEL-GET	confirmed
M-EVENT-REPORT	confirmed/non-confirmed
M-GET	confirmed
M-SET	confirmed/non-confirmed
M-ACTION	confirmed/non-confirmed
M-CREATE	confirmed
M-DELETE	confirmed

5.2 Underlying services

This Recommendation | International Standard uses the RO-INVOKE, RO-RESULT, RO-ERROR and RO-REJECT-U services of the Remote Operations Service Element (ROSE) defined in CCITT Rec. X.219 | ISO/IEC 9072-1. ROSE assumes the use of the presentation service defined in ITU-T Rec. X.216 | ISO/IEC 8822. The confirmed operations of CMIP are operation class 2 (asynchronous) or operation class 1 (synchronous) as required by the application. The choice of operation class is a local matter. The unconfirmed operations of CMIP are operation class 5 (asynchronous, outcome not reported). CMIP uses association class 3.

If the extended service functional unit is successfully negotiated, ROSE APDUs may be mapped on to presentation services other than the P-DATA service.

NOTE – For example, it may be necessary to modify the presentation Defined Context Set (DCS) when the CMIP operation is sent to the peer CMISE-service-user. In this case, the ROSE APDU which carries the CMIP operation will be mapped onto the P-ALTER-CONTEXT service which is also used to perform the changes to the DCS.

Details of which other presentation services are required and how they are used, are described in the description of the application context in use on the association.

5.2.1 Service assumed from the ACSE

This Recommendation | International Standard assumes the use of the A-ASSOCIATE, A-RELEASE, A-ABORT, and A-P-ABORT services of the Association Control Service Element.

5.2.2 Service assumed from the presentation layer

CCITT Rec. X.229 | ISO/IEC 9072-2 assumes the use of the P-DATA service of the presentation layer for the transfer of the RO-INVOKE, RO-RESULT, RO-ERROR and RO-REJECT APDUs.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

5.3 Management information definitions

This Recommendation | International Standard defines the abstract syntax of the Common Management Information Protocol. The definitions of management information to be carried by the protocol are not specified in this Recommendation | International Standard.

5.4 Protocol version

This Recommendation International Standard defines version 2 of CMIP. Version 2 replaces version 1. This Recommendation | International Standard does not define any interworking between version 2 and version 1.

6 Elements of procedure

This clause provides definition for the procedural elements of the CMIP. The procedures define the transfer of CMIP PDUs whose structure, coding and relationship with the CMIS service primitives is specified in clause 7.

The Common Management Information Protocol Machine (CMIPM) accepts CMIS request and response service primitives, and issues CMIP PDUs initiating specific elements of procedure as specified in this clause.

A CMIPM shall accept any well-formed CMIP PDU, and pass it to the performing CMISE-service-user for processing, by means of CMIS indication and confirmation service primitives. If the received PDU is not well formed or does not contain a supported notification or operation, a PDU is returned indicating that the received PDU has been rejected.

The procedures indicate only how to interpret the various fields in the CMIP PDU, not what an invoking CMISE-service-user should do with the information it requests nor how a performing CMISE-service-user should process the invocation.

6.1 Association establishment

The establishment of an association involves two CMISE-service-users, one that is the association-initiator and one that is the association-responder.

A CMISE-service-user may initiate an association establishment by using the A-ASSOCIATE service of ITU-T Rec. X.217 | ISO/IEC 8649.

The application context specifies, among other things, the rules required for the coordination of initialization information corresponding to different ASEs. The association rules for CMISE are specified in Annex A.

6.2 Remote operations

6.2.1 RO elements of procedure

The CMIP elements of procedure rely on the following underlying remote operations elements of procedure:

a) invocation;

b) return-result;

c) return-error;

d) user-reject;

e) provider-reject.

These elements of procedure are described fully in CCITT Rec. X.229 | ISO/IEC 9072-2.

Table 2 specifies the correspondence between CMIS and ROSE parameters.

Table 2 – Correspondence between CMIS and ROSE parameters

CMIS parameter	ROSE parameter
Invoke identifier	InvokeID
Linked identifier	Linked-ID

The correspondence between other CMIS and ROSE parameters is specified in clause 7.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

6.2.2 RO-Reject problem parameters

The RO-Reject problem parameters are mapped or processed as follows.

6.2.2.1 RO-Reject-User.Invoke-problem mapping to CMIS error codes is specified in Table 3.

Table 3 – Mapping RO-Reject-User.Invoke-problem to CMISE error codes

RO-REJECT parameter	CMISE error code
duplicate-invocation	duplicate invocation
mistyped-argument	mistyped argument
resource-limitation	resource limitation
unrecognized-operation	unrecognized operation

Other Invoke-problem parameters are a local matter.

6.2.2.2 Other RO-Reject parameters will be handled as a local matter.

6.3 Event reporting procedure

6.3.1 Invocation

The event reporting procedures are initiated by the M-EVENT-REPORT request primitive.

On receipt of the M-EVENT-REPORT request primitive, the CMIPM shall:

a) in the confirmed mode, construct an APDU requesting the m-EventReport-Confirmed operation, otherwise, construct an APDU requesting the m-EventReport operation;

b) send the APDU using the RO-INVOKE procedure.

6.3.2 Receipt

On receipt of an APDU requesting either the m-EventReport or m-EventReport-Confirmed operation, the CMIPM shall, if the APDU is well formed, issue an M-EVENT-REPORT indication primitive to the CMISE-service-user with the mode parameter indicating whether or not confirmation is requested, otherwise, construct an APDU containing notification of the error and send it using the RO-REJECT-U procedure.

6.3.3 Response

In the confirmed mode, the CMIPM shall accept an M-EVENT-REPORT response primitive and shall:

a) construct an APDU confirming the M-EVENT-REPORT notification;

b) if the parameters in the M-EVENT-REPORT response primitive indicate that the notification was accepted, send the APDU using the RO-RESULT procedure, otherwise, send the APDU using the RO-ERROR procedure.

6.3.4 Receipt of response

On receipt of an APDU responding to an M-EVENT-REPORT notification, the CMIPM shall, if the APDU is well formed, issue an M-EVENT-REPORT confirmation primitive to the CMISE-service-user, thus completing the notification procedure, otherwise, construct an APDU containing notification of the error and send it using the RO-REJECT-U procedure.

6.4 Get procedure

6.4.1 Invocation

The Get procedures are initiated by the M-GET request primitive.

On receipt of the M-GET request primitive, the CMIPM shall:

a) construct an APDU requesting the m-Get operation;

b) send the APDU using the RO-INVOKE procedure.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

6.4.2 Receipt

On receipt of an APDU requesting the m-Get operation, the CMIPM shall, if the APDU is well formed, issue an M-GET indication primitive to the CMISE-service-user, otherwise, construct an APDU containing notification of the error and send it using the RO-REJECT-U procedure.

6.4.3 Response

The CMIPM shall:

a) accept zero or more M-GET response primitives containing a linked-ID followed by a single M-GET response primitive without a linked-ID;

b) for each M-GET response primitive containing a linked-ID:

- construct an APDU requesting the m-Linked-Reply operation with LinkedReplyArgument set appropriately as either getListError, getResult or processingFailure;
- send each APDU using the RO-INVOKE procedure;

c) for the M-GET response primitive not containing a linked-ID:

- construct an APDU confirming the m-Get operation;
- if the parameters in the M-GET response primitive indicate that the operation was performed correctly, send the APDU using the RO-RESULT procedure. If the parameters in the M-GET response primitive indicate that the operation was performed with partial success or was not performed because of an error, the CMIPM shall send the APDU using the RO-ERROR procedure.

6.4.4 Receipt of response

On receipt of an APDU responding to an m-Get operation, the CMIPM shall:

a) if the APDU included a linked-ID and is well formed, issue an M-GET confirmation primitive to the CMISE-service-user;

b) if the APDU is the last response (i.e. not containing a linked-ID) and is well formed, issue an M-GET confirmation primitive to the CMISE-service-user, thus completing the M-GET procedure;

c) if the APDU is not well formed, construct an APDU containing notification of the error and send it using the RO-REJECT-U procedure.

6.4.5 CancelGet procedure

6.4.5.1 Invocation

The CancelGet procedures are initiated by the M-CANCEL-GET request primitive.

On receipt of the M-CANCEL-GET request primitive, the CMIPM shall:

a) construct an APDU requesting the m-CancelGet operation;

b) send the APDU using the RO-INVOKE procedure.

6.4.5.2 Receipt

On receipt of an APDU requesting the m-CancelGet operation, the CMIPM shall, if the APDU is well formed, issue an M-CANCEL-GET indication primitive to the CMISE-service-user, otherwise, construct an APDU containing notification of the error and send it using the RO-REJECT-U procedure.

6.4.5.3 Response

The CMIPM shall:

a) construct an APDU confirming the m-CancelGet operation;

b) if the parameters in the M-CANCEL-GET response primitive indicate that the operation was performed correctly, send the APDU using the RO-RESULT procedure otherwise, send the APDU using the RO-ERROR procedure. If the m-CancelGet operation is successful, the performing CMISE-service-user shall cease from sending linked replies to the m-Get operation and shall issue an M-GET response primitive which shall contain the "operation cancelled" error.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

6.4.5.4 Receipt of response

On receipt of an APDU responding to an m-CancelGet operation, the CMIPM shall, if the APDU is well formed, issue an M-CANCEL-GET confirmation primitive to the CMISE-service-user, otherwise, construct an APDU containing notification of the error and send it using the RO-REJECT-U procedure.

6.5 Set procedure

6.5.1 Invocation

The Set procedures are initiated by the M-SET request primitive.

On receipt of the M-SET request primitive, the CMIPM shall:

a) in the confirmed mode, construct an APDU requesting the m-Set-Confirmed operation, otherwise, construct an APDU requesting the m-Set operation;

b) send the APDU using the RO-INVOKE procedure.

6.5.2 Receipt

On receipt of an APDU requesting the m-Set or m-Set-Confirmed operation, the CMIPM shall, if the APDU is well formed, issue an M-SET indication primitive to the CMISE-service-user, with the mode parameter indicating whether or not confirmation is requested, otherwise, construct an APDU containing notification of the error and send it using the RO-REJECT-U procedure.

6.5.3 Response

In the confirmed mode, the CMIPM shall:

a) accept zero or more M-SET response primitives containing a linked-ID followed by a single M-SET response primitive without a linked-ID;

b) for each M-SET response primitive containing a linked-ID:

- construct an APDU requesting the m-Linked-Reply operation with LinkedReplyArgument set appropriately as either setListError, setResult or processingFailure;
- send each APDU using the RO-INVOKE procedure;

c) for the M-SET response primitive not containing a linked-ID:

- construct an APDU confirming the m-Set operation;
- if the parameters in the M-SET response primitive indicate that the operation was performed correctly, send the APDU using the RO-RESULT procedure. If the parameters in the M-SET response primitive indicate that the operation was performed with partial success or was not performed because of an error, the CMIPM shall send the APDU using the RO-ERROR procedure.

6.5.4 Receipt of response

On receipt of an APDU responding to an m-Set-Confirmed operation, the CMIPM shall:

a) if the APDU included a linked-ID and is well formed, issue an M-SET confirmation primitive to the CMISE-service-user;

b) if the APDU is the last response (i.e. not containing a linked-ID) and is well formed, issue an M-SET confirmation primitive to the CMISE-service-user, thus completing the M-SET procedure;

c) if the APDU is not well formed, construct an APDU containing notification of the error and send it using the RO-REJECT-U procedure.

6.6 Action procedure

6.6.1 Invocation

The Action procedures are initiated by the M-ACTION request primitive.

On receipt of the M-ACTION request primitive, the CMIPM shall:

a) in the confirmed mode, construct an APDU requesting the m-Action-Confirmed operation otherwise, construct an APDU requesting the m-Action operation;

b) send the APDU using the RO-INVOKE procedure.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

6.6.2 Receipt

On receipt of an APDU requesting the m-Action or m-Action-Confirmed operation, the CMIPM shall, if the APDU is well formed, issue an M-ACTION indication primitive to the CMISE-service-user, with the mode parameter indicating whether or not confirmation is requested, otherwise, construct an APDU containing notification of the error and send it using the RO-REJECT-U procedure.

6.6.3 Response

In the confirmed mode, the CMIPM shall:

a) accept zero or more M-ACTION response primitives containing a linked-ID followed by a single M-ACTION response primitive without a linked-ID;

b) for each M-ACTION response primitive containing a linked-ID:

- construct an APDU requesting the m-Linked-Reply operation with LinkedReplyArgument set appropriately as either actionError, actionResult or processingFailure;
- send each APDU using the RO-INVOKE procedure;

c) for the M-ACTION response primitive not containing a linked-ID:

- construct an APDU confirming the m-Action operation;
- if the parameters in the M-ACTION response primitive indicate that the operation was performed correctly, send the APDU using the RO-RESULT procedure, otherwise, send the APDU using the RO-ERROR procedure.

6.6.4 Receipt of response

On receipt of an APDU responding to an m-Action-Confirmed operation, the CMIPM shall:

a) if the APDU included a linked-ID and is well formed, issue an M-ACTION confirmation primitive to the CMISE-service-user;

b) if the APDU is the last response (i.e. not containing a linked-ID) and is well formed, issue an M-ACTION confirmation primitive to the CMISE-service-user, thus completing the M-ACTION procedure;

c) if the APDU is not well formed, construct an APDU containing notification of the error and send it using the RO-REJECT-U procedure.

6.7 Create procedure

6.7.1 Invocation

The Create procedures are initiated by the M-CREATE request primitive.

On receipt of the M-CREATE request primitive, the CMIPM shall:

a) construct an APDU requesting the m-Create operation;

b) send the APDU using the RO-INVOKE procedure.

6.7.2 Receipt

On receipt of an APDU requesting the m-Create operation, the CMIPM shall, if the APDU is well formed, issue an M-CREATE indication primitive to the CMISE-service-user, otherwise, construct an APDU containing notification of the error and send it using the RO-REJECT-U procedure.

6.7.3 Response

The CMIPM shall accept an M-CREATE response primitive and shall:

a) construct an APDU confirming the m-Create operation;

b) if the parameters in the M-CREATE response primitive indicate that the operation was performed correctly, send the APDU using the RO-RESULT procedure, otherwise, send the APDU using the RO-ERROR procedure.

6.7.4 Receipt of response

On receipt of an APDU responding to an m-Create operation, the CMIPM shall, if the APDU is well formed, issue an M-CREATE confirmation primitive to the CMISE-service-user, thus completing the M-CREATE procedure, otherwise, construct an APDU containing notification of the error and send it using the RO-REJECT-U procedure.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

6.8 Delete procedure

6.8.1 Invocation

The Delete procedures are initiated by the M-DELETE request primitive.

On receipt of the M-DELETE request primitive, the CMIPM shall:

a) construct an APDU requesting the m-Delete operation;

b) send the APDU using the RO-INVOKE procedure.

6.8.2 Receipt

On receipt of an APDU requesting the m-Delete operation, the CMIPM shall, if the APDU is well formed, issue an M-DELETE indication primitive to the CMISE-service-user, otherwise, construct an APDU containing notification of the error and send it using the RO-REJECT-U procedure.

6.8.3 Response

The CMIPM shall:

a) accept zero or more M-DELETE response primitives containing a linked-ID followed by a single M-DELETE response primitive without a linked-ID;

b) for each M-DELETE response primitive containing a linked-ID:

- construct an APDU requesting the m-Linked-Reply operation with LinkedReplyArgument set appropriately as either deleteError, deleteResult or processingFailure;
- send each APDU using the RO-INVOKE procedure;

c) for the M-DELETE response primitive not containing a linked-ID:

- construct an APDU confirming the m-Delete operation;
- if the parameters in the M-DELETE response primitive indicate that the operation was performed correctly, send the APDU using the RO-RESULT procedure, otherwise, send the APDU using the RO-ERROR procedure.

6.8.4 Receipt of response

On receipt of an APDU responding to an m-Delete operation, the CMIPM shall:

a) if the APDU included a linked-ID and is well formed, issue an M-DELETE confirmation primitive to the CMISE-service-user;

b) if the APDU is the last response (i.e. not containing a linked-ID) and is well formed, issue an M-DELETE confirmation primitive to the CMIS-service-user, thus completing the M-DELETE procedure;

c) if the APDU is not well formed, construct an APDU containing notification of the error and send it using the RO-REJECT-U procedure.

6.9 Association orderly release

Either CMISE-service-user may initiate an orderly release of the association by using the A-RELEASE service of ITU-T Rec. X.217 | ISO/IEC 8649.

NOTE – This specification is different from the ROSE use of the BIND operation in which only the association-initiator may use the A-RELEASE procedure.

6.10 Association abrupt release

Either CMISE-service-user may initiate an abrupt release of the association using the A-ABORT service of ITU-T Rec. X.217 | ISO/IEC 8649.

The CMISE-service-user may receive an indication of the abrupt release of the association via the A-ABORT or A-P-ABORT services of ITU-T Rec. X.217 | ISO/IEC 8649.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

7 Abstract syntax[1)]

This clause specifies the abstract syntax for the CMIP PDUs.

7.1 Conventions

The abstract syntax is defined using the notation specified in CCITT Rec. X.208 | ISO/IEC 8824. The ASN.1 MACRO productions used or referenced by this Recommendation | International Standard do not exercise the ambiguous aspects of the grammar.

For each of the CMISE service parameters which is to be transferred by a CMIP PDU, there is a PDU field (an ASN.1 NamedType) with the same name as the corresponding service parameter (see ITU-T Rec. X.710 | ISO/IEC 9595), except for the differences required by the use of ASN.1, which are that blanks between words are removed and the first letter of the following word is capitalized, e.g. "managed object class" becomes "managedObjectClass". To make some of the names shorter, some words are abbreviated as follows:

ack acknowledgement
arg argument
id identifier
info information
sync synchronization

7.2 Correspondence between CMISE primitives and CMIP operations

Table 4 – Correspondence between CMISE primitives and CMIP operations

CMIS primitive	Mode	Linked-ID	CMIP operation
M-CANCEL-GET req/ind	Confirmed	Not applicable	m-Cancel-Get-Confirmed
M-CANCEL-GET rsp/conf	Not applicable	Not applicable	m-Cancel-Get-Confirmed
M-EVENT-REPORT req/ind	Non-confirmed	Not applicable	m-EventReport
M-EVENT-REPORT req/ind	Confirmed	Not applicable	m-EventReport-Confirmed
M-EVENT-REPORT rsp/conf	Not applicable	Not applicable	m-EventReport-Confirmed
M-GET req/ind	Confirmed	Not applicable	m-Get
M-GET rsp/conf	Not applicable	Absent	m-Get
M-GET rsp/conf	Not applicable	Present	m-Linked-Reply
M-SET req/ind	Non-confirmed	Not applicable	m-Set
M-SET req/ind	Confirmed	Not applicable	m-Set-Confirmed
M-SET rsp/conf	Not applicable	Absent	m-Set-Confirmed
M-SET rsp/conf	Not applicable	Present	m-Linked-Reply
M-ACTION req/ind	Non-confirmed	Not applicable	m-Action
M-ACTION req/ind	Confirmed	Not applicable	m-Action-confirmed
M-ACTION rsp/conf	Not applicable	Absent	m-Action-confirmed
M-ACTION rsp/conf	Not applicable	Present	m-Linked-Reply
M-CREATE req/ind	Confirmed	Not applicable	m-Create
M-CREATE rsp/conf	Not applicable	Not applicable	m-Create
M-DELETE req/ind	Confirmed	Not applicable	m-Delete
M-DELETE rsp/conf	Not applicable	Absent	m-Delete
M-DELETE rsp/conf	Not applicable	Present	m-Linked-Reply
NOTE – The mapping from the OPERATION and ERROR macros to ROSE is defined in CCITT Rec. X.219	ISO/IEC 9072-1.		

1) Users of this Recommendation | International Standard may freely reproduce the abstract syntax definitions in the clause so that they may be used for their intended purpose.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

7.3 ACSE user data

The ACSE protocol (see ITU-T Rec. X.227 | ISO/IEC 8650-1) is described using ASN.1. The "user information" is defined using the EXTERNAL data type.

7.3.1 A-ASSOCIATE user data

The encoding of the CMIP user information to be passed to A-ASSOCIATE in the "user information" parameter is defined as follows:

CMIP-A-ASSOCIATE-Information {joint-iso-itu-t ms(9) cmip(1) modules(0) aAssociateUserInfo(1)}

```
DEFINITIONS             ::= BEGIN
FunctionalUnits   ::= BIT STRING {
    multipleObjectSelection     (0),
    filter                      (1),
    multipleReply               (2),
    extendedService             (3),
    cancelGet                   (4)
    }

--  Functional unit i is supported if and only if bit i is one

--  Information carried in user-information parameter of A-ASSOCIATE

CMIPUserInfo      ::= SEQUENCE {
    protocolVersion     [0] IMPLICIT ProtocolVersion DEFAULT { version1 },
    functionalUnits     [1] IMPLICIT FunctionalUnits DEFAULT {},
    accessControl       [2] EXTERNAL OPTIONAL,
    userInfo            [3] EXTERNAL OPTIONAL
    }

ProtocolVersion   ::= BIT STRING {
    version1            (0),
    version2            (1)
    }

END
```

The encoding of other "user information" supplied by the CMISE-service user is not defined by this Recommendation | International Standard.

7.3.2 A-ABORT user data

The encoding of the CMIP user information to be passed to A-ABORT in the "user information" parameter is defined as follows:

CMIP-A-ABORT-Information {joint-iso-itu-t ms(9) cmip(1) modules(0) aAbortUserInfo(2)}

```
DEFINITIONS             ::= BEGIN

--  Information carried in user-information parameter of A-ABORT

CMIPAbortInfo     ::= SEQUENCE {
    abortSource         [0] IMPLICIT CMIPAbortSource,
    userInfo            [1] EXTERNAL OPTIONAL
    }

CMIPAbortSource   ::= ENUMERATED {
    cmiseServiceUser        (0),
    cmiseServiceProvider    (1)
    }

END
```

The encoding of other "user information" supplied by the CMISE-service user is not defined by this Recommendation | International Standard.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

7.4 CMIP data units

The protocol is described in terms of Common Management Information Protocol Data Units exchanged between the peer CMISEs. The PDUs are specified using ASN.1 and the Remote Operations Protocol OPERATION and ERROR external macros defined in CCITT Rec. X.219 | ISO/IEC 9072-1.

```
-- Common Management Information Protocol (CMIP)

CMIP-1 {joint-iso-itu-t ms(9) cmip(1) modules(0) protocol(3)}

DEFINITIONS ::= BEGIN

-- Remote Operations definitions

IMPORTS OPERATION, ERROR FROM Remote-Operation-Notation {joint-iso-ccitt remote-operations(4) notation(0)}

-- Remote Operations Service definitions

InvokeIDType FROM Remote-Operations-APDUs {joint-iso-ccitt remote-operations(4) apdus(1)}

-- Directory Service definitions
-- This Recommendation | International Standard imports abstract syntax from CCITT Rec. X.501 (1988) |
-- ISO/IEC 9594-2:1990. Annex D to this Recommendation | International Standard provides an extract
-- from CCITT Rec. X.501 (1988) | ISO/IEC 9594-2:1990, sufficient to meet the needs of CMIP.

DistinguishedName, RDNSequence
    FROM InformationFramework {joint-iso-ccitt ds(5) modules(1) informationFramework(1)};

-- CMISE operations
-- in the following operations, the argument type is mandatory in the corresponding ROSE APDU
-- Action operations (M-ACTION)

m-Action OPERATION
    ARGUMENT ActionArgument
    ::= localValue : 6

m-Action-Confirmed OPERATION
    ARGUMENT    ActionArgument
    RESULT      ActionResult  -- this result is conditional; for conditions see 8.3.3.2.9 of ITU-T Rec. X.710 |
                              -- ISO/IEC 9595
    ERRORS {    accessDenied, classInstanceConflict, complexityLimitation, invalidScope,
                invalidArgumentValue, invalidFilter, noSuchAction, noSuchArgument, noSuchObjectClass,
                noSuchObjectInstance, processingFailure, syncNotSupported }
    LINKED { m-Linked-Reply }
    ::= localValue : 7

m-CancelGet OPERATION
    ARGUMENT
    getInvokeId     InvokeIDType
    RESULT
    ERRORS {    mistypedOperation, noSuchInvokeId, processingFailure }
    ::= localValue : 10

-- Create operation (M-CREATE)

m-Create OPERATION
    ARGUMENT    CreateArgument
    RESULT      CreateResult  -- this result is conditional; for conditions see 8.3.4.1.3 of ITU-T Rec. X.710 |
                              -- ISO/IEC 9595
    ERRORS {    accessDenied, classInstanceConflict, duplicateManagedObjectInstance,
                invalidAttributeValue, invalidObjectInstance, missingAttributeValue, noSuchAttribute,
                noSuchObjectClass, noSuchObjectInstance, noSuchReferenceObject, processingFailure }
    ::= localValue : 8

-- Delete operation (M-DELETE)

m-Delete OPERATION
    Argument    DeleteArgument
    RESULT      DeleteResult  -- this result is conditional; for conditions see 8.3.5.2.8 of ITU-T Rec. X.710 |
                              -- ISO/IEC 9595
    ERRORS {    accessDenied, classInstanceConflict, complexityLimitation, invalidFilter,
                InvalidScope, noSuchObjectClass, noSuchObjectInstance, processingFailure, syncNotSupported }
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
    LINKED { m-Linked-Reply }
    ::= localValue : 9

--  Event Reporting operations (M-EVENT-REPORT)

m-EventReport OPERATION
    ARGUMENT      EventReportArgument
    ::= localValue : 0

m-EventReport-Confirmed OPERATION
    ARGUMENT      EventReportArgument
    RESULT        EventReportResult    -- optional
    ERRORS {      invalidArgumentValue, noSuchArgument, noSuchEventType, noSuchObjectClass,
                  noSuchObjectInstance, processingFailure }
    ::= localValue : 1

--  Get operation (M-GET)

m-Get OPERATION
    ARGUMENT      GetArgument
    RESULT        GetResult -- this result is conditional; for conditions see 8.3.1.2.8 of ITU-T Rec. X.710 |
                            -- ISO/IEC 9595
    ERRORS {      accessDenied, classInstanceConflict, complexityLimitation, getListError, invalidFilter, invalidScope,
                  noSuchObjectClass, noSuchObjectInstance, operationCancelled, processingFailure, syncNotSupported
                }
    LINKED { m-Linked-Reply }
    ::= localValue : 3

--  Linked operation to M-GET, M-SET (Confirmed), M-ACTION (Confirmed), and M-DELETE

m-Linked-Reply OPERATION
    ARGUMENT      LinkedReplyArgument
    ::= localValue : 2

--  Set operations (M-SET)

m-Set OPERATION
    ARGUMENT      SetArgument
    ::= localValue : 4

m-Set-Confirmed OPERATION
    ARGUMENT      SetArgument
    RESULT        SetResult -- this result is conditional; for conditions see 8.3.2.2.9 of ITU-T Rec. X.710 |
                            -- ISO/IEC 9595
    ERRORS {      accessDenied, classInstanceConflict, complexityLimitation, invalidFilter, invalidScope,
                  noSuchObjectClass, noSuchObjectInstance, processingFailure, setListError, syncNotSupported }
    LINKED { m-Linked-Reply }
    ::= localValue : 5

--  CMIS error definitions
--  in the following errors, unless otherwise indicated, the parameter type is mandatory in the corresponding ROSE
--  APDU

accessDenied ERROR
    ::= localValue : 2

classInstanceConflict ERROR
    PARAMETER     BaseManagedObjectId
    ::= localValue : 19

complexityLimitation ERROR
    PARAMETER     ComplexityLimitation-- optional
    ::= localValue : 20

duplicateManagedObjectInstance ERROR
    PARAMETER     ObjectInstance
    ::= localValue : 11

getListError ERROR
    PARAMETER     GetListError
    ::= localValue : 7
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

invalidArgumentValue ERROR
PARAMETER InvalidArgumentValue
::= localValue : 15

invalidAttributeValue ERROR
PARAMETER Attribute
::= localValue : 6

invalidFilter ERROR
PARAMETER CMISFilter
::= localValue : 4

invalidObjectInstance ERROR
PARAMETER ObjectInstance
::= localValue : 17

invalidScope ERROR
PARAMETER Scope
::= localValue : 16

missingAttributeValue ERROR
PARAMETER SET OF AttributeId
::= localValue : 18

mistypedOperation ERROR
::= localValue : 21

noSuchAction ERROR
PARAMETER NoSuchAction
::= localValue : 9

noSuchArgument ERROR
PARAMETER NoSuchArgument
::= localValue : 14

noSuchAttribute ERROR
PARAMETER AttributeId
::= localValue : 5

noSuchEventType ERROR
PARAMETER NoSuchEventType
::= localValue : 13

noSuchInvokeId ERROR
PARAMETER InvokeIDType
::= localValue : 22

noSuchObjectClass ERROR
PARAMETER ObjectClass
::= localValue : 0

noSuchObjectInstance ERROR
PARAMETER ObjectInstance
::= localValue : 1

noSuchReferenceObject ERROR
PARAMETER ObjectInstance
::= localValue : 12

operationCancelled ERROR
::= localValue : 23

processingFailure ERROR
PARAMETER ProcessingFailure -- *optional*
::= localValue : 10

setListError ERROR
PARAMETER SetListError
::= localValue : 8

syncNotSupported ERROR
PARAMETER CMISSync
::= localValue : 3

-- *Supporting type definitions*

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
AccessControl       ::= EXTERNAL

ActionArgument      ::= SEQUENCE {
    COMPONENTS OF       BaseManagedObjectId,
    accessControl       [5] AccessControl OPTIONAL,
    synchronization     [6] IMPLICIT CMISSync DEFAULT bestEffort,
    scope               [7] Scope DEFAULT namedNumbers : baseObject,
    filter              CMISFilter DEFAULT and : {},
    actionInfo          [12] IMPLICIT ActionInfo
    }

ActionError     ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance   ObjectInstance OPTIONAL,
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    actionErrorInfo         [6] ActionErrorInfo
    }

ActionErrorInfo     ::= SEQUENCE {
    errorStatus     ENUMERATED  {   accessDenied        (2),
                                    noSuchAction        (9),
                                    noSuchArgument      (14),
                                    invalidArgumentValue (15) },
    errorInfo       CHOICE {
        actionType          ActionTypeId,
        actionArgument      [0] NoSuchArgument,
        argumentValue       [1] InvalidArgumentValue
    } }

ActionInfo      ::= SEQUENCE {
    actionType      ActionTypeId,
    actionInfoArg   [4] ANY DEFINED BY actionType OPTIONAL
    }

ActionReply     ::= SEQUENCE {
    actionType          ActionTypeId,
    actionReplyInfo     [4] ANY DEFINED BY actionType
    }

ActionResult    ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance   ObjectInstance OPTIONAL,
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    actionReply             [6] IMPLICIT ActionReply OPTIONAL
    }

ActionTypeId    ::= CHOICE {
    globalForm      [2] IMPLICIT OBJECT IDENTIFIER,
    localForm       [3] IMPLICIT INTEGER
    }
-- This Recommendation | International Standard does not allocate any values for localForm. Where this alternative is
-- used, the permissible values for the integers and their meanings shall be defined as part of the application context in
-- whichthey are used

Attribute ::= SEQUENCE {
    attributeId     AttributeId,
    attributeValue  ANY DEFINED BY  attributeId
    }

AttributeError      ::= SEQUENCE {
    errorStatus     ENUMERATED {    accessDenied            (2),
                                    noSuchAttribute         (5),
                                    invalidAttributeValue   (6),
                                    invalidOperation        (24),
                                    invalidOperator         (25) },
    modifyOperator  [2] IMPLICIT ModifyOperator OPTIONAL,   -- present for invalidOperator & invalidOperation
    attributeId     AttributeId,
    attributeValue  ANY DEFINED BY attributeId OPTIONAL     -- absent for setToDefault
    }
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
AttributeId     ::= CHOICE {
    globalForm          [0] IMPLICIT OBJECT IDENTIFIER,
    localForm           [1] IMPLICIT INTEGER
    }
-- This Recommendation | International Standard does not allocate any values for localForm. Where this alternative is
--  used, the permissible values for the integers and their meanings shall be defined as part of the application context in
-- which they are used

AttributeIdError    ::= SEQUENCE {
    errorStatus         ENUMERATED {        accessDenied            (2),
                                            noSuchAttribute         (5) },
    attributeId     AttributeId
    }

BaseManagedObjectId     ::= SEQUENCE {
    baseManagedObjectClass      ObjectClass,
    baseManagedObjectInstance       ObjectInstance
    }

CMISFilter      ::= CHOICE {
    item        [8] FilterItem,
    and         [9] IMPLICIT SET OF CMISFilter,
    or          [10] IMPLICIT SET OF CMISFilter,
    not         [11] CMISFilter
    }

CMISSync        ::= ENUMERATED {    bestEffort      (0),
                                    atomic          (1) }

ComplexityLimitation        ::= SET {
    scope       [0] Scope OPTIONAL,
    filter      [1] CMISFilter OPTIONAL,
    sync        [2] CMISSync OPTIONAL
    }

CreateArgument      ::= SEQUENCE {
    managedObjectClass          ObjectClass,
    managedOrSuperiorObjectInstance     CHOICE {
        managedObjectInstance               ObjectInstance,
        superiorObjectInstance              [8] ObjectInstance } OPTIONAL,
    accessControl               [5] AccessControl OPTIONAL,
    referenceObjectInstance     [6] ObjectInstance OPTIONAL,
    attributeList               [7] IMPLICIT SET OF Attribute OPTIONAL
    }

CreateResult    ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance   ObjectInstance OPTIONAL,    -- shall be returned if omitted from CreateArgument
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    attributeList           [6] IMPLICIT SET OF Attribute OPTIONAL
    }

DeleteArgument      ::= SEQUENCE {
    COMPONENTS OF       BaseManagedObjectId,
    accessControl       [5] AccessControl OPTIONAL,
    synchronization     [6] IMPLICIT CMISSync DEFAULT bestEffort,
    scope               [7] Scope DEFAULT namedNumbers : baseObject,
    filter              CMISFilter DEFAULT and : {}
    }

DeleteError     ::= SEQUENCE {
    managedObjectClass          ObjectClass OPTIONAL,
    managedObjectInstance       ObjectInstance OPTIONAL,
    currentTime                 [5] IMPLICIT GeneralizedTime OPTIONAL,
    deleteErrorInfo             [6] ENUMERATED { accessDenied (2)
    } }

DeleteResult    ::= SEQUENCE {
    managedObjectClass          ObjectClass OPTIONAL,
    managedObjectInstance       ObjectInstance OPTIONAL,
    currentTime                 [5] IMPLICIT GeneralizedTime OPTIONAL
    }
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
EventReply      ::= SEQUENCE {
    eventType           EventTypeId,
    eventReplyInfo      [8] ANY DEFINED BY eventType OPTIONAL
    }

EventReportArgument     ::= SEQUENCE {
    managedObjectClass      ObjectClass,
    managedObjectInstance   ObjectInstance,
    eventTime               [5] IMPLICIT GeneralizedTime OPTIONAL,
    eventType               EventTypeId,
    eventInfo               [8] ANY DEFINED BY eventType OPTIONAL
    }

EventReportResult   ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance   ObjectInstance OPTIONAL,
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    eventReply              EventReply OPTIONAL
    }

EventTypeId     ::= CHOICE {
    globalForm      [6] IMPLICIT OBJECT IDENTIFIER,
    localForm       [7] IMPLICIT INTEGER
    }
-- This Recommendation | International Standard does not allocate any values for localForm. Where this alternative is
-- used, the permissible values for the integers and their meanings shall be defined as part of the application context in
-- which they are used

FilterItem      ::= CHOICE {
    equality                [0] IMPLICIT Attribute,
    substrings              [1] IMPLICIT SEQUENCE OF CHOICE {
        initialString           [0] IMPLICIT SEQUENCE {
                                    attributeIdAttributeId,
                                    string      ANY DEFINED BY attributeId },
        anyString               [1] IMPLICIT SEQUENCE {
                                    attributeIdAttributeId,
                                    string      ANY DEFINED BY attributeId },
        finalString             [2] IMPLICIT SEQUENCE {
                                    attributeIdAttributeId,
                                    string      ANY DEFINED BY attributeId} },
    greaterOrEqual          [2] IMPLICIT Attribute, -- asserted value ≥ attribute value
    lessOrEqual             [3] IMPLICIT Attribute, -- asserted value ≤ attribute value
    present             [4] AttributeId,
    subsetOf                [5] IMPLICIT Attribute, -- asserted value is a subset of attribute value
    supersetOf              [6] IMPLICIT Attribute, -- asserted value is a superset of attribute value
    nonNullSetIntersection  [7] IMPLICIT Attribute
    }

GetArgument     ::= SEQUENCE {
    COMPONENTS OF       BaseManagedObjectId,
    accessControl       [5] AccessControl OPTIONAL,
    synchronization     [6] IMPLICIT CMISSync DEFAULT bestEffort,
    scope               [7] Scope DEFAULT namedNumbers : baseObject,
    filter              CMISFilter DEFAULT and : {},
    attributeIdList     [12] IMPLICIT SET OF AttributeId OPTIONAL
    }

GetInfoStatus   ::= CHOICE {
    attributeIdError    [0] IMPLICIT AttributeIdError,
    attribute           [1] IMPLICIT Attribute
    }

GetListError    ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance   ObjectInstance OPTIONAL,
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    getInfoList             [6] IMPLICIT SET OF GetInfoStatus
    }
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
GetResult       ::= SEQUENCE {
    managedObjectClass          ObjectClass OPTIONAL,
    managedObjectInstance       ObjectInstance OPTIONAL,
    currentTime                 [5] IMPLICIT GeneralizedTime OPTIONAL,
    attributeList               [6] IMPLICIT SET OF Attribute OPTIONAL
    }

InvalidArgumentValue    ::= CHOICE {
    actionValue         [0] IMPLICIT ActionInfo,
    eventValue          [1] IMPLICIT SEQUENCE {
        eventType           EventTypeId,
        eventInfo           [8] ANY DEFINED BY eventType OPTIONAL }
    }

LinkedReplyArgument     ::= CHOICE {
    getResult               [0] IMPLICIT GetResult,
    getListError            [1] IMPLICIT GetListError,
    setResult               [2] IMPLICIT SetResult,
    setListError            [3] IMPLICIT SetListError,
    actionResult            [4] IMPLICIT ActionResult,
    processingFailure       [5] IMPLICIT ProcessingFailure,
    deleteResult            [6] IMPLICIT DeleteResult,
    actionError             [7] IMPLICIT ActionError,
    deleteError             [8] IMPLICIT DeleteError
    }

ModifyOperator      ::= INTEGER {   replace         (0),
                                    addValues       (1),
                                    removeValues    (2),
                                    setToDefault    (3) }

NoSuchAction        ::= SEQUENCE {
    managedObjectClass      ObjectClass,
    actionType              ActionTypeId
    }

NoSuchArgument      ::= CHOICE {
    actionId        [0] IMPLICIT SEQUENCE {
        managedObjectClass      ObjectClass OPTIONAL,
        actionType              ActionTypeId },
    eventId         [1] IMPLICIT SEQUENCE {
        managedObjectClass      ObjectClass OPTIONAL,
        eventType               EventTypeId }
    }

NoSuchEventType     ::= SEQUENCE {
    managedObjectClass      ObjectClass,
    eventType               EventTypeId
    }

ObjectClass     ::= CHOICE {
    globalForm          [0] IMPLICIT OBJECT IDENTIFIER,
    localForm           [1] IMPLICIT INTEGER
    }
-- This Recommendation | International Standard does not allocate any values for localForm. Where this alternative is
-- used, the permissible values or the integers and their meanings shall be defined as part of the application context in
-- which they are used

ObjectInstance      ::= CHOICE {
    distinguishedName           [2] IMPLICIT DistinguishedName,
    nonSpecificForm             [3] IMPLICIT OCTET STRING,
    localDistinguishedName      [4] IMPLICIT RDNSequence
    }
-- localDistinguishedName is that portion of the distinguished name that is necessary to unambiguously identify the
-- managed object within the context of communication between the open systems

ProcessingFailure   ::= SEQUENCE {
    managedObjectClass          ObjectClass,
    managedObjectInstance       ObjectInstance OPTIONAL,
    specificErrorInfo           [5] SpecificErrorInfo
    }
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
Scope      ::= CHOICE { namedNumbers      INTEGER {  baseObject        (0),
                                                     firstLevelOnly    (1),
                                                     wholeSubtree      (2) },
    individualLevels      [1] IMPLICIT INTEGER,   -- POSITIVE integer indicates the level to be selected
    baseToNthLevel        [2] IMPLICIT INTEGER }  -- POSITIVE integer N indicates that the range of levels
                                                  -- (0 – N) is to be selected
--  with individualLevels and baseToNthLevel, a value of 0 has the same semantics as baseObject
--  with individualLevels, a value of 1 has the same semantics as firstLevelOnly

SetArgument   ::= SEQUENCE {
    COMPONENTS OF      BaseManagedObjectId,
    accessControl      [5] AccessControl OPTIONAL,
    synchronization    [6] IMPLICIT CMISSync DEFAULT bestEffort,
    scope              [7] Scope DEFAULT namedNumbers : baseObject,
    filter             CMISFilter DEFAULT and : {},
    modificationList   [12] IMPLICIT SET OF SEQUENCE {
        modifyOperator     [2] IMPLICIT ModifyOperator DEFAULT replace,
        attributeId        AttributeId,
        attributeValue     ANY DEFINED BY attributeId OPTIONAL    -- absent for setToDefault
    } }

SetInfoStatus      ::= CHOICE {
    attributeError     [0] IMPLICIT AttributeError,
    attribute          [1] IMPLICIT Attribute
    }

SetListError   ::= SEQUENCE {
    managedObjectClass       ObjectClass OPTIONAL,
    managedObjectInstance    ObjectInstance OPTIONAL,
    currentTime              [5] IMPLICIT GeneralizedTime OPTIONAL,
    setInfoList              [6] IMPLICIT SET OF SetInfoStatus
    }

SetResult      ::= SEQUENCE {
    managedObjectClass       ObjectClass OPTIONAL,
    managedObjectInstance    ObjectInstance OPTIONAL,
    currentTime              [5] IMPLICIT GeneralizedTime OPTIONAL,
    attributeList            [6] IMPLICIT SET OF Attribute OPTIONAL
    }

SpecificErrorInfo  ::= SEQUENCE {
    errorId            OBJECT IDENTIFIER,
    errorInfo          ANY DEFINED BY errorId
    }

END        -- End of CMIP syntax definitions
```

7.5 Definition of abstract syntax for CMIP

This Recommendation | International Standard assigns the ASN.1 object identifier value

{joint-iso-itu-t ms(9) cmip(1) cmip-pci(1) abstractSyntax(4)}

as an abstract syntax name for the set of presentation data values, each of which is either a value of the ASN.1 type

Remote-Operations-APDUs.ROSEapdus

as defined in CCITT Rec. X.229 | ISO/IEC 9072-2 with the argument component filled according to the definitions in CMIP-1, or a value of one of the ASN.1 types:

– CMIP-A-ASSOCIATE-Information.CMIPUserInfo;

– CMIP-A-ABORT-Information.CMIPAbortInfo.

The corresponding ASN.1 object descriptor value shall be

"CMIP-PCI".

This abstract syntax is defined to include all data types resolved by the ANY DEFINED BY X productions, in which X is of type OBJECT IDENTIFIER.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

The ASN.1 object identifier and object descriptor values

{joint-iso-ccitt asn1(1) basic-encoding(1)} and "Basic Encoding of single ASN.1 type"

(assigned to an object in CCITT Rec. X.209 | ISO/IEC 8825) can be used as a transfer syntax name with this abstract syntax.

7.5.1 Extensibility rules

7.5.1.1 When processing incoming CMIP-A-ASSOCIATE-Information, the accepting CMIPM shall:

- ignore all tagged values that are not defined in the abstract syntax of this Recommendation | International Standard; and
- ignore all unknown bit name assignments within a BIT STRING.

7.5.1.2 The abstract syntax name may be used when the presentation data values are modified to include:

- new system management operations;
- new tagged elements within a SET or SEQUENCE;
- new bit name assignments within a BIT STRING;
- new named numbers for an INTEGER; and
- new named enumerations within an ENUMERATED.

8 Conformance

A system claiming to implement the procedures specified in this Recommendation | International Standard shall comply with the requirements in 8.1 and 8.2.

8.1 Static requirements

An implementation that is claimed to conform to this Recommendation | International Standard shall be accompanied by a PICS in conformance with the PICS proforma as specified by ITU-T Rec. X.712 | ISO/IEC 9596-2. In particular, it shall be stated that the implementation either:

1) supports the protocol, required to provide all of the CMIS services defined in the kernel functional unit, in both the invoker and performer roles; or
2) supports the protocol, required to provide some of the CMIS services defined in the kernel functional unit, in the invoker and/or performer roles; but not all of the protocol in both roles for all of the CMIS services.

The implementation shall:

a) support the elements of procedure specified in clause 6 of this Recommendation | International Standard for those services in the role for which conformance is claimed;

b) support the abstract syntax associated with the protocol data units that are necessary to convey the requests and/or responses for those services in the role for which conformance is claimed;

c) support the transfer syntax derived from the encoding rules specified in CCITT Rec. X.209 | ISO/IEC 8825 and named

{joint-iso-ccitt asn1(1) basic-encoding(1)},

for the purpose of generating and interpreting CMIP PDUs as defined by the abstract syntax

"CMIP-PCI",

for the elements of protocol to which conformance is claimed:

d) support the ACSE protocol defined in ITU-T Rec. X.227 | ISO/IEC 8650-1, to establish and to release an association;

e) support the rules specified in Annex A in any application context that includes CMISE as one of the ASEs;

f) support association class 3 of the ROSE protocol defined in CCITT Rec. X.229 | ISO/IEC 9072-2;

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

g) support the elements of protocol that are required to provide the multiple reply functional unit if the multiple object selection functional unit is selected;

h) support the elements of protocol that are required to provide the M-GET service if the cancel get functional unit is supported;

8.2 Dynamic requirements

The system shall:

a) support the elements of procedure for each of the CMIS services in the role for which conformance is claimed;

b) when used, verify the optional security parameters defined in the CMIP PDUs;

c) when the extended service functional unit is supported, support the presentation protocol defined in ITU-T Rec. X.226 | ISO/IEC 8823-1, as required by the application context;

d) when scoping is provided, support the elements of procedure for the multiple reply functional unit.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Annex A

Association rules for CMISE

(This annex does not form an integral part of this Recommendation | International Standard)

A.1 ACSE, session and presentation requirements

A.1.1 CMISE requires the kernel presentation functional unit as defined in ITU-T Rec. X.216 | ISO/IEC 8822.

A.1.2 CMISE requires the kernel and full duplex session functional units as defined in ITU-T Rec. X.215 | ISO/IEC 8326.

A.1.3 CMISE requires the normal mode of ACSE and presentation services as defined in ITU-T Rec. X.227 | ISO/IEC 8650-1 and ITU-T Rec. X.216 | ISO/IEC 8822.

A.2 Association initialization rules

A.2.1 Request

The CMISE-service-user that initiates the association establishment shall provide the A-ASSOCIATE user information defined by ITU-T Rec. X.710 | ISO/IEC 9595. The CMIP user information shall be made available to the CMIPM which shall:

a) construct CMIPUserInfo from the information supplied;

b) set the protocol version parameter within CMIPUserInfo by setting the bit corresponding to each version supported;

c) include CMIPUserInfo as a separate EXTERNAL in the user information parameter of the A-ASSOCIATE request primitive;

d) wait for the user information specific to CMIS to be returned in the A-ASSOCIATE confirmation primitive.

A.2.2 Indication

On receipt of an A-ASSOCIATE indication primitive, the CMIPUserInfo parameter shall be made available to the CMIPM which shall:

a) check that at least one of the proposed protocol version can be supported;

b) verify that the optional access control parameter is valid;

c) if any of the checks fail, the association shall be rejected by setting the reason for failure parameter in the A-ASSOCIATE response primitive to "rejected by responder (permanent)". The association is not established and that instance of the CMIPM shall cease to exist;

d) if the above checks succeed, the following information, if present in CMIPUserInfo, shall be made available to the CMISE-service-user: functional units supported by the CMISE-service-provider, access control and user information. The CMIPM shall wait for the response from the CMISE-service-user.

A.2.3 Response

The A-ASSOCIATE response primitive indicating "accepted" or "rejected", and which if accepted, includes the functional units, access control and user information parameters, shall be made available to the CMIPM which shall:

a) construct CMIPUserInfo required for the response. The CMIPUserInfo shall include the version parameter indicating all versions of CMIP that are supported;

b) include CMIPUserInfo as a separate EXTERNAL in the user information parameter of the A-ASSOCIATE response primitive;

c) if the association response indicates "accepted", the protocol version agreed to is the version corresponding to the highest number supported by both CMIPMs. The CMIPM shall then be ready to accept CMISE indication primitives;

d) if the association response indicates "rejected", that instance of the CMIPM shall cease to exist.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

A.2.4 Confirmation

On receipt of the A-ASSOCIATE confirmation primitive, the CMIPUserInfo parameter shall be made available to the CMIPM which shall:

a) if the association confirmation indicates success, the association is established and the functional units, access control and user information parameters, if present in the confirmation, are made available to the association-initiator. The functional units agreed to correspond to those for which both CMISE-service-users indicated support and the protocol version is the highest version number supported by both CMIPMs;

b) if the association confirmation indicates failure, the association is not established and that instance of the CMIPM shall cease to exist.

A.3 Association release rules

Either CMISE-service-user may initiate an association release.

A.3.1 Request

On receipt of a request for association release, the necessary A-RELEASE parameters shall be made available to the CMIPM which shall cease to accept service requests and wait for the confirmation of the release of the association.

A.3.2 Indication

On receipt of an A-RELEASE indication primitive, the necessary A-RELEASE indication parameters shall be made available to the responding CMIPM which shall wait for the association release response.

A.3.3 Response

On receipt of an association release response from the responding CMISE-service-user, the necessary A-RELEASE response parameters shall be made available to the responding CMIPM. Thereafter, that instance of the CMIPM shall cease to exist.

A.3.4 Confirmation

On receipt of an A-RELEASE confirmation primitive, the necessary A-RELEASE confirmation parameters shall be made available to the initiating CMIPM. Thereafter, that instance of the CMIPM shall cease to exist.

A.4 Association abort rules

Either CMISE-service-user may initiate an abrupt termination of the association.

On the basis of local information, if the ability of the underlying services to convey unlimited user information by A-ABORT does not exist, the CMIPAbortInfo parameter may not be included in the A-ABORT service primitives.

A.4.1 A-ABORT request

On receipt of a request to abort the association, the necessary A-ABORT request parameters including the A-ABORT user information defined by ITU-T Rec. X.710 | ISO/IEC 9595 shall be made available to the CMIPM which shall:

a) construct CMIPAbortInfo from the information supplied;

b) set the abort source parameter within CMIPUserInfo to CMISE-service-user;

c) include CMIPAbortInfo as a separate field in the user information parameter of the A-ABORT request primitive;

d) thereafter, that instance of the CMIPM shall cease to exist.

A.4.2 A-ABORT indication

On receipt of an A-ABORT indication primitive, the necessary A-ABORT indication parameters including CMIPAbortInfo shall be made available to the CMIPM. Thereafter, that instance of the CMIPM shall cease to exist.

A.4.3 A-P-ABORT indication

On receipt of an A-P-ABORT indication primitive, the necessary A-P-ABORT indication parameters shall be made available to the CMIPM. Thereafter, that instance of the CMIPM shall cease to exist.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

A.4.4 CMIP protocol error

On detecting a protocol error, the CMIPM shall:

a) construct CMIPAbortInfo with the abort source parameter set to CMISE-service-provider;

b) indicate to the CMISE-service-user that a protocol error has occurred;

c) include CMIPAbortInfo as a separate field in the user information parameter of the A-ABORT request primitive;

d) thereafter, that instance of the CMIPM shall cease to exist.

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Annex B

Expanded ASN.1 syntax

(This annex does not form an integral part of this Recommendation | International Standard)

This annex describes how the OPERATION and ERROR macros of CCITT Rec. X.219 | ISO/IEC 9072-1 are expanded into ASN.1 data types and subtypes.

If any inconsistencies exist between these definitions and the definitions in clause 7, then the definitions in clause 7 take precedence.

```
-- Common Management Information Protocol (CMIP)

CMIP-1 {joint-iso-itu-t ms(9) cmip(1) modules(0) protocol(3)}

DEFINITIONS ::= BEGIN

-- Remote Operations definitions

IMPORTS OPERATION, ERROR FROM Remote-Operation-Notation {joint-iso-ccitt remote-operations(4) notation(0)}

-- Directory Service definitions

DistinguishedName, RDNSequence
    FROM InformationFramework {joint-iso-ccitt ds(5) modules(1) informationFramework(1)};

--  CMISE operations

ROSEapdus ::= CHOICE {
    roiv-apdu       [1] IMPLICIT ROIVapdu,
    rors-apdu       [2] IMPLICIT RORSapdu,
    roer-apdu       [3] IMPLICIT ROERapdu,
    rorj-apdu       [4] IMPLICIT RORJapdu
    }

ROIVapdu ::= SEQUENCE {
    invokeID            InvokeIDType,
    linked-ID           [0] IMPLICIT InvokeIDType OPTIONAL,
    operation-value     OPERATION,
    argument            ANY DEFINED BY operation-value OPTIONAL
    }

RORSapdu ::= SEQUENCE {
    invokeID        InvokeIDType,
    SEQUENCE {      operation-value   OPERATION,
                    result            ANY DEFINED BY operation-value } OPTIONAL
    }

ROERapdu ::= SEQUENCE {
    invokeID        InvokeIDType,
    error-value     ERROR,
    parameter       ANY DEFINED BY error-value OPTIONAL
    }

RORJapdu ::= SEQUENCE {
    invokeID    CHOICE {InvokeIDType,
                        NULL },
    problem     CHOICE {    [0] IMPLICIT GeneralProblem,
                            [1] IMPLICIT InvokeProblem,
                            [2] IMPLICIT ReturnResultProblem,
                            [3] IMPLICIT ReturnErrorProblem }
    }

InvokeIDType ::= INTEGER

--  The use of the GeneralProblem, ReturnResultProblem, and ReturnErrorProblem codes are a local issue.

GeneralProblem              ::= INTEGER {
    unrecognisedAPDU    (0), -- ROSE-provider detected
    mistypedAPDU        (1),
    badlyStructuredAPDU (2)
    }
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
InvokeProblem ::= INTEGER {
    duplicateInvocation          (0), -- ROSE-user detected
    unrecognisedOperation        (1),
    mistypedArgument             (2),
    resourceLimitation           (3),
    initiatorReleasing           (4),
    unrecognisedLinkedID         (5),
    linkedResponseUnexpected     (6),
    unexpectedChildOperation     (7)
    }

ReturnResultProblem    ::= INTEGER {
    unrecognisedInvocation       (0), -- ROSE-user detected
    resultResponseUnexpected     (1),
    mistypedResult               (2)
    }

ReturnErrorProblem     ::= INTEGER {
    unrecognisedInvocation       (0), -- ROSE-user detected
    errorResponseUnexpected      (1),
    unrecognisedError            (2),
    unexpectedError              (3),
    mistypedParameter            (4)
    }

-- This part of the ASN.1 specification provides a definition of the InvokeProblem subtype used by CMIP.

InvokeProblem-CMIPUser     ::= InvokeProblem (
    duplicateInvocation          |
    unrecognisedOperation        |
    mistypedArgument             |
    resourceLimitation
    )

-- This part of the ASN.1 specification provides a definition of ROIVapdu and RORSapdu subtypes used by CMIP.
-- The subtypes of the ROIVapdu define the allowed values of the operation-value and argument defined by that
-- operation-value for all CMIP notifications and operations. The subtypes of the RORSapdu define the allowed
-- values of the operation-value and result defined by that operation-value for all CMIP notifications and operations.

m-Action OPERATION  ::= localValue : 6

ROIV-m-Action      ::= ROIVapdu (WITH COMPONENTS {
    invokeID                     PRESENT,
    linked-ID                    ABSENT,
    operation-value              (m-Action),
    argument                     (INCLUDES ActionArgument) } )

m-Action-Confirmed OPERATION ::= localValue : 7

ROIV-m-Action-Confirmed    ::= ROIVapdu (WITH COMPONENTS {
    invokeID                     PRESENT,
    linked-ID                    ABSENT,
    operation-value              (m-Action-Confirmed),
    argument                     (INCLUDES ActionArgument) } )

RORS-m-Action-Confirmed    ::= RORSapdu (WITH COMPONENTS {
    ... ,
    invokeID                     PRESENT,
    -- result sequence -- (WITH COMPONENTS
    { operation-value            (m-Action-Confirmed),
    result                       (INCLUDES ActionResult) } )
    -- required only if there is a single reply to the ROIV-m-Action-Confirmed ROIVapdu and data is to be returned in
    -- the RORSapdu
    } )
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
m-Cancel-Get OPERATION          ::= localValue : 10

ROIV-m-Cancel-Get       ::= ROIVapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    linked-ID           ABSENT,
    operation-value     (m-Cancel-Get),
    argument            (INCLUDES InvokeIDType)
    } )

RORS-m-Cancel-Get       ::= RORSapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    -- There is no result sequence for RORS-m-Cancel-Get
    } )

m-Create OPERATION  ::= localValue : 8

ROIV-m-Create       ::= ROIVapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    linked-ID           ABSENT,
    operation-value     (m-Create),
    argument            (INCLUDES CreateArgument) } )

RORS-m-Create       ::= RORSapdu (WITH COMPONENTS {
    ... ,
    invokeID            PRESENT,
    -- result sequence -- (WITH COMPONENTS
    { operation-value   (m-Create),
    result              (INCLUDES CreateResult) } )
    } )

m-Delete OPERATION  ::= localValue : 9

ROIV-m-Delete       ::= ROIVapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    linked-ID           ABSENT,
    operation-value     (m-Delete),
    argument            (INCLUDES DeleteArgument) } )

RORS-m-Delete       ::= RORSapdu (WITH COMPONENTS {
    ... ,
    invokeID            PRESENT,
    -- result sequence -- (WITH COMPONENTS
    { operation-value   (m-Delete),
    result              (INCLUDES DeleteResult) } )
    -- required only if there is a single reply to the ROIV-m-DeleteROIVapdu and data is to be returned in the RORSapdu
    } )

m-EventReport OPERATION ::= localValue : 0

ROIV-m-EventReport      ::= ROIVapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    linked-ID           ABSENT,
    operation-value     (m-EventReport),
    argument            (INCLUDES EventReportArgument) } )

m-EventReport-Confirmed OPERATION       ::= localValue : 1

ROIV-m-EventReport-Confirmed    ::= ROIVapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    linked-ID           ABSENT,
    operation-value     (m-EventReport-Confirmed),
    argument            (INCLUDES EventReportArgument) } )

RORS-m-EventReport-Confirmed    ::= RORSapdu (WITH COMPONENTS {
    ... ,
    invokeID            PRESENT,
    -- result sequence -- (WITH COMPONENTS
    { operation-value   (m-EventReport-Confirmed),
    result              (INCLUDES EventReportResult) } )
    -- required only if data is to be returned in the RORSapdu
    } )
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
m-Get OPERATION      ::= localValue : 3

ROIV-m-Get                    ::= ROIVapdu (WITH COMPONENTS {
    invokeID                  PRESENT,
    linked-ID                 ABSENT,
    operation-value           (m-Get),
    argument                  (INCLUDES GetArgument) } )

RORS-m-Get  ::= RORSapdu (WITH COMPONENTS {
    ... ,
    invokeID                  PRESENT,
    -- result sequence -- (WITH COMPONENTS
    { operation-value         (m-Get),
    result                    (INCLUDES GetResult) } )
    -- required only if there is a single reply to the ROIV-m-Get ROIVapdu
    } )

m-Linked-Reply OPERATION      ::= localValue : 2

ROIV-m-Linked-Reply   ::= ROIVapdu (WITH COMPONENTS {
    invokeID                  PRESENT,
    linked-ID                 PRESENT,
    operation-value           (m-Linked-Reply),
    argument                  (INCLUDES LinkedReplyArgument) } )

--  This part of the ASN.1 specification provides a definition of ROIV-m-Linked-Reply subtypes used by CMIP. The
--  subtypes of the ROIV-m-Linked-Reply ROIVapdu define the allowed values of the argument defined by the
--  operation-value for the specific CMIP linked reply operations.

ROIV-m-Linked-Reply-Action      ::= ROIV-m-Linked-Reply (WITH COMPONENTS {
    invokeID                  PRESENT,
    linked-ID                 PRESENT,
    operation-value           (m-Linked-Reply),
    argument                  (INCLUDES LinkedReplyArgument (WITH COMPONENTS {
                                  getResult             ABSENT,
                                  getListError          ABSENT,
                                  setResult             ABSENT,
                                  setListError          ABSENT,
                                  actionResult          PRESENT,
                                  processingFailure     PRESENT,
                                  deleteResult          ABSENT,
                                  actionError           PRESENT,
                                  deleteError           ABSENT } )
    ) } )

ROIV-m-Linked-Reply-Delete      ::= ROIV-m-Linked-Reply (WITH COMPONENTS {
    invokeID                  PRESENT,
    linked-ID                 PRESENT,
    operation-value           (m-Linked-Reply),
    argument                  (INCLUDES LinkedReplyArgument (WITH COMPONENTS {
                                  getResult             ABSENT,
                                  getListError          ABSENT,
                                  setResult             ABSENT,
                                  setListError          ABSENT,
                                  actionResult          ABSENT,
                                  processingFailure     PRESENT,
                                  deleteResult          PRESENT,
                                  actionError           ABSENT,
                                  deleteError           PRESENT } )
    ) } )

ROIV-m-Linked-Reply-Get    ::= ROIV-m-Linked-Reply (WITH COMPONENTS {
    invokeID                  PRESENT,
    linked-ID                 PRESENT,
    operation-value           (m-Linked-Reply),
    argument                  (INCLUDES LinkedReplyArgument (WITH COMPONENTS {
                                  getResult             PRESENT,
                                  getListError          PRESENT,
                                  setResult             ABSENT,
                                  setListError          ABSENT,
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
                        actionResult        ABSENT,
                        processingFailure   PRESENT,
                        deleteResult        ABSENT,
                        actionError         ABSENT,
                        deleteError         ABSENT } )
    ) } )

ROIV-m-Linked-Reply-Set    ::= ROIV-m-Linked-Reply (WITH COMPONENTS {
    invokeID            PRESENT,
    linked-ID           PRESENT,
    operation-value     (m-Linked-Reply),
    argument            (INCLUDES LinkedReplyArgument (WITH COMPONENTS {
                        getResult           ABSENT,
                        getListError        ABSENT,
                        setResult           PRESENT,
                        setListError        PRESENT,
                        actionResult        ABSENT,
                        processingFailure   PRESENT,
                        deleteResult        ABSENT,
                        actionError         ABSENT,
                        deleteError         ABSENT } )
    ) } )

m-Set OPERATION     ::= localValue : 4

ROIV-m-Set    ::= ROIVapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    linked-ID           ABSENT,
    operation-value     (m-Set),
    argument            (INCLUDES SetArgument) } )

m-Set-Confirmed OPERATION     ::= localValue : 5

ROIV-m-Set-Confirmed  ::= ROIVapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    linked-ID           ABSENT,
    operation-value     (m-Set-Confirmed),
    argument            (INCLUDES SetArgument) } )

RORS-m-Set-Confirmed  ::= RORSapdu (WITH COMPONENTS {
    ... ,
    invokeID            PRESENT,
    -- result sequence -- (WITH COMPONENTS
    { operation-value   (m-Set-Confirmed),
    result              (INCLUDES SetResult) } )
    -- required only if there is a single reply to the ROIV-m-Set-Confirmed ROIVapdu and data is to be returned in the
    -- RORSapdu
    } )

--  This part of the ASN.1 specification provides a definition of ROERapdu subtypes used by CMIP. The subtypes of
--  the ROERapdu define the allowed values of the error value and parameter defined by that error-value for all
--  CMIP notifications and operations.

accessDenied ERROR     ::= localValue : 2

ROER-accessDenied::= ROERapdu (WITH COMPONENTS {
    invokeID        PRESENT,
    error-value     (accessDenied) } )

--  This ROERapdu may only be returned in response to the ROIV-m-Get, ROIV-m-Set-Confirmed,
--  ROIV-m-Action-Confirmed, ROIV-m-Create and ROIV-m-Delete ROIVapdus

classInstanceConflict ERROR     ::= localValue : 19

ROER-classInstanceConflict      ::= ROERapdu (WITH COMPONENTS {
    invokeID        PRESENT,
    error-value     (classInstanceConflict),
    parameter       (INCLUDES BaseManagedObjectId) } )

--  This ROERapdu may only be returned in response to the ROIV-m-Get, ROIV-m-Set-Confirmed,
--  ROIV-m-Action-Confirmed, ROIV-m-Create and ROIV-m-Delete ROIVapdus
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
complexityLimitation ERROR      ::= localValue : 20

ROER-complexityLimitation       ::= ROERapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    error-value         (complexityLimitation),
    parameter           (INCLUDES ComplexityLimitation) OPTIONAL } )

--  This ROERapdu may only be returned in response to the ROIV-m-Get, ROIV-m-Set-Confirmed,
--  ROIV-m-Action-Confirmed and ROIV-m-Delete ROIVapdus

duplicateManagedObjectInstance ERROR    ::= localValue : 11

ROER-duplicateManagedObjectInstance::= ROERapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    error-value         (duplicateManagedObjectInstance),
    parameter           (INCLUDES ObjectInstance) } )

--  This ROERapdu may only be returned in response to the ROIV-m-Create ROIVapdu

getListError ERROR              ::= localValue : 7

ROER-getListError ::= ROERapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    error-value         (getListError),
    parameter           (INCLUDES GetListError) } )

--  This ROERapdu may only be returned in response to the ROIV-m-Get ROIVapdu

invalidArgumentValue ERROR              ::= localValue : 15

ROER-invalidArgumentValue ::= ROERapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    error-value         (invalidArgumentValue),
    parameter           (INCLUDES InvalidArgumentValue) } )

--  This ROERapdu may only be returned in response to the ROIV-m-EventReport-Confirmed
--  and ROIV-m-Action-Confirmed ROIVapdus

invalidAttributeValue ERROR             ::= localValue : 6

ROER-invalidAttributeValue  ::= ROERapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    error-value         (invalidAttributeValue),
    parameter           (INCLUDES Attribute) } )

--  This ROERapdu may only be returned in response to the ROIV-m-Create ROIVapdu

invalidFilter ERROR     ::= localValue : 4

ROER-invalidFilter ::= ROERapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    error-value         (invalidFilter),
    parameter           (INCLUDES CMISFilter) } )

--  This ROERapdu may only be returned in response to the ROIV-m-Get, ROIV-m-Set-Confirmed,
--  ROIV-m-Action-Confirmed and ROIV-m-Delete ROIVapdus

invalidObjectInstance ERROR     ::= localValue : 17

ROER-invalidObjectInstance  ::= ROERapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    error-value         (invalidObjectInstance),
    parameter           (INCLUDES ObjectInstance) } )

--  This ROERapdu may only be returned in response to the ROIV-m-Create ROIVapdu

invalidScope ERROR              ::= localValue : 16

ROER-invalidScope       ::= ROERapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    error-value         (invalidScope),
    parameter           (INCLUDES Scope) } )

--  This ROERapdu may only be returned in response to the ROIV-m-Get, ROIV-m-Set-Confirmed,
--  ROIV-m-Action-Confirmed and ROIV-m-Delete ROIVapdus
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

```
missingAttributeValue ERROR      ::= localValue : 18

ROER-missingAttributeValue ::= ROERapdu (WITH COMPONENTS {
    invokeID          PRESENT,
    error-value       (missingAttributeValue),
    parameter         (INCLUDES SET OF AttributeId) } )

-- This ROERapdu may only be returned in response to the ROIV-m-Create ROIVapdu

mistypedOperation ERROR    ::= localValue : 21

ROER-mistypedOperation     ::= ROERapdu (WITH COMPONENTS {
    invokeID          PRESENT,
    error-value       (mistypedOperation) } )

-- This ROERapdu may only be returned in response to the ROIV-m-Cancel-Get ROIVapdu

noSuchAction ERROR    ::= localValue : 9

ROER-noSuchAction          ::= ROERapdu (WITH COMPONENTS {
    invokeID          PRESENT,
    error-value       (noSuchAction),
    parameter         (INCLUDES NoSuchAction) } )

-- This ROERapdu may only be returned in response to the ROIV-m-Action-Confirmed ROIVapdu

noSuchArgument ERROR      ::= localValue : 14

ROER-noSuchArgument       ::= ROERapdu (WITH COMPONENTS {
    invokeID          PRESENT,
    error-value       (noSuchArgument),
    parameter         (INCLUDES NoSuchArgument) } )

-- This ROERapdu may only be returned in response to the ROIV-m-EventReport-Confirmed and
-- ROIV-m-Action-Confirmed ROIVapdus

noSuchAttribute ERROR::= localValue : 5

        ROER-noSuchAttribute  ::= ROERapdu (WITH COMPONENTS {
    invokeID          PRESENT,
    error-value       (noSuchAttribute),
    parameter         (INCLUDES AttributeId) } )

-- This ROERapdu may only be returned in response to the ROIV-m-Create ROIVapdu

noSuchEventType ERROR     ::= localValue : 13

ROER-noSuchEventType::= ROERapdu (WITH COMPONENTS {
    invokeID          PRESENT,
    error-value       (noSuchEventType),
    parameter         (INCLUDES NoSuchEventType) } )

-- This ROERapdu may only be returned in response to the ROIV-m-EventReport-Confirmed ROIVapdu

noSuchInvokeId ERROR      ::= localValue : 22

ROER-noSuchInvokeId   ::= ROERapdu (WITH COMPONENTS {
    invokeID          PRESENT,
    error-value       (noSuchInvokeId),
    parameter         (INCLUDES InvokeIDType) } )

-- This ROERapdu may only be returned in response to the ROIV-m-Cancel-Get ROIVapdu

noSuchObjectClass ERROR          ::= localValue : 0

ROER-noSuchObjectClass     ::= ROERapdu (WITH COMPONENTS {
    invokeID          PRESENT,
    error-value       (noSuchObjectClass ),
    parameter         (INCLUDES ObjectClass) } )

-- This ROERapdu may only be returned in response to the ROIV-m-EventReport-Confirmed, ROIV-m-Get,
-- ROIV-m-Set-Confirmed, ROIV-m-Action-Confirmed, ROIV-m-Create, and ROIV-m-Delete ROIVapdus
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

```
noSuchObjectInstance ERROR      ::= localValue : 1

ROER-noSuchObjectInstance       ::= ROERapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    error-value         (noSuchObjectInstance),
    parameter           (INCLUDES ObjectInstance) } )

--  This ROERapdu may only be returned in response to the ROIV-m-EventReport-Confirmed, ROIV-m-Get,
--  ROIV-m-Set-Confirmed, ROIV-m-Action-Confirmed, ROIV-m-Create, and ROIV-m-Delete ROIVapdus

noSuchReferenceObject ERROR     ::= localValue : 12

ROER-noSuchReferenceObject      ::= ROERapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    error-value         (noSuchReferenceObject),
    parameter           (INCLUDES ObjectInstance) } )

--  This ROERapdu may only be returned in response to the ROIV-m-Create ROIVapdu

operationCancelled ERROR        ::= localValue : 23

ROER-operationCancelled         ::= ROERapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    error-value         (operationCancelled) } )

--  This ROERapdu may only be returned in response to the ROIV-m-Get ROIVapdu

processingFailure ERROR         ::= localValue : 10

ROER-processingFailure          ::= ROERapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    error-value         (processingFailure),
    parameter           (INCLUDES ProcessingFailure) OPTIONAL } )

--  This ROERapdu may only be returned in response to the ROIV-m-EventReport-Confirmed, ROIV-m-Get,
--  ROIV-m-Set-Confirmed, ROIV-m-Action-Confirmed, ROIV-m-Create, and ROIV-m-Delete ROIVapdus

setListError ERROR              ::= localValue : 8

ROER-setListError               ::= ROERapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    error-value         (setListError),
    parameter           (INCLUDES SetListError) } )

--  This ROERapdu may only be returned in response to the ROIV-m-Set-Confirmed ROIVapdu

syncNotSupported ERROR          ::= localValue : 3

ROER-syncNotSupported           ::= ROERapdu (WITH COMPONENTS {
    invokeID            PRESENT,
    error-value         (syncNotSupported),
    parameter           (INCLUDES CMISSync) } )

--  This ROERapdu may only be returned in response to the ROIV-m-Get, ROIV-m-Set-Confirmed,
--  ROIV-m-Action-Confirmed and ROIV-m-Delete ROIVapdus

--  To complete the abstract syntax specification provided in this annex, the definitions of the supporting types in 7.4
--  are incorporated by reference

END -- of CMIP syntax definitions
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

Annex C

Examples of CMISE ROSE APDUs

(This annex does not form an integral part of this Recommendation | International Standard)

This annex provides some examples of the complete expansion of ROSE APDUs carrying CMIP information.

These examples are provided as guidance for users of this Recommendation | International Standard.

-- ROIVapdu for the CMISE confirmed action operation.

```
ROIVapdu-example          ::= [1] IMPLICIT SEQUENCE {
    invokeID              InvokeIDType,
    operation-value       INTEGER {m-Action-Confirmed (7)},
    argument              SEQUENCE {
        COMPONENTS OF         BaseManagedObjectId,
            accessControl     [5] AccessControl OPTIONAL,
            synchronization   [6] IMPLICIT CMISSync OPTIONAL,
            scope             [7] Scope DEFAULT baseObject,
            filter            CMISFilter DEFAULT and {},
    actionInfo            [12] IMPLICIT SEQUENCE {
    actionType            ActionTypeId,
    actionInfoArg         [4] ANY DEFINED BY actionType OPTIONAL
    } } }
```

-- RORSapdu for the CMISE confirmed action operation.

```
RORSapdu-example      ::= [2] IMPLICIT SEQUENCE {
    invokeID              InvokeIDType,
    SEQUENCE {
        operation-value       INTEGER {m-Action-Confirmed (7)},
        result                SEQUENCE {
            managedObjectClass      ObjectClass OPTIONAL,
            managedObjectInstance   ObjectInstance OPTIONAL,
            currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
            actionReply             [6] IMPLICIT SEQUENCE {
            actionType              ActionTypeId,
            actionReplyInfo         [4] ANY DEFINED BY actionType } OPTIONAL
    } } }
```

-- ROIVapdu for the CMISE Linked Reply for a confirmed action operation.

```
ROIVapdu-linked-example       ::= [1] IMPLICIT SEQUENCE {
    invokeID                      InvokeIDType,
    linked-ID                     [0] IMPLICIT InvokeIDType,
    operation-value               INTEGER {m-Action-Confirmed (7)},
    argument                      CHOICE {
        actionResult                  [4] IMPLICIT ActionResult,
        processingFailure             [5] IMPLICIT ProcessingFailure,
        actionError                   [7] IMPLICIT ActionError
    } }
```

-- ROERapdu for the CMISE confirmed action operation when a noSuchAction error occurs.

```
ROERapdu-example      ::= [3] IMPLICIT SEQUENCE {
    invokeID              InvokeIDType,
    error-value           INTEGER {noSuchAction (9)},
    parameter             SEQUENCE { managedObjectClass     ObjectClass OPTIONAL,
                                     actionId               ActionTypeId
    } }
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS Not for Resale

Annex D

Directory abstract syntax

(This annex does not form an integral part of this Recommendation | International Standard)

This Recommendation | International Standard imports specifications from the first edition of the Directory. This annex provides an extract from CCITT Rec. X.501 (1988) | ISO/IEC 9594-2:1990, so that a copy of the required abstract syntax is maintained in a current publication.

The directory standard has extensibility rules (specified in ITU-T Rec. X.519 (1993) | ISO/IEC 9594-5:1995), stating that if a 1990 directory system encounters extended syntax, it should ignore what is not understood. This could have implications for name bindings for OSI managed objects involving directory entries as a naming parent, since the directory relative distinguished name components might use the extended syntax. In such a case, the optional components of the extended DistinguishedName syntax will have to be removed before forming the OSI management distinguished name for the managed object that has such a Directory entry as naming parent.

The following productions, used for DistinguishedName syntx imported by CMIP and other standards, are reproduced in this annex from the ASN.1 module,

InformationFramework {joint-iso-ccitt ds(5) modules(1) informationFramework(1)},

originally published in CCITT Rec. X.501 (1988) | ISO/IEC 9594-2:1990.

```
AttributeType ::= OBJECT IDENTIFIER

AttributeValue ::= ANY

AttributeValueAssertion ::= SEQUENCE {
    type        AttributeType,
    assertion   AttributeValue}

Name ::= CHOICE { rdnSequence   RDNSequence }

RDNSequence   ::= SEQUENCE OF RelativeDistinguishedName

DistinguishedName ::= RDNSequence

RelativeDistinguishedName ::= SET OF AttributeValueAssertion
```


Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS
Not for Resale

© ISO/IEC

ICS 35.100.70

Price based on 35 pages

Copyright International Organization for Standardization
Provided by IHS under license with ISO
No reproduction or networking permitted without license from IHS

Not for Resale