

ANSI C78.391-1997 (R2002)

American National Standard

Characteristics of Miniature Lamps of T1 and T1-3/4 Shapes

Secretariat:

National Electrical Manufacturers Association

Approved as an

American National Standards Institute, Inc.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

The National Electrical Manufacturers Association (NEMA) standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process and establishes rules to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, express or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety–related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

STD.NEMA C78.391-ENGL 1997 ■ 6470247 0512978 456 ■

AMERICAN NATIONAL STANDARD

American National Standard

ANSI C78.391-1997

AMERICAN NATIONAL STANDARD

FOR ELECTRIC LAMPS—

CHARACTERISTICS OF MINIATURE LAMPS OF T1 AND T1-3/4 SHAPES

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION
1300 NORTH 17TH STREET, SUITE 1847, ROSSLYN, VA 22209
(703) 841-3200 FAX: (703) 841-3300

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

STD.NEMA C78.391-ENGL 1997 ■ 6470247 0512979 392 ■

American National Standard

Approved July 11, 1997 Secretariat: National Electrical Manufacturers Association

for electric lamps:

Characteristics of Miniature Lamps of T1 and T1-3/4 Shapes

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. It is intended as a guide to aid the manufacturer, the consumer, and the general public. The existence of an American National Standard does not in any respect preclude anyone, whether he has approved the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards. Users are cautioned to obtain the latest editions.
The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute.
CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Copyright © 1997 by National Electrical Manufacturers Association
1300 North 17th Street, Suite 1847, Rosslyn, VA 22209

First Edition
May 1997

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

ANSI C78.391-1997

American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer. An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution. The existence of an American National Standard does not in any respect preclude anyone, whether he has approved the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards. It is intended as a guide to aid the manufacturer, the consumer, and the general public.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on this title page.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published by

National Electrical Manufacturers Association

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America

Copyright © 1997 by National Electrical Manufacturers Association
1300 North 17th Street, Suite 1847, Rosslyn, VA 22209

First Edition
May 1997

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

CONTENTS

Page

1 Scope 1

2 Reference Standards and Related Publications 1

3 Definitions 1

4 Lamp Designations 1

5 Bulb Designations 1

6 Bulb Finish 1

7 Base Specifications 2

8 Electrical, Photometric and Life Characteristics 2

9 Physical Electrical Photometric Requirements 4

Copyright © 1997 by National Electrical Manufacturers Association
1300 North 17th Street, Suite 1847, Rosslyn, VA 22209

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Foreword (This Foreword is not part of ANSI C78.391-1997.)

Suggestions for improvement of this standard should be submitted to the Secretariat C78, National Electrical Manufacturers Association, 1300 North 17th Street, Suite 1847, Rosslyn, VA 22209.

This standard was processed and approved by Accredited Standards Committee on Electric Lamps, C78, and its Sub-Committee, C78-7 for Miniature and Sealed Beam Lamps. Committee approval of the standard does not necessarily imply that all committee members voted for that approval. At the time it approved this standard, the C78 Committee had the following members:

Al Rousseau, Chairman, C78
Thomas C. Knopp, Technical Coordinator
Randolph N. Roy, Secretariat

Organization Represented:	*Name of Representative:*
Advance Transformer Company	Norman Grimshaw
Duro-Test Corporation	Larry Sheinberg
Edison Electric Institute	William Maguire (Delegate)
GE Lighting	Cynthia Minshall
Illuminating Engineering Society	Rita M. Harrold
ITS, Inc.	Craig Davenport
National Electrical Manufacturers Association	(vacant) (Delegate)
OSRAM SYLVANIA INC.	Peter Bleasby
Philips Lighting Company	Al Rousseau
Underwriters Laboratories, Inc.	David Belt

At the time it approved this standard, the C78-7 Sub-Committee had the following members:

Tom Knopp, Chairman, C78-7

Organization Represented:	*Name of Representative:*
GE Lighting	Bernard Rachel
Micro Lamps, Inc.	Thomas C. Knopp
OSRAM SYLVANIA INC.	Daniel Devir
	Roman Milokovsky
	David H. Fox
Philips Lighting Company	Al Rousseau

Copyright © 1997 by National Electrical Manufacturers Association
1300 North 17th Street, Suite 1847, Rosslyn, VA 22209
First Edition
May 1997

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

for electric lamps—

CHARACTERISTICS OF MINIATURE LAMPS OF T1 AND T1-314 SHAPES

1 Scope

This standard sets forth the physical and electrical characteristics of those groups of miniature incandescent lamps with T1 and T1-3/4 bulb shapes. Lamps with various base or termination configurations are included.

2 Reference standards and related publications

2.1 Normative references

When the following American National Standards, referred to in this standard, are superseded by a revision approved by the American National Standards Institute, Inc., the revision shall apply.

ANSI C79.1-1994, *Nomenclature for Glass Bulbs Intended for use with Electric Lamps.*

ANSI C81.61-1990 (1996), *Specifications for Electric Lamp Bases.*

ANSI C81.63-1991 (1996) , *Gauges for Electric Lamp Bases and Lamp Holders.*

ANSI C78.390-1992, *Miniature and Sealed beam Incandescent Lamps-Method of Designation.*

2.2 Related publications

Special Report, SR 25d-1996, *ANS Assigned Miniature Lamp Codes.*

3 Definitions

Application: the type of service or use for which the lamp was originally intended.

4 Lamp designations

Lamp number designations are assigned to miniature lamps in accordance with ANSI C78.390. Assignment of lamp numbers is performed by the Administrator of the designation program.

5 Bulb designations

Bulb designations are defined in ANSI C79.1. Customary units have long been utilized for lamps of this kind, so their use is continued in this standard.

6 Bulb finish

Unless otherwise indicated, the bulbs of all lamp types shown in tables in clause 9 shall have a clear finish.

Copyright © 1997 by National Electrical Manufacturers Association
1300 North 17th Street, Suite 1847, Rosslyn, VA 22209

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

7 Base specifications

7.1 Bases on finished lamps shall comply with the standards sheets included in ANSI C81.61. Standard sheets for the gauges for checking bases are included in ANSI C81.63.

7.2 Wire terminal type lamp bases are not standardized. They normally consist of lead wires extending from the lamp bulb pinch to be used for an external connection.

8 Electrical, photometric and life characteristics

8.1 The value of lamp voltage, current and candela shown in the tables are those rated or nominal values that apply at the initial photometry point after the lamps have been aged.

8.2 Lamps shall be measured at rated voltage ± .1 volts. Lamps shall be operated on an AC or DC voltage equal to their rated voltage. For life testing, the voltage shall be maintained within ± .1 volts.

8.3 Lamp current

Not more than 20% of the test lamps shall deviate from the current specified for the relevant lamp in Tables 9.1 through 9.5 by more than an allowance of 10%.

8.4 Initial candelas

Not more than 20% of the test lamps with clear finish shall deviate from the candlepower value specified for the relevant lamp in Tables 9.1 through 9.5 by more than an allowance of 25%.

8.5 Life

Test lamps shall yield an average life to burn-out of not less than that specified for the relevant lamp in Tables 9.1 through 9.5 as modified below to take account of the statistical effect of sample size.

Sample size	Allowable variation from specified life (%)
10–19	8
20–39	7
40–99	6
100 & above	5

8.5.1 Estimated performance characteristics at other than design voltage may be obtained by use of the following formulas. Note: This is only an approximation and the accuracy diminishes as V and V_1 become more widely separated (usually no more than 50% is acceptable).

8.5.1.1 Current consumption of a lamp is approximately proportional to the 0.55 power of the voltage ratio.

$$\text{Voltage Ratio} = \left(\frac{V}{V_1}\right)^{0.55}$$

Where:

V = Application Voltage
V_1 = Rated Voltage

Copyright © 1997 by National Electrical Manufacturers Association
1300 North 17th Street, Suite 1847, Rosslyn, VA 22209

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

This voltage ratio factor when multiplied by the rated current in amps approximates the new current at the application voltage.

8.5.1.2 Candela (MSCD) of a lamp is approximately proportional to the 3.5 power of the voltage ratio.

$$\text{Voltage Ratio} = \left(\frac{V}{V_1}\right)^{3.5}$$

Where:

V = Application Voltage
V_1 = Rated Voltage

This voltage ratio factor when multiplied by the rated candela (MSCD) approximates the new candelas at the application voltage.

8.5.1.3 Life of a lamp is approximately proportional to the 12th power of the inverse voltage ratio.

$$\text{Voltage Ratio} = \left(\frac{V_1}{V}\right)^{12}$$

Where:

V = Application Voltage
V_1 = Rated Voltage

This voltage ratio factor when multiplied by the rated life hours approximates the new life at the application voltage.

8.5.2 Accelerated life tests

Since many of the lamps in this standard have extremely long life, accelerated life testing (testing at higher than rated voltage) may be used to approximate the actual life at rated voltage.

For reasonably accurate results the accelerated voltage should not exceed more than 50% of the rated voltage.

The following formula may be used:

$$\left[\begin{array}{c}\text{Average life at}\\ \text{accelerated voltage}\end{array}\right] \times \left(\frac{V_1}{V}\right)^{12} = \left[\begin{array}{c}\text{Approximate average}\\ \text{life at rated voltage}\end{array}\right]$$

Where:

V = Application Voltage
V_1 = Rated Voltage

Copyright © 1997 by National Electrical Manufacturers Association
1300 North 17th Street, Suite 1847, Rosslyn, VA 22209

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

9 Physical electrical photometric requirements

9.1 T-1 bulb, SX4 base, 4.8mm LCL[1], 9.65mm MOL[2]

Lamp Number	Rated Voltage	Nom. Amperes	MSCD [3]	Life hours	Principal Applications
8022	5.0	0.021	0.03	10000	P.C. Boards
682	5.0	0.06	0.03	60000	Aircraft
685	5.0	0.06	0.05	25000	Aircraft
714	5.0	0.075	0.09	25000	Aircraft
718	5.0	0.115	0.15	40000	Aircraft
7240	10.0	0.027	0.10	10000	Indicator
7241	18.0	0.026	0.15	10000	Indicator
6839	28.0	0.024	0.15	4000	Indicator

9.2 T1 bulb, G1.3 bipin base, 7.1 mm LCL[1], 9.6mm MOL[2]

Lamp Number	Rated Voltage	Nom. Amperes	MSCD[3]	Life hours	Principal Applications
7683	5.0	0.06	0.05	25000	P.C. Boards
7714	5.0	0.075	0.09	25000	P.C. Boards
7715	5.0	0.115	0.15	40000	P.C. Boards
8099	18.0	0.02	0.15	10000	P.C. Boards
7839	28.0	0.024	0.15	4000	P.C. Boards

9.3 T1 bulb, wire terminals, 6.35mm MOL[2]

Lamp Number	Rated voltage	Nom. Amperes	MSCD [3]	Life hours	Principal Applications
6022	5.0	0.021	0.034	10000	Indicator
680	5.0	0.06	0.03	60000	Aircraft
683	5.0	0.06	0.05	25000	Aircraft
6834	5.0	0.06	0.05	25000	Indicator
713	5.0	0.075	0.09	25000	Aircraft
715	5.0	0.115	0.15	40000	Aircraft
7219	12.0	0.06	0.15	10000	Indicator
7220	18.0	0.026	0.15	16000	Indicator
6838	28.0	0.024	0.15	4000	Indicator

Copyright © 1997 by National Electrical Manufacturers Association
1300 North 17th Street, Suite 1847, Rosslyn, VA 22209
First Edition
May 1997

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

9.4 T-1 3/4 bulb, SX6 midget flange base, 9.65mm LCL[1], 15.88mm MOL[2]

Lamp Number	Rated Voltage	Nom. Amperes	MSCD[3]	Life hours	Principal Applications
331	1.35	0.06	0.01	500	Indicator
368	2.5	0.20	0.22	500	Indicator
338	2.7	0.06	0.04	500	Indicator
375	3.0	0.015	*	10000	Indicator
3150	5.0	0.06	0.15	5000	Indicator
7332	5.0	0.06	0.03	60000	Indicator
7333	5.0	0.06	0.05	25000	Indicator
7335	5.0	0.115	0.15	40000	Indicator
345	6.0	0.04	0.03	10000	Indicator
328	6.0	0.20	0.34@05.0V	1000	Aircraft
328R	6.0	0.20	**	1000	Aircraft
380	6.3	0.04	0.03	20000	Indicator
377	6.3	0.075	0.23	1000	Indicator
350	6.3	0.15	0.45	3000	Aircraft
349	6.3	0.20	0.55	5000	Indicator
381	6.3	0.20	0.40	20000	Indicator
344	10.0	0.014	*	50000	Indicator
367	10.0	0.04	0.08	5000	Indicator
394	12.0	0.04	0.04	10000	Indicator
330	14.0	0.08	0.50	750	Aircraft
330R	14.0	0.08	**	750	Aircraft
382	14.0	0.08	0.30	15000	Indicator
8918	14.0	0.10	0.50	10000	Indicator
370	18.0	0.04	0.50	10000	Indicator
459	22.0	0.04	0.30	2000	Indicator
327	28.0	0.04	0.34	1000	Aircraft
327R	28.0	0.04	**	1000	Aircraft
385	28.0	0.04	0.15	10000	Indicator
387	28.0	0.04	0.30	7000	Indicator
387R	28.0	0.04	**	7000	Indicator
376	28.0	0.06	0.34	25000	Indicator
7341	28.0	0.065	0.65	5000	Indicator
269	32.0	0.04	0.30	4000	Automotive

* Below .01 MSCD
**Approximately 1/10 of clear lamp

Copyright © 1997 by National Electrical Manufacturers Association
1300 North 17th Street, Suite 1847, Rosslyn, VA 22209

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

9.5 T-1 3/4 bulb-W2.1 x 4.9d wedge type base-10.16mm LCL[1], 20.32mm MOL[2]

Lamp Number	Rated Voltage	Nom. Amperes	MSCD[3]	Life Hours	Principal Applications
11	2.5	.20	.20	1000	Indicator
75	2.5	.35	Lens End	10000	Instrument
56	5.0	.115	.15	20000	Indicator
79	6.0	.20	.60	1000	Indicator
84	6.3	.04	.03	20000	Indicator
86*	6.3	.20	.40	20000	Indicator
18	14.0	.04	.04	5000	Indicator
73*	14.0	.08	.08	15000	Indicator
37*	14.0	.09	.09	1500	Auto
74	14.0	.10	.10	500	Auto
70	14.0	.15	.15	100	Auto
85*	28.0	.04	.04	7000	Indicator
17	28.0	.065	.065	5000	Indicator

*Suffix "E" after P/N denotes lamp is provided with leads extended for use as a wire terminal lamp.

Notes:

1 The values of Light Center Length (LCL) shown in the tables are nominal values.
2 The values shown in the tables for MOL are maximum overall length values.
3 MSCD = Mean Spherical Candela.

Copyright © 1997 by National Electrical Manufacturers Association
1300 North 17th Street, Suite 1847, Rosslyn, VA 22209

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale