ANSI C81.61 90 ■ 0724150 0005964 T ■

American National Standard

for Electrical Lamp Bases

ANSI C81.61-1990

ANSI American National Standards Institute
1430 Broadway
New York , New York
10018

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

ANSI C81.61 90 ■ 0724150 0005965 1 ■

ANSI ®
C81.61-1990

partial revision and consolidation of
ANSI C81.10-1976,
C81.20-1976, C81.30-1976, C81.40-1976,
and C81.50-1976

American National Standard

for Electrical Lamp Bases

Secretariat
National Electrical Manufacturers Association

Approved October 27, 1989
American National Standards Institute, Inc

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published by

American National Standards Institute
1430 Broadway, New York, New York 10018

Copyright © 1990 by American National Standards Institute, Inc
All rights reserved.

No part of this publication may be reproduced in any form,
in an electronic retrieval system or otherwise, without
the prior written permission of the publisher.

Printed in the United States of America

BB5C690/80

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Foreword

(This Foreword is not part of American National Standard C81.61-1990.)

ANSI C81.61-1990 is a new presentation of the standard sheets of electric lamp bases. This standard does not contain any sheets for lampholders or gauges.

This arrangement is a major departure from the previous standards in the C81 series. A primary feature of this new format is that all the new base sheets are concentrated in one standard. Secondly, the general format of the sheets has been revised to offer better associations among related bases, lampholders, and gauges. Also, test requirements are now located on the product sheets (base sheet or holder sheet) to which they apply, as opposed to being located on the gauge sheets.

A standard in the old series of standards (ANSI C81.10, ANSI C81.20, and so on) contained the standard sheets for a certain category of bases along with their associated holders and gauges. Under the new approach, base sheets are in ANSI C81.61-1990, holders in another standard (ANSI C81.62, pending), and gauges in a third standard (ANSI C81.63, pending). In addition, it is planned that a fourth standard will contain general information. This pattern is similar to the organization of the IEC standards for base and holder systems.

Under this new scheme, ANSI C81.61-1990 does not replace an old standard, such as ANSI C81.10-1976, in its entirety. Therefore, the old standards cannot be withdrawn until all of the new series of standards are issued.

With this issue in the new format, the titles of the data sheets show new names for the bases. These names are generally a combination of an IEC code and a common name. It is assumed that a transition phase, of several years duration, in which both kinds of identification are shown will help familiarize users with the IEC codes. Eventually, it is expected that use of IEC codes will be sufficient. New bases, for which common names never had been assigned, bear only their IEC codes.

Another part of the new format is a new standard sheet numbering system. The sequence numbers in this system basically put sheets in the alphanumeric sequence of the IEC codes. The Appendix contains a cross-reference, relating new sheet numbers to the old.

The new base standard sheets in this document are generally not changed technically from the older versions. However, some work being processed by the C81 subcommittees has been merged into the new standard. Also, some new base types have been added. Since the last issues of the old standards or their supplements, the following standard sheets have undergone technical revisions: 1-10, 1-20, 1-22, 1-23, 1-30, 1-157, 1-159, 1-162, 1-187, 1-356, 1-393, 1-406, 1-420, 1-430, 1-431, 1-493, and 1-700.

Suggestions for improvement of this standard will be welcome. They shall be sent to the National Electrical Manufacturers Association, 2101 L Street, NW, Suite 300, Washington, DC 20037.

This standard was processed and approved for submittal by Accredited Standards Committee on Electrical Lamp Bases and Holders, C81. Committee approval of the standard does not necessarily imply that all committee members voted for its approval. At the time it approved this standard, the C81 Committee had the following members:

(Vacant), Chairman
Charles Chase, Vice-Chairman

Organization Represented	*Name of Representative*
Challenger Circle F, Inc	D.H. Turner
Duro-Test Corporation	Don Northrop
General Electric Corporation	Wallace H. Henshaw, Jr
	Ted A. Pickett
GTE Products Corporation	Robert Scoledge
Leviton Manufacturing Company, Inc	Charles Chase
Osram Corporation	Russell D. Liddle, Jr
Philips Lighting Company	Alfred C. Rousseau

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Contents

Code	Common Name	Standard Sheet Number
BA9	Miniature Bayonet Base	1-10-1
BA15s, BA15d	Candelabra Single-Contact and Double-Contact-Bayonet Bases	1-20-1
BAY15s, BAY15d	—	1-22-1
BAZ15d	—	1-23-1
BY22d	—	1-30-1
E5	Midget Screw Base	1-100-1
E10	Miniature Screw Base	1-111-1
E11	Mini-Can Screw Base	1-123-1
E12	Candelabra Screw Base	1-131-1
E17	Intermediate Screw Base	1-144-1
E26/24	Single-Contact Medium Screw Base	1-157-1
E26d	Double-Contact Medium Screw Base	1-158-1
E26/50 × 39	Skirted Medium Screw Base	1-159-1
E26/53 × 39	Special Skirted Medium Screw Base	1-162-1
E39	Mogul Screw Base	1-185-1
E39d	Double-Contact Mogul Screw Base	1-187-1
EP39	Position-Oriented Mogul Screw Base	1-202-1
Fa8	Single-Pin Base	1-250-1
G1.3–2.4	Subminiature Bipin Base (T3/4)	1-288-1
G1.3–3.2	Subminiature Bipin Base (T1)	1-291-1
G2.5	Subminiature Bipin Base (T1-1/4)	1-294-1
G3.2	Subminiature Bipin Base (T1-3/4)	1-297-1
G3.9	—	1-300-1
G5	Miniature Bipin Base	1-310-1
G5.3	—	1-320-1
GX5.3	—	1-321-1
GY5.3	—	1-322-1
G6.35/GY6.35	—	1-340-1
GZ6.35	—	1-342-X *
G7.9/GX7.9	—	1-356-1
G9.5	—	1-368-1
GY9.5/GZ9.5	—	1-369-1
G10q	Four-Pin Circular Fluorescent Lamp Base	1-383-1
2G11	—	1-393-1
G13	Medium Bipin Base	1-406-1
2G13	U-Shaped Fluorescent Base	1-420-1
GX16d	Mogul and Extended Mogul End-Prong Bases	1-430-1
GX16d	Termination	1-431-1
G17t	Tri-Pin Prefocus Base	1-439-1
G17q/GX17q	Four-Pin Prefocus Base	1-440-1
G20	Mogul-Bipin Base	1-452-1
G22	Medium Bipost Base	1-466-1
G23	—	1-475-1
GX23	—	1-476-1
G24d, G24q	—	1-493-1
G32/GX32	—	1-506-X *
G38	Mogul Bipost Base	1-519-1

*No standard sheet has been issued for this item. The sheet number is held in reserve.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Code	Common Name	Standard Sheet Number
P13.5s	Single-Contact Miniature Flanged Base	1-600-1
P28	Medium Prefocus Base	1-700-1
P30	Candelabra Prefocus Base	1-709-1
P40	Mogul Prefocus Base	1-715-1
R7s	Recessed Single-Contact Base	1-770-1
R12.5	—	1-774-X *
R17d	Recessed Double-Contact Base	1-777-1
SX4	Submidget Flanged Base	1-850-1
S5.7	Midget Grooved Base	1-856-1
SX6	Midget Flanged Base	1-862-1
T7.2-1	Telephone Slide Base No. 1	1-875-1
T7.2-2	Telephone Slide Base No. 2	1-876-1
T7.2-3	Telephone Slide Base No. 3	1-877-1
T7.2-5	Telephone Slide Base No. 5	1-878-1
T7.2-6	Telephone Slide Base No. 6	1-879-1
T7.2-7	Telephone Slide Base No. 7	1-880-1
T7.2-8	Telephone Slide Base No. 8	1-881-1

*No standard sheet has been issued for this item. The sheet number is held in reserve.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS


Not for Resale

BA9 Miniature Bayonet Base

ANSI C81.61-1990
Std Sheet 1-10-1

The designation assigned to this base by the International Electrotechnical Commission (IEC) is BA9. This standard sheet is equivalent to IEC Publication 61.

The drawing is intended only to indicate the dimensions to be controlled.



	Standard Dimensions (millimeters)				Nearest Equivalent (inch)			
	Unmounted (Note 7)		Finished Lamp		Unmounted (Note 7)		Finished Lamp	
Reference	Min	Max	Min	Max	Min	Max	Min	Max
A (Note 1)	9.08	9.20	9.08	9.25	0.357	0.362	0.357	0.364
B	9.75	10.11	9.75	10.16	0.384	0.398	0.384	0.400
C	1.50	–	–	–	0.059	–	–	–
D	4.30	5.20	–	–	0.169	0.205	–	–
D_1	–	–	4.30	5.90	–	–	0.169	0.232
E (Note 2)	1.50	1.70	1.50	1.70	0.059	0.067	0.059	0.067
F	0.64	–	0.64	–	0.025	–	0.025	–
H	3.50	4.00	3.50	4.00	0.138	0.157	0.138	0.157
M (Note 3)	12.90	13.30	–	–	0.508	0.524	–	–
N (Note 4)	4.50	–	4.50	–	0.177	–	0.177	–
P	–	10.95	–	11.00	–	0.431	–	0.433
U (Note 5)	–	–	–	10.41	–	–	–	0.410
r (Note 6)	–	–	–	–	–	–	–	–

NOTES:

(1) Bases may be made with a flare, with the diameter not to be more than 0.50 mm (0.20 inch) greater than dimension A max.

(2) On a finished lamp, the maximum pin diameter is checked in conjunction with the allowance for misalignment of pins. The "go" gauge shown on Standard Sheet X-X-X (under consideration) is used.

(3) Dimension M lists the OAL limits of the BA9/13 base. For the BA9/14 base, the limits are 13.75 mm–14.25 mm (0.541 inch–0.561 inch).

(4) Dimension N denotes the minimum length of shell that shall conform to the limits of dimension A.

(5) Dimension U includes allowance for side-solder. It is measured from opposite the barrel or the flare, if present.

(6) Rounded edge recommended to aid insertion.

(7) These dimensions are solely for base design and are not to be gauged on the finished lamp.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Gauging
The base of the lamp shall enter Gauge 3-10 until the pins have passed through the two slots q. When the pins are in close contact with surface s, the contact(s) shall be between surface x and surface z.

The base on the lamp shall not enter Gauge 3-11.

See ANSI C81.63 for gauges.

Lampholder
See ANSI C81.62, Standard Sheet 2-10.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale


BA15s, BA15d Candelabra Single-Contact and Double-Contact Bayonet Bases

The designations assigned to variations of these bases by the International Electrotechnical Commission (IEC) are BA15s and BA15d. This standard sheet is equivalent to IEC Publication 61.

The drawing is intended only to indicate the dimensions to be controlled.



SINGLE CONTACT
BAY15s



DOUBLE CONTACT
BAY15d

OPTIONAL CONTACT
CONFIGURATION

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

	Standard Dimensions (millimeters)				Nearest Equivalent (inches)			
	Unmounted (Note 8)		Finished Lamp		Unmounted (Note 8)		Finished Lamp	
Reference	Min	Max	Min	Max	Min	Max	Min	Max
A (Note 1)	15.05	15.25	15.05	15.30	0.5925	0.6004	0.5925	0.6025
B	15.65	16.10	15.65	16.15	0.616	0.634	0.616	0.636
C	1.50	–	–	–	0.059	–	–	–
D	6.00	6.60	–	–	0.236	0.260	–	–
D_1 (Note 2)	–	–	6.32	7.50	–	–	0.249	0.295
E (Note 3)	1.80	2.20	1.80	2.20	0.071	0.087	0.071	0.087
F	0.64	–	0.64	–	0.025	–	0.025	–
G	9.00 Nom		–	–	0.354 Nom		–	–
H_1	4.50	5.20	–	–	0.177	0.204	–	–
H_2	4.50	–	–	–	0.177	–	–	–
J_1	3.00	–	–	–	0.118	–	–	–
J_2	1.70	–	–	–	0.067	–	–	–
K_1	7.00	8.00	–	–	0.276	0.315	–	–
K_2	6.50	7.10	–	–	0.256	0.280	–	–
M (Note 4)	18.75	19.25	–	–	0.738	0.758	–	–
N (Note 5)	8.90	–	8.90	–	0.350	–	0.350	–
P	–	16.95	–	17.00	–	0.667	–	0.669
U (Note 6)	–	–	–	16.26	–	–	–	0.640
r (Note 7)	–	–	–	–	–	–	–	–

NOTES:

(1) Bases may be made with a flare, with the diameter not more than 1 mm (0.039 inch) greater than dimension A.

(2) On double circular contact bases, the solder height of the two contacts shall be within 0.50 mm (0.020 inch) of each other.

(3) On a finished lamp, the maximum pin diameter is checked in conjunction with the allowance for misalignment of pins. The "go" gauge shown on Standard Sheet X-X-X (under consideration) is used.

(4) Dimension M lists the OAL limits of the BA15/19 base. For the BA15/17.5 base, the limits are 17.25 mm–17.75 mm (0.679 inch–0.699 inch), and for the BA15/21 base, the limits are 20.75 mm–21.25 mm (0.817 inch–0.837 inch).

(5) Dimension N denotes the minimum length of the shell that shall conform to the limits of dimension A.

(6) Dimension U includes allowance for side-solder. It is measured from opposite the barrel or the flare, if present.

(7) Rounded edge recommended to aid insertion.

(8) These dimensions are for base design only, and are not to be gauged on the finished lamp.

Gauging

The base of the lamp shall enter Gauge 3-20 until the pins have passed through the two slots q. When the pins are in close contact with surface s, the contact(s) shall be between surface x and surface z.

The base on the lamp shall not enter Gauge 3-21.

See ANSI C81.63 for gauges.

Lampholder

See ANSI C81.62, Standard Sheet 2-20.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

BAY15s and BAY15d Bases


ANSI C81.61-1990
Std Sheet 1-22-1

The designations assigned to variations of these bases by the International Electrotechnical Commission (IEC) are BAY15s and BAY15d. This standard sheet is equivalent to IEC Publication 61.

The drawing is intended only to indicate the dimensions to be controlled.



SINGLE CONTACT
BA15s



DOUBLE CONTACT
BA15d

OPTIONAL CONTACT
CONFIGURATION

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

	Standard Dimensions (millimeters)				Nearest Equivalent (inch)			
	Unmounted (Note 8)		Finished Lamp		Unmounted (Note 8)		Finished Lamp	
Reference	Min	Max	Min	Max	Min	Max	Min	Max
A (Note 1)	15.05	15.25	15.05	15.30	0.5925	0.6004	0.5925	0.6025
B	15.65	16.10	15.65	16.15	0.616	0.634	0.616	0.636
C	1.50	–	–	–	0.059	–	–	–
D	6.00	6.60	–	–	0.236	0.260	–	–
D_1 (Note 2)	–	–	6.32	7.50	–	–	0.249	0.295
E (Note 3)	1.80	2.20	1.80	2.20	0.071	0.087	0.071	0.087
F	0.64	–	0.64	–	0.025	–	0.025	–
G	9.00 Nom		–	–	0.354 Nom		–	–
H_1	4.50	5.20	–	–	0.177	0.204	–	–
H_2	4.50	–	–	–	0.177	–	–	–
J_1	3.00	–	–	–	0.118	–	–	–
J_2	1.70	–	–	–	0.067	–	–	–
K_1	7.00	8.00	–	–	0.276	0.315	–	–
K_2	6.50	7.10	–	–	0.256	0.280	–	–
L	3.00	3.40	3.00	3.40	0.118	0.134	0.118	0.134
M (Note 4)	18.75	19.25	–	–	0.738	0.758	–	–
N (Note 5)	8.90	–	8.90	–	0.350	–	0.350	–
P	–	16.95	–	17.00	–	0.667	–	0.669
U (Note 6)	–	–	–	16.26	–	–	–	0.640
r (Note 7)	–	–	–	–	–	–	–	–

NOTES:

(1) Bases may be made with a flare, with the diameter not more than 1 mm (0.039 inch) greater than dimension A.

(2) On double circular contact bases, the solder height of the two contacts shall be within 0.50 mm (0.020 inch) of each other.

(3) On finished lamps, the maximum pin diameter is checked in conjunction with the allowance for misalignment of pins. The "go" gauge shown on Standard Sheet X-X-X (under consideration) is used.

(4) Dimension M lists the OAL limits of the BAY15/19 base. For the BAY15/21 base, the limits are 20.75 mm–21.25 mm (0.817 inch–0.837 inch).

(5) Dimension N denotes the minimum length of the shell that shall conform to the limits of dimension A.

(6) Dimension U includes allowance for side-solder. It is measured from opposite the barrel or the flare, if present.

(7) Rounded edge recommended to aid insertion.

(8) These dimensions are for base design only, and are not to be gauged on the finished lamp.

Gauging

Gauges have not been developed for this base.

Lampholder


A lampholder standard has not been developed for use with this base standard.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

BAZ15d Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is BAZ15d. This standard sheet is equivalent to IEC Publication 61.

The drawing is intended only to indicate the dimensions to be controlled.



Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

	Standard Dimension (millimeters)				Nearest Equivalent (inch)			
	Unmounted (Note 8)		Finished Lamp		Unmounted (Note 8)		Finished Lamp	
Reference	Min	Max	Min	Max	Min	Max	Min	Max
A (Note 1)	15.05	15.25	15.05	15.30	0.5925	0.6004	0.5925	0.6025
B	15.65	16.10	15.65	16.15	0.616	0.634	0.616	0.636
C	1.50	–	–	–	0.059	–	–	–
D	6.00	6.60	–	–	0.236	0.260	–	–
D_1 (Note 2)	–	–	6.32	7.50	–	–	0.249	0.295
E (Note 3)	1.80	2.20	1.80	2.20	0.071	0.087	0.071	0.087
F	0.64	–	0.64	–	0.025	–	0.025	–
G	9.00 Nom		–	–	0.354 Nom		–	–
H	4.50	–	–	–	0.177	–	–	–
J_1	3.00	–	–	–	0.118	–	–	–
J_2	1.70	–	–	–	0.067	–	–	–
K_1	7.00	8.00	–	–	0.276	0.315	–	–
K_2	6.50	7.10	–	–	0.256	0.280	–	–
L	3.00	3.40	3.00	3.40	0.118	0.134	0.118	0.134
M (Note 4)	18.75	19.25	–	–	0.738	0.758	–	–
N (Note 5)	8.90	–	8.90	–	0.350	–	0.350	–
U (Note 6)	–	–	–	16.26	–	–	–	0.640
r (Note 7)	–	–	–	–	–	–	–	–
α (degrees)	90° Nom		90° Nom		90° Nom		90° Nom	
θ (degrees)	150° Nom		150° Nom		150° Nom		150° Nom	

NOTES:

(1) Bases may be made with a flare, with the diameter not more than 1 mm (0.039 inch) greater than dimension A.

(2) On double circular contact bases, the solder height of the two contacts shall be within 0.50 mm (0.020 inch) of each other.

(3) On a finished lamp, the maximum pin diameter is checked in conjunction with the allowance for misalignment of pins. The "go" gauge shown on Standard Sheet X-X-X (under consideration) is used.

(4) Dimension M lists the OAL limits of the BAZ15/19 base. For the BAZ15/21 base, the limits are 20.75 mm–21.25 mm (0.817 inch–0.837 inch).

(5) Dimension N denotes the minimum length of the shell that shall conform to the limits of dimension A.

(6) Dimension U includes allowance for side-solder. It is measured from opposite the barrel or the flare, if present.

(7) Rounded edge recommended to aid insertion.

(8) These dimensions are for base design only, and are not to be gauged on the finished lamp.

Gauging

Gauges have not been developed for this base.

Lampholder


A lampholder standard has not been developed for use with this base standard.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

BY22d Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is BY22d. This standard sheet is equivalent to IEC Publication 61.

The drawing is intended only to indicate the dimensions to be controlled.



Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Reference	Standard Dimensions (inch) Min	Max	Nearest Metric Equivalent (millimeters) Min	Max
A (Note 3)	0.816	0.870	21.5	22.1
C	0.071	–	1.8	–
C_1	–	0.402	–	10.2
D (Note 1)	0.275	0.295	7.0	7.5
D_1 (Note 1)	0.295	0.354	7.5	9.0
E	0.071	0.086	1.8	2.2
F	0.108 approx		2.75 approx	
G (Note 2)	0.394	–	10.0	–
H (Note 2)	0.236 approx		6 approx	
K	0.394 approx (Note 5)		10 approx (Note 5)	
L (Note 3)	–	–	–	–
M (Note 3)	–	–	–	–
N (Note 2)	0.264	–	6.7	–
X	–	0.165	–	4.2

NOTES:

(1) The values shown for dimensions D and D_1 are future objectives. In order to facilitate their adoption, the minimum value of dimension D may be reduced to 0.234 inch (6.0 mm) during the validity of this issue of the standard sheet. As a consequence, the minimum value of dimension D_1 need not be complied with during the same period. Work on a new issue of the standard sheet is in progress.

(2) Dimension N denotes the minimum length to which dimension A shall conform.

(3) These dimensions are under consideration.

(4) Base may be made with a flare the diameter of which shall be not more than 0.039 inch (1 mm) (see Note 5) greater than L maximum.

(5) These dimensions are solely for base design and are not to be gauged on finished lamps.

Gauging

Gauges have not been developed for this base.

Lampholder


See ANSI C81.62, Standard Sheet 2-30.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

E5 Midget Screw Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is E5. This standard sheet is nearly equivalent to IEC Publication 61.

The drawing is intended only to indicate the dimensions to be controlled.



	Standard Dimensions (inch)				Metric Equivalents of Standard Dimensions (millimeters)			
	Unmounted (Note 5)		On Finished Lamps		Unmounted (Note 5)		On Finished Lamps	
Reference	Min	Max	Min	Max	Min	Max	Min	Max
C	0.031	–	0.031	–	0.79	–	0.79	–
H	0.100	0.120	0.100	0.120	2.54	3.05	2.54	3.05
J	–	0.175	–	0.175	–	4.44	–	4.44
T	0.213	–	–	–	5.41	–	–	–
T_1	–	–	0.213	–	–	–	5.41	–
OAL (Notes 3, 4, and 5)	0.310	0.340	–	–	7.87	8.64	–	–
d	0.206	0.210	0.206	0.210	5.23	5.33	5.23	5.33
d_1	–	0.188	–	0.188	–	4.77	–	4.77
M (Note 5)	–	0.228	–	–	–	5.79	–	–
N (Note 5)	0.181	–	–	–	4.60	–	–	–

NOTES:

(1) Minimum inside diameter of unthreaded portion of metal shell.

(2) Spacing over surface of insulator or through air shall not be less than 0.031 inch (0.79 mm).

(3) Bases used on lamps for series-connected decorative applications must have a reduced overall length so that the total base length, including solder, does not exceed 0.359 inch (9.13 mm).

(4) The IEC limits for overall length of the E5/9 base are 0.331 inch min (8.4 mm) to 0.346 inch max (8.8 mm).

(5) These dimensions are solely for base design and are not to be gauged on the finished lamp.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Form of E5 Midget Screw Threads

Threads per inch	25.4
Pitch of thread, *p*	0.03937 inch (1.00 mm)
Radius of thread, *r*	0.0115 inch (0.293 mm)
Direction of threads	right hand

Gauging

The base on a finished lamp shall enter Gauge 3-100 until the center contact is flush with or projects beyond the gauge surface. From the position where the center contact is flush with the gauge surface, a minimum of two turns shall be required to disengage the thread.

The center contact shall not project beyond the uppermost surface of Gauge 3-101. Only the mass of the gauge itself shall be used.

See ANSI C81.63 for gauges.

Lampholder

See ANSI C81.62, Standard Sheet 2-100.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale


E10 Miniature Screw Base

The dimension assigned to this base by the International Electrotechnical Commission (IEC) is E10/12. This standard sheet is nearly equivalent to IEC Publication 61.

The drawing is intended only to indicate the dimensions to be controlled.



DETAIL OF THREAD



	Standard Dimensions (inch)				Nearest Metric Equivalent (millimeters)			
	Unmounted (Note 2)		On Finished Lamps		Unmounted (Note 2)		On Finished Lamps	
Reference	Min	Max	Min	Max	Min	Max	Min	Max
C	0.055	–	0.055	–	1.40	–	1.40	–
H	0.141	0.172	0.141	0.172	3.58	4.37	3.58	4.37
J	–	0.260	–	0.260	–	6.60	–	6.60
M (Note 2)	–	0.390	–	–	–	9.91	–	–
OAL (Note 2)	0.464	0.504	–	–	11.79	12.80	–	–
T	0.305	–	–	–	7.75	–	–	–
T_1	–	–	0.320	–	–	–	8.13	–
d	0.365	0.375	0.365	0.3765	9.27	9.53	9.27	9.56
d_1	–	0.335	–	0.3365	–	8.51	–	8.55

NOTES:
(1) Spacing over surface of insulator or through air shall not be less than 0.047 inch (1.19 mm).
(2) These dimensions are solely for base design and are not to be gauged on the finished lamp.

Form of E10 Miniature Screw Threads

Threads per inch	14
Pitch of thread, *p*	0.07143 inch (1.814 mm)
Radius of thread, *r*	0.0210 inch (0.533 mm)
Direction of threads	right hand

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Gauging
The center contact shall not project beyond the opposite surface of Gauge 3-111. Only the mass of the gauge itself shall be used.

When the lamp is fully screwed into Gauge 3-112, the center contact shall be in contact with surface x of the gauge and the top edge of the base including solder or any other conductive material shall not protrude above surface z.

See ANSI C81.63 for gauges.

Lampholder
See ANSI C81.62, Standard Sheet 2-111.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale


E11 Mini-Can Screw Base

The designation assigned to this base in accordance with the coding system of the International Electrotechnical Commission (IEC) is E11. At the time of issuance of this standard sheet there was no comparable IEC standard in existence.

The drawing is intended only to indicate the dimensions to be controlled.



DETAIL OF THREAD



Reference	Standard Dimensions (inch) Min	Max	Nearest Metric Equivalent (millimeters) Min	Max
A (Notes 3, 4)	0.575	0.615	14.61	15.62
B	–	0.300	–	7.62
C	–	0.140	–	3.56
E (Note 3)	–	0.161	–	4.09
G (Note 3)	0.053	–	1.35	–
J (Note 1)	0.062	–	1.57	–
L (Note 3)	0.370	0.415	9.40	10.54
W (Notes 3, 5)	0.550	0.590	13.97	14.99
d	0.415	0.425	10.54	10.80
d_1	–	0.385	–	9.78
α (degrees)	43°	47°	–	–

NOTES:

(1) Above this line the diameter of the base is not restricted to the conical section shown.

(2) Spacing over surface of insulator or through air shall not be less than 0.125 inch (3.18 mm).

(3) These dimensions are measured at a diameter of 0.531 inch (13.49 mm).

(4) This dimension includes solder.

(5) This dimension is solely for base design and is not to be gauged on finished lamp. This dimension excludes solder, but includes eyelet.

(6) The upper edge of the metal shell shall not extend into the conical section.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Form of E11 Mini-Can Screw Threads

Threads per inch	14
Pitch of thread, *p*	0.0714 inch
Radius of thread, *r*	0.021 inch (0.533 mm)
Direction of threads	right hand

Gauging

It shall be possible to insert the base of a lamp into Gauge 3-123 until the sloping shoulder seats against the 45-degree shoulder at the entrance of the gauge. Under these conditions, the eyelet solder shall be within the perpendicular distance between surface x and surface y. The bottom of the threaded metal shell shall also be within the perpendicular distance between surface s and surface t. At no time after the lamp is fully inserted shall the metal screw shell be visible in slot z.

The torque required to seat the lamp shall not exceed 4 inch-pounds (0.45 newton-meters). When the lamp is removed from the gauge, at least two full turns shall be needed to disengage the threads.

See ANSI C81.63 for gauge.

Lampholder

See ANSI C81.62, Standard Sheet 2-123.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale


E12 Candelabra Screw Base

The designation assigned to this base, according to the coding system of the International Electrotechnical Commission (IEC), is E12/15. At the time of issuance of this standard, there was no comparable IEC standard in existence.

The drawing is intended only to indicate the dimensions to be controlled.



DETAIL OF THREAD



	Standard Dimensions (inch)				Nearest Metric Equivalent (millimeters)			
	Unmounted (Note 2)		On Finished Lamps		Unmounted (Note 2)		On Finished Lamps	
Reference	Min	Max	Min	Max	Min	Max	Min	Max
C	0.063	–	0.063	–	1.60	–	1.60	–
H	0.141	0.172	0.141	0.172	3.58	4.37	3.58	4.37
J	–	0.290	–	0.290	–	7.37	–	7.37
L (Note 2)	–	0.485	–	–	–	12.32	–	–
OAL (Note 2)	0.574	0.614	–	–	14.58	15.60	–	–
T	0.400	–	–	–	10.16	–	–	–
T_1	–	–	0.420	–	–	–	10.67	–
d	0.455	0.465	0.455	0.468	11.56	11.81	11.56	11.89
d_1	–	0.415	–	0.418	–	10.54	–	10.62

NOTES:
(1) Spacing over surface of insulator or through air shall not be less than 0.079 inch (2 mm).
(2) These dimensions are solely for base design and are not to be gauged on the finished lamp.

Form of E12 Candelabra Screw Threads

Threads per inch	10
Pitch of thread, *p*	0.1000 inch (2.540 mm)
Radius of thread, *r*	0.0312 inch (0.792 mm)
Direction of threads	right hand

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Gauging
When a lamp is fully screwed into Gauge 3-131, the center contact of the base shall be in contact with surface x of the gauge. During removal, at least two full turns shall be necessary to disengage the threads.

The center contact of a base shall not project beyond the opposite surface of Gauge 3-132. Only the mass of the gauge itself shall be used in the test.

A lamp shall fit into Gauge 3-133 until surface w reaches surface v or projects beyond it. When surfaces v and w are coincident, the top of the base, including any solder or other conductive material, shall not extend above surface x.

See ANSI C81.63 for gauges.

Lampholder
See ANSI C81.61, Standard Sheet 2-131.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

E17 Intermediate Screw Base


The designation assigned to this base by the International Electrotechnical Commission (IEC) is E17/20.

The base is nearly equivalent to the E17 base found in IEC Publication 61.

The drawing is intended only to indicate the dimensions to be controlled.



DETAIL OF THREAD



	Standard Dimensions (inch)				Nearest Metric Equivalent (millimeters)			
	Unmounted (Note 2)		On Finished Lamps		Unmounted (Note 2)		On Finished Lamps	
Reference	Min	Max	Min	Max	Min	Max	Min	Max
C	0.093	–	0.093	–	2.36	–	2.36	–
H	0.177	0.197	0.177	0.197	4.50	5.00	4.50	5.00
J	–	0.406	–	0.406	–	10.31	–	10.31
M (Note 2)	–	0.680	–	–	–	17.27	–	–
OAL (Note 2)	0.750	0.780	–	–	19.05	19.81	–	–
T	0.600	–	–	–	15.24	–	–	–
T_1	–	–	0.600	–	–	–	15.24	–
d	0.641	0.651	0.641	0.655	16.28	16.54	16.28	16.64
d_1	–	0.597	–	0.601	–	15.16	–	15.27

NOTES:
(1) Spacing over surface of insulator or through air shall not be less than 0.118 inch (3 mm).
(2) These dimensions are solely for base design and are not to be gauged on the finished lamp.

Form of E17 Intermediate Screw Threads

Threads per inch	9
Pitch of thread, *p*	0.11111 inch (2.822 mm)
Radius of thread, *r*	0.0353 inch (0.897 mm)
Direction of threads	right hand

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Gauging
When a lamp is fully screwed into Gauge 3-144, the center contact of the base shall be in contact with surface x of the gauge. During removal, at least two full turns shall be necessary to disengage the threads.

The center contact of a base shall not project beyond the opposite surface of Gauge 3-145. Only the mass of the gauge itself shall be used in the test.

The shape of the lamp with regard to the fit in the lampholder is assumed to be correct if the lamp can be pushed into Gauge 3-146 until surface w reaches surface v or projects beyond it. When surfaces v and w are coincident, the top of the base, including any solder or other conductive material, shall not extend above surface x.

See ANSI C81.63 for gauges.

Lampholder
See ANSI C81.61, Standard Sheet 2-144.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS


Not for Resale

E26/24 Single-Contact Medium Screw Base


ANSI C81.61-1990
Std Sheet 1-157-1

The designation assigned to this base by the International Electrotechnical Commission (IEC) is E26/24. This standard sheet is nearly equivalent to IEC Publication 61.

The drawing is intended only to indicate the dimensions to be controlled.



DETAIL OF THREAD



RIGHT-HAND THREAD SHOWN

	Standard Dimensions (inches)				Metric Equivalents of Standard Dimensions (millimeters)			
	Unmounted (Note 2)		On Finished Lamps		Unmounted (Note 2)		On Finished Lamps	
Reference	Min	Max	Min	Max	Min	Max	Min	Max
C	0.128	–	0.128	–	3.25	–	3.25	–
H	0.360	0.455	0.360	0.455	9.14	11.56	9.14	11.56
L	0.600	0.670	0.600	0.670	15.24	17.01	15.24	17.01
M (Note 2)	–	1.085	–	–	–	27.56	–	–
OAL (Note 2)	0.917	0.957	–	–	23.29	24.31	–	–
T	0.770	–	–	–	19.56	–	–	–
T_1	–	–	0.770	–	–	–	19.56	–
d	1.029	1.037	1.029	1.041	26.14	26.34	26.14	26.45
d_1	–	0.971	–	0.975	–	24.66	–	24.77

NOTES:
(1) Spacing over surface of insulator or through air shall not be less than 0.118 inch (3 mm).
(2) These dimensions are solely for base design and are not to be gauged on the finished lamp.

Form of E26 Medium Screw Threads

Threads per inch	7
Pitch of thread, *p*	0.14286 inch (3.629 mm)
Radius of thread, *r*	0.0469 inch (1.191 mm)
Direction of threads	right hand or left hand

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Gauging
When a lamp is fully screwed into Gauge 3-156, the center contact of the base shall be in contact with surface x of the gauge. During removal, at least two full turns shall be necessary to disengage the threads.

The center contact of a base shall not project beyond the opposite surface of Gauge 3-158. Only the mass of the gauge itself shall be used in the test.

When a base is fully screwed into Gauge 3-159, the minimum depth (T) shall be attained.

See ANSI C81.63 for gauges.

Lampholder
See ANSI C81.62, Standard Sheet 2-157.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale


E26d Double-Contact Medium Screw Base

ANSI C81.61-1990
Std Sheet 1-158-1


The designation assigned to this base by the International Electrotechnical Commission (IEC) is E26d.


This standard sheet is nearly equivalent to IEC Publication 61.

The drawing is intended only to indicate the dimensions to be controlled.



DETAIL OF THREAD





C, S, T – WITHOUT EYELET SOLDER
C_1, S_1, T_1 – WITH EYELET SOLDER

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

	Standard Dimensions (inches)				Metric Equivalents of Standard Dimensions (millimeters)			
	Unmounted (Note 7)		On Finished Lamps		Unmounted (Note 7)		On Finished Lamps	
Reference	Min	Max	Min	Max	Min	Max	Min	Max
C (Note 5)	0.009	0.105	–	–	0.23	2.67	–	–
C_1 (Note 5)	–	–	0.031	0.125	–	–	0.79	3.17
H	0.172	0.203	0.172	0.203	4.37	5.16	4.37	5.16
J	0.330	0.410	0.330	0.410	8.38	10.41	8.38	10.41
L	0.610	0.760	0.610	0.760	15.49	19.30	15.49	19.30
M (Note 7)	–	1.085	–	–	–	27.56	–	–
OAL	0.917	0.957	–	–	23.29	24.31	–	–
S (Note 6)	0.200	0.305	–	–	5.08	7.75	–	–
S_1 (Note 6)	–	–	0.200	0.325	–	–	5.08	8.25
T	0.759	–	-	–	19.27	–	–	–
T_1	–	–	0.770	–	–	–	19.56	–
d	1.029	1.037	1.029	1.042	26.14	26.34	26.14	26.47
d_1	–	0.971	–	0.976	–	24.66	–	24.79

NOTES:

(1) Spacing over surface of insulator or through air shall not be less than 0.118 inch (3 mm).

(2) Spacing over surface of insulator or through air shall not be less than 0.047 inch (1.19 mm).

(3) The ring contact may be either circular or noncircular, and may be either conical or flat (for purposes of illustration the contact in the drawing has been made circular and conical). Noncircular contacts shall have a maximum OD (outside diameter) at any point not exceeding L max and a minimum OD at any point not less than L min.

(4) The eyelet and ring contacts shall not be of opposite polarity.

(5) The limits shown for these dimensions are applicable at all points between reference diameters of 0.410 inch (10.4 mm) and 0.520 inch (13.2 mm). (See ANSI C81.63, Standard Sheets 3-163 and 3-164.)

(6) These dimensions shall be checked from a measuring circle having a diameter of 0.906 inch (23 mm). These dimensions are required for compliance with IEC Publication 61. They are not part of this American National Standard.

(7) These dimensions are solely for base design and are not to be gauged on the finished lamp.

Form of E26 Medium Screw Threads

Threads per inch	7
Pitch of thread, *p*	0.14286 inch (3.629 mm)
Radius of thread, *r*	0.0469 inch (1.191 mm)
Direction of threads	right hand

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Gauging
When a lamp is fully screwed into Gauge 3-156, the center contact of the base shall be in contact with surface x of the gauge. During removal, at least two full turns shall be necessary to disengage the threads.

The center contact of a base shall not project beyond the opposite end of Gauge 3-158. Only the mass of the gauge itself shall be used in the test.

When an unmounted base is fully screwed into Gauge 3-159, the minimum depth (T) shall be attained. During removal, at least two full turns shall be required to disengage the threads. The base shall be screwed into the gauge with a torque not exceeding 7 in-lbs (0.785 Nm).

When the base of a lamp is pushed into Gauge 3-163 as far as possible, surface w shall not project beyond surface v. For an unmounted base, surface w shall not project beyond surface x.

When the base of a lamp is pushed into Gauge 3-164 as far as possible, surface w shall reach or project beyond surface v.

It shall be possible to insert a lamp into Gauge 3-165 until surface w reaches or projects beyond surface v. When surfaces v and w are coincident, the top of the base, including any solder or other conductive material, shall not extend above surface y.

See ANSI C81.63 for gauges.

Lampholder
See ANSI C81.62, Standard Sheet 2-158.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

E26/50 × 39 Skirted Medium Screw Base

The designation assigned to this base in accordance with the coding system of the International Electrotechnical Commission (IEC) is E26/50 × 39. At the time of issuance of this standard, there was no comparable IEC standard in existence.

The drawing is intended only to indicate the dimensions to be controlled.



Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

	Standard Dimensions (inches)				Metric Equivalents of Standard Dimensions (millimeters)			
	Unmounted (Note 7)		On Finished Lamps		Unmounted (Note 7)		On Finished Lamps	
Reference	Min	Max	Min	Max	Min	Max	Min	Max
A (Note 7)	1.535 Nom		–	–	39.0 Nom		–	–
A_1 (Note 6)	–	1.220	–	1.220	–	31.0	–	31.0
B	1.057	1.097	1.057	1.097	26.85	27.86	26.85	27.86
C	0.125	–	0.125	–	3.18	–	3.18	–
E	0.118	–	0.118	–	3.00	–	3.00	–
F_1 (Note 6)	0.512	0.551	0.512	0.551	13.0	14.0	13.0	14.0
F	0.859	0.890	0.859	0.890	21.82	22.61	21.82	22.61
G (Note 3)	0.394	–	0.394	–	10.00	–	10.00	–
H	0.360	0.455	0.360	0.455	9.14	11.56	9.14	11.56
M	–	1.585	–	–	–	40.26	–	–
N (Notes 1, 3)	1.485	1.515	–	–	37.72	38.48	–	–
OAL	1.922	1.984	–	–	48.82	50.39	–	–
R	0.040 Nom		0.040 Nom		1.0 Nom		1.0 Nom	
T	0.759	–	–	–	19.28	–	–	–
T_1	–	–	0.770	–	–	–	19.56	–
d	1.029	1.042	1.029	1.042	26.14	26.47	26.14	26.47
d_1	–	0.976	–	0.976	–	24.79	–	24.79

NOTES:
(1) Inside diameter.
(2) Variations in the skirt slots, if used, are not covered by this standard.
(3) Minimum length over which dimension A is applicable.
(4) Spacing over surface of insulation or through air shall not be less than 0.118 inch (3.0 mm).
(5) For finished lamps, the spacing over surface of insulator or through air between the insulated skirt and live parts shall not be less than 0.079 inch (2.0 mm). Future objective: 0.118 inch (3.0 mm).
(6) Dimension A_1 and F_1 apply only to the tapered skirt design option, as shown.
(7) Outside dimension.
* These dimensions are solely for base design and are not to be gauged on finished lamps.

Form of E26 Medium Screw Threads

Threads per inch	7
Pitch of thread, *p*	0.14286 inch (3.629 mm)
Radius of thread, *r*	0.0469 inch (1.191 mm)
Direction of threads	right hand

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Gauging
When a lamp is fully screwed into Gauge 3-156, the center of contact of the base shall be in contact with surface x of the gauge. During removal, at least two full turns shall be necessary to disengage the threads.

The center contact of a base shall not project beyond the opposite end of Gauge 3-158. Only the mass of the gauge itself shall be used in the test.

When a mounted base on a finished lamp is fully screwed into Gauge 3-160, the center contact shall be in contact with surface x of the gauge. During removal, at least two full turns shall be necessary to disengage the threads.

It shall be possible to insert a lamp into Gauge 3-166 until surface w reaches surface v or projects beyond it. When surfaces v and w are coincident, the top of the base, including any solder or other conductive material, shall not extend above surface y.

See ANSI C81.63 for gauges.

Related Standard Sheet
Specifications for the E26 Base are shown on ANSI C81.61, Standard Sheet 1-157.

Lampholder
See ANSI C81.62, Standard Sheet 2-157.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

E26/53 × 39 Skirted Medium Screw Base

The designation assigned to this base in accordance with the coding system of the International Electrotechnical Commission (IEC) is E26/53 × 39. At the time of issuance of this standard, there was no comparable IEC standard in existence.

The drawing is intended only to indicate the dimensions to be controlled.



Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

	Standard Dimensions (inches)				Nearest Metric Equivalent (millimeters)			
	Unmounted*		On Finished Lamps		Unmounted*		On Finished Lamps	
Reference	Min	Max	Min	Max	Min	Max	Min	Max
A (Note 1)	1.447	1.453	–	–	36.76	36.90	–	–
A_1 (Note 2)	1.435	1.445	–	–	36.45	36.70	–	–
B	1.057	1.097	1.057	1.097	26.85	27.86	26.85	27.86
C	0.125	–	0.125	–	3.18	–	3.18	–
E	0.118	–	0.118	–	3.00	–	3.00	–
F	0.969	0.999	0.969	0.999	24.61	25.38	24.61	25.38
G	0.125		–		3.18		–	
H	0.360	0.455	0.360	0.455	9.14	11.56	9.14	11.56
J	0.063		–		1.60		–	
K	0.625		–		15.88		–	
L	0.173	0.203	–	–	4.40	5.15	–	–
M	–	1.550	–	–	–	39.37	–	–
OAL	2.031	2.094	–	–	51.59	53.18	–	–
R (radius)	0.080		–		2.03		–	
T	0.759	–	–	–	19.28	–	–	–
T_1	–	–	0.770	–	–	–	19.56	–
d	1.029	1.042	1.029	1.042	26.14	26.47	26.14	26.47
d_1	–	0.976	–	0.976	–	24.79	–	24.79

NOTES:
(1) Inside diameter at dimensions G and J.
(2) Inside diameter at dimensions K and L.
(3) Spacing over surface of insulation or through air shall not be less than 0.118 inch (3.00 mm).
(4) For finished lamps, the spacing between the insulated skirt and live parts in the wireway shall not be less than 0.079 inch (2.00 mm). (Future objective: 0.118 inch [3.00 mm]).
(5) Dimension r, which is derived from the theoretical thread profile, is not to be checked on the base.
* These dimensions are solely for base design and are not to be gauged on finished lamps.

Form of E26 Medium Screw Thread

Threads per inch	7
Pitch of thread, *p*	0.14286 inch (3.629 mm)
Radius of thread, *r*	0.0469 inch (1.191 mm) (Note 5)
Direction of threads	right hand

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Gauging
When the chamfered end of Gauge 3-158 is placed over the base thread of a finished lamp, held base up, the center contact shall not project beyond the opposite gauge surface. Only the weight of the gauge itself shall be used in the test.

When the base on a finished lamp is pushed into Gauge 3-165, surface w shall reach surface v or project beyond it. When surfaces v and w are coincident, the top of the insulation between the metal skirt and the metal shell shall not extend above surface y.

When the base or lamp is fully screwed into Gauge 3-160, the center contact of the base shall be in contact with surface x of the gauge. As the base or lamp is removed from the gauge, at least two full turns shall be required to disengage the threads.

NOTE: Two separate gauges are required; one to accommodate unmounted bases [T], and one to accommodate based lamps [T_1].

See ANSI C81.63 for gauges.

Lampholder
See ANSI C81.62, Standard Sheet 2-157.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

E39 Mogul Screw Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is E39. This standard sheet is nearly equivalent to IEC Publication 61.

The drawing is intended only to indicate the dimensions to be controlled.



	Standard Dimensions (inches)				Nearest Metric Equivalent (millimeters)			
	Unmounted (Note 2)		On Finished Lamps		Unmounted (Note 2)		On Finished Lamps	
Reference	Min	Max	Min	Max	Min	Max	Min	Max
C	0.187	–	0.187	–	4.75	–	4.75	–
H	0.530	0.595	0.530	0.595	13.46	15.11	13.46	15.11
J	–	1.250	–	–	–	31.75	–	–
M (Note 2)	–	1.585	–	–	–	40.26	–	–
OAL (Note 2)	1.595	1.655	–	–	40.51	42.04	–	–
T	1.185	–	–	–	30.10	–	–	–
T_1	–	–	1.190	–	–	–	30.23	–
d	1.542	1.555	1.542	1.555	39.17	39.50	39.17	39.60
d_1	–	1.455	–	1.460	–	36.96	–	37.08

NOTES:
(1) Spacing over surface of insulator or through air shall not be less than 0.200 inch (5.08 mm).
(2) These dimensions are solely for base design and are not to be gauged on the finished lamp.

Form of E39 Mogul Screw Threads

Threads per inch	4
Pitch of thread, *p*	0.25000 inch (6.350 mm)
Radius of thread, *r*	0.0906 inch (2.301 mm)
Direction of threads	right hand

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Gauging
When a lamp is fully screwed into Gauge 3-185, the center contact of the base shall be in contact with surface x of the gauge. During removal, at least two full turns shall be necessary to disengage the threads.

The center contact of a base shall not project beyond the opposite surface of Gauge 3-186. Only the mass of the gauge itself shall be used in the test.

It shall be possible to insert the lamp into Gauge 3-187 until surface w reaches surface v or projects beyond it.

NOTE: Some existing lamp designs employing G-shaped bulbs with short necks may not satisfy this gauge.

When Gauge 3-187 surfaces v and w are coincident, the top of the base, including any solder or other conductive material, shall not extend above surface x.

See ANSI C81.63 for gauges.

Related Standard Sheet
Specifications for the EP39 base are shown on Standard Sheet 1-202.


Lampholder
See ANSI C81.62, Standard Sheet 2-185.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale


E39d Double-Contact Mogul Screw Base

The designation assigned to this base in accordance with the coding system of the International Electrotechnical Commission (IEC) is E39d. At the time of issuance of this standard, there was no comparable IEC standard in existence.

The drawing is intended only to indicate the dimensions to be controlled.



DETAIL OF THREAD



(OPTIONAL)
RING CONTACT CONFIGURATION

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

	Standard Dimensions (inches)				Metric Equivalents of Standard Dimensions (millimeters)			
	Unmounted (Note 1)		On Finished Lamps		Unmounted (Note 1)		On Finished Lamps	
Reference	Min	Max	Min	Max	Min	Max	Min	Max
C	0.109	0.141	–	–	2.77	3.58	–	–
C_1	–	–	0.109	0.196	–	–	2.77	4.98
D	0.172	0.203	–	–	4.37	5.15	–	–
H	0.296	0.328	0.296	0.328	7.52	8.33	7.52	8.33
J	0.460	0.500	–	–	11.68	12.70	–	–
L	0.984	1.016	0.984	1.016	24.99	25.80	24.99	25.80
L_1	0.840	1.016	0.840	1.016	21.33	25.80	21.33	25.80
M	–	1.585	–	–	–	40.26	–	–
OAL	1.633	1.679	–	–	41.48	41.64	–	–
T	1.185	–	–	–	30.10	–	–	–
T_1	–	–	1.190	–	–	–	30.23	–
d (Note 4)	1.537	1.553	1.537	1.558	39.04	39.44	39.04	39.56
d_1 (Note 4)	–	1.453	–	1.458	–	36.90	–	37.02

NOTES:
(1) These dimensions are solely for base design and are not to be gauged on finished lamps.
(2) Spacing over surface of insulation or through air shall not be less than 0.125 inch (3.18 mm). Variations in the contour of the insulator(s) are not covered by this standard.
(3) The eyelet and ring contacts shall not be of the opposite polarity.
(4) The metric equivalents for dimensions d max and d_1 max are rounded downward to achieve better international harmonization.
(5) Dimension r, which is derived from the theoretical thread profile, is not to be checked on the base.

Form of E39 Mogul Screw Threads

Threads per inch	4
Pitch of thread, *p*	0.25000 inch (6.350 mm)
Radius of thread, *r* (Note 5)	0.09060 inch (2.301 mm)
Direction of threads	right hand

Gauging

The shape of the lamp with regard to the fit in the lampholder shall be assumed correct if the lamp can be pushed into Gauge 3-187 until surface w reaches surface v or projects beyond it.

When the lamp is fully screwed into Gauge 3-185, the center contact of the base shall be in contact with surface x of the gauge. When the lamp is removed from the gauge, at least two full turns shall be required to disengage the threads.

When the chamfered end of Gauge 3-186 is placed over the base thread of a finished lamp held base up, the center contact shall not project beyond the opposite gauge surface. Only the weight of the gauge itself shall be used in the test.

See ANSI C81.63 for gauges.

Lampholder


A lampholder standard has not been developed for use with this base standard.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale


EP39 Position-Oriented Mogul Screw Base


The designation assigned to this base in accordance with the system of the International Electrotechnical Commission (IEC) is EP39. At the time of publication there was no comparable IEC standard in existence.

The drawing is intended only to indicate the dimensions to be controlled.



DETAIL OF THREAD





Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

	Standard Dimensions (millimeters)				Nearest Metric Equivalent (inches)			
	Unmounted (Note 3)		On Finished Lamps		Unmounted (Note 3)		On Finished Lamps	
Reference	Min	Max	Min	Max	Min	Max	Min	Max
C	0.187	–	0.187	–	4.75	–	4.75	–
H	0.530	0.595	0.530	0.595	13.46	15.11	13.46	15.11
J	–	1.250	–	–	–	31.75	–	–
K	0.062	0.094	–	–	1.59	2.39	–	–
M (Note 3)	–	1.585	–	–	–	40.26	–	–
OAL (Note 3)	1.595	1.655	–	–	40.51	42.04	–	–
T	1.185	–	–	–	30.10	–	–	–
X (Note 2)	1.000	1.031	–	–	25.40	26.19	–	–
X_1	–	–	1.000	1.047	–	–	25.93	26.59
d	1.542	1.555	1.542	1.560	39.17	39.50	39.17	39.62
d_1	–	1.455	–	1.460	–	36.96	–	37.08
e (dia)	0.090	0.095	–	–	2.36	2.41	–	–

NOTES:
(1) Spacing over surface of insulator or through air shall not be less than 0.200 inch (5.08 mm).
(2) Pin is located on major thread diameter d.
(3) These dimensions are solely for base design and are not to be gauged on finished lamps.

Form of EP39 Mogul Screw Threads

Threads per inch	4
Pitch of thread, *p*	0.25000 inch (6.350 mm)
Radius of thread, *r*	0.0905 inch (2.301 mm)
Direction of threads	right hand

Gauging
The center contact of a base shall not project beyond the opposite surface of Gauge 3-186. Only the mass of the gauge itself shall be used in the test.

When a lamp is fully screwed into Gauge 3-202, the center contact of the base shall be in contact with surface x of the gauge.

It shall be possible to insert the lamp into Gauge 3-203 until surface w reaches surface v or projects beyond it.

When Gauge 3-187 surfaces v and w are coincident, the top of the base, including any solder or other conductive material, shall not extend above surface x.

See ANSI C81.63 for gauges.

Related Standard
Specifications for the E39 base are shown on Standard Sheet 1-185.

Lampholder
See ANSI C81.62, Standard Sheet 2-202.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Fa8 Single-Pin Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is Fa8. This standard sheet is equivalent to IEC Publication 61.

Single-pin bases are generally used on fluorescent lamps with T6, T8, or T12 bulbs.

The drawings are intended only to indicate the dimensions to be controlled.



Reference	Standard Dimensions (inches) Min	Max	Nearest Metric Equivalent (millimeters) Min	Max
A	0.343	–	8.71	–
F_1	–	0.380	–	9.65
S (Note 2)	–	0.750 (T6)	–	19.05 (T6)
	–	1.017 (T8)	–	25.83 (T8)
	–	1.438 (T12)	–	36.52 (T12)
T (Note 3)	–	0.430 (T6)	–	10.92 (T6)
	–	0.555 (T8)	–	14.10 (T8)
	–	0.800 (T12)	–	20.32 (T12)

NOTES:


(1) Represents length of lamp over which dimension T is applicable.

(2) Maximum base shell diameter (S) is shown separately for T6, T8, and T12 bulb lamps.

(3) The T dimension includes allowance for possible offset of the bulb axis with respect to the base axis. This dimension is shown separately for T6, T8, and T12 bulb lamps.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

ANSI C81.61-1990
Std Sheet 1-250-1



DETAIL OF PIN

Reference	Standard Dimensions (inch) Min	Max	Nearest Metric Equivalent (millimeters) Min	Max
E	0.300	0.325	7.62	8.26
F	0.271	0.323	6.88	8.20
F_1	–	0.380	–	9.65
G	–	0.020	–	0.51
H	–	0.380	–	9.65
J	–	0.065	–	1.65
r	0.150	0.1625	3.81	4.13

NOTES:
(4) End of pin may either be hemispherical in shape or have a tip falling within the limits shown.
(5) The base face is that surface of the base that contacts the lampholder.

Gauging

It shall be possible for the pin of a base of a lamp to enter Gauge 3-250 until the base face is in full contact with surface x of the gauge. In this position, the gauge plunger shall reach surface y, but not project beyond surface z.

Attempt to insert the pin of a lamp into Gauge 3-251. It shall not enter far enough to permit the base face to come in contact with surface x of the gauge.

See ANSI C81.63 for gauges.

Lampholder

See ANSI C81.62, Standard Sheet 2-250.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

G1.3–2.4 Subminiature Bipin Base for T3/4 Lamps

The designation assigned to this base in accordance with the system of the International Electrotechnical Commission (IEC) is G1.3–2.4. At the time of issuance of this standard sheet, there was no comparable IEC standard in existence.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.



	Standard Dimensions (inch)			Nearest Metric Equivalent (millimeters)		
Reference	Min	Nom	Max	Min	Nom	Max
B	0.090	–	0.100	2.29	–	2.54
C (Note 1)	0.120	–	0.130	3.05	–	3.30
D	0.045	–	0.055	1.14	–	1.40
E	0.018	–	0.022	0.46	–	0.56
F (Note 2)	–	0.190 approx	0.022	–	4.83 approx	–
N (Note 3)	0.062	–	–	1.57	–	–

NOTES:
(1) Some existing designs have dimensions of 0.095 inch–0.105 inch (2.41 mm–2.67 mm).
(2) Length of pin may vary in accordance with application.
(3) Dimension N denotes the minimum length over which dimension D applies.

Gauging

Gauges have not been developed for this base.

Lampholder

A lampholder has not been developed for use with this base standard.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

G1.3–3.2 Subminiature Bipin Base for T1 Lamps

The designation assigned to this base in accordance with the system of the International Electrotechnical Commission (IEC) is G1.3–3.2. At the time of issuance of this standard sheet, there was no comparable IEC standard in existence.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.



	Standard Dimensions (inch)			Nearest Metric Equivalent (millimeters)		
Reference	Min	Nom	Max	Min	Nom	Max
B	0.120	–	0.130	3.05	–	3.30
C	0.120	–	0.130	3.05	–	3.30
D	0.045	–	0.055	1.14	–	1.40
E	0.018	–	0.022	0.46	–	0.56
F (Note 1)	–	0.250 approx	–	–	6.35 approx	–
N (Note 2)	0.062	–	–	1.57	–	–

NOTES:
(1) Length of pin may vary in accordance with application.
(2) Dimension N denotes the minimum length over which dimension D applies.

Gauging
Gauges have not been developed for this base.

Lampholder
A lampholder standard has not been developed for use with this base standard.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

G2.5 Subminiature Bipin Base for T1 1/4 Lamps

The designation assigned to this base in accordance with the system of the International Electrotechnical Commission (IEC) is G2.5. At the time of issuance of this standard sheet, there was no comparable IEC standard in existence.

The dimensions shown on this sheet apply to finished bases after asssembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.



	Standard Dimensions (inch)			Nearest Metric Equivalent (millimeters)		
Reference	Min	Nom	Max	Min	Nom	Max
B	0.168	–	0.178	4.28	–	4.52
C	0.265	–	0.300	6.73	–	7.62
D (Note 1)	0.095	–	0.105	2.41	–	2.67
E	0.018	–	0.022	0.46	–	0.56
F (Note 2)	–	0.250 approx	–	–	6.35 approx	–
N (Note 3)	0.062	–	–	1.57	–	–

NOTES:
(1) Certain manufacturers are currently using a D dimension of 0.120 inch– 0.130 inch (3.05 mm–3.30 mm). This alternative dimension shall be considered acceptable until such time as it can be phased out and replaced by the recommended D dimension of 0.095 inch– 0.105 inch (2.41 mm–2.67 mm).
(2) Length of pin may vary in accordance with application.
(3) Dimension N denotes the minimum length over which dimension D applies.

Gauging

Gauges have not been developed for this base.

Lampholder

A lampholder standard has not been developed for use with this base standard.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

G3.2 Subminiature Bipin Base for T1 3/4 Lamps

The designation assigned to this base in accordance with the system of the International Electrotechnical Commission (IEC) is G3.2 At the time of issuance of this standard sheet, there was no comparable IEC standard in existence.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimension to be controlled.



	Standard Dimensions (inch)			Nearest Metric Equivalent (millimeters)		
Reference	Min	Nom	Max	Min	Nom	Max
B	0.220	–	0.230	5.59	–	5.84
C	0.295	–	–	7.49	–	–
D (Note 1)	0.120	–	0.130	3.05	–	3.30
E	0.018	–	0.022	0.46	–	0.56
F (Note 2)	–	0.250	–	–	6.35	–
N (Note 3)	0.062	–	–	1.57	–	–

NOTES:
(1) Some existing designs have lead spacing (D) of 0.120 inch (3.05 mm) nominal [0.115 inch (2.92 mm) min, 0.125 inch (3.18 mm) max].
(2) Length of pin may vary in accordance with application.
(3) Dimension N denotes the minimum length over which dimension D applies.

Gauging
Gauges have not been developed for this base.

Lampholder
A lampholder standard has not been developed for use with this base standard.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

G3.9 Base

The designation assigned to this base, in accordance with the system of the International Electrotechnical Commission (IEC), is G3.9. At the time of issuance of this standard sheet, there was no comparable IEC standard in existence.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.



Reference	Standard Dimensions (millimeters)			Nearest Equivalent (inches)		
	Min	Nom	Max	Min	Nom	Max
A (Note 1)	12.50	–	–	0.492	–	–
D	–	3.97	–	–	0.156	–
E (Note 2)	1.54	–	1.60	0.061	–	0.063
F	7.00	–	12.00	0.276	–	0.472

NOTES:
(1) Area reserved for connector.
(2) Slight chamfering or radius is required for lead on end of pins.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Gauging
When the base on a finished lamp is inserted into Gauge 3-300 until it meets with surface x of the gauge, both pin ends shall appear between surface y and surface z. In applying this gauge, the force used shall not exceed 5.0 newtons (1.1 lbf). Each pin of the base shall pass through gauge hole E2, but shall not enter hole E1.

See ANSI C81.63 for gauges.

Lampholder
See ANSI C81.62, Standard Sheet 2-300.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

G5 Miniature Bipin Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is G5. This standard sheet is equivalent to IEC Publication 61.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.



Reference	Standard Dimensions (inch)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A (Note 1)	0.343	–	–	8.71	–	–
D	–	0.187	–	–	4.75	–
E (Notes 2, 3)	0.090	–	0.105	2.29	–	2.67
F (Note 2)	0.260	–	0.300	6.60	–	7.62
G	–	–	0.030	–	–	0.76
H	–	–	0.130	–	–	3.30
J (Note 4)	–	–	0.610	–	–	15.49
L (Notes 5, 6)	0.205	–	–	5.21	–	–
M (Note 7)	0.750	–	–	19.05	–	–
T (Note 8)	–	–	0.340	–	–	8.64
r	0.015	–	–	0.38	–	–

NOTES:

(1) Dimension A is the length over which dimension J applies.

(2) Diameter and length dimensions include solder.

(3) Prior to welding or soldering, the pin diameter shall be 0.093 inch ± 0.003 inch (2.36 mm ± 0.076 mm). This dimension is not to be gauged on the finished lamp.

(4) Maximum base shell diameter shown is for T5 bulb lamps.

(5) This dimension is solely for base design and is not to be gauged on the finished lamp.

(6) Dimension L is the minimum length of the cylindrical portion of the pin.

(7) Represents length of lamp over which dimension T is applicable.

(8) The T dimension includes allowance for possible offset of the bulb axis with respect to the base axis.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Gauging

Finished lamps employing the G5 Base shall satisfy Gauge 3-310. In applying this gauge, the force used shall not exceed 1 lbf (4.45 N).

The pins of the bases on finished lamps shall enter the two gauge holes E5 at surface o. When fully inserted so that the surfaces of base and gauge are in contact, the end of the pins shall reach at least to surface x and shall not project beyond surface y. Each individual base pin shall enter gauge hole E4 at surface o until the face of the base and the surface of the gauge are in contact. The cylindrical portion of each pin shall not be able to enter hole E1.

See ANSI C81.63 for gauges.

Lampholder

See ANSI C81.62, Standard Sheet 2-310.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale


G5.3 Base


ANSI C81.62-1990
Std Sheet 1-320-1

The designation assigned to this base by the International Electrotechnical Commission (IEC) is G5.3. This standard sheet is equivalent to IEC Publication 61.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.





Reference	Standard Dimensions (inch) Min	Nom	Max	Nearest Metric Equivalent (millimeters) Min	Nom	Max
A	0.296	–	0.345	7.52	–	8.76
B	0.713	–	0.745	18.11	–	18.92
C	0.600	–	–	15.24	–	–
D	–	0.210	–	–	5.33	–
E	0.058	–	0.065	1.47	–	1.65
F	0.240	–	0.280	6.10	–	7.11
N	0.030	–	–	0.76	–	–

NOTE: For finished lamps, the electrical spacing between contact pins shall not be less than 0.098 inch (2.5 mm) over the insulator surface or through the air.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Gauging
It shall be possible to insert the base of a finished lamp into Gauge 3-320 until the reference plane of the base meets with surface w of the gauge. In this position both pins shall project beyond surface z of the gauge, but shall not project beyond surface y. The top of the base shall reach at least to surface w.

Each individual pin shall enter hole E_2 of Gauge 3-320 until the reference plane of the base meets surface w of the gauge.

The pins shall not enter hole E_3 of Gauge 3-320.

In applying Gauge 3-320, the force used shall not exceed 1 lbf (4.45 newtons).

See ANSI C81.63 for gauges.

Lampholder
See ANSI C81.62, Standard Sheet 2-320.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS


Not for Resale

GX5.3 Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is GX5.3. This standard sheet is equivalent to IEC Publication 61.

The sheet dimensions shown apply to the base portion of finished lamps.

The drawing is intended only to indicate the dimensions to be controlled.



Reference	Standard Dimensions (inch) Min	Nom	Max	Nearest Metric Equivalent (millimeters) Min	Nom	Max
D	–	0.210	–	–	5.33	–
E Diameter	0.057	–	0.063	1.45	–	1.60
F	0.205	–	0.265	5.21	–	6.73
G	–	–	0.295	–	–	7.49
H (Note 3)	0.355	–	0.415	9.02	–	10.54
J	–	–	0.030	–	–	0.76
K (Note 2)	–	0.394	–	–	10.0	–
L (Note 2)	–	0.984	–	–	25.0	–
P (Note 3)	–	0.030	–	–	0.76	–
R	–	–	0.515	–	–	13.08
S (Note 3)	0.600	–	0.660	15.24	–	16.76
W (Note 4)	–	–	0.050	–	–	1.27
r_2 (Note 5)	–	–	0.015	–	–	0.38
r_4 (Notes 5, 6)	–	–	0.025	–	–	0.64

NOTES:
(1) Slight chamfer or radius required for lead-in on the ends of the pins.
(2) Dimensions K and L show the theoretical demarcation between the space that the lamp may occupy on the one side and the space in which parts of the holder or equipment may be present on the other side.
(3) Dimensions H and S measured at reference plane p, distance P from surface z.
(4) E maximum does not apply within distance W.
(5) Dimensions r_2 and r_4 are toleranced in order to maintain sufficient area for surface z.
(6) For design purposes only, not to be gauged.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Gauging
Individual pins shall enter hole E9 of Gauge 3-321 and the pair of pins shall enter the holes labeled E. Penetration into the holes E and E9 shall be a minimum distance of F3.

As the pins are inserted into the E3–E4 slot of Gauge 3-321, surface z of the lamp shall seat on surface z of the gauge.

When the base is completely seated in the 3-321 gauge, the pin ends shall be coplanar with or project beyond surface x, but not beyond surface y.

Individual pins shall not enter the E10 hole of the 3-323 gauge beyond their rounded ends.

As the pins are inserted from the viewing slot side of Gauge 3-323, the "H Not-go" Gauge, the base shall not completely enter and mate with surface z.

As the pins are inserted from the viewing slot side of Gauge 3-323, the "S Not-Go" Gauge, the base shall not completely enter and mate with surface z.

See ANSI C81.63 for gauges.

Lampholder
See ANSI C81.62, Standard Sheet 2-321.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

GY5.3 Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is GY5.3. This standard sheet is equivalent to IEC Publication 61.

The sheet dimensions shown apply to the base portion of finished lamps.

The drawing is intended only to indicate the dimensions to be controlled.



Reference	Standard Dimensions (inch) Min	Nom	Max	Nearest Metric Equivalent (millimeters) Min	Nom	Max
D	–	0.210	–	–	5.33	–
E_1	0.023	–	0.031	0.58	–	0.79
E_2	0.070	–	0.090	1.78	–	2.29
F	0.205	–	0.265	5.21	–	6.73
G	–	–	0.295	–	–	7.49
H (Note 3)	0.355	–	0.415	9.02	–	10.54
J	–	–	0.030	–	–	0.76
K (Note 2)	–	0.394	–	–	10.0	–
L (Note 2)	–	0.984	–	–	25.0	–
P (Note 3)	–	0.030	–	–	0.76	–
R	–	–	0.515	–	–	13.08
S (Note 3)	0.600	–	0.660	15.24	–	16.76
W (Note 4)	–	–	0.050	–	–	1.27
r_2 (Note 5)	–	–	0.015	–	–	0.38
r_3	0.012	–	–	0.30	–	–
r_4 (Notes 5, 6)	–	–	0.025	–	–	0.64

NOTES:

(1) Slight chamfer or radius required for lead-in on the ends of the pins.

(2) Dimensions K and L show the theoretical demarcation between the space which the lamp may occupy on the one side and the space in which parts of the holder or equipment may be present on the other side.

(3) Dimensions H and S measured at reference plane p, distance P from surface z.

(4) E_1 maximum and E_2 maximum do not apply within distance W.

(5) Dimensions r_2 and r_4 are toleranced in order to maintain sufficient area for surface z.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Gauging
Individual pins shall enter the E1–E2 hole of Gauge 3-322, and the pair of pins shall enter the holes labeled E11–E12. Penetration into the holes E1–E2 and E11–E12 shall be a minimum distance of f3.

As the pins are inserted into the E7–E8 slot of Gauge 3-322, surface z of the lamp shall seat on surface z of the gauge.

When the base is completely seated in Gauge 3-322, the pin ends shall be coplanar with or project beyond surface x, but not beyond surface y.

When the individual flat pins are tested in both the E1–E5 and the E2–E6 holes of Gauge 3-323, a pin shall not enter either hole beyond its rounded end.

As the pins enter from the viewing slot side of Gauge 3-323, the "H Not-go Gauge," the base shall not completely enter and mate with surface z.

As the pins enter from the viewing slot side of Gauge 3-323, the "S Not-go Gauge," the base shall not completely enter and mate with surface z.

See ANSI C81.63 for gauges.

Lampholder
See ANSI C81.62, Standard Sheet 2-322.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS


Not for Resale

G6.35 and GY6.35 Bases

ANSI C81.61-1990
Std Sheet 1-340-1

The designations assigned to these bases by the International Electrotechnical Commission (IEC) are G6.35 and GY6.35, plus a suffix as indicate in the table below. This standard sheet is equivalent to IEC Publication 61.

The drawing is intended only to indicate the dimensions to be controlled.



Standard Dimensions
(inches)

	G6.35-15			G6.35-20			G6.35-25			G6.35-30		
Reference	Min	Nom	Max	Min	Nom	Max	Min	Nom	Max	Min	Nom	Max
A (Note 1)	0.037	–	0.041	0.037	–	0.041	0.037	–	0.041	0.037	–	0.041
B	–	0.250	–	–	0.250	–	–	0.250	–	–	0.250	–
C	0.295	–	–	0.295	–	–	0.295	–	–	0.295	–	–
E (Note 2)	–	–	0.295	–	–	0.295	–	–	0.354	–	–	0.354
L (Note 2)	–	–	0.591	–	–	0.787	–	–	0.984	–	–	1.181
N (Note 2)	0.374	–	–	0.374	–	–	0.512	–	–	0.591	–	–

Metric Equivalent
(millimeters) (Note 3)

	G6.35-15			G6.35-20			G6.35-25			G6.35-30		
Reference	Min	Nom	Max	Min	Nom	Max	Min	Nom	Max	Min	Nom	Max
A (Note 1)	0.95	–	1.05	0.95	–	1.05	0.95	–	1.05	0.95	–	1.05
B	–	6.35	–	–	6.35	–	–	6.35	–	–	6.35	–
C	7.5	–	–	7.5	–	–	7.5	–	–	7.5	–	–
E (Note 2)	–	–	7.5	–	–	7.5	–	–	9.0	–	–	9.0
L (Note 2)	–	–	15.0	–	–	20.0	–	–	25.0	–	–	30.0
N (Note 2)	9.5	–	–	9.5	–	–	13.0	–	–	15.0	–	–

NOTES:

(1) For base GY6.35, pin diameter A has values of 0.047 inch–0.051 inch (1.2 mm–1.3 mm). The designation is then GY6.35-____ (as appropriate). This version is not recommended for new designs of lamps.

(2) Dimensions E and L define the maximum limits of the cross section of the base over length N.

(3) The inch units of measurement were derived from the metric values. This accounts for the fact that converting from inches to metric equivalent does not necessarily round off as shown.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Gauging
When the base is completely inserted in the appropriate 3-340 gauge, the pins shall be coplanar with or project beyond surface y.

The individual pins shall enter hole A_2, but shall not enter hole A_1 of Gauge 3-341.

See ANSI C81.63 for gauges.

Lampholder
See ANSI C81.61, Standard Sheet 2-340.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

G7.9 and GX7.9 Bases

ANSI C81.61-1990
Std Sheet 1-356-1


The designations assigned to these bases in accordance with the system of the International Electrotechnical Commission (IEC) are G7.9 and GX7.9. At the time of issuance of this standard sheet, there was no comparable IEC standard in existence.

The G7.9 and GX7.9 bases differ in respect to their pin arrangements. The drawing shows the G7.9 version. For the GX7.9, low-voltage arrangement, the large and small pins are interchanged.

These bases are intended for application where precise aiming and positioning requirements exist for side-prong based lamps.

The dimensions shown on this sheet apply to bases after assembly on finished lamps.

The drawing is intended only to indicate the dimensions to be controlled.



Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Reference	Standard Dimensions (inch)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A	0.180	–	0.278	4.57	–	7.06
B	0.618	–	0.622	15.70	–	15.80
C (Notes 5, 6)	–	0.625	–	–	15.87	–
D (Note 7)	–	0.312	–	–	7.92	–
E_1 Dia (Note 8)	0.091	–	0.098	2.31	–	2.49
E_2 Dia (Note 8)	0.123	–	0.130	3.12	–	3.30
F	0.526	–	0.575	13.36	–	14.61
G	–	–	0.167	–	–	4.24
H_1 Dia	–	–	0.135	–	–	3.43
H_2 Dia	–	–	0.180	–	–	4.57
I (Notes 5, 7)	–	0.281	–	–	7.14	–
J	0.560	–	0.563	14.22	–	14.30
K	0.152	–	–	3.86	–	–
N	0.098	–	0.123	2.49	–	3.12
P (Note 4)	0.706	–	–	17.93	–	–
R (Note 5)	–	0.437	–	–	11.10	–
S	0.088	–	0.107	2.24	–	2.72
T	0.600	–	–	15.24	–	–
U (Note 8)	0.461	–	–	11.71	–	–
V (Note 7)	0.149	–	0.157	3.78	–	3.99
W	–	–	0.194	–	–	4.93
r_1	0.046	–	0.093	1.17	–	2.36
r_2	0.012	–	0.050	0.53	–	1.27
r_3	0.057	–	0.090	1.45	–	2.29

NOTES:

(1) The arrow shows direction of light beam when the base is used in side-prong applications.

(2) Planes x, y, and z are theoretical; they establish an orthogonal framework for positioing the three mounting surfaces x, y, and z of the base. At least three points of surface x shall be in plane x to provide mechanically stable contact. Simultaneously, at least two points of surface z shall be in plane z, and at least one point of surface y shall be in plane y to provide mechanically stable contact. Points on surfaces x, y, and z shall not penetrate their corresponding planes.

(3) Radius r_2 applies at the four edges of the volume defined by dimensions A and B.

(4) Dimension P provides a boundary for surface x only. No parts of the base or the holder shall interfere with surface x, distance P.

(5) Dimension C and I locate the optical axis relative to planes x and z, respectively.

(6) Dimensions R and C define a location for the application of lamp retention and positioning forces provided by appropriate devices.

(7) Dimensions D, I, and V are checked by the base gauge. Dimension I positions the pin centerlines relative to plane z.

(8) The distance given by dimension U minus dimension G defines the minimum length over which dimension E_1 and E_2 apply.

(9) Surface x shall be flat within 0.003 inch (0.08 mm). Dimensions J, S, and T define the minimum surface area of surface x.

(10) Bases shall be able to withstand a temperature of 200°C (392°F) in normal operation.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Gauging
The base shall enter Gauge 3-356. When the base is fully seated, the reference plane x of the base shall be in contact with surface x of the gauge. In this position, the ends of both pins shall be coplanar with or project beyond surface u, but they shall not project beyond surface w.

See ANXI C81.63 for gauges.

Lampholder
See ANSI C81.62, Standard Sheet 2-356.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale


G9.5 Base

ANSI C81.61-1990
Std Sheet 1-368-1

The designation assigned to this base by the International Electrotechnical Commission (IEC) is G9.5. This standard sheet is equivalent to IEC Publication 61.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.



NOTES:
(1) Dimension C_1 indicates the minimum base height over which the limits for dimensions A and B apply.
(2) Dimple or elongated recess.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Reference	Standard Dimensions (inch)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A	0.365	–	0.385	9.27	–	9.78
B	0.923	–	0.943	23.44	–	23.95
C	0.920	–	–	23.37	–	–
C_1 (Note 3)	0.750	–	–	19.05	–	–
D	–	0.375	–	–	9.53	–
E	0.122	–	0.128	3.10	–	3.25
F	0.375	–	0.450	9.53	–	11.43
G	–	–	0.119	–	–	3.02
H	0.650	–	0.700	16.51	–	17.78
J	0.280	–	0.290	7.11	–	7.37
L	–	–	0.300	–	–	7.62
S	0.031	–	–	0.79	–	–
U (Note 4)	0.312	–	–	7.92	–	–
r	–	0.114	–	–	2.90	–
r_1	0.125	–	0.182	3.18	–	4.62
r_2	0.030	–	0.067	0.76	–	1.70
r_3	0.011	–	–	0.28	–	–
r_4	0.050	–	–	1.27	–	–

NOTES:
(3) Dimension C_1 indicates the minimum base height over which the limits for dimensions A and B apply.
(4) Dimension U is the minimum length of the cylindrical portion of the pin.

Gauging

The pins on the base of a finished lamp shall enter Gauge 3-368 and, when fully inserted, the reference plane of the base shall contact surface x of the gauge. In this position, the ends of both pins shall reach at least to surface z and shall not project beyond surface y.

See ANSI C81.63 for gauges.

Lampholder

See ANSI C81.62, Standard Sheet 2-368.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale


GY9.5 and GZ9.5 Bases

The designations assigned to these bases by the International Electrotechnical Commission (IEC) are GY9.5 and GZ9.5. This standard sheet is equivalent to IEC Publication 61.

Bases GY9.5 and GZ9.5 differ only in respect to dimensions B and J. The GY9.5 is intended for lamp application over 700 watts, and the GZ9.5 is intended for application up to 700 watts.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.



Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Reference	Standard Dimensions (inches)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A	0.420	–	0.440	10.67	–	11.18
B (GY9.5)	1.075	–	1.180	27.31	–	29.97
B (GZ9.5)	0.807	–	0.950	20.5	–	24.13
C (Note 5)	0.620	–	–	15.75	–	–
C_1 (Note 6)	0.118	–	–	3.0	–	–
D (Note 7)	–	0.375	–	–	9.53	–
E_1	0.090	–	0.096	2.29	–	2.44
E_2	0.122	–	0.128	3.10	–	3.25
F	0.280	–	0.340	7.11	–	8.64
J (GY9.5)	0.550	–	–	14.0	–	–
J (GZ9.5)	0.550	–	0.750	14.0	–	19.05
J_1	0.500	–	–	12.7	–	–
N	0.039	–	–	1.0	–	–
P	0.360	–	0.394	9.14	–	10.0
R	0.305	–	0.325	7.75	–	8.26
T	0.540	–	0.565	13.72	–	14.35
U (Note 8)	0.200	–	–	5.08	–	–
α (Note 1)	40°	–	90°	40°	–	90°

NOTES:

(1) In cases where angle α approaches 90°, the upper edges of the retaining lugs shall be rounded off to approximately 0.016 inch (0.4 mm).

(2) The insulation may be open at the narrow sides. Under these circumstances, the width of the base and the seal on the finished lamp shall not exceed, within the distance defined by dimension C, dimension B maximum. When this form of construction is used, care should be taken to ensure that no live parts are accessible.

(3) The bosses of the pins shall not project beyond the reference plane.

(4) The ends of the pins shall be rounded or tapered to provide easy entry into and removal from lampholders.

(5) Dimension C defines the minimum distance over which the maximum limits of dimensions A and B shall apply.

(6) Dimension C_1 defines the minimum distance over which both the minimum and maximum limits for dimensions A and B shall apply.

(7) Dimension D is for design purposes. Practical tolerances, in combination with pin diameters, are incorporated in the gaging system.

(8) Dimension U defines the minimum length over which both the minimum and maximum limits of dimensions E_1 and E_2 shall be observed; below this only the limits for E_1 maximum and E_2 maximum are applicable.

(9) The clearance and creepage distances between parts of opposite polarity shall be not less than 0.098 inch (2.5 mm).

Gauging

It shall be possible to insert the base into Gauge 3-369 until the supporting bosses are in contact with surface z.

In this position, the ends of the pins shall be coplanar with or project beyond surface x, but shall not project beyond surface w. In addition, the top edge of the shell shall project beyond or be coplanar with surface y, and the edges of the retainer projections shall lie between surfaces r and r_1 or be coplanar with them.

It shall be possible to insert the appropriate individual pins into hole E_5 or E_3 as far as the supporting bosses. It shall not be possible to insert the appropriate individual pins into hole E_4 or E_2 for a distance greater than that which allows a clearance of at least 5.08 mm between the surface of the gauge and the supporting bosses.

See ANSI C81.63 for gauges.

Lampholder

See ANSI C81.62, Standard Sheet 2-369.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS


Not for Resale


G10q Four-Pin Circular Fluorescent Lamp Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is G10q. This standard is equivalent to IEC Publication 61.


The dimensions shown on this sheet apply to finished bases after assembly on lamps.


The drawing is intended only to indicate the dimensions to be controlled.





ENLARGED VIEW
OF PIN





BASE POSITION
SECTION VIEW

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Reference	Standard Dimensions (inches)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
E (dia) (Note 12)	0.090	–	0.100	–	–	–
F	0.250	–	0.300	6.35	–	7.62
G (Note 2)	–	–	0.050	–	–	1.27
H (dia)	–	–	0.130	–	–	3.30
L (dia) (Notes 6, 7)	–	–	1.220	–	–	31.00
M (Notes 8, 9, 10)	0.220	–	–	5.59	–	–
N (Note 6)	0.937	–	–	23.80	–	–
R_1 (Note 5)	0.457	–	–	11.61	–	–
R_2 (Notes 3, 4, 5)	–	–	0.165	–	–	4.20
S	0.657	–	–	16.69	–	–
T	0.626	–	–	15.90	–	–
U (Notes 11, 12)	–	0.250	–	–	6.35	–
V (Notes 11, 12)	–	0.312	–	–	7.92	–
Y (Note 13)	0.374	–	0.492	9.5	–	12.5
α (degrees) (Note 14)	–	45° approx	–	–	45° approx	–

NOTES:

(1) The ends of the pins shall be rounded or chamfered.

(2) The contour of the boss is controlled by the gauge on Standard Sheet 3-383.

(3) Dimension R_2, if present, is the radius of the arc of the rounded corners, located to be tangent to the sides.

(4) Dimension R_2, future objective = 0.150 inch (3.8 mm), maximum.

(5) In the case where the design option is exercised that allows unrestricted expansion of dimension S or dimension T, or both, the features defined by dimensions R_1 and R_2 may not be present.

(6) Dimension N denotes the distance over which diameter L applies.

(7) Irregularities are permitted on the surface of the base, provided that dimension L is maintained from the centerline to the reference plane (dimension Y) and along dimension N for proper mating to full-size lampholders (providing both holder and connector functions).

(8) Dimension M defines the minimum distance from the reference plane within which the pin shall be cylindrical, with the exception of the boss height dimension G.

(9) Indentations or grooves in the surface of the pins are allowed providing . . . . . (to be determined).

(10) This dimension is solely for base design and is not to be gauged on the finished lamp.

(11) The diameter of the circle on which the four pins are located is approximately 0.394 in (10 mm).

(12) Dimensions E, U, and V are checked in combination with other dimensions by the gauge shown on ANSI C81.63, Standard Sheet 3-383.

(13) Dimension Y is for base design purposes.

(14) Amount of rotation required by insertion into lampholder is shown in American National Standard for Dimension and Electrical Characteristics of Fluorescent Lamps – Rapid-Start Types, ANSI C78.1-1978 (R1984) and its supplements.

Gauging

The pins on bases of finished lamps shall enter Gauge 1-383 at surface o. Surface o shall contact the bottom of the base cavity. In this position, the end of the pins shall reach at least to surface x and shall not project beyond surface y.

See ANSI C81.63 for gauges.

Lampholder

See ANSI C81.62, Standard Sheet 2-383.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

2G11 Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is 2G11.

The dimensions shown apply to bases after assembly on lamps.

The drawings are intended only to indicate the dimensions to be controlled.



Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Reference	Dimensions (millimeters) Min	Nom	Max
A (Note 3)	–	22	–
A_1	43.3*	–	43.9*
B	23.2*	–	23.6*
D	–	11	–
E (Note 4)	2.29	–	2.67
F	6.0	–	6.8
F_1	5.5	–	–
N (Note 5)	6.5*	–	–
Q (Note 5, 6)	1.5*	–	–
R (Note 3)	–	B/2*	–
S (Note 5, 6)	3.5*	–	3.9
T	7.0*	–	–
Y	12.7*	–	–
r_1 (Note 6)	0.3*	–	0.5*
r_2 (Note 6)	0.2*	–	0.5*
α (Note 5, 6)	–	45°	–

* These dimensions are solely for base design and are not to be gauged on the finished lamp.

NOTES:

(1) Dimension Y denotes the minimum length over which the maximum limits of dimensions A_1, B, and R shall be observed.

(2) The shape of the end of the pin is either chamfered or rounded to aid insertion.

(3) Dimension A denotes centerline spacing of two sets of pins, not necessarily the center for dimension R.

(4) For unmounted bases, E max = 2.44.

(5) Dimensions N, S, and α define the minimum length of the notch over which dimensions Q and T apply. The maximum length of the notch is not specified and the notch could run up to the top of the base.

(6) Dimensions Q, S, r_1, r_2 minimum, and α shall apply within the width of the notch, dimension T. Outside dimension T, only the limit for dimension r_2 maximum applies.

(7) Indentations or grooves in the surface of the pins are allowed provided they do not extend into that part of the pin radius which is bounded by angles of 30° to the plane through the centerlines of the pins. The diameter of the pins, measured in the plane through the centerlines of the pins, shall not be less than 2.29 mm in every plane parallel to the base face.

Gauging

It shall be possible to insert a lamp base into Gauge 3-393 until the reference plane of the base is in contact with surface x of the gauge. In this position, all pins shall be coplanar with, or project beyond surface y, but shall not project beyond surface z.

See ANSI C81.63 for gauges.

Lampholder

See ANSI C81.62, Standard Sheet 2-393.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

G13 Medium Bipin Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is G13. This standard sheet is nearly equivalent to IEC Publication 61.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.

Design variants of dimension J exist for application on three sizes of lamp bulbs.




Figure 1
Base on Lamp

	Standard Dimensions (inches)			Nearest Metric Equivalent (millimeters)		
Reference	Min	Nom	Max	Min	Nom	Max
A (Note 1)	0.343	–	–	8.71	–	–
D	–	0.500	–	–	12.70	–
E (Notes 2, 3)	0.090	–	0.105	2.29	–	2.67
F	0.250*	–	0.300	6.35	–	7.62
G	–	–	0.034	–	–	0.86
H	–	–	0.130	–	–	3.30
J (Note 4)	–	–	1.015 (T8)	–	–	25.78 (T8)
	–	–	1.240 (T10)	–	–	31.50 (T10)
	–	–	1.438 (T12)	–	–	36.52 (T12)
L (Notes 5, 6, 9)	0.205	–	–	5.21	–	–
M (Note 7)	1.25	–	–	31.75	–	–
T (Note 8)	–	–	0.555 (T8)	–	–	14.10 (T8)
	–	–	0.680 (T10)	–	–	17.27 (T10)
	–	–	0.800 (T12)	–	–	20.32 (T12)
r	0.015	–	–	0.38	–	–

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale




Figure 2
Enlarged Cross-Sectional View of Pins in a Plane Parallel to Base Face. (See Note 9(a))




Figure 3
Enlarged Cross-Sectional View of An Indented or Grooved Pin in a Plane Parallel to the Base Face at the Point of the Largest Crimp Diameter. (See Note 9)

NOTES:

(1) Dimension A is the length over which dimension J applies. The minimum limit is the same for T8 (T25), T10 (T32), and T12 (T38) bulbs.

(2) Prior to welding, soldering, or crimping, the pin diameter shall be 0.093 inch ± 0.003 inch (2.36 mm ± 0.08 mm). This dimension is not to be gauged on the finished lamp.

(3) An allowance of 0.105 inch (2.67 mm) maximum, for gauging, accounts for possible solder buildup, welding burn-over or distortion at the crimp.

(4) Maximum base shell diameter J is shown separately for T8 (T25), T10 (T32), and T12 (T38) bulb lamps.

(5) This dimension is solely for base design and is not to be gauged on the finished lamp.

(6) Dimensinon L is the minimum length within which the pin shall be cylindrical, with the exception of the height of the bead, dimension G.

(7) Dimension M represents length of lamp over which dimension T is applicable.

(8) The T dimension includes allowance for possible offset of the bulb axis with respect to the base axis. This dimension is shown separately for T8 (T25), T10 (T32), and T12 (T38) bulb lamps.

(9) Indentations or grooves in the surfaces of the pins are allowed provided that they extend into a zone of 0.016 inch (0.4 mm) measured from the end of the pin.

(a) One "crimp zone" per pin is allowed. Each zone is centered on the pin centerline perpendicular to a plane through both pins. The zone shall not exceed a total angle of 100°. The crimp may lie anywhere in the zone, but its radial width shall not exceed 0.052 inch (1.32 mm). These zones are shown on both pins in Figure 2. They may also be located on the opposite side of the centerline. The diameter of the pins measured in the plane through the centerlines of the pins shall not be less than 0.090 inch (2.29 mm) in every plane parallel to the base face.

(b) They shall be such that the depth of the indentations be no greater than one-half the original pin diameter. See Figure 3.

(c) Sharp corners of the crimp, which may hang up in lampholder contacts, should be avoided.

(d) The cross-sectional shape of the indentation is not limited to the shape shown in Figure 3.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Gauging
The pins of a finished lamp base shall enter Gauge 3-406, holes E_2 at surface o. When fully inserted, the surfaces of the base and gauge shall be in contact, and the ends of the pins shall reach at least to surface x and shall not project beyond surface y. Insertion force shall not exceed 1 lbf (4.45 N).

Each individual pin shall enter hole E_1 at surface o until the face of the base and the surface of the gauge contact.

The cylindrical portion of each pin shall not enter hole E_3.

Each individual pin of an unmounted base shall fully enter hole E_2 of Gauge 3-407 until the boss contacts the gauge. Each pin shall not fully enter hole E_1.

See ANSI C81.63 for gauges.

Pin Strength Test
A base is acceptable if it passes either the torsion test or one of the pin force tests.

Torsion strength of the pins shall be tested by means of Test Device 3-410. Properly insert the base pins into the test device. Apply a rotational torque, increasing from 0 to 6 lbf•in (0.68 N•m), and hold for 5 seconds maximum. A limit of 7 lbf•in (0.79 N•m) is under consideration.

A force perpendicular to the pin's axis shall be applied to any pin. With the test lamp mounted horizontally, force may be applied with either an anvil point or a wire-weight at a point 0.180 inch (4.57 mm) from the base face.

Use a force gage with an anvil point of a radius of approximately 0.025 inch (0.64 mm) to apply a force of 12 lb (5.45 kg). A value of 14 lb (6.35 kg) is under consideration.

Suspend a 12-lb (5.45-kg) mass by a loop of solid wire 0.050 inch (1.27 mm) in diameter. A value of 14 lb (6.35 kg) is under consideration.

The pin under test shall sustain the force for 5 seconds without that degree of deformation that would allow the anvil or wire loop to slip off the end of the pin.

NOTE: The test point, 0.180 inch (4.57 mm) from the base face, was chosen for measurement purposes so that irregularities in the pin's surface near the ends of the pins could be avoided. In actual practice, smaller forces may occur further along the length of the pins.

Lampholder
See ANSI C81.62, Standard Sheet 2-406.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

2G13 U-Shaped Fluorescent Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is 2G13.

The dimensions shown on this sheet apply to finished bases after assembly on U-shaped fluorescent lamps.

The drawing is intended only to indicate the dimensions essential for interchangeability.



Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

2G13-41 (1-5/8 inch) Spacing

Reference	Standard Dimensions (inches)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A	–	1.625	–	–	41	–
B	0.098	–	–	2.5	–	–
D	–	–	1.015 (T8)	–	–	25.78
D_1	–	–	1.098 (T8)	–	–	27.90
G	–	–	0.512	–	–	13.0
H (Note 2)	0.118	–	–	3.0	–	–
r	–	–	0.138	–	–	3.5

2G13-92 (3-5/8 inch) Spacing

Reference	Standard Dimensions (inches)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A	–	3.625	–	–	92	–
B	0.098	–	–	2.5	–	–
D	–	–	1.438 (T-12)	–	–	36.52
D_1	–	–	1.516 (T-12)	–	–	38.5
G	–	–	0.512	–	–	13.0
N (Note 2)	0.118	–	–	3.0	–	–
r	–	–	0.138	–	–	3.5

2G13-152 (6 inch) Spacing

Reference	Standard Dimensions (inches)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A	–	6.00	–	–	152	–
B	0.098	–	–	2.5	–	–
D	–	–	1.438 (T-12)	–	–	36.52
D_1	–	–	1.516 (T-12)	–	–	38.5
G	–	–	0.512	–	–	13.0
N (Note 2)	0.118	–	–	3.0	–	–
r	–	–	0.138	–	–	3.5

NOTES:

(1) The cross-sectional shape of the brace is optional. The purpose of the leg brace is to maintain proper spacing of the lamp's legs. It shall not be used to retain or support the lamp in the lampholder of the fixture.

(2) Dimension N denotes the minimum length over which dimension D shall be observed.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Gauging
Without using undue force, it shall be possible to insert the pins of the base into the slots of Gauge 3-420 so that the side of at least one pin of each pair is in contact with surface z. There shall be contact between the underside of at least one of the G13 sections of the base and surface x of the gauge.

See ANSI C81.63 for gauges.

Lampholder
See ANSI C81.62, Standard Sheet 2-420.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS


Not for Resale

GX16d Mogul and Extended Mogul End-Prong Bases

The designation assigned to these bases by the International Electrotechnical Commission (IEC) is GX16d. At the time of issuance of this standard sheet, there was no comparable IEC standard.

The dimensions shown apply to bases after assembly on lamps.

The drawings are intended only to indicate the dimensions to be controlled.



Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Reference	Standard Dimensions (inches)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A	0.739	–	0.769	18.76	–	19.53
B	2.032	–	2.094	51.61	–	53.19
C	0.477*	–	0.492*	12.11*	–	12.50*
C_1	1.230*	–	1.285*	31.24*	–	32.64*
r_1	0.039	–	–	1.0	–	–
r_2	0.365	–	–	9.27	–	–

NOTES:
(1) These bases are intended to provide an electrical connection function only, not a mechanical support function.
(2) The insulation blocks may float relative to the fixed-position prongs specified on Standard Sheet 1-431.
* This dimension is for base design and is not gauged on a finished lamp.

Gauging
It shall be possible to insert the base of a lamp into the cavity of Gauge 3-430 without undue force. When surface x of the base is in contact with surface x of the gauge, the prongs shall extend at least to surface y, but not beyond surface z.

See ANSI C81.63 for gauges.

Lampholder
See ANSI C81.62, Standard Sheet 2-430.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

GX16d Termination

The designation assigned to this termination by the International Electrotechnical Commission (IEC) is GX16d.

The dimensions shown apply after assembly on finished lamps. This termination may represent the only features involved in interchangeability or it may be part of the base employing additional features.




Figure 1
As Employed on a Pressed Glass Lamp

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale




Figure 2
As Employed on a GX16d Base

Reference	Standard Dimensions (inches)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
D	–	0.656	–	–	16.66	–
E_1	0.028	–	0.034	0.71	–	0.86
E_2	0.304	–	0.320	7.72	–	8.13
F	0.430	–	0.540	10.92	–	13.72
F_1	–	0.187	–	–	4.75	–
K	–	0.125	–	–	3.18	–

NOTES:
(1) Prong end taper optional. If present, provides a lead-in for insertion into holder.
(2) Tang optional and may be on either side of prong.
(3) Distance between prong end and solder, or optional tang.
(4) Slight chamfer or convex radius required on end of prong.

Gauging

At the time of issuance of this standard sheet, gauges did not exist.

Lampholder

See ANSI C81.62, Standard Sheet 2-430.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

G17t Tri-Pin Prefocus Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is G17t. This standard sheet is nearly equivalent to IEC Publication 61.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.



NOTE: For values of the indicated dimensions, refer to Standard Sheet 1-440.

Pin Arrangement
This base is identical to G17q (Standard Sheet 1-440) except that pin 2 has been omitted.

Lamps are aligned on pins 1 and 3; contact-making pins are 1 and 4. The reference planes are X-X, which defines the base seating surface, and Y-Y, which is at 90 degrees to X-X and passes through the center of pins 1 and 3, pin 1 being the primary reference and pin 3 merely serving to limit rotation about pin 1.

Gauging
It shall be possible to insert a lamp into Gauge 3-439 until the base face is in contact with surface x. In this position, the end of each of the three pins shall be between surfaces s1 and s2 and the center post shall be between surfaces s3 and s4.

See ANSI C81.63 for gauge descriptions and procedures.

Related Standard Sheet
Specifications for the G17q base are shown on Standard Sheet 1-440.

Lampholder
See ANSI C81.62, Standard Sheet 2-440.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS


Not for Resale


G17q and GX17q
Four-Pin Prefocus Bases

The designations assigned to these bases by the International Electrotechnical Commission (IEC) are G17q and GX17q. This standard sheet is nearly equivalent to IEC Publication 61.


The dimensions shown on this sheet apply to finished bases after assembly on lamps.


The drawings are intended only to indicate the dimensions to be controlled.






The three shell bosses shown below are an alternative to the rib contour shown above. All other dimensions of the base remain the same.







Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Reference	Standard Dimensions (inches)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A	0.258	–	0.266	6.55	–	6.76
B	0.684	–	0.690	17.37	–	17.53
C	0.395	–	–	10.03	–	–
D	0.301	–	0.311	7.64	–	7.90
E	0.083	–	0.087	2.11	–	2.21
F	0.049	–	0.051	1.24	–	1.30
G	0.235	–	0.295	5.97	–	7.49
H (Note 1)	1.172	–	1.190	29.77	–	30.23
J	0.395	–	0.420	10.03	–	10.67
K	0.028	–	–	0.71	–	–
L	0.525	–	0.545	13.34	–	13.84
M	0.490	–	0.510	12.45	–	12.95
N_1	1.160	–	1.180	29.46	–	29.97
N_2 (Note 3)	–	1.170	–	–	29.72	–
P	0.020	–	0.030	0.51	–	0.76
Q_1	–	0.200 approx	–	–	5.08 approx	–
Q_2	0.100	–	–	2.54	–	–
R_1	0.325	–	0.345	8.26	–	8.76
R_2 (Note 3)	0.355	–	0.365	9.02	–	9.27
S	0.115	–	0.135	2.92	–	3.43
T	0.0025	–	0.0075	0.064	–	0.190
U (Note 3)	–	0.200	–	–	5.08	–
V (Note 3)	0.037	–	0.043	0.940	–	1.09
W (Note 3)	–	0.080	–	–	2.03	–
α (degrees) (Note 2)	–	67°30'	–	–	–	–

NOTES:
(1) The minimum dimension shall be checked with calipers. The maximum dimension shall be checked with a ring gauge. The nominal design center of diameter H shall be 1.180 inches (29.97 mm).
(2) The angle α is the angle between the key and pin 1.
(3) These dimensions are solely for base design and are not to be gauged on the finished lamp.

Optical Axis
It is recommended that the direction of the optical axis of lamps using the four-pin prefocus base be specified by an angle measured clockwise from the primary reference pin when viewing the lamp from the base end. The plane containing the optical axis will normally pass through a point defined as being on a line between the two reference pins and at a distance of 0.3435 inch (8.72 mm) from the center of the primary reference pin.

Pin Arrangement 1 (See Note 4)
Lamps using this arrangement are aligned on pins 1 and 3; contact-making pins are 1 and 4 (the IEC designation for this arrangement is G17q). The reference planes are X-X, which defines the base seating surface, and Y-Y, which is at 90 degrees to X-X passing through the centers of pins 1 and 3, pin 1 being the primary reference and pin 3 merely serving to limit rotation about pin 1.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Pin Arrangement 2 (See Note 5)
Lamps using this arrangement are aligned on pins 2 and 4; contact-making pins are 1 and 2 (the IEC designation for this arrangement is GX17q). The reference planes are X-X, which defines the base seating surface, and Z-Z, which is at 90 degrees to X-X passing through the centers of pins 2 and 4, pin 2 being the primary reference and pin 4 merely serving to limit rotation about pin 2.

NOTES:
(4) Lamps using pin arrangement 1 are currently "standard" or "high-voltage" lamps.
(5) Lamps using pin arrangement 2 are currently "low-voltage" lamps.

Gauging
It shall be possible to insert a lamp in Gauge 3-349 until the base face is in contact with surface x. In this position, the end of each of the four pins shall be between surfaces s1 and s2, and the center post shall be between surfaces s3 and s4.

See ANSI C81.63 for gauge description and testing procedures.

Related Standard Sheet
Specifications for the G17t base are shown on Standard Sheet 1-439.

Lampholder
See ANSI C81.62, Standard Sheet 2-440.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale


G20 Mogul Bipin Base

ANSI C81.61-1990
Std Sheet 1-452-1

The designation assigned to this base by the International Electrotechnical Commission (IEC) is G20. This standard sheet is nearly equivalent to IEC Publication 61.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.



Reference	Standard Dimensions (inches) Min	Nom	Max	Nearest Metric Equivalent (millimeters) Min	Nom	Max
D	–	0.781	–	–	19.84	–
E (Note 1)	0.120	–	0.139	3.05	–	3.53
F (Note 1)	0.615	–	0.660	15.62	–	16.76
G	–	–	0.065	–	–	1.65
H	–	–	0.190	–	–	4.83
J	–	–	2.040	–	–	51.82
L (Notes 2, 3)	0.500	–	–	12.70	–	–
M (Note 4)	2.0	–	–	50.8	–	–
T (Note 5)	–	–	1.110	–	–	28.19

NOTES:
(1) Diameter and length of pins include solder. Nominal pin diameter is 0.125 inch (3.18 mm).
(2) This dimension is solely for base design and is not to be gauged on the finished lamp.
(3) Dimension L is the minimum length of the cylindrical portion of the pin.
(4) Represents length of lamp over which dimension T is applicable.
(5) The T dimension includes allowance for possible offset of the bulb axis with respect to the base axis.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Gauging
It shall be possible for the bases on a lamp to enter Gauge 3-452 at the two holes E5 at surface o until the surface of the base and gauge contact each other. In this position, the ends of the pins shall reach at least to surface x and shall not project beyond surface y. Each individual base pin shall enter hole E4 at surface o until the face of the base and the surface of the gauge are in contact.

In applying this gauge, the force shall not exceed 1.5 lbf (6.67 N).

See ANSI C81.63 for gauges.

Lampholder
See ANSI C81.62, Standard Sheet 2-850.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

G22 Medium Bipost Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is G22. This standard sheet is equivalent to IEC Publication 61.

The dimensions shown apply to bases after assembly on lamps.

The drawings are intended only to indicate the dimensions to be controlled.



NOTE: All other dimensions are the same as those on the glass base.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Reference	Dimensions (inches)			Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A_1 (Note 1)	–	–	1.791	–	–	45.49
A_2 (Note 1)	–	–	1.857	–	–	47.17
C (Note 1)	0.197	–	–	5.00	–	–
D	–	0.875	–	–	22.22	–
E	0.248	–	0.252	6.30	–	6.40
F	0.980	–	1.045	24.89	–	26.54
G	0.394	–	0.429	10.00	–	10.90
H	–	–	0.465	–	–	11.81
J (Note 2)	–	–	0.236	–	–	5.99
K (Note 3)	–	–	0.350	–	–	8.89
M	0.153	–	0.159	3.89	–	4.04
P	0.154	–	–	3.90	–	–
X (Note 4)	–	–	1.000	–	–	25.40
Y (Notes 4, 5)	–	–	1.550	–	–	39.37
Z (Note 5)	1.620	–	1.791	41.15	–	45.49
r	0.040	–	0.124	1.02	–	3.15

NOTES:
(1) The part of the base above the reference plane shall lie within the space defined by dimensions A_1, A_2, and C.
(2) Dimension J includes the eccentricity of location in addition to the diameter of the exhaust tip.
(3) To ensure a fit in European holders, a K maximum value of 0.295 inches (7.5 mm) must be observed.
(4) Dimensions Y and X define the area reserved for installation of the posts and the exhaust tip within which surface irregularities are allowed. Outside this area, there shall be no surface irregularities projecting below the reference plane.
(5) Dimensions Y and Z (shaded area) define the limits of the seating area.

Gauging

When the lamp base is fully inserted into the recess of Gauge 3-466, the reference plane of the base shall seat on surface x. Dimensions F, G, and K are checked by sighting across the reference surfaces representing the maximums or minimums of these dimensions. The post diameters are checked singly by insertion into the gauge holes designated E_1 and E_2. Each post must enter the "Go" Gauge over its entire cylindrical length. The posts must enter the "Not-Go" gauge beyond the radiused ends.

See ANSI C81.63 for gauges.

Lampholder

See ANSI C81.62, Standard Sheet 1-466.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

G23 Base

ANSI C81.61-1990
Std Sheet 1-475-1

The designation assigned to this base by the International Electrotechnical Commission (IEC) is G23. This standard sheet is equivalent to IEC Publication 61.

The drawing is intended only to indicate the dimensions to be controlled.



NOTE: The G23 fit is developed for single-ended fluorescent lamps with a preheating current not exceeding 240 mA. For lamps with a preheating current exceeding 240 mA, see GX23 fit (ANSI C81.61, Standard Sheet 1-476).

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Reference	Standard Dimensions (millimeters) Min	Nom	Max	Reference	Standard Dimensions (millimeters) Min	Nom	Max
A (Note 2)	31.5	–	32.5	Q	1.2	–	–
B (Notes 1, 2)	17.7	–	18.1	R (Note 2)	–	–	9.05
D (Note 11)	–	23.0	–	S	8.85	–	9.15
E (Notes 6, 3, 11)	2.29	–	2.67	T (Notes 1, 11)	3.5	–	4.5
F (Note 11)	6.0	–	6.8	U (Note 9)	–	–	0.2
F_1 (Notes 9, 10)	5.5	–	–	V (Note 1)	–	11	–
K_1 (Notes 4, 11)	16.15	–	16.3	W (Notes 1, 8)	3.0	–	–
K_2 (Note 5)	15.6	–	15.75	Y (Note 2)	10.2	–	–
L_1 (Notes 4, 11)	13.75	–	13.9	Z (Note 9)	0.5	–	–
L_2 (Note 5)	13.2	–	13.35	r_1	–	–	0.4
M	–	–	23.0	r_2 (Notes 7, 9)	0.8 approx	–	–
N_1 (Note 4)	–	0.5	–	r_3 (Note 9)	0.5	–	1.0
N_2 (Note 5)	–	21.0	–	α (Note 9)	–	35°	–
P (Note 11)	20.6	–	21.0	β	20°	–	30°

NOTES:

(1) Dimension B minimum shall apply outside dimension T up to at least dimension V and up to dimension W minimum. Dimension B maximum shall apply outside dimension T.

(2) Dimension Y denotes the minimum length over which the maximum limits of dimensions A, B, and R shall be observed.

(3) On unmounted bases E maximum = 2.44 mm.

(4) Dimensions K_1 and L_1 are measured at distance N_1 below the reference plane.

(5) Dimensions K_2 and L_2 are measured at distance N_2 below the reference plane.

(6) Indentations or grooves in the surface of the pins are allowed, provided that they do not extend into that part of the pin-radius that is bounded by the angles of 60° and 120° of the plane through the centerlines of the pins (see drawing). The diameter of the pins measured in the direction perpendicular to the plane through the centerlines of the pins shall be not less than 2.29 mm in every plane parallel to the base face.

(7) A chamfer of approximately 0.8 mm is also allowed.

(8) Dimension W denotes the height of the insulating part.

(9) These dimensions are solely for base design and are not gauged on the finished lamp.

(10) Dimension F_1 is the minimum length of the cylindrical portion of the pin.

(11) The combined displacement and the diameter of the pins, the minimum and the maximum diameter of the individual pins, the minimum and the maximum pin lengths, and the maximum values of dimensions K_1, L_1, P and T are checked by the base gauge.

(12) The shape of the end of the pin may be either chamfered or rounded.

Gauging

When the lamp base center post is fully inserted in Gauge 3-475 at surface o, the reference plane of the base and the surface of the gauge shall be in contact. In this position the ends of the pins shall be coplanar with or project beyond surface f_1 but they shall not project beyond surface f_2. It shall be possible to insert each pin in turn into hole E_1 until the reference plane of the base and the surface of the gauge are in contact. It shall not be possible to insert the pins, other than the extreme tips, into hole E_2.

See ANSI C81.63 for gauges.

Lampholder


See ANSI C81.62, Standard Sheet 2-475.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

GX23 Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is GX23. This standard sheet is equivalent to IEC Publication 61.

This drawing is intended only to indicate the dimensions to be controlled.



NOTE: If this fit is used for single-ended fluorescent lamps, the maximum preheating current should be in the range of $240 < Ip \leq 525$ mA. For lamps with a preheating current not exceeding 240 mA, see G23 fit (ANSI C81.61, Std Sheet 1-475).

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Reference	Standard Dimensions (millimeters) Min	Nom	Max	Reference	Standard Dimensions (millimeters) Min	Nom	Max
A (Note 2)	31.5	–	32.5	Q	1.2	–	–
B (Notes 1, 2)	17.7	–	18.1	R (Note 2)	–	–	9.05
D (Note 11)	–	23.0	–	S	8.85	–	9.15
E (Notes 6, 3, 11)	2.29	–	2.67 (Note 3)	T (Notes 1, 11)	3.5	–	4.5
F (Note 11)	6.0	–	6.8	U (Note 9)	–	–	0.2
F_1 (Notes 9, 10)	5.5	–	–	W (Notes 1, 8)	3.0	–	–
K_1 (Notes 4, 11)	16.15	–	16.3	X	3.5	–	–
K_2 (Note 5)	15.6	–	15.75	Y (Note 2)	10.2	–	–
L_1 (Notes 4, 11)	13.75	–	13.9	Z (Note 9)	0.5	–	–
L_2 (Note 5)	13.2	–	13.35	r_1	–	–	0.4
M	–	–	23.0	r_2 (Notes 7, 9)	0.8 approx	–	–
N_1 (Note 4)	–	0.5	–	α (Note 9)		35°	–
N_2 (Note 5)	–	21.0	–	β	20°	–	30°
P (Note 11)	20.6	–	21.0				

NOTES:

(1) Dimension B minimum shall apply within the width X and up to dimension W minimum. Dimension B maximum shall apply outside dimension T.

(2) Dimension Y denotes the minimum length over which the maximum limits of dimensions A, B, and R shall be observed.

(3) On unmounted bases $E_{max} = 2.44$ mm.

(4) Dimensions K_1 and L_1 are measured at distance N_1 below the reference plane.

(5) Dimensions K_2 and L_2 are measured at distance N_2 below the reference plane.

(6) Indentations or grooves in the surface of the pins are allowed, provided that they do not extend into that part of the pin-radius that is bounded by the angles of 60° and 120° of the plane through the centerlines of the pins (see drawing). The diameter of the pins measured in the direction perpendicular to the plane through the centerlines of the pins shall be not less than 2.29 mm in every plane parallel to the base face.

(7) A chamfer of approximately 0.8 mm is also allowed.

(8) Dimension W denotes the height of the insulating part.

(9) These dimensions are solely for base design and are not to be gauged on the finished lamp.

(10) Dimension F_1 is the minimum length of the cylindrical portion of the pin.

(11) The combined displacement and the diameter of the pins, the minimum and the maximum diameter of the individual pins, the minimum and the maximum pin lengths, and the maximum values of dimensions K_1, L_1, and T are checked by the base gauge.

(12) The shape of the end of the pin may be either chamfered or rounded.

Gauging

When the lamp base is fully inserted into Gauge 3-476 at surface o, the reference plane of the base and the surface of the gauge shall be in contact. In this position, the ends of the pins shall be coplanar with or project beyond surface f_1 but they shall not project beyond surface f_2.

It shall be possible to insert each pin in turn into hole E_1 until the reference plane of the cap and the surface of the gauge are in contact. It shall not be possible to insert the pins, other than the extreme tips, into hole E_2.

See ANSI C81.63 for gauges.

Lampholder


See ANSI C81.62, Standard Sheet 2-476.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

G24d and G24q Bases

The designations assigned to these bases by the International Electrotechnical Commission (IEC) are G24d-1, G24d-2, and G24d-3, G24q-1, G24q-2, and G24q-3. This standard sheet is fully compatible with that pending for IEC Publication 61.

These drawings are intended only to indicate the dimensions to be controlled.



NOTE: Only the G24d-1 base is shown. For bases with different designations, see page 2.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

G24d-1, G24d-2, G24d-3, G24q-1, G24q-2, G24q-3 Bases

Pin Location




Figure 1




Figure 2

Keying System




Figure 3




Figure 4




Figure 5

Designation	Pin Location Figure	Keying System	Dimension X_1 nom
G24d-1 G24q-1	1 2	3	Note 4
G24d-2 G24q-2	1 2	4	9.3
G24d-3 G24q-3	1 2	5	9.3

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Reference	Standard Dimensions (millimeters) Min	Nom	Max
A (Note 5)	27.5	–	28.5
A_1	27.5	–	31.0
B	–	–	35.0
D_1	–	23.0	–
D_2	–	8.0	–
E (Note 3)	2.29	–	2.67 (Note 6)
F	6.0	–	6.8
F_1	5.5	–	–
K_1 (Note 2)	16.15	–	16.3
K_2 (Note 1)	15.6	–	15.75
L_1 (Note 2)	13.75	–	13.9
L_2 (Note 1)	13.2	–	13.35
M	–	–	23.0
N_1 (Note 2)	–	0.5	–
N_2 (Note 1)	–	21.0	–
P	20.6	–	21.0
Q	1.2	–	–
R (Note 5)	8.4	–	9.5
R_1	9.0	–	–
S	8.85	–	9.15
T	3.5	–	4.5
U*	–	–	0.2
V	32.0	–	33.0
X_1	–	See Table, Page 2	–
X_2	2.5	–	–
Y (Note 5)	5.7	–	–
Z*	0.5	–	–
r_1	–	–	0.4
r_2* (Note 7)	–	0.8 approx	–
r_3	0.5	–	1.5
r_4	–	–	0.2
r_5	0.2	–	0.5
α*	–	Nom 35°	–
β	20°	–	30°
γ	–	30° approx	–

* These dimensions are solely for base design and are not to be gauged on the finished lamp.

NOTES:

(1) Dimensions K_2 and L_2 are measured at distance N_2 from the reference plane.

(2) Dimensions K_1 and L_1 are measured at distance N_1 from the reference plane.

(3) Indentations or grooves in the surface of the pins are allowed, provided that they do not extend into that part of the pin-radius which is bounded by the angles of 60° and 120° to the two parallel planes separated by dimension D_2 (see detail X). The diameter of the pins measured in the direction perpendicular to these planes through the centerlines shall be not less than 2.29 mm in every plane parallel to the base face.

(4) In this design, the keys are located on the centerline.

(5) With the exception of the keys, the circumference of the base, within dimension Y, shall lie between the limits determined by dimensions A_{max}, $A_{1\,max}$, and R_{min} on the one side and A_{max}, $A_{1\,max}$, and R_{max} on the other.

(6) On unmounted bases, $E_{max} = 2.44$.

(7) A chamfer of approximately 0.8 mm is also allowed.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Gauging
When the center post and pins of the base are fully inserted into Gauge 3-493, the reference plane of the base and the surface o of the gauge shall be in contact. In this position, the ends of the pins shall be coplanar with or project beyond f_1, but they shall not project beyond surface f_2.

It shall be possible to insert each pin in turn into hole E_1 until the reference plane of the base and the surface x of Gauge 3-493 shall be in contact.

It shall not be possible to insert the pins, other than the extreme tips, into hole E_2 of Gauge 3-493.

See ANSI C81.63 for gauges.

Lampholder
See ANSI C81.62, Standard Sheet 2-493.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

G38 Mogul Bipost Base

ANSI C81.61-1990
Std Sheet 1-519-1

The designation assigned to this base by the International Electrotechnical Commission (IEC) is G38. This standard sheet is equivalent to IEC Publication 61.

The drawing is intended only to indicate the dimensions to be controlled.



NOTES:

(1) The reference plane of the base is defined as the position of surface x of the "go" gauge shown on Standard Sheet 3-519 when that surface is in contact either with one or both bosses of the posts or with the surface of the insulator, depending upon the design of the base.

(2) The contour of the end of each post shall lie within the shaded area shown in detail P. In every case the ends of the posts shall be provided with a radius or chamfer sufficient to enable easy entry into the lampholder contacts.

(3) The broken lines in the above drawings correspond with the recesses in the "go" gauge shown on Standard Sheet 3-519.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Reference	Standard Dimensions (inches)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A_1 (Notes 4, 5)	–	–	3.012	–	–	76.5
A_2 (Notes 4, 5)	–	–	3.504	–	–	89.0
C (Notes 4, 5)	1.614	–	–	41.0	–	–
D (Note 5)	–	1.500	–	–	38.1	–
E (Notes 5, 6)	0.432	–	0.442	10.97	–	11.23
F	–	–	1.156	–	–	29.36
G (Notes 4, 5)	0.256	–	–	6.5	–	–
H_1 (Notes 4, 5)	–	–	0.795	–	–	20.2
H_2 (Notes 4, 5)	–	–	2.287	–	–	58.1
K	0.138	–	–	3.5	–	–
R	–	0.118	–	–	3.0	–
S	–	0.039	–	–	1.0	–
U (Note 7)	0.873	–	–	22.17	–	–
α (degrees)	–	45°	–	–	–	–

NOTES:

(4) The portion of the base above the reference plane shall lie within the space defined by dimensions A_1, A_2, C, G, H_1, and H_2.

(5) The contour of the base above the reference plane, the combined displacement and diameter of the posts and the maximum post lengths are checked by the gauge shown on Standard Sheet 3-519.

(6) The diameter of each of the individual posts is checked by the gauge shown on Standard Sheet 3-520.

(7) Dimension U denotes the minimum length over which dimension E shall be maintained.

(8) For finished lamps, the creepage distance over insulation between live parts and the metal shell, when provided, shall be not less than 0.118 inch (3.0 mm).

Gauging

When the lamp base has been fully inserted into gauge 3-519 with the posts entering at surface x, one or both of the bosses of the posts or the surface of the base shall be in contact with surface x or shall seat at diameter E_2. The cylindrical portion of the posts shall extend to or beyond surface v, and the ends of the posts shall not project beyond surface w.

When lamp base posts are inserted into Gauge 3-520 hole E_2, the boss of post or surface of the base shall be in contact with surface x.

It shall not be possible to insert the individual posts into hole E_1 at surface x. (This does not apply to the contoured end of the post.)

See ANSI C81.63 for gauges.

Lampholder

See ANSI C81.62, Standard Sheet 2-519.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS


Not for Resale

P13.5s Single-Contact Miniature Flanged Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is P13.5s. This standard sheet is equivalent to the version approved for publication in IEC Publication 61.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.



Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

	Standard Dimensions (inch)			Nearest Metric Equivalent (millimeters)		
Reference	Min	Nom	Max	Min	Nom	Max
A	0.358	–	0.364	9.09	–	9.25
A_1 (Note 1)	–	0.441	–	–	11.2	–
C	0.051 (Note 5)	–	–	1.3 (Note 5)	–	–
F	0.031	–	–	0.79	–	–
H	0.138	–	0.161	3.51	–	4.08
L (Note 2)	0.525	–	0.533	13.34	–	13.54
M	0.547	–	0.567 (Note 5)	13.90	–	14.40 (Note 5)
M_1	0.547	–	0.606	13.90	–	15.40
P	0.003	–	0.015 (Note 5)	0.08	–	0.38 (Note 5)
Q (Note 4)	–	0.079	–	–	2.0	–
R (Note 4)	–	0.441 (Note 5)	–	–	11.2 (Note 5)	–
α (degrees)	–	90° (Note 5)	–	–	90° (Note 5)	–
β (degrees)	–	120° (Note 5)	–	–	120° (Note 5)	–

NOTES:

(1) The theoretical cylinder with dimension A_1 delineates the demarcation between the space that may be occupied by parts of the base (for example, side-solder) and the space that may be occupied by rigid parts of the lampholder.

(2) The value L min does not apply in the area of the three supporting bosses and the optional notch.

(3) The slot in the barrel and the notch in the flange are optional.

(4) Dimensions Q and R are reference dimensions. The shape of the barrel-to-flange transition is optional, provided the contour does not exceed a line connecting the traces of the circles delineated by the actual dimension A at distance Q from the reference plane and dimension R on the flange.

(5) These values are solely for base design and are not to be gauged on the finished lamp.

Gauging

Gauges have not been developed for this base.

Lampholder


A lampholder standard has not been developed for use with this base standard.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

P28 Medium Prefocus Base

The designation assigned to this base in accordance with the system of the International Electrotechnical Commission (IEC) is P28/25. This base is very similar to the one referred to as P28/24 in IEC Publication 61. There are minor differences in dimensions A, B, and G. Nevertheless, the IEC standard includes the American values as future objectives so that the difference will be eliminated eventually.

The drawing is intended only to indicate the dimensions to be controlled.



The winged flanges of the base shell are the intended means of location of the lamp filament position. The top surface of the flanges determines the vertical location; the diameter determines the lateral location; and the leading edge of the larger flange determines the rotational alignment.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

	Standard Dimensions (inches)						Nearest Metric Equivalent (millimeters)					
	Unmounted (Note 3)			On Finished Lamps			Unmounted (Note 3)			On Finished Lamps		
Reference	Min	Nom	Max	Min	Nom	Max	Min	Nom	Max	Min	Nom	Max
A	1.065	–	1.085	1.065	–	1.090	27.05	–	27.56	27.05	–	27.69
B	0.945	–	0.985	–	–	–	24.00	–	25.02	–	–	–
B_1	–	–	–	0.953	–	1.025	–	–	–	24.21	–	26.04
C	1.313	–	1.333	1.313	–	1.336	33.35	–	33.86	33.35	–	33.93
D	–	–	1.116	–	–	1.116	–	–	28.35	–	–	28.35
G	0.030	–	0.060	0.030	–	0.060	0.76	–	1.52	0.76	–	1.52
J	–	–	0.886	–	–	0.886	–	–	22.50	–	–	22.50
K	–	0.44 approx	–	–	0.44 approx	–	–	11.18 approx	–	–	11.18 approx	–
L	–	–	1.085	–	–	1.085	–	–	27.56	–	–	27.56
M	–	–	–	0.118	–	–	–	–	–	3.00	–	–
N (Note 1)	0.354	–	–	0.354	–	–	9.00	–	–	9.00	–	–
r	–	–	0.010	–	–	0.010	–	–	0.25	–	–	0.25
α (degrees)	59°	–	61°	59°	–	61°	–	–	–	–	–	–
β (degrees)	79°	–	81°	79°	–	81°	–	–	–	–	–	–

NOTES:
(1) Dimension N denotes the minimum length over which both the minimum and maximum limits of dimension A apply; below this length, dimension L applies.
(2) The creepage distance over the insulation on finished lamps shall not be less than 0.118 in (3 mm).
(3) These dimensions are solely for base design and are not to be gauged on the finished lamp.

Gauging
When a lamp is fully inserted into Gauge 3-700 and the flanges pressed to surface x, the contact making surface shall reach to surface y, but shall not project beyond surface z. During insertion, the force shall not exceed 1 lbf (4.45 N).

See ANSI C81.63 for gauges.

Lampholder
See ANSI C81.62, Standard Sheet 2-700.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

P30 Candelabra Prefocus Bases

This standard sheet covers both single- and double-contact prefocus bases.

The designations assigned by the International Electrotechnical Commission (IEC) to the single-contact prefocus base is P30s-10.3 and the double-contact base is P30d-10.3 (see Note 5).

This base standard differs from a similar single-contact version covered by the IEC as P30s-10.3 in several ways. Diameter F of the focusing collar has a broader tolerance, and the tapered slot is slightly larger; these differences exist because applications in the United States have not required the high precision of focusing that other lamps need. The major shell diameter of this base is approximately 0.003 inch larger than the IEC version; this relates to a long-standing difference in the basic BA15 base designs between Europe and the United States.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.




Figure 1
Double-Contact Base

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale




Figure 2
Single-Contact Base

Slot Data (Note 8)

Slot Angle * (degrees)	Diameter	
	Inch	Millimeters
10	0.091	2.31
13	0.103	2.62
16	0.115	2.92
19	0.127	3.23
22	0.139	3.53
25	0.151	3.84
28	0.163	4.14
31	0.175	4.45
34	0.187	4.75
37	0.200	5.08

* Measured from 0 degree reference.




Figure 3
Slot Detail

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Reference	Standard Dimensions (inches)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A	–	–	0.6025	–	–	15.30
B (Note 5)	0.356	–	0.456	9.04	–	11.58
C	0.006	–	0.012	0.15	–	0.30
D (Note 9)	0.741	–	0.760	18.82	–	19.30
E (Note 9)	0.059	–	–	1.50	–	–
F (dia)	1.180	–	1.186	29.98	–	30.12
G	–	–	0.044	–	–	1.11
H	0.177	–	0.205	4.50	–	5.20
J	0.047	–	–	1.19	–	–
K	0.255	–	0.279	6.48	–	7.08
L (Note 9)	–	0.031	–	–	0.79	–
M	0.121	–	0.129	3.07	–	3.27
N	0.086	–	0.096	2.18	–	2.43
P (dia) (Note 9)	–	0.093	–	–	2.36	–
Q (dia)	0.895	–	0.898	22.73	–	22.81
R (Note 9)	–	–	0.670	–	–	17.01
r (Note 9)	–	0.093	–	–	2.36	–
S (Note 6)	0.015	–	–	0.38	–	–
ϕ (degrees) (Note 9)	–	115°	–	–	115°	–
σ (degrees) (Note 9)	–	46.5°	–	–	46.5°	–
α (degrees)	98°	–	102°	98°	–	102°
β (degrees) (Note 9)	–	87°	–	–	87°	–
θ (degrees)	128°	–	132°	128°	–	132°

NOTES:

(1) On double-contact bases, the solder heights of the two contacts shall be within 0.020 inch (0.5 mm) of each other.

(2) On double-contact bases, the outer surfaces of the eyelets shall be coincident with or lie below the surface of the insulator.

(3) For base insulator retention. The configuration may vary.

(4) Flare optional. If used, the maximum diameter shall be 0.635 inch (16.12 mm).

(5) Dimension B specifies the standard position of the prefocus collar for a P30s-10.3 or P39d-10.3 base. The identifier following the hyphen (10.3) denotes the additional dimension that is essential for the fit. Other collar positions may be in use, but they are considered to be nonpreferred. They would require a new identifier following the hyphen. When applying for assignment of an American National Standard lamp designation, the collar position should be specified, by its particular identifier, as part of the base description.

(6) Applies to double-contact base only.

(7) The collar orientation and the tilt angle tolerance are determined by the individual lamp design.

(8) The slot data tolerances are ±1°, ±0.005 inch (±0.127 mm).

(9) These dimensions are for base collar design and are not to be gauged on finished lamps.

Gauging

When a lamp is inserted at opening X of gauge 3-709, the collar shall enter opening F_1. When inserted at opening Y, the collar shall not enter opening F_2.

See ANSI C81.63 for gauges.

Lampholder

See ANSI C81.62, Standard Sheet 2-709.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

P40 Mogul Prefocus Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is P40s/41.

There are several differences between this base and the one defined by the IEC as P40s/41. These differences have existed for a long time. The D max dimension is larger on this base; thus American lamps will not enter some European-made holders. This base has a looser tolerance on the maximum shell diameter A. Differences exist in dimensions K min, β min, and β max, but these are not critical to the fit.

The drawing is intended only to indicate the dimensions to be controlled.



The winged flanges, together with the base shell diameter, are the intended means of reference for the lamp filament position. The top surface of the flanges (reference plane x) determines the vertical location; the diameter of the base shell determines the lateral location; and the leading edges of the flanges (reference plane y) determine the rotational alignment.

On finished lamps the creepage distance over insulation shall be not less than 5 mm.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

	Standard Dimensions (inches)				Nearest Metric Equivalent (millimeters)			
	Unmounted (Note 1)		On Finished Lamps		Unmounted (Note 1)		On Finished Lamps	
Reference	Min	Max	Min	Max	Min	Max	Min	Max
A	1.543	1.557	1.543	1.559	39.19	39.54	39.19	39.60
B	1.610	1.640	–	–	40.90	41.66	–	–
B_1	–	–	1.610	1.701	–	–	40.90	43.21
C	1.984	2.008	1.984	2.012	50.40	51.00	50.40	51.10
D	–	1.631	–	1.635	–	41.43	–	41.53
G	0.060	0.076	0.060	0.076	1.52	1.93	1.52	1.93
J	–	1.398	–	1.398	–	35.50	–	35.50
K	0.511	0.906	–	–	12.97	23.01	–	–
M (Note 3)	–	–	0.118	–	–	–	3.00	–
N (Note 2)	0.500	–	0.500	–	12.70	–	12.70	–
P	–	0.125	–	0.125	–	3.18	–	3.18
r	–	0.010	–	0.010	–	0.25	–	0.25
β (degrees)	69°	71°	69°	71°	69°	71°	69°	71°

NOTES:
(1) These dimensions are solely for base design and shall not be gauged on the finished lamp.
(2) Dimension N denotes the minimum length over which both the minimum and maximum limits of dimension A shall be observed, with the exception of the retaining groove area; below this, only the limits for A maximum shall apply.
(3) Controls neck clearance required by fit to lampholder.

Gauging

When a lamp is fully inserted into Gauge 3-715, and the flanges pressed to surface x, the contact making surface shall reach to surface y, but shall not project beyond surface x. During insertion, the force shall not exceed 10 lbf (44.5 N).

See ANSI C81.63 for gauges.

Lampholder

See ANSI C81.62, Standard Sheet 2-715.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale


R7s Recessed Single-Contact Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is R7s. This standard sheet is nearly equivalent to IEC Publication 61.


The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawings are intended only to indicate the dimensions to be controlled.

Type A Base



Type B Base



NOTE: The centerline shown is the line passing through the center of the contacts at the two ends of the lamp.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Reference	Standard Dimension (inch) Min	Max	Nearest Metric Equivalent (millimeters) Min	Max
E	–	0.295	–	7.49
F	0.165	–	4.19	–
G	0.110	–	2.79	–
H	0.070	0.110	1.78	2.79
J	(Note 1)	0.080	(Note 1)	2.03
K (Note 2)	–	0.290 (T3)	–	7.37 (T3)
	–	0.355 (T4)	–	9.02 (T4)
	–	0.420 (T5)	–	10.67 (T5)
	–	0.440 (T6)	–	11.18 (T6)
L	0.115	–	2.92	–
M (Note 3)	–	0.160	–	4.06
Q (Note 4)	–	0.360	–	9.14
P (Note 5)	0.195	–	4.95	–
S	–	(Note 6)	–	–

NOTES:

(1) The minimum for dimension J is determined by the requirement that a test probe having a hemispherical end with a radius of 0.205 inch (5.21 mm) shall not be able to touch the metal contact.

(2) Includes eccentricity of bulb with respect to the centerline. Dimension K is shown separately for T3, T4, T5, and T6 bulb lamps.

(3) Includes eccentricity of insulator with respect to the centerline.

(4) The two lamp bases shall be aligned to fit between two parallel planes spaced 0.370 inch (9.40 mm) apart [objective for future design of Type B bases].

(5) This dimension shall be measured at a reference diameter of 0.295 inch (7.49 mm).

(6) The thickness of this part of the lamp must be such as to fit the gauge shown in American National Standard for Electric Lamps – Tubular Tungsten-Halogen Lamps – Physical Characteristics, ANSI C78.260-1985.

Gauging

Gauges have not been developed for this base.

Lampholder

See ANSI C81.62, Standard Sheet 2-770.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale


R17d Recessed Double-Contact Base

ANSI C81.61-1990
Std Sheet 1-777-1

The designation assigned to this base by the International Electrotechnical Commission (IEC) is R17d. This standard sheet is equivalent to IEC Publication 61.

The drawing is intended only to indicate the dimensions to be controlled.

These bases are used on fluorescent lamps with T12, PG17, and TH17 bulbs.



Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Reference	Standard Dimensions (inches)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A (Note 1)	0.343	–	–	8.71	–	–
D	–	–	0.075	–	–	1.90
D_1 (Note 2)	0.036	–	–	0.91	–	–
E (Note 3)	0.335	–	0.350	8.51	–	8.89
F (Note 4)	0.307	–	0.320	7.80	–	8.13
G (Note 3)	0.640	–	0.658	16.26	–	16.71
H	0.088	–	–	2.24	–	–
J	0.201	–	–	5.11	–	–
K	0.272	–	0.285	6.91	–	7.24
M (Note 5)	1.250	–	–	31.75	–	–
N	0.250	–	–	6.35	–	–
S	0.040	–	–	1.02	–	–
T (Note 6)	–	–	0.800 (T12)	–	–	20.32 (T12)
	–	–	1.110 (PG17)	–	–	28.19 (PG17)
	–	–	1.110 (TH17)	–	–	28.19 (TH17)
U (Note 7)	–	–	1.438 (T12)	–	–	36.53 (T12)
	–	–	2.040 (PG17)	–	–	51.82 (PG17)
	–	–	2.040 (TH17)	–	–	51.82 (TH17)
Z (Note 8)	0.896	–	–	22.76	–	–
r	–	0.05	–	–	1.27	–
r_1	0.030	–	–	0.76	–	–
r_2	0.020	–	0.050	0.51	–	1.27

NOTES:
(1) Represents length of base over which dimension U is applicable.
(2) Includes solder or weld pip.
(3) Dimensions E and G are measured at a point 0.050 inch (1.27 mm) from flat surface of base.
(4) Dimension F is from the highest flat surface of the base to the end of the boss.
(5) Represents length of lamp over which dimension T is applicable.
(6) The T dimension includes allowance for possible offset of the bulb axis with respect to the base axis. This dimension is shown separately for T12, PG17, and TH17 bulb lamps.
(7) Maximum base shell diameter (U) is shown separately for T12, PG17, and TH17 bulb lamps.
(8) The base face should be reasonably smooth, surrounding the contact boss and within the area defined by dimension Z, to provide a gasket seating surface.

Clearance for Live Parts

The base contacts shall be recessed so that they cannot be touched by a test probe having a hemispherical end with a radius of 0.205 inch (5.2 mm).

Gauging

When the "go" end of Gauge 3-777 is inserted into a lamp base recess, it shall seat on surface x without binding. The "Not go" end of the gauge shall not enter.

See ANSI C81.63 for gauges.

Lampholder

See ANSI C81.62, Standard Sheet 2-777.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

SX4 Submidget Flanged Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is SX4. At the time of publication, there was no comparable IEC standard in existence.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.



(a) Primary Design *(b) Alternate Design*

Reference	Standard Dimensions (inch) Min	Max	Nearest Metric Equivalent (millimeters) Min	Max
A	0.153	0.159	3.89	4.04
B	0.176	0.186	4.47	4.72
C	0.017	0.023	0.43	0.58
D	0.051	0.059	1.30	1.50
D_1 (Note 2)	0.061	0.085	1.55	2.16
E	0.101	0.107	2.57	2.72
F	0.013*	0.017*	0.33*	0.43*
G	0.146	0.154	3.71	3.91
N (Note 3)	0.125*	–	3.18*	–
r	–	0.030*	–	0.76*

NOTES:

(1) Chamfer or radius optional.

(2) This dimension includes solder.

(3) Inside diameter of base.

(4) A solder hole in the cylindrical part of the shell is permissible, except that on finished lamps, the diameter, including the solder, shall not exceed A max.

* Solely for base design, not to be gauged on a finished lamp.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Gauging
When Gauge 3-850 is placed over the bulb end of a finished lamp (bulb end up), the gauge shall drop to the base's flange. Only the mass (weight) of the gauge itself shall be used. While the bottom of the gauge is in contact with the flange, the upper rim of the base shall not project beyond the uppermost surface of the gauge.

When Gauge 3-851 is placed over the bulb end of a finished lamp (bulb held up), the gauge shall not pass beyond the chamfered or curved section of the base's rim. Only the mass (weight) of the gauge itself shall be used.

See ANSI C81.63 for gauges.


Lampholder
See ANSI C81.62, Standard Sheet 2-850.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

S5.7 Midget Grooved Base

The designation assigned to this base by the International Electrotechnical Commission (IEC) is S5.7s. This standard sheet is nearly equivalent to IEC Publication 61.

The drawing is intended only to indicate the dimensions to be controlled.



Reference	Standard Dimensions (inch) Min	Max	Nearest Metric Equivalent (millimeters) Min	Max
A (Note 3)	0.219	0.229	5.56	5.82
A_1	–	0.259	–	6.58
B	0.217	0.225	5.51	5.72
C	0.031	–	0.8	–
D (Note 1)	0.067	0.106	1.7	2.7
D_1 (Note 2)	0.094	0.130	2.4	3.3
F (Notes 1,4)	0.189	0.200	4.8	5.08
H	–	0.125	–	3.2
M (Note 1)	0.319	0.341	8.10	8.65
Y	–	0.090	–	2.3
r (Note 1)	0.015	0.020	0.38	0.51

NOTES:

(1) These dimensions are solely for base design and are not to be gauged on the finished lamp.

(2) This dimension includes solder.

(3) Bases may be made with a flare the diameter of which shall not be more than 0.020 inch (0.5 mm) greater than A max.

(4) Dimension F is the root diameter of the groove.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Gauging
Gauges have not been developed for this base.

Lampholder
A lampholder standard has not been developed for use with this base standard.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS


Not for Resale

SX6 Midget Flanged Base

The designation assigned to the base by the International Electrotechnical Commission (IEC) is SX6. This standard sheet is nearly equivalent to IEC Publication 61.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.



Reference	Standard Dimensions (inch)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A	0.240	–	0.250	6.10	–	6.35
B	0.280	–	0.290	7.11	–	7.37
C	0.024	–	–	0.60	–	–
D (Note 3)	0.057	–	0.076	1.45	–	1.93
D_1 (Note 4)	0.067	–	0.110	1.70	–	2.80
E	0.250	–	0.270	6.35	–	6.86
G	0.245	–	0.275	6.22	–	6.98
H	0.100	–	0.130	2.54	–	3.30
N	–	0.214	–	–	5.44	–

NOTES:

(1) An access hole or indentation for soldering in the cylindrical part of the shell is permissible except that, on finished lamps, the diameter A max shall not be exceeded, including the solder.

(2) An edge with a radius is required in order that a grip may be obtained with fingernails during removal of a lamp. A chamfer or other suitable shape is permissible as an alternative.

(3) These dimensions are solely for base design and are not to be gauged on the finished lamp.

(4) This dimension includes solder.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Gauging
Gauges have not been developed for this base.


Lampholder
A lampholder standard has not been developed for use with this base standard.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

T7.2-1 Telephone Slide Base No. 1 for T2 Lamps

The designation assigned to this base in accordance with the coding system of the International Electrotechnical Commission (IEC) is T7.2-1. At the time of publication there was no comparable IEC standard in existence.

The drawing is intended only to indicate the dimensions to be controlled.





Reference	Standard Dimensions (inches)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A	0.270	–	0.300	6.86	–	7.62
A_1	–	–	0.234	–	–	5.94
B	–	–	0.265	–	–	6.73
B_1	0.205	–	0.245	5.21	–	6.22
C	–	0.422	–	–	10.72	–
H	0.078	–	–	1.98	–	–
J	–	–	0.260	–	–	6.60
K	–	0.156	–	–	3.97	–
K_1	–	0.141	–	–	3.58	–
L	–	–	0.531	–	–	13.49
OAL	–	1.188	–	–	30.18	–
R	–	0.031	–	–	0.79	–
α	–	80°	–	–	80°	–

Gauging
Gauges have not been developed for this base.

Lampholder
A lampholder standard has not been developed for use with this base standard.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

T7.2-2 Telephone Slide Base No. 2 for T2 Lamps

The designation assigned to this base in accordance with the coding system of the International Electrotechnical Commission (IEC) is T7.2-2. At the time of publication there was no comparable IEC standard in existence.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.



Reference	Standard Dimensions (inches) Min	Nom	Max	Nearest Metric Equivalent (millimeters) Min	Nom	Max
A	0.270	–	0.300	6.86	–	7.62
A_1	–	–	0.234	–	–	5.94
B	–	–	0.270	–	–	6.86
H	0.078	–	–	1.98	–	–
J	–	–	0.275	–	–	6.99
OAL	–	1.188	–	–	30.18	–
α	–	90°	–	–	90°	–

NOTE: Sides may be flat or have a slight radius.

Gauging

Gauges have not been developed for this base.

Lampholder

A lampholder standard has not been developed for use with this base standard.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale


T7.2-3 Telephone Slide Base No. 3 for T2 Lamps

The designation assigned to this base in accordance with the coding system of the International Electrotechnical Commission (IEC) is T7.2-3. At the time of publication there was no comparable IEC standard in existence.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.





Reference	Standard Dimensions (inches)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A	0.270	–	0.300	6.86	–	7.62
A_1	–	–	0.234	–	–	5.94
B	–	–	0.270	–	–	6.86
B_1	0.205	–	0.245	5.21	–	6.22
H	0.078	–	–	1.98	–	–
J	–	–	0.275	–	–	6.99
L	–	–	0.531	–	–	13.49
OAL	–	1.188	–	–	30.18	–
R (rad.)	–	0.031	–	–	0.79	–
α	–	90°	–	–	90°	–

Gauging

Gauges have not been developed for this base.

Lampholder

A lampholder standard has not been developed for use with this base standard.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS


Not for Resale

T7.2-5 Telephone Slide Base No. 5 for T2 Lamps

The designation assigned to this base in accordance with the coding system of the International Electrotechnical Commission (IEC) is T7.2-5. At the time of publication there was no comparable IEC standard in existence.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.



Reference	Standard Dimensions (inches)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A	0.270	–	0.300	6.86	–	7.62
A_1	–	–	0.234	–	–	5.94
B	–	–	0.280	–	–	7.11
C	–	0.219	–	–	5.56	–
H	0.078	–	–	1.98	–	–
J	–	–	0.245	–	–	6.22
OAL	–	0.656	–	–	16.67	–
R	–	0.375	–	–	9.53	–
R_1	–	0.046	–	–	1.17	–
α	–	80°	–	–	80°	–

Gauging
Gauges have not been developed for this base.

Lampholder
A lampholder standard has not been developed for use with this base standard.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

T7.2-6 Telephone Slide Base No. 6 for T2 Lamps

The designation assigned to this base in accordance with the coding system of the International Electrotechnical Commission (IEC) is T7.2-6. At the time of publication there was no comparable IEC standard in existence.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.



Reference	Standard Dimensions (inches)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A	0.270	–	0.300	6.86	–	7.62
A_1	–	–	0.234	–	–	5.94
H	0.078	–	–	1.98	–	–
J	–	–	0.245	–	–	6.22
OAL	–	0.625	–	–	15.88	–
α	–	72°	–	–	72°	–

Gauging
Gauges have not been developed for this base.

Lampholder
A lampholder has not been developed for use with this base standard.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

T7.2-7 Telephone Slide Base No. 7 for T2 Lamps

The dimension assigned to this base in accordance with the coding system of the International Electrotechnical Commission (IEC) is T7.2-7. At the time of publication there was no comparable IEC standard in existence.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.



Reference	Standard Dimensions (inches)			Nearest Metric Equivalent (millimeters)		
	Min	Nom	Max	Min	Nom	Max
A	0.270	–	0.300	6.86	–	7.62
A_1	–	–	0.234	–	–	5.94
B	–	–	0.165	–	–	4.19
C	–	–	0.531	–	–	13.49
H	0.078	–	–	1.98	–	–
J	–	0.260	–	–	6.60	–
OAL	–	1.188	–	–	30.16	–

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Gauging
Gauges have not been developed for this base.

Lampholder
A lampholder standard has not been developed for use with this base standard.


Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

T7.2-8 Telephone Slide Base No. 8 for T2 Lamps

The designation assigned to this base in accordance with the coding system of the International Electrotechnical Commission (IEC) is T7.2-8. At the time of publication there was no comparable IEC standard in existence.

The dimensions shown on this sheet apply to finished bases after assembly on lamps.

The drawing is intended only to indicate the dimensions to be controlled.



	Standard Dimensions (inches)			Nearest Metric Equivalent (millimeters)		
Reference	Min	Nom	Max	Min	Nom	Max
A	0.270	–	0.300	6.86	–	7.62
A_1	–	–	0.234	–	–	5.94
B	–	–	0.245	–	–	6.22
C	–	–	0.531	–	–	13.49
H	0.078	–	–	1.98	–	–
J	–	–	0.245	–	–	6.22
OAL	–	1.250	–	–	31.75	–

Gauging

Gauges have not been developed for this base.

Lampholder

A lampholder standard has not been developed for use with this base standard.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Appendix

(This Appendix is not part of American National Standard C81.61-1990, but is included for information only.)

Former Designations of C81 Standards

LAMP BASES

Code	Common Name	Standard Sheet Number	Former Standard Sheet Number	Former ANSI Standard
BA9	Miniature Bayonet Base	1-10-1	1-1	C81.30a-1983
BA15s, BA15d	Candelabra, Single-Contact and Double-Contact Bayonet Bases	1-20-1	1-3	C81.30d-1986
BAY15s, BAY15d	–	1-22-1	1-11	C81.30d-1986
BAZ15d	–	1-23-1	1-12	C81.30d-1986
BY22d	–	1-30-1	1-15	C81.30c-1986
E5	Midget Screw Base	1-100-1	1-1	C81.10a-1979
E10	Miniature Screw Base	1-111-1	1-3	C81.10-1976
E11	Mini-Can Screw Base	1-123-1	1-5	C81.10a-1979
E12	Candelabra Screw Base	1-131-1	1-7	C81.10d-1986
E17	Intermediate Screw Base	1-144-1	1-9	C81.10d-1986
E26/24	Single-Contact Medium Screw Base	1-157-1	1-11	C81.10d-1986
E26d	Double-Contact Medium Screw Base	1-158-1	1-13	C81.10d-1986
E26/50 × 39	Skirted Medium Screw Base	1-159-1	1-15	C81.10c-1983
E26/53 × 39	Special Skirted Medium Screw Base	1-162-1	New	–
E39	Mogul Screw Base	1-185-1	1-17	C81.10d-1986
E39d	Double-Contact Mogul Screw Base	1-187-1	New	–
EP39	Position-Oriented Mogul Screw Base	1-202-1	1-19	C81.10b-1983
Fa8	Single-Pin Base	1-250-1	1-1	C81.20-1976
G1.3–2.4	Subminiature Bipin Base (T3/4)	1-288-1	1-3	C81.50-1976
G1.3–3.2	Subminiature Bipin Base (T1)	1-291-1	1-5	C81.50-1976
G2.5	Subminiature Bipin Base (T1-1/4)	1-294-1	1-7	C81.50-1976
G3.2	Subminiature Bipin Base (T1-3/4)	1-297-1	1-9	C81.50-1976
G3.9	–	1-300-1	1-15	C81.40b-1983
G5	Miniature Bipin Base	1-310-1	1-3	C81.20-1976
G5.3	–	1-320-1	1-1	C81.40-1976
GX5.3	–	1-321-1	1-2	C81.40d-1986
GY5.3	–	1-322-1	1-4	C81.40d-1986
G6.35/GY6.35	–	1-340-1	1-3	C81.40-1976
GZ6.35	–	1-342-X*	–	–
G7.9/GX7.9	–	1-356-1	1-5	C81.40c-1983
G9.5	–	1-368-1	1-7	C81.40c-1983
GY9.5/GZ9.5	–	1-369-1	1-9	C81.40d-1986
G10q	Four-Pin Circular Fluorescent Lamp Base	1-383-1	1-9	C81.20b-1985
2G11	–	1-393-1	New	–

*No standard sheet has been issued for this item. The sheet number is held in reserve.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Code	Common Name	Standard Sheet Number	Former Standard Sheet Number	Former ANSI Standard
G13	Medium Bipin Base	1-406-1	1-5	C81.20c-1977
2G13	U-Shaped Fluorescent Base	1-420-1	1-6	C81.20
GX16d	Mogul and Extended Mogul-End Prong Bases	1-430-1	1-17	C81.40
GX16d	Termination	1-431-1	1-19	C81.40
G17t	Tri-Pin Prefocus Base	1-439-1	1-10	C81.30a-1983
G17q/GX17q	Four-Pin Prefocus Base	1-440-1	1-9	C81.30-1976
G20	Mogul Bipin Base	1-452-1	1-7	C81.20-1976
G22	Medium Bipost Base	1-466-1	1-11	C81.40a-1979
G23	–	1-475-1	1-17	C81.20c-1987
GX23	–	1-476-1	1-19	C81.20c-1987
G24d/G24q	–	1-493-1	New	–
G32/GX32	–	1-506-X*	New	–
G38	Mogul Bipost Base	1-519-1	1-13	C81.40-1976
P13.5s	Single-Contact Miniature Flanged Base	1-600-1	1-2	C81.30d-1986
P28	Medium Prefocus Base	1-700-1	1-5	C81.30b-1983
P30	Candelabra Prefocus Base	1-709-1	1-4	C81.30a-1983
P40	Mogul Prefocus Base	1-715-1	1-7	C81.30a-1983
R7s	Recessed Single-Contact Base	1-770-1	1-1	C81.50-1976
R12.5	–	1-774-X*	–	–
R17d	Recessed Double-Contact Base	1-777-1	1-11	C81.20a-1984
SX4	Submidget Flanged Base	1-850-1	1-2	C81.50b-1983
S5.7	Midget Grooved Base	1-856-1	1-26	C81.50c-1985
SX6	Midget Flanged Base	1-862-1	1-25	C81.50c-1985
T7.2-1	Telephone Slide Base No. 1	1-875-1	1-11	C81.50a-1981
T7.2-2	Telephone Slide Base No. 2	1-876-1	1-13	C81.50a-1981
T7.2-3	Telephone Slide Base No. 3	1-877-1	1-15	C81.50a-1981
T7.2-5	Telephone Slide Base No. 5	1-878-1	1-17	C81.50a-1981
T7.2-6	Telephone Slide Base No. 6	1-879-1	1-19	C81.50a-1981
T7.2-7	Telephone Slide Base No. 7	1-880-1	1-21	C81.50a-1981
T7.2-8	Telephone Slide Base No. 8	1-881-1	1-23	C81.50a-1981

*No standard sheet has been issued for this item. The sheet number is held in reserve.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale