6470247 0521070 T38

ADOPTION NOTICE

National Electrical Manufacturers Association (NEMA) Standard NEMA WC 66, "Performance Standard for Category 6 and Category 7 100 Ohm Shielded and Unshielded Twisted Cable Pairs," was adopted on 21 January 2000 for use by the Department of Defense (DoD). Proposed changes by DoD activities must be submitted to the DoD Adopting Activity: Defense Logistics Agency, Defense Supply Center, Columbus, ATTN: DSCC-VAI, P.O. Box 3990, Columbus, OH 43216-5000. DoD activities may obtain copies of this standard from the Defense Automated Printing Service, DODSSP, 700 Robbins Avenue, Building 4, Section D, Philadelphia, PA 19111-5094. The private sector and other Government agencies may purchase the document from the National Electrical Manufacturers Association, 1300 North 17th Street, Suite 1847, Rosslyn, VA 22209.

CONCLUDING MATERIAL

Custodians:
DLA – CC

Adopting Activity:
DLA – CC

(Project 6145-2221)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

STD.NEMA WC 66-ENGL 1999 ■ 6470247 0516023 87T ■

NEMA STANDARDS PUBLICATION

NEMA WC 66

PERFORMANCE STANDARD FOR CATEGORY 6 AND CATEGORY 7 100 OHM SHIELDED AND UNSHIELDED TWISTED PAIR CABLES

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

NEMA Standards Publication No. WC 66-1999

Performance Standard for Category 6 and Category 7
100 Ohm Shielded and Unshielded
Twisted Pair Cables

Published by:

National Electrical Manufacturers Association
1300 North 17th Street
Rosslyn, Virginia 22209

© Copyright 1999 by the National Electrical Manufacturers Association. All rights including translation into other languages, reserved under the Universal Copyright Convention, the Berne Convention for the Protection of Literary and Artistic Works, and the International and Pan American Copyright Conventions.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

TABLE OF CONTENTS

Foreword iv
Scope v

Section 1 REFERENCE STANDARDS 1

Section 2 PART IDENTIFICATION NUMBER (PIN) 3
2.1 Part Identification Number (PIN) 3

Section 3 MATERIALS AND MECHANICAL REQUIREMENTS 5
3.1 Conductors 5
3.1.1 Bare Copper Wire 5
3.1.2 Tin-Coated Copper Wire 5
3.1.3 Silver-Coated Copper Wire 5
3.1.4 Stranded Copper Wire 5
3.2 Insulating Materials 5
3.3 Shields 5
3.3.1 Individually Shielded Pairs, Foil 5
3.3.2 Individually Shielded, Pairs, Braid 6
3.3.3 Overall Shield, Foil 6
3.3.4 Overall Shield, Braid 6
3.3.5 Drain Wire(s) 6
3.3.6 Braid Shield 6
3.4 Mechanical, Physical, Dimensional, and Safety Considerations 6

Section 4 ELECTRICAL DEFINITIONS 7
4.1 Resistance 7
4.1.1 DC Conductor Resistance 7
4.1.2 DC Resistance Unbalance 7
4.1.3 Insulation Resistance 7
4.2 Input Impedance 7
4.3 Characteristic Impedance 7
4.4 Return Loss 8
4.5 Attenuation 8
4.6 Crosstalk Loss 8
4.6.1 Near-End Crosstalk Loss 8
4.6.2 Power Sum Near-End Crosstalk Loss 9
4.6.3 Equal Level Far-End Crosstalk Loss 9
4.6.4 Power Sum Equal Level Far-End Crosstalk Loss 10
4.7 Attenuation Crosstalk Ratio 10
4.7.1 Power Sum Attenuation To Crosstalk Ratio 10
4.8 Transfer Impedance 10
4.9 Phase Velocity 11
4.10 Phase Delay 11
4.11 Phase Delay Skew 11
4.12 Balance 11
4.12.1 Longitudinal Conversion Loss 11
4.12.2 Longitudinal Conversion Transfer Loss 11

Section 5 TEST METHODS 13
5.1 General 13
5.2 Input Impedance 13

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

5.3 Characteristic Impedance 13
5.4 Return Loss 13
5.5 Attenuation 13
5.6 Near-End Crosstalk/Power Sum Near-End Crosstalk Loss 13
5.7 Equal Level Far-End Crosstalk Loss/Power Sum Equal Level Far-End Crosstalk Loss 13
5.8 Attenuation To Crosstalk Ratio / Power Sum Attenuation To Crosstalk Ratio 14
5.9 Transfer Impedance 14
5.10 Phase Velocity 14
5.11 Phase Delay 14
5.12 Phase Delay Skew 14
5.13 Balance 14
5.13.1 Longitudinal Conversion Loss 14
5.13.2 Longitudinal Conversion Transfer Loss 14

Section 6 ELECTRICAL REQUIREMENTS 15
6.1 General 15
6.2 Resistance 15
6.2.1 DC Resistance 15
6.2.2 DC Resistance Unbalance 15
6.2.3 Insulation Resistance 15
6.3 Impedance 15
6.3.1 Input Impedance 15
6.3.2 Characteristic Impedance 16
6.4 Return Loss 16
6.5 Attenuation 16
6.5.1 Horizontal and Backbone Cables 16
6.5.2 Patch (Stranded) Cables 17
6.6 Crosstalk Loss 17
6.6.1 Near-End Crosstalk Loss 17
6.6.2 Power Sum Near-End Crosstalk Loss 18
6.6.3 Equal Level Far-End Crosstalk Loss 18
6.6.4 Power Sum Equal Level Far-End Crosstalk Loss 19
6.7 Attenuation to Crosstalk Ratio 19
6.7.1 Power Sum Attenuation To Crosstalk Ratio 19
6.8 Transfer Impedance 19
6.9 Phase Velocity 20
6.10 Phase Delay Skew 20
6.11 Balance 20
6.11.1 Longitudinal Conversion Loss 20
6.11.2 Longitudinal Conversion Transfer Loss 20

Appendix A ELECTRICAL PERFORMANCE REQUIREMENTS AND REFERENCES FOR CATEGORY 6 AND CATEGORY 7 CABLES 21

Tables 2-1a NEMA Category Designation 3
2-1b NEC/CSA Types 3
2-2a Allowable AWG Sizes for Solid Conductors in Horizontal and Backbone Cable 4
2-2b Allowable AWG Sizes for Stranded Conductors in Patch Cords 4
2-3 Allowable Shielding Options 4
6-1 DC Resistance 15
6-2 Input Resistance 15
6-3 Characteristic Impedance 16
6-4 Return Loss 16

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

6-5 Coefficients for Attenuation Formula 17
6-6 Phase Velocity 20
6-7 Phase Delay Skew 20

A-1a Requirements for Electrical Performance of Category 6 Cables 21
A-1b Reference for Electrical Performance of Category 6 Cables 22
A-2a Requirements for Electrical Performance of Category 7 Cables 23
A-2b Reference for Electrical Performance of Category 7 Cables 24

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Foreword

This standard is one of a series of standards developed by NEMA on cables to be used for voice, data, video, and other high-frequency signal transmission. The other standards are NEMA WC 63.1, "Performance Standard for Twisted Pair Premise Voice and Data Communications Cable" and ANSI/NEMA WC 63.2, "Performance Standard for Coaxial Premise Data Communications Cable."

The user's attention is called to the possibility that compliance with this standard may require use of an invention covered by patent rights. By publication of this standard, no position is taken with respect to the validity of this claim or of any patent rights in connection therewith. The patent holder has, however, filed a statement of willingness to grant a license under these rights on reasonable and non-discriminatory terms and conditions to applicants desiring to obtain such a license. Details may be obtained from the publisher.

This standard has been developed by the Premise Wiring Subcommittee (members as listed below) of the High Performance Wire and Cable Section of NEMA, in close coordination between manufacturers, users, third-party certifying agencies, and others having specialized experience. The Premise Wiring Subcommittee of the High Performance Wire and Cable Section of NEMA periodically reviews this standard for any revisions necessary to keep it up to date. Proposed revisions or comments should be submitted to:

Vice President, Engineering Department
National Electrical Manufacturers Association
1300 North 17th Street
Rosslyn, Virginia 22209

Members of NEMA High Performance Wire and Cable Section that participated in the development of this standard were:

Alcatel Electronics Cable—Elm City, NC
Belden Wire & Cable Company—Richmond, IN
BICC Brand-Rex Company—Willimantic, CT
Coleman Cable CCI—North Chicago, IL
CommScope Network Cable Division—Claremont, NC
General Cable Corporation—Highland Heights, KY
Harbour Industries—Shelburne, VT
Helix/Hi-Temp Cables, Inc.—Franklin, MA
Hitachi Cable Manchester, Inc.—Manchester, NH
Judd Wire Inc.—Turner Falls, MA
Lucent Technologies—Norcross, GA
Mohawk/CDT—Leominster, MA
Montrose/CDT—Auburn, MA
Nordx/CDT—Pointe-Claire, PQ Canada
Prestolite Wire—Port Huron, MI
Remee Products—Florida, NY
Southwire Company—Carrollton, GA

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Scope

This standard primarily defines minimum electrical performance and allowable conductor sizes, stranding and shielding for premise wiring cables for voice and data applications for 100 ohm shielded and unshielded twisted pair cables. The cables included in this standard are intended to conform with the cabling system architecture and design as specified in ANSI/TIA/EIA 568A and to harmonize with international standards such as ISO/IEC 11801. These cables have improved return loss (RL) and crosstalk loss performance requirements beyond the Category 5 values in NEMA WC 63.1. These cables may be used for voice, data, and video applications whose spectral bandwidth extends up to 200 MHz for Category 6 and 600 MHz for Category 7. These cables are tested at a frequency 25% greater than the spectral bandwidth specified above: 250 MHz for Category 6 and 750 MHz for Category 7. Applicable definitions, test methods, and performance requirements are included. The material and mechanical characteristics for these cables are covered under UL 444/CSA 22.2 No. 214 based on the flame and smoke requirements.

Unless otherwise specified, the constructions defined herein are 2 through 25 pair cables and 22 through 26 AWG, including patch cords.

This document complements other specifications by including, for the first time, a part numbering system to assist in procurement of these types of cables.

The products covered in this standard shall conform to the requirements of Part 68 of the FCC rules and regulations, as well as the applicable article(s) of the National Electrical Code and/or other national and local codes and safety standards.

The performance requirements contained in this document are for cables as manufactured. Link and channel requirements are beyond the scope of this document.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Section 1
REFERENCED STANDARDS

Copies of referenced documents may be obtained from the appropriate sources as follows.

American Society for Testing and Materials (ASTM)
100 Barr Harbor Drive
West Conshohocken, PA 19428-2959

ASTM B 3-95	*Soft or Annealed Copper Wire*
ASTM B 8-95	*Concentric-Lay-Stranded Copper Conductors, Hard, Medium-Hard, or Soft*
ASTM B 33-94	*Tinned Soft or Annealed Copper Wire for Electrical Purposes*
ASTM B 286-95	*Copper Conductors for Use in Hookup Wire for Electronic Equipment*
ASTM B 298-94	*Standard Specification for Silver-Coated Soft or Annealed Copper Wire*
ASTM D 4566-94	*Standard Test Methods for Electrical Performance Properties of Insulations and Jackets for Telecommunications Wire & Cable*

Federal Communications Commission (FCC)
1919 M Street N.W.
Washington, DC 20554

Code of Federal Regulations, Title 47, Telecommunications, Chapter 1-FCC, Part 68.

Insulated Cable Engineers Association (ICEA)
P.O. Box 440
South Yarmouth, Massachusetts 02644

ANSI/ICEA S-90-661-1997	*Standard for Individually Unshielded Twisted-Pair Indoor Cables for Use in Communication Wiring Systems*

International Electrotechnical Commission (IEC)
3 Rue de Varembé
Case Postal 131
CH-1211, Geneva 20
Switzerland

ISO/IEC 11801-1995	*Generic Cabling for Customer Premises*

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

National Electrical Manufacturers Association (NEMA)
1300 North 17th Street
Rosslyn, Virginia 22209

ANSI/NEMA WC 61-1992	*Standard for Transfer Impedance Testing*
NEMA WC 63.1-1996	*Performance Standard for Twisted Pair Premise Voice and Data Communications Cables*
ANSI/NEMA WC 63.2-1996	*Performance Standard for Coaxial Premise Voice and Data Communications Cables*

National Fire Protection Association (NFPA)
Batterymarch Park
Quincy, MA 02269

ANSI/NFPA-70-1999	*National Electrical Code (NEC)*

Telecommunications Industry Association (TIA)
2500 Wilson Blvd.
Arlington, VA 22201

ANSI/TIA/EIA 568A-1995	*Commercial Building Telecommunications Cabling Standard*

Underwriters Laboratories Inc. (UL)
333 Pfingsten Road
Northbrook, IL 60062

Canadian Standards Association (CSA)
178 Rexdale Boulevard
Etobicoke, ON M9W 1R3
Canada

UL 444-94/CSA 22.2, No. 214 1994	*Communications Cables*

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Section 2
PART IDENTIFICATION NUMBER (PIN)

2.1 PART IDENTIFICATION NUMBER (PIN)

The part numbers shall be as follows:

WC66-(Category)(NEC/CSA Type)(AWG/Stranding)(Coating)(Pairs)(Shield[1])(Drain Wire)

Where:

Category	=	Character for NEMA Category as determined in Table 2-1a
NEC/CSA Type	=	Character for NEC/CSA Type as determined in Table 2-1b
AWG/Stranding	=	Character for conductor gauge size and stranding as determined from Table 2-2
Coating	=	Character for conductor coating. "B" for Bare Copper ,"T" for Tin Coated Copper, or "S" for Silver Coated Copper
Pairs	=	Number of pairs in cable (i.e.: 2, 4, 12, 25, etc.)
Shield	=	Character(s) for type of shield(s) as determined from Table 2-3
Drain Wire	=	"D," if specified.

Table 2-1a
NEMA CATEGORY DESIGNATION

Category	Description
6	100 Ohm, Twisted-Pair Cables, for frequencies tested up to 250 MHz
7	100 Ohm, Twisted-Pair Cables, for frequencies tested up to 750 MHz

Table 2-1b
NEC/CSA TYPES

Character	Cable Types	Description
P	MPP, CMP	Plenum
R	MPR, CMR	Riser
G	MPG, MP, CMG, CM	General Purpose
X	CMX, CMH	Limited Use

[1]Shield also refers to screen

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Table 2-2a
ALLOWABLE AWG SIZES FOR SOLID CONDUCTORS IN HORIZONTAL AND BACKBONE CABLE

Character	AWG Size
A	22
B	24
C	n/a

Table 2-2b
ALLOWABLE AWG SIZES FOR STRANDED CONDUCTORS IN PATCH CORDS

Character	AWG Size	Stranding	Character	AWG Size	Stranding
D	22	7	G	24	19
E	22	19	H	26	7
F	24	7	J	26	19

Table 2-3
ALLOWABLE SHIELDING OPTIONS

Character	Description
S	Individually shielded Pair, Foil
K	Individually shielded Pair, Braid
F	Overall shield, Foil
B	Overall shield, Braid
U	Unshielded

The following are examples of possible part numbers:

WC66-7PAB4SB: Category 7, plenum, 22 AWG, solid bare copper, 4 pair, individually foil shielded pairs with an overall braid shield.

WC66-6GFT4F: Category 6, general purpose, 24 AWG, 7 strand, tinned coated copper, 4 pair, overall foil shield.

WC66-6RBB4U: Category 6, riser, 24 AWG, solid bare copper, 4 pair, unshielded.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Section 3
MATERIALS AND MECHANICAL REQUIREMENTS

3.1 CONDUCTORS

Conductors shall conform to the requirements of the applicable ASTM document(s) with the exception that the requirements for "Dimensions and Permissible Variations" shall be waived. The minimum dimensions and maximum strand lay shall be in accordance with UL 444/CSA 22.2 No. 214. Minimum elongation of solid conductors from a finished cable shall be in accordance with ICEA S-90-661.

3.1.1 Bare Copper Wire

Bare copper wire shall conform to soft or annealed wire in accordance with ASTM B 3, except that the requirements for "Dimensions and Permissible Variations" shall not apply.

3.1.2 Tin-Coated Copper Wire

Tin-coated copper wire shall conform to soft or annealed wire in accordance with ASTM B 33, except that the requirements for "Dimensions and Permissible Variations" shall not apply.

3.1.3 Silver-Coated Copper Wire

Silver-coated copper wire shall conform to soft or annealed wire in accordance with ASTM B 298, except that the requirements for "Dimensions and Permissible Variations" shall not apply.

3.1.4 Stranded Copper Wire

Stranded bare, silver-coated, or tin-coated copper wire shall conform to ASTM B 8 or B 286, except the minimum dimensions and maximum strand lay shall be in accordance with UL 444/CSA 22.2 No. 214. Stranded conductors are used for patch or equipment cords, and as such are intended to be used in short lengths.

3.2 INSULATING MATERIALS

The copper conductors shall be insulated with one or more layers of solid or expanded material. The core consisting of two or more conductors and other construction components shall be protected with an overall covering generally referred to as an "outer jacket." The insulation jacket, plus other components such as core wrap, shield, and inner jackets shall conform to the applicable requirements of UL 444/CSA 22.2 No. 214.

3.3 SHIELDS

When a type of shield is specified in the part identification number, that shield shall be constructed as described below:

3.3.1 Individually Shielded Pairs, Foil

The individual pair shield shall be a polymeric/metallic laminated tape, such as polyester/aluminum, electrically continuous and satisfy the criteria of UL 444/CSA 22.2 No. 214 and ICEA S-90-661, Section 5. One or more drain wire(s) shall be provided per paragraph 3.3.5.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

3.3.2 Individually Shielded Pairs, Braid

The individual pair shield shall be a braid, electrically continuous and satisfy the criteria of UL 444/CSA 22.2 No. 214 and ICEA S-90-661, Section 5.

3.3.3 Overall Shield, Foil

The foil overall shield shall be a polymeric/metallic laminated tape, such as polyester/aluminum, electrically continuous and satisfy the criteria of UL 444/CSA 22.2 No. 214 and ICEA S-90-661, Section 5. Drain wire(s), at the manufacturer's option, shall be provided per paragraph 3.3.5.

3.3.4 Overall Shield, Braid

A braid overall shield shall be applied per paragraph 3.3.6

3.3.5 Drain Wire(s)

One or more drain wire(s) shall be provided when foil shields are specified without a braid shield. Drain wire(s) may be provided when a braid shield is specified. The drain wire(s) shall:

a. Consist of a solid tinned copper conductor(s) per ASTM B 33 or stranded tinned copper conductor(s) per ASTM B 286, except that the stranding lay may be 1" maximum
b. Be equivalent or larger in gauge size than the twisted pair conductors comprising the core
c. Be in contact with the metallic side of the foil tape, and
d. Be electrically continuous.

3.3.6 Braid Shield

The braid shield shall:

a. Be tinned copper wires in accordance with ASTM B 33, and
b. Provide a minimum of 60% coverage.

3.4 MECHANICAL, PHYSICAL, DIMENSIONAL, AND SAFETY CONSIDERATIONS

The cable shall be in accordance with NFPA 70 (NEC) and conform to the applicable requirements of UL 444/CSA 22.2 No. 214. These will be determined primarily by the wide variety of insulation and jacket material choices. Additionally, the environmental, fire performance, and electrical characteristics as required by this standard will influence cable design parameters.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS Not for Resale

Section 4
ELECTRICAL DEFINITIONS

4.1 RESISTANCE

4.1.1 DC Conductor Resistance

The DC resistance of any conductor is defined as:

$$R = V/I$$

Where:

R = DC conductor resistance (in ohms)
V = Applied DC voltage
I = Measured DC current

4.1.2 DC Resistance Unbalance

The dc resistance unbalance between the two conductors of any pair is defined as:

$$R_{ub} = \frac{(R_{max} - R_{min})}{R_{min}} \times 100$$

Where:

R_{ub} = Resistance unbalance (in percent)
R_{max} = The resistance of the conductor with higher resistance value in ohms
R_{min} = The resistance of the conductor with lower resistance value in ohms

4.1.3 Insulation Resistance

Insulation resistance is defined as the measured resistance between any single conductor and ground. All other conductors and shields, if present, in the cable are grounded.

4.2 INPUT IMPEDANCE

The input impedance of any pair is defined as:

$$Z_{in} = \sqrt{Z_{open} \times Z_{short}}$$

Where:

Zin = Input impedance in ohms
Z_{open} = Measured open circuit impedance in ohms
Z_{short} = Measured short circuit impedance in ohms

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

4.3 CHARACTERISTIC IMPEDANCE

The characteristic impedance is calculated by a least squares function fit of input impedance data as defined in ASTM D 4566 Section 44, Method 3.

4.4 RETURN LOSS

The return loss of any pair relates the input impedance to 100 Ohms. It is defined as:

$$RL = -20 \log_{10} \left| \frac{Z_{in} - 100}{Z_{in} + 100} \right|$$

Where:

RL = Return loss in decibels
Z_{in} = Input impedance in ohms

4.5 ATTENUATION

The attenuation of any pair is defined as:

$$\alpha = \left| 10 \log_{10} \frac{P_2}{P_1} \right| = \left| 20 \log_{10} \frac{V_2}{V_1} \right|$$

Where:

α = The attenuation in decibels
P_1 = The input power in watts
P_2 = The output power in watts
V_1 = The input voltage in volts
V_2 = The output voltage in volts

4.6 CROSSTALK LOSS

4.6.1 Near-End Crosstalk Loss (NEXT)

The near-end crosstalk lossloss of any pair combination is defined as:

$$NEXT = \left| 10 \log_{10} \frac{P_{2N}}{P_{1N}} \right| = \left| 20 \log_{10} \frac{V_{2N}}{V_{1N}} \right|$$

Where:

NEXT = Near-end crosstalk lossloss in decibels
P_{1N} = The input power of the disturbing pair in watts
P_{2N} = The output power of the disturbed pair at the near-end of the cable in watts
V_{1N} = The input voltage of the disturbing pair in volts
V_{2N} = The output voltage of the disturbed pair at the near-end of the cable in volts

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

4.6.2 Power Sum Near-End Crosstalk Loss (PSNEXT)

The power sum near-end crosstalk lossloss of any disturbed pair is defined as:

$$PSNEXT = \left| 10 \log_{10} \sum_{i=1}^{n} \left| 10^{\left(\frac{-xi}{10}\right)} \right| \right|$$

Where:

PSNEXT	=	Power sum near-end crosstalk loss in decibels
x_i	=	Measured near-end crosstalk loss in decibels of the pair combination consisting of the disturbed pair, and the i-th disturbing pair
n	=	Number of disturbing pairs (the number of pairs in the cable minus one)
i	=	Disturbing pair number

4.6.3 Far-End Crosstalk Loss (FEXT)/Equal Level Far-End Crosstalk Loss (ELFEXT)

4.6.3.1 Far-End Crosstalk Loss (FEXT)

The FEXT loss is defined as an input to output crosstalk loss (the power input to the disturbing pair as compared to the output power coupled into the disturbed pair at the opposite end of the cable from the disturbing source). For a four pair cable there will be 12 combinations as indicated in the following example:

Example: FEXT (1-2) Near-end pair 1 to Far-end pair 2
FEXT (2-1) Near-end pair 2 to Far-end pair 1
FEXT (1-3) Near-end pair 1 to Far-end pair 3
FEXT (3-1) Near-end pair 3 to Far-end pair 1, etc.

The first pair is the "Disturbing Pair" and the second pair is the "Disturbed Pair."

Far-end crosstalk loss is defined as:

$$FEXT = \left| 20 \log_{10} \frac{V_{2F}}{V_{1N}} \right|$$

Where:

FEXT	=	Far-end crosstalk loss measured in decibels
V_{1N}	=	Disturbing pair input voltage at the near-end
V_{2F}	=	Disturbed pair output voltage at the far-end

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

4.6.3.2 Equal Level Far-End Crosstalk (ELFEXT) Loss

The ELFEXT loss is FEXT loss with the cable attenuation removed to achieve equal-level comparisons (i.e., voltages are compared at the end of the cable opposite the power input).

The ELFEXT loss is calculated from the 12 FEXT combinations for a four pair cable in 4.6.3.1, minus the attenuation of the "Disturbed Pair."

Example: ELFEXT (1-2) = FEXT (1-2) - Attenuation (2)
ELFEXT (2-1) = FEXT (2-1) - Attenuation (1) etc.

4.6.4 Power Sum Equal Level Far-End Crosstalk Loss (PSELFEXT)

The power sum equal level far-end crosstalk loss of any pair is defined as the power sum of the ELFEXT loss as:

$$PSELFEXT = \left| 10 \log_{10} \sum_{i=1}^{n} \left| 10^{\left(\frac{-xi}{10}\right)} \right| \right|$$

Where:

PSELFEXT	=	Power sum equal level far-end crosstalk loss in decibels
x_i	=	Calculated equal level far-end crosstalk loss in decibels
n	=	Number of disturbing pairs (the number of pairs in the cable minus one)
i	=	Disturbing pair number

4.7 ATTENUATION CROSSTALK RATIO (ACR)

For any given pair, ACR is calculated from the difference between the worse case near-end crosstalk loss as defined in 4.6.1 and attenuation as defined in 4.5.

4.7.1 Power Sum Attenuation To Crosstalk Ratio (PSACR)

For any given pair, the PSACR is calculated from the difference between power sum near-end crosstalk loss as specified in 4.6.2 and attenuation as specified in 4.5.

4.8 TRANSFER IMPEDANCE

The transfer impedance (Z_t) of the shield in an electrically short, longitudinally uniform cable is defined as the ratio of the longitudinal electromotive force induced in the disturbed circuit to the current flowing in the interfering circuit.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

4.9 PHASE VELOCITY

Phase velocity of any pair is defined as:

Where:

$$v = \frac{\omega}{\beta}$$

v = Phase velocity in meters/second
ω = Angular frequency in radians/second
β = Phase constant in accordance section 39 of ASTM D 4566

4.10 PHASE DELAY

Phase delay is the reciprocal of the phase velocity.

4.11 PHASE DELAY SKEW

Phase delay skew is defined as the difference in phase delay between any two pairs.

4.12 BALANCE

4.12.1 Longitudinal Conversion Loss (LCL)

The test method and requirements are being developed, but are not yet finalized.

4.12.2 Longitudinal Conversion Transfer Loss (LCTL)

The test method and requirements are being developed, but are not yet finalized.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Section 5
TEST METHODS

5.1 GENERAL

Unless otherwise specified below, measurements shall be in accordance with ASTM D 4566.

Measurements shall be performed on a cable sample which is a minimum of 100 m (328 ft) in length, unless otherwise specified.

The measurements of input impedance, return loss, attenuation, near-end crosstalk, equal level far-end crosstalk, and phase velocity shall be performed on a cable sample of 100 m (328 ft) or greater removed from the reel or package. The test sample shall be laid along a non-conducting surface, loosely coiled, or supported in aerial spans. On reel or packaged cable measurements that satisfy the performance requirements are acceptable. In case of conflict, the aerial span procedure shall be used as the referee method.

For swept frequency testing, the maximum test frequency shall be 25% greater than the maximum rated frequency as stated in the scope. A minimum of 100 points per decade shall be sampled. Logarithmic spacing shall be used for referee testing to ensure uniform weighting across the applicable frequency range.

5.2 INPUT IMPEDANCE

Input impedance shall be determined using Section 43, Method 2, Option 1 or Option 2 in ASTM D 4566. Option 1 is the referee method.

5.3 CHARACTERISTIC IMPEDANCE

Characteristic impedance shall be calculated using Section 44, Method 3, in ASTM D 4566.

5.4 RETURN LOSS

Return loss shall be determined per Section 45.3 of ASTM D 4566.

5.5 ATTENUATION

The sample length shall exhibit no less than three decibels at the lowest frequency tested and no more than 50 decibels for applicable frequencies. More than one length may be required to test a full range of frequencies.

5.6 NEAR-END CROSSTALK LOSS (NEXT) AND POWER SUM NEAR-END CROSSTALK LOSS (PSNEXT)

NEXT loss shall be measured and PSNEXT loss shall be calculated per Section 24 of ASTM D 4566.

5.7 FAR-END CROSSTALK LOSS (FEXT), EQUAL LEVEL FAR-END CROSSTALK LOSS (ELFEXT), AND POWER SUM EQUAL LEVEL FAR-END CROSSTALK LOSS (PSELFEXT)

FEXT loss shall be measured with a network analyzer per section 4.6.3.1. ELFEXT loss and PSELFEXT loss shall be calculated per section 4.6.3.2 and 4.6.4, respectively.

Previous page is blank

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

5.8 ATTENUATION CROSSTALK RATIO (ACR) AND POWER SUM ATTENUATION CROSSTALK RATIO (PSACR)

Refer to paragraphs 4.7 and 4.7.1.

5.9 TRANSFER IMPEDANCE

The transfer impedance of a shielded cable shall be measured using the method in NEMA WC 61. Note that this test method is only valid to a maximum frequency of 100 MHz.

5.10 PHASE VELOCITY

The phase velocity shall be measured at frequencies of 1, 10, and 100 MHz using the method in Section 41 of ASTM D 4566.

5.11 PHASE DELAY

Phase delay shall be determined from the phase velocity using the following equation:

$$t_d = \frac{100\,L}{V_p C}$$

Where:

t_d = Phase delay in nanoseconds
L = Reference length in meters (usually 100m)
V_p = Phase velocity as a percent of the speed of light in free space
C = 0.3 m/ns

5.12 PHASE DELAY SKEW

The phase delay skew shall be calculated by determining the maximum difference in phase delay between all pairs in a four pair cable. For cables greater than four pair, the phase delay skew shall be calculated by determining the maximum difference in phase delay between any four consecutive pairs.

5.13 BALANCE

5.13.1 Longitudinal Conversion Loss (LCL)

The test method and requirements are being developed, but are not yet finalized.

5.13.2 Longitudinal Conversion Transfer Loss (LCTL)

The test method and requirements are being developed, but are not yet finalized.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Section 6
ELECTRICAL REQUIREMENTS

6.1 GENERAL

This is a performance standard and conductor sizes are not specified for given levels of performance. (Note: Values in Tables A-1a and A-2a are requirements. Values in Tables A-1b and A-2b are included for reference only.)

6.2 RESISTANCE

6.2.1 DC Resistance

The maximum DC resistance at or corrected to 20°C shall be as follows:

Table 6-1
DC RESISTANCE

AWG	DC Resistance Ω/100 m(328 ft.)
26	14.8
24	9.38
22	5.91

6.2.2 DC Resistance Unbalance

The maximum DC resistance unbalance of any pair shall be 3%.

6.2.3 Insulation Resistance

The minimum insulation resistance of any insulated conductor shall be 1500 MΩ – 100 m (328 ft).

6.3 IMPEDANCE

6.3.1 Input Impedance

For Category 6 and 7 cables, the input impedance shall be as follows:

Table 6-2
INPUT IMPEDANCE

Category	Frequency (MHz)	Input Impedance (Ohms)
6 and 7	1 - 100	100 ± 15
6 and 7	> 100 - 200	100 ± 22
6 and 7	> 200 - 250	100 ± 32
7	> 250 - 750	100 ± 32

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

6.3.2 Characteristic Impedance

For Category 6 and Category 7 cables, the characteristic impedance shall be as follows:

Table 6-3
CHARACTERISTIC IMPEDANCE

Category	Frequency (MHz)	Characteristic Impedance (Ohms)
6	1 - 250	100 ± 6
7	1 - 750	100 ± 6

6.4 RETURN LOSS

For Category 6 cables, the minimum return loss shall be as listed below. For Category 7 cables, the minimum return loss is currently under study.

Table 6-4
RETURN LOSS

Frequency (MHz)	Return Loss (dB)	
	Category 6	Category 7
1 to 10	$19+4\log_{10}(f)$	tbd
> 10 to 20	23	tbd
> 20 to 250	$23-7\log_{10}(f/20)$	tbd
>250 - 750	n/a	tbd

6.5 ATTENUATION

6.5.1 Horizontal and Backbone Cables

The maximum attenuation of any pair at or corrected to a temperature of 20°C shall be less than or equal to the value determined using the following formula for all frequencies from 0.772 to 250 MHz for Category 6 and 0.772 to 750 MHz for Category 7:

$$\alpha(f) \le k_1\sqrt{f} + k_2 f + \frac{k_3}{\sqrt{f}}$$

Where:

α = Attenuation in dB/100m (328 ft)
f = Frequency in MHz.
$k_{1,2,3}$ = See Table 6-5

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Table 6-5
COEFFICIENTS FOR ATTENUATION FORMULA

Coefficient	k_1	k_2	k_3
Category 6	1.820	0.020	0.200
Category 7	1.847	0.008	0.145

The cable attenuation shall be verified at a temperature of 40 degrees Celsius and 60 degrees Celsius, and shall meet the requirements of the formula above after adjusting the formula for temperature. The maximum attenuation determined using the above formula shall be adjusted at elevated temperatures using a factor of 0.4% increase per degree Celsius.

6.5.2 Patch (Stranded) Cables

The requirements for attenuation for cables employing 22 and 24 AWG stranded conductors shall be 20% higher than the values determined by the formula in 6.5.1. For 26 AWG stranded conductors, the requirements shall be 50% higher than the values determined by the formula in 6.5.1.

6.6 CROSSTALK LOSS

6.6.1 Near-End Crosstalk Loss (NEXT)

The minimum near-end crosstalk loss of any pair combination shall be greater than or equal to the value determined using the following formula for all frequencies from 0.772 to 250 MHz for Category 6 and 0.772 to 750 MHz for Category 7:

Category 6

$$NEXT(f) \geq 76 - 15 \log_{10}\left(\frac{f}{0.772}\right)$$

Category 7

for frequencies $\leq$ 31.25 MHz

$$NEXT(f) \geq 80$$

for frequencies > 31.25 MHz

$$NEXT(f) \geq 80 - 15 \log_{10}\left(\frac{f}{31.25}\right)$$

Where:

NEXT = Near-end crosstalk loss in dB
f = Frequency in MHz

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

6.6.2 Power Sum Near-End Crosstalk Loss (PSNEXT)

The minimum power sum near-end crosstalk loss of any pair, in cables employing more than two pairs, shall be greater than or equal to the value determined using the following formula for all frequencies from 0.772 to 250 MHz for Category 6.

Category 6

$$PSNEXT(f) \geq 74 - 15 \log_{10}\left(\frac{f}{0.772}\right)$$

Category 7

To Be Determined

Where:

PSNEXT = Power sum near-end crosstalk loss in dB
f = Frequency in MHz

6.6.3 Equal Level Far-End Crosstalk Loss (ELFEXT)

The minimum equal level far-end crosstalk loss of any pair combination shall be greater than or equal to the value determined using the following formula for all frequencies from 0.772 to 250 MHz for Category 6:

Category 6

$$ELFEXT(f) \geq 70 - 20 \log_{10}\left(\frac{f}{0.772}\right)$$

Category 7

To Be Determined

Where:

ELFEXT = Equal level far-end crosstalk loss in dB
f = Frequency in MHz

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

6.6.4 Power Sum Equal Level Far-End Crosstalk Loss (PSELFEXT)

The minimum power sum equal level far-end crosstalk loss of any pair, in cables employing more than two pairs, shall be greater than or equal to the value determined using the following formula for all frequencies from 0.772 to 250 MHz for Category 6:

Category 6

$$PSELFEXT(f) \geq 67 - 20\log_{10}\left(\frac{f}{0.772}\right)$$

Category 7

To Be Determined

Where:

PSELFEXT = Power sum equal level far-end crosstalk loss in dB
f = Frequency in MHz

6.7 ATTENUATION TO CROSSTALK RATIO (ACR)

For any given pair, the minimum ACR is calculated from the difference between the worse case near-end crosstalk loss as specified in 6.6.1 and attenuation as specified in 6.5.

6.7.1 Power Sum Attenuation To Crosstalk Ratio (PSACR)

Category 6 cables: For any given pair, the minimum PSACR is calculated from the difference between power sum near-end crosstalk loss as specified in 6.6.2 and attenuation as specified in 6.5.

Category 7 cables: To be determined.

6.8 TRANSFER IMPEDANCE

The maximum common mode transfer impedance for shielded cables shall be less than or equal to the value determined using the following formula for all frequencies from 1 MHz to 100 MHz. Refer back to 5.9 for frequency limitations:

$$Z_t(f) \leq 37 + 4f + 4\sqrt{f} + 5\sqrt[3]{f}$$

Where:

Z_t = Transfer impedance, in mΩ/m
f = Frequency in MHz

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

6.9 PHASE VELOCITY

The phase velocity shall be as follows:

Table 6-6
PHASE VELOCITY

Frequency (MHz)	Minimum Phase Velocity %
1	58.5
10	61.1
100	62.0

6.10 PHASE DELAY SKEW

The maximum phase delay skew at 20°C shall be as follows:

Table 6-7
PHASE DELAY SKEW

Frequency (MHz)	Maximum Phase Delay Skew (ns/100m)	
	Four Pair Cable	Greater Than Four Pair Cable
1	45	48
10	45	48
100	45	48

For cables greater than four pairs, the maximum phase delay skew shall be as specified above between any four consecutive pairs.

The phase delay skew as specified above shall not vary more than 10 ns from the 20°C measurement at each frequency when measured at 0°C, 40°C, and 60°C.

6.11 BALANCE

6.11.1 Longitudinal Conversion Loss (LCL)

The test method and requirements are being developed, but are not yet finalized.

6.11.2 Longitudinal Conversion Transfer Loss (LCTL)

The test method and requirements are being developed, but are not yet finalized.

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale

Appendix A
ELECTRICAL PERFORMANCE REQUIREMENTS AND REFERENCES FOR CATEGORY 6 AND CATEGORY 7 CABLES

Table A-1a
ELECTRICAL PERFORMANCE REQUIREMENTS FOR CATEGORY 6 CABLES

Electrical Parameters	Category 6		
	22 AWG	24 AWG	26 AWG
Maximum DC Resistance (Ohms/100 m [328 ft]) at 20°C	5.91	9.38	14.8
Maximum DC Resistance Unbalance (%)	3		
Minimum Insulation Resistance (MΩ-100 m [328 ft])	1500		
Minimum Phase Velocity at 1 MHz (%)	58.5		
Minimum Phase Velocity at 10 MHz (%)	61.1		
Minimum Phase Velocity at 100 MHz (%)	62.0		
Maximum Phase Delay Skew at 1 MHz (ns/100 m [328 ft]) for a four-pair cable	45		
Maximum Phase Delay Skew at 10 MHz (ns/100 m [328 ft]) for a four-pair cable	45		
Maximum Phase Delay Skew at 100 MHz (ns/100 m [328 ft]) for a four-pair cable	45		
Maximum Phase Delay Skew at 1 MHz (ns/100m [328 ft]) for greater than four-pair cable	48		
Maximum Phase Delay Skew at 10 MHz (ns/100m [328 ft]) for greater than four-pair cable	48		
Maximum Phase Delay Skew at 100 MHz (ns/100m [328 ft]) for greater than four-pair cable	48		

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

STD·NEMA WC 66-ENGL 1999 ■ 6470247 0516050 8T8 ■

Table A-1b
ELECTRICAL PERFORMANCE REFERENCE FOR CATEGORY 6 CABLES

Frequency (MHz)	Input Impedance (Ohms)	Characteristic Impedance (Ohms)	Return Loss (dB) Minimum	Attenuation (dB/100m) Maximum*	NEXT (dB) Min.	PSNEXT (dB/100m) Minimum	ELFEXT (dB/100m) Minimum	PSELFEXT (dB/100m) Minimum	ACR (dB/100m) Minimum*	PSACR (dB/100m) Minimum*	Transfer Impedance (mΩ/m) Maximum**
1	100 ± 15	100 ± 6	19.0	2.0	74.3	72.3	67.8	64.8	72.3	70.3	50
4	100 ± 15	100 ± 6	21.4	3.8	65.3	63.3	55.7	52.7	61.5	59.5	69
8	100 ± 15	100 ± 6	22.6	5.4	60.8	58.8	49.7	46.7	55.4	53.4	90
10	100 ± 15	100 ± 6	23.0	6.0	59.3	57.3	47.8	44.8	53.3	51.3	100
16	100 ± 15	100 ± 6	23.0	7.7	56.3	54.3	43.7	40.7	48.6	46.6	130
20	100 ± 15	100 ± 6	23.0	8.6	54.8	52.8	41.7	38.7	46.2	44.2	148
25	100 ± 15	100 ± 6	22.3	9.6	53.3	51.3	39.8	36.8	43.7	41.7	172
31.25	100 ± 15	100 ± 6	21.6	10.8	51.9	49.9	37.9	34.9	41.1	39.1	200
62.5	100 ± 15	100 ± 6	19.5	15.7	47.4	45.4	31.8	28.8	31.7	29.7	338
100	100 ± 15	100 ± 6	18.1	20.2	44.3	42.3	27.8	24.8	24.1	22.1	500
125	100 ± 22	100 ± 6	17.4	22.9	42.9	40.9	25.8	22.8	20.0	18.0	-
155.52	100 ± 22	100 ± 6	16.8	25.8	41.4	39.4	23.9	20.9	15.6	13.6	-
175	100 ± 22	100 ± 6	16.4	27.6	40.7	38.7	22.9	19.9	13.1	11.1	-
200	100 ± 22	100 ± 6	16.0	29.8	39.8	37.8	21.7	18.7	10.0	8.0	-
250	100 ± 32	100 ± 6	15.3	33.8	38.3	36.3	19.8	16.8	4.5	2.5	-

*Applicable for horizontal and backbone cables only
**For shielded cable only

Not for Resale

Table A-2a

ELECTRICAL PERFORMANCE REQUIREMENTS FOR CATEGORY 7 CABLES

	Category 7		
Electrical Parameters	**22 AWG**	**24 AWG**	**26 AWG**
Maximum DC Resistance (Ohms/100 m [328 ft]) at 20°C	5.91	9.38	14.8
Maximum DC Resistance Unbalance (%)	3		
Minimum Insulation Resistance (MΩ-100 m [328 ft])	1500		
Minimum Phase Velocity at 1 MHz (%)	58.5		
Minimum Phase Velocity at 10 MHz (%)	61.1		
Minimum Phase Velocity at 100 MHz (%)	62.0		
Maximum Phase Delay Skew at 1 MHz (ns/100 m [328 ft]) for a four-pair cable	45		
Maximum Phase Delay Skew at 10 MHz (ns/100 m [328 ft]) for a four-pair cable	45		
Maximum Phase Delay Skew at 100 MHz (ns/100 m [328 ft]) for a four-pair cable	45		

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

Not for Resale

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS

STD-NEMA WC 66-ENGL 1999 ■ 6470247 0516052 670 ■

Table A-2b
ELECTRICAL PERFORMANCE REFERENCE FOR CATEGORY 7 CABLES*

Frequency (MHz)	Input Impedance (Ohms)	Characteristic Impedance (Ohms)	Attenuation (dB/100m) Maximum*	NEXT (dB) Minimum	ACR (dB/100m) Minimum	Transfer Impedance (mΩ/m) Maximum**
1	100 ± 15	100 ± 6	2.0	80.0	78.0	50
4	100 ± 15	100 ± 6	3.8	80.0	76.2	69
8	100 ± 15	100 ± 6	5.3	80.0	74.7	90
10	100 ± 15	100 ± 6	6.0	80.0	74.0	100
16	100 ± 15	100 ± 6	7.6	80.0	72.4	130
20	100 ± 15	100 ± 6	8.5	80.0	71.5	148
25	100 ± 15	100 ± 6	9.5	80.0	70.5	172
31.25	100 ± 15	100 ± 6	10.6	80.0	69.4	200
62.5	100 ± 15	100 ± 6	15.1	75.5	60.4	338
100	100 ± 15	100 ± 6	19.3	72.4	53.1	500
125	100 ± 22	100 ± 6	21.7	71.0	49.3	-
155.52	100 ± 22	100 ± 6	24.3	69.5	45.2	-
175	100 ± 22	100 ± 6	25.8	68.8	43.0	-
200	100 ± 22	100 ± 6	27.7	67.9	40.2	-
250	100 ± 32	100 ± 6	31.2	66.5	35.3	-
300	100 ± 32	100 ± 6	34.4	65.3	30.9	-
350	100 ± 32	100 ± 6	37.4	64.3	26.9	-
400	100 ± 32	100 ± 6	40.1	63.4	23.3	-
600	100 ± 32	100 ± 6	50.0	60.8	10.8	-
750	100 ± 32	100 ± 6	56.6	59.3	2.7	-

* Applicable for horizontal and backbone cables only
**For shielded cable only

Not for Resale

STD.NEMA WC 66-ENGL 1999. 6470247 0516053 507



NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION • 1300 NORTH 17TH STREET • SUITE 1847 • ROSSLYN, VA 22209

Copyright National Electrical Manufacturers Association
Provided by IHS under license with NEMA
No reproduction or networking permitted without license from IHS
Not for Resale